

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE EAST AND NORTH BOUNDARIES,

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 55 NORTH, RANGE 75 WEST,

OF THE SIXTH PRINCIPAL MERIDIAN,

IN THE STATE OF WYOMING.

EXECUTED BY

RICHARD A. KOHLER

CADASTRAL SURVEYOR

Under Special Instructions dated FEBRUARY 22, 2001, approved FEBRUARY 22, 2001, which provided for the surveys included under Group Number 685, and assignment instructions dated FEBRUARY 22, 2001.

Survey commenced AUGUST 8, 2001

Survey completed MAY 29, 2002

INDEX DIAGRAM

Township 55 North, Range 75 West

	20	19	18	17	16	14					
6	79	5	64	4	52	3	42	2	31	1	13
78		77		62		51		41		30	
7	75	8	61	9	49	10	40	11	29	12	11
74		73		60		49		39		28	
18	72	17	59	16	47	15	38	14	27	13	8
71		71		58		47		37		27	
19	70	20	57	21	46	22	36	23	25	24	6
69		68		56		45		34		24	
30	67	29	54	28	44	27	33	26	23	25	4
66		65		54		43		32		23	
31	64	32	53	33	42	34	31	35	21	36	2

T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>The following field notes are those of the dependent resurvey of the east and north boundaries and the subdivisional lines, Township 55 North, Range 75 West, Sixth Principal Meridian, Wyoming.</p> <p>A history of surveys pertaining to this resurvey is as follows:</p> <p>Mortimer N. Grant surveyed the south and east boundaries in 1883. Charles Holcomb retraced the south and east boundaries and surveyed the remaining exterior boundaries and the subdivisional lines in 1883. Mark M. Kelley independently resurveyed a portion of the east boundary and dependently resurveyed the remainder of the east boundary in 1917. Mark M. Kelley and Mark D. King established tract corners and closing corners along the east boundary in 1917-21. Richard A. Kohler dependently resurveyed the west boundary in 1988-89 and the south boundary in 2000-01.</p> <p>A number of local surveys have been conducted in the area and acceptance of these surveys is detailed herein.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 685, Wyoming, dated February 22, 2001.</p> <p>Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data were thoroughly verified and only true line field notes are given herein, which refer to the completed survey.</p> <p>The survey was executed with TRIMBLE Model 4700 Global Positioning System (GPS) receivers, a LIETZ Model SET4 electronic total station and by chaining methods. The instruments were maintained in proper adjustment at all times. The directions of all lines refer to the true meridian as determined by GPS observations. GPS control network and supporting data are contained in the official group file.</p> <p>The geographic position of the southeast corner of the township, based on NAD 83 (1993) and determined by GPS methods, is:</p> <p>Latitude 44° 41' 50.342" N., Longitude 105° 49' 22.759" W.</p>
--------	---

T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<p>The mean magnetic declination is $11\frac{1}{2}^{\circ}$ E.</p> <hr/>												
	<p style="text-align: center;">Dependent Resurvey of the East Boundary, T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming</p> <hr/>												
	<p style="text-align: center;">(Restoring the resurvey executed by Mark M. Kelley and Mark D. King in 1917-21)</p> <hr/>												
	<p>Beginning at the cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, at intersection of S. right-of-way fence of U.S. Highway Nos. 14 and 16, extending E. and W., and fence extending S., with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T55N</td> </tr> <tr> <td style="text-align: center;">R75W</td> <td style="text-align: center;">R74W</td> </tr> <tr> <td style="text-align: center;">S 25</td> <td style="text-align: center;">S 30</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 36</td> <td style="text-align: center;">S 31</td> </tr> <tr> <td colspan="2" style="text-align: center;">1917</td> </tr> </table>	T55N		R75W	R74W	S 25	S 30	-----		S 36	S 31	1917	
T55N													
R75W	R74W												
S 25	S 30												

S 36	S 31												
1917													
	<p>S. $0^{\circ} 04'$ W., bet. secs. 31 and 36.</p>												
	<p>Over gently rolling terrain, along fence.</p>												
16.40	<p>Cor. of fences extending N. and E.</p>												
18.80	<p>Chicken Creek Draw, drains WSW.</p>												
26.90	<p>Improved road, bears SE. and NW.</p>												
40.05	<p>The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with the upper portion of a rusted iron post, 22 ins. long, 1 in. diam., loosely set 8 ins. in the ground, in a collar of stone, with brass cap mkd. $\frac{1}{4}$ S31 S36 1917.</p>												
	<p>At the corner point</p>												
	<p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												

Dependent Resurvey of the East Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R75W R74W 1/4 S 36 S 31 2001</p> <p>Deposit the 1917 monument inside and set a steel fence post alongside the stainless steel post.</p> <hr style="width: 30%; margin: auto;"/> <p>S. 0° 07' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
19.45	<p>The witness cor. to the closing cor. of Tps. 55 N., Rs. 74 and 75 W., monumented with an iron post, 3 ins. diam., as described in the 2000-01 field notes of the dependent resurvey, T. 54 N., R. 75 W.</p> <hr style="width: 30%; margin: auto;"/> <p>S. 0° 07' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
0.476	<p>Point for the closing cor. of Tps. 55 N., Rs. 74 and 75 W., on the projection of the section line from the N., at intersection with the N. bdy. of sec. 1, T. 54 N., R. 75 W.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">CC T55N R75N R74W S 36 S 31 ----- S 1 T54N 2001</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located in Spotted Horse Creek (dry), course NE.</p>

Dependent Resurvey of the East Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, the cor. of Tps. 54 N., Rs. 74 and 75 W., bears N. 87° 27' E., 18.89 chs. dist., monumented with an iron post, 3 ins. diam., as described in the 2000 field notes of the dependent resurvey, T. 54 N., R. 74 W.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36.</p> <p>N. 0° 28' E., bet. secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>Over gently rolling terrain.</p>
0.80	U.S. Highway Nos. 14 and 16, bears E. and W.
20.04	<p>Cor. No. 3, Tract 82, T. 55 N., R. 74 W., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap erroneously mkd. T55N R74W R75W 7 TR82 S25 S30 1920. This position now also functions as the S. 1/16 sec. cor. of secs. 25 and 30. Remark the brass cap to read</p> <div style="text-align: center; margin: 10px 0;"> <pre> T55N TR 82 3 S 25 ----- S 30 R75W R74W 2002 1920 </pre> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 2 lks. W. of W. right-of-way fence of Werner Road, extending N. and S.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 28' E., beginning new measurement, on the E. bdy. of sec. 25, identical with line 3-4, Tract 82, T. 55 N., R. 74 W.</p> <p>Over gently rolling terrain.</p>
20.04	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <pre> 1/4 S 25 S 30 1917 </pre> </div>

Dependent Resurvey of the East Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS																			
	<p>Cor. is located 2 lks. W. of W. right-of-way fence of Werner Road, extending N. and S.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 28' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>																		
20.07	<p>Cor. No. 4, Tract 82, T. 55 N., R. 74 W., monumented with an iron post, 1 in. diam., firmly set flush with the surface of the ground in W. borrow pit of Werner Road, extending N. and S., with brass cap erroneously mkd. T55N R73W R74W 8 TR82 S25 S30 1920. This position now also functions as the N. 1/16 sec. cor. of secs. 25 and 30. Remark the brass cap to read</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding-right: 10px;">T55N</td> <td style="padding-right: 10px;">R74W</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 30</td> </tr> <tr> <td style="padding-right: 10px;">S 25</td> <td style="border-left: 1px solid black;"></td> <td style="border-left: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black;"></td> <td style="border-left: 1px solid black; text-align: center;">4</td> </tr> <tr> <td style="padding-right: 10px;">R75W</td> <td style="padding-right: 10px;">TR 82</td> <td style="border-left: 1px solid black;"></td> </tr> <tr> <td></td> <td></td> <td style="border-left: 1px solid black; text-align: center;">2002</td> </tr> <tr> <td></td> <td></td> <td style="border-left: 1px solid black; text-align: center;">1920</td> </tr> </table> </div> <p>Set steel fence posts N. and S. of the iron post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 27' E., beginning new measurement.</p> <p>Over rolling terrain, along Werner Road.</p>	T55N	R74W	S 30	S 25					4	R75W	TR 82				2002			1920
T55N	R74W	S 30																	
S 25																			
		4																	
R75W	TR 82																		
		2002																	
		1920																	
20.04	<p>The cor. of secs. 19, 24, 25 and 30, identical with Cor. 7, Tract 80, T. 55 N., R. 74 W., monumented with an iron post, 2 ins. diam., firmly set 14 ins. below the graveled surface of Werner Road, extending N. and S., at projection of fence from the W., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td colspan="3" style="padding-bottom: 5px;">T55N</td> </tr> <tr> <td style="padding-right: 10px;">R75N</td> <td style="padding-right: 10px;">R74W</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">S 24</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 19</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">S 25</td> <td style="border-left: 1px solid black; border-bottom: 1px solid black; padding-left: 5px;">S 30</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; text-align: center;">1917</td> <td></td> </tr> </table> </div>	T55N			R75N	R74W		S 24	S 19		S 25	S 30			1917				
T55N																			
R75N	R74W																		
S 24	S 19																		
S 25	S 30																		
	1917																		

Dependent Resurvey of the East Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, in right-of-way fence extending N. and S., bears S. 47° E., 100.8 lks. dist., with brass cap mkd. RM T55N R74W TR80 66.5 FT. TO COR. 2002 and an arrow pointing to the cor.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance, falls in Werner Road, extending N. and S.; there is no remaining evidence of the 1917 resurvey monument.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. below the scoria surface of the road, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R75N R74W 1/4 S 24 S 19 2002</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, in a collar of stone, in right-of-way fence extending N. and S., bears S. 45° W., 119.4 lks. dist., with brass cap mkd. RM T55N R75W S24 78.8 FT. TO COR. 2002 and an arrow pointing to the cor.</p>
	<p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, in a collar of stone, in right-of-way fence extending N. and S., bears N. 45¾° W., 114.1 lks. dist., with brass cap mkd. RM T55N R75W S24 75.3 FT. TO COR. 2002 and an arrow pointing to the cor.</p>
70.90	<p>Leave Werner Road, bears S. and NW.; thence along old Werner Road (abandoned).</p>
77.90	<p>Ridge, bears SE. and NW.</p>
80.18	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance by the method of irregular boundary adjustment; the 1917 resurvey monument, an iron post, 36 ins. long, 2 ins. diam., with brass cap mkd. T55N R74W R75W S13 S18 S19 S24 1917 found badly bent and lying loose nearby.</p>

Dependent Resurvey of the East Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R75N R74W S 13 S 18 ----- S 24 S 19 2002</p> </div> <p>Bury the 1917 monument and set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located N. 43° W., 78 lks. dist., from intersection of fences extending N., E., S. and W.</p> <p>From this point, a position established by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, bears S. 86° E., 7 lks. dist., monumented with a steel reinforcement rod, ½ in. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R74W R75W S13 S18 S19 S24 PLS 5655 2000. This position was based upon erroneous calculation of proportionate position and is not accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>N. 1° 34' E., bet. secs. 13 and 18.</p> <p>Over rolling terrain, along abandoned Werner Road.</p> <p>20.24 Cor. No. 3, Tract 66, T. 55 N., R. 74 W., identical with Station 13 of abandoned Mitchell Road, extending N. and E., monumented with an iron post, 36 ins. long, 1 in. diam., badly bent but firmly set 2 ins. below the surface of the ground, with brass cap mkd. T55N R74W R75W 3 TR66 S18 1917. This position now also functions as the S. 1/16 sec. cor. of sec. 13 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the East Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.25	<div style="text-align: center;"> <p>T55N R75W R74W TR 66 3 S 13 S 18 2002</p> </div> <p>Bury the 1917 monument and set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 50 lks. W. of fence extending N. and S.</p> <hr/> <p>N. 1° 27' E., on the E. bdy. of sec. 13, identical with line 3-4, Tract 66, T. 55 N., R. 74 W.</p> <p>Over gently rolling terrain, along abandoned Mitchell Road.</p> <p>The 1/4 sec. cor. of sec. 13 only, monumented with an iron post, 36 ins. long, 1 in. diam., badly bent but firmly set 5 ins. below the surface of the ground, with brass cap mkd. 1/4 S13 1917</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R75W R74W 1/4 S 13 2002</p> </div> <p>Bury the 1917 monument and set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 55 lks. W. of fence extending N. and S.</p> <hr/> <p>N. 1° 29' E., beginning new measurement.</p> <p>Over gently rolling terrain, along abandoned Mitchell Road.</p>

Dependent Resurvey of the East Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.24	<p>Cor. No. 4, Tract 66, T. 55 N., R. 74 W., monumented by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, with a steel reinforcement rod, 24 ins. long, $\frac{5}{8}$ in. diam., firmly set flush with the surface of the ground, with aluminum cap inscribed JONES PELS 4250 and mkd. T55N R74W R75W 4 TR66 S13 S18 2001. This position is accepted as a careful and faithful reestablishment of the 1917 cor. position and now also functions as the N. 1/16 sec. cor. of sec. 13 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R75W R74W S 13 S 18 4 TR 66 2002</p> </div> <p>Bury the steel reinforcement rod inside and set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 50 lks. W. of gate in fence extending N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $1^{\circ} 29'$ E., beginning new measurement.</p> <p>Over rolling terrain, along abandoned Mitchell Road.</p>
18.94	<p>Point for the closing cor. of secs. 7 and 18, T. 55 N., R. 74 W. The 1917 monument for this cor., an iron pipe, 36 ins. long, 2 ins. diam., found lying loose nearby, with no brass cap.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R75W R74W S 13 S 7 C C S 18 2002</p> </div>

Dependent Resurvey of the East Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set a steel fence post alongside the stainless steel post and remove the 1917 monument from the area.</p>										
20.24	<p>The cor. of secs. 12 and 13 only, identical with Station 14 of abandoned Mitchell Road, monumented with an iron post, 36 ins. long, 2 ins. diam., badly bent but firmly set 24 ins. in the ground, with brass cap mkd. T55N R74W R75W S12 S13 1917.</p> <p>from which</p> <p style="padding-left: 40px;">A sandstone, firmly set, projecting 14x7x4 ins. above the ground, at intersection of fences extending N., S. and W., bears N. 45½ ° E., 70.1 lks. dist., plainly mkd. CR on SW. face, no other mks. visible</p> <p style="padding-left: 40px;">A broken sandstone, base portion firmly set flush with the surface of the ground, bears S. 45° W., 69.4 lks. dist., with upper portion, 14x11x4 ins., lying loose alongside, plainly mkd. CR on NE. face, no other mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T55N</td></tr> <tr><td>R75N</td><td>R74W</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">12</td><td style="padding-left: 5px;"> </td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">13</td><td style="padding-left: 5px;"> S 7</td></tr> <tr><td colspan="2">2001</td></tr> </table> </div> <p>Bury the 1917 monument and set a steel fence post alongside the stainless steel post.</p> <hr style="border: 0.5px solid black;"/> <p>N. 1° 21' E., on the E. bdy. of sec. 12.</p> <p>Over rolling terrain.</p>	T55N		R75N	R74W	12		13	S 7	2001	
T55N											
R75N	R74W										
12											
13	S 7										
2001											
8.90	New Deal Draw, drains NW.										
12.20	Spur, slopes WNW.										

Dependent Resurvey of the East Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
17.70	New Deal Draw, drains E.
40.19	<p>The 1/4 sec. cor. of sec. 12 only, identical with Cor. No. 9, Tract 69, T. 55 N., R. 74 W., monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins above the ground, in fence extending N. and S., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T55N R75W R74W 1/4 TR 69 9 S 12 S 7 1917</p> </div> <p>Cor. is located on ridge, bears SE. and NW.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 1° 21' E., beginning new measurement on the E. bdy. of sec. 12, identical with line 9-10, Tract 69, T. 55 N., R. 74 W.</p> <p>Over rolling terrain, along fence.</p>
20.10	Wash, drains E.
38.58	<p>The closing cor. of secs. 6 and 7, T. 55 N., R. 74 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, at intersection of fences extending N., E., S. and W., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T55N R75W R74W S 6 S 12 S 7 1917</p> </div>
40.07	<p>The cor. of secs. 1 and 12 only, identical with Cor. No. 10, Tract 69, T. 55 N., R. 74 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, in fence extending N. and S., with brass cap mkd.</p>

Dependent Resurvey of the East Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS																	
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T55N</td></tr> <tr><td style="text-align: center;">R75N</td><td style="text-align: center;">R74W</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">12</td><td style="text-align: center;">10</td></tr> <tr><td></td><td style="text-align: center;"> TR 69</td></tr> <tr><td></td><td style="text-align: center;">1917</td></tr> </table>	T55N		R75N	R74W	S 1	S 6	-----		12	10		TR 69		1917		
T55N																	
R75N	R74W																
S 1	S 6																

12	10																
	TR 69																
	1917																
	<p>N. 1° 22' E., on the E. bdy. of sec. 1.</p> <p>Over gently rolling terrain, along fence.</p>																
16.20	Improved road, bears NE. and SW.																
40.14	The 1/4 sec. cor. of sec. 1 only, identical with Cor. No. 13, Tract 69, T. 55 N., R. 74 W., monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, in fence extending N. and S., with brass cap mkd.																
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T55N</td></tr> <tr><td style="text-align: center;">R75W</td><td style="text-align: center;">R74W</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td></td><td style="text-align: center;"> TR 69</td></tr> <tr><td></td><td style="text-align: center;">13</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">-----</td></tr> <tr><td></td><td style="text-align: center;"> S 6</td></tr> <tr><td></td><td style="text-align: center;">1917</td></tr> </table>	T55N		R75W	R74W	1/4			TR 69		13	S 1	-----		S 6		1917
T55N																	
R75W	R74W																
1/4																	
	TR 69																
	13																
S 1	-----																
	S 6																
	1917																
	<p>Encircle the iron post with a collar of stone.</p> <p>Cor. is located in wash, drains ESE.</p>																
	<p>N. 1° 22' E., beginning new measurement on the E. bdy. of sec. 1, identical in part with line 13-14, Tract 69, T. 55 N., R. 74 W.</p> <p>Over rolling terrain, along fence.</p>																
15.70	Intersection of fences extending SE., S. and NW.																
20.13	Cor. No. 14, Tract 69, T. 55 N., R. 74 W., monumented with an iron post, 36 ins. long, 1 in. diam., badly bent but firmly set 24 ins. in the ground, with brass cap mkd. T55N R74W R75W 14 TR69 S6 1917.																
	At the corner point																

Dependent Resurvey of the East Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T55N</td></tr> <tr><td>R75W</td><td>R74W</td></tr> <tr><td></td><td style="border-left: 1px solid black; border-right: 1px solid black;">S 6</td></tr> <tr><td>S 1</td><td style="border-left: 1px solid black; border-right: 1px solid black;">14</td></tr> <tr><td></td><td style="border-left: 1px solid black; border-right: 1px solid black;">TR 69</td></tr> <tr><td colspan="2">2002</td></tr> </table> </div> <p>Bury the 1917 monument and set a steel fence post alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 1° 17' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>2.40 L X Bar Creek, course NW.</p> <p>20.04 The cor. of Tps. 55 and 56 N., Rs. 74 and 75 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above the ground, at cor. of fences extending N. and W., with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T56N R74W</td></tr> <tr><td>S 36</td><td style="border-left: 1px solid black; border-right: 1px solid black;">S 31</td></tr> <tr><td>S 1</td><td style="border-left: 1px solid black; border-right: 1px solid black;">S 6</td></tr> <tr><td>R75W</td><td>T55N</td></tr> <tr><td colspan="2">1917</td></tr> </table> </div> <p>Cor. is located 30 lks. E. of improved road extending SSE. and NNW.</p> <hr style="width: 80%; margin: 10px auto;"/> <div style="text-align: center; margin: 10px auto;"> <p>Dependent Resurvey of the North Boundary, T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming</p> <hr style="width: 80%; margin: 10px auto;"/> <p>(Restoring the survey executed by Charles Holcomb in 1883)</p> <hr style="width: 80%; margin: 10px auto;"/> </div> <p>From the cor. of Tps. 55 and 56 N., Rs. 74 and 75 W.</p> <p>S. 89° 43' W., bet. secs. 1 and 36.</p>	T55N		R75W	R74W		S 6	S 1	14		TR 69	2002		T56N R74W		S 36	S 31	S 1	S 6	R75W	T55N	1917	
T55N																							
R75W	R74W																						
	S 6																						
S 1	14																						
	TR 69																						
2002																							
T56N R74W																							
S 36	S 31																						
S 1	S 6																						
R75W	T55N																						
1917																							

Dependent Resurvey of the North Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	S. 89° 43' W., bet. secs. 1 and 36.
	Over rolling terrain, along fence.
16.00	L X Bar Creek, course NNE.
19.60	Wash, drains NE.
40.32	Point for the 1/4 sec. cor. of secs. 1 and 36, determined longitudinally by proportionate measurement and latitudinally by fence extending E. and W.; there is no remaining evidence of the original monument.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T56N R75W S 36 1/4 ——— S 1 T55N 2001
	—————
	S. 89° 39' W., beginning new measurement.
	Over rolling to broken terrain, along fence.
8.90	Spur, slopes ESE.
40.19	Leave fence, bears E. and SSW.
40.32	The cor. of secs. 1, 2, 35 and 36, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 30 ins. long, ⅝ in. diam., firmly set 29 ins. in the ground, in a collar of stone, at projection of fences from the E. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T56N R75W S1 S2 S35 S36 T55N PLS 5655 2000. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the North Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS															
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T56N</td><td>R75W</td></tr> <tr><td>S 35</td><td> S 36</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 2</td><td> S 1</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2" style="text-align: center;">T55N</td></tr> <tr><td colspan="2" style="text-align: center;">2001</td></tr> </table>	T56N	R75W	S 35	S 36			S 2	S 1			T55N		2001	
T56N	R75W														
S 35	S 36														
S 2	S 1														
T55N															
2001															
	Deposit the steel reinforcement rod inside and set a steel fence post alongside the stainless steel post.														
	S. 88° 35' W., bet. secs. 2 and 35.														
	Over rolling to broken terrain.														
40.53	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.														
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T56N</td><td>R75W</td></tr> <tr><td>S 35</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2" style="text-align: center;">T55N</td></tr> <tr><td colspan="2" style="text-align: center;">2001</td></tr> </table>	T56N	R75W	S 35		1/4	—	S 2				T55N		2001	
T56N	R75W														
S 35															
1/4	—														
S 2															
T55N															
2001															
	Set a steel fence post alongside the stainless steel post.														
72.10	Wash, drains NW.														
76.60	Spur, slopes NW.														
80.06	The witness cor. to the cor. of secs. 2, 3, 34 and 35, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 30 ins. long, 5/8 in. diam., firmly set 28 ins. in the ground, in a collar of stone, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T56N R75W W.C. 66.0' S2 S3 S34 S35 T55N PLS 5655 2000.														
	At the witness cor. point														
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.														

Dependent Resurvey of the North Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<div style="text-align: center;"> WC T56N R75W S 34 S 35 <— — S 3 S 2 T55N 2001 </div>
81.06	<p>Deposit the steel reinforcement rod inside the stainless steel post.</p> <p>True point for the cor. of secs. 2, 3, 34 and 35, at cor. of fences extending S. and W., in approximately 10 ins. of water in S. end of stock pond on Reservoir Creek, course N., where it is impracticable to establish a permanent monument.</p> <p>This position is accepted as the best available evidence of the original cor. position.</p> <hr/>
40.33	<p>S. 89° 13' W., bet. secs. 3 and 34.</p> <p>Over rolling terrain, along fence.</p> <p>The 1/4 sec. cor. of secs. 3 and 34, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 30 ins. long, 5/8 in. diam., firmly set 28 ins. in the ground, in a collar of stone, at intersection of fences extending E., S. and W., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T56N R75W 1/4 S3 S34 T55N PLS 5655 2000. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T56N R75W S 34 1/4 ——— S 3 T55N 2001 </div>
	<p>Deposit the steel reinforcement rod inside the stainless steel post.</p> <hr/>

Dependent Resurvey of the North Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS																											
40.31	<p>S. 89° 00' W., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p> <p>The cor. of secs. 3, 4, 33 and 34, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, witnessed by 4 pits, NE., SE., SW. and NW. of the cor., in fence extending E. and W., with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 5px;">T56N</td><td style="padding: 0 5px;">R75W</td></tr> <tr><td style="padding: 0 5px;">S 33</td><td style="border-left: 1px solid black; padding: 0 5px;">S 34</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; height: 5px;"></td></tr> <tr><td style="padding: 0 5px;">S 4</td><td style="border-left: 1px solid black; padding: 0 5px;">S 3</td></tr> <tr><td colspan="2" style="padding: 0 5px;">T55N</td></tr> <tr><td colspan="2" style="padding: 0 5px;">PLS 538</td></tr> <tr><td colspan="2" style="padding: 0 5px;">2001</td></tr> </table> </div> <p>This position is accepted as a careful and faithful determination of the original cor. position.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>S. 89° 10' W., bet. secs. 4 and 33.</p> <p>Over gently rolling terrain, along fence.</p> <p>The 1/4 sec. cor. of secs. 4 and 33, monumented by Don A. Davis, Wyoming Registered Land Surveyor No. 4824, with a steel reinforcement rod, 30 ins. long, 5/8 in. diam., firmly set 29 ins. in the ground, 3 lks. W. of intersection of fences extending E., S. and NW., with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WLC and mkd. T56N R75W 1/4 S4 S33 T55N LS 4824 1999. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 5px;">T56N</td><td style="padding: 0 5px;">R75W</td></tr> <tr><td style="padding: 0 5px;">S 33</td><td></td></tr> <tr><td style="padding: 0 5px;">1/4</td><td style="border-top: 1px solid black; width: 20px;"></td></tr> <tr><td style="padding: 0 5px;">S 4</td><td></td></tr> <tr><td colspan="2" style="padding: 0 5px;">T55N</td></tr> <tr><td colspan="2" style="padding: 0 5px;">2001</td></tr> </table> </div>	T56N	R75W	S 33	S 34			S 4	S 3	T55N		PLS 538		2001		T56N	R75W	S 33		1/4		S 4		T55N		2001	
T56N	R75W																										
S 33	S 34																										
S 4	S 3																										
T55N																											
PLS 538																											
2001																											
T56N	R75W																										
S 33																											
1/4																											
S 4																											
T55N																											
2001																											

Dependent Resurvey of the North Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS															
	<p>Deposit the steel reinforcement rod inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 06' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>														
1.50	S A Road, on curve, bears S. and NW.														
40.76	<p>The cor. of secs. 4, 5, 32 and 33, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground, witnessed by 4 pits, NE., SE., SW. and NW. of the cor., with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T56N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T55N</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">PLS 538</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2001</td> </tr> </table> </div> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>S. 89° 06' W., bet. secs. 5 and 32.</p> <p>Over rolling terrain.</p>	T56N	R75W	S 32	S 33	S 5	S 4	T55N		PLS 538		2001			
T56N	R75W														
S 32	S 33														
S 5	S 4														
T55N															
PLS 538															
2001															
40.76	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, witnessed by 2 pits, N. and S. of the cor., with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T56N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">S 32</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-bottom: 1px solid black; width: 20px;"></td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">S 5</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T55N</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">LS 538</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2001</td> </tr> </table> </div>	T56N	R75W	S 32		1/4		S 5		T55N		LS 538		2001	
T56N	R75W														
S 32															
1/4															
S 5															
T55N															
LS 538															
2001															

Dependent Resurvey of the North Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>S. 89° 06' W., beginning new measurement.</p> <p>Over mountainous terrain.</p>												
9.70	Ridge, bears SE. and NW.												
22.90	Spur, slopes S.												
26.90	Spur, slopes WNW.												
40.76	<p>The cor. of secs. 5, 6, 31 and 32, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, in a mound of stone, 3½ ft. base, to top, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T56N</td> <td>R75W</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td colspan="2">T55N</td> </tr> <tr> <td colspan="2">PLS 538</td> </tr> <tr> <td colspan="2">2001</td> </tr> </table> </div>	T56N	R75W	S 31	S 32	S 6	S 5	T55N		PLS 538		2001	
T56N	R75W												
S 31	S 32												
S 6	S 5												
T55N													
PLS 538													
2001													
	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>S. 89° 06' W., bet. secs. 6 and 31.</p> <p>Over rolling to broken terrain.</p>												
0.60	Wash, drains SSW.												
0.80	Abandoned fence, bears irregularly N. and S.												
19.90	Spotted Horse Creek, course NNW.												

Dependent Resurvey of the North Boundary,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.76	<p>The 1/4 sec. cor. of secs. 6 and 31, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with a steel fence post alongside, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <p style="text-align: center;">T56N R75W S 31 1/4 ——— S 6 T55N LS 538 2001</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 06' W., beginning new measurement.</p> <p>Over rolling to broken terrain.</p>
1.40	Improved road, bears SE. and NW.
22.70	Spur, slopes NNW.
38.19	<p>The cor. of Tps. 55 and 56 N., Rs. 75 and 76 W., monumented with an iron post, 2½ ins. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 56 N., R. 76 W.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the Subdivisional Lines, T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Charles Holcomb in 1883)</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the 2000-01 field notes of the dependent resurvey, T. 54 N., R. 75 W.</p> <p>N. 16° 33' W., bet. secs. 35 and 36.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling to broken terrain.
16.005	Point for the S. 1/16 sec. cor. of secs. 35 and 36. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T55N R75W S1/16 S 35 S 36 2001 </div> Set a steel fence post alongside the stainless steel post. Cor. is located 79 lks. E. of fence extending irregularly N. and S.
32.01	Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T55N R75W 1/4 S 35 S 36 2001 </div> Set a steel fence post alongside the stainless steel post. Cor. is located 69 lks. E. of fence extending irregularly N. and S.
64.02	The cor. of secs. 25, 26, 35 and 36, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor., 1 lk. E. of fence extending N. and irregularly S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd. <div style="text-align: center;"> T55N R75W S 26 S 25 <hr style="width: 50%; margin: 0 auto;"/> S 35 S 36 PLS 538 1998 </div>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>This position is accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.</p> <p>S. 89° 04' W., bet. secs. 25 and 36.</p> <p>Over gently rolling terrain, along fence.</p>
40.05	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, determined latitudinally by fence extending E. and W. and longitudinally at projection of fence from the N.; there is no remaining evidence of the original monument.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T55N R75W</p> <p>S 25</p> <p>1/4 ———</p> <p>S 36</p> <p>2001</p> </div> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 04' W., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p>
24.40	<p>Leave fence, curves to the NW.</p>
40.23	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0° 26' E., bet. secs. 25 and 26.</p> <p>Over rolling to broken terrain, along fence.</p>
1.70	<p>Wash, drains W.</p>
6.60	<p>U.S. Highway Nos. 14 and 16, bears ESE. and WNW.</p>
25.20	<p>Store Draw, drains W.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
39.97	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T55N</td><td>R75W</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 26</td><td> S 25</td></tr> <tr><td>2001</td><td></td></tr> </table> <hr style="width: 20%; margin: 10px auto;"/> </div> <p>N. 0° 31' E., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p>	T55N	R75W	1/4		S 26	S 25	2001			
T55N	R75W										
1/4											
S 26	S 25										
2001											
39.97	<p>The cor. of secs. 23, 24, 25, and 26, remonumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 20 ins. in the ground, in a collar of stone, with a lava stone, 8x8x5 ins., plainly mkd. 2 grooves on a face, buried alongside, at intersection of fences extending N., E. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W S23 S24 S25 S26 PLS 5655 2000. This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T55N</td><td>R75W</td></tr> <tr><td>S 23</td><td> S 24</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 26</td><td> S 25</td></tr> <tr><td>2001</td><td></td></tr> </table> </div> <p>Deposit the steel reinforcement rod inside and bury the original cor. stone alongside the stainless steel post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 89° 13' W., bet. secs. 24 and 25.</p>	T55N	R75W	S 23	S 24			S 26	S 25	2001	
T55N	R75W										
S 23	S 24										
S 26	S 25										
2001											

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling terrain, along fence.
40.03	The 1/4 sec. cor. of secs. 24 and 25, monumented in 1978 by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 2 ins. below the surface of the ground, at intersection of fences extending E., S. and W. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R75W S 24 1/4 ——— S 25 2001
	Deposit the steel reinforcement rod inside the stainless steel post.
	—————
	S. 88° 32' W., beginning new measurement.
	Over rolling terrain, along fence.
28.30	Wash, drains NNW.
40.22	The cor. of secs. 23, 24, 25 and 26.
	—————
	N. 0° 05' E., bet. secs. 23 and 24.
	Over rolling to broken terrain, along fence.
11.60	Wash, drains WNW.
40.67	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance, falls in cultivated field.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T55N R75W 1/4 S 23 S 24 2001
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 87 lks. W. of fence extending irregularly N. and S.
56.50	Wash, drains WNW.
61.40	Spur, slopes W.
63.60	Wash, drains W.
71.30	Ridge, bears SE. and NW.
79.80	Wash, drains WNW.
81.34	<p>The cor. of secs. 13, 14, 23 and 24, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 19 ins. in the ground, in a collar of stone, at intersection of fences extending E., S., W. and irregularly N., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W S13 S14 S23 S24 PLS 5655 2000. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	T55N R75W S 14 S 13 ———— S 23 S 24 2001
	Deposit the steel reinforcement rod inside the stainless steel post.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	S. 89° 43' W., bet. secs. 13 and 24.
	Over rolling to broken terrain.
4.60	Werner Road, bears ESE. and WNW.
8.20	Cor. of fences extending ENE. and W.; thence along fence.
39.20	Leave fence, bears WSW.
40.31	Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance, falls in projection of fence from the E.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T55N R75W S 13 1/4 ——— S 24 2001
	Set a steel fence post alongside the stainless steel post.
80.62	The cor. of secs. 13, 14, 23 and 24.
	N. 1° 11' E., bet. secs. 13 and 14.
	Over rolling to broken terrain.
17.40	Ridge, bears SE. and NW.; thence along fence.
29.60	Wash, drains WSW.
39.52	The 1/4 sec. cor. of secs. 13 and 14, at intersection of fences extending N., S. and W. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T55N R75W 1/4 S 14 S 13 2001 <hr/>
	N. 1° 11' E., beginning new measurement.
	Over rolling terrain, along fence.
32.90	Ridge, bears SE. and NW.
40.88	The cor. of secs. 11, 12, 13 and 14, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 20 ins. in the ground, in a collar of stone, at cor. of fences extending E. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W S11 S12 S13 S14 PLS 5655 2000. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T55N R75W S 14 S 13 <hr/> S 23 S 24 2001
	Deposit the steel reinforcement rod inside the stainless steel post.
	<hr/>
	From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp.
	S. 89° 28' W., bet. secs. 12 and 13.
	Over gently rolling terrain.
20.20	Cor. of fences extending N. and W.; thence along fence.
40.53	Point for the 1/4 sec. cor. of secs. 12 and 13, determined longitudinally by proportionate measurement and latitudinally by fence extending E. and W.; there is no remaining evidence of the original monument.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R75W S 12 1/4 ——— S 13 2001</p> <hr style="width: 30%; margin: auto;"/>
	<p>S. 89° 11' W., beginning new measurement.</p>
	<p>Over nearly level terrain, along fence.</p>
20.20	<p>Werner Road, bears N. and S.</p>
40.53	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr style="width: 60%; margin: auto;"/>
	<p>N. 1° 13' E., bet. secs. 11 and 12.</p>
	<p>Over gently rolling terrain.</p>
39.74	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, determined latitudinally by Broyles Road, previously known as Mitchell Road, extending E. and W., and longitudinally at projection of fence from the N., falls in cattle guard; there is no remaining evidence of the original monument.</p> <p>Chisel an X inside a 1 in. square, on center cross pipe of cattle guard</p> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, in right-of-way fence extending E. and W., bears S. 49¾° E., 74.8 lks. dist., with brass cap mkd. RM T55N R75W S12 49.4 FT. TO COR. 2002 and an arrow pointing to the cor.</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, in right-of-way fence extending E. and W., bears S. 37¾° W., 64.1 lks. dist., with brass cap mkd. RM T55N R75W S11 42.3 FT. TO COR. 2002 and an arrow pointing to the cor.</p> <hr style="width: 30%; margin: auto;"/>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS																
40.43	<p>N. 1° 15' E., beginning new measurement.</p> <p>Over gently rolling terrain, along fence.</p> <p>Point for the cor. of secs. 1, 2, 11 and 12, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 11</td> <td style="padding: 0 5px;">S 12</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">2002</td> <td></td> </tr> </table> </div> <p>From this point, a position established by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, bears N. 2° 24' E., 35 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, in a collar of stone, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W S1 S2 S11 S12 PLS 5655 2000. This position was based upon proportionate measurement but ignored local control to the S. and is not accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp.</p> <p>S. 89° 16' W., bet. secs. 1 and 12.</p> <p>Over gently rolling terrain.</p>	T55N	R75W		S 2	S 1		S 11	S 12			2002				
T55N	R75W															
S 2	S 1															
S 11	S 12															
	2002															
40.605	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> <td></td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 1</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 5px;"></td> <td></td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 12</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">2002</td> <td></td> </tr> </table> </div>	T55N	R75W			S 1		1/4				S 12			2002	
T55N	R75W															
	S 1															
1/4																
	S 12															
	2002															

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 4.0 chs. W. of small rise.
81.21	The cor. of secs. 1, 2, 11 and 12.
	N. 1° 44' E., bet. secs. 1 and 2.
	Over gently rolling terrain, along fence.
19.00	Intersection of fences extending N., S. and W.; continue along fence.
40.44	Point for the 1/4 sec. cor. of secs. 1 and 2, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R75W 1/4 S 2 S 1 2002
	N. 1° 41' E., beginning new measurement.
	Over gently rolling terrain, along fence.
19.75	Dim fence scar, bears E.
40.47	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., as described in the 2000-01 field notes of the dependent resurvey, T. 54 N., R. 75 W.
	N. 15° 52' W., bet. secs. 34 and 35.
	Over mountainous terrain.
12.80	Wash, drains SE.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
22.00	Ridge, bears SE. and NW.
32.97	Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T55N R75W 1/4 S 34 S 35 2001 </div>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.
56.00	Wash, drains E.
65.94	The cor. of secs. 26, 27, 34 and 35, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, ⅝ in. diam., firmly set 16 ins. in the ground, in a collar of stone, in fence extending E. and W., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W S26 S27 S34 S35 PLS 5655 2000. This position is accepted as a careful and faithful determination of the original cor. position. At the corner point Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T55N R75W S 27 S 26 ———— S 34 S 35 LS 5655 2000 </div>
	Deposit the steel reinforcement rod inside the stainless steel post. <hr/>
	From the cor. of secs. 25, 26, 35 and 36. S. 88° 52' W., bet. secs. 26 and 35. Over rolling to broken terrain.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.10	Spotted Horse Creek, course NNW.
39.40	Fence, bears N. and S.
40.33	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T55N R75W S 26 1/4 ——— S 35 2001 </div>
	Set a steel fence post alongside the stainless steel post.
60.495	Point for the W. 1/16 sec. cor. of secs. 26 and 35, falls in wash, drains NE. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T55N R75W S 26 W1/16 ——— S 35 2001 </div>
	Set a steel fence post alongside the stainless steel post.
67.50	Cor. of fences extending ENE. and W.; thence along fence.
80.66	The cor. of secs. 26, 27, 34 and 35. <hr/> N. 0° 47' E., bet. secs. 26 and 27. Over rolling to broken terrain.
25.60	U.S. Highway Nos. 14 and 16, bears ENE. and WSW.
40.69	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance, falls on steep E. slope of wash, drains NNE.; there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T55N R75W 1/4 S 27 S 26 2001</p> <p>Set a steel fence post alongside the stainless steel post.</p>
43.50	Wash, drains NE.
60.10	Ridge, bears NE. and SW.
61.035	Point for the N. 1/16 sec. cor. of secs. 26 and 27.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R75W N1/16 S 27 S 26 2001</p> <p>Set a steel fence post alongside the stainless steel post.</p>
81.38	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance, falls in cultivated field.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T55N R75W S 22 S 23 ----- S 27 S 26 2001</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89° 54' W., bet. secs. 23 and 26.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling to broken terrain.
20.045	<p>Point for the E. 1/16 sec. cor. of secs. 23 and 26, falls in cultivated field.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T55N R75W S 23 E1/16 ——— S 26 2001 </div> <p>Set a steel fence post alongside the stainless steel post.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T55N R75W S 23 1/4 ——— S 26 2001 </div> <p>Set a steel fence post alongside the stainless steel post.</p>
59.40	Improved road, bears SE. and NW.
60.135	<p>Point for the W. 1/16 sec. cor. of secs. 23 and 26, falls in cultivated field.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T55N R75W S 23 W1/16 ——— S 26 2001 </div> <p>Set a steel fence post alongside the stainless steel post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
72.20	Spotted Horse Creek, course NNW.
80.18	The cor. of secs. 22, 23, 26 and 27. <hr/>
	N. 0° 36' E., bet. secs. 22 and 23. Over rolling to broken terrain.
3.60	Spotted Horse Creek, course NW.
6.50	Spotted Horse Creek, course NE.
8.70	Spotted Horse Creek, course WSW.
40.69	Point for the 1/4 sec. cor. of secs. 22 and 23, determined longitudinally by proportionate measurement and latitudinally by abandoned fence extending E. and W.; there is no remaining evidence of the original monument. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T55N R75W 1/4 S 22 S 23 2001</div>
	Set a steel fence post alongside the stainless steel post. <hr/>
	N. 0° 36' E., beginning new measurement. Over rolling to broken terrain.
9.70	Wash, drains SSW.
29.30	Cor. of fences extending N. and SSW.; thence along fence.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
40.16	<p>The cor. of secs. 14, 15, 22 and 23, monumented by Lawrence C. Kay, Wyoming Registered Land Surveyor No. 489, with a steel reinforcement rod, 30 ins. long, $\frac{3}{4}$ in. diam., firmly set 23 ins. in the ground, at intersection of fences extending N., E. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed UINTAH ENG & L.S. and mkd. T55N R75W S14 S15 S22 S23 WYO 489 2000. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2001</td> </tr> </table> </div> <p>Deposit the steel reinforcement rod inside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. $88^{\circ} 49'$ W., bet. secs. 14 and 23.</p> <p>Over rolling to broken terrain, along fence.</p>	T55N	R75W	S 15	S 14	S 22	S 23	2001			
T55N	R75W										
S 15	S 14										
S 22	S 23										
2001											
4.30	Wash, drains NW.										
8.30	Wash, drains SSW.										
39.73	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, determined longitudinally by proportionate measurement and latitudinally by fence extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="padding: 0 5px;">$\frac{1}{4}$</td> <td style="border-top: 1px solid black; padding: 0 5px;">—</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2001</td> </tr> </table> </div> <hr/>	T55N	R75W		S 14	$\frac{1}{4}$	—		S 23	2001	
T55N	R75W										
	S 14										
$\frac{1}{4}$	—										
	S 23										
2001											

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 89° 45' W., beginning new measurement.
	Over gently rolling terrain, along fence.
2.30	Head of wash, drains SE.
39.72	The cor. of secs. 14, 15, 22 and 23.
<hr/>	
	N. 0° 07' E., bet. secs. 14 and 15.
	Over rolling terrain, along fence.
19.70	Wash, drains NW.
20.01	Point for the S. 1/16 sec. cor. of secs. 14 and 15.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T55N R75W S1/16 S 15 S 14 2001
	Cor. is located 4 lks. E. of fence extending N. and S.
40.02	The 1/4 sec. cor. of secs. 14 and 15, monumented by Lawrence C. Kay, Wyoming Registered Land Surveyor No. 489, with a steel reinforcement rod, 30 ins. long, ¾ in. diam., firmly set 24 ins. in the ground, at intersection of fences extending N., E., S. and W., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed UINTAH ENG & L.S. and mkd. T55N R75W 1/4 S14 S15 WYO 489 2000. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R75W 1/4 S 15 S 14 2001

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS																
	<p>Deposit the steel reinforcement rod inside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 41' E., beginning new measurement.</p> <p>Over rolling terrain.</p>															
40.28	<p>The cor. of secs. 10, 11, 14 and 15, monumented by Lawrence C. Kay, Wyoming Registered Land Surveyor No. 489, with a steel reinforcement rod, 30 ins. long, ¾ in. diam., firmly set flush with the surface of the ground, at projected intersection of fences from the E. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed UINTAH ENG & L.S. and mkd. T55N R75W S14 S15 S22 S23 WYO 489 2000. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S 10</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 11</td> <td></td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; height: 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S 15</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 14</td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">2001</td> </tr> </table> </div> <p>Deposit the steel reinforcement rod inside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89° 29' W., bet. secs. 11 and 14.</p> <p>Over rolling terrain.</p>	T55N	R75W		S 10	S 11					S 15	S 14		2001		
T55N	R75W															
S 10	S 11															
S 15	S 14															
2001																
13.50	Ridge, bears SE. and NW.															
40.255	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>															

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T55N R75W S 11 1/4 ——— S 14 2001
	Set a steel fence post alongside the stainless steel post.
53.90	Cor. of fences extending SSE. and W.; thence along fence.
56.80	Wash, drains NNE.
80.51	The cor. of secs. 10, 11, 14 and 15.
	<hr/> N. 0° 56' E., bet. secs. 10 and 11. Over rolling to broken terrain.
21.60	Wash, drains WNW.
39.37	Point for the 1/4 sec. cor. of secs. 10 and 11, determined longitudinally by proportionate measurement and latitudinally by Broyles Road, previously known as Mitchell Road, extending E. and W.; there is no remaining evidence of the original monument.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. below the graveled surface of the road, with brass cap mkd.
	T55N R75W 1/4 S 10 S 11 2002
	from which
	A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, in a collar of stone, in right-of-way fence extending E. and W., bears S. 46½° E., 69.2 lks. dist., with brass cap mkd. RM T55N R75W S11 45.7 FT. TO COR. 2002 and an arrow pointing to the cor.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, in a collar of stone, in right-of-way fence extending E. and W., bears S. 47° W., 72.1 lks. dist., with brass cap mkd. RM T55N R75W S10 47.6 FT. TO COR. 2002 and an arrow pointing to the cor.</p> <p>From this point, a right-of-way monument to Station 22 of Mitchell Road, a sandstone, firmly set, projecting 12x5x5 ins. above the ground, in right-of-way fence extending E. and W., plainly mkd. CR on N. face, no other mks. visible, bears S. 82° 14' E., 3.97 chs. dist. The survey notes for Mitchell Road, presently known as Broyles Road, were not found at the Campbell County Court House.</p> <hr/> <p>N. 0° 56' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>										
39.97	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T55N</td> <td>R75W</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 88° 53' W., bet. secs. 2 and 11.</p> <p>Over rolling terrain.</p>	T55N	R75W	S 3	S 2			S 10	S 11	2002	
T55N	R75W										
S 3	S 2										
S 10	S 11										
2002											
40.465	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>										

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T55N R75W S 2 1/4 ——— S 11 2002
	Set a steel fence post alongside the stainless steel post.
80.93	The cor. of secs. 2, 3, 10 and 11.
	<hr/> N. 1° 37' E., bet. secs. 2 and 3. Over rolling terrain.
39.98	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R75W 1/4 S 3 S 2 2002
	Set a steel fence post alongside the stainless steel post and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of the cor.
	Cor. is located 1.0 ch. E. of wash, drains NNW.
51.00	Wash, drains NE.
54.80	Fence, bears N. and E.; thence along fence.
80.47	True point for the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.
	<hr/> From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the 2000-01 field notes of the dependent resurvey, T. 54 N., R. 75 W. N. 13° 46' W., bet. secs. 33 and 34. Over mountainous terrain.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
18.00	Ridge, bears SE. and NW.
36.87	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance, falls on sandstone boulder, 6x6x2 ft. above the ground; there is no remaining evidence of the original cor.</p> <p>Set a brass tablet, 3¼ ins. diam., 3½ in. stem, in drill hole in sandstone boulder, with top mkd.</p>
	<p style="text-align: center;">T55N R75W 1/4 S 33 S 34 2001</p>
	Set a steel fence post alongside the sandstone boulder.
43.80	Wash, drains NW.
73.74	<p>The cor. of secs. 27, 28, 33 and 34, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 8 ins. below the surface of cultivated field, at projection of abandoned fence from the E., with plastic cap mkd. B.E. RUMPH LS 538. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R75W S 28 S 27 ----- S 33 S 34 2001</p>
	Deposit the steel reinforcement rod inside and set a steel fence post alongside the stainless steel post.
	From the cor. of secs. 26, 27, 34 and 35.
	N. 86° 53' W., bet. secs. 27 and 34.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling to broken terrain, leaving fence.
24.30	Spur, slopes N.
40.18	Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance, falls in wash, drains NNW.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T55N R75W S 27 1/4 ——— S 34 2001 </div>
	Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.
77.30	Howell Draw, drains N.
80.36	The cor. of secs. 27, 28, 33 and 34. <hr/>
	N. 1° 26' E., bet. secs. 27 and 28. Over rolling terrain.
39.39	Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T55N R75W 1/4 S 28 S 27 2001 </div>
	Set a steel fence post alongside the stainless steel post.
47.20	U.S. Highway Nos. 14 and 16, bears ESE. and WSW.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
78.78	<p>The cor. of secs. 21, 22, 27 and 28, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, $\frac{5}{8}$ in. diam., firmly set 14 ins. below the surface of a cultivated field, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W S21 S22 S23 S24 LS 5655 2000. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, over the steel reinforcement rod, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">2001</td> </tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located N. $17^{\circ} 25'$ W., 2.23 chs. dist., from intersection of fences extending N., S. and W.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. $88^{\circ} 44'$ W., bet. secs. 22 and 27.</p> <p>Over rolling to broken terrain.</p>	T55N	R75W	S 21	S 22	S 28	S 27	2001			
T55N	R75W										
S 21	S 22										
S 28	S 27										
2001											
32.20	Ridge, bears SSE. and NNW.										
39.70	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-bottom: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">2001</td> </tr> </table> </div>	T55N	R75W		S 22	1/4			S 27	2001	
T55N	R75W										
	S 22										
1/4											
	S 27										
2001											

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the stainless steel post.
	Cor. is located on W. edge of trail road extending SSE. and NNW.
44.20	Wash, drains NW.
50.90	Spur, slopes NW.
63.70	Rucker Draw, drains NNE.
79.40	The cor. of secs. 21, 22, 27 and 28.
	<hr/>
	N. 0° 26' E., bet. secs. 21 and 22.
	Over rolling terrain.
39.37	The 1/4 sec. cor. of secs. 21 and 22, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 20 ins. in the ground, in a collar of stone, in fence extending E. and W., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W 1/4 S21 S22 LS 5655 2000. This position is accepted as a careful and faithful determination of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T55N R75W 1/4 S 21 S 22 2001
	Deposit the steel reinforcement rod inside the stainless steel post, remove the collar of stone and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.
	<hr/>
	N. 0° 26' E., beginning new measurement.
	Over rolling to broken terrain.
4.70	Ridge, bears SE. and NW.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
39.20	Spotted Horse Creek, course WNW.										
39.91	<p>The cor. of secs. 15, 16, 21 and 22, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, at cor. of fences extending N. and W., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">PLS 538</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2000</td> </tr> </table> </div> <p>This position is accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89° 52' W., bet. secs. 15 and 22.</p> <p>Over rolling to broken terrain.</p>	T55N	R75W	S 16	S 15	S 21	S 22	PLS 538		2000	
T55N	R75W										
S 16	S 15										
S 21	S 22										
PLS 538											
2000											
10.30	Wash, drains WSW.										
39.81	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">_____</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2001</td> </tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p>	T55N	R75W		S 15	1/4	_____		S 22	2001	
T55N	R75W										
	S 15										
1/4	_____										
	S 22										
2001											
79.62	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 0° 25' E., bet. secs. 15 and 16.</p>										

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over gently rolling terrain, along fence.
19.93	<p>Point for the S. 1/16 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R75W S1/16 S 16 S 15 2001</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 3 lks. E. of fence extending N. and S.</p>
26.10	Wash, drains SW.
39.86	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, at intersection of fences extending N., E. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <p style="text-align: center;">T55N R75W 1/4 S 16 S 15 PLS 538 1999</p> <p>This position is accepted as the best available evidence of the original cor. position.</p> <p style="text-align: center;">_____</p> <p>N. 0° 04' E., beginning new measurement.</p> <p>Over rolling to broken terrain, along fence.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
39.20	<p>The cor. of secs. 9, 10, 15 and 16, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground, in a collar of stone, in fence extending N. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">PLS 538</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1999</td> </tr> </table> </div> <p>This position is accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89° 15' W., bet. secs. 10 and 15.</p> <p>Over rolling to broken terrain.</p>	T55N	R75W	S 9	S 10	S 16	S 15	PLS 538		1999	
T55N	R75W										
S 9	S 10										
S 16	S 15										
PLS 538											
1999											
29.60	Wash, drains NNW.										
39.915	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">_____</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2002</td> </tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p>	T55N	R75W		S 10	1/4	_____		S 15	2002	
T55N	R75W										
	S 10										
1/4	_____										
	S 15										
2002											
79.83	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>N. 1° 16' E., bet. secs. 9 and 10.</p>										

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over mountainous terrain, along fence.
3.80	Intersection of fences extending ESE., S. and WNW.
27.00	Ridge, bears SE. and NW.
39.65	Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.
	T55N R75W 1/4 S 9 S 10 2002
	from which
	A pine, 23 ins. diam., bears S. 76° W., 54 lks. dist., mkd. 1/4 S9 BT.
	Set a steel fence post alongside the stainless steel post.
46.90	Wash, drains WNW.
68.00	Ridge, bears NE. and SSW.
77.30	Wash, drains SW.
79.30	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance, falls on sandstone outcrop, 24x18 ins., flush with the surface of the ground; there is no remaining evidence of the original cor.
	Set a brass tablet, 3¼ ins. diam., 3½ in. stem, in drill hole in sandstone outcrop, in a collar of stone, with top mkd.
	T55N R75W S 4 S 3 ———— S 9 S 10 2002

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which</p> <p style="text-align: center;">A pine, 13 ins. diam., bears S. 1° E., 22 lks. dist., mkd. T55N R75W S10 BT.</p> <p>Set a steel fence post near the sandstone outcrop.</p> <p>Cor. is located on spur, slopes ESE.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 88° 46' W., bet. secs. 3 and 10.</p> <p>Over gently rolling terrain.</p> <p>21.20 Broyles Road, on curve, bears S. and W.; thence along road.</p> <p>39.10 Leave Broyles Road, on curve, bears N.</p> <p>40.34 The 1/4 sec. cor. of secs. 3 and 10, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set flush with the surface of the ground, in borrow pit of Broyles Road, at projected intersection of road from the N. and E., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W 1/4 S3 S10 LS 5655 2000. This position is accepted as the best available evidence of the original cor. position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R75W</p> <p>S 3</p> <p>1/4 ———</p> <p>S 10</p> <p>2001</p> </div> <p>Deposit the steel reinforcement rod inside and set a steel fence post alongside the stainless steel post.</p> <hr/> <p>S. 89° 40' E., beginning new measurement.</p> <p>Over rolling to broken terrain.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
37.40	Wash, drains SE.
39.03	The cor. of secs. 3, 4, 9 and 10.
	<hr/> <p>N. 0° 42' E., bet. secs. 3 and 4.</p> <p>Over rolling to broken terrain.</p>
2.30	Wash, drains SE.
39.64	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, 5/8 in diam., firmly set 6 ins. below the scoria surface of Broyles Road, extending E. and W., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W 1/4 S3 S4 LS 5655 2000. This position is accepted as the best available evidence of the original cor. position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. below the surface of the road, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T55N R75W 1/4 S 4 S 3 2002</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, in a collar of stone, in right-of-way fence extending E. and W., bears S. 47½° E., 70.3 lks. dist., with brass cap mkd. RM T55N R75W S3 46.4 FT. TO COR. 2002 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, in a collar of stone, in right-of-way fence extending E. and W., bears S. 48½° W., 71.7 lks. dist., with brass cap mkd. RM T55N R75W S4 47.3 FT. TO COR. 2002 and an arrow pointing to the cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Deposit the steel reinforcement rod inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 43' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
40.64	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with a brass tablet, 3¼ ins. diam., as described in the 2000-01 field notes of the dependent resurvey, T. 54 N., R. 75 W.</p> <p>N. 14° 13' W., bet. secs. 32 and 33.</p> <p>Over rolling to broken terrain.</p>
26.60	<p>Wash, at bend, drains NNE.</p>
34.77	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T55N R75W 1/4 S 32 S 33 2001</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p>
38.10	<p>Trail road, bears E. and W., across stock dam in wash, drains NNW.</p>
69.54	<p>The cor. of secs. 28, 29, 32 and 33, monumented with a lava stone, 17x10x7 ins., firmly set 7 ins. in the ground, no mks. visible, and perpetuated by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 20 ins. in the ground, in a collar of stone, and a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. 28 29 32 33 LS 5655 2000. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T55N</td><td>R75W</td></tr> <tr><td>S 29</td><td> S 28</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 32</td><td> S 33</td></tr> <tr><td colspan="2" style="text-align: center;">2001</td></tr> </table>	T55N	R75W	S 29	S 28			S 32	S 33	2001	
T55N	R75W										
S 29	S 28										
S 32	S 33										
2001											
	Deposit the steel reinforcement rod inside and bury the unmkd. stone alongside the stainless steel post.										
	From the cor. of secs. 27, 28, 33 and 34.										
	S. 86° 11' W., bet. secs. 28 and 33.										
	Over rolling to broken terrain.										
5.80	Wash, drains NNW.										
25.10	Wash, drains NNW.										
35.80	Trail road, bears N. and S.										
39.29	Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original cor.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T55N</td><td>R75W</td></tr> <tr><td></td><td>S 28</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 33</td></tr> <tr><td colspan="2" style="text-align: center;">2001</td></tr> </table>	T55N	R75W		S 28	1/4	—		S 33	2001	
T55N	R75W										
	S 28										
1/4	—										
	S 33										
2001											
	Cor. is located on W. edge of drainage ditch extending NNE. and SSW.										
78.58	The cor. of secs. 28, 29, 32 and 33.										
	N. 0° 56' E., bet. secs. 28 and 29.										
	Over rolling to broken terrain.										

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
7.60	Rucker Draw, drains NNE.
22.50	Spur, slopes NE.
29.50	Wash, drains NE., thence along abandoned fence.
31.20	Spur, slopes NE.
33.20	Wash, drains ESE.
39.94	The 1/4 sec. cor. of secs. 28 and 29, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 22 ins. in the ground, in a collar of stone, in abandoned fence extending N. and S., and a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. 1/4 28 29 LS 5655 2000. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T55N R75W 1/4 S 29 S 28 2001
	Deposit the steel reinforcement rod inside the stainless steel post.

	N. 0° 04' E., beginning new measurement.
	Over rolling terrain, along abandoned fence.
3.00	Intersection of fence extending E. and W. and abandoned fence extending S.
36.60	U.S. Highway Nos. 14 and 16, bears ESE. and WNW.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS																
41.63	<p>The cor. of secs. 20, 21, 28 and 29, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, $\frac{5}{8}$ in. diam., firmly set 21 ins. in the ground, in a collar of stone, and a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W S20 S21 S28 S29 LS 5655 2000. This cor. position, which is located in a cultivated field, is based upon cor. ties contained in the field notes of the right-of-way survey of Custer Battlefield Highway by J. C. Harvey, Deputy County Surveyor, in 1920, and is accepted as a careful and faithful perpetuation of the reestablishment of this cor. position by an early surveyor named Vale.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S 20</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 21</td> <td></td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; height: 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S 29</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 28</td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">2001</td> </tr> </table> </div> <p>Deposit the steel reinforcement rod inside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. $88^{\circ} 15'$ W., bet. secs. 21 and 28.</p> <p>Over gently rolling terrain.</p>	T55N	R75W		S 20	S 21					S 29	S 28		2001		
T55N	R75W															
S 20	S 21															
S 29	S 28															
2001																
39.84	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> <td></td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 21</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">$\frac{1}{4}$</td> <td style="border-top: 1px solid black; padding: 0 5px;"></td> <td></td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 28</td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">2001</td> </tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p>	T55N	R75W			S 21		$\frac{1}{4}$				S 28		2001		
T55N	R75W															
	S 21															
$\frac{1}{4}$																
	S 28															
2001																

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
59.80	S A Road, bears N. and S.
79.68	The cor. of secs. 20, 21, 28 and 29.
	<hr/> <p>N. 0° 14' W., bet. secs. 20 and 21.</p> <p>Over gently rolling terrain.</p>
36.90	Fence, bears E. and W.
39.84	Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T55N R75W 1/4 S 20 S 21 2001</p>
	Deposit a red clay brick as a memorial and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.
79.68	The cor. of secs. 16, 17, 20 and 21, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, alongside old cor. post with fence scars extending N. and W., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.
	<p>T55N R75W S 17 S 16 <hr/>S 20 S 21 PLS 538 1999</p>
	This position is accepted as the best available evidence of the original cor. position.
	<hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	S. 88° 33' W., bet. secs. 16 and 21.
	Over mountainous terrain, leaving fence.
2.70	Spotted Horse Creek, course NW.
14.60	Ridge, bears SSE. and NNW.
20.14	The E. 1/16 sec. cor. of secs. 16 and 21, monumented by Jeffery C. Lewis, Wyoming Registered Land Surveyor No. 3886, with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 4 ft. base, 1½ ft. high, as filed in the Campbell County Clerk's Office, with brass cap mkd.
	T55N R75W S 16 E1/16 ——— S 21 LS 3886 2000
	This position is accepted as a careful and faithful determination of the cor. position.
	Cor. is located on steep N. slope of wash, drains WNW., S. 66° 26' W., 1.08 chs. dist., from cor. of fences extending E. and irregularly S.
	—————
	S. 88° 33' W., beginning new measurement.
	Over mountainous terrain.
7.00	Wash, drains NNE.
20.14	The 1/4 sec. cor. of secs. 16 and 21, monumented by Jeffery C. Lewis, Wyoming Registered Land Surveyor No. 3886, with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 2½ ft. base, 1½ ft. high, as filed in the Campbell County Clerk's Office, with brass cap mkd.
	T55N R75W S 16 1/4 ——— S 21 LS 3886 2000

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located on steep NE. slope of spur, slopes NE.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>S. 88° 33' W., beginning new measurement.</p> <p>Over mountainous terrain.</p>
14.70	Ridge, bears NE. and SW.
20.14	<p>The W. 1/16 sec. cor. of secs. 16 and 21, monumented by Jeffery C. Lewis, Wyoming Registered Land Surveyor No. 3886, with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, as filed in the Campbell County Clerk's Office, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T55N R75W S 16 W1/16 ——— S 21 LS 3886 2000</p> </div> <p>This position is accepted as a careful and faithful determination of the cor. position.</p> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>S. 88° 33' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
2.30	S A Road, bears N. and S.
20.14	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr style="width: 80%; margin-left: 0;"/> <p>N. 0° 56' E., bet. secs. 16 and 17.</p> <p>Over mountainous terrain, leaving fence scar.</p>
21.50	Ridge, bears E. and W.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.85	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R75W 1/4 S 17 S 16 2001</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 2.90 chs. E. of fence extending irregularly N. and S.</p>
41.30	Spur, slopes SE.
79.70	<p>The cor. of secs. 8, 9, 16 and 17, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground, in a collar of stone, with a broken lava stone, 15x8x7 ins., plainly mkd. 4 grooves on a face, 3 grooves on broken portion of adjacent face, no other mks. visible, buried alongside, at cor. of fences extending S. and WNW., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <div style="text-align: center;"> <p>T55N R75W S 8 S 9 ----- S 17 S 16 PLS 538 1999</p> </div> <p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 88° 59' W., bet. secs. 9 and 16.</p> <p>Over mountainous terrain.</p>
18.20	Ridge, bears NE. and SW.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.78	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R75W S 9 1/4 ——— S 16 2001</p> </div> <p>Set a steel fence post alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2½ ft. high, N. of the cor.</p>
44.30	S A Road, bears SSE. and NNW.
51.30	Spotted Horse Creek, course NNW.
79.56	The cor. of secs. 8, 9, 16 and 17.
	<hr/> <p>N. 0° 47' E., bet. secs. 8 and 9.</p> <p>Over rolling terrain.</p>
21.30	Improved road, bears SE. and NW.
36.00	Spotted Horse Creek, course NNE.
40.01	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R75W 1/4 S 8 S 9 2001</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p>
59.30	Spur, slopes SW.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
60.015	<p>Point for the N. 1/16 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T55N</td><td>R75W</td></tr> <tr><td>N1/16</td><td></td></tr> <tr><td>S 8</td><td> S 9</td></tr> <tr><td>2002</td><td></td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p>	T55N	R75W	N1/16		S 8	S 9	2002			
T55N	R75W										
N1/16											
S 8	S 9										
2002											
80.02	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T55N</td><td>R75W</td></tr> <tr><td>S 5</td><td> S 4</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 8</td><td> S 9</td></tr> <tr><td>2001</td><td></td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located on S. edge of small wash, drains SW.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 85° 19' W., bet. secs. 4 and 9.</p> <p>Over mountainous terrain.</p>	T55N	R75W	S 5	S 4	<hr/>		S 8	S 9	2001	
T55N	R75W										
S 5	S 4										
<hr/>											
S 8	S 9										
2001											
39.43	<p>The 1/4 sec. cor. of secs. 4 and 9, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, witnessed by 2 pits, N. and S. of the cor., at cor. of fences extending NE. and W., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p>										

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R75W S 4 1/4 ——— S 9 PLS 538 2001</p>
	<p>This position is accepted as the best available evidence of the original cor. position.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/>
	<p>N. 86° 25' W., beginning new measurement.</p>
	<p>Over rolling to broken terrain, leaving fence.</p>
23.20	S A Road, bears NNE. and SSW.
40.97	The cor. of secs. 4, 5, 8 and 9.
	<hr style="width: 80%; margin-left: 0;"/> <p>N. 0° 04' E., bet. secs. 4 and 5.</p>
	<p>Over mountainous terrain.</p>
32.70	Wash, drains SW.
40.01	Point for the 1/4 sec. cor. of secs. 4 and 5, determined longitudinally by proportionate measurement and latitudinally by fence extending E. and W.; there is no remaining evidence of the original monument.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R75W 1/4 S 5 S 4 2001</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/>
	<p>N. 0° 04' E., beginning new measurement.</p>
	<p>Over mountainous terrain.</p>
39.69	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the 2000-01 field notes of the dependent resurvey, T. 54 N., R. 75 W.</p> <p>N. 14° 47' W., bet. secs. 31 and 32.</p> <p>Over mountainous terrain.</p>
24.10	Saddle in ridge, bears NNE. and SSW.
33.50	Spur, slopes W.
34.88	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R75W 1/4 S 31 S 32 2001</p>
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p>
52.32	<p>Point for the N. 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R75W N1/16 S 31 S 32 2001</p>
	<p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 17 lks. S. of fence extending ESE. and WNW., on spur, slopes W.</p>
54.00	Wash, drains WSW.
66.80	Spur, slopes WNW.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS																
69.76	<p>The cor. of secs. 29, 30, 31 and 32, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, $\frac{5}{8}$ in. diam., firmly set 22 ins. in the ground, in a collar of stone, in fence extending N. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W S29 S30 S31 S32 LS 5655 2000. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 30</td> <td style="padding: 0 5px;">S 29</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 31</td> <td style="padding: 0 5px;">S 32</td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">2001</td> </tr> </table> </div> <p>Deposit the steel reinforcement rod inside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. $89^{\circ} 12'$ W., bet. secs. 29 and 32.</p> <p>Over mountainous terrain.</p>	T55N	R75W		S 30	S 29		S 31	S 32		2001					
T55N	R75W															
S 30	S 29															
S 31	S 32															
2001																
4.90	Rucker Draw, drains NE.															
38.60	Fence, bears N. and S.															
39.73	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> <td></td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 29</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">$\frac{1}{4}$</td> <td style="border-top: 1px solid black; padding: 0 5px;">—</td> <td></td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 32</td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">2001</td> </tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p>	T55N	R75W			S 29		$\frac{1}{4}$	—			S 32		2001		
T55N	R75W															
	S 29															
$\frac{1}{4}$	—															
	S 32															
2001																

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Cor. is located on E. edge of wash, drains SE.
67.20	Ridge, bears N. and S.
79.46	The cor. of secs. 29, 30, 31 and 32.
	<hr/> S. 88° 17' W., bet. secs. 30 and 31. Over rolling to broken terrain.
21.07	Point for the E. 1/16 sec. cor. of secs. 30 and 31, falls in wash, drains NNW.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T55N R75W S 30 E1/16 ——— S 31 2001
	Set a steel fence post alongside the stainless steel post.
42.14	Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T55N R75W S 30 1/4 ——— S 31 2001
	Set a steel fence post alongside the stainless steel post.
	Cor. is located on E. edge of wash, drains NNW.
64.40	Ridge, bears SE. and NW.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS															
82.81	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 55 N., R. 76 W.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0° 13' E., bet. secs. 29 and 30.</p> <p>Over rolling to broken terrain, along fence.</p>														
39.87	<p>Point for the 1/4 sec. cor. of secs. 29 and 30, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T55N</td><td>R75W</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 30</td><td> S 29</td></tr> <tr><td>2001</td><td></td></tr> </table> <hr style="width: 30%; margin: 0 auto;"/> </div> <p>N. 0° 02' E., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p>	T55N	R75W	1/4		S 30	S 29	2001							
T55N	R75W														
1/4															
S 30	S 29														
2001															
37.20	U.S. Highway Nos. 14 and 16, bears ENE. and WSW.														
39.87	<p>The cor. of secs. 19, 20, 29 and 30, monumented by Don A. Davis, Wyoming Registered Land Surveyor No. 4824, with an iron post, 2½ ins. diam., firmly set 2 ins. below the surface of a cultivated field, as filed in the Campbell County Clerk's Office, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>WLC</td><td></td></tr> <tr><td>T55N</td><td>R75W</td></tr> <tr><td>S 19</td><td> S 20</td></tr> <tr><td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td>S 30</td><td> S 29</td></tr> <tr><td>LS 4824</td><td></td></tr> <tr><td>1999</td><td></td></tr> </table> </div> <p>from which reference monuments established by Mr. Davis,</p>	WLC		T55N	R75W	S 19	S 20	<hr style="width: 50%; margin: 0 auto;"/>		S 30	S 29	LS 4824		1999	
WLC															
T55N	R75W														
S 19	S 20														
<hr style="width: 50%; margin: 0 auto;"/>															
S 30	S 29														
LS 4824															
1999															

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>A steel reinforcement rod, $\frac{5}{8}$ in. diam., firmly set, projecting 1 in. above the ground, bears S. 43° E., 227.2 lks. dist.</p>
	<p>A steel reinforcement rod, $\frac{5}{8}$ in. diam., firmly set, projecting 1 in. above the ground, bears SOUTH, 186.3 lks. dist.</p>
	<p>Reference monuments are located in right-of-way fence extending E. and W.</p>
	<p>This position is accepted as a reestablishment of the original cor position.</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>Cor. is located 26 lks. E. of trail road extending N. and S.</p>
	<hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p>
	<p>S. $87^{\circ} 54'$ W., bet. secs. 20 and 29.</p>
	<p>Over rolling terrain.</p>
16.30	<p>U.S. Highway Nos. 14 and 16, bears ESE. and WNW.</p>
29.10	<p>Ridge, bears SSE. and NNW.</p>
39.72	<p>The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with a steel reinforcement rod, 24 ins. long, $\frac{5}{8}$ in. diam., firmly set 22 ins. in the ground, in a collar of stone, in fence extending N. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd. T55N R75W $\frac{1}{4}$ S20 S29 LS 5655 2000. This position is accepted as a careful and faithful determination of the original cor. position.</p>
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T55N R75W S 20 1/4 ——— S 29 2001
	Deposit the steel reinforcement rod inside the stainless steel post. <hr style="width: 20%; margin: 10px auto;"/>
	S. 87° 54' W., beginning new measurement.
	Over gently rolling terrain.
11.90	U.S. Highway Nos. 14 and 16, bears ENE. and WSW.
40.29	The cor. of secs. 19, 20, 29 and 30.
	<hr/>
	S. 88° 13' W., bet. secs. 19 and 30.
	Over rolling terrain.
2.50	Wash, drains NW.
40.23	The 1/4 sec. cor. of secs. 19 and 30, at cor. of fences extending S. and W. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T55N R75W S 19 1/4 ——— S 30 2001
	<hr/>
	S. 87° 36' W., beginning new measurement.
	Over rolling terrain, leaving fence.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
40.39	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 55 N., R. 76 W.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 23' W., bet. secs. 19 and 20.</p> <p>Over rolling terrain.</p>										
40.21	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance, falls at edge of cultivated field; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T55N</td><td>R75W</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td>S 19</td><td> S 20</td></tr> <tr><td></td><td>2001</td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located S. 40° W., 73 lks. dist., from cor. of fences extending S. and W., and N. 34° W., 44 lks. dist., from cor. of fences extending N. and E.</p>	T55N	R75W		1/4	S 19	S 20		2001		
T55N	R75W										
	1/4										
S 19	S 20										
	2001										
80.42	<p>Point for the cor. of secs. 17, 18, 19, and 20, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T55N</td><td>R75W</td></tr> <tr><td>S 18</td><td> S 17</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 19</td><td> S 20</td></tr> <tr><td></td><td>2001</td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located S. 67° W., 1.96 chs. dist., from cor. of fences extending W. and irregularly N.</p> <hr/>	T55N	R75W	S 18	S 17			S 19	S 20		2001
T55N	R75W										
S 18	S 17										
S 19	S 20										
	2001										

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 88° 26' W., bet. secs. 17 and 20.</p> <p>Over rolling terrain, along fence scar.</p>
16.40	Cor. of fences extending ENE. and W.; thence along fence.
20.70	Leave fence, bears NW.
37.80	Trail road, bears NE. and SW.
40.09	<p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T55N R75W S 17 1/4 ——— S 20 2002 </div> <p>Set a steel fence post alongside the stainless steel post.</p>
42.70	Ridge, bears SE. and NW.
66.80	Improved road, bears SE. and NW.
80.18	The cor. of secs. 17, 18, 19 and 20.
	<hr/> <p>S. 88° 59' W., bet. secs. 18 and 19.</p> <p>Over rolling terrain.</p>
40.03	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T55N R75W S 18 1/4 ——— S 19 2001
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 38 lks. S. of fence extending E. and W.
78.40	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 55 N., R. 76 W.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 1° 16' E., bet. secs. 17 and 18.
	Over rolling terrain.
40.22	Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R75W 1/4 S 18 S 17 2002
	Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. diam., 1½ ft. high, W. of the cor.
76.30	Leave cultivated field, bears E. and W.
80.44	The cor. of secs. 7, 8, 17 and 18, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, in projection of fence from the E., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T55N</td> <td style="padding: 2px 10px;">R75W</td> </tr> <tr> <td style="padding: 2px 10px; border-right: 1px solid black;">S 7</td> <td style="padding: 2px 10px;">S 8</td> </tr> <tr> <td style="padding: 2px 10px; border-right: 1px solid black;">S 18</td> <td style="padding: 2px 10px;">S 17</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px; text-align: center;">PLS 538</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px; text-align: center;">2001</td> </tr> </table> <p style="margin-top: 10px;">This position is accepted as a careful and faithful determination of the original cor. position.</p> <p>Cor. is located 6 lks. N. of fence extending irregularly E. and W.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 88° 57' W., bet. secs. 8 and 17.</p> <p>Over mountainous terrain.</p>	T55N	R75W	S 7	S 8	S 18	S 17	PLS 538		2001			
T55N	R75W												
S 7	S 8												
S 18	S 17												
PLS 538													
2001													
39.83	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, witnessed by 2 pits, N. and S. of the cor., with a mound of stone, 2 ft. base, 1 ft. high, W. of the cor., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p>												
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T55N</td> <td style="padding: 2px 10px;">R75W</td> </tr> <tr> <td style="padding: 2px 10px;"></td> <td style="padding: 2px 10px;">S 8</td> </tr> <tr> <td style="padding: 2px 10px;">1/4</td> <td style="padding: 2px 10px;">———</td> </tr> <tr> <td style="padding: 2px 10px;"></td> <td style="padding: 2px 10px;">S 17</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px; text-align: center;">PLS 538</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px; text-align: center;">2001</td> </tr> </table> <p style="margin-top: 10px;">This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Rebuild the mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>S. 88° 57' W., beginning new measurement.</p> <p>Over rolling terrain.</p>	T55N	R75W		S 8	1/4	———		S 17	PLS 538		2001	
T55N	R75W												
	S 8												
1/4	———												
	S 17												
PLS 538													
2001													
2.80	<p>Cor. of fences extending NE. and W., on ridge, bears N. and S.; thence along fence.</p>												

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.83	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 88° 32' W., bet. secs. 7 and 18.</p> <p>Over mountainous terrain, along fence.</p>
2.00	<p>Intersection of fences extending E. and irregularly S. and abandoned fence extending W., on ridge, bears SSE. and NNW.; thence along abandoned fence.</p>
19.95	<p>Point for the E. 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T55N R75W S 7 E1/16 ——— S 18 2001</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located on N. edge of pipeline scar extending E. and W.</p>
24.00	<p>Wash, drains NNW.</p>
39.90	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with a broken sandstone, 24x18x12 ins., base portion firmly set flush with the surface of the ground, and perpetuated by David L. Vliem, Wyoming Registered Land Surveyor No. 6872, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 20 ins. in the ground, in a collar of stone, no mkd. stone found, at intersection of abandoned fences extending N., E. and WSW., and a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC and mkd. 1/4 S7 S18 LS 6872 2000. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T55N R75W S 7 1/4 ——— S 18 2001
	Deposit the steel reinforcement rod inside and bury the broken sandstone alongside the stainless steel post.
	Remove the collar of stone and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.

	S. 88° 53' W., beginning new measurement.
	Over rolling terrain.
2.90	Wash, drains NNE.
4.20	South Prong Spotted Horse Creek, course NNW.
5.40	South Prong Spotted Horse Creek, course SE.
9.70	South Prong Spotted Horse Creek, course NNW.
40.20	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 55 N., R. 76 W.

	From the cor. of secs. 7, 8, 17 and 18.
	N. 0° 24' W., bet. secs. 7 and 8.
	Over mountainous terrain.
6.30	Wash, drains NW.
14.60	Spur, slopes NW.
20.04	Point for the S. 1/16 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base, to top, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R75W S1/16 S 7 S 8 2002</p>
	<p>from which</p>
	<p style="text-align: center;">A pine, 14 ins. diam., bears S. 32° E., 27 lks. dist., mkd S1/16 S8 BT</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
22.30	<p>Spur, slopes NW.</p>
40.08	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R75W 1/4 S 7 S 8 2002</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
43.30	<p>South Prong Spotted Horse Creek.</p>
60.12	<p>Point for the N. 1/16 sec. cor. of secs. 7 and 8.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R75W N1/16 S 7 S 8 2002</p>
	<p>Set a steel fence post alongside the stainless steel post.</p>
61.10	<p>Wash, drains SE.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS																			
80.16	<p>The cor. of secs. 5, 6, 7 and 8, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, witnessed by 4 pits, NE., SE., SW. and NW. of the cor., with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">6</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 5</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; height: 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">7</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 8</td> </tr> <tr> <td colspan="3" style="padding: 0 5px;">PLS 538</td> </tr> <tr> <td colspan="3" style="padding: 0 5px;">2001</td> </tr> </table> </div> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89° 04' W., bet. secs. 5 and 8.</p> <p>Over rolling to broken terrain.</p>	T55N	R75W		S	6	S 5				S	7	S 8	PLS 538			2001		
T55N	R75W																		
S	6	S 5																	
S	7	S 8																	
PLS 538																			
2001																			
40.65	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">R75W</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 5px;"></td> <td></td> </tr> <tr> <td></td> <td></td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td colspan="3" style="padding: 0 5px;">2001</td> </tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p>	T55N	R75W				S 5	1/4					S 8	2001					
T55N	R75W																		
		S 5																	
1/4																			
		S 8																	
2001																			
51.60	Spotted Horse Creek, course NW.																		
56.30	Improved road, bears SE. and NW.																		
60.975	Point for the W. 1/16 sec. cor. of secs. 5 and 8, falls on steep E. slope of spur, slopes SE.																		

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T55N R75W S 5 W1/16 ——— S 8 2001</p>
81.30	<p>Set a steel fence post alongside the stainless steel post.</p> <p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>S. 89° 00' W., bet. secs. 6 and 7.</p> <p>Over rolling terrain.</p>
20.39	<p>Point for the E. 1/16 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T55N R75W S 6 E1/16 ——— S 7 2001</p>
40.78	<p>Set a steel fence post alongside the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 6 and 7, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, in a collar of stone, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <p style="text-align: center;">T55N R75W S 6 1/4 ——— S 7 PLS 2001</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located N. 29° 54' W., 2.50 chs. dist., from cor. of abandoned fences extending E. and S.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>S. 89° 00' W., beginning new measurement.</p> <p>Over rolling to broken terrain.</p>
38.49	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 55 N., R. 76 W.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0° 06' W., bet. secs. 5 and 6.</p> <p>Over mountainous terrain.</p>
20.03	<p>Point for the S. 1/16 sec. cor. of secs. 5 and 6, falls on steep NE. slope of ridge, bears SE. and NW.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T55N R75W S1/16 S 6 S 5 2001 </div> <p>Set a steel fence post alongside the stainless steel post.</p>
35.70	<p>Improved road, bears SSE. and NNW.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 55 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T55N R75W 1/4 S 6 S 5 2001</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>47.40 Spotted Horse Creek, course SW.</p> <p>79.74 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area embraced by this survey is situated in the northwestern portion of Campbell County, in the immediate vicinity of Spotted Horse, Wyoming. The terrain varies from gently rolling to mountainous, with the elevation ranging from about 3,730 feet above sea level, where Spotted Horse Creek crosses the north boundary, to about 4,480 feet above sea level near the head of South Prong Spotted Horse Creek, in the southwest portion of the township. The soil varies from gravelly loam to rocky clay with areas of exposed scoria. Vegetation consists of a light to moderate growth of sagebrush and native grasses throughout with scattered areas of pine and juniper in the higher elevations and occasional small stands of cottonwood along the drainages.</p> <p>Primary drainage is provided by Spotted Horse Creek, which courses northwesterly through the entire township, with tributaries draining the eastern portion. South Prong Spotted Horse Creek drains the western portion. The Drake Ranch is located in section 32, the area being suitable for grazing purposes. Methane gas exploration and development is currently in progress.</p> <p>Access to the township is provided by U.S. Highway Nos. 14 and 16, which crosses the southern portion of the township with county roads and trail roads leading north and south; namely Werner Road, which follows along a portion of the east boundary, by S A Road, which runs northerly through the central portion and by Broyles Road, which connects the two in the northern portion of the township. Improved oil field roads and trail roads lead from the main roads to most areas of the township.</p>
--------	---

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
Gerald W. Geer	Surveying Technician
Tyrel F. Hoon	Surveying Aid
Trudy Ann Wadley	Surveying Aid

CERTIFICATE OF SURVEY

I, Richard A. Kohler, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day of February, 2001, I have dependently resurveyed the east and north boundaries and the subdivisional lines, Township 55 North, Range 75 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

SEP 24 2004

(Date)

Richard A. Kohler
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of the east and north boundaries and the subdivisional lines, Township 55 North, Range 75 West, Sixth Principal Meridian, Wyoming, executed by Richard A. Kohler, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

SEP 24 2004

(Date)

John P. Lee
(Signature of Authorized Officer)