

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE FOURTEENTH STANDARD PARALLEL NORTH,

THROUGH RANGE 75 WEST,

THE EAST BOUNDARY

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 56 NORTH, RANGE 75 WEST,

OF THE SIXTH PRINCIPAL MERIDIAN,

IN THE STATE OF WYOMING.

EXECUTED BY

RICHARD A. KOHLER

CADASTRAL SURVEYOR

Under Special Instructions dated FEBRUARY 22, 2001, approved FEBRUARY 22, 2001, which provided for the surveys included under Group Number 685, and assignment instructions dated FEBRUARY 22, 2001.

Survey commenced MAY 28, 2002

Survey completed AUGUST 29, 2002

INDEX DIAGRAM

Township 56 North, Range 75 West

<i>FOURTEENTH</i>		<i>STANDARD</i>		<i>PARALLEL</i>		<i>NORTH</i>	
10	9	7	6	4	3		2
6	77 5	62 4	50 3	39 2	29 1		17
76	76	61	49	39	28		
7	74 8	59 9	48 10	37 11	27 12		16
73	73	59	48	37	26		
18	71 17	57 16	47 15	35 14	25 13		15
71	70	57	46	35	24		
19	69 20	55 21	45 22	34 23	23 24		14
68	67	54	44	33	22		
30	66 29	54 28	43 27	32 26	21 25		12
65	64	53	42	32	20		
31	63 32	52 33	41 34	31 35	19 36		11

T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>The following field notes are those of the dependent resurvey of the Fourteenth Standard Parallel North, through Range 75 West, the east boundary and the subdivisional lines, Township 56 North, Range 75 West, Sixth Principal Meridian, Wyoming.</p> <p>The history of surveys pertaining to this resurvey is as follows:</p> <p>Mortimer N. Grant surveyed a portion of the Fourteenth Standard Parallel North (north boundary) and the east boundary in 1883. Charles Holcomb retraced a portion of the north boundary and the east boundary and surveyed the remainder of the north boundary, the south and west boundaries and the subdivisional lines in 1883. William H. Clark dependently resurveyed the north boundary in 1917. Arthur D. Davis and Mark D. King independently resurveyed the subdivisional lines of T. 57 N., R. 75 W., and established closing corners on the north boundary in 1917. Mark L. Bush and Bruce M. Mortimer dependently resurveyed the west boundary in 1988-89. Richard A. Kohler dependently resurveyed the south boundary during the dependent resurvey of T. 55 N., R. 75 W., executed concurrently under this same group.</p> <p>Several private surveys have been conducted in the area and the acceptance of such surveys is detailed herein.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 685, Wyoming, dated February 22, 2001.</p> <p>Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data were thoroughly verified and only true line field notes are given herein, which refer to the completed survey.</p> <p>The survey was executed with TRIMBLE Model 4700 Global Positioning System (GPS) receivers, a LIETZ Model SET4 electronic total station and by chaining methods. The instruments were maintained in proper adjustment at all times. The directions of all lines refer to the true meridian, as determined by GPS observations. GPS control network and supporting data are contained in the official group file.</p> <p>The geographic position of the southeast corner of the township, based on NAD 83 (1993) and determined by GPS methods, is:</p>
--------	---

T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Latitude 44° 46' 51.248" N., Longitude 105° 49' 16.210" W.</p> <p>The mean magnetic declination is 11½° E.</p> <hr/> <p>Dependent Resurvey, Fourteenth Standard Parallel North, through Range 75 West, T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>(Restoring the retracement and restoration executed by William H. Clark in 1917)</p> <hr/> <p>Beginning at the angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 31, T. 57 N., R. 74 W., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T57N R74W AP</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1917</p> <p>S. 89° 54' W., on the S. bdy. of sec. 31.</p> <p>Over mountainous terrain.</p> <p>3.67 From this point, the closing cor. of Tps. 57 N., Rs. 74 and 75 W., bears NORTH, 0.017 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above the ground, at intersection of abandoned fences extending N., E. and SSE., with brass cap incorrectly mkd. T57N R74W R75W CC S31 S36 T56N R75W S1 1917. Change the mks. to read</p> <p style="text-align: center;">T57N R75W R74W CC S 36 S 31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S6 T56N R74W 1917 2002</p> <p>10.90 Wash, drains NW.</p>
--------	---

Dependent Resurvey, Fourteenth Standard Parallel North,
through Range 75 West,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
16.88	The closing cor. of Tps. 56 N., Rs. 74 and 75 W., hereinafter described.
21.10	Ridge, bears SSE. and NNW.
40.02	The angle point marking the restored position of the original standard cor. of Tps. 57 N., Rs. 74 and 75 W., identical with Cor. No. 2, Tract 40, T. 57 N., R. 75 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above the ground, with a mound of stone, 3 ft. base, 1½ ft. high, N. of the cor., as filed in the Campbell County Clerk's Office, with brass cap mkd.
	R75W R74W T57N AP <hr style="width: 20%; margin: auto;"/> 1917
	S. 89° 57' W., on line 2-3, Tract 40, T. 57 N., R. 75 W.
	Over mountainous terrain.
16.855	Point for the 1/4 sec. cor. of sec. 1 only, T. 56 N., R. 75 W., hereinafter described.
40.08	The angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 36, T. 57 N., R. 75 W., monumented with the lower portion of an iron post, 28 ins. long, 1 in. diam., badly bent but firmly set 2 ins. below the surface of the ground, on E. shoulder of oil field road extending NE. and SW., upper portion with brass cap not recovered.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. below the scoria surface of the road, with brass cap mkd.
	T57N R75W AP <hr style="width: 20%; margin: auto;"/> 2002
	from which
	A drill hole, ¼ in. diam., in top of SE. end of oil field road culvert, a corrugated metal pipe, 30 ft. long, 18 ins. diam., extending SE. and NW., bears N. 49° 51' E., 2.49 chs. dist.

Dependent Resurvey, Fourteenth Standard Parallel North,
through Range 75 West,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Cor. is located 15 lks. S. of pipeline scar extending ENE. and WSW.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. 89° 58' W., beginning new measurement.</p>
3.85	<p>The closing cor. of secs. 35 and 36, T. 57 N., R. 75 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with a mound of stone, 2 ft. base, 1 ft. high, N. of the cor., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>CC T57N R75W S 35 S 36</p> <hr style="width: 50%; margin: 0 auto;"/> <p>1917</p> </div>
16.77	<p>Point for the closing cor. of secs. 1 and 2, T. 56 N., R. 75 W., hereinafter described.</p>
40.06	<p>The angle point marking the restored position of the original standard cor. of secs. 35 and 36, identical with Cor. No. 3, Tract 40 and Cor. No. 2, Tract 41, T. 57 N., R. 75 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor., as filed in the Campbell County Clerk's Office, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T57N R75W TR41 TR40 2 3</p> <hr style="width: 50%; margin: 0 auto;"/> <p>AP 1917</p> </div>
	<p>S. 89° 55' W., on line 2-3, Tract 41, T. 57 N., R. 75 W.</p> <p>Over rolling terrain.</p>
8.80	<p>S A Creek, course NW.</p>
16.84	<p>Point for the 1/4 sec. cor. of sec. 2 only, T. 56 N., R. 75 W., hereinafter described.</p>
20.06	<p>Cor. No. 3, Tract 41 and Cor. No. 2, Tract 42, T. 57 N., R. 75 W., monumented with an iron post, 36 ins. long, 1 in. diam., badly bent but firmly set 24 ins. in the ground, with brass cap mkd. TR 42 2 TR41 3 1917.</p>

Dependent Resurvey, Fourteenth Standard Parallel North,
through Range 75 West,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS															
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T57N</td><td>R75W</td></tr> <tr><td>TR42</td><td>TR41</td></tr> <tr><td>2</td><td>3</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S</td><td>2</td></tr> <tr><td>T56N</td><td></td></tr> <tr><td>2002</td><td></td></tr> </table> </div> <p>Bury the 1917 monument and set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 80 lks. E. of improved road extending SE. and NW.</p> <hr/> <p>WEST, on line 2-3, Tract 42, T. 57 N., R 75 W.</p> <p>Over mountainous terrain.</p>	T57N	R75W	TR42	TR41	2	3	<hr/>		S	2	T56N		2002	
T57N	R75W														
TR42	TR41														
2	3														
<hr/>															
S	2														
T56N															
2002															
13.00	Ridge, bears SSE. and NNW.														
20.01	<p>The angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 35, identical with Cor. No. 3, Tract 42, T. 57 N., R 75 W., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, in a scattered mound of stone, as filed in the Campbell County Clerk's Office, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T57N</td><td></td></tr> <tr><td>R75W</td><td></td></tr> <tr><td></td><td>TR42</td></tr> <tr><td>AP</td><td>3</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>1917</td><td></td></tr> </table> </div> <p>Rebuild the mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p> <hr/> <p>S. 89° 58' W., on the S. bdy. of sec. 35.</p> <p>Over rolling terrain.</p>	T57N		R75W			TR42	AP	3	<hr/>		1917			
T57N															
R75W															
	TR42														
AP	3														
<hr/>															
1917															

Dependent Resurvey, Fourteenth Standard Parallel North,
through Range 75 West,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
3.72	<p>The closing cor. of secs. 34 and 35, T. 57 N., R. 75 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor., as filed in the Campbell County Clerk's Office, with brass cap mkd.</p> <div style="text-align: center;"> <p>CC T57N R75W S 34 S 35</p> <hr style="width: 50%; margin: auto;"/> <p>1917</p> </div>
16.30	Wash, drains NW.
16.90	The closing cor. of secs. 2 and 3, T. 56 N., R. 75 W., hereinafter described.
18.80	Wash, drains NNE.
24.90	Top of sharp knob, bears N. and S.
37.10	Wash, drains NNE.
40.03	<p>The angle point marking the restored position of the original standard cor. of secs. 34 and 35, T. 57 N., R. 75 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with a mound of stone, 2 ft. base, 1 ft. high, N. of the cor., with brass cap mkd.</p> <div style="text-align: center;"> <p>T57N R75W AP</p> <hr style="width: 50%; margin: auto;"/> <p>1917</p> </div> <hr style="border: 0.5px solid black;"/> <p>N. 87° 58' W., on the S. bdy. of sec. 34.</p> <p>Over rolling terrain.</p>
19.45	Point for the 1/4 sec. cor. of sec. 3 only, T. 56 N., R. 75 W., hereinafter described.
43.52	The closing cor. of secs. 33 and 34, T. 57 N., R. 75 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with an embedded mound of stone N. of the cor., with brass cap mkd.

Dependent Resurvey, Fourteenth Standard Parallel North,
through Range 75 West,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T57N R75W CC S 33 S 34 <hr style="width: 50%; margin: auto;"/> 1917
	Rebuild the mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.
43.80	The angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 34, T. 57 N., R. 75 W., monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above the ground, in an embedded mound of stone, with brass cap mkd.
	T57N R75W AP <hr style="width: 50%; margin: auto;"/> 1917
	Rebuild the mound of stone, 2 ft. base, 1 ft. high, N. of the cor.
	N. 87° 55' W., on the S. bdy. of sec. 33.
	Over rolling to broken terrain.
2.20	Wash, drains NNW.
3.40	Low spur, slopes N.
4.60	Wash, drains NNE.
18.25	Point for the closing cor. of secs. 3 and 4, T. 56 N., R. 75 W., hereinafter described.
43.69	The angle point marking the restored position of the original standard cor. of secs. 33 and 34, T. 57 N., R. 75 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.
	T57N R75W AP <hr style="width: 50%; margin: auto;"/> 1917
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.

Dependent Resurvey, Fourteenth Standard Parallel North,
through Range 75 West,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
	N. 87° 54' W., on the S. bdy. of sec. 33.										
	Over mountainous terrain.										
4.20	Wash, drains NNE.										
18.28	Point for the 1/4 sec. cor. of sec. 4 only, T. 56 N., R. 75 W., hereinafter described.										
26.10	Improved road, bears NE. and SW.										
36.31	From this point, the closing cor. of secs. 32 and 33, T. 57 N., R. 75 W., bears SOUTH, 0.022 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, in a collar of stone, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T57N</td><td>R75W</td></tr> <tr><td>CC</td><td></td></tr> <tr><td>S 32</td><td> S 33</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2" style="text-align: center;">1917</td></tr> </table>	T57N	R75W	CC		S 32	S 33			1917	
T57N	R75W										
CC											
S 32	S 33										
1917											
40.14	Point for the W. 1/16 sec. cor. of sec. 4 only, hereinafter described.										
43.77	The angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 33, T. 57 N., R. 75 W., monumented with the lower portion of an iron post, 20 ins. long, 1 in. diam., firmly set 5 ins. below the surface of the ground, upper portion with brass cap mkd. T57N R75W AP 1917 found 3 ins. below the surface of the ground nearby, with a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.										
	At the corner point										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T57N</td><td>R75W</td></tr> <tr><td>AP</td><td></td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2" style="text-align: center;">2002</td></tr> </table>	T57N	R75W	AP				2002			
T57N	R75W										
AP											
2002											
	Deposit the 1917 monument inside the stainless steel post and rebuild the mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.										

Dependent Resurvey, Fourteenth Standard Parallel North,
through Range 75 West,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 87° 44' W., on the S. bdy. of sec. 32. Over rolling to broken terrain.
18.23	Point for the closing cor. of secs. 4 and 5, T. 56 N., R. 75 W., hereinafter described.
43.73	The angle point marking the restored position of the original standard cor. of secs. 32 and 33, T. 57 N., R. 75 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with a mound of stone, 2 ft. base, 1 ft high, N. of the cor., with brass cap mkd. <div style="text-align: center;">T57N R75W AP <hr style="width: 20%; margin: auto;"/>1917</div>
	S. 88° 54' W., on the S. bdy. of sec. 32. Over rolling to mountainous terrain.
15.71	Point for the 1/4 sec. cor. of sec. 5 only, T. 56 N., R. 75 W., hereinafter described.
28.82	From this point, the closing cor. of secs. 31 and 32, T. 57 N., R. 75 W., bears SOUTH, 0.271 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, in abandoned fence extending E. and W., with brass cap mkd. <div style="text-align: center;">T57N R75W CC S 31 S 32 <hr style="width: 20%; margin: auto;"/>1917</div>
39.93	The angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 32, identical with Cor. No. 2, Tract 37, T. 57 N., R. 75 W., monumented with an iron post, 1 in. diam., firmly set 2 ins. below the surface of the ground, with brass cap mkd.

Dependent Resurvey, Fourteenth Standard Parallel North,
through Range 75 West,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">TR</td> <td style="padding: 2px;">T57N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">37</td> <td style="padding: 2px;">R75W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">2</td> <td style="padding: 2px;">AP</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center; padding: 2px;">1917</td> </tr> </table> <p>Encircle the iron post with a collar of stone and set a steel fence post alongside.</p> <hr/> <p>N. 89° 50' W., on line 2-3, Tract 37, T. 57 N., R. 75 W.</p> <p>Over rolling to broken terrain.</p> <p>11.60 L X Bar Creek, course NW.</p> <p>16.99 Point for the closing cor. of secs. 5 and 6, T. 56 N., R. 75 W., hereinafter described.</p> <p>40.23 The angle point marking the restored position of the original standard cor. of secs. 31 and 32, identical with Cor. No. 3, Tract 37, T. 57 N., R. 75 W., determined from the accessory to the cor., an embedded mound of stone N. of the cor., the 1917 monument found lying loose alongside. Reset the monument, an iron post, 36 ins. long, 2 ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">T57N</td> <td style="padding: 2px;">R75W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">TR 37</td> <td style="padding: 2px;">3 AP</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center; padding: 2px;">1917</td> </tr> </table> <p>Set a steel fence post alongside the iron post and rebuild the mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p> <hr/> <p>N. 89° 56' W., on the S. bdy. of sec. 31.</p> <p>Over rolling to broken terrain.</p> <p>16.88 Point for the 1/4 sec. cor. of sec. 6 only, T. 56 N., R. 75 W., hereinafter described.</p>	TR	T57N	37	R75W	2	AP	1917		T57N	R75W	TR 37	3 AP	1917	
TR	T57N														
37	R75W														
2	AP														
1917															
T57N	R75W														
TR 37	3 AP														
1917															

Dependent Resurvey, Fourteenth Standard Parallel North,
through Range 75 West,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS 28.72	<p>From this point, the closing cor. of Tps. 57 N., Rs. 75 and 76 W., bears SOUTH, 0.034 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above the ground, with an embedded mound of stone N. of the cor., with brass cap mkd.</p> <div style="text-align: center;"> <p>T57N R76W R75W CC S 36 S 31 ----- 1917</p> </div> <p>Rebuild the mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p>
40.06	<p>The angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 31, T. 57 N., R. 75 W., monumented with an iron post, 1 in. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 56 N., R. 76 W.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N. of the cor.</p> <p>From this point, the closing cor. of Tps. 56 N., Rs. 75 and 76 W., bears N. 89° 55' W., 14.30 chs. dist., monumented with an iron post, 2½ ins. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 56 N., R. 76 W.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the East Boundary, T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Mortimer N. Grant in 1883)</p> <hr/> <p>From the cor. of Tps. 55 and 56 N., Rs. 74 and 75 W., monumented with an iron post, 3 ins. diam., as described in the field notes of the dependent resurvey, T. 55 N., R. 75 W., executed concurrently under this same group.</p> <p>N. 0° 27' W., bet. secs. 31 and 36.</p> <p>Over rolling to broken terrain, along fence.</p>
40.43	<p>The 1/4 sec. cor. of secs. 31 and 36, at intersection of fences extending N., E. and W. This position is accepted as the best available evidence of the original cor. position.</p>

Dependent Resurvey of the East Boundary,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T56N R75W R74W 1/4 S 36 S 31 2002</p> <p>Cor. is located on ridge, bears SE. and NW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 34' E., beginning new measurement.</p> <p>Over rolling to broken terrain, along fence.</p>
39.78	<p>The cor. of secs. 25, 30, 31 and 36, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, at cor. of fences extending E. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <p style="text-align: center;">T56N R75W R74W S 25 S 30 ----- S 36 S 31 PLS 538 2000</p> <p>This position is accepted as the best available evidence of the original cor. position.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 07' E., bet. secs. 25 and 30.</p> <p>Over rolling to broken terrain.</p>
12.00	<p>Ridge, bears SE. and NW.</p>

Dependent Resurvey of the East Boundary,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.46	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented by Donald F. Brady, Wyoming Registered Land Surveyor No. 5655, with an aluminum post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, in a mound of stone, 3 ft. base, 1 ft. high, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed LAND SURVEYING INC. and mkd.</p> <p style="text-align: center;">T56N R75W R74W 1/4 S 25 S 30 PLS 5655 2001</p> <p>This position is accepted as the best available evidence of the original cor. position. Set a steel fence post alongside the aluminum post.</p> <p>Cor. is located 80 lks. S. of wash, drains NNE.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 14' E., beginning new measurement.</p> <p>Over rolling to broken terrain.</p>
11.00	Wash, drains NW.
25.00	Spur, slopes W.
35.50	Wash, drains SW.
39.98	<p>The cor. of secs. 19, 24, 25 and 30, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, in an embedded mound of stone, no mkd. stone found, at cor. of abandoned fences extending N. and W., with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <p style="text-align: center;">T56N R75W R74W S 24 S 19 ----- S 25 S 30 PLS 538 1988</p>

Dependent Resurvey of the East Boundary,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>This position is accepted as the best available evidence of the original cor. position. Rebuild the mound of stone, 2 ft. diam., 1 ft. high, W. of the cor.</p> <hr/> <p>N. 0° 09' W., bet. secs. 19 and 24.</p> <p>Over rolling to broken terrain, along abandoned fence.</p> <p>20.00 Improved road, on ridge, bears SE. and NW.</p> <p>32.90 Wash, drains NW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 19 and 24, determined latitudinally by proportionate measurement and longitudinally by abandoned fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W R74W 1/4 S 24 S 19 2002</p> <hr/> </div> <p>N. 0° 07' E., beginning new measurement.</p> <p>Over mountainous terrain, along abandoned fence.</p> <p>9.10 Leave fence, bears NW.</p> <p>9.50 Ridge, bears SE. and NW.</p> <p>15.00 Wash, drains WNW.</p> <p>25.80 Ridge, bears SE. and NW.</p> <p>31.70 Wash, drains NW.</p> <p>40.00 Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the East Boundary,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<div style="text-align: center;"> <p>T56N R75W R74W S 13 S 18 ----- S 24 S 19 2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 76° E., 118 lks. dist., mkd T56N R74W S19 BT</p> <p style="padding-left: 40px;">A twin pine, 10 ins. diam., bears S. 6° W., 109 lks. dist., mkd. T56N R75W S24 BT</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0° 07' E., bet. secs. 13 and 18.</p> <p>Over mountainous terrain.</p> <p>4.80 Ridge, bears SE. and NW.</p> <p>16.10 Wash, drains NW.</p> <p>23.00 Spur, slopes NW.</p> <p>27.50 Wash, drains NW.</p> <p>31.50 Spur, slopes WNW.</p> <p>33.50 Wash, drains WNW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W R74W 1/4 S 13 S 18 2002</p> </div>
--------	--

Dependent Resurvey of the East Boundary,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 30 lks. S. of spur, slopes NW.</p> <p>46.80 Wash, drains WNW.</p> <p>52.20 Spur, slopes NW.</p> <p>68.80 Wash, drains NW.</p> <p>80.00 Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T56N</td></tr> <tr><td>R75W</td><td>R74W</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2">2002</td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0° 07' E., bet. secs. 7 and 12.</p> <p>Over rolling terrain.</p> <p>22.40 Improved road, bears SE. and NW.</p> <p>34.00 Enter bottom land.</p> <p>39.30 S A Creek (new channel), course NNW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T56N		R75W	R74W	S 12	S 7	<hr style="width: 50%; margin: 0 auto;"/>		S 13	S 18	2002	
T56N													
R75W	R74W												
S 12	S 7												
<hr style="width: 50%; margin: 0 auto;"/>													
S 13	S 18												
2002													

Dependent Resurvey of the East Boundary,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T56N R75W R74W 1/4 S 12 S 7 2002
	Set a steel fence post alongside the stainless steel post.
56.20	Leave bottom land.
67.80	Wash, drains SW.
80.00	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W R74W S 1 S 6 ———— S 12 S 7 2002
	Set a steel fence post alongside the stainless steel post.
	From this point, a position established by Duane A. Wamre, Wyoming Registered Land Surveyor No. 5149, bears S. 10° 59' E., 2.29 chs. dist., monumented with a steel reinforcement rod, ½ in. diam., firmly set, projecting 4 ins. above the ground, with a broken sandstone, 13x12x8 ins., loosely set alongside, no mks. visible, and a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed KADRMAS, LEE & JACKSON, no other mks. Based on information contained in the 1917 field notes of the restoration of the Fourteenth Standard Parallel North through Ranges 73, 74, 75 and 76 West, and the position of controlling corners south, this position is not accepted as the best available evidence of the original cor. position.
	N. 0° 07' E., bet. secs. 1 and 6.
	Over mountainous terrain.
31.80	Wash, drains WNW.

Dependent Resurvey of the East Boundary,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T56N R75W R74W 1/4 S 1 S 6 2002</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this point, a position established by Duane A. Wamre, Wyoming Registered Land Surveyor No. 5149, bears S. 11° 01' E., 1.18 chs. dist., monumented with a steel reinforcement rod, ½ in. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed KADRMAS LEE & JACKSON, no other mks. This position was based upon erroneous position of controlling corner south and is not utilized during the course of this resurvey.</p>
40.80	Wash, drains SW.
60.00	<p>Point for the N. 1/16 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T56N R75W R74W N1/16 S 1 S 6 2002</p> <p>Set a steel fence post alongside the stainless steel post.</p>
63.00	Ridge, bears SE. and NW.
81.39	<p>The closing cor. of Tps. 56 N., Rs. 74 and 75 W., monumented with a sandstone, 22x14x2 ins., firmly set 11 ins. in the ground, plainly mkd. 6 grooves on E., S. and W. faces, and dimly mkd. CC on S. face, with a steel reinforcement rod, 18 ins. long, ½ in. diam., firmly set alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed KADRMAS LEE & JACKSON, no other mks., with a mound of stone, 3 ft. diam., 2 ft. high, S. of the cor.</p>

Dependent Resurvey of the East Boundary,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T57N R75W</td></tr> <tr><td colspan="2">S 36</td></tr> <tr><td colspan="2"><hr style="width: 100%;"/></td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td style="text-align: center;">R75W</td><td style="text-align: center;">R74W</td></tr> <tr><td colspan="2" style="text-align: center;">T56N</td></tr> <tr><td colspan="2" style="text-align: center;">CC</td></tr> <tr><td colspan="2" style="text-align: center;">2002</td></tr> </table> </div> <p>Deposit the steel reinforcement rod inside, bury the original cor. stone and set a steel fence post alongside the stainless steel post.</p> <p>From this point, the angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 31, T. 57 N., R 74 W., bears N. 89° 54' E., 16.88 chs. dist.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p style="text-align: center;">Dependent Resurvey of the Subdivisional Lines, T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p style="text-align: center;">(Restoring the survey executed by Charles Holcomb in 1883)</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the 2001-02 field notes of the dependent resurvey, T. 55 N., R. 75 W.</p> <p>N. 0° 57' E., bet. secs. 35 and 36.</p> <p>Over mountainous terrain.</p> <p>4.50 Wash, drains E.</p> <p>39.73 Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>	T57N R75W		S 36		<hr style="width: 100%;"/>		S 1	S 6	R75W	R74W	T56N		CC		2002	
T57N R75W																	
S 36																	
<hr style="width: 100%;"/>																	
S 1	S 6																
R75W	R74W																
T56N																	
CC																	
2002																	

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T56N R75W 1/4 S 35 S 36 2002
	from which A pine, 8 ins. diam., bears S. 32° E., 18 lks. dist., mkd. 1/4 S36 BT. A pine, 8 ins. diam., bears N. 30° W., 8 lks. dist., mkd. 1/4 S35 BT. Set a steel fence post alongside the stainless steel post.
79.46	The cor. of secs. 25, 26, 35 and 36, at angle point in abandoned fence extending irregularly E. and W., with evidence of use by other surveyors; this position is accepted as the best available evidence of the original cor. position. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W S 26 S 25 ----- S 35 S 36 2002
	Cor. is located 80 lks. W. of fence extending irregularly N. and S.
	<hr/> From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp. S. 88° 20' W., bet. secs. 25 and 36. Over rolling to broken terrain.
12.50	Wash, drains SSW.
22.80	Cor. of abandoned fences extending ESE. and W., on spur, slopes S.; thence along abandoned fence.
39.17	The 1/4 sec. cor. of secs. 25 and 36, at intersection of abandoned fences extending N., E. and W. This position is accepted as the best available evidence of the original cor. position.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T56N R75W S 25 1/4 ——— S 36 2002
	Set a steel fence post alongside the stainless steel post.
	—————
	S. 89° 54' W., beginning new measurement.
	Over rolling terrain.
3.10	Improved road, bears SSE. and NNW.
18.00	L X Bar Creek, course NNE.
24.70	L X Bar Creek, course SW.
28.40	L X Bar Creek, course NW.
40.21	The cor. of secs. 25, 26, 35 and 36.
	—————
	N. 0° 46' W., bet. secs. 25 and 26.
	Over rolling to broken terrain.
14.40	L X Bar Creek, course NW.
25.20	Improved road, bears ESE. and WNW.
40.08	Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T56N R75W 1/4 S 26 S 25 2002</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located on spur, slopes W.</p>
54.10	Improved road, bears NE. and SW.
56.30	Wash, drains SW.
80.16	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R75W S 23 S 24 ----- S 26 S 25 2002</p> <p>Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.</p> <p>N. 89° 28' W., bet. secs. 24 and 25.</p> <p>Over rolling to broken terrain, along abandoned fence.</p>
29.20	Improved road, bears SSE. and NNW.
39.91	The 1/4 sec. cor. of secs. 24 and 25, at projected intersection of abandoned fences from the E. and S., falls on W. side of wash, drains SW.; there is no remaining evidence of the original monument.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T56N R75W S 24 1/4 ——— S 25 2002
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 90 lks. W. of intersection of abandoned fences extending E., SSW. and NNW.

	S. 88° 47' W., beginning new measurement.
	Over rolling to broken terrain.
19.60	Wash, drains SSW.
40.76	The cor. of secs. 23, 24, 25 and 26.

	N. 1° 25' W., bet. secs. 23 and 24.
	Over rolling to broken terrain.
29.10	Wash, drains WSW.
40.09	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W 1/4 S 23 S 24 2002
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 50 lks. S. of small wash, drains WSW.
46.80	Trail road, bears SE. and NW.; thence across cultivated field.
68.00	Improved oil field road, on ridge, bears SE. and NW.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>80.18 Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T56N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td style="padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 23</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 24</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">2002</td> </tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>S. 89° 46' W., bet. secs. 13 and 24.</p> <p>Over mountainous terrain.</p> <p>7.50 Wash, drains NW.</p> <p>15.80 Spur, slopes NNW.</p> <p>25.20 Wash, drains NW.</p> <p>32.70 Spur, slopes N.</p> <p>39.00 Wash, drains NNE.</p> <p>42.68 Point for the 1/4 sec. cor. of secs. 13 and 24, determined latitudinally by proportionate measurement and longitudinally by abandoned fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T56N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td style="padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td style="padding: 0 5px;">S 24</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">2002</td> </tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="border: 0.5px solid black;"/>	T56N	R75W	S 14	S 13	S 23	S 24	2002		T56N	R75W	S 13	—	1/4	—	S 24	—	2002	
T56N	R75W																		
S 14	S 13																		
S 23	S 24																		
2002																			
T56N	R75W																		
S 13	—																		
1/4	—																		
S 24	—																		
2002																			

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	S. 89° 46' W., beginning new measurement.
	Over rolling to broken terrain.
8.80	Spur, slopes SE.
27.70	Improved road, on curve on ridge, bears NE. and SE.
38.20	Wash, drains NNW.
39.91	The cor. of secs. 13, 14, 23 and 24.
	N. 1° 47' E., bet. secs. 13 and 14.
	Over rolling to broken terrain.
7.20	Wash, drains NNW.
19.50	Spur, slopes NNW.
28.30	Wash, drains NNE.
40.095	Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T56N R75W 1/4 S 14 S 13 2002</p>
	from which
	<p style="text-align: center;">A pine, 8 ins. diam., bears N. 6° E., 18 lks. dist., mkd. 1/4 S13 BT.</p>
	<p style="text-align: center;">A pine, 8 ins. diam., bears S. 60° W., 38 lks. dist., mkd. 1/4 S14 BT.</p>
	Set a steel fence post alongside the stainless steel post.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
41.00	Spur, slopes SE.										
51.20	Wash, drains NNW.										
80.19	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original cor. position. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T56N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 11</td> <td style="padding: 0 5px;">S 12</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">2002</td> </tr> </table> </div> from which <div style="text-align: center;"> A pine, 16 ins. diam., bears N. 60° W., 16 lks. dist., mkd. T56N R75W S11 BT </div>	T56N	R75W	S 11	S 12	S 14	S 13	2002			
T56N	R75W										
S 11	S 12										
S 14	S 13										
2002											
	<hr/> From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp. S. 89° 53' W., bet. secs. 12 and 13. Over mountainous terrain.										
5.40	Stock pond in draw (dry), drains N.										
40.115	Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance, falls on steep S. slope of spur, slopes WSW.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T56N</td> <td style="padding: 0 5px;">R75W</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 12</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">2002</td> </tr> </table> </div> Set a steel fence post alongside the stainless steel post.	T56N	R75W		S 12	1/4			S 13	2002	
T56N	R75W										
	S 12										
1/4											
	S 13										
2002											

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
41.00	Abandoned fence, on ridge, bears NE. and SW.
48.40	Sharp spur, slopes NW.
80.23	The cor. of secs. 11, 12, 13 and 14.
	<hr/> N. 0° 06' E., bet. secs. 11 and 12. Over rolling to broken terrain.
1.60	Wash, drains WNW.
7.50	Spur, slopes W.
21.20	Wash, drains NNE.
40.075	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center; margin: 10px 0;"> T56N R75W 1/4 S 11 S 12 2002 </div> Set a steel fence post alongside the stainless steel post. Cor. is located at head of small wash, drains SE.
80.15	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center; margin: 10px 0;"> T56N R75W S 2 S 1 <hr style="width: 50%; margin: 0 auto;"/> S 11 S 12 2002 </div> Set a steel fence post alongside the stainless steel post. <hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>WEST, bet. secs. 1 and 12.</p> <p>Over rolling terrain.</p>
20.057	<p>Point for the E. 1/16 sec. cor. of secs. 1 and 12, falls on S. side of oil field road extending ENE. and WSW.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W S 1 E1/16 ——— S 12 2002</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 5 lks. N. of fence extending ENE. and WSW.</p>
40.115	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W S 1 1/4 ——— S 12 2002</p> </div> <p>Set two steel fence posts alongside the stainless steel post.</p> <p>Cor. is located 20 lks. W. of S A Creek, course NNE.</p>
54.60	<p>Improved road, bears ESE. and WNW., across stock dam in wash, drains NNE.</p>
80.23	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 0° 16' E., bet. secs. 1 and 2.
	Over rolling to broken terrain.
1.00	Improved oil field road, bears NE. and SW.
35.70	Improved road, bears SE. and NW.
40.08	Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance, falls in bottom land; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T56N R75W 1/4 S 2 S 1 2002
	from which
	A box elder, 6 ins. diam., bears S. 12° W., 125 lks. dist., mkd. X at breast height and BT at the base.
	A box elder, 8 ins. diam., bears S. 64° W., 86 lks. dist., mkd. 1/4 S2 BT.
	Set a steel fence post alongside the stainless steel post.
41.90	S A Creek, course WSW.
53.70	Oil field road, bears E. and W.
58.40	Wash, (new channel), drains W.
60.12	Point for the N. 1/16 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T55N R75W N1/16 S 2 S 1 2002

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS															
	Set a steel fence post alongside the stainless steel post.														
63.70	Improved oil field road, on curve, bears NE. and WSW.														
81.31	Point for the closing cor. of secs. 1 and 2, at intersection with the Fourteenth Standard Parallel North, at proportionate distance; there is no remaining evidence of the original cor.														
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T57N</td><td>R75W</td></tr> <tr><td>S</td><td>35</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S</td><td>2 S</td></tr> <tr><td>T56N</td><td>R75W</td></tr> <tr><td>C</td><td>C</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">2002</td></tr> </table>	T57N	R75W	S	35			S	2 S	T56N	R75W	C	C	2002	
T57N	R75W														
S	35														
S	2 S														
T56N	R75W														
C	C														
2002															
	Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 1½ ft. high, S. of the cor.														
	From this point, the angle point marking the restored position of the original standard ¼ sec. cor. of sec. 36, T. 57 N., R. 75 W., bears N. 89° 58' E., 16.77 chs. dist.														
	<hr/>														
	The point for the ¼ sec. cor. of sec. 1 only, T. 56 N., R. 75 W., is at midpoint on the N. bdy. of sec. 1.														
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T57N</td><td>R75W</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>1/4</td><td>S</td></tr> <tr><td>T56N</td><td>R75W</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">2002</td></tr> </table>	T57N	R75W			1/4	S	T56N	R75W	2002					
T57N	R75W														
1/4	S														
T56N	R75W														
2002															
	Set a steel fence post alongside the iron post.														
	From this point, the angle point marking the restored position of the original standard cor. of Tps. 57 N., Rs. 74 and 75 W., identical with Cor. No. 2, Tract 40, T. 57 N., R. 75 W., bears N. 89° 57' E., 16.855 chs. dist.														
	<hr/>														

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the true point for the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., as described in the field notes of the dependent resurvey, T. 55 N., R. 75 W., executed concurrently under this same group.</p> <p>N. 0° 14' E., bet. secs. 34 and 35.</p> <p>Over rolling to broken terrain.</p>
16.40	Reservoir Creek, course NNW.
29.20	Reservoir Creek, course SE.
32.20	Reservoir Creek, at bend, course NE.
40.30	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W 1/4 S 34 S 35 2002</p> </div> <p>Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p>
80.60	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W S 27 S 26 ----- S 34 S 35 2002</p> </div> <p>Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 25, 26, 35 and 36.
	S. 89° 24' W., bet. secs. 26 and 35.
	Over mountainous terrain.
21.10	Ridge, bears SSE. and NW.
41.01	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W S 26 1/4 ——— S 35 2002
	Set a steel fence post alongside the stainless steel post. Cor. is located on N. slope of small wash, drains WSW.
44.00	Wash, drains NW.
51.50	Sharp spur, slopes NW.
70.90	Reservoir Creek, course N.
82.02	The cor. of secs. 26, 27, 34 and 35.

	N. 0° 14' W., bet. secs. 26 and 27.
	Over mountainous terrain.
1.60	Wash, drains ESE.
37.10	Ridge, bears SE. and NW.
40.30	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T56N R75W 1/4 S 27 S 26 2002
	Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.
80.60	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T56N R75W S 22 S 23 ———— S 27 S 26 2002
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 30 lks. N. and 30 lks. E. of L X Bar Creek, course NW.
	From the cor. of secs. 23, 24, 25 and 26.
	S. 89° 43' W., bet. secs. 23 and 26.
	Over mountainous terrain.
14.00	Stock pond in wash, drains S.
28.20	Ridge, bears SE. and NW.
40.625	Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W S 23 1/4 ——— S 26 2002

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the stainless steel post.
51.00	Spur, slopes S.
81.25	The cor. of secs. 22, 23, 26 and 27.
	N. 0° 16' W., bet. secs. 22 and 23.
	Over rolling to broken terrain.
37.10	Wash, drains WSW.
40.30	Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W 1/4 S 22 S 23 2002
	Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ base, 1½ ft. high, S. (downhill side) of the cor.
70.60	Ridge, bears ESE. and SW.
80.60	The cor. of secs. 14, 15, 22 and 23, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, at cor. of abandoned fences extending N. and E., witnessed by 4 pits, NE., SE., SW. and NW. of the cor., with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.
	T56N R75W S 15 S 14 ———— S 22 S 23 PLS 538 2000
	This position is accepted as the best available evidence of the original cor. position.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Cor. is located 1.8 chs. S. of wash, drains W.
	From the cor. of secs. 13, 14, 23 and 24.
	N. 89° 00' W., bet. secs. 14 and 23.
	Over rolling to broken terrain.
13.60	Improved road, bears SE. and NW.
39.80	The 1/4 sec. cor. of secs. 14 and 23, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, at cor. of abandoned fences extending S. and W., witnessed by 2 pits, N. and S. of the cor., and a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor., with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.
	T56N R75W S 14 1/4 ——— S 23 PLS 538 2002
	This position is accepted as the best available evidence of the original cor. position.
	S. 89° 06' W., beginning new measurement.
	Over rolling to broken terrain, along abandoned fence.
10.00	Improved road, on ridge, bears N. and S.
39.83	The cor. of secs. 14, 15, 22 and 23.
	N. 1° 26' E., bet. secs. 14 and 15.
	Ascend over mountainous terrain, along abandoned fence.
15.20	Top of ascent; enter cultivated field, bears SE. and NW.
20.047	Point for the S. 1/16 sec. cor. of secs. 14 and 15, falls in cultivated field.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R75W S1/16 S 15 S 14 2002</p>
	<p>Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p>
31.00	<p>Leave cultivated field, bears E. and W.; descend through scattering pine and juniper.</p>
40.095	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T56N R75W 1/4 S 15 S 14 2002</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 45° W., 61 lks. dist., mkd. 1/4 S15 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 62° W., 9 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
42.10	<p>Wash, drains W.</p>
80.19	<p>The cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T56N R75W S 10 S 11 ----- S 15 S 14 2002
	Set a steel fence post alongside the stainless steel post.
	From the cor. of secs. 11, 12, 13 and 14.
	N. 89° 57' W., bet. secs. 11 and 14.
	Over mountainous terrain.
14.90	Improved oil field road, bears NE. and SW.
25.20	Wash, drains NE.
40.045	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W S 11 1/4 ----- S 14 2002
	Set a steel fence post alongside the stainless steel post.
62.80	Wash, drains SE.
76.20	Improved road, bears SSE. and NNW.
80.09	The cor. of secs. 10, 11, 14 and 15.
	N. 0° 19' W., bet. secs. 10 and 11.
	Over rolling to mountainous terrain.
6.50	Improved road, bears SE. and NW.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
38.385	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <pre> WC T56N R75W 1/4 ↑ S 10 S 11 2002 </pre> </div> <p>from which</p> <p style="text-align: center;">A pine, 12 ins. diam., bears N. 4° W., 26 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
40.085	<p>True point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance, falls on steep W. bank of narrow wash, drains NNE., where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.</p>
42.40	<p>Wash, drains SE.</p>
52.20	<p>Ridge, bears SSE. and NNW.</p>
80.17	<p>The cor. of secs. 2, 3, 10 and 11, monumented by person(s) unknown with a steel reinforcement rod, 30 ins. long, ½ in. diam., firmly set 22 ins. in the ground, in a collar of stone, as shown on oil well location plat prepared by Frank Luers, Wyoming Professional Engineer and Land Surveyor No. 487, in 1970, and obtained from the Wyoming Oil and Gas Conservation Commission. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <pre> T56N R75W S 3 S 2 ----- S 10 S 11 2002 </pre> </div>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Deposit the steel reinforcement rod inside and set a steel fence post alongside the stainless steel post.
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89° 57' W., bet. secs. 2 and 11.
	Over rolling to broken terrain.
1.80	Improved oil field road, bears NE. and SW.
39.20	Improved oil field road, bears N. and S., in wash, drains ENE.
40.325	Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance, falls on N. edge of bottom of wash, drains NE.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W S 2 1/4 ——— S 11 2002
	Set a steel fence post alongside the stainless steel post.
64.80	Spur, slopes NNW.
79.10	Wash, drains NNW.
80.65	The cor. of secs. 2, 3, 10 and 11.
	N. 0° 32' E., bet. secs. 2 and 3.
	Over rolling to broken terrain.
40.16	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance, falls on N. edge of pipeline scar extending E. and W.; there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T56N R75W 1/4 S 3 S 2 2002
	Set a steel fence post alongside the stainless steel post.
57.50	Fence, bears E. and W.
60.24	Point for the N. 1/16 sec. cor. of secs. 2 and 3.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T56N R75W N1/16 S 3 S 2 2002
	Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
81.18	The closing cor. of secs. 2 and 3, at intersection with the Fourteenth Standard Parallel North, monumented by person(s) unknown with an iron pipe, 19 ins. long, 1¼ ins. diam., firmly set 15 ins. in the ground, as shown on oil well location plat prepared by Frank Luers, Wyoming Professional Engineer and Land Surveyor No. 487, in 1970, and obtained from the Wyoming Oil and Gas Conservation Commission. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T57N R75W S 34 ----- S 3 S 2 T56N R75W C C 2002

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS

Deposit the iron pipe inside and set a steel fence post alongside the stainless steel post.

From this point, the angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 35, T. 57 N., R. 74 W., identical with Cor. No. 3, Tract 42, T. 57 N., R. 75 W., bears N. 89° 58' E., 16.90 chs. dist.

The point for the 1/4 sec. cor. of sec. 2 only, T. 56 N., R. 75 W., is at midpoint on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T57N R75W

1/4 S 2

T56N R75W

2002

Set a steel fence post alongside the stainless steel post.

From this point, Cor. No. 3, Tract 41 and Cor. No. 2, Tract 42, T. 57 N., R. 75 W., bears S. 89° 55' W., 3.22 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 55 N., R. 75 W., executed concurrently under this same group.

N. 0° 40' W., bet. secs. 33 and 34.

Over gently rolling terrain.

40.58 Point for the 1/4 sec. cor. of secs. 33 and 34, determined longitudinally by proportionate measurement and latitudinally by fence extending E. and W.; there is no remaining evidence of the original monument.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, supported by a mound of stone, 2½ ft. base, to top, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T56N R75W 1/4 S 33 S 34 2002 <hr style="width: 30%; margin: 10px auto;"/>
	N. 0° 40' W., beginning new measurement.
	Over rolling terrain.
40.09	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T56N R75W S 28 S 27 <hr style="width: 30%; margin: 5px auto;"/> S 33 S 34 2002
	Set a steel fence post alongside the stainless steel post.
	<hr style="width: 80%; margin: 10px auto;"/>
	From the cor. of secs. 26, 27, 34 and 35.
	S. 89° 09' W., bet. secs. 27 and 34.
	Over rolling terrain.
40.935	Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T56N R75W S 27 1/4 ——— S 34 2002
	Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
81.87	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0° 21' E., bet. secs. 27 and 28.</p> <p>Over rolling to broken terrain.</p>
36.40	Wash, drains WNW.
40.085	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T56N R75W 1/4 S 28 S 27 2002</p> <p>Set a steel fence post alongside the stainless steel post.</p>
46.50	Spur, slopes NW.
60.127	<p>Point for the N. 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T56N R75W N1/16 S 28 S 27 2002</p> <p>Set a steel fence post alongside the stainless steel post.</p>
64.80	Wash, drains NW.
80.17	<p>The cor. of secs. 21, 22, 27 and 28, monumented by Lawrence C. Kay, Wyoming Registered Land Surveyor No. 489, with a steel reinforcement rod, 30 ins. long, ¾ in. diam., firmly set 24 ins. in the ground, at cor. of abandoned fences extending N. and W., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed UINTAH ENG. & L S WYO 489 and mkd. T56N R75W S21 S22 S27 S28 2000. This position is accepted as the best available evidence of the original cor. position.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAIN											
	At the corner point										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T56N</td> <td>R75W</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td colspan="2" style="text-align: center;">— —</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table>	T56N	R75W	S 21	S 22	— —		S 28	S 27	2002	
T56N	R75W										
S 21	S 22										
— —											
S 28	S 27										
2002											
	Deposit the steel reinforcement rod inside the stainless steel post.										
	From the cor. of secs. 22, 23, 26 and 27.										
	S. 88° 50' W., bet. secs. 22 and 27.										
	Over mountainous terrain.										
27.60	Spur, slopes N.										
31.80	Wash, drains NNE.										
40.525	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T56N</td> <td>R75W</td> </tr> <tr> <td></td> <td>S 22</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 27</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table>	T56N	R75W		S 22	1/4	—		S 27	2002	
T56N	R75W										
	S 22										
1/4	—										
	S 27										
2002											
	Set a steel fence post alongside the stainless steel post.										
43.80	Ridge, bears N. and S.										
60.787	Point for the W. 1/16 sec. cor. of secs. 22 and 27.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base, to top, with brass cap mkd.										

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

	<p style="text-align: center;">T56N R75W S 22 W1/16 ——— S 27 2002</p>
	<p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 60 lks. W. of sharp spur, slopes NNW.</p>
81.05	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>N. 1° 07' E., bet. secs. 21 and 22.</p> <p>Over mountainous terrain, along abandoned fence.</p>
6.10	<p>Fence, bears NE. and SW.; continue along abandoned fence.</p>
10.00	<p>L S Draw, drains NNE.</p>
15.80	<p>Leave abandoned fence, bears NE.</p>
35.40	<p>Spur, slopes SE.</p>
40.28	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance, falls in bottom of wash, drains ESE.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R75W 1/4 S 21 S 22 2002</p>
	<p>Set a steel fence post alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>
45.40	<p>Ridge, bears NE. and W.</p>
80.56	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an embedded mound of stone, no mkd. stone found, at intersection of abandoned fences extending N., SSE. and W., with an old chaining pin buried in mound. This position is accepted as the best available evidence of the original cor. position.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T56N</td><td>R75W</td></tr> <tr><td>S 16</td><td>S 15</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 21</td><td>S 22</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">2002</td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post and rebuild the mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 88° 46' W., bet. secs. 15 and 22.</p> <p>Over rolling to broken terrain.</p> <p>28.20 Ridge, bears SE. and NW.</p> <p>39.545 Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T56N</td><td>R75W</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S 15</td></tr> <tr><td>1/4</td><td>_____</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S 22</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">2002</td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>48.00 Improved road, bears SSE. and NNW.</p> <p>54.10 L X Bar Creek, course NNW.</p> <p>56.80 L X Bar Creek, course ESE.</p> <p>59.00 L X Bar Creek, course NW.</p>	T56N	R75W	S 16	S 15			S 21	S 22	2002		T56N	R75W	S 15		1/4	_____	S 22		2002	
T56N	R75W																				
S 16	S 15																				
S 21	S 22																				
2002																					
T56N	R75W																				
S 15																					
1/4	_____																				
S 22																					
2002																					

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

79.09	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 0° 05' W., bet. secs. 15 and 16.</p> <p>Over rolling to broken terrain, along abandoned fence.</p>
12.30	L X Bar Creek, course WNW.
40.84	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, determined latitudinally by proportionate measurement and longitudinally by abandoned fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W 1/4 S 16 S 15 2002</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0° 41' E., beginning new measurement.</p> <p>Over rolling to broken terrain, along abandoned fence.</p>
19.20	Leave abandoned fence, bears ENE.
40.84	<p>Point for the cor. of secs. 9, 10, 15 and 16, determined latitudinally by proportionate measurement and longitudinally at projection of abandoned fence from the S.; there is no remaining evidence of the original monument.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W S 9 S 10 ----- S 16 S 15 2002</p> </div> <p>Deposit a brown glass bottle at base of stainless steel post, set a steel fence post alongside and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

40.315	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89° 52' W., bet. secs. 10 and 15.</p> <p>Over mountainous terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W</p> <p>S 10</p> <p>1/4 ———</p> <p>S 15</p> <p>2002</p> </div> <p>Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p>
50.20	Wash, drains SSW.
65.00	Spur, slopes SE.
80.63	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>N. 0° 13' W., bet. secs. 9 and 10.</p> <p>Over mountainous terrain.</p>
2.90	Wash, drains WSW.
24.80	Ridge, bears E. and W.
35.20	Wash, drains W.
40.835	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T56N R75W 1/4 S 9 S 10 2002
	Set a steel fence post alongside the stainless steel post.
46.50	Wash, drains WSW.
72.90	Top of abrupt ascent.
75.40	Improved road, bears ESE. and WNW.
81.67	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T56N R75W S 4 S 3 ———— S 9 S 10 2002
	Set a steel fence post alongside the stainless steel post.
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89° 04' W., bet. secs. 3 and 10.
	Over mountainous terrain.
15.00	Ridge, bears SSE. and NNW.
40.24	Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T56N R75W S 3 1/4 ——— S 10 2002
	Set a steel fence post alongside the stainless steel post.
	Cor. is located at E. edge of bottom of wash, drains N.
50.40	Spur, slopes N.
67.10	Wash, drains NE.
72.90	Top of abrupt ascent.
80.48	The cor. of secs. 3, 4, 9 and 10.
—————	
	N. 2° 45' W., bet. secs. 3 and 4.
	Over mountainous terrain.
13.60	Improved oil field road, bears ESE. and WNW.
33.60	Descend abruptly over steep NE. slope of ridge.
40.88	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.
	T56N R75W 1/4 S 4 S 3 2002
	Set a steel fence post alongside the stainless steel post.
42.00	Wash, drains ESE.
45.90	Spur, slopes NE.
61.32	Point for the N. 1/16 sec. cor. of secs. 3 and 4.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T56N R75W N1/16 S 4 S 3 2002</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located on N. side of small wash, drains NW.</p>
68.50	Wash, drains NE.
82.16	<p>The closing cor. of secs. 3 and 4, at intersection with the Fourteenth Standard Parallel North, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T57N R75W S 33 ----- S 4 S 3 T56N R75W C C 2002</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this point, the angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 34, T. 57 N., R. 75 W., bears S. 87° 55' E., 18.25 chs. dist.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 3 only, T. 56 N., R. 75 W., is at midpoint on the N. bdy. of sec. 3 and falls on W. edge of improved oil field road, bears NNE. and SSW.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. below the scoria surface of the road, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T57N R75W ----- 1/4 S 3 T56N R75W 2002</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 68½° E., 51.5 lks. dist., with brass cap mkd. RM T56N R75W S3 34.0 FT. TO COR. 2002 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 0¾° W., 55.4 lks. dist., with brass cap mkd. RM T57N R75W S34 36.6 FT. TO COR. 2002 and an arrow pointing to the cor.</p> <p>Set steel fence posts alongside the reference monuments.</p> <p>From this point, the angle point marking the restored position of the original standard cor. of secs. 34 and 35, T. 57 N., R. 75 W., bears S. 87° 58' E., 19.45 chs. dist.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 55 N., R. 75 W., executed concurrently under this same group.</p> <p>N. 1° 40' W., bet. secs. 32 and 33.</p> <p>Over rolling to broken terrain.</p> <p>39.625 Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R75W 1/4 S 32 S 33 2002</p>
--------	--

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor is located 40 lks. W. of fence extending irregularly N. and S.</p>										
51.70	Wash, drains W.										
79.25	<p>The cor. of secs. 28, 29, 32 and 33, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, at intersection of fences extending E., W. and irregularly S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T56N</td> <td>R75W</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> <tr> <td colspan="2">PLS 538</td> </tr> <tr> <td colspan="2">2000</td> </tr> </table> </div> <p>This position is accepted as the best available evidence of the original cor. position.</p> <p>Cor. is located on spur, slopes WSW.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 88° 08' W., bet. secs. 28 and 33.</p> <p>Over rolling terrain.</p>	T56N	R75W	S 29	S 28	S 32	S 33	PLS 538		2000	
T56N	R75W										
S 29	S 28										
S 32	S 33										
PLS 538											
2000											
41.225	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T56N</td> <td>R75W</td> </tr> <tr> <td></td> <td>S 28</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 33</td> </tr> <tr> <td></td> <td>2002</td> </tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p>	T56N	R75W		S 28	1/4	_____		S 33		2002
T56N	R75W										
	S 28										
1/4	_____										
	S 33										
	2002										

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
60.50	S A Road, on curve, bears N. and SSW.; thence along fence.
82.45	The cor. of secs. 28, 29, 32 and 33. <hr/>
	N. 2° 26' E., bet. secs. 28 and 29. Over rolling to broken terrain.
11.90	Wash, drains W.
28.60	Spur, slopes NW.
38.40	Matz Road, on ridge, bears SE. and NW.
40.755	Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> 56N R75W 1/4 S 29 S 28 2002 </div> Set a steel fence post alongside the stainless steel post.
56.20	Spur, slopes SE.
79.30	Edge of stock pond, bears ESE. and WNW.
81.51	True point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance, falls in stock pond where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor. <hr/>
	From the cor. of secs. 21, 22, 27 and 28. S. 89° 01' W., bet. secs. 21 and 28. Over mountainous terrain, along abandoned fence.
6.00	Cor. of fences extending NE. and irregularly W.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
6.70	L S Draw, drains NNE.
39.09	<p>The 1/4 sec. cor. of secs. 21 and 28, at projected intersection of fences extending E., S. and WNW, with evidence of use by other surveyors. This position is accepted as the best available evidence of the original cor. position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W S 21 1/4 ——— S 28 2002</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 88° 57' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
36.80	S A Road, bears SSE. and NNW.
39.82	<p>Point selected for the witness cor. to the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T56N R75W S 20 S 21 ←————— ————— S 29 S 28 2002</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p>
40.20	Edge of stock pond, bears NE. and SW.
40.32	<p>True point for the cor. of secs. 20, 21, 28 and 29.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 0° 59' W., bet. secs. 20 and 21.</p> <p>Over mountainous terrain.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
2.00	Edge of pond, bears SE. and NW.
17.90	Wash, drains NNW.
18.70	S A Road, bears SSE. and NNW.
40.725	Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W 1/4 S 20 S 21 2002
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 60 lks. E. of fence extending irregularly N. and S.
61.30	Ridge, bears SE. and NW.; thence along fence.
81.45	The cor. of secs. 16, 17, 20 and 21, monumented by Lawrence C. Kay, Wyoming Registered Land Surveyor No. 489, with a steel reinforcement rod, 30 ins. long, ¾ in. diam., firmly set 25 ins. in the ground, at cor. of fences extending E., S. and W., as filed in the Campbell County Clerks Office, with aluminum cap inscribed UINTAH ENG. & LS WYO 489 and mkd. T56N R75W S16 S17 S20 S21 2000. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T56N R75W S 17 S 16 ----- S 20 S 21 2002
	Bury the steel reinforcement rod alongside the stainless steel post.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Cor. is located on ridge, bears N. and S.
	From the cor. of secs. 15, 16, 21 and 22.
	S. 88° 59' W., bet. secs. 16 and 21.
	Over mountainous terrain, leaving abandoned fence.
19.80	From this point, intersection of fences extending S. and W. and abandoned fence extending N., bears SOUTH, 0.2 ch. dist.
40.92	The 1/4 sec. cor. of secs. 16 and 21, at intersection of fences extending N., E. and W. This position is accepted as the best available evidence of the original cor. position.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T56N R75W S 16 1/4 ——— S 21 2002
	N. 89° 43' W., beginning new measurement.
	Over mountainous terrain, along fence.
11.70	Spur, slopes NW.
23.50	Wash, drains NNW.
41.43	The cor. of secs. 16, 17, 20 and 21.
	N. 0° 50' E., bet. secs. 16 and 17.
	Over mountainous terrain.
18.80	Wash, drains NE.
29.30	S A Road, bears NE. and SW.
33.70	Wash, drains SE.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
41.46	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T56N</td><td>R75W</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td>S 17</td><td> S 16</td></tr> <tr><td></td><td>2002</td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located on top of small knoll.</p>	T56N	R75W		1/4	S 17	S 16		2002		
T56N	R75W										
	1/4										
S 17	S 16										
	2002										
55.10	Ridge, bears E. and W.										
82.92	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T56N</td><td>R75W</td></tr> <tr><td>S 8</td><td> S 9</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 17</td><td> S 16</td></tr> <tr><td></td><td>2000</td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this point, a position established by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, as shown on well location plat prepared by Mr. Rumph and obtained from the Wyoming Oil and Gas Conservation Commission, bears S. 76° 44' W., 3.82 chs. dist., monumented with a steel spike in a collar of stone, no mkd. stone found, and perpetuated by Lawrence C. Kay, Wyoming Registered Land Surveyor No. 489, with a steel reinforcement rod, 30 ins. long, ¾ in. diam., firmly set 26 ins. in the ground alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed UINTAH ENG. & LS WYO 489 and mkd. T56N R75W S8 S9 S16 S17 2000. This position is not accepted as the best available evidence of the original cor. position. With the permission of Mr. Kay, remove the steel reinforcement rod and aluminum cap.</p> <hr style="width: 60%; margin-left: 0;"/>	T56N	R75W	S 8	S 9			S 17	S 16		2000
T56N	R75W										
S 8	S 9										
S 17	S 16										
	2000										

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89° 30' W., bet. secs. 9 and 16.
	Over rolling to broken terrain.
3.40	Wash, drains SSW.
37.30	Enter L X Bar Creek, course W.
40.775	Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance, falls in L X Bar Creek, course W., where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.
41.60	Leave L X Bar Creek, course WSW.
42.835	Point selected for the witness cor. to the 1/4 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> W C T56N R75W S 9 1/4 —————> S 16 2002 </pre>
	Set a steel fence post alongside the stainless steel post.
48.00	L X Bar Creek, course NW.
52.60	S A Road, bears NNE. and SSW.
81.55	The cor. of secs. 8, 9, 16 and 17.

	N. 0° 10' E., bet. secs. 8 and 9.
	Over rolling to broken terrain.
2.00	Wash, drains NE.
13.50	Spur, slopes SE.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
41.455	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T56N</td><td>R75W</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td>S</td><td>8 S 9</td></tr> <tr><td></td><td>2002</td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p>	T56N	R75W		1/4	S	8 S 9		2002		
T56N	R75W										
	1/4										
S	8 S 9										
	2002										
49.10	Kline Draw, drains ENE.										
56.70	L X Bar Creek, course NW.										
82.91	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T56N</td><td>R75W</td></tr> <tr><td>S</td><td>5 S 4</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S</td><td>8 S 9</td></tr> <tr><td></td><td>2002</td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this point, a position established by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, as shown on well location plat prepared by Mr. Rumph and obtained from the Wyoming Oil and Gas Conservation Commission, bears S. 67° 09' W., 3.94 chs. dist., monumented with a sandstone, 27x25x10 ins., embedded horizontally, no mks. visible, and perpetuated by Lawrence C. Kay, Wyoming Registered Land Surveyor No. 489, with a steel reinforcement rod, 30 ins. long, ¾ in. diam., firmly set 25 ins. in the ground alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed UINTAH ENG. & LS WYO 489 and mkd. T56N R75W S4 S5 S8 S9 2000. This position is not accepted as the best available evidence of the original cor. position. With the permission of Mr. Kay, remove the steel reinforcement rod and aluminum cap.</p> <hr/>	T56N	R75W	S	5 S 4	<hr/>		S	8 S 9		2002
T56N	R75W										
S	5 S 4										
<hr/>											
S	8 S 9										
	2002										

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 3, 4, 9 and 10.
	N. 88° 37' W., bet. secs. 4 and 9.
	Over mountainous terrain.
11.60	Improved road, bears SE. and NW.
14.80	Descend abruptly over steep W. slope of ridge, bears NNE. and SSW.
20.245	Point for the E. 1/16 sec. cor. of secs. 4 and 9.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W S 4 E1/16 ——— S 9 2002
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 50 lks. S. of wash, drains WNW.
36.00	Spur, slopes NW.
40.49	Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T56N R75W S 4 1/4 ——— S 9 2002
53.60	Wash, drains NNW.
65.10	S A Road, bears SSE. and NNW.
80.98	The cor. of secs. 4, 5, 8 and 9.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 7° 06' W., bet. secs. 4 and 5.
	Over rolling to broken terrain.
40.60	Wash, drains NW.
41.78	Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W 1/4 S 5 S 4 2002
	Set a steel fence post alongside the stainless steel post.
84.00	The closing cor. of secs. 4 and 5, at intersection with the Fourteenth Standard Parallel North, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T57N R75W S 32 ----- S 5 S 4 T56N R75W C C 2002
	Set a steel fence post alongside the stainless steel post.
	From this point, the angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 33, T. 57 N., R. 75 W., bears S. 87° 44' E., 18.23 chs. dist.
	<hr/>
	The point for the 1/4 sec. cor. of sec. 4 only, T. 56 N., R. 75 W., is at midpoint on the N. bdy. of sec. 4.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<div style="text-align: center;"> <p>T57N R75W</p> <hr style="width: 10%; margin: 0 auto;"/> <p>1/4 S 4</p> <p>T56N R75W</p> <p>2002</p> </div> <p>Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 2 ft. high, S. of the cor.</p> <p>Cor. is located 35 lks. S. of trail road extending E. and W.</p> <p>From this point, the angle point marking the restored position of the original standard cor. of secs. 33 and 34, T. 57 N., R. 75 W., bears S. 87° 54' E., 18.28 chs. dist.</p> <hr/> <p>The point for the W. 1/16 sec. cor. of sec. 4 only, T. 56 N., R. 75 W., is at midpoint bet. the closing cor. of secs. 4 and 5 and the 1/4 sec. cor. of sec. 4 only, on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T57N R75W</p> <hr style="width: 10%; margin: 0 auto;"/> <p>W1/16 S 4</p> <p>T56N R75W</p> <p>2002</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this point, the angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 33, T. 57 N., R. 75 W., bears N. 87° 54' W., 3.63 chs. dist.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 55 N., R. 75 W., executed concurrently under this same group.</p> <p>N. 0° 32' W., bet. secs. 31 and 32.</p> <p>Over mountainous terrain.</p>
34.20	Wash, drains NW.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
39.735	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>W</td><td>C</td></tr> <tr><td>T56N</td><td>R75W</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 31</td><td> S 32</td></tr> <tr><td>2002</td><td></td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p>	W	C	T56N	R75W	1/4		S 31	S 32	2002	
W	C										
T56N	R75W										
1/4											
S 31	S 32										
2002											
40.735	<p>True point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance, falls on steep S. slope of small wash, drains SW., where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.</p>										
49.50	<p>Spur, slopes NW.</p>										
71.20	<p>Wash, drains SSW.</p>										
81.47	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T56N</td><td>R75W</td></tr> <tr><td>S 30</td><td> S 29</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 31</td><td> S 32</td></tr> <tr><td>2002</td><td></td></tr> </table> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located 20 lks. N. of small wash, drains SSE.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89° 18' W., bet. secs. 29 and 32.</p> <p>Over mountainous terrain.</p>	T56N	R75W	S 30	S 29	<hr/>		S 31	S 32	2002	
T56N	R75W										
S 30	S 29										
<hr/>											
S 31	S 32										
2002											

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
18.50	Wash, drains NW.
28.50	Ridge, bears SSE. and NNW.
39.98	Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> 56N R75W S 29 1/4 ——— S 32 2002 </div>
	Set a steel fence post alongside the stainless steel post.
	Cor. is located on small spur, slopes S.
62.70	Wash, drains SSW.
79.96	The cor. of secs. 29, 30, 31 and 32. <hr/>
	S. 88° 04' W., bet. secs. 30 and 31. Over mountainous terrain.
15.00	Ridge, bears NE. and SW.
39.96	Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T56N R75W S 30 1/4 ——— S 31 2002 </div>
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 25 lks. N. of fence extending irregularly E. and W.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
59.50	Wash, drains SW.
77.57	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 56 N., R. 76 W.
	<hr/> From the cor. of secs. 29, 30, 31 and 32. N. 2° 06' E., bet. secs. 29 and 30. Over mountainous terrain.
26.80	Ridge, bears E. and W.
37.40	Spur, slopes WNW.
40.76	Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T56N R75W 1/4 S 30 S 29 2002 </div> Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.
52.50	Ridge, bears SSE. and WNW.
63.50	Cor. of abandoned fences extending N. and W., thence along abandoned fence.
71.30	Wash, drains W.
81.52	The cor. of secs. 19, 20, 29 and 30, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set flush with the surface of the ground, at cor. of abandoned fences extending N., S. and W., with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T56N</td> <td style="padding: 2px;">R75W</td> </tr> <tr> <td style="padding: 2px;">S 19</td> <td style="padding: 2px;">S 20</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px;">S 30</td> <td style="border-top: 1px solid black; padding: 2px;">S 29</td> </tr> <tr> <td style="padding: 2px;">PLS 538</td> <td style="padding: 2px;"></td> </tr> <tr> <td style="padding: 2px;">2000</td> <td style="padding: 2px;"></td> </tr> </table>	T56N	R75W	S 19	S 20	S 30	S 29	PLS 538		2000	
T56N	R75W										
S 19	S 20										
S 30	S 29										
PLS 538											
2000											
<p>1.90</p> <p>23.20</p> <p>40.21</p>	<p>This position is accepted as the best available evidence of the original cor. position.</p> <p>Set a steel fence post alongside the aluminum post.</p> <p>From this point, a position established by Richard T. Doyle, Wyoming Registered Land Surveyor No. 2333, bears S. 13° 00' E., 3.91 chs. dist., monumented with a steel reinforcement rod, $\frac{5}{8}$ in. diam., firmly set, projecting 15 ins. above the ground, in a mound of stone, 5 ft. base, 1½ ft. high, no mkd. stone found, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed DLS RLS 2333, no other marks. There are a number of such mounds of stone around this and other cultivated fields; therefore, this position is not accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the true point for the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89° 17' W., bet. secs. 20 and 29.</p> <p>Over rolling to broken terrain.</p> <p>Leave pond, bears NNE. and SSW.</p> <p>Ridge, bears SE. and NW.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. below the surface of the ground, with brass cap mkd.</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T56N</td> <td style="padding: 2px;">R75W</td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;">S 20</td> </tr> <tr> <td style="padding: 2px;">1/4</td> <td style="padding: 2px;">_____</td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;">S 29</td> </tr> <tr> <td style="padding: 2px;">2002</td> <td style="padding: 2px;"></td> </tr> </table> <p>Set a steel fence post alongside the stainless steel post.</p>	T56N	R75W		S 20	1/4	_____		S 29	2002	
T56N	R75W										
	S 20										
1/4	_____										
	S 29										
2002											

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Cor. is located in wash, drains WNW.
47.50	Spur, slopes NW.
51.20	Wash, drains N.
57.40	Improved road, on curve, bears SE. and NW.
80.42	The cor. of secs. 19, 20, 29 and 30.
	N. 89° 52' W., bet. secs. 19 and 30.
	Over mountainous terrain, along abandoned fence.
28.50	Wash, drains S.
41.34	Point for the 1/4 sec. cor. of secs. 19 and 30, determined longitudinally by proportionate measurement and latitudinally by abandoned fence extending E. and W.; there is no remaining evidence of the original monument.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T56N R75W S 19 1/4 ——— S 30 2002
	Set a steel fence post alongside the stainless steel post.
	S. 84° 01' W., beginning new measurement.
	Over mountainous terrain, along abandoned fence.
9.10	Ridge, bears N. and S.
29.60	Wash, drains SSE.
39.31	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 56 N., R. 76 W.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 19' W., bet. secs. 19 and 20.</p> <p>Over rolling to broken terrain, across cultivated field and along portions of abandoned fence.</p> <p>41.90 The 1/4 sec. cor. of secs. 19 and 20, at projected intersection of abandoned fences from the S. and W., falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W 1/4 S 19 S 20 2002</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 2° 22' E., beginning new measurement.</p> <p>Over rolling to broken terrain, across cultivated field.</p> <p>1.90 Improved road, on curve, bears SE. and WNW.; thence along abandoned fence.</p> <p>20.40 Ridge, bears ESE. and WNW.</p> <p>39.03 The cor. of secs. 17, 18, 19 and 20, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with a steel reinforcement rod, 18 ins. long, ⅝ in. diam., firmly set 16 ins. in the ground, at intersection of fences extending N., E. and W., and abandoned fence extending S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd. T56N R75W S17 S18 S19 S20 RLS 538 1998</p> <p>At the corner point.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T56N</td> <td style="padding: 2px;">R75W</td> </tr> <tr> <td style="padding: 2px;">S 18</td> <td style="padding: 2px;">S 17</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px;">S 19</td> <td style="border-top: 1px solid black; padding: 2px;">S 20</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">2002</td> </tr> </table>	T56N	R75W	S 18	S 17	S 19	S 20	2002			
T56N	R75W										
S 18	S 17										
S 19	S 20										
2002											
	<p style="text-align: center;">Deposit the steel reinforcement rod inside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89° 40' W., bet. secs. 17 and 20.</p> <p>Over mountainous terrain, along fence.</p> <p>6.50 Wash, drains NNE.</p> <p>9.30 S A Road, bears N. and S.; thence leave fence, bears WNW.</p> <p>15.90 Spur, slopes N.</p> <p>33.60 Wash, drains NNE.</p> <p>38.81 Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original cor.</p> <p style="text-align: center;">Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T56N</td> <td style="padding: 2px;">R75W</td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;">S 17</td> </tr> <tr> <td style="padding: 2px;">1/4</td> <td style="border-top: 1px solid black; padding: 2px;"></td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;">S 20</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">2002</td> </tr> </table> <p>from which</p> <p style="text-align: center;">A pine, 8 ins. diam., bears N. 34° E., 58 lks. dist., mkd. 1/4 S17 BT.</p> <p style="text-align: center;">Set a steel fence post alongside the stainless steel post.</p> <p>67.60 Ridge, bears N. and S.; thence along fence.</p> <p>77.62 The cor. of secs. 17, 18, 19 and 20.</p> <hr/>	T56N	R75W		S 17	1/4			S 20	2002	
T56N	R75W										
	S 17										
1/4											
	S 20										
2002											

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	S. 86° 14' W., bet. secs. 18 and 19.
	Over mountainous terrain, along fence.
5.30	Wash, drains NNW.; thence leave fence, bears irregularly WSW.
38.50	Spur, slopes NW.
40.40	Wash, drains NNW.
42.00	Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance, falls on steep W. slope of wash; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.
	T56N R75W S 18 1/4 ——— S 19 2002
	from which
	A juniper, 6 ins. diam., bears S. 11° W., 29 lks. dist., mkd. 1/4 S19 BT.
	A juniper, 8 ins. diam., bears N. 32° W., 23 lks. dist., mkd. 1/4 S18 BT.
	Set a steel fence post alongside the stainless steel post.
78.50	Improved road, bears N. and S.
81.50	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an aluminum rod, 5/8 in. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 56 N., R. 76 W.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 1° 35' W., bet. secs. 17 and 18.
	Over mountainous terrain, leaving fence.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS											
24.10	Ridge, bears SE. and NW.										
31.00	Wash, drains NW.										
39.00	Spur, slopes NW.										
41.47	Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original cor.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T56N</td><td>R75W</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 18</td><td> S 17</td></tr> <tr><td>2002</td><td></td></tr> </table>	T56N	R75W	1/4		S 18	S 17	2002			
T56N	R75W										
1/4											
S 18	S 17										
2002											
	Set a steel fence post alongside the stainless steel post.										
43.40	Wash, drains WNW.										
56.30	Spur, slopes NW.										
74.70	Kline Draw, drains NE.										
82.94	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original cor.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T56N</td><td>R75W</td></tr> <tr><td>S 7</td><td> S 8</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 18</td><td> S 17</td></tr> <tr><td>2002</td><td></td></tr> </table>	T56N	R75W	S 7	S 8			S 18	S 17	2002	
T56N	R75W										
S 7	S 8										
S 18	S 17										
2002											
	Set a steel fence post alongside the stainless steel post.										
	The cor. position of the cor. of secs. 7, 8, 17 and 18, as shown on Certified Land Corner Recordation prepared by Robert L. St. Claire, Wyoming Registered Land Surveyor No. 584, as filed in the Campbell County Clerk's Office, searched for but not recovered.										

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 8, 9, 16 and 17.
	N. 89° 41' W., bet. secs. 8 and 17.
	Over mountainous terrain.
2.10	Wash, drains NE.
22.60	Ridge, bears N. and SSW.
40.55	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.
	T56N R75W S 8 1/4 ——— S 17 2002
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 35 lks. E. of small wash, drains NW.
74.60	Kline Draw, drains NNW.
81.10	The cor. of secs. 7, 8, 17 and 18.

	S. 84° 13' W., bet. secs. 7 and 18.
	Over mountainous terrain.
30.70	Ridge, bears N. and S.
40.78	Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T56N R75W S 7 1/4 ——— S 18 2002
	Set a steel fence post alongside the stainless steel post.
58.47	Point selected for the witness cor. to the W. 1/16 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	W C T56N R75W S 7 W1/16 <——— S 18 2002
	Set a steel fence post alongside the stainless steel post.
60.50	Wash, drains WNW.
61.17	True point for the W. 1/16 sec. cor. of secs. 7 and 18, falls on steep SW. slope of wash where it is impracticable to establish a permanent monument.
64.30	Spur, slopes NNW.
68.50	Wash, drains NNE.
78.82	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 56 N., R. 76 W.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0° 15' E., bet. secs. 7 and 8.
	Over mountainous terrain.
15.90	Abandoned fence, bears E. and W.
22.80	Spur, slopes SSE.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
36.90	Wash, drains SSE.
41.455	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T56N R75W 1/4 S 7 S 8 2002 </div> <p>Set a steel fence post alongside the stainless steel post.</p>
45.70	Ridge, bears ESE. and WNW.; thence along steep NE. slope of spur.
62.182	<p>Point for the N. 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T56N R75W N1/16 S 7 S 8 2002 </div> <p>Set a steel fence post alongside the stainless steel post.</p>
63.30	Foot of steep slope, bears SSE. and NNW.
82.91	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T56N R75W S 6 S 5 ----- S 7 S 8 2002 </div> <p>Set a steel fence post alongside the stainless steel post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, a position established by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, as shown on well location plat prepared by Mr. Rumph and obtained from the Wyoming Oil and Gas Conservation Commission, bears S. 0° 35' W., 2.70 chs. dist., monumented with a sandstone, 10x7x5 ins., loosely set 2 ins. in the ground, no mks. visible, with a steel spike firmly set alongside. This position is not accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89° 41' W., bet. secs. 5 and 8.</p> <p>Over rolling to broken terrain.</p>
17.40	L X Bar Creek, course NW.
40.49	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T56N R75W S 5 1/4 ——— S 8 2002 </div> <p>Set a steel fence post alongside the stainless steel post.</p>
48.10	Ridge, bears SSE. and NNW.
80.98	The cor. of secs. 5, 6, 7 and 8.
	<hr/> <p>S. 82° 20' W., bet. secs. 6 and 7.</p> <p>Over rolling to broken terrain.</p>
8.50	Ridge, bears N. and S.
34.00	Wash, drains NW.

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.72	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T56N R75W S 6 1/4 ——— S 7 2002 </div> <p>Set a steel fence post alongside the stainless steel post.</p>
43.60	Ridge, bears N. and S.
61.08	<p>Point for the W. 1/16 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T56N R75W S 6 W1/16 ——— S 7 2002 </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located in wash, drains WNW.</p>
62.60	Spur, slopes NNW.
64.90	Wash, drains NNE.
78.89	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1988-89 field notes of the dependent resurvey, T. 56 N., R. 76 W.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 8° 05' W., bet. secs. 5 and 6.</p> <p>Over rolling to broken terrain.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	
41.87	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R75W 1/4 S 6 S 5 2002</p> </div> <p>from which</p> <p style="text-align: center;">A pine, 11 ins. diam., bears N. 87° W., 42 lks. dist., mkd. 1/4 S6 BT.</p> <p>Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p>
47.20	Descend through scattering juniper and pine.
65.20	Wash, drains ENE.
84.04	<p>The closing cor. of secs. 5 and 6, at intersection with the Fourteenth Standard Parallel North, at proportionate distance, falls on E. edge of steep bank of small wash, drains N.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, over a steel fence post, supported by a mound of stone, 1½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T57N R75W S 31</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S 6 S 5 T56N R75W C C 2002</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this point, the angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 32, identical with Cor. No. 2, Tract 37, T. 57 N., R. 74 W., bears S. 89° 50' E., 16.99 chs. dist.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>The point for the 1/4 sec. cor. of sec. 5 only, T. 56 N., R. 75 W., is at midpoint on the N. bdy. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} \text{T57N R75W} \\ \hline 1/4 \quad \text{S } 5 \\ \text{T56N R75W} \\ 2002 \end{array}$ </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this point, the angle point marking the restored position of the original standard cor. of secs. 32 and 33, T. 57 N., R. 75 W., bears N. 88° 54' E., 15.71 chs. dist.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>The point for the 1/4 sec. cor. of sec. 6 only, T. 56 N., R. 75 W., is at proportionate distance on the N. bdy. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} \text{T57N R75W} \\ \hline 1/4 \quad \text{S } 6 \\ \text{T56N R75W} \\ 2002 \end{array}$ </div> <p>Set a steel fence post alongside the stainless steel post.</p> <p>From this point, the angle point marking the restored position of the original standard cor. of secs. 31 and 32, T. 57 N., R. 75 W., bears S. 89° 56' E., 16.88 chs. dist.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/>
--------	---

T. 56 N., R. 75 W., Sixth Principal Meridian, Wyoming

CHAINS

GENERAL DESCRIPTION

The area embraced by this survey is situated in the northwestern portion of Campbell County, approximately 9 miles north-northwest of Spotted Horse, Wyoming. The terrain varies from gently rolling to mountainous, with the elevation ranging from about 3,630 feet above sea level, where L X Bar Creek crosses the north boundary, to about 4,220 feet above sea level along the ridge east of L X Bar Creek in section 25. The soil varies from gravelly loam to rocky clay with areas of exposed scoria. Vegetation consists of a light to moderate growth of sagebrush and native grasses throughout with scattered stands of cottonwood along the drainages and areas of juniper and pine in the higher elevations.

Primary drainage is provided by L X Bar Creek, which courses northwesterly through the township. The northeastern portion is drained by S A Creek and southwestern portion by Linn Draw, both also coursing northwesterly. The William F. West ranch is located in section 28, the area being suitable for grazing purposes. Coal bed methane exploration and development is currently in progress.

Access to the central portion of the township is provided by S A Road, leading north from U.S. Highway Nos. 14 and 16, and numerous improved oil and gas field roads and trail roads extending throughout the township.

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
Tyrel F. Hoon	Surveying Technician
Joshua N. Anderson	Surveying Aid

CERTIFICATE OF SURVEY

I, Richard A. Kohler, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day of February, 2001, I have dependently resurveyed the Fourteenth Standard Parallel North, through Range 75 West, the east boundary and the subdivisional lines, Township 56 North, Range 75 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

SEP 24 2004

(Date)

Richard A. Kohler

Richard A. Kohler
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of the Fourteenth Standard Parallel North, through Range 75 West, the east boundary and the subdivisional lines, Township 56 North, Range 75 West, executed by Richard A. Kohler, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

SEP 24 2004

(Date)

John P. Lee

John P. Lee
Chief Cadastral Surveyor for Wyoming