

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE EIGHTH STANDARD PARALLEL NORTH,

THROUGH RANGE 108 WEST,

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE

SUBDIVISION OF SECTIONS 4, 5, 8 AND 9,

TOWNSHIP 32 NORTH, RANGE 108 WEST,

OF THE SIXTH PRINCIPAL MERIDIAN,

IN THE STATE OF WYOMING.

EXECUTED BY

OLIAN T. SHOCKLEY

CADASTRAL SURVEYOR

Under Special Instructions dated JULY 16, 2003, approved JULY 16, 2003, which provided for the surveys included under Group Number 718 and assignment instructions dated JULY 16, 2003.

Survey commenced JULY 28, 2003

Survey completed JULY 26, 2004

INDEX DIAGRAM

Township 32 North, Range 108 West

	EIGHTH	STANDARD	PARALLEL		NORTH
		6	4	2	
6	22 5	16 4	10 3	2	1
7	22 20 8	14 12 9	8 10	11	12
18	18 17	12 16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 4.....Pages 24
 Subdivision of Section 5.....Pages 26
 Subdivision of Section 8.....Pages 29
 Subdivision of Section 9.....Pages 32

T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>The following field notes are those of the dependent resurvey of a portion of the Eighth Standard Parallel North, through Range 108 West, and a portion of the subdivisional lines, and the subdivision of sections 4, 5, 8 and 9, Township 32 North, Range 108 West, of the Sixth Principal Meridian, Wyoming.</p> <p>Franklin O. Sawin surveyed the Eighth Standard Parallel North through Range 108 West (north boundary) in 1889 and a portion of the subdivision lines in 1890. William S. Adams retraced the Eighth Standard Parallel North through Range 108 West and selected section lines, and completed the survey of the subdivision lines in 1908. Wayne M. Gardner dependently resurveyed the Thirteenth Auxiliary Guide Meridian through Township 32 North, between Ranges 108 and 109 West (west boundary) in 1969.</p> <p>All local monuments set by private surveyors and accepted or rejected during the course of this resurvey are on file in the Sublette County Courthouse in Pinedale, Wyoming. Exceptions are noted in the field notes.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 718, Wyoming, dated July 16, 2003.</p> <p>Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions. Lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data were thoroughly verified and only true line field notes are given herein, which refer to the completed survey.</p> <p>The survey was executed with TRIMBLE Model 4700 Global Positioning System (GPS) receivers. The directions of all lines refer to the true meridian as determined by GPS observations. GPS control network and supporting data are contained in the official group file.</p> <p>The geographic position of the corner of sections 9, 10, 15 and 16, based on NAD 83 (1993) and determined by Global Positioning System Methods is:</p> <p>Latitude 42° 45' 01.172" N., Longitude 109° 42' 53.696" W.</p> <p>The mean magnetic declination as determined by The United States Geological Survey Geomagix program (magnetic model US-2000) is 13° E.</p> <hr/>
--------	--

Dependent Resurvey of a Portion of the Eighth Standard Parallel North,
Through Range 108 West, Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">(Restoring the Retracement executed by William S. Adams in 1908)</p> <hr/> <p>Beginning at the standard cor. of secs. 35 and 36, T. 33 N., R. 108 W., perpetuated by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, in a rubber tire, with brass cap mkd.</p> <p style="text-align: center;">PAUL N. SCHERBEL RLS 164 BIG PINEY WYOMING T33N R108W SC S 35 S 36 <hr/>S3 T32N R108W 1971</p> <p>This is accepted as a careful and faithful perpetuation of the original cor. position. Cor. point not remonumented.</p> <p>The cor. is located ½ lk. N. of a 4 strand barbed wire fences, bears E. and W., and 14 lks S. of a trail road, bears E. and W.</p> <p>N. 89° 36' W., on the S. bdy. of sec. 35, T. 33 N., R. 108 W.</p> <p>Over flat terrain.</p> <p>39.94 Point for the standard 1/4 sec. cor. of sec. 35, Tp. 33 N., R. 108 W., determined by irregular boundary method, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, over a plastic coated magnet, with brass cap mkd.</p> <p style="text-align: center;">SC T33N R108W 1/4 S 35 <hr/>2004</p> <p>The cor. is located 3 lks. N. of a 4 strand barbed wire fence, bears E. and W., and 65 lks S. of Sublette County Road 23-125, graded surface, 35 lks. wide, bears ENE. and WSW.</p>

Dependent Resurvey of a Portion of the Eighth Standard Parallel North,
Through Range 108 West, Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, the cor. position for the standard 1/4 sec. cor. of sec. 35, established by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with a granite stone, 12x7x6 ins., loosely set, no visible mks., on the N. side of the post, bears S. 83° 03' W., 17.7 lks. dist., with brass cap mkd.</p> <p style="text-align: center;">PAUL N. SCHERBEL RLS 164 BIG PINEY WYOMING T33N R108W SC S 35 1/4 ——— T32N R108W 1971</p> <p>This cor. position was determined utilizing an erroneous measurement and is not accepted as a careful and faithful reestablishment of the original cor. position. When notified of this miscalculation Paul N. Scherbel removed his monument from this location. In an effort to perpetuate this position, because it had been used by at least one prior local survey, a steel reinforcement rod, 24 ins. long, ⅝ in. diam., was set 24 ins. in the ground, at the former Scherbel cor. position.</p> <p style="text-align: center;">—————</p> <p>N. 89° 44' W., beginning new measurement.</p> <p>Over level terrain.</p> <p>5.195 Point for the closing cor. of secs. 3 and 4, T. 32 N., R.108 W., hereinafter described.</p> <p>7.95 Center of Sublette County Road 23-104, graded surface, 35 lks. wide, bears ENE. and WSW.</p> <p>39.90 The standard cor. of secs. 34 and 35, T. 33 N., R. 108 W., monumented with a granite stone, 16x8x7 ins., firmly set, projecting 10 ins. above ground, plainly marked SC on the N. face, with 2 dim grooves on the E. face, and 4 dim grooves on the W. face, with a steel fence post nearby.</p> <p>from which the remaining original bearing trees:</p> <p style="text-align: center;">A pine stump, 16 ins. diam., bears N. 63½° E., 36 lks. dist., with illegible scribe mks. visible on the rotted trunk lying nearby. (1889 rec.: 10 ins. diam., bears N. 60° E., 37 lks. dist., mkd. T33N R108W S35 BT)</p>

Dependent Resurvey of a Portion of the Eighth Standard Parallel North,
Through Range 108 West, Sixth Principal Meridian, Wyoming

CHAINS					
	<p>A pine stump, 15 ins. diam., bears N. 55° W., 49 lks. dist., with no scribe mks. visible. (1889 rec.: 12 ins. diam., bears N. 59° W., 50 lks. dist., mkd. T33N R108W S34 BT)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, over a plastic coated magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC</p> <p>T33N R108W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center;">2003</td> </tr> </table> </div> <p>Bury the original stone alongside the stainless steel post.</p> <p>The cor. is located in the bottom lands of Boulder Creek, on the S. side of a slough.</p> <hr/> <p>N. 89° 29' W., on the S. bdy. of sec. 34, T. 33 N., R. 108 W.</p> <p>Over flat terrain.</p> <p>5.255 Point for the 1/4 sec. cor. of sec. 4 only, T. 32 N., R.108 W., hereinafter described.</p> <p>7.00 Left bank of Boulder Creek, course SE.</p> <p>8.10 Right bank of Boulder Creek.</p> <p>25.235 Point for the W 1/16 sec. cor. of sec. 4 only, T. 32 N., R.108 W., hereinafter described.</p> <p>39.935 The standard 1/4 sec. cor. of sec. 34, T. 33 N., R. 108 W., monumented with a broken and crumbling sandstone, 12x7x3 ins., firmly set, projecting 3 ins. above ground, no mks.visible , with a rubber tire nearby.</p> <p>At the corner point</p>	S 34	S 35	2003	
S 34	S 35				
2003					

Dependent Resurvey of a Portion of the Eighth Standard Parallel North,
Through Range 108 West, Sixth Principal Meridian, Wyoming

CHAINS	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a plastic coated magnet, with brass cap mkd.</p> <p style="text-align: center;">SC T33N R108W <u>1/4 S 34</u> 2003</p> <p>Bury the original stone alongside the iron post, and set a steel fence post nearby.</p> <p>The cor. is located on open, sagebrush covered ground.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 37' W., beginning new measurement.</p> <p>Over level terrain.</p> <p>2.30 Center of B.L.M. Road 5106, graded surface, 30 lks. wide, bears NNW. and SSE.</p> <p>5.285 The closing cor. of secs. 4 and 5, T. 32 N., R.108 W., hereinafter described.</p> <p>25.285 Point for the E 1/16 sec. cor. of sec. 5 only, T. 32 N., R.108 W., hereinafter described.</p> <p>39.955 The standard cor. of secs. 33 and 34, T. 33 N., R. 108 W., perpetuated by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625, monumented with a steel reinforcement rod, 15 ins. long, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. RIO VERDE ENGR PELS 625. This is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a plastic coated magnet, with brass cap mkd.</p>
--------	--

Dependent Resurvey of a Portion of the Eighth Standard Parallel North,
Through Range 108 West, Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">SC T33N R108W</p> <p style="text-align: center;">S 33 S 34 -----</p> <p style="text-align: center;">2003</p> <p>Deposit the reinforcement rod inside the stainless steel post.</p> <p>The cor. is located at the E. side of a wooden fence cor., 5 strand barbed wire fence extends N., and a wire mesh fence extends E. and W.</p> <hr/> <p>N. 89° 34' W., on the S. bdy. of sec. 33, T. 33 N., R. 108 W.</p> <p>Over flat terrain.</p> <p>5.32 Point for the 1/4 sec. cor. of sec. 5 only, T. 32 N., R.108 W., hereinafter described.</p> <p>40.03 Point for the standard 1/4 sec. cor. of sec. 33, Tp. 33 N., R.. 108 W., determined by the irregular boundary method, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, over a plastic coated magnet, with brass cap mkd.</p> <p style="text-align: center;">SC T33N R108W</p> <p style="text-align: center;">1/4 S 33 -----</p> <p style="text-align: center;">2003</p> <p>The cor. is located 7 lks. N. of a 5 strand barbed wire fence, bears E. and W. and 9½ lks. E. of a 5 strand barbed wire fence, bears N. and S.</p>
--------	--

Dependent Resurvey of a Portion of the Eighth Standard Parallel North,
Through Range 108 West, Sixth Principal Meridian, Wyoming

CHAINS																	
	<p>From this cor. point, the cor. position of the standard 1/4 sec. cor. of sec. 33, established by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. RIO VERDE ENGR PELS 625 bears S. 15° 10' W., 7.7 lks. dist. This cor. position was established using improper procedures and is not utilized in the course of this resurvey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 47' W., beginning new measurement.</p> <p>Over level terrain.</p>																
5.25	The closing cor. of secs. 5 and 6, T. 32 N., R. 108 W., hereinafter described.																
34.40	Center of U.S. Highway 191, asphalt surface, 36 lks. wide, bears SE. and NW.																
40.07	The standard cor. of secs. 32 and 33, T. 33 N., R. 108 W., set by Wayne M. Gardner in 1969, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above ground, with a small mound of stone to the N. and a steel fence post nearby, with brass cap mkd.																
	<p>SC</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> <tr> <td style="border-right: 1px solid black; border-top: 1px solid black; padding: 0 5px;">T32N</td> <td style="border-top: 1px solid black; padding: 0 5px;">R108W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1969</td> </tr> </table> <p>(1969 record: brass cap mkd.)</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">SC</td> </tr> <tr> <td colspan="2" style="text-align: center;">T33N R108W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> <tr> <td style="border-right: 1px solid black; border-top: 1px solid black; padding: 0 5px;"></td> <td style="border-top: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1969</td> </tr> </table> <hr style="width: 80%; margin: 10px auto;"/>	S 32	S 33	T32N	R108W		1969	SC		T33N R108W		S 32	S 33				1969
S 32	S 33																
T32N	R108W																
	1969																
SC																	
T33N R108W																	
S 32	S 33																
	1969																

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS

(Restoring the Survey
executed by Franklin O. Sawin in 1890)

From the cor. of secs. 9, 10, 15 and 16, reestablished by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, in a rubber tire, with a steel fence post nearby, with brass cap mkd.

PAUL N. SCHERBEL RLS 164 BIG PINEY WYOMING
T32N R108W
S 9 | S 10

S 16 | S 15
1971

This is accepted as a careful and faithful reestablishment of the original cor. position. Cor. point not remonumented.

N. 0° 19' E., bet. secs. 9 and 10.

Over flat terrain.

40.15 The 1/4 sec. cor. of secs. 9 and 10, reestablished by Skylar V. Wilson, Wyoming Professional Land Surveyor No. 4274, monumented with a steel reinforcement rod, 5/8 in. diam., 4 ins. below the surface of the ground, with aluminum cap mkd.

WILSON LAND SURVEYING
T32N R108W
S 9 | S 10
1/4
2001
LS4274

This is accepted as a careful and faithful reestablishment of the original cor. position. Cor. point not remonumented.

The cor. is located 1 ½ lks. W. of the W. edge of Sublette County Road 23-125, graded surface, 35 lks. wide, bears N. and S.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this cor. point, a steel reinforcement rod, 5/8 ins. diam., firmly set, flush with the surface of the ground, in a 4 strand barbed wire fence, bears N. and S., established by Skylar V. Wilson for a reference monument, bears N. 89° 27' W., 36.3 lks. dist., with aluminum cap mkd. WILSON -LAND SURVEYING WC 24.00' W. 2001 LS4274.</p> <hr/> <p>N 0° 19' E., beginning new measurement</p> <p>Along the W. edge of Sublette County Road 23-104.</p>
20.075	<p>A steel reinforcement rod, 5/8 in. diam., 6 ins. below the surface of Sublette County Road 23-125, with aluminum cap mkd.</p> <p style="text-align: center;">WILSON LAND SURVEYING T32N R108W S 9 S 10 N 1/16 2001 LS4274</p>
40.15	<p>From this rod, an aluminum post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, established by Skylar V. Wilson for a reference monument, bears N. 89° 33' W., 45.5 lks. dist., with aluminum cap mkd. WILSON LAND SURVEYING T32N R108W S9 S10 N 1/16 W.C. 30.00' W. 2001 PLS 4274.</p> <p>The cor. of secs. 3, 4, 9 and 10, reestablished by Skylar V. Wilson, Wyoming Registered Land Surveyor No. 4274, monumented with an aluminum post, 2½ ins. diam., firmly set, flush with the surface of the ground, with a steel fence post nearby, with aluminum cap mkd.</p> <p style="text-align: center;">WILSON LAND SURVEYING T32N R108W S 4 S 3 <hr/>S 9 S 10 2001 PLS 4274</p>
	<p>This is accepted as a careful and faithful reestablishment of the original cor. position. Cor. point not remonumented.</p> <p>The cor. is located in a hay meadow.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>(Restoring the Survey executed by William S. Adams in 1908)</p> <hr/>
	N. 0° 09' W., bet. secs. 3 and 4.
	Over flat terrain.
23.75	Power transmission line, bears N. 9° E. and S. 9° W.
40.015	The 1/4 sec. cor. of secs. 3 and 4, reestablished by Skylar V. Wilson, Wyoming Registered Land Surveyor No. 4274, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 3 ins. above the surface of the ground, with a steel fence post nearby, with aluminum cap mkd.
	<p>WILSON LAND SURVEYING T32N R108W S 4 S 3 1/4 2001 PLS4274</p>
	This is accepted as a careful and faithful reestablishment of the original cor. position. Cor. point not remonumented.
	The cor. is located at the N. edge of a hay meadow, and 3 lks. S. of the S. edge of an irrigation ditch, 10 lks. wide, 2 ft. deep, course W.
	<hr/>
	N 0° 11' W., beginning new measurement
0.36	Old wooden fence cor., 3 strand barbed wire fence extends E., 2 strand barbed wire and wire mesh fence extends W. and 5 strand barbed wire fence extends N.
	Thence along a 5 strand barbed wire fence.
37.475	The original closing cor. of secs. 3 and 4, a wooden fence cor., 12 ins. diam., 3 strand barbed wire fence extends E., 5 strand barbed wire fence extends S., and 4 strand barbed wire fence extends W.
	This is accepted as the as the best available evidence of the position of the original cor..
37.68	Point for the closing cor. of secs. 3 and 4, at intersection with the Eighth Standard Parallel North.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, over a plastic coated magnet, with brass cap mkd.

T33N R108W
S35

S 4		S 3
T32N R108W		
CC		
2004		

The cor. is located 25 lks S. of Sublette County Road 23-125, graded surface, 35 lks. wide, bears E. and W.

From this cor. point, the cor. position for the closing cor. of secs. 3 and 4, established by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, monumented with an iron post, 2½ ins. diam., flush with the surface of the ground, with a small imbedded mound of stones, S., bears S. 75° 46' W., 9.1 lks. dist., with brass cap mkd.

PAUL N. SCHERBEL RLS 164 BIG PINEY WYOMING
T33N R108W
S35

S 4		S 3
CC		
T32N R108W		
1971		

This cor. position was determined utilizing an erroneous measurement and is not accepted as a careful and faithful reestablishment of the original cor. position. When notified of this miscalculation Paul N. Scherbel removed his monument from this location. In an effort to perpetuate this position, because it had been used by at least one prior local survey, a steel reinforcement rod, 24 ins. long, ⅝ in. diam., was set 24 ins. in the ground, at the former Scherbel cor. position.

From this same cor. point, the standard 1/4 sec. cor. of sec. 35 bears S. 89° 44' E., 5.195 chs. dist., hereinbefore described.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>(Restoring the Survey executed by Franklin O. Sawin in 1890)</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16, hereinbefore described.</p> <p>N. 89° 38' W., bet. secs. 9 and 16.</p> <p>39.765 Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist., there is no remaining evidence of the original cor..</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, in an imbedded collar of stone, over a plastic coated magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R108W S 9 1/4 ——— S 16 2003</p> </div> <p>Set a steel fence post nearby.</p> <p>47.70 Center of U.S. Highway 191, asphalt surface, 36 lks. wide, bears SE. and NW.</p> <p>79.53 The cor. of secs. 8, 9, 16 and 17, reestablished by Floyd Bishop, Wyoming Professional Engineer and Registered Land Surveyor No. 303, monumented with a sandstone, 8x7 ins., firmly set, projecting 4 ins. above ground, in a rubber tire, with a steel fence post nearby, plainly mkd. FB ("F" reversed and adjoining "B") on the N. face, with 4 grooves on the E. face, and 4 grooves on the S. face.</p> <p>This is accepted as a careful and faithful reestablishment of the original cor. position. Cor. point not remonumented.</p> <p>The cor. is located on boggy ground.</p> <hr/> <p>N. 0° 01' W., bet. secs. 8 and 9.</p> <p>Over level terrain.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.82	Steel reinforcement rod set by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625 for a reference monument, $\frac{5}{8}$ in. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd. RP 400 W 1/4 S9 and an arrow pointing to the left, bears EAST, 7.48 chs. dist.
39.84	Steel reinforcement rod set by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625 for a reference monument, $\frac{5}{8}$ in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. RP 450 W 1/4 S9, bears EAST, 6.73 chs. dist.
40.19	Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist., there is no remaining evidence of the original cor.. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, over a plastic coated magnet, with brass cap mkd. <div style="text-align: center;"> T32N R108W 1/4 S 8 S 9 2003 </div> Set a steel fence post alongside the stainless steel post. From this cor. point, the point for the 1/4 sec. cor. of secs. 8 and 9, determined by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625, computed from Harrower's reference monuments, bears S. $71^{\circ} 25' E.$, 70.4 lks. dist. This cor. point was established using improper procedures and is not utilized in the course of this resurvey.
40.45	Right bank of old side channel of the New Fork River, now the S. edge of a slough, bears E. and W.
41.05	Left bank of old side channel of the New Fork River, now the N. edge of a slough, bears E. and W.
44.00	Base of bluff, bears irregularly E. and W. Thence ascend steep south slope.
45.70	Top of bluff, bears irregularly E. and W.
45.71	4 strand barbed wire fence, bears E. and W.
57.25	Center of U.S. Highway 191, asphalt surface, 36 lks. wide, bears SE. and NW.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS																					
79.93	Wooden rail fence, bears E. and W.																				
80.38	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist., there is no remaining evidence of the original cor..</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, over a plastic coated magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T32N</td> <td style="padding: 0 5px;">R108W</td> <td></td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">5</td> <td style="border-left: 1px solid black; padding: 0 5px;">S</td> <td style="padding: 0 5px;">4</td> </tr> <tr> <td colspan="4" style="border-top: 1px solid black;"></td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">8</td> <td style="border-left: 1px solid black; padding: 0 5px;">S</td> <td style="padding: 0 5px;">9</td> </tr> <tr> <td colspan="4" style="text-align: center; padding-top: 5px;">2003</td> </tr> </table> </div> <p>Set a steel fence post nearby.</p> <p>The cor. is located on open, level ground.</p> <p>From this cor. point, a steel reinforcement rod of unknown origin, 5/8 in. diam., loosely set, projecting 3 ins. above ground, no cap or tag, with the remnants of an old wooden fence cor. nearby, bears S. 69° 54' E., 1.36 chs. dist. Reinforcement rod is in the projection of a new 4 strand barbed wire fence, extending SW.</p> <p>From this same cor. point, a steel reinforcement rod of unknown origin, ½ in. diam., firmly set, projecting 1 in. above ground, no cap or tag, with the remnants of an old rotted cedar post buried alongside, bears S. 70° 42' E., 1.40 chs. dist. This rod was accepted as the best available evidence of the cor. of secs. 4, 5, 8 and 9, by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625, in 1980 and utilized to resurvey and subdivide sec. 8. Since the origin of this reinforcement rod could not be determined through examination of local survey records or interviews with local landowners and surveyors; it's position cannot be reconciled to adjacent original and accepted local cor.s; and the loose, unmarked sandstone cited by Harrower could not be located, it was not utilized in the course of this resurvey. Reinforcement rod is in the projection of a new wooden rail fence, extending N., and an older 4 strand barbed wire fence, extending S.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 3, 4, 9 and 10, hereinbefore described.</p> <p>N. 89° 34' W., bet. secs. 4 and 9.</p> <p>Over flat terrain, across a hay meadow.</p>	T32N	R108W			S	5	S	4					S	8	S	9	2003			
T32N	R108W																				
S	5	S	4																		
S	8	S	9																		
2003																					

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
10.45	Center of Sublette County Road 23-104, graded surface, 35 lks. wide, bears NNW. and SSE.
27.90	Center of Boulder Creek, 90 lks. wide, course SE.
39.58	Old 6 strand barbed wire fence, bear N. and S.
39.81	New 5 strand barbed wire fence, bears N. and S.
	Thence across a hay meadow.
39.98	Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist., there is no remaining evidence of the original cor..
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, over a plastic coated magnet, with brass cap mkd.
	<p style="text-align: center;">T32N R108W S 4 1/4 ——— S 9 2003</p>
	The cor. is located in a hay meadow.
	From this cor. point, the cor. position of the 1/4 sec. cor. of secs. 4 and 9, established by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with a steel fence post nearby, and aluminum cap mkd. RIO VERDE ENGR PINEDALE WY T32N R108W 1/4 S4 S9 PELS 625 1984 bears S. 72° 18' E., 1.03 chs. dist. This cor. position was established using improper procedures and is not utilized in the course of this resurvey.
48.00	Base of bluff, bears irregularly NNE. and SSW.
	Thence ascend steep E. slope of bluff.
52.00	Top of bluff, bears irregularly NNW. and SSE.
59.97	Point for the W 1/16 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a plastic coated magnet, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T32N R108W S 4 W 1/16 ——— S 9 2003
	Set a steel fence post nearby.
	From this cor. point, a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, no cap or tag, bears S. 70° 55' E., 1.20 chains dist.
	The cor. is located on open sagebrush covered ground.
67.65	Center of B.L.M. Road 5106, graded surface, 30 lks. wide, bears NW. and SE.
79.96	The cor. of secs. 4, 5, 8 and 9.
<hr/> (Restoring the Survey executed by William S. Adams in 1908) <hr/>	
	N. 0° 17' W., bet. secs. 4 and 5.
	Over level terrain.
38.28	A concrete post, 6 ins. diam., firmly set, leaning, projecting 9 ins. above ground, with a standard U.S. Bureau of Reclamation brass tablet set in the top, mkd. R US ABOVE SEA LEVEL DATUM FEET with a cross and punch mark in the center, bears EAST, 1.8 lks. dist.
40.19	The 1/4 sec. cor. of secs. 4 and 5, monumented with a sandstone, 15x8x6 ins., firmly set, projecting 7 ins. above ground, plainly mkd. 1/4 on the W. face, and witnessed by a scattered mound of stone W. of cor.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, in a collar of stone, over a plastic coated magnet, with brass cap mkd.
	T32N R108W 1/4 S 5 S 4 2003

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>37.47</p>	<p>Bury the original stone alongside the stainless steel post, and set a steel fence post nearby.</p> <p>The cor. is located 1 lk. E. of a 4 strand barbed wire fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 01' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>The closing cor. of secs. 4 and 5, at intersection with the Eighth Standard Parallel North, monumented with a sandstone, 11x8x5 ins., firmly set, projecting 3 ins. above ground, plainly mkd. with 4 notches on E. edge, CC on the S. face, and with 2 notches on W. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, over a plastic coated magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T33N R108W S 34</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S 5 S 4 T32N R108W CC 2003</p> </div> <p>Bury the original stone alongside the stainless steel post.</p> <p>The cor. is located at the SE. side of a wooden fence cor., 4 strand barbed wire fences extend S. and W.</p> <p>From this cor. point, the standard 1/4 sec. cor. of sec. 34 bears S. 89° 37' E., 5.285 chs. dist., hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Point for the 1/4 sec. cor. of sec. 4 only, determined at midpoint on the N. boundary of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, over a bundle of 60D common nails, with brass cap mkd.</p>
----------------------------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T33N R108W</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 4 T32N R108W 2003</p> <p>From this cor. point, the standard cor. of secs. 34 and 35 bears S. 89° 29' E, 5.255 chs. dist., hereinbefore described.</p> <hr style="width: 20%; margin: auto;"/> <p>Point for the W 1/16 sec. cor. of sec. 4 only, determined at midpoint between the closing cor. of secs. 4 and 5 and the 1/4 sec. cor. of sec. 4 only, on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, over a bundle of 60D common nails, with brass cap mkd.</p> <p style="text-align: center;">T33N R108W</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">W 1/16 S 4 T32N R108W 2003</p> <p>From this cor. point, the standard 1/4 sec. cor. of sec. 34 bears N. 89° 29' .W, 14.70 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">(Restoring the Survey executed by Franklin O. Sawin in 1890)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 8, 9, 16 and 17, hereinbefore described.</p> <p>N. 89° 30' W., bet. secs. 8 and 17.</p> <p>Over level terrain.</p> <p>2.06 Center of County Road 23-136, graded surface, bears NNE. and SSW.</p> <p>39.96 The 1/4 sec. cor. of secs. 8 and 17, reestablished by Floyd Bishop, Wyoming Professional Engineer and Registered Land Surveyor No. 303, monumented with a granite stone, 16x11x3 ins., firmly set, projecting 1 in. above ground, with a wooden fence cor. lying nearby, plainly mkd. 1/4 on N. face, and FB ("F" reversed and adjoining "B") on S. face. This is accepted as a careful and faithful reestablishment of the original cor. position.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, over a plastic coated magnet, with brass cap mkd.
	<p style="text-align: center;">T32N R108W S 8 1/4 ——— S 17 2003</p>
	Bury the Bishop stone alongside the iron post.
	The cor. is located in an open pasture, 35 lks. S. of an irrigation ditch, 20 lks. wide, 4 ft. deep, course SE.
	<hr style="width: 20%; margin: auto;"/> <p>N. 89° 31' W., beginning new measurement.</p>
	Over level terrain.
3.17	Center of Last Chance Ditch, 20 lks. wide, 4 ft. deep, course SSE.
15.50	Center of Paradise Ditch road, bears SSE. and NNW.
18.00	Center of graded road, bears SE. and NW.
19.97	Point for the W 1/16 sec. cor. of secs. 8 and 17.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a plastic coated magnet, with brass cap mkd.
	<p style="text-align: center;">T32N R108W S 8 W 1/16 ——— S 17 2003</p>
	Set a steel fence post nearby.
39.94	The cor. of secs. 7, 8, 17 and 18, perpetuated by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with a rubber tire and steel fence post nearby, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS																					
	<p>PAUL N. SCHERBEL RLS 164 BIG PINEY WYOMING</p> <p>T32N R108W</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">S 7</td> <td style="padding: 2px;">S 8</td> </tr> <tr> <td style="padding: 2px;">S 18</td> <td style="padding: 2px;">S 17</td> </tr> </table> <p style="text-align: center;">1981</p> <p>This is accepted as a careful and faithful perpetuation of the original cor. position. Cor. point not remonumented.</p> <p>The cor. is located 45 lks. S. of the center of a graded road surface, bears E. and W.</p> <hr/> <p style="text-align: center;">(Restoring the Retracement executed by William S. Adams in 1908)</p> <hr/> <p>N. 0° 08' W., bet. secs. 7 and 8.</p> <p>Over level terrain.</p> <p>19.95 Trail road, bears ESE. and WNW.</p> <p>20.315 Point for the S 1/16 sec. cor. of sec. 7 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="padding: 2px;">T32N R108W</td> </tr> <tr> <td style="padding: 2px;">S 1/16</td> <td style="padding: 2px;"> </td> </tr> <tr> <td style="padding: 2px;">S 7</td> <td style="padding: 2px;"> </td> </tr> <tr> <td colspan="2" style="padding: 2px;">2003</td> </tr> </table> <p>Set a steel fence post alongside the stainless steel post.</p> <p>20.47 Point for the S 1/16 sec. cor. of sec. 8 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="padding: 2px;">T32N R108W</td> </tr> <tr> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 1/16</td> </tr> <tr> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 8</td> </tr> <tr> <td colspan="2" style="padding: 2px;">2003</td> </tr> </table>	S 7	S 8	S 18	S 17	T32N R108W		S 1/16		S 7		2003		T32N R108W			S 1/16		S 8	2003	
S 7	S 8																				
S 18	S 17																				
T32N R108W																					
S 1/16																					
S 7																					
2003																					
T32N R108W																					
	S 1/16																				
	S 8																				
2003																					

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.94	<p>Set a steel fence post alongside the stainless steel post.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the original cor..</p> <p>Note: 1980 retracement distances to the original stone, recorded by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625, on file in the Sublette County Courthouse in Pinedale, Wyoming, were utilized to determine this point.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a plastic coated magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T32N R108W 1/4 S 7 S 8 2003 </div> <p>Set a steel fence post nearby and raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p> <p>The cor. is located 55 lks. E. of Paradise Ditch Road, bears SSE. and NNW.</p>
80.59	<p>The cor. of secs. 5, 6, 7 and 8, perpetuated by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> PAUL N. SCHERBEL RLS 164 BIG PINEY WYOMING T32N R108W S 6 S 5 ----- S 7 S 8 1964 </div> <p>This is accepted as a careful and faithful perpetuation of the original cor. position. Cor. point not remonumented.</p> <p>The cor. is located in a 3 strand barbed wire fence, bears N. and S.</p> <hr style="width: 60%; margin: 20px auto;"/> <div style="text-align: center; margin: 10px auto;"> (Restoring the Survey executed by Franklin O. Sawin in 1890) </div> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 4, 5, 8 and 9, hereinbefore described.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 89° 21' W., bet. secs. 5 and 8.
	Over level terrain.
22.00	E. right-of-way fence of U.S. Highway 191, bears SE. and NW.
23.70	Center of U.S. Highway 191, asphalt surface, 36 lks. wide, bears SE. and NW.
25.35	W. right-of-way fence of U.S. Highway 191, bears SE. and NW.
39.40	Top of bluff, bears SSE. and NNW.
	Thence descend gentle west slope.
40.03	Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist., there is no remaining evidence of the original cor..
	Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, over a plastic coated magnet and 5 ft. long steel fence post, with brass cap mkd.
	<div style="text-align: center;"> <p>T32N R108W</p> <p>S 5</p> <p>1/4 ———</p> <p>S 8</p> <p>2003</p> </div>
	Set a steel fence post nearby.
	The cor. is located on the gentle W. slope of a low bluff.
	From this cor. point, the cor. position of the 1/4 sec. cor. of secs. 5 and 8, established by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with a steel fence post nearby, and aluminum cap mkd. RIO VERDE ENGR PELS 625 bears S. 70° 49' E., 69.8 lks. dist. This cor. position was established using improper procedures and is not utilized in the course of this resurvey.
41.40	Base of bluff, bears SE. and NW.
80.06	The cor. of secs. 5, 6, 7 and 8, hereinbefore described.
	<hr/>
	N. 0° 01' W., bet. secs. 5 and 6.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over level terrain.
18.03	Steel reinforcement rod, $\frac{5}{8}$ in. diam., firmly set, projecting 1 in. above ground, with an aluminum cap mkd. RIO VERDE ENGR PELS 625. Reinforcement rod is located 1 lk. W. of a fence cor., 4 strand barbed wire fences extend N., E. and S.
	Thence along a barbed wire fence
20.04	An iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. PAUL N. SCHERBEL RLS 164 BIG PINEY WYOMING T32N R108W S 1/16 S6 S5 1964. Iron post is located 1 lk. W. of a 4 stand barbed wire fence, bears N. and S.
40.00	The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, reestablished by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, witnessed by a mound of stone, 2 ft. base, 1 ft. high, W., with brass cap mkd.
	<p style="text-align: center;">PAUL N. SCHERBEL RLS 164 BIG PINEY WYOMING T32N R108W 1/4 S 6 S 5 1964</p>
	This is accepted as a careful and faithful reestablishment of the original cor. position. Cor. point not remonumented.
	The cor. is located 1 lk. W. of a 4 strand barbed wire fence, bears N. and S.
	<p style="text-align: center;">(Restoring the Survey executed by William S. Adams in 1908)</p>
	N. $0^{\circ} 09'$ W., beginning new measurement.
	Over level terrain, along a barbed wire fence.
9.35	S. right -of-way fence of U.S. Highway 191, bears SE. and NW.
10.85	Center of U.S. Highway 191, asphalt surface, 36 lks. wide, bears SE. and NW.
12.35	N. right-of-way fence of U.S. Highway 191, bears SE. and NW.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS			
20.00	<p>An iron post, 2½ ins. diam., 30 ins. long, bent and flattened, 5 ins. below the surface of the ground, with brass cap mkd. PAUL N. SCHERBEL RLS 164 B (mks. obliterated) Y WYOMING T32N R (mks. obliterated) N 1/16 S6 S5 1964. At the request of Paul N. Scherbel, reset the iron post, 3 ins. below the surface of the ground, over a plastic coated magnet, and set a steel fence post nearby.</p>		
37.325	<p>The closing cor. of secs. 5 and 6, at intersection with the Eighth Standard Parallel North, monumented with a sandstone, 13x7x5 ins., 12 ins. below the surface of the ground, plainly mkd. with 5 grooves on E. face, CC on S. face, and with 1 groove on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, over a plastic coated magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R108W S 33</p> <hr style="width: 10%; margin: auto;"/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> </table> <p>T32N R108W CC 2003</p> </div> <p>Bury the original stone alongside the stainless steel post.</p> <p>The cor. is located on the N. side of a dry irrigation ditch, bears E. and W.</p> <p>From this cor. point, the standard 1/4 sec. cor. of sec. 33 bears S. 89° 47' E., 5.25 chs. dist., hereinbefore described.</p> <hr style="width: 80%; margin: 20px auto;"/> <div style="text-align: center;"> <p>Subdivision of Section 4, T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming</p> <hr style="width: 30%; margin: auto;"/> </div> <p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0° 10' W., on the N. and S. center line of sec. 4.</p>	S 6	S 5
S 6	S 5		
40.10	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground over a plastic coated magnet, with brass cap mkd.</p>		

Subdivision of Section 4,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T32N R108W C 1/4 S 4 2003
	<p>Cor. is located in a pasture, 27 lks. W. of a trail road, bears N. and S., and 46 lks. W. of a 4 strand barbed wire fence, bears N. and S.</p> <p>From this cor. point, the cor. position of the center 1/4 sec. cor. of sec. 4, established by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with aluminum cap mkd. RIO VERDE ENGR T32N R108W C 1/4 S4 PELS 625 1984 bears S. 82° 27' E., 45.4 lks. dist. This cor. position was established using improper procedures and is not utilized in the course of this resurvey.</p>
77.60	<p>The 1/4 sec. cor. of sec. 4 only.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>N. 89° 27' W., on the E. and W. center line of sec. 4.</p>
39.98	<p>The center 1/4 sec. cor. of sec. 4.</p>
60.01	<p>Point for the center W 1/16 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground over a plastic coated magnet, with brass cap mkd.</p> <p style="text-align: center;"> T32N R108W W 1/16 C ————— C S 4 2003 </p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 23 lks. W. of a 4 strand barbed wire fence, bears N. and S.</p>

Subdivision of Section 4,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From this cor. point, the cor. position of the center W 1/16 sec. cor. of sec. 4, established by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd. RIO VERDE PELS 625 bears S. 82° 29' E., 22.5 lks. dist. This cor. position was established using improper procedures and is not utilized in the course of this resurvey.
80.04	The 1/4 sec. cor. of secs. 4 and 5.
	From the W 1/16 sec. cor. of secs. 4 and 9. N. 0° 13' W., on the N. and S. center line of the SW1/4 of sec. 4.
40.15	The center W 1/16 sec. cor. of sec. 4.
	From the center W 1/16 sec. cor. of sec. 4. N. 0° 05' W., on the N. and S. center line of the NW1/4 of sec. 4.
37.49	The W 1/16 sec. cor. of sec. 4 only.
<p>Subdivision of Section 5, T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming</p>	
	From the 1/4 sec. cor. of secs. 5 and 8. N. 0° 08' W., on the N. and S. center line of sec. 5.
13.24	S. right-of-way fence of U.S. Highway 191, bears SE. and NW.
14.76	Center of U.S. Highway 191, asphalt surface, 36 lks. wide, bears SE. and NW.
16.28	N. right-of-way fence of U.S. Highway 191, bears SE. and NW.
39.51	A wooden fence cor., 5 strand barbed wire and wire mesh fences extending E. and S., bears EAST, 32 lks. dist.
39.64	A bridge spike, set flush with the surface of the ground, bears EAST, 32.4 lks. dist.

Subdivision of Section 5,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.09	<p>Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground over a plastic coated magnet, with brass cap mkd.</p> <p style="text-align: center;">T32N R108W</p> <p style="text-align: center;">C 1/4 S 5</p> <p style="text-align: center;">2003</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 29 lks. N. of the center of Dale Road, graded gravel surface, 27 lks. wide, bears E. and W.</p>
50.06	<p>Steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with aluminum cap mkd. RIO VERDE PELS 625, witnessed by a mound of concrete, 5 ft. base, 3 ft. high, N. of the reinforcement rod, bears EAST., 23.4 lks. dist.</p>
77.48	<p>The 1/4 sec. cor. of sec. 5 only, determined by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd. RIO VERDE PELS. This is accepted as a careful and faithful determination of the position of the cor.. Add the mks. AM, and bury the reinforcement rod 1 in. below the surface of the ground.</p>
77.485	<p>Point for the 1/4 sec. cor. of sec. 5 only, at intersection with the Eighth Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a plastic coated magnet, with brass cap mkd.</p> <p style="text-align: center;">T33N R108W</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 5</p> <p style="text-align: center;">T32N R108W</p> <p style="text-align: center;">2003</p> <p>The cor. is located 3 lks. N. of a 3 strand barbed wire fence, bears E. and W.</p>

Subdivision of Section 5,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From this cor. point, the standard cor. of secs. 33 and 34 bears S. 89° 34' E., 5.32 chs. dist., hereinbefore described.
	From the 1/4 sec. cor. of secs. 4 and 5. N. 89° 30' W., on the E. and W. center line of sec. 5.
19.81	4 strand barbed wire fence, bears N. and S.
19.96	Point for the center E 1/16 sec. cor. of sec. 5. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground over a plastic coated magnet, with brass cap mkd.
	T32N R108W E 1/16 C ————— C S 5 2003
	Set a steel fence post nearby. Cor. is located 1 lk. N. of a wire mesh fence, bears E. and W.
29.70	Bent steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with aluminum cap mkd. RIO VERDE PELS, bears NORTH, 0.5 lk. dist.
39.92	The center 1/4 sec. cor. of sec. 5.
66.22	E. right-of-way fence of U.S. Highway 191, bears SE. and NW.
67.90	Center of U.S. Highway 191, asphalt surface, 36 lks. wide, bears SE. and NW.
69.58	W. right-of-way fence of U.S. Highway 191, bears SE. and NW.
79.87	The 1/4 sec. cor. of secs. 5 and 6.
	From the center E 1/16 sec. cor. of sec. 5. N. 0° 05' W., on the N. and S. center line of the NE1/4 of sec. 4.

Subdivision of Section 5,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
28.42	NW. cor. of a concrete post, 5 1/2 ins. square, 4 ft. high, with bronze tablet mkd. GRAVE MARKER INFANT CHILD OF GEO. DE NISE 1911 SUBLETTE COUNTY HISTORICAL BOARD, bears EAST, 2.31 chs. dist.
37.43	<p>Point for the E 1/16 sec. cor. of sec. 5 only, at intersection with the Eighth Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a plastic coated magnet, with brass cap mkd.</p> <p style="text-align: center;">T33N R108W</p> <p style="text-align: center;">E 1/16 S 5 T32N R108W 2003</p> <p>The cor. is located in a 4 strand barbed wire fence, bears E. and W.</p> <p>From this cor. point, the E 1/16 sec. cor. of sec. 5 only, determined by Robert A. Harrower, Wyoming Professional Engineer and Registered Land Surveyor No. 625, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd. RIO VERDE PELS, bears . N. 0° 05' W., 0.5 lk. dist. This is accepted as a careful and faithful determination of the position of the cor. Add the mks. AM, and bury the reinforcement rod 1 in. below the surface of the ground.</p> <p>From this same cor. point, the standard cor. of secs. 33 and 34 bears N. 89° 37' W, 14.67 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Section 8, T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 17.</p> <p>N. 0° 04' W., on the N. and S. center line of sec. 8.</p>
20.28	<p>Point for the center S 1/16 sec. cor. of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground over a plastic coated magnet, with brass cap mkd.</p>

Subdivision of Section 8,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T32N R108W C S 1/16 S 8 C 2003
	<p>Set a steel fence post alongside the stainless steel post.</p> <p>Cor. is located in an open pasture.</p>
40.56	<p>Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground over a plastic coated magnet, with brass cap mkd.</p>
	T32N R108W C 1/4 S 8 2003
	<p>Set a steel fence post nearby.</p> <p>Cor. is located 60 lks. W. of the right bank of the New Fork River, approximately 1.60 chs. wide, course SSW.</p> <p>From this cor. point, an iron pipe fence cor., 6 ins. diam., 48 ins. high, braided steel cable extends N., bears S. 73° 44' E., 35.6 lks. dist.</p>
60.36	<p>Iron pipe 2½ ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T32N R108W C-N 1/16 S8 1977 PELS 659, bears East, 50.2 lks. dist.</p>
80.48	<p>The 1/4 sec. cor. of secs. 5 and 8.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 8 and 9.</p> <p>N. 88° 58' W., on the E. and W. center line of sec. 8.</p>
40.00	<p>The center 1/4 sec. cor. of sec. 8.</p>
59.995	<p>Point for the center W 1/16 sec. cor. of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground over a plastic coated magnet, with brass cap mkd.</p>

Subdivision of Section 8,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T32N R108W W 1/16 C ————— C S 8 2003
	Set a steel fence post nearby. Cor. is located in a boggy pasture, 10 lks. N. of an irrigation ditch, 12 lks. wide, 1 ft. deep, course E.
79.99	The 1/4 sec. cor. of secs. 7 and 8. SW1/4 of Section 8 From the W 1/16 sec. cor. of secs. 8 and 17. N. 0° 06' W., on the N. and S. center line of the SW1/4 of sec. 8.
20.375	Point for the SW 1/16 sec. cor. of sec. 8, at intersection with the E. and W. center line of the SW1/4 of sec. 8. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground over a plastic coated magnet, with brass cap mkd.
	T32N R108W SW 1/16 S 8 2003
40.75	Set a steel fence post nearby. Cor. is located 6 lks. N. of a 4 strand barbed wire fence, bears E. and W. The center W 1/16 sec. cor. of sec. 8. <hr/> From the center S 1/16 sec. cor. of sec. 8. N. 89° 14' W., on the E. and W. center line of the SW1/4 of sec. 8.

Subdivision of Section 8,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	
19.985	The SW 1/16 sec. cor. of sec. 8.
39.97	The S 1/16 sec. cor. of sec. 8 only.
<hr/> Subdivision of Section 9, T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming <hr/>	
	From the 1/4 sec. cor. of secs. 9 and 16.
	N. 0° 09' E., on the N. and S. center line of sec. 9.
40.17	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line of sec. 9.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground over a plastic coated magnet, with brass cap mkd.
	T32N R108W
	C 1/4 S 9
	2003
	Set a steel fence post nearby.
	Cor. is located in an aspen grove, in a cluster of Circle 9 Ranch guest cabins.
80.34	The 1/4 sec. cor. of secs. 4 and 9.
<hr/> From the 1/4 sec. cor. of secs. 9 and 10. <hr/>	
	N. 89° 36' W., on the E. and W. center line of sec. 9.
39.87	The center 1/4 sec. cor. of sec. 9.
59.805	Point for the center W 1/16 sec. cor. of sec. 9.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground over a plastic coated magnet, with brass cap mkd.

Subdivision of Section 9,
T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>T32N R108W W 1/16 C ————— C S 9 2003</p>
	<p>Set a steel fence post nearby.</p> <p>Cor. is located 60 lks. W. of a 4 strand barbed wire fence, bears N. and S.</p> <p>From this cor. point, the cor. position of the center W 1/16 sec. cor. of sec. 9, established by Robert A. Harrower, Wyoming Professional Engineer and Licensed Land Surveyor No. 625, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, flush with the surface of the ground, in a 4 strand barbed wire fence, bears N. and S., with aluminum cap mkd. RIO VERDE PELS 625 bears S. 71° 10' E., 59.9 lks. dist. This cor. position was established using improper procedures and is not utilized in the course of this resurvey.</p>
79.74	<p>The 1/4 sec. cor. of secs. 8 and 9.</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 9.</p> <p>N. 0° 04' E., on the N. and S. center line of the NW1/4 of sec. 9.</p>
40.18	<p>The W 1/16 sec. cor. of secs. 4 and 9.</p> <hr/>

T. 32 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area encompassed by this survey is situated in the south central portion of Sublette County, approximately one mile northwest of Boulder, Wyoming and 9 miles southeast of Pinedale, Wyoming. The terrain varies from level to gently rolling to steep, with an average elevation of 7,000 feet above sea level. The soil is a mixture of sand, sandy loam, and loam with scattered areas of exposed sandstone bedrock. Natural vegetation is primarily sagebrush, cacti, and sparse native grasses with isolated stands of pine. Both cottonwoods and willows grow along Boulder Creek and the New Fork River.</p> <p>The principal water sources in Sections 4, 5, 8 and 9 are the New Fork River, Boulder Creek, and various irrigation ditches. Stock raising and evidence of hay growing were observed during the course of this survey, and numerous permanent residences exist in all sections.</p> <p>Primary access is provided by Wyoming State Highway No. 191, then B.L.M. Road No. 5106 and Sublette County Road 23-104, secondary access is via numerous graded roads which are utilized to access subdivisions and residences.</p>
--------	---

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
Kathi A. Fine	Surveying Technician
Steven Harrison	Surveying Technician

CERTIFICATE OF SURVEY

I, Olian T. Shockley, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of July, 2003, I have dependently resurveyed a portion of the Eighth Standard Parallel North, through Range 108 West, and a portion of the subdivisional lines, and the subdivision of sections 4, 5, 8 and 9, Township 32 North, Range 108 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

AUG 3 0 2004

(Date)

Olian T. Shockley
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of a portion of the Eighth Standard Parallel North, through Range 108 West, and a portion of the subdivisional lines, and the subdivision of sections 4, 5, 8 and 9, Township 32 North, Range 108 West,, of the Sixth Principal Meridian, in the State of Wyoming, executed by Olian T. Shockley, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

AUG 3 0 2004

(Date)

John P. Lee
(Signature of Authorized Officer)