

**ORIGINAL**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD NOTES**

OF THE  
DEPENDENT RESURVEY  
OF A PORTION OF  
THE SUBDIVISIONAL LINES  
AND THE  
SUBDIVISION OF SECTIONS 7, 17 AND 18,  
TOWNSHIP 14 NORTH, RANGE 84 WEST,  
OF THE SIXTH PRINCIPAL MERIDIAN,  
IN THE STATE OF WYOMING.

**EXECUTED BY**

LYNN A. FORBES

CADASTRAL SURVEYOR

Under Special Instructions dated OCTOBER 5 1999, approved OCTOBER 5 1999, which provided for the surveys included under Group Number 667, and assignment instructions dated OCTOBER 5, 1999.

Survey commenced OCTOBER 13, 1999

Survey completed JUNE 29, 2000

INDEX DIAGRAM

Township 14 North, Range 84 West

6	5	4	3	2	1
7	8	9	10	11	12
5	6 4				
18	3 17	2 16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 7.....Page 7  
 Subdivision of Section 17.....Page 10  
 Subdivision of Section 18.....Page 14

## T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 7, 17 and 18, Township 14 North, Range 84 West, of the Sixth Principal Meridian, Wyoming.

William O. Downey surveyed the west boundary in 1879. Franklin O. Sawin surveyed a portion of the subdivisional lines in 1889. Howard B. Carpenter retraced a portion of the west boundary in 1898. Thomas W. Crawford remonumented the 1/4 sec. cor. of secs. 7 and 12, and the cor. of secs. 13, 18, 19 and 24, on the west boundary of the township in 1960. William H. Herbst dependently resurveyed portions of the west boundary and subdivisional lines, and subdivided certain sections in 1977.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 667, Wyoming, dated October 5, 1999.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. All corners of the 1977 dependent resurvey were found to be in good condition. The retracement data was thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

The survey was executed with a Global Positioning System (GPS) TRIMBLE Model 4700 receiver, and by chaining methods. The instruments were maintained in proper adjustment at all times. The direction of all lines refer to the true meridian. All distances and the geographic position were determined by Global Positioning System methods.

The geographic position of the 1/4 sec. cor. of secs. 16 and 17, based on NAD 83(1993) and determined by Global Positioning Systems methods is:

Latitude 41° 10' 55.38" N., Longitude 106° 51' 18.66" W.

The magnetic declination is 11¾° E.

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>(Restoring the survey executed by William H. Herbst in 1977)</p> <hr/> <p>Beginning at the 1/4 sec. cor. of secs. 16 and 17, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 2 ft. base to top, with a mound of stone, 2 ft. base, 2 ft. high, W. of the cor., with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W 1/4 S 17   S 16 1977</p> <p>Cor. is located in fence extending N. and S. on steep S. slope. N. 0° 24' W., bet. secs. 16 and 17. Over rolling and broken terrain.</p>
19.93	<p>The N. 1/16 sec. cor. of secs. 16 and 17, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with mound of stone, 2 ft. base, 1 ft. high, W. of the cor., with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W N1/16 S 17   S 16 1977</p> <p>Cor. is located 8 lks. E, of fence extending N. and S.</p> <hr/> <p>N. 0° 24' W., beginning new measurement. Over rolling and broken terrain.</p>
13.00	<p>Wyoming State Highway No. 70, bears NE. and SW.</p>
19.93	<p>The cor. of secs. 8, 9, 16 and 17, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with a mound of stone, 2 ft. base, 2 ft. high, W. of the cor, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W S 8   S 9 <hr/>S 17   S 16 1977</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Cor. is located at intersection of fences extending N., E. and WNW.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W 1/4 S 18   S 17 1977</p> <p>N. 0° 49' E., bet. secs. 17 and 18.</p> <p>Over rolling terrain.</p> <p>19.96 The N. 1/16 sec. cor. of secs. 17 and 18, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 4 ft. base to top, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W N1/16 S 18   S 17 1977</p> <hr/> <p>N. 0° 52' E., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>19.88 The cor. of secs. 7, 8, 17 and 18, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W S 7   S 8 ----- S 18   S 17 1977</p> <p>from which the 1977 bearing trees</p> <p style="text-align: center;">A fir, 12 ins. diam., bears N. 78° E., 3 lks. dist., mkd. T14N R84W S8 BT on a partially healed blaze.</p>
--------	--

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>A fir, 14 ins. diam., bears S. 66° W., 17 lks. dist., mkd. T14N R84W S18 BT on a partially healed blaze.</p> <p>An aspen, 8 ins. diam., bears N. 63° W., 24 lks. dist., mkd. T14N R85W S7 BT .</p>
	<hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89° 35' W., bet. secs. 8 and 17.</p> <p>Over rolling terrain along fence.</p>
20.14	<p>The E. 1/16 sec. cor. of secs. 8 and 17, monumented with an aluminum post, 2½ ins. diam., firmly set 8 ins. below the surface of the ground, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W S 8 E1/16 ——— S 17 1977</p>
	<p>Cor. is located at base of dam of small reservoir.</p> <hr/> <p>S. 89° 37' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
20.15	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W S 8 1/4 ——— S 17 1977</p>
	<hr/> <p>S. 89° 56' W., beginning new measurement.</p> <p>Over rolling terrain.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
19.75	<p>The W. 1/16 sec. cor. of secs. 8 and 17, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with a mound of stone, 2 ft. base, 2 ft. high, N. of the cor., with a steel fence post alongside, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W S 8 W1/16— S 17 1977</p> <p>No remains of the 1977 bearing trees were found.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 52' W., beginning new measurement.</p> <p>Over rolling terrain, through scattered pine and aspen timber.</p>
19.76	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr style="width: 50%; margin: auto;"/> <p>N. 89° 52' W., bet. secs. 7 and 18.</p> <p>Over rolling terrain, through scattered timber.</p>
19.64	<p>The E. 1/16 sec. cor. of secs. 7 and 18, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W S 7 E1/16— S 18 1977</p> <p>from which the 1977 bearing trees</p> <p style="padding-left: 40px;">A pine stump, 10 ins. diam., bears N. 17° E., 21 lks. dist.</p> <p style="padding-left: 40px;">A aspen, 10 ins. diam., bears S. 46° E., 16 lks. dist., bark scribed E1/16 S18 BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 53' W., beginning new measurement.</p> <p>Over rolling terrain, through scattered timber.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
18.45	Fence, bears N. and S.
19.65	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with a mound of stone, 2 ft. base, 2 ft. high, N. of cor., with a steel fence post alongside, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W S 7 1/4 ——— S 18 1977</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0° 20' E., bet. secs. 7 and 8.</p> <p>Over rolling terrain.</p>
19.93	<p>The S. 1/16 sec. cor. of secs. 7 and 8, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor., with a steel fence post alongside, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W S 1/16 S 7   S 8 1977</p> <hr/> <p>N. 0° 21' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
19.91	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W 1/4 S 7   S 8 1977</p> <hr/>

Subdivision of Section 7,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 7 and 18. N. 0° 17' W., on the N. and S. center line of sec. 7. Over rolling terrain, through scattered timber, along fence.</p>
19.73	<p>Point for the center S. 1/16 sec. cor. of sec. 7. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R84W C S1/16   S 7 C 1999</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears S. 49° E., 33 lks. dist., mkd. C-S 1/16 S7 BT.</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears S. 81° W., 36 lks. dist., mkd. C-S 1/16 S7 BT.</p> <p>Set a steel fence post alongside the iron post. Cor. is located 64 lks. E. of fence extending N. and S.</p>
39.46	<p>Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R84W C1/4 S 7 1999</p> <p>Set a steel fence post alongside the iron post. Cor. is located approximately N. 65½° E., 79 lks. dist., from intersection of fences extending N., S. and W.</p>
59.13	<p>Point for the center N. 1/16 sec. cor. of sec. 7.</p>

Subdivision of Section 7,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T14N R84W C N1/16   S 7 C 1999</p>
	Set a steel fence post alongside the iron post.
	Cor. is located approximately S. 44° E ., 89 lks. dist., from intersection of fences extending E., S. and W.
78.79	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 45 ins. above the ground, with a mound of stone, 2 ft. base, 2 ft. high, N. of cor., with a steel fence post alongside, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T14N R84W S 6 1/4 ——— S 7 1977</p>
	From the 1/4 sec. cor. of secs. 7 and 8.
	S. 89° 35' W., on the E. and W. center line of sec. 7.
	Over rolling terrain.
19.855	Point for the center E. 1/16 sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, supported by a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T14N R84W E1/16 C ——— C S 7 1999</p>
	Set a steel fence post alongside the iron post.
39.71	The center 1/4 sec. cor. of sec. 7; thence along fence.

Subdivision of Section 7,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
81.13	<p>The 1/4 sec. cor. of sec. 7 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N   1/4 S 7   R84W 1977 1960</p> <p>Cor. is located at intersection of fences extending E., S. and W.</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 7 and 18. N. 0° 02' E., on the N. and S. center line of the SE¼ of sec. 7. Over rolling terrain, through scattered timber.</p>
19.82	<p>Point for the SE. 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the SE¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R84W SE 1/16 S 7 1999</p> <p>Set a steel fence post alongside the iron post. Cor. is located on N. edge of aspen grove; thence over rolling terrain.</p>
39.64	<p>The center E. 1/16 sec. cor. of sec. 7.</p> <hr/> <p>From the S. 1/16 sec. cor. of sec. 7 and 8. S. 89° 50' W., on the E. and W. center line of the SE¼ of sec. 7. Over rolling terrain, through scattered timber.</p>

Subdivision of Section 7,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
19.74	The SE. 1/16 sec. cor. of sec. 7.
39.49	The center S. 1/16 sec. cor. of sec. 7.
<p>Subdivision of Section 17, T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming</p>	
<p>From the 1/4 sec. cor. of secs. 17 and 20, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a mound of stone, 4 ft. base, 2 ft. high, N. of the cor., with aluminum cap mkd.</p>	
<p>T14N R84W S 17 1/4 ——— S 20 1977</p>	
<p>N. 0° 15' E., on the N. and S. center line of sec. 17.</p>	
<p>Over rolling terrain, through scattered timber.</p>	
39.13	<p>The center 1/4 sec. cor. of sec. 17, established by Billy W. Raspberry, Wyoming Registered Land Surveyor No. 2926, monumented with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with a steel fence post alongside, with aluminum cap mkd. C1/4 S17 HAS LS 2926. This position is accepted as a careful and faithful determination of the cor. position.</p>
<p>At the corner point</p>	
<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>	
<p>T14N R84W C1/4 S 17 2000</p>	
<p>Deposit the steel reinforcement rod and retain the steel fence post alongside the iron post.</p>	
46.40	Wyoming State Highway No. 70, bears NE. and SW.

Subdivision of Section 17,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
59.00	<p>The center N. 1/16 sec. cor. of sec. 17, established by Billy W. Raspberry, Wyoming Registered Land Surveyor No. 2926, monumented with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, in a collar of stone, with a steel fence post alongside, with aluminum cap mkd. C-N 1/16 HAS LS 2926. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T14N R84W C N1/16   S 17 C 2000</p> <p>Deposit the steel reinforcement rod and retain the steel fence post alongside the iron post.</p>
78.87	<p>The 1/4 sec. cor. of secs. 8 and 17.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>S. 89° 46' W., on the E. and W. center line of sec. 17.</p> <p>Over rolling terrain.</p>
20.37	<p>The center E. 1/16 sec. cor. of sec. 17, established by Billy W. Raspberry, Wyoming Registered Land Surveyor No. 2926, monumented with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with a steel fence post alongside, with aluminum cap mkd. C-E 1/16 HAS LS 2926. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, supported by a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R84W E1/16 C———C S 17 2000</p>

Subdivision of Section 17,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Deposit the steel reinforcement rod and retain the steel fence post alongside the iron post.
40.74	The center 1/4 sec. cor. of sec. 17.
53.75	Wyoming State Highway No. 70, bears NE. and SW.
60.70	Point for the center W. 1/16 sec. cor. of sec. 17.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R84W W1/16 C—C S 17 2000</p>
80.66	The 1/4 sec. cor. of secs. 17 and 18.
	<hr/> <p>From the center E. 1/16 sec. cor. of sec. 17. N. 0° 04' W., on the N. and S. center line of the NE¼ of sec. 17. Over rolling terrain.</p>
18.42	Wyoming State Highway No. 70, bears NE. and SW.
19.90	Point for the NE. 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the NE¼.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R84W NE 1/16 S 17 2000</p>
	<p>Set a steel fence post alongside the iron post.</p> <p>from which A witness cor. established by Billy W. Raspberry, Wyoming Registered Land Surveyor No. 2926, bears WEST, 88 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. WC 58 NE 1/16 HAS LS 2926.</p>

Subdivision of Section 17,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>39.80</p> <p>18.25</p> <p>20.25</p> <p>40.50</p> <p>5.00</p> <p>19.92</p>	<p>The E. 1/16 sec. cor. of secs. 8 and 17.</p> <hr/> <p>From the N. 1/16 sec. cor of secs. 16 and 17.</p> <p>S. 89° 41' W., on the E. and W. center line of the NE¼ of sec. 17.</p> <p>Over rolling terrain.</p> <p>Wyoming State Highway No. 70, bears NE. and SW.</p> <p>The NE. 1/16 sec. cor. of sec. 17.</p> <p>The center N. 1/16 sec. cor. of sec. 17.</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 17.</p> <p>N. 0° 33' E., on the N. and S. center line of the NW¼ of sec. 17.</p> <p>Over rolling terrain.</p> <p>Top of ridge, bears E. and W., enter scattered timber.</p> <p>Point for the NW. 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the NW¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T14N R84W</p> <p style="text-align: center;">NW 1/16 S 17</p> <p style="text-align: center;">2000</p> <p>from which</p> <p style="padding-left: 40px;">An aspen, 12 ins. diam., bears S. 33° W., 5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 48° W., 21 lks. dist., mkd. T14N R84W NW1/16 S17 BT.</p> <p>From this point, a 1 in. diam. iron pipe, firmly set, projecting 8 ins. above the ground, monumented by person(s) unknown, bears N. 22° E., 12 lks. dist. This monument is not utilized during the course of this survey.</p>
--	---

Subdivision of Section 17,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.81	The W. 1/16 sec. cor. of secs. 8 and 17.
	<hr/> <p>From the center N. 1/16 sec. cor. of sec. 17.</p> <p>S. 89° 53' W., on the E. and W. center line of the NW¼ of sec. 17.</p> <p>Over rolling terrain, through scattered timber.</p>
19.86	The NW. 1/16 sec. cor. of sec. 17.
39.73	The N. 1/16 sec. cor. of sec. 17 and 18.
	<hr/> <p style="text-align: center;">Subdivision of Section 18, T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming</p> <hr/>
	<p>From the 1/4 sec. cor. of sec. 18 only, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, N. of the cor., with aluminum cap mkd.</p> <p style="text-align: center;">T14N R84W 1/4 S 18 <hr/>1977</p>
	<p>from which the 1977 bearing tree</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 15° E., 86 lks. dist., mkd. 1/4 S18 BT, on partially healed blaze.</p>
	<p>N. 1° 51' E., on the N. and S. center line of sec. 18.</p> <p>Over rolling terrain, through scattered timber.</p>
35.00	Wyoming State Highway No. 70, bears NE. and SW.
39.84	<p>Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>

Subdivision of Section 18,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T14N R84W C1/4 S 18 2000</p>
59.90	<p>Point for the center N. 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R84W C N1/16   S 18 C 2000</p>
79.96	<p>The 1/4 sec. cor. of secs. 7 and 18.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>S. 89° 45' W., on the E. and W. center line of sec. 18.</p> <p>Over rolling terrain, through scattered timber.</p>
20.00	<p>Point for the center E. 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R84W E1/16 C———C S 18 2000</p>
40.00	<p>The center 1/4 sec. cor. of sec. 18.</p>
80.91	<p>The 1/4 cor. of secs. 13 and 18, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T14N R85W R84W 1/4 S 13   S 18 1977</p>

Subdivision of Section 18,  
T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which the 1977 bearing trees</p> <p>A pine, 12 ins. diam., bears N. 70° E., 31 lks. dist., mkd. 1/4 S18 BT.</p> <p>A pine stump, 6 ins. diam., bears S. 80° W., 65 lks. dist., cut trunk lying nearby mkd. 1/4 S13 BT.</p> <p>Cor. is located 8 lks. E. of fence, extending N. and S.</p>
20.01	<p>From the center E. 1/16 sec. cor. of sec. 18.</p> <p>N. 1° 21' E., on the N. and S. center line of the NE¼ of sec. 18.</p> <p>Over rolling terrain.</p> <p>Point for the NE. 1/16 sec. cor. of sec. 18, at intersection with the E. and W. center line of the NE¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, supported by a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R84W</p> <p style="text-align: center;">NE 1/16 S 18</p> <p style="text-align: center;">2000</p>
39.98	<p>The E. 1/16 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 17 and 18.</p> <p>S. 89° 53' W., on the E. and W. center line of the NE¼ of sec. 18.</p> <p>Over rolling terrain.</p>
19.81	<p>The NE. 1/16 sec. cor. of sec. 18.</p>
39.64	<p>The center N. 1/16 sec. cor. of sec. 18.</p> <hr/>

T. 14 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	GENERAL DESCRIPTION
	<p>The area embraced by this survey is situated in the southeastern portion of Carbon County, approximately 5 miles southwest of Encampment Wyoming. The terrain is rolling with an average elevation of about 8,240 feet above sea level. The soil is mostly rocky, and vegetation consists of sagebrush and native grasses. Timber consists of stands of pine, fir and aspen.</p> <p>Drainage of the area is southeasterly into the North Fork Encampment River and northeasterly into numerous draws. Access is provided by Wyoming State Highway No. 70, and numerous trails in the area. The area is uninhabited and there was no evidence of mineral activity, however a logging operation had recently been in the area.</p>



## CERTIFICATE OF SURVEY

I, Lynn A. Forbes, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day of October, 1999, I have dependently resurveyed a portion of the subdivisional lines and subdivided sections 7, 17 and 18, Township 14 North, Range 84 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JAN 23 2002

(Date)

Lynn A. Forbes  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 7, 17 and 18, Township 14 North, Range 84 West, Sixth Principal Meridian, Wyoming, executed by Lynn A. Forbes, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 23 2002

(Date)

John P. Lee  
(Signature of Authorized Officer)