

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>A spruce, 24 ins. diam., bears S. 32° E., 16 lks. dist., mkd. BT on partially healed blaze. (Record: 14 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R80W S 3 1/4 ——— S 10 1991</p> <p>from which a new bearing tree</p> <p>A spruce, 19 ins. diam., bears S. 84° E., 17 lks. dist., mkd. T16N R80W 1/4 S10 BT.</p> <p>Bury the original cor. stone alongside the iron post.</p> <hr/> <p>S. 89° 50' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>6.73 Stream, 15 lks. wide, 2 lks. deep, course N.</p> <p>18.50 Stream, 5 lks. wide, 1 lk. deep, course N.</p> <p>28.34 Center of road, 18 lks. wide, bears NE. and SW.</p> <p>31.54 Top of ridge, bears SE. and NW.</p> <p>39.74 The cor. of secs. 3, 4, 9, and 10.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89° 47' W., bet. secs. 21 and 28.</p> <p>Over rolling and broken terrain.</p> <p>23.50 Top of ridge, bears N. and S., begin descent.</p> <p>40.10 The ¼ sec. cor. of secs. 21 and 28, monumented with a granite stone, 16x7x6 ins., loosely set 3 ins. in the ground, dimly mkd. 1/4 on N. face, from which the remains of an original bearing tree</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>A pine, 18 ins. diam., bears S. 24° W., 25 lks. dist., with healed blaze. (Record: S. 28½° W.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, in a mound of stone, 1½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T16N R80W S 21 1/4 ——— S 28 1991</p> </div> <p>from which new bearing trees</p> <p>A spruce, 10 ins. diam., bears N. 10° E., 44 lks. dist., mkd. T16N R80W 1/4 S21 BT.</p> <p>A pine, 13 ins. diam., bears N. 53° E., 72 lks. dist., mkd. T16N R80W 1/4 S21 XBT.</p> <p>Bury the original cor. stone alongside the iron post in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 55' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>40.16 The cor. of secs. 20, 21, 28 and 29, monumented with a granite stone, 14x12x6 ins., firmly set 9 ins. in the ground, plainly mkd. 4 grooves on E. face and 2 grooves on S. face, from which the remains of an original bearing tree</p> <p>A dead pine, 18 ins. diam., bears N. 68° E., 28 lks. dist., mkd. T16N R80W S21 BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T16N R80W S 20 S 21 ——— ——— S 29 S 28 1991</p> </div>
--------	---

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which new bearing trees</p> <p>A fir, 5 ins. diam., bears S. 80° E., 13 lks. dist., mkd. T16N R80W S28 BT.</p> <p>A pine, 9 ins. diam., bears S. 66° W., 59 lks. dist., mkd. T16N R80W S29 BT.</p> <p>A fir, 7 ins. diam., bears S. 76° W., 10 lks. dist., mkd. T16N R80W S29 BT.</p> <p>A pine, 9 ins. diam., bears N. 84° W., 66 lks. dist., mkd. T16N R80W S20 BT.</p> <p>Bury the original cor. stone alongside the iron post in the mound of stone.</p> <hr/> <p>N. 0° 15' E., bet secs. 20 and 21.</p> <p>Over rolling and broken terrain.</p>
14.97	Stream, 11 lks. wide, 1 lk. deep, course NW.
17.50	Top of ridge, bears SE. and NW.
39.90	<p>The ¼ sec. cor. of secs. 20 and 21, monumented with a granite stone, 12x24x4 ins., loosely set 3 ins. in the ground, plainly mkd. 1/4 on W. face, from which the original bearing tree.</p> <p>A fir, 15 ins. diam., bears N. 74° E., 23 lks. dist., with illegible scribing on partially healed blaze. (Record: N. 51° E., 24 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T16N R80W 1/4 S 20 S 21 1991</p> <p>from which new bearing trees</p> <p>A pine, 16 ins. diam., bears N. 1° E., 14 lks. dist., mkd. T16N R80W 1/4 S21 BT.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>A fir, 12 ins. diam., bears N. 81° E., 26 lks. dist., mkd. T16N R80W 1/4 S21 XBT.</p> <p>A fir, 24 ins. diam., bears S. 70° W., 32 lks. dist., mkd. T16N R80W 1/4 S20 BT.</p> <p>Bury the original cor. stone alongside the iron post in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>14.10 Stream, 4 lks. wide, 1 lk. deep, course W.</p> <p>17.00 Top of spur, slopes SW.</p> <p>18.45 Brush Creek, 25 lks. wide, 3 lks. deep, course SW.</p> <p>39.37 The cor. of secs. 16, 17, 20 and 21, monumented with a granite stone, 14x11x4 ins., firmly set 9 ins. in the ground, plainly mkd. 4 notches on E. edge and 3 notches on S. edge, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A pine log, 17 ins. diam., bears N. 53° E., 8 lks. dist., mkd. T16N R80W S16. (Record: N. 30° E., 7 lks.)</p> <p style="padding-left: 40px;">A dead pine snag, 14 ins. diam., bears S. 66° E., 21 lks. dist., mkd. T16N R80W S21 BT. (Record: S. 65° E., 19 lks.)</p> <p style="padding-left: 40px;">A pine log, 10 ins. diam., bears S. 53° W., 6 lks. dist., mkd. T16N R80W S20 BT. (Record: S. 58° W.)</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 63° W., 6 lks. dist., with healed blaze. (Record: N. 60° W., 6 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T16N R80W</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 17</td><td style="padding: 0 5px;">S 16</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; border-right: 1px solid black; border-left: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 20</td><td style="padding: 0 5px;">S 21</td></tr> <tr><td colspan="2" style="padding: 0 5px;">1991</td></tr> </table> </div>	T16N R80W		S 17	S 16			S 20	S 21	1991	
T16N R80W											
S 17	S 16										
S 20	S 21										
1991											

0 27

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which new bearing trees</p> <p>A fir, 14 ins. diam., bears N. 74° E., 24 lks. dist., mkd. T16N R80W S16 BT.</p> <p>A fir, 14 ins. diam., bears S. 44° E., 66 lks. dist., mkd. T16N R80W S21 BT.</p> <p>A fir, 20 ins. diam., bears S. 40° W., 11 lks. dist., mkd. T16N R80W S20 BT.</p> <p>Bury the original cor. stone alongside the iron post in the mound of stone.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89° 38' W., bet. secs. 16 and 21.</p> <p>Over rolling and broken terrain.</p>
21.67	Intersect line 2-3, M.S. No. 96, King Solomon Placer, at a point from which Cor. No. 2, bears S. 1° 12' W., 12.90 chs. dist., hereinafter described.
29.12	Stream, 1 lk. wide, 1 lk. deep, course S.
39.91	<p>The ¼ sec. cor. of secs. 16 and 21, monumented with a quartzite stone, 24x11x9 ins., firmly set 13 ins. in the ground, plainly mkd. 1/4 on W. face, from which the original bearing trees</p> <p>A pine, 18 ins. diam., bears N. 26° E., 28 lks. dist., mkd. 1/4 S BT. (Record: N. 20° E., 19 lks.)</p> <p>A pine, 10 ins. diam., bears S. 21° W., 20 lks. dist., mkd. 1/4 S BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T16N R80W S 16 1/4 ——— S 21 1991</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which a new bearing tree</p> <p>A pine, 13 ins. diam., bears N. 89° W., 43 lks. dist., mkd. T16N R80W 1/4 S16 BT.</p> <p>Bury the original cor. stone alongside the iron post in the mound of stone.</p> <hr/> <p>S. 89° 02' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p>
19.20	Stream, 10 lks. wide, 1 lk. deep, course S.
39.89	The cor. of secs. 16, 17, 20, and 21.
	<hr/> <p>N. 1° 08' W., bet. secs. 16 and 17.</p> <p>Over rolling and broken terrain.</p>
2.04	Enter clearcut.
26.57	Leave clearcut.
29.80	Center of road, 17 lks. wide, bears NE. and SW.
39.84	<p>The ¼ sec. cor. of secs. 16 and 17, monumented with a quartzite stone, 10x9x6 ins., firmly set 5 ins. in the ground, plainly mkd. 1/4 on N. face, from which the original bearing trees</p> <p>A pine, 12 ins. diam., bears S. 70° E., 60 lks. dist., with healed blaze. (Record: N. 73° E.)</p> <p>A pine, 10 ins. diam., bears S. 88° W., 15 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground with brass cap mkd.</p>
	<p style="text-align: center;">T16N R80W 1/4 S 17 S 16 1991</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>from which new bearing trees</p> <p>A fir, 11 ins. diam., bears N. 75° E., 44 lks. dist., mkd. T16N R80W 1/4 S16 BT.</p> <p>A spruce, 12 ins. diam., bears N. 2° W., 17 lks. dist., mkd. T16N R80W 1/4 S17 XBT.</p> <p>Bury the original cor. stone alongside the iron post.</p> <hr/> <p>N. 0° 10' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p>										
5.07	Top of slope.										
15.47	Top of ridge.										
25.46	Center of road, 35 lks. wide, bears SE. and NW.										
39.91	<p>The cor. of secs. 9, 10, 15 and 16, monumented with a granite stone, 14x11x5 ins., firmly set 12 ins. in the ground, plainly mkd. 4 notches on E. edge and 4 notches on S. edge, from which the original bearing trees</p> <p>A pine, 27 ins. diam., bears N. 32° E., 75 lks. dist., mkd. R80W S9 BT on partially healed blaze. (Record: N. 73° E., 60 lks.)</p> <p>A pine, 21 ins. diam., bears S. 33° E., 136 lks. dist., mkd. T16N R80W S16 BT. (Record: N. 88° W., 15 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T16N R80W</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>from which a new bearing tree</p> <p>A fir, 28 ins. diam., bears N. 69° W., 73 lks. dist., mkd. T16N R80W S8 BT.</p>	T16N R80W		S 8	S 9			S 17	S 16	1991	
T16N R80W											
S 8	S 9										
S 17	S 16										
1991											

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Bury the original cor. stone alongside the iron post in the mound of stone.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 87° 30' W., bet. secs. 9 and 16.</p> <p>Over rolling and broken terrain.</p>
8.74	Center of dirt road, 15 lks. wide, bears NE. and SW.
12.88	Center of dirt road, 15 lks. wide, bears NE. and SW.
16.77	Arrastre Creek, 9 lks. wide, 4 lk. deep, course SW.
19.24	Stream, 20 lks. wide, 2 lks. deep, course S.
20.00	Center of dirt road, 15 lks. wide, bears NE. and SW.
26.06	Stream, 2 lks. wide, course S.
35.40	Center of road, 14 lks. wide, bears NE. and SW.
40.87	<p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented with a granite stone, 11x8x3 ins., loosely set in a mound of stone, 2$\frac{1}{2}$ ft. base, plainly mkd. 1/4 on S. face, from which the original bearing trees</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears N. 79° E., 87 lks. dist., with healed blaze. (Record: N. 50° E., 63 lks.)</p> <p style="padding-left: 40px;">A pine, 34 ins. diam., bears S. 36° W., 109 lks. dist., with partially healed blaze. (Record: S. 40° W., 106 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;">T16N R80W S 9 1/4 ——— S 16 1991</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which a new bearing tree</p> <p>A fir, 11 ins. diam., bears S. 79° E., 71 lks. dist., mkd. 1/4 S16 XBT.</p> <p>Bury the original cor. stone alongside the iron post.</p> <hr/> <p>N. 88° 50' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p>
8.10	Stream, 4 lks. wide, 1 lk. deep, course S.
10.00	Top of slope, bears N. and S.
26.72	Center of road, 32 lks. wide, bears N. and S.
35.99	Center of road, 26 lks. wide, bears SE. and NW.
39.99	The cor. of secs. 8, 9, 16, and 17.
	<hr/> <p>N. 0° 07' E., bet. secs. 8 and 9.</p> <p>Over rolling and broken terrain.</p>
2.50	Center of road, 30 lks. wide, bears SE. and NW.
9.21	Enter swamp.
16.00	Leave swamp.
38.50	Stream, 3 lks. wide, 1 lk. deep, course W.
40.02	<p>The ¼ sec. cor. of secs. 8 and 9, monumented with a granite stone, 12x11x8 ins., firmly set 12 ins. in the ground, plainly mkd. 1/4 on S. face, from which the original bearing trees</p> <p>A spruce, 16 ins. diam., bears N. 70° E., 25 lks. dist., with healed blaze. (Record: N. 79° E., 26 lks.)</p> <p>A pine, 22 ins. diam., bears S. 62° W., 72 lks. dist., with healed blaze. (Record: S. 59° W., 71 lks.)</p> <p>At the corner point</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 1 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T16N R80W 1/4 S 8 S 9 1991</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 64° E., 45 lks. dist., mkd. 1/4 S9 XBT.</p> <p>Bury the original cor. stone alongside the iron post in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>6.59 Stream, 5 lks. wide, 1 lk. deep, course SW.</p> <p>11.86 Center of road, 24 lks. wide, bears E. and W.</p> <p>39.84 The cor. of secs. 4, 5, 8 and 9, monumented with a granite stone, 18x6x4 ins., firmly set 5 ins. in the ground, plainly mkd., 4 notches on E. edge and 5 notches on S. edge, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A spruce stump, 20 ins. diam., bears N. 29° E., 27 lks. dist., mkd. BT on open blaze. (Record: N. 32° E., 26 lks.)</p> <p style="padding-left: 40px;">A pine stump, 24 ins. diam., bears S. 52° E., 64 lks. dist., with open blaze. (Record: S. 50° E., 63 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T16N R80W S 5 S 4 ----- S 8 S 9 1991</p>


Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which new bearing trees</p> <p>A spruce, 10 ins. diam., bears N. 15° E., 50 lks. dist., mkd. T16N R80W S4 BT.</p> <p>A fir, 23 ins. diam., bears S. 45° E., 76 lks. dist., mkd. T16N R80W S9 BT.</p> <p>A spruce, 14 ins. diam., bears S. 44° W., 18 lks. dist., mkd. T16N R80W S8 BT.</p> <p>A spruce, 7 ins. diam., bears N. 83° W., 26 lks. dist., mkd. T16N R80W S5 BT.</p> <p>Bury the original cor. stone alongside the iron post in the mound of stone.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89° 39' W., bet. secs. 4 and 9.</p> <p>Over rolling and broken terrain.</p>
8.43	E. side of ravine.
13.50	W. side of ravine.
39.96	<p>The ¼ sec. cor. of secs. 4 and 9, monumented with a granite stone, 13x10x5 ins., loosely set 13 ins. in the ground, in a mound of stone, 3 ft. base, plainly mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T16N R80W S 4 1/4 ——— S 9 1991</p>
	<p>from which</p> <p>A fir, 14 ins. diam., bears N. 89° E., 114 lks. dist., mkd. 1/4 S4 BT.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>A spruce, 7 ins. diam., bears S. 63° W., 99 lks. dist., mkd. 1/4 S9 BT.</p> <p>Bury the original cor. stone alongside the iron post in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 44' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>13.68 Enter moderate timber.</p> <p>24.60 Center of road, 26 lks. wide, bears NE. and SW.</p> <p>27.80 Center of road, 27 lks. wide, bears N. and S.</p> <p>39.65 The cor. of secs. 4, 5, 8, and 9.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Portion of Mineral Survey No. 85, T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the surveys executed by James C. Kennedy in 1898)</p> <hr/> <p>From Cor. No. 1, M.S. No. 85, Lakeside Lode, monumented with a syenite stone, 53x28x12 ins., firmly set 20 ins. in the ground, in a mound of stone, 3 ft. base, plainly mkd. 1-85 on S. face, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A spruce stump, bears S. 35½° W., 51 lks. dist., no mks. visible.</p> <p style="padding-left: 40px;">A spruce stump, bears N. 81° W., 45 lks. dist., no mks. visible.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p>
--------	--

Dependent Resurvey, Portion of Mineral Survey No. 85,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T16N R80W S 15</p>  <p style="text-align: center;">1 MS 85 LL 1998</p> <p>from which new bearing trees</p> <p>A spruce, 14 ins. diam., bears N. 48° E., 33 lks. dist., mkd. 1-85 BT.</p> <p>A spruce, 11 ins. diam., bears S. 87° E., 20 lks. dist., mkd. 1-85 LL BT.</p> <p>A spruce, 14 ins. diam., bears N. 22° W., 51 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <p>Cor. is located in thick timber on a gentle facing SW. slope part way up a small ridge W. of a seasonal marsh.</p> <p>From this point, the ¼ sec. cor. of secs. 15 and 16, bears S. 53° 05' W., 5.22 chs. dist.</p> <p>S. 36° 31' E., on line 1-2, M.S. No. 85, Lakeside Lode.</p> <p>Over gently rolling terrain.</p> <p>4.52 Cor. No. 2, M.S. No. 85, Lakeside Lode, identical with Cor. No. 1, M.S. No. 85, Acme Lode, identical with Cor. No. 1, M.S. 157, Golden Wedge Lode, monumented with a syenite stone, 10x6x4 ins. broken off at ground level, in a mound of stone, 3 ft. base, plainly mkd. 2/85 on NE. face, 1/157 on SE. face, and 1/85 on SW. face, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A downed spruce, 30 ins. diam., bears S. 19½° E., 18 lks. dist., mkd. 1-157 BT.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 17 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p>
--------	---

Dependent Resurvey, Portion of Mineral Survey No. 85,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS

T16N R80W
S 15
MS 85 MS157
LL 2 1 GWL
1
MS 85
AL
1998

from which new bearing trees

A fir, 18 ins. diam., bears S. 5° E., 39 lks. dist.,
mkd. 1-85 BT.

A spruce, 27 ins. diam., bears N. 21° W., 72 lks.
dist., mkd. 2-85 BT.

A spruce, 12 ins. diam., bears N. 63° W., 45 lks.
dist., mkd. XBT.

Bury the original cor. stone alongside the aluminum post in the
mound of stone.

Cor. is located in scattered timber near a fork in a
trail at the N. end of a seasonal marsh.

From this point, the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, bears
N. 85° 52' W., 6.88 chs. dist.

From cor. No. 3, M.S. No. 85, Lakeside Lode, identical with Cor.
No. 4, M.S. No. 85, Acme Lode, monumented with a granite stone,
23x10x3 ins., firmly set, in approximately 4 ft. of water 35 ft.
from the N. shore of Stamp Mill Lake, plainly mkd. 3-85 on N.
face, and 4-85 on S. face, where it is impractical to remonument
the position, from which an original bearing tree

A spruce, 20 ins. diam., bears N. 37 $\frac{1}{2}$ ° E., 288 lks.
dist., with healed blaze. (Record: 286 lks.)

from which new bearing trees

A pine, 7 ins. diam., bears NORTH, 105 lks. dist.,
mkd. 4/85 BT.


A pine, 7 ins. diam., bears S. 87° W., 64 lks. dist.,
mkd. 4/85 BT.

Dependent Resurvey, Portion of Mineral Survey No. 85,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>From this same point, the ¼ sec. cor. of secs. 15 and 16, bears N. 32° 59' E., 18.25 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 37° 13' W., beginning new measurement, on line 3-4, M.S. No. 85, Lakeside Lode, identical in part with line 4-5, M.S. No. 96, King Solomon Placer.</p> <p>Over gently rolling terrain.</p>
0.70	<p>Point selected for the witness cor. to Cor. No. 3, M.S. No. 85, Lakeside Lode, identical with Cor. No. 4, M.S. No. 85, Acme Lode, on N. shore of Stamp Mill Lake.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>WC T16N R80W MS 85 LL 3 MS 96 4 AL K S P MS 85</p> </div> <p style="text-align: center;">1991</p>
2.55	<p>Cor. No. 4, M.S. No. 96, King Solomon Placer hereinafter described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 36° 59' W., beginning new measurement,</p> <p>Over gently rolling terrain.</p>
1.25	<p>Cor. No. 4, M.S. No. 85, Lakeside Lode, identical with Cor. No. 2, M.S. No. 92, Lakeside Placer, monumented with a syenite stone, 24x12x3 ins., buried in a mound of stone, plainly mkd. 4-85 on SE. face, from which an original bearing tree</p> <p style="padding-left: 40px;">A spruce, 28 ins. diam., bears N. 54° E., 42 lks. dist., with healed blaze. (Record: N. 50° E.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>

Dependent Resurvey, Portion of Mineral Survey No. 85,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS



from which new bearing trees

A pine, 18 ins. diam., bears S. 44° W., 44 lks. dist.,
mkd. 4/85 BT.

A pine, 18 ins. diam., bears N. 73° W., 47 lks. dist.,
mkd. 2/92 BT.

Bury the original cor. stone alongside the iron post in the
mound of stone.

Cor. is located on a gentle S. facing slope in moderate
timber N. of Stamp Mill Lake.


From this point, the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, bears
N. $44^\circ 53'$ E., 17.32 chs. dist.

From Cor. No. 2, M.S. No. 85, Acme Lode, identical with Cor. No.
2, M.S. No. 157, Golden Wedge Lode, monumented with a black
granite stone, 20x6x6 ins., loosely set 1 in. in the ground, in
a mound of stone, 3 ft. base, plainly mkd. 2-85 on SW. face,
and 2-157 on NE. face, from which an original bearing tree

A spruce, 36 ins. diam., bears S. $17\frac{1}{2}^\circ$ E., 76.5 lks.
dist., mkd. 2/157.

At the corner point

Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in
the ground, in a mound of stone, 3 ft. base to top, with
magnetic aluminum cap mkd.




Dependent Resurvey, Portion of Mineral Survey No. 85,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which new bearing trees</p> <p>A spruce, 11 ins. diam., bears N. 65° E., 57 lks. dist., mkd. 2/85 BT.</p> <p>A spruce, 16 ins. diam., bears S. 55° E., 67 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <p>Cor. is located in tall grass in a small meadow area near the end of a jeep trail NE. of a mining excavation.</p> <hr/> <p>S. 46° 31' W., on line 2-3, M.S. No. 85, Acme Lode, identical in part with line 5-6, M.S. No. 96, King Solomon Placer.</p> <p>Over gently rolling terrain.</p>
8.86	<p>The point for Cor. No. 6, M.S. No. 96, King Solomon Placer, hereinafter described.</p>
16.68	<p>Intersect the line bet. secs. 15 and 16, at a point from which the $\frac{1}{4}$ sec. cor. of secs. 15, and 16, bears N. 0° 19' E., 18.66 chs. dist.</p>
22.55	<p>Cor. No. 3, M.S. No. 85, Acme Lode, identical with Cor. No. 5, M.S. No. 96, King Solomon Placer, monumented with a syenite stone, 24x12x4 ins., firmly set 12 ins. in the ground, in a mound of stone, 3 ft. base, plainly mkd. 3-85 on NW. face, from which the remains of an original bearing tree</p> <p>A pine stump, 18 ins. diam., bears S. 83½° E., 69 lks. dist., with no blaze or scribing visible.</p> <p>A pine stump, 18 ins. diam., bears N. 67½° E., 82 lks. dist., with no blaze or scribing visible.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to bedrock, supported by a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p>

Dependent Resurvey, Portion of Mineral Survey No. 85,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	<div data-bbox="847 300 1002 583" data-label="Diagram"> <p>T16N R80W MS 85 AL 3 5 MS 96 KSP 1998</p> </div> <div data-bbox="418 612 867 646" data-label="Text"> <p>from which new bearing trees</p> </div> <div data-bbox="493 676 1343 740" data-label="Text"> <p>A fir, 10 ins. diam., bears N. 46° E., 38 lks. dist., mkd. 5/96 BT.</p> </div> <div data-bbox="493 772 1359 834" data-label="Text"> <p>A pine, 10 ins. diam., bears S. 48° W., 44 lks. dist., mkd. XBT.</p> </div> <div data-bbox="493 868 1359 932" data-label="Text"> <p>A pine, 15 ins. diam., bears N. 25° W., 65 lks. dist., mkd. 3/85 BT.</p> </div> <div data-bbox="415 963 1430 1025" data-label="Text"> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> </div> <div data-bbox="415 1059 1396 1151" data-label="Text"> <p>Cor. is located on a gentle NW. facing slope in thick small timber S. of an open beach area on the S. shore of Stamp Mill Lake.</p> </div> <hr/> <div data-bbox="500 1219 1352 1287" data-label="Text"> <p>Dependent Resurvey, Portion of Mineral Survey No. 92, T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming</p> </div> <hr/> <div data-bbox="660 1347 1192 1410" data-label="Text"> <p>(Restoring the survey executed by James C. Kennedy in 1899)</p> </div> <hr/> <div data-bbox="415 1472 1398 1536" data-label="Text"> <p>From Cor. No. 2, M.S. No. 92, Lakeside Placer, identical with Cor. No. 4, M.S. No. 85, Lakeside Lode.</p> </div> <div data-bbox="415 1568 1326 1602" data-label="Text"> <p>N. 37° 12' W., on line 2-3, M.S. No. 92, Lakeside Placer.</p> </div> <div data-bbox="415 1634 865 1668" data-label="Text"> <p>Over gently rolling terrain.</p> </div> <div data-bbox="290 1698 363 1727" data-label="Text"> <p>9.97</p> </div> <div data-bbox="415 1698 1443 1821" data-label="Text"> <p>Cor. No. 3, M.S. No. 92, Lakeside Placer, monumented with a quartzite stone, 24x12x6 ins., firmly set 12 ins. in the ground, plainly mkd. 3/92 on E. face, from which an original bearing tree</p> </div>
--------	--

Dependent Resurvey, Portion of Mineral Survey No. 92,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>A spruce, 22 ins. diam., bears S. $45\frac{1}{2}^{\circ}$ W., 15 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W</p>  <p>1998</p> </div> <p>from which a new bearing tree</p> <p>A pine, 11 ins. diam., bears N. 54° W., 45 lks. dist., mkd. 3-92 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p>
	<hr/> <p>N. $47^{\circ} 28'$ E., on line 3-4, M.S. No. 92, Lakeside Placer, identical in part with line 1-2, M.S. No. 264, Mohawk Lode.</p> <p>Over gently rolling terrain.</p>
6.05	<p>Cor. No. 2, M.S. No. 264, Mohawk Lode, hereinafter described.</p> <hr/>
	<p>N. $47^{\circ} 38'$ E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
9.09	<p>Cor. No. 1, M.S. No. 264, Mohawk Lode, hereinafter described.</p> <hr/>
	<p>N. $47^{\circ} 17'$ E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
1.47	<p>Intersect line 1-2, of unpatented M.S. No. 188, Gold Bug Lode, at a point from which Cor. No. 2, M.S. No. 188, Gold Bug Lode, bears S. $88^{\circ} 30'$ W., 10.15 chs. dist., hereinafter described.</p>

Dependent Resurvey, Portion of Mineral Survey No. 92,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
4.57	<p>Cor. No. 4, M.S. No. 92, Lakeside Placer, monumented with a granite stone, 20x10x4 ins., firmly set 9 ins. in the ground, plainly mkd. 4/92, from which the original bearing trees</p> <p>A spruce, 16 ins. diam., bears N. 47½° E., 28 lks. dist., with healed blaze.</p> <p>A spruce, 16 ins. diam., bears S. 26° W., 20 lks. dist., with healed blaze. (Record: 21 lks.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W S 16</p>  </div> <p>from which a new bearing tree</p> <p>A spruce, 13 ins. diam., bears S. 59° E., 23 lks. dist., mkd. 4-92 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <p>From this point, the ¼ sec. cor. of secs. 15 and 16, bears S. 22° 30' E., 14.27 chs. dist.</p>
	<hr/> <p>S. 37° 29' E., on line 4-1, M.S. No. 92, Lakeside Placer.</p>
	<p>Over gently rolling terrain.</p>
2.52	<p>Intersect line 1-2, of unpatented M.S. No. 188, Gold Bug Lode, at a point from which Cor. No. 1, M.S. No. 188, Gold Bug Lode, bears N. 88° 30' E., 8.52 chs. dist., hereinafter described.</p>
6.10	<p>Intersect the line bet. secs. 15 and 16, at a point from which the ¼ sec. cor. of secs. 15, and 16, bears S. 0° 08' W., 4.14 chs. dist.</p>

Dependent Resurvey, Portion of Mineral Survey No. 92,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS

9.73


Cor. No. 1, M.S. No. 92, Lakeside Placer, on line 4-1, M.S. No. 85, Lakeside Lode, monumented with a granite stone, 28x12x5 ins., firmly set 16 ins. in the ground, plainly mkd. 1/92 on W. face, from which the original bearing tree

A spruce, 24 ins. diam., bears S. 24° W., 9 lks. dist., with healed blaze. (Record: 66 ft.)

A spruce stump, 18 ins. diam., bears N. 83° W., 80 lks. dist., with no mks. visible.

At corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 17 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.



from which new bearing trees

A pine, 12 ins. diam., bears N. 67° E., 23 lks. dist., mkd. 1-92 BT.

A fir, 11 ins. diam., bears N. 64° W., 26 lks. dist., mkd. 1-92 L BT.

Bury the original cor. stone alongside the aluminum post in the mound of stone.

From this point, Cor. No. 1, M.S. No. 85 Lakeside Lode, bears N. 46° 28' E., 2.72 chs. dist.

From this same point, the ¼ sec. cor. of secs. 15 and 16, bears S. 60° 11' W., 2.54 chs. dist.


Dependent Resurvey, Portion of Mineral Survey No. 96,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">(Restoring the surveys executed by James C. Kennedy in 1900)</p> <hr style="width: 20%; margin: auto;"/> <p>From Cor. No. 2, M.S. No. 96, King Solomon Placer, determined from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A burned pine stump, 30 ins. diam., bears N. 64° 15' E., 84 ft. dist., no visible scribing.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T16N R80W</p> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">MS 96</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">KSP</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">2</td> <td style="padding: 2px 5px;"></td> </tr> </table> <p>S 21</p> <p style="margin-left: 40px;">1990</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 15° E., 42 lks. dist., mkd. KS 2/96 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 62° E., 15 lks. dist., mkd. XBT.</p> <p style="padding-left: 40px;">A spruce, 11 ins. diam., bears N. 83° W., 23 lks. dist., mkd. KS 2/96 S21 BT.</p> <p>N. 1° 12' E., on line 2-3, M.S. No. 96, King Solomon Placer.</p> <p>Over gently rolling terrain.</p> <p>12.90 Intersect the line bet. secs. 16 and 21, at a point from which the ¼ sec. cor. of secs. 16 and 21, bears S. 89° 38' W., 18.24 chs. dist.</p> <p>39.81 Cor. No. 3, M.S. No. 96, King Solomon Placer, monumented by person(s) unknown, with a quartzite stone, 17x18x11 ins., firmly set 10 ins. in the ground, plainly mkd. 3/96 on E. face. (Record: a pine post) This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p>	MS 96		KSP		2	
MS 96							
KSP							
2							

Dependent Resurvey, Portion of Mineral Survey No. 96,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS

Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.

T16N R80W
S 16 
1998

from which new bearing trees

A spruce, 13 ins. diam., bears S. 5° E., 10 lks. dist., mkd. 3-96 BT.

A pine, 16 ins. diam., bears WEST, 23 lks. dist., mkd. XBT.

Bury the mkd. stone alongside the aluminum post in the mound of stone.


S. 89° 33' E., on line 3-4, M.S. No. 96, King Solomon Placer.

Over gently rolling terrain.

9.85 Cor. No. 4, M.S. No. 96, King Solomon Placer, monumented by person(s) unknown, with a granite stone, 17x10x7 ins., firmly set 8 ins. in the ground, in a mound of stone, 2 ft. base, plainly mkd. 4/96 on SW. face. (Record: a spruce post) This position is accepted as a careful and faithful determination of the cor. position.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T16N R80W
S 16 
1998

Dependent Resurvey, Portion of Mineral Survey No. 96,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS

from which new bearing trees

A pine, 10 ins. diam., bears N. 14° E., 112 lks.
dist., mkd. 4/96 KSP BT.

A fir, 9 ins. diam., bears S. 46° W., 9 lks. dist.,
mkd. XBT.

A pine, 12 ins. diam., bears N. 37° W., 48 lks. dist.,
mkd. 4/96 BT.

Bury the mkd. stone alongside the iron post.

From this point, Cor. No. 4, M.S. No. 85, Lakeside Lode, bears
N. 36° 59' W., 1.25 chs. dist.

From the point for Cor. No. 6, M.S. No. 96, King Solomon Placer,
at proportionate distance on line 2-3, M.S. No. 85, Acme Lode,
there is no remaining evidence of the original cor.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in
the ground, in a mound of stone, 3 ft. base to top, with
magnetic aluminum cap mkd.

T16N R80W
AL
MS 85 / S 15

6 MS 96
KSP
1998

from which

A pine, 10 ins. diam., bears N. 58° E., 32 lks. dist.,
mkd. 6/96 S15 BT.

A pine, 9 ins. diam., bears S. 70° E., 40 lks. dist.,
mkd. XBT.

A pine, 12 ins. diam., bears SOUTH, 14 lks. dist.,
mkd. 6/96 BT.

From this point, Cor. No. 2, M.S. No. 85, Acme Lode, bears
N. 46° 31' E., 8.86 chs. dist.

Dependent Resurvey, Portion of Mineral Survey No. 96,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>S. 87° 08' E., on line 6-7, M.S. No. 96, King Solomon Placer.</p> <p>Over gently rolling terrain.</p> <p>12.58 Cor. No. 7, M.S. No. 96, King Solomon Placer, monumented with a quartzite stone, 19x11x3 ins., firmly set 12 ins. in the ground, in mound of stone, plainly mkd. 7/96 on SW. face, from which the original bearing trees</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears S. 19¾° W., 3.8 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears N. 22° W., 43 lks. dist., with healed blaze. (Record: N. 45° 18' W., 583.8 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to bedrock, supported by a mound of stone, 5 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T16N R80W S 15</p> <div style="border-left: 1px solid black; border-right: 1px solid black; border-bottom: 1px solid black; width: 50px; margin: 0 auto; position: relative;"> 7 MS 96 KSP </div> <p style="margin: 0 auto;">1998</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 5° E., 23 lks. dist., mkd. 7/96 BT.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 60° E., 24 lks. dist., mkd. 7/96 KS BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p>
25.83	<p>S. 0° 35' W., on line 7-1, M.S. No. 96, King Solomon Placer.</p> <p>Over gently rolling terrain.</p> <p>Intersect the line bet. secs. 15 and 22, at a point from which the cor. of secs. 15, 16, 21, and 22, bears S. 89° 19' W., 18.10 chs. dist.</p>

Dependent Resurvey, Portion of Mineral Survey No. 96,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS

39.71

Cor. No. 1, M.S. No. 96, King Solomon Placer, monumented by person(s) unknown, with an iron pipe $1\frac{1}{4}$ ins. in diam., firmly set, projecting 21 ins. above the ground, alongside remains of wood post, in a mound of stone, 3 ft. base to top. This position is accepted as a careful and faithful perpetuation of the original cor. position.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.

T16N R80W	
MS 96	
KS	S 22
COR 1	

MS 96
LS
1987

from which

A spruce, 10 ins. diam., bears N. 46° W., 41 lks. dist., mkd. 1-96 KS BT.

Bury the iron pipe alongside the iron post.

From this point, Cor. No. 2, M.S. No. 96, Lucky Strike Placer, bears N. $87^\circ 14'$ E., 2.21 chs. dist., hereinafter described.

From Cor. No. 2, M.S. No. 96, Lucky Strike Placer, perpetuated by person(s) unknown, with an iron pipe, $1\frac{1}{4}$ ins. diam., firmly set, projecting 18 ins. above the ground, from which the original bearing trees

A spruce, 18 ins. diam., bears N. 39° E., 23 lks. dist., with healed blaze. (Record: N. $36^\circ 46'$ E., 13.8 ft.)

A spruce, 20 ins. diam., bears South, 50 lks. dist., mkd. with healed blaze. (Record: S. $4^\circ 20'$ W., 36 ft.)

At the corner point

Dependent Resurvey, Portion of Mineral Survey No. 96,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T16N R80W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">COR 2</td> <td style="padding: 2px 5px;">S 22</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">LS</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">MS 96</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">1987</td> </tr> </table> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A spruce, 9 ins. diam., bears N. 34° W., 48 lks. dist., mkd. 2/96 LS BT.</p> <p>Bury the iron pipe alongside the iron post in the mound of stone.</p> <p>From this point, Cor. No. 1, M.S. No. 96, King Solomon Placer, bears S. 87° 14' W., 2.21 chs. dist.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>S. 0° 29' W., on line 2-3, M.S. No. 96, Lucky Strike Placer.</p> <p>Over gently rolling terrain.</p> <p>9.73 Cor. No. 3, M.S. No. 96, Lucky Strike Placer, determined from the original bearing trees</p> <p style="margin-left: 40px;">A pine, 17 ins. diam., bears S. 57° E., 52 lks. dist., with healed blaze. (Record: S. 56° 15' E., 34.8 ft.)</p> <p style="margin-left: 40px;">A pine, 20 ins. diam., bears S. 79° W., 40 lks. dist., with healed blaze. (Record: S. 76° 35' W., 27.5 ft.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T16N R80W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">MS 96</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">LS</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">COR 3</td> <td style="padding: 2px 5px;">S 22</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">1987</td> </tr> </table> </div>	COR 2	S 22	LS		MS 96			1987	MS 96		LS		COR 3	S 22		1987
COR 2	S 22																
LS																	
MS 96																	
	1987																
MS 96																	
LS																	
COR 3	S 22																
	1987																

Dependent Resurvey, Portion of Mineral Survey No. 96,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which a new bearing tree</p> <p>A spruce, 16 ins. diam., bears N. 78° E., 25 lks. dist., mkd. 3-96 LS BT.</p>
	<p>N. 89° 05' W., on line 3-4, M.S. No. 96, Lucky Strike Placer.</p> <p>Over gently rolling terrain.</p>
9.86	<p>Cor. No. 4, M.S. No. 96, Lucky Strike Placer, determined from the original bearing trees</p> <p>A pine, 19 ins. diam., bears S. 48° E., 18.8 ft. dist., no mks. visible on partially healed blaze.</p> <p>A pine, 19 ins. diam., bears N. 34° W., 24 ft. dist., no mks. visible on partially healed blaze.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T16N R80W MS 96 LS S 22 4 1987</p>
	<p>S. 0° 28' W., on line 4-5, M.S. No. 96, Lucky Strike Placer.</p> <p>Over gently rolling terrain.</p>
4.97	<p>Cor. No. 5, M.S. No. 96, Lucky Strike Placer, perpetuated by person(s) unknown with an iron pipe, 1½ diam., firmly set, projecting 20 ins. above the ground, in a mound of stone, 2½ ft. base, from which the original bearing trees</p> <p>A spruce, 17 ins. diam., bears S. 18° E., 43 lks. dist., with partially healed blaze. (Record: S. 19° 35' E., 29.3 ft.)</p> <p>A spruce, 19 ins. diam., bears N. 20° W., 9 lks. dist., with partially healed blaze. (Record: N. 19° 35' W., 3.7 ft.)</p>

Dependent Resurvey, Portion of Mineral Survey No. 96,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS																																	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T16N R80W</td><td></td></tr> <tr><td></td><td>MS 96</td><td rowspan="3"> S 22</td></tr> <tr><td></td><td>LS</td></tr> <tr><td></td><td>COR 5</td></tr> <tr><td></td><td colspan="2">└───┘</td></tr> <tr><td></td><td colspan="2">1987</td></tr> </table> </div> <p>from which a new bearing tree</p> <p>A pine, 12 ins. diam., bears S. 13° W., 43 lks. dist., mkd. 5/96 LS BT.</p> <hr/> <p>N. 89° 49' W., on line 5-6, M.S. No. 96, Lucky Strike Placer.</p> <p>Over gently rolling terrain, through intermittant timber.</p> <p>9.97 Intersect the line bet. secs. 21 and 22, at a point from which the ¼ sec. cor. of secs. 15 and 16, bears S. 0° 25' E., 11.88 chs. dist.</p> <p>29.98 Cor. No. 6, M.S. No. 96, Lucky Strike Placer, monumented with a small mound of stone, varified from an original bearing tree</p> <p>A spruce, 19 ins. diam., bears N. 73° 45' W., 34.5 ft. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T16N R80W</td><td></td></tr> <tr><td></td><td>MS 96</td><td rowspan="3"> </td></tr> <tr><td></td><td>LSP</td></tr> <tr><td></td><td>6</td></tr> <tr><td>S 21</td><td colspan="2">└───┘</td></tr> <tr><td></td><td colspan="2">1990</td></tr> </table> </div>		T16N R80W			MS 96	S 22		LS		COR 5		└───┘			1987			T16N R80W			MS 96			LSP		6	S 21	└───┘			1990	
	T16N R80W																																
	MS 96	S 22																															
	LS																																
	COR 5																																
	└───┘																																
	1987																																
	T16N R80W																																
	MS 96																																
	LSP																																
	6																																
S 21	└───┘																																
	1990																																

Dependent Resurvey, Portion of Mineral Survey No. 96,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>from which new bearing trees</p> <p>A spruce, 15 ins. diam., bears S. 10° E., 12 lks. dist., mkd. 6/96 LS BT.</p> <p>A spruce, 12 ins. diam., bears S. 58° W., 22 lks. dist., mkd. XBT.</p> <hr/> <p>N. 0° 24' E., on line 6-1, M.S. No. 96, Lucky Strike Placer.</p> <p>Over gently rolling terrain.</p> <p>14.96 Cor. No. 1, M.S. No. 96, King Solomon Placer, determined from an original bearing tree</p> <p>A pine, 30 ins. diam., bears N. 51° W., 65 lks. dist., with healed blaze. (Record: 43.2 ft.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W MS 96 KSP</p> <hr style="width: 50px; margin: 0 auto;"/> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">1</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">MS 96</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">LSP</td> </tr> </table> <p>1990</p> </div> <p>from which new bearing trees</p> <p>A spruce, 14 ins. diam., bears S. 25° E., 59 lks. dist., mkd. LS 1/96 BT.</p> <p>A spruce, 17 ins. diam., bears S. 30° W., 65 lks. dist., mkd. LS 1 S21 BT.</p> <p>From this point, Cor. No. 2, King Solomon Placer, bears N. 89° 35' W., 2.24 chs. dist.</p> <hr/>	S 21	1		MS 96		LSP
S 21	1						
	MS 96						
	LSP						