

Dependent Resurvey of Mineral Survey No. 117,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS


(Restoring the surveys executed by  
Charles Bellamy in 1900)

From Cor. No. 1, M.S. No. 117, Wyoming No. 2 Lode, monumented with a quartzite stone, 18x14x14 ins., firmly set 6 ins. in the ground, in a small mound of stone, plainly mkd. 1/117 on W. face, from which the remains of an original bearing tree

A root hole, bears SOUTH, 37 lks. dist.  
(Record: S. 8° E., 24.7 ft.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 2½ ft. base to top, with magnetic aluminum cap mkd.



from which new bearing trees

A spruce, 12 ins. diam., bears N. 3° E., 49 lks. dist., mkd. 1-117 BT.

A spruce, 18 ins. diam., bears N. 48° E., 86 lks. dist., mkd. 1-117 BT.

A spruce, 24 ins. diam., bears S. 8° E., 33 lks. dist., mkd. 1-117 BT.

Bury the original cor. stone alongside the aluminum post in the mound of stone.

From this point, the ¼ sec. cor. of secs. 10 and 15, bears S. 32° 36' W., 4.38 chs. dist.


S. 45° 29' W., on line 1-2, M.S. No. 117, Wyoming No. 2 Lode.

Over gently rolling terrain.

Dependent Resurvey of Mineral Survey No. 117,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
5.25	Intersect the line bet. secs. 10 and 15, at a point from which the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, bears N. $89^{\circ} 57'$ E., 1.39 chs. dist.
22.69	<p>Cor. No. 2, M.S. No. 117, Wyoming No. 2 Lode, monumented with a quartzite stone, 15x8x6 ins., firmly set 5 ins. in the ground, in a small mound of stone, plainly mkd. 2-117 on NE. face, from which the remains of an original bearing tree</p> <p>A root hole, bears S. <math>1^{\circ}</math> E., 27 lks. dist., alongside of which is lying a dead and fallen spruce, 15 ins. diam., with healed blaze. (Record: 17.7 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 18 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W MS 117 W2L 2</p>  <p>S 15 1998</p> </div> <p>from which new bearing trees</p> <p>A spruce, 11 ins. diam., bears S. <math>84^{\circ}</math> E., 45 lks. dist., mkd. 2-117 W BT.</p> <p>A spruce, 20 ins. diam., bears S. <math>8^{\circ}</math> W., 43 lks. dist., mkd. 2-117 W BT.</p> <p>A spruce, 10 ins. diam., bears N. <math>73^{\circ}</math> W., 33 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>N. <math>43^{\circ} 53'</math> W., on line 2-3, M.S. No. 117, Wyoming No. 2 Lode.</p> <p>Over gently rolling terrain.</p>
3.75	Intersect line 1-2, M.S. No. 117, Idaho Lode, at a point from which Cor. No. 2, bears S. $52^{\circ} 00'$ W., 2.48 chs. dist., hereinafter described.


Dependent Resurvey of Mineral Survey No. 117,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
4.55	<p>Cor. No. 3, M.S. No. 117, Wyoming No. 2 Lode, monumented with a quartzite stone, 18x13x10 ins., firmly set 16 ins. in the ground, in a mound of stone, plainly mkd. 3/117 W on E. face, from which the remains of an original bearing tree</p> <p>A spruce stump, 34 ins. diam., bears S. 50° W., 22 lks. dist., with a blaze and illegible scribing.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a mound of stone, 2½ ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W</p>  <p>1998</p> </div> <p>from which new bearing trees</p> <p>A spruce, 11 ins. diam., bears N. 20° E., 40 lks. dist., mkd. 3/117 W 2 BT.</p> <p>A spruce, 9 ins. diam., bears S. 45° E., 59 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p>
	<p>N. 45° 17' E., on line 3-4, M.S. No. 117, Wyoming No. 2 Lode,</p> <p>Over gently rolling terrain.</p>
12.78	<p>Intersect the line bet. secs. 10 and 15, at a point from which the ¼ sec. cor. of secs. 15 and 16, bears N. 89° 57' E., 7.85 chs. dist.</p>
20.29	<p>Intersect line 1-4, M.S. No. 117, Idaho Lode, at a point from which Cor. No. 4, bears N. 37° 31' W., 1.48 chs. dist. hereinafter described.</p>
22.62	<p>Cor. No. 4, M.S. No. 117, Wyoming No. 2 Lode, monumented with a quartzite stone, 20x18x7 ins., firmly set 8 ins. in the ground, in a mound of stone, plainly mkd. 4/117 W on SW. face, from which an original bearing tree</p>

Dependent Resurvey of Mineral Survey No. 117,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p>	<p>A spruce, 35 ins. diam., bears S. 37° W., 130 lks. dist., with illegible scribing on partially healed blaze. (Record: S. 49° 30' W., 86.1 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W S 10 4 MS 117 W2L 1998</p>  </div> <p>from which new bearing trees</p> <p>A spruce, 18 ins. diam., bears N. 40° E., 11 lks. dist., mkd. 4-117 BT.</p> <p>A spruce, 30 ins. diam., bears S. 65° W., 57 lks. dist., mkd. 4/117 BT.</p> <p>A spruce, 26 ins. diam., bears N. 52° W., 62 lks. dist., mkd. 4-117 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>S. 44° 37' E., on line 4-1, M.S. No. 117, Wyoming No. 2 Lode.</p> <p>Over gently rolling terrain.</p> <p>4.50 Cor. No. 1, M.S. No. 117, Wyoming No. 2 Lode.</p> <hr/> <p>From Cor. No. 1, M.S. No. 117, Idaho Lode, monumented with a quartzite stone, 21x15x8 ins., loosely set in mound of stone, 2 ft. base, plainly mkd. 1/117 on N. face and I on E. face, from which the remains of an original bearing tree</p> <p>A spruce stump, 24 ins. diam., bears N. 82° W., 27 lks. dist., no mks. visible. (Record: 27.4 ft.)</p>
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



Dependent Resurvey of Mineral Survey No. 117,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W</p>  <p>MS 117 IL 1 MS 117 W2L 1998</p> </div> <p>from which new bearing trees</p> <p>A spruce, 40 ins. diam., bears N. 12° E., 99 lks. dist., mkd. 1/117 ID BT.</p> <p>A spruce, 16 ins. diam., bears S. 25° W., 13 lks. dist., mkd. 1/117 BT.</p> <p>A spruce, 52 ins. diam., bears N. 28° W., 63 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <p>From this point, the ¼ sec. cor. of secs. 10 and 15, bears S. 12° 21' E., 2.89 chs. dist.</p> <p>From this same point, Cor. No. 1, M.S. No. 117, Wyoming No. 2 Lode, bears N. 74° 08' E., 3.09 chs. dist.</p> <p>S. 52° 00' W., on line 1-2, M.S. No. 117, Idaho Lode,</p> <p>Over gently rolling terrain.</p> <p>4.60 Intersect the line bet. secs. 10 and 15, at a point from which the ¼ sec. cor. of secs. 15, and 16, bears N. 89° 57' E., 4.25 chs. dist.</p> <p>20.06 Intersect line 2-3, M.S. No. 117, Wyoming No. 2 Lode, at a point from which Cor. No. 3, M.S. No. 117, Wyoming No. 2 Lode, bears N. 43° 53' W., 0.80 chs. dist.</p> <p>At the point of intersection on a boulder of indeterminate size, chiseled an X and the letters INT.</p>


Dependent Resurvey of Mineral Survey No. 117,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>from which</p> <p>A fir, 13 ins. diam., bears S. 38° E., 43 lks. dist., mkd. MS 117 I BT.</p> <p>A spruce, 48 ins. diam., bears S. 52° W., 37 lks. dist., mkd. S 15 BT.</p> <p>22.54 Cor. No. 2, M.S. No. 117, Idaho Lode, monumented with a quartzite stone, 20x14x5 ins., firmly set 4 ins. in the ground, in a mound of stone, plainly mkd. 2/117 on N. face, from which the remains of an original bearing tree</p> <p>A spruce stump, 18 ins. diam., bears S. 85° E., 5 lks. dist., with illegible scribing. (Record: S. 65° E., 3.4 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T16N R80W</p> <p style="text-align: center;">MS 117 IL 2</p> <p style="text-align: center;">S 15 1998</p> <p>from which new bearing trees</p> <p>A spruce, 10 ins. diam., bears N. 47° E., 12 lks. dist., mkd. 2/117 I BT.</p> <p>A spruce, 10 ins. diam., bears S. 40° W., 20 lks. dist., mkd. XBT.</p> <p>A spruce, 12 ins. diam., bears N. 55° W., 65 lks. dist., mkd. 2/117 I BT.</p> <p>Bury the original corner stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>N. 37° 43' W., on line 2-3, M.S. No. 117, Idaho Lode.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------


Dependent Resurvey of Mineral Survey No. 117,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Over gently rolling terrain.</p> <p>3.78 Intersect line 2-3, M.S. No. 441, Magnolia Lode, at a point from which Cor. No. 3, bears S. 7° 41' E., 1.18 chs. dist., hereinafter described.</p> <p>At the point of intersection</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W</p>  </div> <p>from which</p> <p>A spruce, 12 ins. diam., bears S. 88° E., 44 lks. dist., mkd. 117 I BT.</p> <p>A spruce, 7 ins. diam., bears S. 84° W., 12 lks. dist., mkd. 441 M BT.</p>
4.49	<p>Cor. No. 3, M.S. No. 117, Idaho Lode, monumented with a quartzite stone, 19x12x7 ins., firmly set 10 ins. in the ground, in a small mound of stone, plainly mkd. 3/117 on S. face, from which an original bearing tree</p> <p>A spruce, 30 ins. diam., bears S. 59° W., 36 lks. dist., with healed blaze. (Record: S. 66° W., 24 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T28N R71W</p>  </div>

Dependent Resurvey of Mineral Survey No. 117,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which new bearing trees</p> <p>A spruce, 24 ins. diam., bears S. 43° E., 29 lks. dist., mkd. 3/117 I BT.</p> <p>A spruce, 16 ins. diam., bears N. 18° W., 77 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p>
	<p>N. 51° 55' E., on line 3-4, M.S. No. 117, Idaho Lode.</p>
	<p>Over gently rolling terrain.</p>
<p>0.41</p>	<p>Intersect line 2-3, M.S. No. 441, Magnolia Lode, at a point from which Cor. No. 3, bears S. 7° 41' E., 2.01 chs. dist., hereinafter described.</p>
	<p>At point of intersection</p>
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T16N R80W</p> 
	<p>from which</p>
	<p>A spruce, 8 ins. diam., bears S. 80° E., 25 lks. dist., mkd. 117 I BT.</p>
	<p>A spruce, 30 ins. diam., bears N. 51° W., 12 lks. dist., mkd. 441 M BT.</p>
<p>12.13</p>	<p>Intersect the line bet. secs. 10 and 15, at a point from which the ¼ sec. cor. of secs. 15 and 16, bears N. 89° 57' E., 11.59 chs. dist.</p>
<p>22.56</p>	<p>Cor. No. 4, M.S. No. 117, Idaho Lode, monumented with a quartzite stone, 30x12x9 ins., firmly set 7 ins. in the ground, in a mound of stone, plainly mkd. 4/117 on S. face.</p>

Dependent Resurvey of Mineral Survey No. 117,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W S 10</p>  <p>4 MS 117 IL 1998</p> </div> <p>from which new bearing trees</p> <p>A fir, 20 ins. diam., bears N. 64° E., 40 lks. dist., mkd. 4-117 BT.</p> <p>A fir, 16 ins. diam., bears S. 86° E., 87 lks. dist., mkd. 4-117 BT.</p> <p>A spruce, 18 ins. diam., bears N. 5° W., 33 lks. dist., mkd. 4-117 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>S. 37° 31' E., on line 4-1, M.S. No. 117, Idaho Lode.</p> <p>Over gently rolling terrain.</p> <p>1.48 Intersect line 3-4, M.S. No. 117, Wyoming No. 2 Lode, at a point from which Cor. No. 4, bears N. 45° 37' E., 2.33 chs. dist.</p> <p>At the point of intersection on a quartzzite outcrop of indeterminate size at ground level, chisel an X and the letters INT.</p> <p>from which</p> <p>A fir, 24 ins. diam., bears S. 51° W., 43 lks. dist., mkd. 117 I BT.</p> <p>A spruce, 13 ins. diam., bears N. 17° W., 13 lks. dist., mkd. S 10 BT.</p>

Dependent Resurvey of Mineral Survey No. 117,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS

4.53

Cor. No. 1, M.S. No. 117, Idaho Lode.

Dependent Resurvey of Mineral Survey No. 146  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

(Restoring the survey executed by  
Charles Bellamy in 1901)

From Cor. No. 1, M.S. No. 146, Leviathan, monumented with a quartzite stone, 18x13x10 ins., firmly set 6 ins. in the ground, in a mound of stone, plainly mkd. 1/146 on W. face.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, with magnetic aluminum cap mkd.

T16N R80W

MS 146

LL 1

S 9

1998

from which new bearing trees

A spruce, 11 ins. diam., bears N. 30° W., 62 lks. dist., mkd. 1/146 BT.

A spruce, 17 ins. diam., bears N. 60° E., 81 lks. dist., mkd. 1/146 BT.


A spruce, 10 ins. diam., bears S. 88° E., 94 lks. dist., mkd. 1/146 BT.

Bury the original cor. stone alongside the aluminum post in the mound of stone.

From this point, the ¼ sec. cor. of secs. 9 and 10, bears S. 70° 33' E., 8.82 chs. dist.

From this same point, U.S.L.M. Gold Hill No. 1, bears S. 73° 25' W., 8.78 chs. dist.


Dependent Resurvey of Mineral Survey No. 146,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
22.56	<p>S. 62° 11' W., on line 1-2, M.S. No. 146, Leviathan Lode.</p> <p>Over gently rolling terrain.</p> <p>Cor. No. 2, M.S. No. 146, Leviathan Lode, monumented with a quartzite stone, 18x10x5 ins., firmly set 9 ins. in the ground, in a mound of stone, plainly mkd. 2/146 on E. face, from which an original bearing tree</p> <p style="padding-left: 40px;">A spruce, 38 ins. diam., bears S. 58' W., 25 lks. dist., mkd. 2/146 BT. (Record: S. 80° W., 16.1 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;">  <p>T16N R80W MS 146 LL 2 S 9 1998</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A spruce, 15 ins. diam., bears N. 52' E., 42 lks. dist., mkd. 2-146 BT.</p> <p style="padding-left: 40px;">A spruce, 29 ins. diam., bears S. 52' E., 30 lks. dist., mkd. 2-146 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p>
8.97	<p>N. 28° 37' W., on line 2-3, M.S. No. 146, Leviathan Lode.</p> <p>Over gently rolling terrain.</p> <p>Cor. No. 3, M.S. No. 146, Leviathan Lode, monumented with a quartzite stone, 22x15x4 ins., firmly set 9 ins. in the ground, in a small mound of stone, plainly mkd. 3/146 on E. face.</p> <p>At the corner point</p>



Dependent Resurvey of Mineral Survey No. 146,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p>	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W S 9    3 MS 146          LL 1998</p> </div> <p>from which new bearing trees</p> <p>A spruce, 9 ins. diam., bears N. 21' E., 40 lks. dist., mkd. 3-146 BT.</p> <p>A spruce, 13 ins. diam., bears S. 47' E., 17 lks. dist., mkd. 3-146 BT.</p> <p>A spruce, 12 ins. diam., bears S. 72' W., 23 lks. dist., mkd. 3-146 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>N. 61° 53' E., on line 3-4, M.S. No. 146, Leviathan Lode.</p> <p>Over gently rolling terrain.</p> <p>22.48 Cor. No. 4, M.S. No. 146, Leviathan Lode, monumented with a syenite stone, 22x10x6 ins., firmly set 7 ins. in the ground, in a small mound of stone, plainly mkd. 4/146 on W. face, from which an original bearing tree</p> <p>A spruce, 25 ins. diam., bears S. 15' W., 19 lks. dist., mkd. 4/146 BT on partially healed blaze. (Record: 13.5 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p>
---------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------


Dependent Resurvey of Mineral Survey No. 146,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>9.08</p>	<div style="text-align: center;"> <p>T16N R80W</p>  <p>1998</p> </div> <p>from which new bearing trees</p> <p>A spruce, 10 ins. diam., bears N. 68° E., 33 lks. dist., mkd. 4-146 BT.</p> <p>A spruce, 11 ins. diam., bears S. 86° W., 15 lks. dist., mkd. 4-146 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>S. 29° 08' E., on line 4-1, M.S. No. 146, Leviathan Lode.</p> <p>Over gently rolling terrain.</p> <p>Cor. No. 1, M.S. No. 146, Leviathan Lode.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of Mineral Survey No. 147 T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Charles Bellamy in 1901)</p> <hr/> <p>From Cor. No. 1, M.S. No. 147, Little Giant Lode, monumented with a syenite stone, 18x10x6 ins., firmly set 6 ins. in the ground, in a mound of stone, plainly mkd. 1/147 on N. face, from which the remains of an original bearing tree</p> <p>A balsam fir stump, 19 ins. diam., bears S. 38° W., 11 lks. dist., mkd. 1/147 BT on log lying nearby. (Record: S. 38° 30' W., 7.7 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p>
---------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------


Dependent Resurvey of Mineral Survey No. 147,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<div style="text-align: center;">  <p>T16N R80W MS 147 LGL 1 S 9 1998</p> </div> <p>from which new bearing trees</p> <p>A spruce, 19 ins. diam., bears N. 80° E., 57 lks. dist., mkd. 1-147 BT.</p> <p>A spruce, 22 ins. diam., bears S. 05° E., 75 lks. dist., mkd. 1-147 LG BT.</p> <p>A spruce, 25 ins. diam., bears S. 37° W., 52 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <p>From this point, the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 10, bears S. 40° 46' E., 5.59 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 60° 55' E., on line 1-2, M.S. No. 147, Little Giant Lode.</p> <p>Over gently rolling terrain.</p> <p>4.04 Intersect the line bet. secs. 9 and 10, at a point from which the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 10, bears S. 1° 05' W., 6.20 chs. dist.</p> <p>22.73 Cor. No. 2, M.S. No. 147, Little Giant Lode, monumented with a syenite stone, 21x8x6 ins., firmly set 6 ins. in the ground, in a small mound of stone, plainly mkd. 2-147 on W. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;">  <p>T28N R71W MS 147 LGL 2 S 10 1998</p> </div>

Dependent Resurvey of Mineral Survey No. 147,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which</p> <p>A spruce, 9 ins. diam., bears S. 5° E., 42 lks. dist., mkd. 2-147 BT.</p> <p>A spruce, 19 ins. diam., bears S. 30° W., 150 lks. dist., mkd. 2-147 S10 BT.</p> <p>A spruce, 10 ins. diam., bears S. 50° W., 155 lks. dist., mkd. 2/147 LG BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>N. 23° 37' W., on line 2-3, M.S. No. 147, Little Giant Lode.</p> <p>Over gently rolling terrain.</p>
8.91	<p>Cor. No. 3, M.S. No. 147, Little Giant Lode, monumented with a granite stone, 30x7x6 ins., firmly set 14 ins. in the ground, in a collar of stone, dimly mkd. 3/147 E. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W S 10</p>  <p>MS 147 LGL 1998</p> </div> <p>from which</p> <p>A spruce, 16 ins. diam., bears N. 59° E., 282 lks. dist., mkd. XBT.</p> <p>A spruce, 10 ins. diam., bears S. 72° E., 228 lks. dist., mkd. 3/147 S10 BT.</p> <p>A spruce, 13 ins. diam., bears S. 6° W., 220 lks. dist., mkd. 3/147 LG BT.</p>

Dependent Resurvey of Mineral Survey No. 147,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>S. 61° 20' W., on line 3-4, M. S. 147, Little Giant Lode.</p> <p>Over gently rolling terrain.</p>
14.76	<p>Intersect the line bet. secs. 9 and 10, at a point from which the <math>\frac{1}{4}</math> sec. cor. of secs. 9, and 10, bears S. 1° 05' E., 16.37 chs. dist.</p>
23.74	<p>Cor. No. 4, M.S. No. 147, Little Giant Lode, monumented with a syenite stone, 21x10x6 ins., firmly set 5 ins. in the ground, in mound of stone, plainly mkd. 4/147 on S. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;">  <p>T16N R80W</p> <p>S 9 MS 147 LGL 4</p> <p>1998</p> </div> <p>from which</p> <p>A spruce, 13 ins. diam., bears N. 4' E., 12 lks. dist., mkd. 4-147 BT.</p> <p>A spruce, 9 ins. diam., bears N. 22' E., 25 lks. dist., mkd. 4-147 BT.</p> <p>A spruce, 10 ins. diam., bears S. 65' W., 9 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>S. 30° 05' E., on line 4-1, M.S. No. 147, Little Giant Lode.</p> <p>Over gently rolling terrain.</p>

Dependent Resurvey of Mineral Survey No. 147,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS

9.05

Cor. No. 1, M.S. No. 147, Little Giant Lode.

---

Dependent Resurvey of Mineral Survey No. 150,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

---

(Restoring the surveys executed by  
Charles Bellamy in 1901)

---

From Cor. No. 1, M.S. No. 150, Bridal Veil Lode, perpetuated by person(s) unknown, with a steel reinforcement rod,  $\frac{1}{2}$  in. diam., firmly set, projecting 4 ins. above the ground, with a 1 in. diam. aluminum cap mkd. COR 1 150 on the edge of the northern track of a jeep trail. This position is accepted as a careful and faithful determination of the cor. position.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T16N R80W

MS 157

GWL 1

MS 150

BVL

1992

from which

A spruce, 8 ins. diam., bears N.  $69^{\circ}$  E., 94 lks.  
dist., mkd. 1/150 BT.


A spruce, 6 ins. diam., bears S.  $74^{\circ}$  E., 62 lks.  
dist., mkd. 1/150 BV BT.

A spruce, 14 ins. diam., bears S.  $24^{\circ}$  E., 58 lks.  
dist., mkd. XBT.



Bury the local monument alongside the iron post in the mound of stone.

From this point, the  $\frac{1}{4}$  sec. cor. of secs. 15 and 16, bears N.  $77^{\circ}$  41' W., 13.57 chs. dist.

Dependent Resurvey of Mineral Survey No. 150,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this same point, Cor. No. 2, M.S. No. 85, Acme Lode, bears S. 16° 21' W., 4.47 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 64° 24' E., on line 1-2, M.S. No. 150, Bridal Veil Lode.</p> <p>Over gently rolling terrain.</p>
6.93	<p>Intersect line 2-3, M.S. No. 157, Golden Wedge Lode, at a point from which Cor. No. 2, M.S. No. 157, Golden Wedge Lode, bears S. 45° 52' W., 10.46 chs. dist., hereinafter described.</p> <p>At point of intersection</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center; margin: 20px 0;">  <p style="margin: 0;">T16N R80W</p> <p style="margin: 0;">MS 157 GWL</p> <p style="margin: 0;">MS 157</p> <p style="margin: 0;">MS 150 BVL</p> <p style="margin: 0;">S 15</p> <p style="margin: 0;">1998</p> </div> <p>from which bearing trees</p> <p>A spruce, 12 ins. diam., bears N. 82' E., 78 lks. dist., mkd. 157 GW/150 BV S 15 BT.</p> <p>A spruce, 16 ins. diam., bears S. 22' E., 52 lks. dist., mkd. 157 GW/150 BV BT.</p>
22.60	<p>Cor. No. 2, M.S. No. 150, Bridal Veil Lode, monumented with a quartzite stone, 16x11x9 ins., firmly set 8 ins. in the ground, plainly mkd. 2/150 on SE. face, from which an original bearing tree</p> <p>A spruce, 22 ins. diam., bears N. 42' W., 16 lks. dist., with illegible scribing on partially healed blaze. (Record: N. 51° 30' W., 10.6 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p>

Dependent Resurvey of Mineral Survey No. 150,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<div style="text-align: center;"> <p>T16N R80W S 15</p>  <p>2 MS 150 BVL 1998</p> </div> <p>from which new bearing trees</p> <p>A spruce, 16 ins. diam., bears S. 42° E., 22 lks. dist., mkd. 2/150 S15 BT.</p> <p>A fir, 8 ins. diam., bears S. 82° W., 6 lks. dist., mkd. 2/150 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>S. 25° 53' E., on line 2-3, M.S. No. 150, Bridal Veil Lode.</p> <p>Over gently rolling terrain.</p> <p>4.53 Cor. No. 3, M.S. No. 150, Bridal Veil Lode, identical with Cor. No. 2, M.S. No. 150, Enterprise Lode, monumented with a quartzite stone, 17x9x9 ins., lying loose in a mound of stone, plainly mkd. 3/150 on a face, and 2/150 on opposite face, from which an original bearing tree</p> <p>A spruce, 14 ins. diam., bears S. 41° W., 38 lks. dist., mkd. 1/150 2/150 BT on partially healed blaze.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 17 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W</p>  <p>MS 150 BVL 3 S 15 2 MS 150 EL 1998</p> </div>

Dependent Resurvey of Mineral Survey No. 150,  
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which new bearing trees</p> <p>A spruce, 11 ins. diam., bears S. 78° E., 44 lks. dist., mkd. 2-3-150 BT.</p> <p>A spruce, 12 ins. diam., bears S. 20° E., 28 lks. dist., mkd. XBT.</p> <p>A fir, 9 ins. diam., bears N. 35° W., 28 lks. dist., mkd. 2/3-150 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>S. 64° 17' W., on line 3-4, M.S. No. 150, Bridal Veil Lode, identical with line 1-2, M.S. No. 150, Enterprise Lode.</p> <p>Over gently rolling terrain.</p>
22.57	<p>Cor. No. 4, M.S. No. 150, Bridal Veil Lode, identical with Cor. No. 1, M.S. 150, Enterprise Lode, monumented with a quartzite stone, 24x6x3 ins., firmly set 16 ins. in the ground, in a mound of stone, 3 ft. base to top, plainly mkd. 4/150 and 1/150 on NW. face, from which an original bearing tree</p> <p>A spruce, 30 ins. diam., bears S. 50° W., 16 lks. dist., mkd. BT 4/150 1/150. (Record: 13.6 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 17 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <div data-bbox="836 1415 1096 1670" style="text-align: center;"> <p>T16N R80W</p> </div> <p>from which new bearing trees</p> <p>A spruce, 15 ins. diam., bears S. 73° W., 52 lks. dist., mkd. 1-4-150 BT.</p>