


Dependent Resurvey of Mineral Survey No. 150,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming


CHAINS	
	<p>A spruce, 26 ins. diam., bears N. 51' W., 46 lks. dist., mkd. XBT.</p>
	<p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p>
	<p>From this point, Cor. No. 2, M.S. No. 85, Acme Lode, bears S. 86° 42' W., 3.28 chs. dist.</p>
	<p>From this same point, Cor. No. 7, M.S. No. 96, King Solomon Placer, bears S. 22° 26' E., 7.48 chs. dist.</p>
	<hr/> <p>N. 26° 14' W., on line 4-1, M.S. No. 150, Bridal Veil Lode.</p>
	<p>Over gently rolling terrain.</p>
2.26	<p>Intersect line 2-3, M.S. No. 157, Golden Wedge Lode, from which Cor. No. 2, M.S. No. 157, Golden Wedge Lode, bears S. 45° 52' W., 3.18 chs. dist., hereinafter described.</p>
	<p>At point of intersection</p>
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T16N R80W</p> 
	<p>from which bearing trees</p>
	<p>A spruce, 16 ins. diam., bears S. 43' E., 41 lks. dist., mkd. 150 BV/157 GW BT.</p>
	<p>A spruce, 8 ins. diam., bears S. 40' W., 69 lks. dist., mkd. S 15 BT.</p>
4.57	<p>Cor. No. 1, M.S. No. 150, Bridal Veil Lode.</p>
	<hr/> <p>From Cor. No. 1, M.S. No. 150, Enterprise Lode, identical with Cor. No. 4, M.S. No. 150, Bridal Veil Lode.</p>

Dependent Resurvey of Mineral Survey No. 152,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 17 ins. in the ground, in a mound of stone, 2½ ft. base to top, with magnetic aluminum cap mkd.



from which

A spruce, 11 ins. diam., bears N. 30' W., 67 lks. dist., mkd. COR 2/MS 152 BT.

A spruce, 10 ins. diam., bears N. 05' W., 69 lks. dist., mkd. XBT.


Bury the original cor. stone alongside the aluminum post in the mound of stone.

From Cor. No. 3, M.S. No. 152, Wyoming Lode, identical with Cor. No. 3, M.S. No. 152, Bank Note Lode, monumented with a quartzite stone, 27x13x9 ins., loosely set 12 ins. in the ground, plainly mkd. 3-152 on SW. face and 3-152 on NW. face, from which the remains of an original bearing tree

A dead spruce, 40 ins. diam., bears N. 80' W., 27 lks. dist., mkd. 3/152 3/152 BT. (Record: 19.2 ft.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base to top, with magnetic aluminum cap mkd.



Dependent Resurvey of Mineral Survey No. 150,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 64° 17' E., on line 1-2, M.S. No. 150, Enterprise Lode, identical with line 3-4, M.S. No. 150, Bridal Veil Lode.</p> <p>Over gently rolling terrain.</p>
22.57	<p>Cor. No. 2, M.S. No. 150, Enterprise Lode, identical with Cor. No. 3, M.S. No. 150, Bridal Veil Lode.</p> <hr/>
	<p>S. 26° 06' E., on line 2-3, M.S. No. 150, Enterprise Lode.</p> <p>Over gently rolling terrain.</p>
4.39	<p>Cor. No. 3, M.S. No. 150, Enterprise Lode, monumented with a quartzite stone, 17x8x6 ins., loosely set 1 in. in the ground, in a mound of stone, 3 ft. base, plainly mkd. 3/150 on E. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 base to top, with magnetic aluminum cap mkd.</p> <div data-bbox="803 1032 1015 1223" style="text-align: center;"> <p>T16N R80W</p> </div> <p>from which new bearing trees</p> <p>A spruce, 11 ins. diam., bears N. 39° E., 61 lks. dist., mkd. 3-150 BT.</p> <p>A spruce, 10 ins. diam., bears S. 82° E., 47 lks. dist., mkd. XBT.</p> <p>A fir, 11 ins. diam., bears S. 21° W., 46 lks. dist., mkd. 3-150 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/>
	<p>S. 64° 06' W., on line 3-4, M.S. No. 150, Enterprise Lode.</p> <p>Over gently rolling terrain.</p>


Dependent Resurvey of Mineral Survey No. 150,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>22.60</p>	<p>Cor. No. 4, M.S. No. 150, Enterprise Lode, monumented with a quartzite stone, 9x7x6 ins., loosely set 1 in. in the ground, in a mound of stone, 3 ft. base to top, plainly mkd. 4/150 on N. face, from which the remains of an original bearing tree</p> <p>A pine log, 12 ins. diam., found laying over the cor. stone, mkd. 4/150 BT. (Record: S. 50° W., 13.6 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base to top, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T16N R80W</p> <div style="text-align: center;"> </div> <p>from which new bearing trees</p> <p>A pine, 9 ins. diam., bears S. 85' E., 27 lks. dist., mkd. 4-150 BT.</p> <p>A fir, 10 ins. diam., bears S. 77' W., 22 lks. dist., mkd. 4-150 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>N. 25° 43' W., on line 4-1, M.S. No. 150, Enterprise Lode.</p> <p>Over gently rolling terrain.</p>
<p>4.47</p>	<p>Cor. No. 1, M.S. No. 150, Enterprise Lode, identical with Cor. No. 4, M.S. No. 150, Bridal Veil Lode.</p> <hr/>


Dependent Resurvey of Mineral Survey No. 152,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">(Restoring the surveys executed by Charles Bellamy in 1901)</p> <hr/> <p>From Cor. No. 1, M.S. No. 152, Wyoming Lode, monumented with a quartzite stone, 20x10x10 ins., firmly set 16 ins. in the ground, plainly mkd. 1/152 on N. face, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A spruce snag, 30 ins. diam., bears N. 51' W., 30 lks. dist., mkd. 1/152 BT. (Record: 19 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W</p> <p>MS 152</p> <p>WL</p> <p>1</p>  <p>S 10</p> <p>1998</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A spruce, 22 ins. diam., bears N. 87' E., 12 lks. dist., mkd. 1-152 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 32' W., 18 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <p>From this point, the ¼ sec. cor. of secs. 10 and 15, bears S. 34° 41' W., 5.85 chs. dist.</p> <hr/> <p>N. 41° 39' E., on line 1-2, M.S. No. 152, Wyoming Lode.</p> <p>Over gently rolling terrain.</p> <p>22.75 Cor. No. 2, M.S. No. 152, Wyoming Lode, identical with Cor. No. 2, M.S. No. 152, Bank Note Lode, monumented with a quartzite stone, 23x12x9 ins., firmly set 8 ins. in the ground, in a small mound of stone, plainly mkd. 2-152 on NE. face and 2-152 on NW. face.</p>
--------	--


Dependent Resurvey of Mineral Survey No. 152,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which new bearing trees</p> <p>A fir, 11 ins. diam., bears N. 30' E., 34 lks. dist., mkd. XBT.</p> <p>A pine, 21 ins. diam., bears N. 15' W., 67 lks. dist., mkd. COR 3/MS 152 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p>
	<p>S. 42° 03' W., on line 3-4, M.S. No. 152, Wyoming Lode.</p>
	<p>Over gently rolling terrain.</p>
22.81	<p>Cor. No. 4, M.S. No. 152, Wyoming Lode, monumented with a quartzite stone, 19x8x6 ins., firmly set 11 ins. in the ground, in a small mound of stone, plainly mkd. 4/152 on E. face.</p>
	<p>At the corner point</p>
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T16N R80W</p> 
	<p>from which new bearing trees</p>
	<p>A spruce, 16 ins. diam., bears S. 33' E., 127 lks. dist., mkd. 4-152 BT.</p>
	<p>A spruce, 6 ins. diam., bears N. 37' E., 124 lks. dist., mkd. XBT.</p>
	<p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p>
	<p>S. 48° 06' E., on line 1-4, M.S. No. 152, Wyoming Lode.</p>
	<p>Over gently rolling terrain.</p>
9.01	<p>Cor. No. 1, M.S. No. 152, Wyoming Lode.</p>


Dependent Resurvey of Mineral Survey No. 152,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From Cor. No. 1, M.S. No. 152, Bank Note Lode, monumented with a quartzite stone, 24x8x8 ins., firmly set in a small mound of stone, plainly mkd. 1/152, from which an original bearing tree</p> <p>A spruce, 36 ins. diam., bears S. 80' W., 59 lks. dist., mkd. 1/152.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 2½ ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;">  <p>T16N R80W</p> <p>MS 152</p> <p>1</p> <p>BNL</p> <p>S 10</p> <p>1998</p> </div> <p>from which new a bearing tree</p> <p>A spruce, 9 ins. diam., bears S. 19' E., 73 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <p>From this point, the ¼ sec. cor. of secs. 10 and 11, bears N. 73° 45' E., 5.57 chs. dist.</p> <p>S. 42° 55' W., on line 1-2, M.S. No. 152, Bank Note Lode.</p> <p>Over gently rolling terrain.</p>
22.58	<p>Cor. No. 2, M.S. No. 152, Bank Note Lode, identical with Cor. No. 2, M.S. No. 152, Wyoming Lode.</p>
	<p>From Cor. No. 3, M.S. No. 152, Bank Note Lode, identical with Cor. No. 3, M.S. No. 152, Wyoming Lode.</p> <p>N. 42° 08' E., on line 3-4, M.S. No. 152, Bank Note Lode.</p> <p>Over gently rolling terrain.</p>
22.68	<p>Cor. No. 4, M.S. No. 152, Bank Note Lode, monumented with a quartzite stone, 28x13x11 ins., firmly set 10 ins. in the ground, in a small mound of stone, plainly mkd. 4/152, on SW. face, from which an original bearing tree</p>

Dependent Resurvey of Mineral Survey No. 152,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>A spruce, 24 ins. diam., bears N. 89' W., 16 lks. dist., mkd. 4/152. (Record: S. 58° W., 7.3 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W S 10</p>  <p>MS 152 BNL 1998</p> </div> <p>from which a new bearing tree</p> <p>A spruce, 13 ins. diam., bears N. 16' E., 37 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>S. 47° 06' E., on line 1-4, M.S. No. 152, Bank Note Lode.</p> <p>Over gently rolling terrain.</p> <p>9.16 Cor. No. 1, M.S. No. 152, Bank Note Lode.</p> <hr/> <p>Dependent Resurvey, Portion of Mineral Survey No. 157 T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>(Restoring the surveys executed by Charles Bellamy in 1901)</p> <hr/> <p>From Cor. No. 2, M.S. No. 157, Golden Wedge Lode, identical with Cor. No. 2, M.S. No. 85, Acme Lode.</p> <p>N. 45° 52' E., on line 2-3, M.S. No. 157, Golden Wedge Lode.</p> <p>Over gently rolling terrain.</p>

Dependent Resurvey, Portion of Mineral Survey No. 157,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
3.18	Intersect line 1-4, M.S. No. 150, Bridal Veil Lode, at a point from which Cor. No. 4, M.S. No. 150, Bridal Veil Lode, identical with Cor. No. 1, M.S. No. 150, Enterprise Lode, bears S. 26° 14' E., 2.26 chs. dist.
10.46	Intersect line 1-2, M.S. No. 150, Bridal Veil Lode, at a point from which Cor. No. 1, M.S. No. 150, Bridal Veil Lode, bears S. 64° 24' W., 6.93 chs. dist.
22.42	<p>Cor. No. 3, M.S. No. 157, Golden Wedge Lode, monumented with a quartzite stone, 22x6x5 ins., firmly set 8 ins. in the ground, in a mound of stone, 3 ft. base to top, plainly mkd. 3/157 on W. face, from which an original bearing tree</p> <p style="padding-left: 40px;">A spruce, 28 ins. diam., bears S. 22° E., 25 lks. dist., mkd. 3/157. (Record: S. 46° 05' E., 17.5 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T16N R80W</p>  <p>1998</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 24° E., 35 lks. dist., mkd. 3-157 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 33° W., 52 lks. dist., mkd. 3-157 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p>
	<p>N. 36° 41' W., on line 3-4, M.S. No. 157, Golden Wedge Lode.</p> <p>Over gently rolling terrain.</p>
8.49	Cor. No. 4, M.S. No. 157, Golden Wedge Lode, monumented with a quartzite stone, 14x13x6 ins., firmly set 7 ins. in the ground, in a small mound of stone, plainly mkd. 4/157 on S. face, from which an original bearing tree


Dependent Resurvey, Portion of Mineral Survey No. 157,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS

A double trunked spruce, 21 ins. diam., bears
S. 23° E., 48 lks. dist., mkd. 4/157 BT.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in
the ground, in a mound of stone, 3 ft. to top, with magnetic
aluminum cap mkd.



from which new bearing trees

A spruce, 16 ins. diam., bears S. 43° W., 28 lks.
dist., mkd. XBT.

A spruce, 13 ins. diam., bears N. 55° E., 8 lks.
dist., mkd. 4/157 GW BT.

Bury the original cor. stone alongside the aluminum post in the
mound of stone.

S. 45° 46' W., on line 1-4, M.S. No. 157, Golden Wedge Lode.

Over gently rolling terrain.

22.55

Cor. No. 1, M.S. No. 157, Golden Wedge.

Dependent Resurvey, Portion of Mineral Survey No. 264
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

(Restoring the survey executed by
T. Russell Countryman in 1903)

From Cor. No. 2, M.S. 264, Mohawk Lode, on line 3-4, Lakeside
Placer, monumented with a granite stone, 16x8x6 ins., firmly set
7 ins. in the ground, plainly mkd. 2/264 on NE. face, from which
an original bearing tree

Dependent Resurvey, Portion of Mineral Survey No. 264,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>22.76</p>	<p>A balsam fir, 11 ins. diam., bears S. 41° W., 14 lks. dist., mkd. BT 2/264. (Record: S. 41° 02' W., 9.1 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W MS 264 ML 2 S 16 MS 92 LP 1998</p> </div> <p>from which new bearing trees</p> <p>A fir, 14 ins. diam., bears N. 85° E., 22 lks. dist., mkd. XBT.</p> <p>A fir, 12 ins. diam., bears S. 3° E., 15 lks. dist., mkd. 2-264 BT.</p> <p>A spruce, 9 ins. diam., bears S. 73° W., 64 lks. dist., mkd. S 16 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <p>N. 40° 44' W., on line 2-3, M.S. No. 264, Mohawk Lode.</p> <p>Over gently rolling terrain.</p> <p>Cor. No. 3, M.S. No. 264, Mohawk Lode, monumented with a granite stone, 14x7x7 ins., firmly set 7 ins. in the ground, plainly mkd. 3/264 on SW. face, (Record: A pine post) from which original bearing trees</p> <p>A spruce, 31 ins. diam., bears N. 12° E., 17 lks. dist., mkd. BT 3/264. (Record: N. 7° 02' E., 13.7 ft.)</p> <p>A spruce, 24 ins. diam., bears S. 55° W., 13 lks. dist., mkd. BT 3/264. (Record: S. 69° 25' W., 7.1 ft.)</p>
----------------------------	---

Dependent Resurvey, Portion of Mineral Survey No. 264,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p>	<p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> </div> <p>from which new bearing trees</p> <p>A spruce, 25 ins. diam., bears S. 53° E., 46 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p>N. 47° 39' E., on line 3-4, M.S. No. 264, Mohawk Lode.</p> <p>Over gently rolling terrain.</p> <p>9.07 Cor. No. 4, M.S. No. 264, Mohawk Lode, monumented with a granite stone, 14x14x9 ins., firmly set 9 ins. in the ground, in a small mound of stone, plainly mkd. 4/264 on SW. face, (Record: a pine post) from which the original bearing trees</p> <p>A balsam fir, 18 ins. diam., bears S. 57° E., 5 lks. dist., mkd. BT 4/264. (Record: S. 55° 45' E., 3.6 ft.)</p> <p>A spruce, 19 ins. diam., bears S. 14° W., 29 lks. dist., with healed blaze. (Record: S. 17° 05' W., 19.3 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p>
---------------	---

Dependent Resurvey, Portion of Mineral Survey No. 264,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming


CHAINS	<div data-bbox="850 300 1003 517" data-label="Diagram"> <p>T16N R80W S 16</p> </div> <p data-bbox="423 549 886 580">from which a new bearing tree</p> <p data-bbox="500 614 1260 674">A spruce, 12 ins. diam., bears N. 15° E. 19 lks. dist., mkd. 4-264 BT.</p> <p data-bbox="423 708 1424 768">Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <hr/> <p data-bbox="423 838 1278 870">S. 40° 47' E., on line 4-1, M.S. No. 264, Mohawk Lode.</p> <p data-bbox="423 902 862 934">Over gently rolling terrain.</p> <p data-bbox="280 963 1403 995">15.77 Intersect line 3-4, of unpatented M.S. No. 188, Gold Bug Lode.</p> <p data-bbox="423 1027 807 1059">At point of intersection</p> <p data-bbox="423 1091 1393 1187">Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p> <div data-bbox="771 1221 998 1406" data-label="Diagram"> <p>T16N R80W</p> <p>MS 264 ML 1998</p> </div> <p data-bbox="423 1442 586 1470">from which</p> <p data-bbox="500 1506 1276 1566">A spruce, 13 ins. diam., bears S. 33° W., 42 lks. dist., mkd. S 16 BT.</p> <p data-bbox="500 1602 1276 1661">A spruce, 12 ins. diam., bears N. 48° W., 31 lks. dist., mkd. MS 264 M BT.</p> <p data-bbox="423 1698 1424 1853">From this point, Cor. No. 3, of unpatented M.S. No. 188, Gold Bug Lode, bears S. 88° 18' W., 4.70 chs. dist., monumented with a quartzite stone, 16x6x5 ins., loosely set 4 ins. in the ground, in a small mound of stone, plainly mkd. 3-188 on N. face, from which the remains of an original bearing tree</p>
--------	--

Dependent Resurvey, Portion of Mineral Survey No. 264,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS							
	<p>From this point, Cor. No. 2, of unpatented M.S. No. 188, Gold Bug Lode, bears S. 88° 30' W., 8.25 chs. dist., monumented with a quartzite stone, 23x10x4 ins., loosely set 8 ins. in the ground, leaning downhill, in a mound of stone, 3 ft. base, plainly mkd. 2/188 on N. face, from which an original bearing tree</p> <p>A spruce, 24 ins. diam., bears S. 13° W., 29.2 lks. dist., with illegible scribing on partially healed blaze.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td>T16N R80W</td> </tr> <tr> <td></td> <td>MS 188</td> </tr> <tr> <td>MS 264</td> <td>2 GBL</td> </tr> </table> <p>1998</p> </div> <p>from which new bearing trees</p> <p>A spruce, 15 ins. diam., bears S. 39° E., 38 lks. dist., mkd. 2-188 BT.</p> <p>A fir, 12 ins. diam., bears S. 41° W., 49 lks. dist., mkd. XBT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p>		T16N R80W		MS 188	MS 264	2 GBL
	T16N R80W						
	MS 188						
MS 264	2 GBL						
22.76	<p>Cor. No. 1, M.S. No. 264, Mohawk Lode, on line 3-4, Lakeside Placer, monumented with a granite stone, 23x9x8 ins., firmly set 10 ins. in the ground, plainly mkd. 1/264 on S. face, (Record: a pine post) from which an original bearing tree</p> <p>A spruce, 22 ins. diam., bears S. 16° W., 18 lks. dist., mkd. BT 1/264. (Record: S. 15° 53' W., 12.3 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p>						

Dependent Resurvey, Portion of Mineral Survey No. 264,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS



from which new bearing trees

A spruce, 26 ins. diam., bears N. 53° W., 41 lks.
dist., mkd. 1-264 M BT.

A spruce, 18 ins. diam., bears N. 32° W., 45 lks.
dist., mkd. 1-264 BT.

Bury the original cor. stone alongside the aluminum post in the mound of stone.

From this point, the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, bears
S. 50° 17' E., 9.21 chs. dist.

From this same point, Cor. No. 2, of unpatented M.S. No. 188,
Gold Bug Lode, bears N. 85° 16' W., 9.10 chs. dist.

Dependent Resurvey of Mineral Survey No. 441,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

(Restoring the survey executed by
Robert Z. McCoy in 1909)

From Cor. No. 1, M.S. No. 441, Magnolia Lode, monumented with a
syenite stone, 28x13x8 ins., firmly set 17 ins. in the ground,
in a mound of stone, plainly mkd. 1-441 on S. face, from which
an original bear tree

A balsam fir, 16 ins. diam., bears N. 74° E., 21 lks.
dist., mkd. 1/441 BT. (Record: N. 75° 25' E.,
13.9 ft.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in
the ground, in a mound of stone, 3 ft. base to top, with
magnetic aluminum cap mkd.


Dependent Resurvey of Mineral Survey No. 441,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T16N R80W</p> <p style="text-align: center;">S 16 1 MS 441 ML</p> <p style="text-align: center;">1998</p> <p>from which new bearing trees</p> <p>A spruce, 9 ins. diam., bears S. 20' W., 26 lks. dist., mkd. 1-441 BT.</p> <p>A fir, 8 ins. diam., bears N. 70' W., 25 lks. dist., mkd. 1/441 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <p>From this point, the cor. of secs. 9, 10, 15, and 16, bears N. 27° 16' E., 8.57 chs. dist.</p> <p>N. 82° 24' E., on line 1-2, M.S. No. 441, Magnolia Lode.</p> <p>Over gently rolling terrain.</p>
4.02	Intersect the line bet. secs. 15 and 16, at a point from which the cor. of secs. 15, 16, 21, and 22, bears N. 0° 08' W., 7.17 chs. dist.
22.79	<p>Cor. No. 2, M.S. No. 441, Magnolia Lode, monumented with a quartzite stone, 19x14x11 ins., firmly set 8 ins. in the ground, in a mound of stone, plainly mkd. 2-441 on S. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T16N R80W</p> <p style="text-align: center;">S 15</p> <p style="text-align: center;">2 MS 441 ML</p> <p style="text-align: center;">1998</p>

Dependent Resurvey of Mineral Survey No. 441,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which new bearing trees</p> <p>A spruce, 8 ins. diam., bears N. 33° W., 33 lks. dist., mkd. 2/441 BT.</p> <p>A spruce, 8 ins. diam., bears S. 71° E., 48 lks. dist., mkd. 2/441 BT.</p> <p>Bury the original cor. stone alongside the aluminum post in the mound of stone.</p> <p>From this point, Cor. No. 3, M.S. No. 117, Idaho Lode, bears S. 0° 16' E., 2.77 chs. dist.</p> <hr/> <p>S. 7° 41' E., on line 2-3, M.S. No. 441, Magnolia Lode.</p> <p>Over gently rolling terrain.</p>
2.54	<p>Intersect line 3-4, M.S. No. 117, Idaho Lode, at a point from which Cor. No. 3, M.S. No. 117, Idaho Lode, bears S. 51° 55' W., 0.41 chs. dist.</p>
3.37	<p>Intersect line 2-3, M.S. No. 117, Idaho Lode, at a point from which Cor. No. 3, M.S. No. 117, Idaho Lode, bears N. 37° 43' W., 0.71 chs. dist.</p>
4.55	<p>Cor. No. 3, M.S. No. 441, Magnolia Lode, remonumented by John A. Steil, Wyoming Registered Land Surveyor No. 2500, with an aluminum post, 2½ ins. diam., firmly set, projecting 17 ins. above the ground, with aluminum cap mkd. 3 441 LS 2500 1984. This position is accepted as a careful and faithful perpetuation of the original cor. position, from which the remains of an original bearing tree</p> <p>A dead spruce, 32 ins. diam., bears S. 40° W., 11 lks. dist., mkd. BT/3 441. (Record: S. 64° 45' W., 8.6 ft.)</p> <p>from which the 1984 bearing trees, mkd. by Mr. Steil</p> <p>A spruce, 12 ins. diam., bears N. 84° E., 85 lks. dist., mkd. XBT.</p> <p>A spruce, 12 ins. diam., bears N. 20° W., 41 lks. dist., mkd. 3 441 BT.</p> <hr/>

Dependent Resurvey of Mineral Survey No. 441,
T. 16 N., R. 80 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>S. 82° 24' W., on line 3-4, M.S. No. 441, Magnolia Lode.</p> <p>Over gently rolling terrain.</p>
19.37	<p>Intersect the line bet. secs. 15 and 16, at a point from which the cor. of secs. 9, 10, 15 and 16, bears N. 0° 08' W., 11.76 chs. dist.</p>
22.80	<p>Cor. No. 4, M.S. No. 264, Magnolia Lode, monumented with a quartzite stone, 19x12x5 ins., firmly set 9 ins. in the ground, in a small mound of stone, plainly mkd. 4/441 on S. face, from which the remains of an original bearing tree</p> <p>A dead spruce, 26 ins. diam., bears N. 58' W., 48 lks. dist., with illegible scribing on partially healed blaze. (Record: N. 71° 45' W., 30.8 ft.)</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base to top, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T16N R80W</p>  </div> <p>1998</p>
	<p>from which new bearing trees</p> <p>A spruce, 12 ins. diam., bears S. 82' E. 13 lks. dist., mkd. 4-441 BT.</p> <p>A fir, 7 ins. diam., bears S. 51' W., 12 lks. dist., mkd. 4-441 BT.</p>
4.55	<p>N. 7° 35' W., on line 4-1, M.S. No. 441, Magnolia Lode.</p> <p>Over gently rolling terrain.</p> <p>Cor. No. 1, M.S. No. 441, Magnolia Lode.</p>

T. 16 N., R. 108 W., Sixth Principal Meridian, Wyoming

CHAINS	GENERAL DESCRIPTION
	<p>The area embraced by this survey is situated in the eastern central portion of Carbon County, Wyoming, approximately 12 airmiles west of Centennial, and 2 miles west of Medicine Bow Peak, within the Medicine Bow National Forest. The terrain is high rolling and mountainous, with the elevation ranging from about 9,700 feet to about 10,000 feet above sea level. The area is heavily timbered with pine, fir and spruce, light undergrowth consisting of a moderate growth of native grasses.</p> <p>Drainage in the area is all secondary to South Brush Creek, which drains westerly through the area, with numerous other creeks, draws, and ravines throughout the area. The area is accessible from Centennial, Wyoming, by Wyoming Highway 130, a distance of approximately 17 miles to Headquarters Park, then northerly on Forest Development Road No. 200 approximately 1 mile. There are numerous jeep trails in the area. The area resurveyed is uninhabited with several seasonal cabins located on private lands.</p>

CERTIFICATE OF SURVEY

We, Gregory W. Asher, Dana R. Bardsley, and Mickael D. Londe, U.S. Forest Service Cadastral Surveyors, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 7th day of July, 1986, we have dependently resurveyed a portion of the subdivisional lines, portions of Mineral Surveys 85, 92, 96, 157, 264, and Mineral Surveys 117, 146, 147, 150, 152 and 441, Township 16 North, Range 80 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by us and under our direction, said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

APR 23 2001

(Date)

APR 23 2001

(Date)

APR 23 2001

(Date)

Gregory W. Asher
(Cadastral Surveyor U.S.F.S.)

Dana R. Bardsley
(Cadastral Surveyor U.S.F.S.)

Michael D. Londe
(Cadastral Surveyor U.S.F.S.)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and portions of Mineral Surveys 85, 92, 96, 157, 264 and Mineral Surveys 150, 152, 157, 264, and 441, Township 16 North, Range 80 West, of the Sixth Principal Meridian, in the State of Wyoming, executed by Gregory W. Asher, Dana R. Bardsley, and Michael D. Londe, U.S. Forest Service Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

APR 23 2001

(Date)

John P. Lee
(Signature of Authorized Officer)