

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE

SIXTH STANDARD PARALLEL NORTH, THROUGH RANGES 87 AND 88 WEST,

THE ELEVENTH GUIDE MERIDIAN WEST, THROUGH TOWNSHIP 24 NORTH,

BETWEEN RANGES 88 AND 89 WEST,

AND

PORTIONS OF THE SOUTH AND EAST BOUNDARIES,

AND

SUBDIVISIONAL LINES

TOWNSHIP 24 NORTH, RANGE 88 WEST,

OF THE SIXTH PRINCIPAL MERIDIAN,

IN THE STATE OF WYOMING.

EXECUTED BY

LYNN A. FORBES

CADASTRAL SURVEYOR

Under Special Instructions dated MARCH 31, 1997, approved APRIL 4, 1997, which provided for the surveys included under Group Number 636, and assignment instructions dated APRIL 4, 1997.

Survey commenced May 20, 1997

Survey completed AUGUST 20, 1997

INDEX DIAGRAM

Township 24 North, Range 88 West

Sixth Standard Parallel North

7	6	5	4	4	3	2	
10 6 58	59 5 58	47 4 47	39 3 39	31 2 31	23 1 23		16
10 7 56	57 8 56	46 9 46	38 10 38	30 11 30	22 12 21		15
9 18 54	55 17 54	45 16 44	37 15 37	29 14 29	20 13 20		15
9 19 52	53 20 52	43 21 43	36 22 35	28 23 27	19 24 18		14
8 30 50	51 29 50	42 28 42	34 27 34	26 26 26	17 25		
7 31 13	49 32	41 33 12	33 34 12	25 35	36		

T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS

The following field notes are those of the dependent resurvey of a portion of the Sixth Standard Parallel North, through Ranges 87 and 88 West, the Eleventh Guide Meridian West, through Township 24 North, between Ranges 88 and 89 West, and portions of the south and east boundaries and subdivisional lines, Township 24 North, Range 88 West, of the Sixth Principal Meridian, Wyoming.

William O. Downey and Mortimer N. Grant surveyed the Sixth Standard Parallel North, through Range 88 West (north boundary) and the Eleventh Guide Meridian West (west boundary) in 1881. Joseph B. Shelby surveyed the south and east boundaries and the subdivisional lines in 1882. William O. Owen retraced the Sixth Standard Parallel North through Range 88 West, and the Eleventh Guide Meridian West in 1883. (did not change record) Mark D. King dependently resurveyed the exterior boundaries in 1938. Jerry L. Messick dependently resurveyed portions of the Sixth Standard Parallel North through Range 87 West and the east boundary in 1976-77.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 636, Wyoming, dated March 31, 1997.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data was thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

The survey was executed with a WILD theodolite Model T-1000, a WILD electronic distance meter Model DI-2000 and by chaining methods. The instruments were maintained in proper adjustment at all times. The direction of all lines refer to the true meridian, determined by hour angle observations of the sun at various points along the lines of survey and carried forward by sustained angulation.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The "DEEP-1" is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 22 inches long, weigh 22 ounces, and are magnetically detectable to an average depth of 8 feet.

T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>The geographic position of the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., based on NAD 83(1986) and determined by satellite positioning methods, is:</p> <p>Latitude 42° 01' 48.8" N., Longitude 107° 16' 25.9" W.</p> <p>The magnetic declination is 12½° E.</p>
	<p>Dependent Resurvey, Portion of the Sixth Standard Parallel North, Through Range 87 West, Sixth Principal Meridian, Wyoming</p>
	<p>(Restoring the dependent resurveys executed by Mark D. King in 1938)</p>
	<p>Beginning at the standard E. 1/16 sec. cor. of sec. 31, T. 25 N., R. 87 W., monumented with an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the field notes of the 1976-77 dependent resurvey, T. 24 N., R. 87 W.</p>
	<p>N. 89° 32' W., on the S. bdy. of sec. 31, T. 25 N., R. 87 W.</p>
	<p>Over gently rolling terrain.</p>
0.74	<p>The closing cor. of Tps. 24 N., Rs. 87 and 88 W., herinafter described.</p>
19.94	<p>The standard 1/4 sec. cor of sec. 31, on the S. bdy., T. 25 N., R. 87 W., monumented with an iron post, 1 in. diam., as described in the field notes of the 1976-77 dependent resurvey, T. 24 N., R. 87 W.</p>
	<p>N. 89° 49' W., on the S. bdy. of sec. 31, T. 25 N., R. 87 W.</p>
	<p>Over gently rolling terrain.</p>
1.50	<p>Underground pipeline, bears SSE. and NNW.</p>
18.74	<p>Point for the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 88 W., hereinafter described.</p>
24.25	<p>Underground pipeline, bears SE. and NW.</p>
40.07	<p>The standard cor. of Tps. 25 N., Rs. 87 and 88 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the,
Sixth Standard Parallel North, Through Range 87 West,
Sixth Principal Meridian, Wyoming

CHAINS	
	S C T25N R88W R87W S 36 S 31 <hr style="width: 50%; margin: auto;"/> 1938
	Cor. is located in fence extending N. and S.
	Dependent Resurvey, Portion of the Sixth Standard Parallel North, Through Range 88 West, Sixth Principal Meridian, Wyoming
	N. 89° 49' W., on the S. bdy. of sec. 36. Over gently rolling terrain.
16.61	The closing cor. of secs. 1 and 2, T. 24 N., R. 88 W., hereinafter described.
39.93	The standard 1/4 sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.
	S C 1/4 S 36 <hr style="width: 50%; margin: auto;"/> 1938
	N. 89° 45' W., beginning new measurement. Over gently rolling terrain.
18.71	Point for the 1/4 sec. cor. of sec. 2 only, T. 24 N., R. 88 W., hereinafter described.
35.00	Trail road, bears NE. and SW.
40.14	The standard cor. of secs. 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.
	S C T25N R88W S 35 S 36 <hr style="width: 50%; margin: auto;"/> 1938

6

Dependent Resurvey, Portion of the,
Sixth Standard Parallel North, Through Range 88 West,
Sixth Principal Meridian, Wyoming

CHAINS					
	N. 89° 51' W., on the S. bdy. of sec. 35. Over gently rolling terrain.				
20.59	Point for the closing cor. of secs. 2 and 3, T. 24 N., R. 88 W., hereinafter described.				
40.10	The standard 1/4 sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.				
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>S C</td></tr> <tr><td>1/4 S 35</td></tr> <tr><td style="border-top: 1px solid black;">1938</td></tr> </table>	S C	1/4 S 35	1938	
S C					
1/4 S 35					
1938					
	N. 89° 49' W., beginning new measurement. Over gently rolling terrain.				
20.67	Point for the 1/4 sec. cor. of sec. 3 only, T. 24 N., R. 88 W., hereinafter described.				
32.00	Trail road, bears S. and NW.				
39.97	The standard cor. of secs. 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.				
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>S C</td></tr> <tr><td>T25N R88W</td></tr> <tr><td>S 34 S 35</td></tr> <tr><td style="border-top: 1px solid black;">1938</td></tr> </table>	S C	T25N R88W	S 34 S 35	1938
S C					
T25N R88W					
S 34 S 35					
1938					
	N. 89° 43' W., on the S. bdy. of sec. 34. Over gently rolling terrain.				
0.50	Trail road, bears ENE. and WSW.				
20.87	Point for the closing cor. of secs. 3 and 4, T. 24 N., R. 88 W., hereinafter described.				
37.00	Underground pipeline, bears NE. and SW.				

7

Dependent Resurvey, Portion of the,
Sixth Standard Parallel North, Through Range 88 West,
Sixth Principal Meridian, Wyoming

CHAINS	
40.16	<p>The standard 1/4 sec. cor. of sec. 34, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S C 1/4 S 34 <hr/>1938</p> <hr/> <p>N. 89° 49' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
7.50	Trail road, bears N. and S.
21.12	Point for the 1/4 sec. cor. of sec. 4 only, T. 24 N., R. 88 W., hereinafter described.
40.00	<p>The standard cor. of secs. 33 and 34, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T25N R88W S 33 S 34 <hr/>1938</p> <hr/> <p>S. 89° 41' W., on the S. bdy. of sec. 33.</p> <p>Over gently rolling terrain.</p>
21.53	Point for the closing cor. of secs. 4 and 5, T. 24 N., R. 88 W., hereinafter described.
39.75	<p>The standard 1/4 sec. cor. of sec. 33, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S C 1/4 S 33 <hr/>1938</p> <hr/> <p>N. 89° 17' W., beginning new measurement.</p>

80

Dependent Resurvey, Portion of the,
Sixth Standard Parallel North, Through Range 88 West,
Sixth Principal Meridian, Wyoming

CHAINS									
	Over gently rolling terrain.								
22.06	Point for the 1/4 sec. cor. of sec. 5 only, T. 24 N., R. 88 W., hereinafter described.								
40.22	The standard cor. of secs. 32 and 33, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">S</td><td style="padding: 0 10px;">C</td></tr> <tr><td colspan="2" style="padding: 0 10px;">T25N R88W</td></tr> <tr><td style="padding: 0 10px; border-right: 1px solid black;">S 32</td><td style="padding: 0 10px;">S 33</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; padding: 0 10px;">1938</td></tr> </table>	S	C	T25N R88W		S 32	S 33	1938	
S	C								
T25N R88W									
S 32	S 33								
1938									
	N. 88° 40' W., on the S. bdy. of sec. 32.								
	Over gently rolling terrain.								
22.12	Point for the closing cor. of secs. 5 and 6, T. 24 N., R. 88 W., hereinafter described.								
39.24	The standard 1/4 sec. cor. of sec. 32, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">S</td><td style="padding: 0 10px;">C</td></tr> <tr><td colspan="2" style="padding: 0 10px;">1/4 S 32</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; padding: 0 10px;">1938</td></tr> </table>	S	C	1/4 S 32		1938			
S	C								
1/4 S 32									
1938									
	S. 89° 39' W., beginning new measurement.								
	Over gently rolling terrain.								
17.54	Point for the 1/4 sec. cor. of sec. 6 only, T. 24 N., R. 88 W., hereinafter described.								
41.63	The standard cor. of sec. 31 and 32, monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">S</td><td style="padding: 0 10px;">C</td></tr> <tr><td colspan="2" style="padding: 0 10px;">T25N R88W</td></tr> <tr><td style="padding: 0 10px; border-right: 1px solid black;">S 31</td><td style="padding: 0 10px;">S 32</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; padding: 0 10px;">1938</td></tr> </table>	S	C	T25N R88W		S 31	S 32	1938	
S	C								
T25N R88W									
S 31	S 32								
1938									

Dependent Resurvey, Portion of the,
Sixth Standard Parallel North, Through Range 88 West,
Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 89° 51' W., on the S. bdy. of sec. 31.</p> <p>Over gently rolling terrain.</p> <p>6.09 Point for the closing cor. of Tps. 24 N., Rs. 88 and 89 W., hereinafter described.</p> <p>39.15 The standard 1/4 sec. cor. of sec. 31, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C</p> <p><u>1/4 S 31</u></p> <p>1938</p> </div> <hr/> <p style="text-align: center;">Dependent Resurvey, of the Eleventh Guide Meridian West, Through Township 24 North, Between Ranges 88 and 89 West, Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the dependent resurvey executed by Mark D. King in 1938)</p> <hr/> <p>From the cor. of Tps. 23 and 24 N., Rs. 88 and 89 W., monumented with and iron post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24N</p> <p>R89W R88W</p> <p>S 36 S 31</p> <hr style="width: 50%; margin: auto;"/> <p>S 1 S 6</p> <p>T23N</p> <p>1938</p> </div> <p>N. 0° 15' E., bet. secs. 31 and 36.</p> <p>Over nearly level terrain.</p> <p>40.03 Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the 1938 resurvey monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p>
--------	--

Dependent Resurvey, of the Eleventh Guide Meridian West,
Through Township 24 North, Between Ranges 88 and 89 West,
Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T24N R89W R88W 1/4 S 36 S 31 1997</p>
80.06	<p>Cor. is located in abandoned corrals.</p> <p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W R88W S 25 S 30 ----- S 36 S 31 1938</p>
	<p>N. 0° 19' E., bet. secs. 25 and 30.</p> <p>Over nearly level terrain.</p>
18.60	<p>Separation Creek (dry), course NE.</p>
40.00	<p>The 1/4 cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 25 S 30 1938</p>
	<p>N. 0° 14' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
39.99	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W R88W S 24 S 19 ----- S 25 S 30 1938</p>

Dependent Resurvey, of the Eleventh Guide Meridian West,
Through Township 24 North, Between Ranges 88 and 89 West,
Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 0° 10' E., bet. secs. 19 and 24.</p> <p>Over nearly level terrain.</p>
40.03	<p>The 1/4 cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">1/4 S 24 S 19 1938</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 0° 16' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
40.03	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R89W R88W S 13 S 18 ----- S 24 S 19 1938</p> <hr style="width: 60%; margin: auto;"/>
	<p>N. 0° 10' E., bet. secs. 13 and 18.</p> <p>Over nearly level terrain.</p>
40.00	<p>The 1/4 cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">1/4 S 13 S 18 1938</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 0° 08' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
39.97	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p>

Dependent Resurvey, of the Eleventh Guide Meridian West,
Through Township 24 North, Between Ranges 88 and 89 West,
Sixth Principal Meridian, Wyoming

CHAINS	
	T24N R89W R88W S 12 S 7 <hr style="width: 50%; margin: auto;"/> S 13 S 18 1938
	<hr/> N. 0° 23' E., bet. secs. 7 and 12. Over nearly level terrain.
7.60	U.S. Highway No. 287, bears SSE. and NNW.
40.04	The 1/4 cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.
	1/4 S 12 S 7 1938
	<hr/> N. 0° 05' W., beginning new measurement. Over nearly level terrain.
40.01	The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.
	T24N R89W R88W S 1 S 6 <hr style="width: 50%; margin: auto;"/> S 12 S 7 1938
	<hr/> N. 0° 16' E., bet. secs. 1 and 6. Over gently rolling terrain.
19.99	Point for the S. 1/16 sec. cor. of secs. 1 and 6. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.

Dependent Resurvey, of the Eleventh Guide Meridian West,
Through Township 24 North, Between Ranges 88 and 89 West,
Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T24N R89W R88W S1/16 S 1 S 6 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
39.98	<p>The 1/4 cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">1/4 S 1 S 6 1938</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 0° 08' E., beginning new measurement.</p>
	<p>Over nearly level terrain.</p>
40.03	<p>The closing cor. of secs. 1 and 6, at intersection with the Sixth Standard Parallel North, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R88W S 31</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S 1 S 6 R89W R88W T24N C C 1938</p>
	<p>From this point, the standard cor. of secs. 31 and 32, T. 25 N., R. 88 W., bears S. 89° 51' E., 6.09 chs. dist.</p>
	<hr/> <p style="text-align: center;">Dependent Resurvey, Portion of the South Boundary, T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming</p> <hr/>
	<p style="text-align: center;">(Restoring the dependent resurvey executed by Mark D. King in 1938)</p> <hr/>
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the South Boundary,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T24N</td><td>R88W</td></tr> <tr><td>S 34</td><td>S 35</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T23N</td></tr> <tr><td colspan="2">1938</td></tr> </table>	T24N	R88W	S 34	S 35	<hr/>		S 3	S 2	T23N		1938	
T24N	R88W												
S 34	S 35												
<hr/>													
S 3	S 2												
T23N													
1938													
	<p>N. 89° 49' W., bet. secs. 3 and 34.</p> <p>Over gently rolling terrain.</p>												
40.34	<p>The 1/4 cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 34</td></tr> <tr><td>1/4 ———</td></tr> <tr><td>S 3</td></tr> <tr><td>1938</td></tr> </table> <hr style="width: 30%; margin: 10px auto;"/>	S 34	1/4 ———	S 3	1938								
S 34													
1/4 ———													
S 3													
1938													
	<p>N. 89° 50' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>												
40.42	<p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T24N</td><td>R88W</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T23N</td></tr> <tr><td colspan="2">1938</td></tr> </table> <hr style="width: 60%; margin: 10px auto;"/>	T24N	R88W	S 33	S 34	<hr/>		S 4	S 3	T23N		1938	
T24N	R88W												
S 33	S 34												
<hr/>													
S 4	S 3												
T23N													
1938													
	<p>N. 89° 51' W., bet. secs. 4 and 33.</p> <p>Over gently rolling terrain.</p>												
40.11	<p>The 1/4 cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 33</td></tr> <tr><td>1/4 ———</td></tr> <tr><td>S 4</td></tr> <tr><td>1938</td></tr> </table> <hr style="width: 30%; margin: 10px auto;"/>	S 33	1/4 ———	S 4	1938								
S 33													
1/4 ———													
S 4													
1938													

Dependent Resurvey, Portion of the South Boundary,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS													
	WEST, beginning new measurement.												
	Over gently rolling terrain.												
40.07	The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T24N</td><td>R88W</td></tr> <tr><td>S 32</td><td>S 33</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2">T23N</td></tr> <tr><td colspan="2">1938</td></tr> </table>	T24N	R88W	S 32	S 33	<hr/>		S 5	S 4	T23N		1938	
T24N	R88W												
S 32	S 33												
<hr/>													
S 5	S 4												
T23N													
1938													
	From the cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T24N</td><td>R88W</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">T23N</td></tr> <tr><td colspan="2">1938</td></tr> </table>	T24N	R88W	S 31	S 32	<hr/>		S 6	S 5	T23N		1938	
T24N	R88W												
S 31	S 32												
<hr/>													
S 6	S 5												
T23N													
1938													
	S. 89° 05' W., bet. secs. 6 and 31.												
	Over gently rolling terrain.												
40.12	The 1/4 cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>S 31</td></tr> <tr><td>1/4 ———</td></tr> <tr><td>S 6</td></tr> <tr><td>1938</td></tr> </table>	S 31	1/4 ———	S 6	1938								
S 31													
1/4 ———													
S 6													
1938													
	S. 88° 53' W., beginning new measurement.												
	Over gently rolling terrain.												
33.12	The cor. of Tps. 23 and 24 N., Rs. 88 and 89 W.												

Dependent Resurvey, Portion of the East Boundary,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<p>(Restoring the dependent resurvey executed by Mark D. King in 1938, and Jerry L. Messick in 1976-77)</p> <hr/>												
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p>												
	<table border="0"> <tr><td>T24N</td><td></td></tr> <tr><td>R88W R87W</td><td></td></tr> <tr><td>S 24 S 19</td><td></td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 25 S 30</td><td></td></tr> <tr><td>1938</td><td></td></tr> </table>	T24N		R88W R87W		S 24 S 19		<hr/>		S 25 S 30		1938	
T24N													
R88W R87W													
S 24 S 19													
<hr/>													
S 25 S 30													
1938													
	<p>Cor. is located in fence, extending N. and S. N. 0° 18' W., bet. secs. 19 and 24. Over gently rolling terrain, along fence.</p>												
10.00	County road, bears NE. and SW.												
40.04	The 1/4 cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.												
	<table border="0"> <tr><td>1/4</td><td></td></tr> <tr><td>S 24 S 19</td><td></td></tr> <tr><td>1938</td><td></td></tr> </table> <hr/>	1/4		S 24 S 19		1938							
1/4													
S 24 S 19													
1938													
	<p>N. 0° 10' W., beginning new measurement. Over gently rolling terrain, along fence.</p>												
40.04	The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.												
	<table border="0"> <tr><td>T24N</td><td></td></tr> <tr><td>R88W R87W</td><td></td></tr> <tr><td>S 13 S 18</td><td></td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 24 S 19</td><td></td></tr> <tr><td>1938</td><td></td></tr> </table> <hr/>	T24N		R88W R87W		S 13 S 18		<hr/>		S 24 S 19		1938	
T24N													
R88W R87W													
S 13 S 18													
<hr/>													
S 24 S 19													
1938													

Dependent Resurvey, Portion of the East Boundary,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 0° 07' W., bet. secs. 13 and 18.</p> <p>Over gently rolling terrain, along fence.</p>
40.09	<p>The 1/4 cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">1/4 S 13 S 18 1938</p> <hr/>
	<p>N. 0° 13' W., beginning new measurement.</p> <p>Over gently rolling terrain, along fence.</p>
40.01	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R88W R87W S 12 S 7 ----- S 13 S 18 1938</p> <hr/>
	<p>N. 0° 13' W., bet. secs. 7 and 12.</p> <p>Over gently rolling terrain, along fence.</p>
40.05	<p>The 1/4 cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">1/4 S 12 S 7 1938</p> <hr/>
	<p>N. 0° 12' W., beginning new measurement.</p> <p>Over gently rolling terrain, along fence.</p>
40.01	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the East Boundary,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T24N R88W R87W S 1 S 6 <hr style="width: 50%; margin: auto;"/> S 12 S 7 1938
	<p>N. 6° 04' W., bet. secs. 1 and 6.</p> <p>Over gently rolling terrain, along fence.</p>
40.53	<p>The 1/4 cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> 1/4 S 1 S 6 1938 </p> <p>Cor. is located in fence extending W., and E. 40 lks. to intersection of fences extending E., S. and W.</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 0° 03' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
35.77	<p>The closing cor. of secs. 1 and 6, at intersection with the Sixth Standard Parallel North, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above the ground, with a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;"> T25N R87W S 31 <hr style="width: 50%; margin: auto;"/> S 1 S 6 R88W R87W T24N C C 1938 </p> <p>From this point, the standard E. 1/16 sec. cor. of sec. 31, T. 25 N., R. 87 W., bears S. 89° 32' E., 0.74 chs. dist.</p> <hr style="width: 80%; margin: auto;"/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS

(Restoring the survey executed by
Joseph B. Shelby in 1882)

From the point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.

T24N R88W	
S 26	S 25

S 35	S 36
1997	

Set a steel fence post alongside the iron post.

Cor. is located 15 lks. W., of Separation Creek (dry), drains S.

From this point, the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., bears S. 89° 43' E., 80.31 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T24N	
R88W R87W	
S 25	S 30

S 36	S 31
1938	

From this same point, the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., bears S. 0° 11' E., 80.35 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

T24N R88W	
S 35	S 36

S 2	S 1
T23N	
1938	

The control lines were fully retraced, and no evidence of the intervening cors. was found.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 0° 04' W., bet. secs. 25 and 26.</p>
	<p>Over gently rolling terrain.</p>
1.00	<p>Separation Creek (dry), drains SSE. from NW.</p>
24.00	<p>Graded dirt road, bears ENE. and WSW.</p>
40.175	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R88W 1/4 S 26 S 25 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
80.35	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a sandstone, 9x6x4 ins., loosely set 4 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R88W S 23 S 24 ----- S 26 S 25 1997</p>
	<p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p>
	<hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.</p>
	<p>N. 89° 41' W., bet. secs. 24 and 25.</p>
	<p>Over gently rolling terrain.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
16.40	Dirt road, bears NE. and SW.
39.87	<p>The 1/4 sec. cor. of secs. 24 and 25, monumented with a sandstone, 11x8x2 ins., loosely set 5 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T24N R88W S 24 1/4 ——— S 25 1997</p> <p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 41' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
8.00	Trail road, bears SSE. and NNW.
39.88	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0° 40' W., bet. secs. 23 and 24.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T24N R88W 1/4 S 23 S 24 1997</p> <p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS											
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T24N R88W</td></tr> <tr><td>S 14</td><td>S 13</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 23</td><td>S 24</td></tr> <tr><td colspan="2">1997</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>N. 89° 45' W., bet. secs. 13 and 24.</p> <p>Over rolling terrain.</p>	T24N R88W		S 14	S 13	<hr/>		S 23	S 24	1997	
T24N R88W											
S 14	S 13										
<hr/>											
S 23	S 24										
1997											
40.165	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T24N R88W</td></tr> <tr><td colspan="2">S 13</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S 24</td></tr> <tr><td colspan="2">1997</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T24N R88W		S 13		1/4	—	S 24		1997	
T24N R88W											
S 13											
1/4	—										
S 24											
1997											
80.33	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0° 28' W., bet. secs. 13 and 14.</p> <p>Over rolling terrain.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original cor.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T24N R88W 1/4 S 14 S 13 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>80.00 The cor. of secs. 11, 12, 13 and 14, monumented with a sandstone, 13x8x6 ins., firmly set 6 ins. in the ground, plainly mkd. 1 groove on E. face, and 4 grooves on S. face, with an iron pipe, 5/8 in. diam., 9 ins. long, firmly set 5 ins. in the ground alongside, with a mound of stone, 1 ft. base, 1 ft. high, W. of the cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T24N R88W S 11 S 12 ----- S 14 S 13 1997</p> <p>Bury the original cor. stone, the iron pipe, and set a steel fence post alongside the iron post. Rebuild the mound of stone, 1 ft. base, 1 ft. high, W. of the cor.</p>
	<hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p> <p>N. 89° 53' W., bet. secs. 12 and 13.</p> <p>Over rolling terrain.</p> <p>40.73 The 1/4 sec. cor. of secs. 12 and 13, monumented with a sandstone, 8x6x4 ins., firmly set 6 ins. in the ground, plainly mkd. 1/4 on N. face, with an iron pipe, 14 ins. long, 5/8 in. diam., firmly set 8 ins. in the ground alongside.</p> <p>At the corner point</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T24N R88W S 12 1/4 ——— S 13 1997</p> <p>Bury the original cor. stone, the iron pipe, and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 48' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
40.01	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/>
	<p>N. 0° 06' E., bet. secs. 11 and 12.</p> <p>Over rolling terrain.</p>
7.70	<p>Trail road, bears E. and W.</p>
36.00	<p>Trail road, bears NE. and SW.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T24N R88W 1/4 S 11 S 12 1997</p> <p>Set a steel fence post alongside the iron post.</p>
80.08	<p>The cor. of secs. 1, 2, 11 and 12, remonumented by Bradley H. Clow, Wyoming Registered Land Surveyor No. 548, with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	WLCJ LS 548 2 1 T24N --- 11 12 R88W O C 1980
	<p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp. N. 89° 50' W., bet. secs. 1 and 12.</p> <p>Over rolling terrain.</p>
40.14	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> T24N R88W S 1 1/4 ——— S 12 1997 </div>
80.28	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0° 04' E., bet. secs. 1 and 2.</p> <p>Over gently rolling terrain.</p>
39.81	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with a broken and weathered sandstone, 8x8x2 ins., loosely set 4 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R88W 1/4 S 2 S 1 1997</p>
	<p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p>
	<p style="text-align: center;">_____</p> <p>N. 0° 03' E., beginning new measurement.</p>
	<p>Over gently rolling terrain.</p>
0.58	<p>Fence, bears E. and W.</p>
36.32	<p>The original closing cor. of secs. 1 and 2, monumented with a sandstone, 14x8x4 ins., loosely set 5 ins. in the ground, plainly mkd. CC on S. face, no other mks. visible. Add the mks. AM and bury the stone in place, 6 ins. below the surface of the ground.</p>
36.37	<p>Point for the closing cor. of secs. 1 and 2, at intersection with the Sixth Standard Parallel North.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R88W S 36</p>
	<p style="text-align: center;">_____</p> <p style="text-align: center;">C C S 2 S 1 T24N R88W 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>From this point, the standard cor. of Tps. 25 N., Rs. 87 and 88 W., bears S. 89° 49' E., 16.61 chs. dist.</p>
	<p style="text-align: center;">_____</p> <p>The point for the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 88 W., is at midpoint on the N. bdy. of sec. 1.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R87W</p> <hr style="width: 20%; margin: auto;"/>
	<p style="text-align: center;">1/4 S 1</p>
	<p style="text-align: center;">T24N R88W</p>
	<p style="text-align: center;">1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>From this point, the standard 1/4 sec. cor. of sec. 31, T.25 N., R. 87 W., bears S. 89° 49' E., 18.74 chs. dist.</p> <hr/>
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.</p>
	<p>N. 0° 08' E., bet. secs. 34 and 35.</p>
	<p>Over gently rolling terrain.</p>
39.60	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with a mound of stone, 3 ft. base, 2 ft. high, no mkd. stone found. This position is accepted as the best available evidence of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R88W</p>
	<p style="text-align: center;">1/4</p>
	<p style="text-align: center;">S 34 S 35</p>
	<p style="text-align: center;">1997</p>
	<p>Set a steel fence post alongside the iron post.</p> <hr/>
	<p>N. 0° 36' W., beginning new measurement.</p>
	<p>Over gently rolling terrain.</p>
36.15	<p>Graded gravel road, bears NE. and SW.</p>
40.32	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T24N R88W</td> </tr> <tr> <td style="text-align: center;">S 27</td> <td style="text-align: center;">S 26</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 34</td> <td style="text-align: center;">S 35</td> </tr> <tr> <td colspan="2" style="text-align: center;">1997</td> </tr> </table>	T24N R88W		S 27	S 26	-----		S 34	S 35	1997	
T24N R88W											
S 27	S 26										

S 34	S 35										
1997											
	<p>Set a steel fence post alongside the iron post.</p> <hr/>										
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89° 46' W., bet. secs. 26 and 35.</p> <p>Over gently rolling terrain.</p>										
40.10	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T24N R88W</td> </tr> <tr> <td></td> <td style="text-align: center;">S 26</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">-----</td> </tr> <tr> <td></td> <td style="text-align: center;">S 35</td> </tr> <tr> <td colspan="2" style="text-align: center;">1997</td> </tr> </table>	T24N R88W			S 26	1/4	-----		S 35	1997	
T24N R88W											
	S 26										
1/4	-----										
	S 35										
1997											
	<p>Set a steel fence post alongside the iron post, and raise a mound of stone, 1 ft. base, 1 ft. high, N. of the cor.</p>										
72.00	<p>Graded gravel road, bears NE. and SW.</p>										
80.20	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/>										
	<p>N. 0° 31' E., bet. secs. 26 and 27.</p> <p>Over gently rolling terrain.</p>										
40.32	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original cor.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T24N R88W 1/4 S 27 S 26 1997</p>
80.64	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 26, 27, 34 and 35, monumented with a sandstone, 7x5x1 ins., firmly set 4 ins. in the ground, plainly mkd. 3 notches on E. edge, no other mks. visible. (Record: 2 notches on S. and 2 notches on E. edges)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T24N R88W S 22 S 23 ----- S 27 S 26 1997</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p>
8.00	<hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89° 59' W., bet. secs. 23 and 26.</p> <p>Over gently rolling terrain.</p> <p>Separation Creek (dry), drains S.</p>
39.68	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T24N R88W S 23 1/4 ——— S 26 1997</p>
79.36	<p>Set a steel fence post alongside the iron post. The cor. of secs. 22, 23, 26 and 27.</p> <hr/>
3.00	<p>N. 1° 23' W., bet. secs. 22 and 23. Over gently rolling terrain.</p>
40.005	<p>Seperation Creek (dry), drains NE. Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
80.01	<p style="text-align: center;">T24N R88W 1/4 S 22 S 23 1997</p> <p>Set a steel fence post alongside the iron post. Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T24N R88W S 15 S 14 ————— S 22 S 23 1997</p> <p>Set a steel fence post alongside the iron post.</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 13, 14, 23 and 24.
	S. 89° 59' W., bet. secs. 14 and 23.
	Over gently rolling terrain.
40.175	Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	T24N R88W S 14 1/4 ——— S 23 1997
	Set a steel fence post alongside the iron post.
80.35	The cor. of secs. 14, 15, 22 and 23.
	N. 0° 09' E., bet. secs. 14 and 15.
	Over gently rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	T24N R88W 1/4 S 15 S 14 1997
65.50	Trail road, bears E. and W.
80.00	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T24N R88W S 10 S 11 ----- S 15 S 14 1997
	Set a steel fence post alongside the iron post.
	From the cor. of secs. 11, 12, 13 and 14.
	S. 89° 59' W., bet. secs. 11 and 14.
	Over gently rolling terrain.
39.73	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	T24N R88W S 11 1/4 ——— S 14 1997
	Set a steel fence post alongside the iron post.
42.25	Trail road, bears NE. and SW.
79.46	The cor. of secs. 10, 11, 14 and 15.
	N. 0° 06' E., bet. secs. 10 and 11.
	Over gently rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	T24N R88W 1/4 S 10 S 11 1997

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS											
80.00	<p>Set a steel fence post alongside the iron post.</p> <p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T24N R88W</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td colspan="2">1997</td></tr> </table> </div>	T24N R88W		S 3	S 2	<hr/>		S 10	S 11	1997	
T24N R88W											
S 3	S 2										
<hr/>											
S 10	S 11										
1997											
	<p>Set a steel fence post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89° 55' W., bet. secs. 2 and 11.</p> <p>Over gently rolling terrain.</p>										
39.72	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T24N R88W</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td>S 11</td><td></td></tr> <tr><td colspan="2">1997</td></tr> </table> </div>	T24N R88W		S 2		1/4	<hr/>	S 11		1997	
T24N R88W											
S 2											
1/4	<hr/>										
S 11											
1997											
79.44	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 3° 24' W., bet. secs. 2 and 3.</p> <p>Over gently rolling terrain.</p>										
40.07	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R88W 1/4 S 3 S 2 1997</p>
41.02	<p>Set a steel fence post alongside the iron post.</p>
	<p>Fence, bears E. and W.</p>
76.73	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the Sixth Standard Parallel North, at proportionate distance; there is not remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R88W S 35</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">C C S 3 S 2 T24N R88W 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>From this point, the standard cor. of secs. 35 and 36, T. 25 N., R. 88 W., bears S. 89° 51' E., 20.59 chs. dist.</p>
	<hr/> <p>The point for the 1/4 sec. cor. of sec. 2 only, T. 24 N., R. 88 W., is at midpoint on the N. bdy. of sec. 2.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R87W</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 2 T24N R88W 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, the standard 1/4 sec. cor. of sec. 36, T.25 N., R. 88 W., bears S. 89° 45' E., 18.71 chs. dist.</p> <hr/>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp. N. 0° 06' W., bet. secs. 33 and 34.</p>
	<p>Over gently rolling terrain.</p>
12.00	<p>Graded gravel road, bears NE. and SW., trail road bears N.; thence along trail road.</p>
39.71	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with a sandstone, 24x8x8 ins., firmly set 12 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R88W 1/4 S 33 S 34 1997</p>
	<p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p>
	<p>Cor. is located on E. side of trail road, extending N. and S.</p> <hr/>
	<p>N. 0° 11' W., beginning new measurement.</p>
	<p>Over gently rolling terrain.</p>
39.95	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a mound of stone, 2 ft. base, 1 ft. high, no mkd. stone found. This position is accepted as the best available evidence of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T24N R88W S 28 S 27 ———— S 33 S 34 1997
	Set a steel fence post alongside the iron post and raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.
	From the cor. of secs. 26, 27, 34 and 35.
	S. 89° 59' W., bet. secs. 27 and 34.
	Over gently rolling terrain.
40.305	Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	T24N R88W S 27 1/4 ——— S 34 1997
	Set a steel fence post alongside the iron post.
80.00	Trail road, bears N. and S.
80.61	The cor. of secs. 27, 28, 33 and 34.
	N. 0° 28' W., bet. secs. 27 and 28.
	Over gently rolling terrain, along trail road.
40.78	Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS		
	T24N R88W 1/4 S 28 S 27 1997	
	Set a steel fence post alongside the iron post.	
42.00	Trail road, bears SSE. and NNW.	
81.56	The cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 7x5x2 ins., firmly set 4 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.	
	T24N R88W S 21 S 22 ———— S 28 S 27 1997	
	Bury the unmkd. stone and set a steel fence post alongside the iron post.	
	Cor. is located on top of S. bank of Separation Creek (dry), drains NE. from W.	
	<hr/>	
	From the cor. of secs. 22, 23, 26 and 27.	
	N. 89° 22' W., bet. secs. 22 and 27.	
	Over gently rolling terrain.	
1.00	Separation Creek (dry), drains NE.	
5.00	Same Creek (dry), drains S.	
40.99	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.	

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T24N R88W S 22 1/4 ——— S 27 1997</p>
	<p>Set a steel rod, 6 ft. long, alongside the iron post.</p>
81.98	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/>
	<p>N. 0° 23' W., bet. secs. 21 and 22.</p>
1.00	<p>Seperation Creek (dry), drains NE.</p>
	<p>Over gently rolling terrain.</p>
39.76	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R88W 1/4 S 21 S 22 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
79.51	<p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R88W S 16 S 15 ————— S 21 S 22 1997</p>
	<p>Set a steel fence post alongside the iron post.</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89° 42' W., bet. secs. 15 and 22.
	Over gently rolling terrain.
40.27	Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	T24N R88W S 15 1/4 ——— S 22 1997
	Set a steel fence post alongside the iron post.
80.54	The cor. of secs. 15, 16, 21 and 22.
	N. 1° 12' E., bet. secs. 15 and 16.
	Over gently rolling terrain.
39.765	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	T24N R88W 1/4 S 16 S 15 1997
	Set a steel fence post alongside the iron post.
43.75	Trail road, bears E. and W.
79.53	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 24 N., R. 88 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T24N R88W S 9 S 10 <hr style="width: 50%; margin: auto;"/> S 16 S 15 1997
	Set a steel fence post alongside the iron post.
	From the cor. of secs. 10, 11, 14 and 15.
	S. 89° 57' W., bet. secs. 10 and 15.
	Over gently rolling terrain.
39.535	Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	T24N R88W S 10 1/4 ——— S 15 1997
	Set a steel fence post alongside the iron post.
79.07	The cor. of secs. 9, 10, 15 and 16.
	N. 0° 13' E., bet. secs. 9 and 10.
	Over nearly level terrain.
39.755	Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	T24N R88W 1/4 S 9 S 10 1997