

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.87	<p>N. 89° 58' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/>
5.00	<p>N. 0° 20' E., bet. secs. 2 and 3.</p> <p>Over gently rolling terrain.</p> <p>Trail road, bears NE. and SW.</p>
39.93	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with a sandstone, 24x8x4 ins., firmly set 18 ins. in the ground, plainly mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W 1/4 S 3 S 2 1998</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr/>
1.00	<p>NORTH, with record bearing, beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>Fence, bears E. and W.</p>
40.37	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the Sixth Standard Parallel North; there is no remaining evidence of the original cor. This method of restoration at record bearing from the 1/4 sec. cor. of secs. 2 and 3 to intersection with the Sixth Standard Parallel North was determined to be the most applicable to determine the position of the original cor., as explained on page 1.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS

T25N R89W
S 35

S 3	S 2
T24N	R89W
C C	
1999	

Set a steel fence post alongside the iron post.

Cor. is located in dry lake bed.

From this point, the standard cor. of secs. 35 and 36, T. 25 N., R. 89 W., bears S. 89° 55' E., 6.27 chs. dist.

The point for the 1/4 sec. cor. of sec. 2 only, T. 24 N., R. 89 W., is at midpoint on the N. bdy. of sec. 2.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T25N R88W

1/4 S 2
T24N R89W
1999

Set a steel fence post alongside the iron post.

From this point, the 1/4 sec. cor. of sec. 36, T. 25 N., R. 89 W., bears S. 89 ° 39' E., 6.23 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T24N R89W
S 33 | S 34

S 4 | S 3
T23N
1938

N. 0° 03' E., bet. secs. 33 and 34.

Over nearly level terrain.

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
7.00	Underground pipeline, bears NE. and SW.
40.08	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with a sandstone, 12x4x2 ins., firmly set 10 ins. in the ground, plainly mkd. 1/4 on W. face, with 4 stones projecting 18x14x4 ins. in 4 cardinal directions.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W 1/4 S 33 S 34 1999</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post. Raise a mound of stone, 1 ft. base, 1 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
27.40	Mineral X road (asphalt), bears ENE. and WSW.
39.98	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a sandstone, 30x14x3 ins., lying loose on the ground, plainly mkd. 3 notches on one edge, no other mks. visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W S 28 S 27 <hr style="width: 10%; margin: 0 auto;"/> S 33 S 34 1999</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post. Raise a mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89° 47' W., bet. secs. 27 and 34.</p> <p>Over nearly level terrain.</p>
13.50	Trail road and pipeline, bears SE. and NW.
39.84	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with a sandstone, 14x10x4 ins., lying loose on the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W S 27 1/4 ——— S 34 1999</p> <p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 46' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
39.85	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr style="width: 100%;"/> <p>N. 0° 05' W., bet. secs. 27 and 28.</p> <p>Over nearly level terrain.</p>
40.10	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with a weathered sandstone, 20x10x3 ins., loosely set 4 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T24N R89W 1/4 S 28 S 27 1999</p> <p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 06' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
40.08	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 18x12x2 ins., loosely set 4 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W S 21 S 22 ----- S 28 S 27 1999</p> <p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89° 40' W., bet. secs. 22 and 27.</p> <p>Over gently rolling terrain.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W S 22 1/4 ----- S 27 1999</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the iron post.
50.00	Trail road, bears N. and S.
79.20	Underground pipeline, bears SE. and NW.
79.98	The cor. of secs. 21, 22, 27 and 28.
	N. 0° 07' E., bet. secs. 21 and 22.
	Over gently rolling terrain.
0.75	Underground pipeline, bears SE. and NW.
39.96	The 1/4 sec. cor. of secs. 21 and 22, monumented with a sandstone, 12x4x3 ins., firmly set 8 ins. in the ground, plainly mkd. 1/4 on W. face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T24N R89W 1/4 S 21 S 22 1999</p>
	Bury the original cor. stone and set a steel fence post alongside the iron post.
	Cor. is located on W. edge of trail road extending N. and SE.; thence along trail road.
	N. 0° 53' E., beginning new measurement.
	Over gently rolling terrain.
39.94	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T24N R89W S 16 S 15 ----- S 21 S 22 1999</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the iron post.
	Cor. is located 45 lks. W. of trail road extending N. and S.
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89° 27' W., bet. secs. 15 and 22.
	Over rolling terrain.
39.69	Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T24N R89W S 15 1/4 ——— S 22 1999</p>
	Set a steel fence post alongside the iron post.
40.05	Trail road, bears N. and S.
79.38	The cor. of secs. 15, 16, 21 and 22.
	N. 0° 29' W., bet. secs. 15 and 16.
	Over gently rolling terrain, along trail road.
20.00	Trail road bears S. and NW.; leave road.
39.93	The 1/4 sec. cor. of secs. 15 and 16, monumented with a sandstone, 10x4x3 ins., firmly set 4 ins. in the ground, dimly mkd. 1/4 on W. face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T24N R89W 1/4 S 16 S 15 1999</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr/> <p>N. 0° 15' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>40.09 The cor. of secs. 9, 10, 15 and 16, monumented with a sandstone, 22x12x1 ins., lying loose on the ground, dimly mkd. 4 notches on a face, no other mks. visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T24N R89W</td></tr> <tr><td>S 9</td><td>S 10</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 16</td><td>S 15</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr/>	T24N R89W		S 9	S 10	<hr/>		S 16	S 15	1999	
T24N R89W											
S 9	S 10										
<hr/>											
S 16	S 15										
1999											
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89° 03' W., bet. secs. 10 and 15.</p> <p>Over rolling terrain.</p> <p>39.99 Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T24N R89W</td></tr> <tr><td colspan="2">S 10</td></tr> <tr><td colspan="2">1/4 <hr/></td></tr> <tr><td colspan="2">S 15</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T24N R89W		S 10		1/4 <hr/>		S 15		1999	
T24N R89W											
S 10											
1/4 <hr/>											
S 15											
1999											
79.98	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/>										

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 0° 18' E., bet. secs. 9 and 10.</p>
	<p>Over gently rolling terrain.</p>
39.90	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R89W 1/4 S 9 S 10 1999</p>
	<p>Set a steel fence post alongside the iron post.</p>
53.30	<p>Trail road, bears NE. and SW.</p>
79.80	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a sandstone, 16x16x4 ins., firmly set 12 ins. in the ground, plainly mkd. 2 grooves on E. face and 5 notches on S. face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R89W S 4 S 3 ----- S 9 S 10 1999</p>
	<p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p>
	<hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p>
	<p>N. 89° 50' W., bet. secs. 3 and 10.</p>
	<p>Over rolling terrain.</p>
39.92	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T24N R89W S 3 1/4 ——— S 10 1999</p>
79.84	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/>
	<p>N. 0° 11' E., bet. secs. 3 and 4.</p> <p>Over rolling terrain.</p>
40.48	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented with a sandstone, 40x20x12 ins., lying loose on the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R89W 1/4 S 4 S 3 1999</p>
	<p>Bury the unmkd. stone and set a steel fence post alongside the iron post. Raise a mound of stone 3 ft. base, 3 ft. high, W. of the cor.</p> <hr/>
	<p>NORTH, with record bearing, beginning new measurement.</p> <p>Over rolling terrain.</p>
39.85	<p>Point for the closing cor. of secs. 3 and 4, at intersection with the Sixth Standard Parallel North; there is no remaining evidence of the original cor. This method of restoration at record bearing from the 1/4 sec. cor. of secs. 3 and 4, to intersection with the Sixth Standard Parallel North was determined to be the most applicable to determine the position of the original cor. as explained on page 1.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T25N R89W S 34</p> <hr style="width: 50%; margin: auto;"/> <p style="text-align: center;">S 4 S 3 T24N R89W C C 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, the standard cor. of secs. 34 and 35, T. 25 N., R. 89 W., bears S. 89° 55' E., 6.24 chs. dist.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 3 only, T. 24 N., R. 89 W., is at midpoint on the N. bdy. of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R88W</p> <hr style="width: 50%; margin: auto;"/> <p style="text-align: center;">1/4 S 3 T24N R89W 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, the 1/4 sec. cor. of sec. 35, T. 25 N., R. 89 W., bears S. 89° 43' E., 6.24 chs. dist.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W S 32 S 33</p> <hr style="width: 50%; margin: auto;"/> <p style="text-align: center;">S 5 S 4 T23N 1938</p> <p>N. 0° 04' W., bet. secs. 32 and 33.</p> <p>Over nearly level terrain.</p>
--------	--

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.07	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with a sandstone, 10x8x2 ins., firmly set 5 ins. in the ground, plainly mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W 1/4 S 32 S 33 1999</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 04' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
16.50	Mineral X road, bears E. and W.
39.98	<p>The cor. of secs. 28, 29, 32 and 33, monumented with a railroad tie, firmly set, projecting 5 ft. above the ground. This position was accepted during the resurvey of sec. 29 conducted by Jeffrey B. Jones, Wyoming Registered Land Surveyor No. 5910, This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, alongside the railroad tie, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W S 29 S 28 <hr style="width: 10%; margin: 0 auto;"/> S 32 S 33 1999</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89° 51' W., bet. secs. 28 and 33.</p> <p>Over gently rolling terrain.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.84	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W S 28 1/4 ——— S 33 1999</p> <p>Set a steel fence post alongside the iron post.</p>
79.68	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0° 06' E., bet. secs. 28 and 29.</p> <p>Over gently rolling terrain.</p>
40.26	<p>The 1/4 sec. cor. of secs. 28 and 29, remonumented by Jeffrey B. Jones, Wyoming Registered Land Surveyor No. 5910, with a steel reinforcement rod, 24 ins. long, 5/8 ins. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 2 ft. base to top, with aluminum cap mkd. 1/4 S28 S29 1996 LS 5910. This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W 1/4 S 29 S 28 1999</p> <p>Deposit the steel reinforcement rod and set a steel fence post alongside the iron post.</p> <hr/> <p>N. 0° 06' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS						
40.03	<p>The cor. of secs. 20, 21, 28 and 29, remonumented by Jeffrey B. Jones, Wyoming Registered Land Surveyor No. 5910, with a steel reinforcement rod, 24 ins. long, 5/8 ins. diam., firmly set, projecting 4 ins. above the ground, in a mound of stone, 2 ft. base to top, with aluminum cap mkd. T24N R89W S20 S21 S28 S29 1996 PLS 5910. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T24N R89W</td></tr> <tr><td>S 20 S 21</td></tr> <tr><td>-----</td></tr> <tr><td>S 29 S 28</td></tr> <tr><td>1999</td></tr> </table> <p>Deposit the steel reinforcement rod alongside the iron post.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89° 59' W., bet. secs. 21 and 28.</p> <p>Over gently rolling terrain.</p>	T24N R89W	S 20 S 21	-----	S 29 S 28	1999
T24N R89W						
S 20 S 21						

S 29 S 28						
1999						
39.89	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a sandstone, 23x3x2 ins., lying embedded in the ground, erroneously mkd. 4 grooves on a face, no other mks. visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T24N R89W</td></tr> <tr><td>S 21</td></tr> <tr><td>1/4 -----</td></tr> <tr><td>S 28</td></tr> <tr><td>1999</td></tr> </table> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>	T24N R89W	S 21	1/4 -----	S 28	1999
T24N R89W						
S 21						
1/4 -----						
S 28						
1999						

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.64	<p>N. 89° 32' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/>
40.07	<p>N. 0° 15' E., bet. secs. 20 and 21.</p> <p>Over gently rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W 1/4 S 20 S 21 1999</p> <p>Set a steel fence post alongside the iron post.</p>
80.14	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a broken sandstone, 16x8x3 ins., loosely set in a mound of stone, 2 ft. base, 2 ft. high, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W S 17 S 16 <hr/>S 20 S 21 1999</p> <p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89° 26' W., bet. secs. 16 and 21.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over gently rolling terrain.
39.65	The 1/4 sec. cor. of secs. 16 and 21, monumented with a sandstone, 16x8x6 ins., firmly set 10 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T24N R89W S 16 1/4 ——— S 21 1999
	Bury the unmkd. stone and set a steel fence post alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> N. 89° 44' W., beginning new measurement.
	Over gently rolling terrain.
31.10	Underground pipeline, bears SE. and NW.
40.22	The cor. of secs. 16, 17, 20 and 21.
	<hr style="width: 100%;"/> N. 0° 14' E., bet. secs. 16 and 17.
	Over gently rolling terrain.
11.00	Underground pipeline, bears SE. and NW.
39.99	The 1/4 sec. cor. of secs. 16 and 17, monumented with a sandstone, 24x21x1 ins., lying loose on the ground, plainly mkd. 1/4 on a face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T24N R89W 1/4 S 17 S 16 1999

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr/>										
	<p>N. 0° 14' E., beginning new measurement.</p>										
	<p>Over gently rolling terrain.</p>										
39.98	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a sandstone, 24x18x3 ins., lying embedded 1 in. in the ground, plainly mkd. 4 notches on an edge and 4 notches on adjacent edge.</p>										
	<p>At the corner point</p>										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T24N R89W</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S 17</td><td>S 16</td></tr> <tr><td colspan="2">1999</td></tr> </table>	T24N R89W		S 8	S 9	— —		S 17	S 16	1999	
T24N R89W											
S 8	S 9										
— —											
S 17	S 16										
1999											
	<p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr/>										
	<p>From the cor. of secs. 9, 10, 15 and 16.</p>										
	<p>N. 89° 32' W., bet. secs. 9 and 16.</p>										
	<p>Over gently rolling terrain.</p>										
26.00	<p>Trail road, bears SE. and NW.</p>										
39.27	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with a sandstone, 24x16x4 ins., firmly set 12 ins. in the ground, plainly mkd. 1/4 on W. face.</p>										
	<p>At the corner point</p>										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T24N R89W</td></tr> <tr><td>S 9</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 16</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table>	T24N R89W		S 9		1/4	—	S 16		1999	
T24N R89W											
S 9											
1/4	—										
S 16											
1999											

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Bury the original cor. stone and set a steel fence post alongside the iron post. Raise a mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p> <hr/>
	<p>N. 89° 42' W., beginning new measurement.</p>
	<p>Over gently rolling terrain.</p>
40.08	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/>
	<p>N. 0° 17' E., bet. secs. 8 and 9.</p>
	<p>Over gently rolling terrain.</p>
8.00	<p>Trail road, bears NE. and SW.</p>
40.13	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R89W</p>
	<p style="text-align: center;">1/4</p>
	<p style="text-align: center;">S 8 S 9</p>
	<p style="text-align: center;">1999</p>
	<p>Set a steel fence post alongside the iron post.</p>
80.26	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a granite stone, 10x6x5 ins., loosely set 2 ins. in the ground, dimly mkd. 4 notches on E. edge and 5 grooves on S. face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R89W</p>
	<p style="text-align: center;">S 5 S 4</p>
	<p style="text-align: center;">S 8 S 9</p>
	<p style="text-align: center;">1999</p>
	<p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 3, 4, 9 and 10.
	S. 89° 58' W., bet. secs. 4 and 9.
	Over gently rolling terrain.
40.56	The 1/4 sec. cor. of secs. 4 and 9, monumented with a sandstone, 8x3x2 ins., lying loose on the ground, dimly mkd. 1/, no other mks. visible.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T24N R89W
	S 4
	1/4 ———
	S 9
	1999
	Bury the original cor. stone and set a steel fence post alongside the iron post. Raise a mound of stone, 1 ft. base, 1 ft. high, N. of the cor.
	N. 88° 31' W., beginning new measurement.
	Over gently rolling terrain.
21.00	Trail road, bears SE. and NW.
38.79	The cor. of secs. 4, 5, 8 and 9.
	N. 0° 32' E., bet. secs. 4 and 5.
	Over gently rolling terrain.
40.01	The 1/4 sec. cor. of secs. 4 and 5, monumented with a sandstone, 12x10x3 ins., loosely set in a mound of stone, 1 ft. base, 1 ft. high, dimly mkd. 1/4 on a face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T24N R89W 1/4 S 5 S 4 1999
	Bury the original cor. stone alongside the iron post. Cor. is located in fence extending E. and W., on E. edge of trail road, extending SE. and NW.
	<hr/> N. 4° 32' E., beginning new measurement. Over gently rolling terrain.
0.30	Trail road, bears SE. and NW.
39.74	Point for the closing cor. of secs. 4 and 5, at intersection with the Sixth Standard Parallel North. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T25N R89W S 33 <hr/> S 5 S 4 T24N R89W C C 1999
	Set a steel fence post alongside the iron post. From this point, the standard cor. of secs. 34 and 35, Tp. 25 N., R. 89 W., bears EAST, 2.55 chs. dist.
39.87	The original closing cor. of secs. 4 and 5, monumented with a limestone, 18x8x2 ins., firmly set 6 ins. in the ground, plainly mkd. 4 notches on E. face, CC on S. face and 3 notches on W. face. I add the mks. AM and bury the stone in place 6 ins. below the surface of the ground.
	<hr/> The point for the 1/4 sec. cor. of sec. 4 only, T. 25 N., R. 89 W., is at midpoint on the N. bdy. of sec. 4. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T25N R88W <hr/> 1/4 S 4 T24N R89W 1999
	Set a steel fence post alongside the iron post.
	From this point, the 1/4 sec. cor. of sec. 34, T. 25 N., R. 89 W., bears S. 89° 39' E., 4.19 chs. dist.
	<hr/>
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.
	T24N R89W S 31 S 32 <hr/> S 6 S 5 T23N 1938
	N. 0° 04' E., bet. secs. 31 and 32.
	Over gently rolling terrain.
20.00	Trail road, bears NE and SW.
40.00	The 1/4 sec. cor. of secs. 31 and 32, remonumented by Jeffrey B. Jones, Wyoming Registered Land Surveyor No. 5910, with a steel reinforcement rod, 24 ins. long, 5/8 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. 1/4 S31 S32 1996 PLS 5910. This position is accepted as a careful and faithful perpetuation of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T24N R89W 1/4 S 31 S 32 1999
	Deposit the steel reinforcement rod and set a steel fence post alongside the iron post.
	<hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 0° 03' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>20.00 Mineral X road, (asphalt) bears SE. and NW.</p> <p>40.01 The cor. of secs. 29, 30, 31 and 32, reestablished by Jeffrey B. Jones, Wyoming Registered Land Surveyor No. 5910, monumented with a steel reinforcement rod, 24 ins. long, 5/8 ins. diam., firmly set, projecting 4 ins. above the ground, in a mound of stone 2 ft. base to top, with aluminum cap mkd. T24N R89W S29 S30 S31 S32 1996 PLS 5910. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, 2 ft. base to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T24N R89W</td> </tr> <tr> <td style="border-right: 1px solid black;">S 30</td> <td>S 29</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td style="border-right: 1px solid black;">S 31</td> <td>S 32</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> <p>Deposit the steel reinforcement rod alongside the iron post.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89° 49' W., bet. secs. 29 and 32.</p> <p>Over gently rolling terrain.</p> <p>39.78 The 1/4 sec. cor. of secs. 29 and 32, reestablished by Jeffrey B. Jones, Wyoming Registered Land Surveyor No. 5910, monumented with a steel reinforcement rod, 24 ins. long, 5/8 ins. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with aluminum cap mkd. 1/4 S29 S33 1996 PLS 5910. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	T24N R89W		S 30	S 29			S 31	S 32	1999	
T24N R89W											
S 30	S 29										
S 31	S 32										
1999											

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T24N R89W S 29 1/4 ——— S 32 1999
	Deposit the steel reinforcement rod alongside the iron post. Cor. is located 85 lks. W. of dirt access road to ranch. <hr style="width: 20%; margin: 10px auto;"/> N. 89° 47' W., beginning new measurement. Over gently rolling terrain.
39.79	The cor. of secs. 29, 30, 31 and 32. <hr/> S. 89° 57' W., bet. secs. 30 and 31. Over gently rolling terrain.
39.80	Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T24N R89W S 30 1/4 ——— S 31 1999
41.30	Set a steel fence post alongside the iron post. Mineral X road, (asphalt) bears SE. and NW.
77.17	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp. <hr/> From the cor. of secs. 29, 30, 31 and 32. N. 0° 16' E., bet. secs. 29 and 30. Over gently rolling terrain.

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Deposit the steel reinforcement rod alongside and bury the original cor. stone alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p>
	<p>S. 89° 59' W., bet. secs. 20 and 29.</p>
	<p>Over gently rolling terrain.</p>
39.72	<p>The 1/4 sec. cor. of secs. 20 and 29, reestablished by Jeffrey B. Jones, Wyoming Registered Land Surveyor No. 5910, with a steel reinforcement rod, 24 ins. long, 5/8 ins. diam., firmly set, projecting 4 ins. above the ground, in a mound of stone, 2 ft. base to top, with aluminum cap mkd. 1/4 S20 S29 1996 PLS 5910. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone 3 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R89W S 20 1/4 ——— S 29 1999</p>
	<p>Deposit the steel reinforcement rod alongside the iron post.</p> <hr/>
	<p>S. 89° 59' W., beginning new measurement.</p>
	<p>Over gently rolling terrain.</p>
39.73	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/>
	<p>S. 89° 25' W., bet. secs. 19 and 30.</p>
	<p>Over rolling terrain.</p>
40.75	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with a granite, 18x18x10 ins., firmly set 12 ins. in the ground, plainly mkd. 1/4 on N. face.</p>
	<p>At the corner point</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T24N R89W S 19 1/4 ——— S 30 1999</p>
	Bury the original cor. stone and set a steel fence post alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">N. 89° 41' W., beginning new measurement.</p>
	Over gently rolling terrain.
36.39	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.
	<hr style="width: 80%; margin: auto;"/> <p style="text-align: center;">From the cor. of secs. 19, 20, 29 and 30.</p>
	N. 0° 17' E., bet. secs. 19 and 20.
	Over rolling terrain.
39.91	The 1/4 sec. cor. of secs. 19 and 20, monumented with a granite stone, 16x10x6 ins., firmly set 8 ins. in the ground, plainly mkd. 1/4 on W. face, with a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T24N R89W 1/4 S 19 S 20 1999</p>
	Bury the original cor. stone and set a steel fence post alongside the iron post. Rebuild the mound of stone, 2 ft. base, 2 ft. high, W. of the cor.
	<hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">N. 0° 09' E., beginning new measurement.</p>
	Over rolling terrain.

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS											
39.99	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a granite stone, 16x8x6 ins., firmly set 4 ins. in the ground, plainly mkd. 5 grooves on E. face, 3 notches on S. edge, with a mound of stone, 3 ft. base, 3 ft. high, W. of the cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T24N</td><td>R89W</td></tr> <tr><td>S 18</td><td>S 17</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 19</td><td>S 20</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> <p>Bury the original cor. stone and set a steel fence post alongside the iron post. Rebuild the mound of stone, 3 ft. base, 3 ft. high, W. of the cor.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89° 50' W., bet. secs. 17 and 20.</p> <p>Over rolling terrain.</p>	T24N	R89W	S 18	S 17			S 19	S 20	1999	
T24N	R89W										
S 18	S 17										
S 19	S 20										
1999											
39.22	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with a granite stone, 10x4x2 ins., firmly set 5 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T24N</td><td>R89W</td></tr> <tr><td>S 17</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 20</td><td></td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> <p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p> <hr/> <p>S. 89° 47' W., beginning new measurement.</p>	T24N	R89W	S 17		1/4	—	S 20		1999	
T24N	R89W										
S 17											
1/4	—										
S 20											
1999											

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling terrain.
40.27	The cor. of secs. 17, 18, 19 and 20.
	<hr/> S. 89° 26' W., bet. secs. 18 and 19.
	Over rolling terrain.
39.67	The 1/4 sec. cor. of secs. 18 and 19, monumented with a granite stone, 15x10x10 ins., lying embedded in the ground, plainly mkd. 1/4 on a face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T24N R89W S 18 1/4 ——— S 19 1999 </div>
	Bury the original cor. stone and set a steel fence post alongside the iron post.
	<hr/> N. 89° 50' W., beginning new measurement.
	Over rolling terrain.
37.52	The cor. of secs. 18, 19, 13 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.
	<div style="text-align: center;"> T24N R90W R89W S 13 S 18 ——— ——— S 24 S 19 1938 </div>
	Cor. is located in fence extending N. and S.
	<hr/> From the cor. of secs. 17, 18, 19 and 20.
	N. 0° 07' E., bet. secs. 17 and 18.

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Over rolling terrain.</p>
39.84	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with a granite stone, 16x8x6 ins., firmly set 8 ins. in the ground, plainly mkd. 4 on W. face, no other mks. visible, with a mound of stone, 3 ft. base, 2 ft high, W. of the cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W 1/4 S 18 S 17 1999</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post. Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
39.95	<p>The cor. of secs. 7, 8, 17 and 18, monumented with a sandstone, 12x10x3 ins., firmly set 6 ins. in the ground, plainly mkd. 5 grooves on E. face and 4 notches on S. edge, with a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W S 7 S 8 <hr style="width: 10%; margin: 0 auto;"/> S 18 S 17 1999</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post. Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 8, 9, 16 and 17.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>S. 89° 43' W., bet. secs. 8 and 17.</p>
	<p>Over rolling terrain.</p>
39.99	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with a granite stone, 12x10x6 ins., firmly set 4 ins. in the ground, plainly mkd. 4 on N. face, no other mks. visible.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T24N R89W S 8 1/4 ——— S 17 1999</p>
	<p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 89° 38' W., beginning new measurement.</p>
	<p>Over rolling terrain.</p>
17.20	<p>Underground pipeline, bears SE. and NW.</p>
39.69	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/>
	<p>S. 89° 38' W., bet. secs. 7 and 18.</p>
	<p>Over rolling terrain, ascend steep W. slope.</p>
30.00	<p>Top of ascent.</p>
37.67	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with a granite stone, 34x20x20 ins., firmly set 5 ins. in the ground, plainly mkd. 1/4 on N. face, in a mound of stone, 4 ft. base, 2 ft. high.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T24N R89W S 7 1/4 ——— S 18 1999</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post. Rebuild the mound of stone, 4 ft. base, 3 ft. high, N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 54' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>39.29 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R90W R89W S 12 S 7 ————— S 13 S 18 1938</p> <p>Cor. is located in fence extending N. and S.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0° 12' E., bet. secs. 7 and 8.</p> <p>Over rolling and broken terrain.</p> <p>39.87 The 1/4 sec. cor. of secs. 7 and 8, monumented with a sandstone, 12x8x6 ins., firmly set 4 ins. in the ground, no mks. visible, with a mound of stone, 2 ft. base, 2 ft. high, W. of the cor. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone 1 ft. base to top, with brass cap mkd.</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T24N R89W 1/4 S 7 S 8 1999</p> <p>Bury the unmkd. stone and set a steel fence post alongside the iron post. Rebuild the mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 16' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
40.26	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a granite stone, 14x6x4 ins., firmly set 8 ins. in the ground, plainly mkd. 3 notches on E. face and 5 notches on S. edge, no other mks. visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W S 6 S 5 ----- S 7 S 8 1999</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89° 35' W., bet. secs. 5 and 8.</p> <p>Over rolling terrain.</p>
39.87	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W S 5 1/4 ——— S 8 1999</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the iron post and raise a mound of stone, 1 ft. base, 1 ft. high, N. of the cor.
79.74	The cor. of secs. 5, 6, 7 and 8.
	S. 89° 22' W., bet. secs. 6 and 7.
	Over rolling terrain.
19.93	Point for the E. 1/16 sec. cor. of secs. 6 and 7.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T24N R89W S 6 E1/16— S 7 1999</p>
	Set a steel fence post alongside the iron post.
39.86	Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T24N R89W S 6 1/4 — S 7 1999</p>
	Set a steel fence post alongside the iron post.
77.07	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.
	<p style="text-align: center;">T24N R90W R89W S 12 S 7 — — S 13 S 18 1938</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0° 07' E., bet. secs. 5 and 6.</p> <p>Over rolling terrain.</p>
40.21	<p>The 1/4 sec. cor. of secs. 5 and 6, monumented with a sandstone, 20x12x6 ins., loosely set 6 ins. in the ground, plainly mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R89W 1/4 S 6 S 5 1999</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <p>Cor. is located N. 78° W., 1.6 chs. from cor. of fences extending E. and S. (approx.)</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>NORTH, with record bearing, beginning new measurement.</p> <p>Over rolling terrain.</p>
40.12	<p>Point for the closing cor. of secs. 5 and 6, at intersection with the Sixth Standard Parallel North. This method of restoration at record bearing from the 1/4 sec. cor. of secs. 5 and 6, to intersection with the Sixth Standard Parallel North was determined to be the most applicable to determine the position of the original cor., as explained on page 1.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R89W S 32 ----- S 6 S 5 T24N R89W C C 1999</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set a steel fence post alongside the iron post.</p> <p>From this point, the standard cor. of secs. 32 and 33, T. 25 N., R. 89 W., bears S. 89° 52' E., 5.77 chs.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 5 only, T. 24 N., R. 89 W., is at midpoint on the N. bdy. of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R88W ----- 1/4 S 5 T24N R89W 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, the 1/4 sec. cor. of sec. 33, T. 25 N., R. 89 W., bears S. 89° 50' E., 4.21 chs. dist.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 6 only, T. 24 N., R. 89 W., is at proportionate dist. on the N. bdy. of sec. 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R88W ----- 1/4 S 6 T24N R89W 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, the 1/4 sec. cor. of sec. 32, T. 25 N., R. 89 W., bears S. 89° 53' E., 5.57 chs. dist.</p> <hr/>
--------	--

T. 24 N., R. 89 W., Sixth Principal Meridian, Wyoming

CHAINS	GENERAL DESCRIPTION
	<p>The area embraced by this survey is situated in the northwest portion of Carbon County, approximately 21 miles north of Rawlins, Wyoming. The terrain is nearly level to gently rolling, with a mean elevation of about 6,600 feet above sea level. The soil is primarily sandy and alkaline in the dry lake beds. The undergrowth consists of sagebrush, greasewood and native grasses.</p> <p>Drainage of the area is northerly for the north half of the township and southerly for the south half of the township by draws and ravines throughout the township. No mineral activity was noted at the time of the survey. There is one small ranch located in section 29.</p> <p>Access is provided by U. S. Highway No. 287, Mineral X road (BLM 3206) and numerous roads and trails throughout the area.</p>

CERTIFICATE OF SURVEY

132

I, Lynn A. Forbes, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 31st day of March, 1997, I have dependently resurveyed a portion of the Sixth Standard Parallel North, through Ranges 88 and 89 West, a portion of the West boundary and the subdivisional lines, Township 24 North, Range 89 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JAN 23 2002

(Date)

Lynn A. Forbes
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of dependent resurvey of a portion of the Sixth Standard Parallel North, through Ranges 88 and 89 West, a portion of the West boundary and the subdivisional lines, Township 24 North, Range 89 West, of the Sixth Principal Meridian, in the State of Wyoming, executed by Lynn A. Forbes, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 23 2002

(Date)

John P. Lee
(Signature of Authorized Officer)