

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

301

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF PORTIONS OF
THE SUBDIVISIONAL LINES
AND MINERAL SURVEYS NOS. 50, 80, 89, 183 and 509,
THE
SUBDIVISION OF SECTION 20,
AND THE
METES AND BOUNDS SURVEYS
OF LOTS 16, 19 AND 24, SECTION 20,
TOWNSHIP 29 NORTH, RANGE 100 WEST,
OF THE SIXTH PRINCIPAL MERIDIAN,
IN THE STATE OF WYOMING.

EXECUTED BY

JOEL T. EBNER

CADASTRAL SURVEYOR

Under Special Instructions dated AUGUST 29, 2000, approved AUGUST 29, 2000, which provided for the surveys included under Group Number 680, and assignment instructions dated AUGUST 29, 2000.

Survey commenced SEPTEMBER 21, 2000

Survey completed OCTOBER 2, 2000

INDEX DIAGRAM

Township 29 North, Range 100 West

| | | | | | |
|----|--------------|---------|----|----|----|
| 6 | 5 | 4 | 3 | 2 | 1 |
| 7 | 8 | 9 | 10 | 11 | 12 |
| 18 | 17 | 16 | 15 | 14 | 13 |
| 19 | 5 20 4 | 2 21 | 22 | 23 | 24 |
| 30 | 29 | 28 | 27 | 26 | 25 |
| 31 | 32 | 33 | 34 | 35 | 36 |

Dependent Resurvey, Portion of Mineral Survey No. 50.....Page 7
 Dependent Resurvey, Portion of Mineral Survey No. 80.....Page 10
 Dependent Resurvey, Portion of Mineral Survey No. 89.....Page 20
 Dependent Resurvey, Portion of Mineral Survey No. 183.....Page 21
 Dependent Resurvey, Portion of Mineral Survey No. 509.....Page 22
 Subdivision of Section 20.....Page 24
 Metes and Bounds Survey of Lot 16, Section 20.....Page 26
 Metes and Bounds Survey of Lot 19, Section 20.....Page 29
 Metes and Bounds Survey of Lot 24, Section 20.....Page 32

T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS

The following field notes are those of the dependent resurvey of portions of the subdivisional lines and mineral surveys nos. 50, 80, 89, 183 and 509, the subdivision of section 20, and the metes and bounds surveys of Lots 16, 19 and 24, section 20, Township 29 North, Range 100 West, Sixth Principal Meridian, Wyoming.

The history of surveys pertaining to this resurvey is as follows:

John L. Propst surveyed the subdivisional lines in 1883. Newton H. Brown surveyed Mineral Survey No. 40 in 1885. John E. Hill surveyed Mineral Survey No. 50 in 1891. Newton H. Brown surveyed Mineral Survey No. 80 in 1898 and amended Mineral Survey No. 80 and surveyed Mineral Survey No. 89 in 1899. Od H. Midthun surveyed Mineral Survey No. 183 in 1902. Guy W. Higby surveyed Mineral Survey No. 331 in 1905, Mineral Survey No. 426 in 1908, and Mineral Survey Nos. 509 and 510 in 1918. Jack A. Eaves dependently resurveyed a portion of the subdivisional lines in 1961.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 680, Wyoming, dated August 29, 2000.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data were thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

The survey was executed with TRIMBLE Model 4700 Global Positioning System (GPS) receivers and by chaining methods. The instruments were maintained in proper adjustment at all times. The directions of all lines refer to the true meridian, as determined by GPS observations. GPS control network and supporting data are contained in the official group file.

The geographic position of the cor. of sections 20, 21, 28 and 29, based on NAD 83 and determined by Global Positioning System is:

Latitude 42° 27' 50.68" N., Longitude 108° 47' 47.03" W.

The mean magnetic declination is 12½° E.


Dependent Resurvey, Portion of the Subdivisional Lines,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | | | | | | | | | | | |
|------------|---|------------|--|--------|------|-------|------|------|------|------|--|
| | <p>(Restoring the dependent resurvey executed by Jack A. Eaves in 1961)</p> <hr/> | | | | | | | | | | |
| | <p>Beginning at the cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a steel fence post alongside and a mound of stone, 3 ft. base, 1 ft. high, W. of the cor., with brass cap mkd.</p> | | | | | | | | | | |
| | <table border="1"> <tr><td colspan="2">T29N R100W</td></tr> <tr><td>S 20</td><td>S 21</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 29</td><td>S 28</td></tr> <tr><td colspan="2">1961</td></tr> </table> | T29N R100W | | S 20 | S 21 | <hr/> | | S 29 | S 28 | 1961 | |
| T29N R100W | | | | | | | | | | | |
| S 20 | S 21 | | | | | | | | | | |
| <hr/> | | | | | | | | | | | |
| S 29 | S 28 | | | | | | | | | | |
| 1961 | | | | | | | | | | | |
| | <p>N. 0° 42' W., bet. secs. 20 and 21.</p> | | | | | | | | | | |
| | <p>Over rolling and broken terrain.</p> | | | | | | | | | | |
| 16.28 | <p>Point for Cor. No. 4, Lot 24, sec. 20, hereinafter described.</p> | | | | | | | | | | |
| 19.30 | <p>Willow Creek, course ESE.</p> | | | | | | | | | | |
| 19.84 | <p>Point for the S. 1/16 sec. cor. of secs. 20 and 21, identical with Cor. No. 1, Lot 24, sec. 20.</p> | | | | | | | | | | |
| | <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> | | | | | | | | | | |
| | <table border="1"> <tr><td colspan="2">T29N R100W</td></tr> <tr><td colspan="2">S 1/16</td></tr> <tr><td>S 20</td><td>S 21</td></tr> <tr><td colspan="2">2000</td></tr> </table> | T29N R100W | | S 1/16 | | S 20 | S 21 | 2000 | | | |
| T29N R100W | | | | | | | | | | | |
| S 1/16 | | | | | | | | | | | |
| S 20 | S 21 | | | | | | | | | | |
| 2000 | | | | | | | | | | | |
| | <p>Set a steel fence post alongside the stainless steel post.</p> | | | | | | | | | | |
| 29.76 | <p>Cor. No. 2, M.S. No. 331, Carissa Placer, monumented with a schist stone, 24x13x7 ins., firmly set 17 ins. in the ground, plainly mkd. 2 C 331 on NW face, with a steel fence post alongside and a mound of stone, 4 ft. base, 2 ft. high, NW. of the cor.</p> | | | | | | | | | | |
| | <p>At the corner point</p> | | | | | | | | | | |
| | <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> | | | | | | | | | | |

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|--|
| | T29N R100W MS331 CARISSA 2 ----- S 21 S 20 2000 |
| | <p>Bury the original cor. stone alongside the stainless steel post.</p> <p>From this point, a lease corner established by the Wyoming Recreation Committee, bears SOUTH, 1 lk. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. CARISSA PLACER WRC.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 42' W., beginning new measurement.</p> <p>Over rolling terrain.</p> |
| 9.92 | <p>The 1/4 sec. cor. of secs. 20 and 21, identical with Cor. No. 1, M.S. No. 331, Carissa Placer and Cor. No. 1, M.S. No. 331, Tract A, Mono Placer, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, in a collar of stone, with a mound of stone, 3 ft. base, 2 ft. high, NW. of the cor., with brass cap mkd.</p> |
| | T29N R100W 1/4 S 20 S 21 1961 |
| | <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 06' W., beginning new measurement.</p> |
| 3.67 | <p>Point for Cor. No. 6, M.S. No. 331, Carissa Placer, identical with Cor. No. 4, M.S. No. 331, Tract A, Mono placer at intersection with line 2-3, Polly Perkins Lode, falls on E. edge of wash; there is no remaining evidence of the original cor. Point not monumented.</p> |
| 4.00 | <p>Wash, drains SSW.</p> |
| 21.90 | <p>South Pass City Road, bears NNE. and SSW.</p> |
| 32.06 | <p>Intersect line 1-4, M.S. No. 509, Oro Fino Lode, at a point from which Cor. No. 4 bears S. 65° 56' W., 10.628 chs. dist., hereinafter described.</p> |

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|---|
| | <p>At the point of intersection, set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T29N R100W S 20 S 21  ORO FINO MS 509 2000</p> |
| | <p>Set a steel fence post alongside the stainless steel post.</p> |
| 33.70 | <p>U.S. Steel Railroad grade (abandoned), bears ENE. and WSW.</p> |
| 39.87 | <p>The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 30 ins. long, 2½ ins. diam., firmly set 21 ins. in the ground, with a steel fence post alongside and a granite stone, 21x11x7 ins., lying loose alongside, plainly mkd. 4 grooves on a face and 3 grooves on a face, with brass cap mkd. T29N R100W S16 S17 S20 S21 1961. The iron post is badly bent and the brass cap is loose.</p> |
| | <p>At the corner point</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T29N R100W S 17 S 16 <hr/>S 20 S 21 2000</p> |
| | <p>Bury the original cor. stone alongside the stainless steel post and remove the 1961 iron post.</p> |
| | <p>Cor. is located 47 lks. W. of South Pass City Road, bears SSE. and NNW.</p> |
| | <p>From the cor. of secs. 20, 21, 28 and 29.</p> |
| | <p>S. 89° 21' W., bet. secs. 20 and 29.</p> |
| | <p>Over rolling terrain.</p> |
| 23.80 | <p>Enter cemetary, bears N. and S.</p> |



Dependent Resurvey, Portion of the Subdivisional Lines,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|--|
| 26.00 | Leave cemetery, bears N. and S. |
| 27.00 | South Pass City Road, gravel surfaced, bears NNE. and SSW. |
| 33.00 | U.S. Steel Railroad grade (abandoned), bears SE. and NW. |
| 40.07 | The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with brass cap mkd. |
| | T29N R100W S 20 1/4 ——— S 29 1961 |
| | S. 89° 09' W, beginning new measurement. |
| | Over gently rolling terrain. |
| 40.06 | The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground, with a wooden post, 3 ins. sq., set alongside, with brass cap mkd. |
| | T29N R100W S 19 S 20 ——— ——— S 30 S 29 1961 |
| | N. 0° 51' W., bet. secs. 19 and 20. |
| | Over rolling terrain. |
| 21.83 | Intersect line 9-10, M.S. No. 50, Gould and Curry Lode, at a point from which cor. No. 10 bears N. 71° 48' E., 6.253 chs. dist., hereinafter described. |
| 31.36 | Intersect line 11-12, M.S. No. 50, Gould and Curry Lode, at a point from which cor. No. 11 bears N. 71° 41' E., 4.226 chs. dist., hereinafter described. |
| 39.98 | The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, in a collar of stone, with brass cap mkd. |

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|--|
| | T29N R100W 1/4 S 19 S 20 1961 |
| | Set a steel fence post alongside the iron post. <hr/> |
| | N. 0° 32' W., beginning new measurement. |
| | Over rolling terrain. |
| 34.80 | Willow Creek, course SE. |
| 39.61 | The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, in a collar of stone, with brass cap mkd. |
| | T29N R100W S 18 S 17 ----- S 19 S 20 1961 |
| | From the cor. of secs. 16, 17, 20 and 21. |
| | S. 88° 40' W., bet. secs. 17 and 20. |
| | Over rolling land. |
| 40.12 | The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 13 ins. above the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd. |
| | T29N R100W S 17 1/4 ——— S 20 1961 |
| | S. 89° 55' W., beginning new measurement. |
| | Over rolling terrain. |
| 39.72 | The cor. of secs. 17, 18, 19 and 20. <hr/> |

Dependent Resurvey, Portion of Mineral Survey No. 50,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming


| CHAINS | <p style="text-align: center;">(Restoring the survey executed by John E. Hill in 1891)</p> <hr style="width: 20%; margin: auto;"/> <p>From Cor. No. 9, M.S. No. 50, Gould & Curry Lode, monumented with decayed remains of wooden post, firmly set 6 ins. below the surface of the ground, in a mound of earth, with a wooden post, 4½ ft. long, 5 ins. sq., lying loose alongside. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T29N R100W MS 50 9 GC COM S 19 2000</p> </div> <p>Bury the decayed remains of the wooden post and set the 5 in. sq. wooden post alongside the stainless steel post.</p> <p>N. 71° 48' E., on line 9-10, M.S. No. 50, Gould & Curry Lode.</p> <p>Over gently rolling terrain.</p> <p>16.49 Intersect the line bet. secs. 19 and 20, at a point from which the cor. of secs. 19, 20, 29 and 30, bears S. 0° 51' E., 21.83 chs. dist.</p> <p>22.743 Cor. No. 10, M.S. No. 50, Gould & Curry Lode, monumented with an embedded mound of stone, 4 ft. base, 1 ft. high, with several wooden posts lying loose alongside. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;">  <p>T29N R100W MS 50 GC 10 S 20 2000</p> </div> |
|--------|---|
|--------|---|

Dependent Resurvey, Portion of Mineral Survey No. 50,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|--|
| | Set a steel fence post alongside the iron post. |
| | N. 13° 06' W., on line 10-11, M.S. No. 50, Gould & Curry Lode. |
| | Over rolling terrain. |
| 9.136 | Cor. No. 11, M.S. No. 50, Gould & Curry Lode, monumented with decayed remains of wooden post, in an embedded mound of stone, 3 ft. base, 1 ft. high, with several wooden posts lying loose alongside. This position is accepted as the best available evidence of the original cor. position. |
| | At the corner point |
| | Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <div style="text-align: center;"> <p>T29N R100W S 20</p>  </div> |
| | Bury the decayed remains of the wooden post and set a steel fence post alongside the stainless steel post. Raise a mound of stone, 3 ft. base, 2 ft. high, SW. of the cor. |
| | S. 71° 41' W., on line 11-12, M.S. No. 50, Gould & Curry Lode. |
| | Over gently rolling terrain. |
| 4.226 | Intersect the line bet. secs. 19 and 20, at a point from which the 1/4 sec. cor. of secs. 19 and 20, bears N. 0° 51' W., 8.62 chs. dist. |
| 22.726 | Point for Cor. No. 12, M.S. No. 50, Gould & Curry Lode, determined at record distance from Cor. No. 9, M.S. No. 50, Gould & Curry Lode and on line between Cor. No. 5, M.S. No. 50, Ouray Lode and Cor. No. 8, M.S. No. 50, Ouray Lode; there is no remaining evidence of the original cor. This method of restoration was determined to be the most applicable to reestablish the original cor. position. |
| | Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. |

Dependent Resurvey, Portion of Mineral Survey No. 50,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS



Set a steel fence post alongside the stainless steel post.


From this point, Cor. No. 8, M.S. No. 50, Ouray Lode, bears N. 12° 57' W., 2.686 chs. dist., monumented with decayed remains of wooden post, firmly set 4 ins. below the surface of the ground, in a mound of earth, with a decayed wooden post, 4 ft. long, 5 ins. sq., lying loose alongside, from which an original bearing object

A bedrock outcrop, flush with the ground, bears N. 55½° W., 290.2 ft. dist., mkd. X BR 50. (Record: N. 55° W., 190 ft. dist.)

This position is accepted as the best available evidence of the original cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.




Bury the decayed remains of the wooden post and set a steel fence post alongside the stainless steel post.



S. 12° 57' E., on line 12-9, M.S. No. 50, Gould & Curry Lode, identical in part with line 8-5, M.S. No. 50, Ouray Lode, and identical in part with line 4-1, M.S. No. 50, Comstock Lode.

Over gently rolling terrain.


Dependent Resurvey, Portion of Mineral Survey No. 50,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| | |
|----------------------------|---|
| <p>CHAINS</p> <p>6.417</p> | <p>Cor. No. 5, M.S. No. 50, Ouray Lode, identical with Cor. No. 4, M.S. No. 50, Comstock Lode, monumented with decayed remains of wooden post, firmly set 5 ins. below the surface of the ground, with several wooden posts lying loose alongside. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R100W MS 50</p>  </div> <p>Bury the decayed remains of the wooden post alongside the stainless steel post.</p> <hr style="width: 30%; margin: auto;"/> <p>S. 13° 01' E., beginning new measurement.</p> <p>Over rolling terrain.</p> |
| <p>2.674</p> | <p>Cor. No. 9, M.S. No. 50, Gould & Curry Lode.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Portion of Mineral Survey No. 80, T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Newton H. Brown in 1898)</p> <hr/> <p>From Cor. No. 1, M.S. No. 80, J.C.S. Lode, monumented with a schist stone, 29x13x8 ins., firmly set 28 ins. in the ground, plainly mkd. 1 80 on W. face, with an embedded mound of stone, 3 ft. base, 1 ft. high, E. of the cor., from which original bearing objects</p> <p style="text-align: center;">A rock outcrop, 16 ins. above ground, bears N. 12° E., 141.0 ft. dist., mkd. X BR 1-4/80. (Record: N. 12° 10' E., 107.5 ft. dist.)</p> |


Dependent Resurvey, Portion of Mineral Survey No. 80,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|---|
| | <p>A rock outcrop, 17 ins. above ground, bears N. $64\frac{1}{4}^{\circ}$ E., 107.9 ft. dist., mkd. X BR 1-4 80. (Record: N. $64^{\circ} 35'$ E., 94 ft. dist.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;">  <p>T29N R100W MS 80 JCS 1 S 20 2000</p> </div> <p>Bury the original cor. stone alongside the stainless steel post. S. $74^{\circ} 11'$ W., on line 1-2, M.S. No. 80, J.C.S. Lode, identical in part with line 1-2, Lot 19, sec. 20.</p> <p>Over nearly level terrain, through thick willow brush.</p> <p>0.319 Point for Cor. No. 1, Lot 19, at intersection with the N. and S. center line of sec. 20, hereinafter described.</p> <p>4.30 Willow Creek, course S.</p> <p>7.593 Cor. No. 2, M.S. No. 80, J.C.S. Lode, identical with Cor. No. 2 Lot 19, sec. 20, monumented with decayed remains of wooden post, firmly set 4 ins. below the surface of the ground, in a collar of stone. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;">  <p>T29N R100W MS 80 JCS S 20 2 2000</p> </div> <p>Bury the decayed remains of the wooden post and set a steel fence post alongside the stainless steel post.</p> |

Dependent Resurvey, Portion of Mineral Survey No. 80,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|---|
| | <p>N. 8° 15' E., on line 2-3, M.S. No. 80, J.C.S. Lode, identical with line 2-3, Lot 19, sec. 20.</p> <p>Over rolling terrain, through willow brush.</p> |
| 3.50 | Willow creek, course ESE. |
| 7.179 | <p>Cor. No. 3, M.S. No. 80, J.C.S. Lode, identical with Cor. No. 3 Lot 19, sec. 20, at intersection with line 2-3, M.S. No. 80, Alpine Lode, monumented with a hornblende boulder, projecting 8x5x5 ft. above ground, plainly mkd. X 3/80 on top, with a mound of stone, 3 ft. base, 2 ft. high, SE. of the cor., from which original bearing objects</p> <p style="padding-left: 40px;">A rock outcrop, 42 ins. above ground, bears S. 88½° E., 14.5 ft. dist., mkd. X BR 3/80. (Record: S. 87° 47' E.)</p> <p style="padding-left: 40px;">A rock outcrop, 48 ins. above ground, bears S. 7½° W., 11.1 ft. dist., mkd. X BR 3/80. (Record: S. 8° W., 10.1 ft. dist.)</p> |
| | <p>S. 73° 56' W., on line 2-3, M.S. No. 80, Alpine Lode, identical in part with line 3-4, Lot 19, sec. 20.</p> <p>Over rolling terrain, through willow brush.</p> |
| 6.00 | Willow creek, course SE. |
| 8.397 | <p>Cor. No. 3, M.S. No. 80, Alpine Lode, identical with Cor. No. 4 Lot 19, sec. 20, monumented with an embedded mound of stone, 4 ft. base, 1 ft. high, with a wooden post, 4 ft. long, 3 ins. sq., lying loose alongside. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> |
| |  |



Dependent Resurvey, Portion of Mineral Survey No. 80,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|---|
| | Set a steel fence post alongside the iron post. |
| | N. 15° 06' W., on line 3-4, M.S. No. 80, Alpine Lode, identical with line 4-5, Lot 19, sec. 20. |
| | Over rolling terrain, through willow brush. |
| 2.00 | Willow Creek, course SE. |
| 4.836 | Intersect the E. and W. center line of sec. 20, at a point from which the center 1/4 sec. cor. of sec. 20 bears N. 89° 29' E., 15.17 chs. dist. |
| 9.087 | Cor. No. 4, M.S. No. 80, Alpine Lode, identical with Cor. No. 3, M.S. No. 80, Ben Hur Lode, and Cor. No. 5, Lot 19, sec. 20, and Cor. No. 7, Lot 16, sec. 20, monumented with a hornblende stone, 36x18x8 ins., firmly set 18 ins. in the ground, in a collar of stone, plainly mkd. 4/80 on N. face and 3/80 on S. face. |
| | At the corner point |
| | Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd. |
| |  |
| | Bury the original cor. stone alongside the stainless steel post. |
| | N. 15° 55' W., on line 3-4, M.S. No. 80, Ben Hur Lode, identical with line 1-7, Lot 16, sec. 20. |
| | Over broken terrain. |
| 4.30 | U.S. Steel Railroad grade (abandoned), bears ESE. and WNW. |
| 8.956 | Cor. No. 4, M.S. No. 80, Ben Hur Lode, identical with Cor. No. 1, Lot 16, sec. 20, monumented with a hornblende stone, 35x8x6 ins., loosely set in a mound of stone, 4 ft. base, 2 ft. high, plainly mkd. 4/80 on SE. face, from which original bearing objects |

Dependent Resurvey, Portion of Mineral Survey No. 80,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|---|
| | <p>A rock outcrop, 24 ins. above ground, bears S. $43\frac{1}{2}^{\circ}$ E., 37.0 ft. dist., mkd. X BR 4/80. (Record: S. $42^{\circ} 35'$ E., 37.2 ft. dist.)</p> <p>A rock outcrop, 36 ins. above ground, bears N. $3\frac{1}{2}^{\circ}$ W., 20.2 ft. dist., mkd. BR 4/80. (Record: N. $3^{\circ} 20'$ W.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 11 ins. in the ground to bedrock, supported by a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="841 740 1015 932" style="text-align: center;"> </div> <p>Bury the original cor. stone alongside the stainless steel post.</p> |
| | <p>N. $74^{\circ} 16'$ E., on line 4-1, M.S. No. 80, Ben Hur Lode.</p> |
| | <p>Over broken terrain.</p> |
| 19.162 | <p>Intersect the N. and S. center line of sec. 20, at a point from which the center $1/4$ sec. cor. of sec. 20 bears S. $0^{\circ} 56'$ E., 17.78 chs. dist., hereinafter described.</p> |
| 21.80 | <p>Cor. No. 1, M.S. No. 80, Ben Hur Lode, monumented with a hornblende stone, 26x10x8 ins., firmly set 10 ins. in the ground, in a collar of stone, plainly mkd. $1/80$ on SE. face and X on top, from which original bearing objects</p> <p>A rock outcrop, 12 ins. above ground, bears N. $14\frac{1}{2}^{\circ}$ E., 122.3 ft. dist., mkd. X BR $1/80$. (Record: N. $15^{\circ} 05'$ E., 122.7 ft. dist.)</p> <p>A rock outcrop, 36 ins. above ground, bears N. 13° W., 127.0 ft. dist., mkd. X BR $1/80$. (Record: N. $15^{\circ} 55'$ W., 72 ft. dist.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> |



Dependent Resurvey, Portion of Mineral Survey No. 80,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|--|
| | <div style="text-align: center;">  <p>T29N R100W S 20 1 MS 80 BH 2000</p> </div> |
| | <p>Bury the original cor. stone and set a steel fence post alongside the stainless steel post.</p> |
| | <hr/> <p>S. 15° 38' E., on line 1-2, M.S. No. 80, Ben Hur Lode.</p> |
| | <p>Over rolling terrain.</p> |
| 2.10 | <p>U.S. Steel Railroad grade (abandoned), bears NE. and SW.</p> |
| 4.537 | <p>Intersect line 4-1, M.S. No. 80, Charles Dickens Lode, at a point from which Cor. No. 1 bears N. 7° 49' E., 0.701 chs. dist., hereinafter described.</p> |
| | <p>At the point of intersection, set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <div style="text-align: center;">  <p>T29N R100W S 20 MS 80 2000</p> </div> |
| | <p>Set a steel fence post alongside the stainless steel post.</p> |
| 9.033 | <p>Cor. No. 2, M.S. No. 80, Ben Hur Lode, monumented with a schist stone, 24x12x4 ins., firmly set 8 ins. in the ground, plainly mkd. 2 80 on N. face, with a mound of stone, 3 ft. base, 2 ft. high, NW. of the cor., from which original bearing objects</p> |
| | <p>A rock outcrop, 4 ins. above ground, bears N. 81° W., 112.6 ft. dist., mkd. X BR 1 80. (Record: N. 80° 45' W., 113.4 ft. dist.)</p> |
| | <p>A rock outcrop, 12 ins. above ground, bears N. 8¼° W., 134.7 ft. dist., mkd. X BR 2 80. (Record: N. 8° W., 135.5 ft. dist.)</p> |
| | <p>At the corner point</p> |

Dependent Resurvey, Portion of Mineral Survey No. 80,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R100W</p> <p style="text-align: center;">MS 80 CHARLES BEN HUR 2 DICKENS</p> <p style="text-align: center;">2000</p> <p>Bury the original cor. stone alongside the stainless steel post.</p> |
| | <p>From Cor No. 1, M.S. No. 80, Charles Dickens Lode, monumented with the bottom portion of a broken schist stone, 12x12x4 ins., firmly set flush with the ground, top portion of the broken stone, 6x5x2 ins., lying loose alongside, plainly mkd. 1 80 on a face, with an embedded mound of stone, 3 ft. base, 1 ft. high, E. of the cor., from which an original bearing object</p> <p style="text-align: center;">A rock outcrop, 12 ins. above ground, bears N. 51½° E., 18.1 ft. dist., mkd. X BR 1 80.</p> <p>At the corner point</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R100W</p> <p style="text-align: center;">S 20</p> <p style="text-align: center;">1 MS 80 CHARLES DICKENS</p> <p style="text-align: center;">2000</p> <p>Bury the original cor. stone fragments alongside the stainless steel post.</p> <p>S. 81° 50' E., on line 1-2, M.S. No. 80, Charles Dickens Lode.</p> <p>Over rolling terrain.</p> |
| 9.107 | <p>Cor. No. 2, M.S. No. No. 80, Charles Dickens Lode, monumented with a schist stone, 26x16x8 ins., firmly set 15 ins. in the ground, plainly mkd. 2 80 on W. face, from which original bearing objects</p> <p style="text-align: center;">A rock outcrop, 50 ins. above ground, bears N. 34½° E., 96.2 ft. dist., mkd. X BR 2 80. (Record: N. 35° 03' E., 96.7 ft. dist.)</p> |

Dependent Resurvey, Portion of Mineral Survey No. 80,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| CHAINS | |
|--------|--|
| | <p>A rock outcrop, 6 ins. above ground, bears S. 19$\frac{1}{2}$° W., 76.9 ft. dist., mkd. X BR 2 80. (Record: S. 19° 40' W., 76.8 ft. dist.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Bury the original cor. stone and set a steel fence post alongside the stainless steel post. Raise a mound of stone, 3 ft. base, 2 ft. high, SW. of the cor.</p> |
| | <p>S. 8° 11' W., on line 2-3, M.S. No. 80, Charles Dickens Lode.</p> <p>Over rolling terrain.</p> |
| 0.643 | <p>Intersect line 1-4, M.S. No. 183, Jeanette Lode, at a point from which Cor. No. 4 bears S. 74° 15' W., 4.949 chs. dist., hereinafter described.</p> <p>At the point of intersection, set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Set a steel fence post alongside the stainless steel post.</p> |
| 13.563 | <p>Intersect the E. and W. center line of sec. 20, at a point from which the 1/4 sec. cor. of secs. 20 and 21, bears N. 89° 29' E., 29.58 chs. dist.</p> |
| 19.561 | <p>Cor. No. 3, M.S. No. 80, Charles Dickens Lode, monumented with a schist stone, 23x14x6 ins., firmly set 8 ins. in the ground, in a mound of stone, 4 ft. base, 1 ft. high, plainly mkd. 3 80 on NW. face, from which an original bearing object</p> |

Dependent Resurvey, Portion of Mineral Survey No. 80,
T. 29 N., R. 100 W., Sixth Principal Meridian, Wyoming

| | |
|---------------|--|
| <p>CHAINS</p> | <p>A rock outcrop, 6 ins. above ground, bears N. 65° E., 14.7 ft. dist., mkd. X BR 3 80. (Record: N. 75° E., 14.6 ft. dist.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, supported by a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R100W MS 80 CD 3 / MS 426 LB 2000</p> </div> <p>Deposit the original cor. stone in the mound of stone.</p> <hr/> <p>From Cor No. 4, M.S. No. 80, Charles Dickens Lode, at intersection with line 4-1, M.S. No. 80, J.C.S. Lode, monumented with a hornblende stone, 26x12x5 ins., firmly set 12 ins. in the ground, plainly mkd. 4/80 on E. face, with a steel fence post and a lease corner established by the Wyoming Recreation Committee, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set 12 ins. in the ground, with aluminum cap mkd. JCS CD WRC alongside, and with a mound of stone, 4 ft. base, 1 ft. high, E. of the cor., from which original bearing objects</p> <p>A rock outcrop, 13 ins. above ground, bears N. 14½° E., 108.0 ft. dist., mkd. X BR 80. (Record: N. 14° 35' E., 109 ft. dist.)</p> <p>A rock outcrop, 27 ins. above ground, bears N. 66° W., 121.5 ft. dist., mkd. X BR 4 80. (Record: N. 65° 50' W., 128 ft. dist.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R100W MS 80 4 CD JCS / S 20 2000</p> </div> |
|---------------|--|