

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R100W 1/4 S 6 S 5 1999</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post. Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located in abandoned fence extending N. and S.</p> <hr/> <p style="text-align: center;">Subdivision of Section 7, T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>From the ¼ sec. cor. of secs. 7 and 18.</p> <p>N. 1° 00' W., on the N. and S. center line of sec. 7.</p> <p>Over rolling terrain.</p>
19.90	<p>Point for the center S. 1/16 sec. cor. of sec. 7.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T33N R100W C S1/16 S 7 C 1999</p> <p>Set a steel fence post alongside the iron post.</p>
39.80	<p>Point for the center ¼ sec. cor. of sec. 7, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T33N R100W C1/4 S 7 1999</p>

Subdivision of Section 7,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set a steel fence post alongside the iron post.</p> <p>From this point, U. S. Coast and Geodetic Survey triangulation station "TATRO" bears S. 49° 27' W., 14.60 chs. dist., monumented with a brass tablet, 3½ ins. diam., firmly set in a rock outcrop.</p>
79.57	<p>The ¼ sec. cor. of secs. 6 and 7.</p> <hr/>
	<p>From the ¼ sec. cor. of secs. 7 and 8.</p> <p>S. 89° 04' W., on the E. and W. center line of sec. 7.</p> <p>Over rolling terrain.</p>
20.01	<p>Point for the center E. 1/16 sec. cor. of sec. 7.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R100W E1/16 C———C S 7 1999</p>
40.02	<p>Set a steel fence post alongside the iron post.</p> <p>The center ¼ sec. cor. of sec. 7.</p>
60.02	<p>Point for the center W. 1/16 sec. cor. of sec. 7.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R100W W1/16 C———C S 7 1999</p>
80.33	<p>Set a steel fence post alongside the iron post.</p> <p>The ¼ sec. cor. of sec. 7 only, on the W. bdy. of the Tp.</p> <hr/>

Subdivision of Section 7,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the E. 1/16 sec. cor. of secs. 7 and 18.
	N. 1° 19' W., on the N. and S. center line of the SE¼ of sec. 7.
	Over rolling terrain.
10.00	Enter mountainous terrain.
20.01	Point for the SE. 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the SE¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T33N R100W
	SE 1/16 S 7
	1999
	Set a steel fence post alongside the iron post.
	Cor. is located on steep S. slope.
40.02	The center E. 1/16 sec. cor. of sec. 7.
	From the true point for the S. 1/16 sec. cor. of secs. 7 and 8.
	N. 89° 23' W., on the E. and W. center line of sec. 7.
	Over rolling terrain.
20.12	The SE. 1/16 sec. cor. of sec. 7.
40.24	The center S. 1/16 sec. cor. of sec. 7.
	From the W. 1/16 sec. cor. of secs. 7 and 18.
	N. 0° 54' W., on the N. and S. center line of sec. 7.
	Over mountainous terrain.
19.79	Point for the SW. 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the SW¼.

Subdivision of Section 7,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>
	<p>T33N R100W</p>
	<p>SW 1/16 S 7</p>
	<p>1999</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>Cor. is located on steep S. slope.</p>
39.58	<p>The W. 1/16 sec. cor. of sec. 7.</p> <hr/>
	<p>From the center S. 1/16 sec. cor. of sec. 7.</p>
	<p>S. 89° 22' W., on the E. and W. center line of the SW¼ of sec. 7.</p>
	<p>Over mountainous terrain.</p>
20.12	<p>The SW. 1/16 sec. cor. of sec. 7.</p>
40.49	<p>The S. 1/16 sec. cor. of sec. 7 only, on the W. bdy. of the Tp.</p> <hr/>
	<p>Subdivision of Section 8,</p>
	<p>T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming</p> <hr/>
	<p>From the ¼ sec. cor. of secs. 8 and 17.</p>
	<p>N. 2° 05' W., on the N. and S. center line of sec. 8.</p>
	<p>Over rolling terrain.</p>
20.16	<p>Point for the center S. 1/16 sec. cor. of sec. 8.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>T33N R100W</p>
	<p>C</p>
	<p>S1/16 S 8</p>
	<p>C</p>
	<p>1999</p>

Subdivision of Section 8,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the iron post.
20.40	Fence, bears SE. and NW.
40.32	Point for the center $\frac{1}{4}$ sec. cor. of sec. 8, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T33N R100W
	C1/4 S 8
	1999
	Set a steel fence post alongside the iron post.
80.34	The $\frac{1}{4}$ sec. cor. of secs. 5 and 8.
	<hr/> From the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.
	S. $89^{\circ} 58'$ W., on the E. and W. center line of sec. 8.
20.30	Point for the center E. $\frac{1}{16}$ sec. cor. of sec. 8.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base to top, with brass cap mkd.
	T33N R100W
	E1/16
	C—C
	S 8
	1999
	Set a steel fence post alongside the iron post.
40.60	The center $\frac{1}{4}$ sec. cor. of sec. 8.
80.56	The $\frac{1}{4}$ sec. cor. of secs. 7 and 8.
	<hr/> From the E. $\frac{1}{16}$ sec. cor. of secs. 8 and 17.
	N. $1^{\circ} 51'$ W., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 8.

Subdivision of Section 8,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling terrain.
20.17	Point for the SE. 1/16 sec. cor. of sec. 8, at intersection with the E. and W. center line of the SE $\frac{1}{4}$.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T33N R100W
	SE 1/16 S 8
	1999
	Set a steel fence post alongside the iron post.
40.34	The center E. 1/16 sec. cor. of sec. 8.
	From the S. 1/16 sec. cor. of secs. 8 and 9.
	N. 89° 59' W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 8.
	Over rolling terrain.
20.22	The SE. 1/16 sec. cor. of sec. 8.
40.44	The center S. 1/16 sec. cor. of sec. 8.
	Subdivision of Section 10, T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming
	From the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	N. 0° 58' W., on the N. and S. center line of sec. 10.
	Over rolling terrain.
20.51	The center S. 1/16 sec. cor. of sec. 10, established by John D. Hart, Wyoming Registered Land Surveyor No. 6448, monumented with a steel reinforcement rod, 18 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with undated aluminum cap mkd. HART CS 1/16 S10 LS 6448. This position is accepted as a careful and faithful determination of the cor. position.
	At the corner point

Subdivision of Section 10,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T33N R100W C S1/16 S 10 C 1999</p>
	Deposit the steel reinforcement rod and set a steel fence post alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> <p>N. 0° 58' W., beginning new measurement.</p>
	Over rolling terrain.
19.96	Baldwin Creek Road, extending ESE. and WNW.
20.51	The center ¼ sec. cor. of sec. 10, at intersection with the E. and W. center line, established by Joseph W. Manatos, Wyoming Registered Land Surveyor No. 573, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a steel fence post alongside, with aluminum cap mkd.
	<p style="text-align: center;">J F C T33N R100W C1/4 SEC 10 1981 RLS 573</p>
	This position is accepted as a careful and faithful determination of the cor. position.
	<hr style="width: 20%; margin: auto;"/> <p>N. 0° 58' W., beginning new measurement.</p>
	Over rolling terrain.
0.27	Fence, bears N., E. and W.
15.00	Baldwin Creek, course E.
40.54	The ¼ sec. cor. of secs. 3 and 10, monumented by Joseph W. Manatos, Wyoming Registered Land Surveyor No. 573, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd.

Subdivision of Section 10,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">J F C T33N R100W S 3 1/4 ——— S 10 1981 RLS 573</p> <p>This position is accepted as the best available evidence of the original cor. position.</p> <p>Set a steel fence post alongside the aluminum post.</p> <p>Cor. is located 15 lks. E. of fence extending N. and S.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p> <p>S. $89^{\circ} 16'$ W., on the E. and W. center line of sec. 10.</p> <p>Over rolling terrain, along fence.</p>
19.70	<p>The center E. $\frac{1}{16}$ sec. cor. of sec. 10, established by Joseph W. Manatos, Wyoming Registered Land Surveyor No. 573, monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">J F C T33N R100W C-E $\frac{1}{16}$ SEC 10 1981 RLS 573</p> <p>This position is accepted as a careful and faithful determination of the cor. position.</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located S. 34° E., 29 lks. from intersection of fences extending N., E. and S.</p> <hr/> <p>S. $89^{\circ} 16'$ W., beginning new measurement.</p> <p>Over rolling terrain.</p>
13.00	<p>Thence along Baldwin Creek Road, bears NE. and SW.</p>

Subdivision of Section 10,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
19.70	The center $\frac{1}{4}$ sec. cor. of sec. 10.
22.70	Baldwin Creek Road, bears ESE. and WNW.
37.20	Baldwin Creek, bears ENE. and WSW.
39.39	<p>Point for the center W. $\frac{1}{16}$ sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T33N R100W W$\frac{1}{16}$ C—C S 10 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 60 lks. N. of Baldwin Creek Road, extending E. and SW.</p>
59.08	<p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 10.</p> <hr/> <p>From the E. $\frac{1}{16}$ sec. cor. of secs. 10 and 15.</p> <p>N. $0^{\circ} 35'$ W. on the N. and S. center line of the SE$\frac{1}{4}$ of sec. 10.</p> <p>Over rolling terrain, along fence.</p>
20.54	<p>Point for the SE. $\frac{1}{16}$ sec. cor. of sec. 10, at intersection with the E. and W. center line of the SE$\frac{1}{4}$.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T33N R100W SE $\frac{1}{16}$ S 10 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located S. 64° E., 57 lks. dist. from cor. of fences extending E. and S.</p>

Subdivision of Section 10,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
41.07	<p>The center E. 1/16 sec. cor. of sec. 10.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 10 and 11.</p> <p>S. 89° 21' W., on the E. and W. center line of the SE¼ of sec. 10.</p> <p>Over rolling terrain.</p>
10.00	Cor. of fences bears N. and W.
19.57	The SE. 1/16 sec. cor. of sec. 10.
39.14	<p>The center S. 1/16 sec. cor. of sec. 10.</p> <hr/> <p>From the the W. 1/16 sec. cor. of secs. 10 and 15.</p> <p>N. 1° 19' W., on the N. and S. center line of the SW¼ of sec. 10</p> <p>Over rolling terrain.</p>
20.49	<p>Point for the SW. 1/16 sec. cor. of sec. 10, at intersection with the E. and W. center line of the SW¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T33N R100W</p> <p style="text-align: center;">SW 1/16 S 10</p> <p style="text-align: center;">1999</p>
39.80	Baldwin Creek Road, bears NE. and SW.
40.98	<p>The center W. 1/16 sec. cor. of sec. 10.</p> <hr/> <p>From the center S. 1/16 sec. cor. of sec. 10.</p> <p>S. 89° 20' W., on the E. and W. center line of the SW¼ of sec. 10.</p> <p>Over rolling terrain.</p>

Subdivision of Section 10,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
19.57	The SW. 1/16 sec. cor. of sec. 10.
39.14	The S. 1/16 sec. cor. of secs. 9 and 10.
<hr/> Subdivision of Section 14, T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming <hr/>	
<p>From the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.</p> <p>N. $0^{\circ} 52'$ W., on the N. and S. center line of sec. 14.</p> <p>Over rolling terrain.</p>	
19.99	<p>The center S. 1/16 sec. cor. of sec. 14, monumented by person(s) unknown, with a steel reinforcement rod, 18 ins. long, $\frac{1}{2}$ in. diam., firmly set, flush with the surface of the ground, with undated aluminum cap mkd. C S 1/16 C. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T33N R100W C S1/16 S 14 C 1999</p> <p>Deposit the steel reinforcement rod and set a steel fence post alongside the iron post.</p> <p>Cor. is located N. 60° W., 55 lks. dist. from cor. of fences extending E. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 52'$ W., beginning new measurement.</p> <p>Over rolling terrain.</p>
19.99	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 14, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>

Subdivision of Section 14,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T33N R100W C1/4 S 14 1999</p>
40.05	<p>Cor. is located in fence extending E. and W.</p> <p>Point for the center N. 1/16 sec. cor. of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R100W C N1/16 S 14 C 1999</p>
	<p>Cor. is located at W. edge of hay meadow extending SE. and NNW.</p> <p>Thence across hay meadow.</p>
60.11	<p>The ¼ sec. cor. of secs. 11 and 14.</p>
	<hr/> <p>From the ¼ sec. cor. of secs. 13 and 14, monumented by Charles E. Spurlock Jr., Wyoming Professional Engineer and Land Surveyor No. 396, with an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with undated brass cap mkd.</p> <p style="text-align: center;">1972 1/4 S 14 S 13 PE LS 396</p>
	<p>This position is accepted as the best available evidence of the original cor. position.</p>
	<p>Cor. is located at intersection of fences extending N., E., S. and W.</p> <p>S. 89° 13' W., on the E. and W. center line of sec. 14.</p> <p>Over rolling terrain, along fence.</p>
40.07	<p>The center ¼ sec. cor. of sec. 14.</p>
60.24	<p>Point for the center W. 1/16 sec. cor. of sec. 14.</p>

Subdivision of Section 14,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
80.41	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R100W W1/16 C——C S 14 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 11 lks. S. of fence extending E. and W.</p> <p>The ¼ sec. cor. of secs. 14 and 15.</p>
40.16	<hr/> <p>From the center S. 1/16 sec. cor of sec. 14.</p> <p>S. 89° 17' W., on the E. and W. center line of the SW¼ of sec. 14.</p> <p>Over rolling terrain.</p> <p>The S. 1/16 sec. cor. of secs. 14 and 15.</p>
20.00	<hr/> <p>From the center W. 1/16 sec. cor. of sec. 14.</p> <p>N. 1° 09' W., on the N. and S. center line of the NW¼ of sec. 14.</p> <p>Over rolling terrain.</p> <p>Point for the NW. 1/16 sec. cor. of sec. 14, at intersection with the E. and W. center line of the NW¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T33N R100W NW 1/16 S 14 1999</p> <p>Cor. is located at intersection of wire fence extending E. and W., and wooden fence extending N., 5 chs.</p>

Subdivision of Section 14,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
30.00	Gravel road, bears SE. and NW.
40.01	The W. 1/16 sec. cor. of secs. 11 and 14.
	<hr/> <p>From the center N. 1/16 sec. cor. of sec. 14.</p> <p>S. 89° 02' W., on the E. and W. center line of the NW$\frac{1}{4}$ of sec. 14.</p> <p>Over rolling terrain, along fence.</p>
20.26	The NW. 1/16 sec. cor. of sec. 14.
40.53	The N. 1/16 sec. cor. of secs. 14 and 15.
	<hr/> <p style="text-align: center;">Subdivision of Section 17, T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.</p> <p>N. 0° 06' W., on the N. and S. center line of sec. 17.</p> <p>Over rolling terrain.</p>
10.00	Squaw Creek Road, bears SE. and NW.
37.46	The center $\frac{1}{4}$ sec. cor. of sec. 17, at intersection with the E. and W. center line, established by John D. Hart, Wyoming Registered Land Surveyor No. 6448, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with undated brass cap mkd.
	<p>HART</p> <p>C1/4 S 17</p> <p>LS 6448</p>
	<p>This position is accepted as a careful and faithful determination of the cor. position.</p> <hr/> <p>N. 0° 06' W., beginning new measurement.</p> <p>Over rolling terrain.</p>

Subdivision of Section 17,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
6.00	Baldwin Creek Road, bears NE. and SW.
11.00	Baldwin Creek, course NE.
18.73	Point for the center N. 1/16 sec. cor. of sec. 17. Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd. <div style="text-align: center;"> T33N R100W C N1/16 S 17 C 1999 </div> Set a steel fence post alongside the iron post. Cor. is located on W. edge of hay meadow, 30 lks. E. of irrigation ditch, 1 ft. wide, extending N. and S.
37.46	The ¼ sec. cor. of secs. 8 and 17. <hr/> <p>From the ¼ sec. cor. of secs. 16 and 17, reestablished by John D. Hart, Wyoming Registered Land Surveyor No. 6448, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with a steel fence post alongside, with undated aluminum cap mkd.</p> <div style="text-align: center;"> HART 1/4 S 17 S 16 LS 6448 </div> This position is accepted as a careful and faithful reestablishment of the original cor. position. S. 89° 47' W., on the E. and W. center line of sec. 17. Over rolling terrain.
40.34	The center ¼ sec. cor. of sec. 17.
47.85	Squaw Creek Road, bears NE. and SW.
60.51	Point for the center W. 1/16 sec. cor. of sec. 17. Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.

Subdivision of Section 17,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T33N R100W W1/16 C—C S 17 1999
	Set a steel fence post alongside the iron post. Cor. is located in meadow.
65.50	Baldwin Creek, course E.
80.68	The $\frac{1}{4}$ sec. cor. of sec. 17 and 18.
	<hr/> From the center W. 1/16 sec. cor. of sec. 17. N. 0° 04' W., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 17. Over rolling terrain.
2.30	Baldwin Creek, course E.
18.78	Point for the NW. 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the NW $\frac{1}{4}$. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base to top, with brass cap mkd.
	T33N R100W NW 1/16 S 17 1999
	Set a steel fence post alongside the iron post.
37.56	The W. 1/16 sec. cor. of secs. 8 and 17.
	<hr/> From the center N. 1/16 sec. cor. of sec. 17. S. 89° 55' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 17. Over rolling terrain.

Subdivision of Section 17,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.16	The NW. 1/16 sec. cor. of sec. 17.
40.32	The N. 1/16 sec. cor. of secs. 17 and 18.
<hr/> Subdivision of Section 21, T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming <hr/>	
	<p>The ¼ sec. cor. of secs. 21 and 28, monumented by Richard D. Inberg, Wyoming Registered Land Surveyor No. 488, with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with undated aluminum cap mkd.</p>
	<p>LS 488 T33N R100W SEC 21 1/4 ————— SEC 28</p>
	<p>This position is accepted as the best available evidence of the original cor. position.</p>
	<p>Cor. is located in wooden corral fence, extending N. and S., 45 lks. W. of access road to ranch.</p>
	<p>N. 1° 03' W., on the N. and S. center line of sec. 21.</p>
	<p>Over rolling terrain.</p>
37.50	Squaw Creek Road, bears NE. and SW.
40.69	<p>Point for the center ¼ sec. cor. of sec. 21, at intersection with the E. and W. center line.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>T33N R100W C1/4 S 21 1999</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>Cor. is located on right bank of Squaw Creek, 15 lks. wide, course S.</p>

Subdivision of Section 21,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.92	A steel reinforcement rod, 5/8 in. diam., firmly set projecting 18 ins. above the ground, established by John D. Hart, Wyoming Registered Land Surveyor No. 6448, with an undated aluminum cap mkd. HART WC 15 ft N LS 6448.
40.96	Squaw Creek, course NNE.
61.08	The center N. 1/16 sec. cor. of sec. 21, established by John D. Hart, Wyoming Registered Land Surveyor No. 6448, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with undated aluminum cap mkd.
	HART
	CN1/16
	LS 6448
	This position is accepted as a careful and faithful determination of the cor. position.
	Cor. is located at intersection of fences extending N., S. and W.
	<hr style="width: 30%; margin: auto;"/>
	N. 1° 04' W., beginning new measurement.
	Over rolling terrain.
20.42	The ¼ sec. cor. of sec. 16 and 21.
	<hr style="width: 80%; margin: auto;"/>
	From the ¼ sec. cor. of secs. 21 and 22.
	N. 87° 08' W., on the E. and W. center line of sec. 21.
	Over rolling terrain, along the Squaw Creek Road.
13.10	Squaw Cree Road, bears ESE. and WNW.
21.17	Point for the center E. 1/16 sec. cor. of sec. 21.
	Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.
	T33N R100W E1/16 C—C S 21 1999

Subdivision of Section 21,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Cor. is located 25 lks. N. of the center line of the Squaw Creek Road, on N. edge of pavement.
	From this point, an iron post, 2½ ins. diam., bears N. 0° 54' W., 0.264 chs. dist., firmly set, projecting 4 ins. above the ground, in a tire, established by Charles E. Spurlock Jr., Wyoming Professional Engineer and Land Surveyor No. 396, with brass cap mkd. 1972 WC CE 1/16 C-C S21 PE LS 396.
36.60	Squaw Creek Road, bears ENE. and WSW.
42.34	The center ¼ sec. cor. of sec. 21; Squaw Creek Road continues SW.
43.80	Squaw Creek, course NE.
67.30	Squaw Creek road, bears SE. and NW.
84.73	The ¼ sec. cor. of secs. 20 and 21.
<hr/>	
	From the center E. 1/16 sec. cor. of sec. 21.
	N. 0° 23' W., on the N. and S. center line of the NE¼ of sec. 21.
	Over rolling terrain.
0.90	Squaw Creek road, bears E. and W.
6.00	Squaw Creek, course E.
20.12	Point for the NE. 1/16 sec. cor. of sec. 21, at intersection with the E. and W. center line of the NE¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T33N R100W
	NE 1/16 S 21
	1999
	Set a steel fence post alongside the iron post.
20.24	The E. 1/16 sec. cor. of secs. 16 and 21.
<hr/>	

Subdivision of Section 21,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the N. 1/16 sec. cor. of secs. 21 and 22.
	N. 86° 26' W., on the E. and W. center line of the NE¼ of sec. 21.
	Over rolling terrain.
21.42	The NE. 1/16 sec. cor. of sec. 21.
42.84	The center N. 1/16 sec. cor. of sec. 21.
	<p style="text-align: center;">Subdivision of Section 22, T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming</p>
	From the ¼ sec. cor. of secs. 22 and 27, monumented by Harold E. O'Malley, Wyoming Professional Engineer and Land Surveyor No. 468, with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with undated brass cap mkd.
	<p style="text-align: center;">S 22 1/4 ——— S 27 PE LS 468</p>
	This position is accepted as the best available evidence of the original cor. position.
	Cor. is located at intersection of fences extending N., E. and W.
	N. 1° 52' E., on the E. and W. center line of sec. 22.
	Over rolling terrain, along fence.
39.70	Intersection of fences, bears E., S. and W.
40.42	The center ¼ sec. cor. of sec. 22, at intersection with the E. and W. center line, monumented by person(s) unknown, with a concrete nail, 1/4 in. diam., firmly set, flush with the surface of Squaw Creek Road, paved, bearing E. and W., 55 ft. N. of the center. This position is accepted as a careful and faithful determination of the cor. position.
	from which new reference monuments

Subdivision of Section 22,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, in a right of way fence extending E. and W., bears S. 10° E., 60 lks. dist., with brass cap mkd. RM T33N R100W S22 39.6 FT 1999 and an arrow pointing the the cor.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, in a right of way fence extending E. and W., bears S. 41° E., 62.7 lks. dist., with brass cap mkd. RM T33N R100W S22 41FT 1999 and an arrow pointing the the cor.</p>
	<hr/> <p>N. 1° 52' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
5.30	Squaw Creek, course E.
19.92	Point for the center N. 1/16 sec. cor. of sec. 22.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T33N R100W C N1/16 S 22 C 1999</p>
	Set a steel fence post alongside the iron post.
39.85	The ¼ sec. cor. of sec. 15 and 22.
	<hr/> <p>From the ¼ sec. cor. of secs. 22 and 23.</p> <p>S. 88° 51' W., on the E. and W. center line of sec. 22.</p> <p>Over rolling terrain, along Squaw Creek Road.</p>
19.17	The center E. 1/16 sec. cor. of sec. 22, established by John D. Hart, Wyoming Registered Land Surveyor No. 6448, monumented with a steel reinforcement rod, 5/8 ins. diam., firmly set, flush with the surface of the ground, with undated aluminum cap mkd.

Subdivision of Section 22,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	HART E1/16 C———C S 22 LS 6448
	This position is accepted as a careful and faithful determination of the cor. position.
	Cor. is located at cor. of hay meadow, 50 lks. N. of Squaw Creek Road.
	<hr/>
	S. 88° 51' W., beginning new measurement.
	Over rolling terrain, along Squaw Creek Road.
19.15	The center $\frac{1}{4}$ sec. cor. of sec. 22.
	<hr/>
	S. 88° 51' W., beginning new measurement.
35.62	The $\frac{1}{4}$ sec. cor. of secs. 21 and 22.
	<hr/>
	From the center E. 1/16 sec. cor. of sec. 22.
	N. 0° 43' E., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 22.
	Over rolling terrain, along fence.
1.70	Squaw Creek Road, bears E. and W.
7.00	Squaw Creek, course NE.
19.93	Point for the NE. 1/16 sec. cor. of sec. 22, at intersection with the E. and W. center line of the NE $\frac{1}{4}$.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T33N R100W NE 1/16 S 22 1999
	Set a steel fence post alongside the iron post.

Subdivision of Section 22,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Cor. is located 2 lks. W. of fence extending N. and S.
20.11	Intersection of fences, bears N., S. and abandoned W.
39.86	The E. 1/16 sec. cor. of secs. 15 and 22.
	From the N. 1/16 sec. cor. of secs. 22 and 23.
	S. 88° 45' W., on the E. and W. center line of the NE¼ of sec. 22.
	Over rolling terrain.
18.76	The NE. 1/16 sec. cor. of sec. 22.
37.51	The center N. 1/16 sec. cor. of sec. 22.
	From the center N. 1/16 sec. cor. of sec. 22.
	S. 88° 46' W., on the E. and W. center line of the NW¼ of sec. 22.
	Over rolling terrain.
36.16	The N. 1/16 sec. cor. of secs. 21 and 22.
	<p style="text-align: center;">Subdivision of Section 23, T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming</p>
	From the ¼ sec. cor. of secs. 23 and 26.
	N. 0° 42' W., on the N. and S. center line of sec. 23.
	Over rolling terrain.
39.32	The center ¼ sec. cor. of sec. 23, at intersection with the E. and W. center line, established by John D. Hart, Wyoming Registered Land Surveyor No. 6448, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with undated aluminum cap mkd.
	C1/4 S 23
	LS 6448

Subdivision of Section 23,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>This position is accepted as a careful and faithful determination of the cor. position.</p> <p>Cor. is located at cor. of fences extending N. and E.</p> <hr/> <p>N. 0° 43' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
20.00	Intersection of fences, bears E., S. and W.
20.60	Squaw Creek Road, bears NE. and SW.
25.20	Squaw Creek, course E.
40.00	The ¼ sec. cor. of secs. 14 and 23.
	<hr/> <p>S. 89° 29' W., on the E. and W. center line of sec. 23.</p> <p>Over rolling terrain.</p>
40.47	The center ¼ sec. cor. of sec. 23.
60.55	<p>The center W. 1/16 sec. cor. of sec. 22, established by John D. Hart, Wyoming Registered Land Surveyor No. 6448, monumented with a steel reinforcement rod, 18 ins. long, 5/8 in. diam., firmly set, flush with the surface of the ground, with undated aluminum cap mkd. HART CW 1/16 LS 6448. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R100W W1/16 C—C S 23 1999</p> <p>Deposit the steel reinforcement rod alongside the iron post.</p> <p>Cor. is located in fence extending SSE. and N. 42 lks. to intersection of fences extending SSE., S. and N.</p> <hr/>

Subdivision of Section 23,
T. 33 N., R. 100 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>S. 89° 29' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>20.08 The $\frac{1}{4}$ sec. cor. of secs. 22 and 23.</p> <hr/> <p>From the W. 1/16 sec. cor. of secs. 23 and 26.</p> <p>N. 0° 49' W., on the N. and S. center line of the SW$\frac{1}{4}$ of sec. 23.</p> <p>Over rolling terrain.</p> <p>19.85 The SW. 1/16 sec. cor. of sec. 23, established by John D. Hart, Wyoming Registered Land Surveyor No. 6448, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with undated aluminum cap mkd.</p> <p style="text-align: center;">T33N R100W</p> <p style="text-align: center;">SW 1/16 S 23</p> <p style="text-align: center;">LS 6448</p> <hr/> <p>N. 0° 49' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>19.85 The center W. 1/16 sec. cor. of sec. 23.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area embraced by this survey is situated in the central portion of Fremont County, approximately 2 miles east of Lander, Wyoming. The terrain is rolling with an elevation of about 6,000 feet above sea level. The soil is sandy loam and rocky with vegetation consisting of native grasses and juniper.</p> <p>Drainage of the area is easterly by Baldwin Creek and Squaw Creek.</p> <p>Access is by Baldwin Creek road and Squaw Creek road from Lander an by numerous roads and trails throughout the area. The area is heavily inhabited with subdivisions, single family residences and ranches in the area. There was no evidence of mineral activity at the time of this survey.</p>
--------	--

CERTIFICATE OF SURVEY

329

I, Lynn A. Forbes, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 14th day of January, 1999, I have dependently resurveyed of a portion of the Twelfth Auxiliary Guide Meridian West, through Township 33 North, between Ranges 100 and 101 West, and a portion the subdivisional lines and the subdivision of certain sections, Township 33 North, Range 100 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JAN 23 2002

(Date)

Lynn A. Forbes
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of a portion of the Twelfth Auxiliary Guide Meridian West, through Township 33 North, between Ranges 100 and 101 West, and a portion the subdivisional lines and the subdivision of certain sections, Township 33 North, Range 100 West, of the Sixth Principal Meridian, in the State of Wyoming, executed by Lynn A. Forbes, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 23 2002

(Date)

John P. Lee
(Signature of Authorized Officer)