

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
DEPENDENT RESURVEY
OF THE
SUBDIVISIONAL LINES,
TOWNSHIP 42 NORTH, RANGE 74 WEST,
OF THE SIXTH PRINCIPAL MERIDIAN,
IN THE STATE OF WYOMING.

EXECUTED BY

RICHARD A. KOHLER

CADASTRAL SURVEYOR

Under Special Instructions dated APRIL 3, 1995, approved APRIL 3, 1995, which provided for the surveys included under Group Number 601, and assignment instructions dated SEPTEMBER 18, 1996.

Survey commenced JULY 30, 1997

Survey completed JULY 7, 1998

INDEX DIAGRAM

Township 42 North, Range 74 West

6	55 5	38 4	29 3	20 2	11 1
54	53	37	28	19	10
7	51 8	36 9	27 10	18 11	9 12
70	50	36	26	17	8
18	47 17	35 16	25 15	16 14	7 13
46	46	34	24	15	6
19	44 20	33 21	24 22	15 23	5 24
43	43	33	23	14	5
30	40 29	31 28	22 27	13 26	4 25
40	39	31	22	13	3
31	38 32	30 33	21 34	12 35	2 36

T. 42 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS

The following field notes are those of the dependent resurvey of the subdivisional lines, Township 42 North, Range 74 West, Sixth Principal Meridian, Wyoming.

Joseph R. Moore, under joint contract with Charles McCarthy, surveyed the exterior boundaries in 1881. Frank Buckley retraced the exterior boundaries and surveyed the subdivisional lines in 1882. Russell C. MacDonald dependently resurveyed the west boundary in 1954. Richard A. Kohler dependently resurveyed the east boundary in 1990. Joel T. Ebner dependently resurveyed the north boundary in 1992. Richard A. Kohler dependently resurveyed the south boundary during the dependent resurvey of T. 41 N., R. 74 W., executed concurrently under this same group.

Jesse E. Spielman, Campbell County Surveyor, executed surveys of Gillette and Douglas Road in 1917, Savageton Road South in 1921 and Reno-Salt Creek Road in 1924; records of these surveys are filed in the Campbell County Clerk's Office. Connections were made during these surveys to existing original corners, where available, and these connected positions were accepted as the best available evidence of the original corner positions. A number of local surveys have been executed throughout the area and acceptance of these surveys is detailed herein.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 601, Wyoming, dated April 3, 1995.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data was thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

The survey was executed with a Lietz Model SET4 electronic total station, a Wild Model T-16 theodolite and by chaining methods. The instruments were maintained in proper adjustment at all times. The directions of all lines refer to the true meridian, determined by hour angle observations of the sun at various points along the lines of survey and carried forward by sustained angulation.

T. 42 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>The geographic position of the southeast corner of the township, based on NAD 83 and determined by satellite positioning methods, is:</p> <p>Latitude 43° 33' 41.68" N., Longitude 105° 41' 07.21" W.</p> <p>The mean magnetic declination is 11½° E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the Subdivisional Lines, T. 42 N., R. 74 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Frank Buckley in 1882)</p> <hr/> <p>Beginning at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 41 N., R. 74 W., executed concurrently under this same group.</p> <p>N. 0° 43' W., bet. secs. 35 and 36.</p> <p>Over rolling to broken terrain, along fence.</p>
2.60	Bates Creek, 20 lks. wide, course NE.
18.60	Bates Creek, 20 lks. wide, course WNW.
29.90	Bates Creek, 20 lks. wide, course ENE.
34.90	Bates Creek, 20 lks. wide, course WSW.
40.085	True point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance, falls in Bates Creek, 20 lks. wide, course SSE., where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.
41.185	Point selected for the witness cor. to the 1/4 sec. cor. of secs. 35 and 36.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	W C T42N R74W 1/4 S 35 S 36 ↓ 1997

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS											
	<p>Set a steel fence post alongside the iron post.</p> <p>Witness cor. is located 13 lks. W. of fence extending irregularly N. and S. at creek crossing.</p>										
70.50	<p>Spur, slopes SSE.</p>										
80.17	<p>The cor. of secs. 25, 26, 35 and 36, at intersection of fences extending E., S. and W., and dim fence scar extending N. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T42N</td> <td>R74W</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> <tr> <td colspan="2">1997</td> </tr> </table> </div>	T42N	R74W	S 26	S 25	S 35	S 36	1997			
T42N	R74W										
S 26	S 25										
S 35	S 36										
1997											
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., marked with a chiseled cross, inside a 1½ ins. sq., on cross pipe of cattle guard, as described in the 1990 field notes of the dependent resurvey, T. 42 N., R. 73 W.</p> <p>N. 89° 33' W., bet. secs. 25 and 36.</p> <p>Over rolling to broken terrain, along fence.</p>										
39.20	<p>North Bates Creek, 40 lks. wide, course S.</p>										
40.985	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T42N</td> <td>R74W</td> </tr> <tr> <td>S 25</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 36</td> <td></td> </tr> <tr> <td colspan="2">1997</td> </tr> </table> </div>	T42N	R74W	S 25		1/4	—	S 36		1997	
T42N	R74W										
S 25											
1/4	—										
S 36											
1997											
	<p>Set a steel fence post alongside the iron post.</p>										

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	Cor. is located 1.20 chs. S. of fence extending irregularly E. and W.
81.97	The cor. of secs. 25, 26, 35 and 36.
	N. 0° 44' W., bet. secs. 25 and 26.
	Over rolling terrain, along fading fence scar.
39.88	Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T42N R74W 1/4 S 26 S 25 1997</p>
	Set a steel fence post alongside the iron post.
	Cor. is located 20 lks. N. of North Bates Creek (dry), 10 lks. wide, course E.
79.76	The cor. of secs. 23, 24, 25 and 26, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, and a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE WYOMING and mkd.
	<p style="text-align: center;">T42N R74W S 23 S 24 ----- S 26 S 25 P.L.S. 538 1987</p>
	This position is accepted as the best available evidence of the original cor. position.
	Cor. is located S. 17½° E., 3.75 chs. dist., from intersection of fences extending N., E., S. and W.

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., as described in the 1990 field notes of the dependent resurvey, T. 42 N., R. 73 W.</p>
	<p>N. 89° 48' W., bet. secs. 24 and 25.</p>
	<p>Over rolling to broken terrain.</p>
41.545	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T42N R74W S 24 1/4 ——— S 25 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
45.60	<p>Spur, slopes SE.</p>
83.09	<p>The cor. of secs. 23, 24, 25 and 26.</p>
	<hr/> <p>N. 0° 40' W., bet. secs. 23 and 24.</p>
	<p>Over rolling terrain, along E. slope of ridge.</p>
27.00	<p>Spur, slopes ESE.</p>
39.99	<p>The 1/4 sec. cor. of secs. 23 and 24, determined at a point 5 lks. E. of intersection of fences extending N., S. and W. There is no remaining evidence of the stone described in a Certified Land Corner Recordation by Stanton J. Abel Jr., Wyoming Professional Engineer and Land Surveyor No. 2877, as filed in the Campbell County Clerk's Office. This position is accepted as the best available evidence of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T42N R74W 1/4 S 23 S 24 1998</p> <hr/>
	<p>N. 0° 47' E., beginning new measurement.</p>
	<p>Over gently rolling terrain, along fence.</p>
39.96	<p>Point for the cor. of secs. 13, 14, 23 and 24, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T42N R74W S 14 S 13 <hr/>S 23 S 24 1998</p> <hr/>
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an aluminum rod, 5/8 in. diam., as described in the 1990 field notes of the dependent resurvey, T. 42 N., R. 73 W.</p> <p>N. 89° 55' W., bet. secs. 13 and 24.</p> <p>Over rolling to broken terrain.</p>
41.53	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T42N R74W S 13 1/4 — S 24 1998</p>
	<p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
83.06	The cor. of secs. 13, 14, 23 and 24.
	<hr/> N. 0° 57' E., bet. secs. 13 and 14. Over rolling terrain, along fence.
35.80	Leave fence, bears NE. and S.; thence along dim fence scar.
39.20	Wash, 10 lks. wide, drains SW.
39.96	The 1/4 sec. cor. of secs. 13 and 14, at cor. of abandoned fence
	extending S., other direction(s) indeterminate, as evidenced by
	buried stone tie-downs and barbed guy wires. This position is
	accepted as the best available evidence of the original cor.
	position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the
	ground, with brass cap mkd.
	<div style="text-align: center;"> T42N R74W 1/4 S 14 S 13 1998 </div>
	Set a steel fence post alongside the iron post.
	<hr/> N. 0° 14' E., beginning new measurement.
	Over rolling terrain.
41.03	The cor. of secs. 11, 12, 13 and 14, monumented by Edward C.
	Fry, Wyoming Professional Engineer and Land Surveyor No. 662,
	with a steel reinforcement rod, 25 ins. long, 5/8 in. diam.,
	firmly set 20 ins. in the ground, at cor. of fences extending S.
	and W., 96 lks. N. of cor. of fences extending N. and E., with
	aluminum cap inscribed CIVIL ENGR SER and mkd. 11 12 13 14 662,
	as filed in the Campbell County Clerk's Office. This position
	is accepted as the best available evidence of the original cor.
	position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the
	ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	T42N R74W S 11 S 12 ----- S 14 S 13 1997
	<p>Deposit the steel reinforcement rod inside the iron post.</p> <p>From this point, a position established by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, bears S. 66° 38' E., 1.78 chs. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap inscribed ANC and mkd. T42N R74W 11 12 13 14 LS2327 1979, with a steel fence post alongside, as filed in the Campbell County Clerk's Office. This position is not utilized during the course of this resurvey.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an aluminum rod, 5/8 in. diam., as described in the 1990 field notes of the dependent resurvey, T. 42 N., R. 73 W.</p> <p>N. 89° 19' W., bet. secs. 12 and 13.</p> <p>Over rolling terrain.</p>
20.70	Ridge, bears SE. and NW.
41.21	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	T42N R74W S 12 1/4 ——— S 13 1998
53.00	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located N. 78° W., 2.15 chs. dist., from intersection of fences extending N., E. and W.</p> <p>Spur, slopes SSW.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
82.42	The cor. of secs. 11, 12, 13 and 14.
	N. 1° 27' E., bet. secs. 11 and 12.
	Over rolling terrain.
23.20	Ridge, bears SE. and NW.
39.655	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T42N R74W
	1/4
	S 11 S 12
	1998
	Set a steel fence post alongside the iron post.
	From this point, a position established by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, bears S. 66° 42' E., 87 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office. This position is not utilized during the course of this resurvey.
76.30	Wyoming State Highway No. 387, bears ENE. and WSW.
79.31	The cor. of secs. 1, 2, 11 and 12, reestablished by Jesse E. Spielman, Campbell County Surveyor, in 1924, and remonumented by Edward C. Fry, Wyoming Professional Engineer and Land Surveyor No. 662, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 19 ins. in the ground, in abandoned Reno-Salt Creek Road, extending E. and W., with aluminum cap inscribed CIVIL ENGR SER and mkd. 1 2 11 12 662, as filed in the Campbell County Clerk's Office, from which right-of-way monuments established by Mr. Spielman
	A sandstone, firmly set, projecting 11x7x3 ins. above the ground, no mks. visible, bears SOUTH, 51.5 lks. dist.
	A sandstone, 12x6x3 ins., lying loose, plainly mkd. CR on a face, bears N. 3° 53' W., 56 lks. dist.

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS											
	<p>This position is accepted as a reestablishment of the original cor. position.</p>										
	<p>At the corner point</p>										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T42N R74W</td> </tr> <tr> <td style="text-align: center;">S 2</td> <td style="text-align: center;">S 1</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 11</td> <td style="text-align: center;">S 12</td> </tr> <tr> <td colspan="2" style="text-align: center;">1997</td> </tr> </table>	T42N R74W		S 2	S 1	-----		S 11	S 12	1997	
T42N R74W											
S 2	S 1										

S 11	S 12										
1997											
	<p>Deposit the steel reinforcement rod inside and bury the loose county road stone and set a steel fence post alongside the iron post.</p>										
	<p>From this point, a position established by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, bears N. 42° 14' W., 3.7 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. T42N R74W 1 2 11 12 LS2327 1979, as filed in the Campbell County Clerk's Office. This position is not utilized during the course of this resurvey.</p>										
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an aluminum rod, 5/8 in. diam., as described in the 1990 field notes of the dependent resurvey, T. 42 N., R. 73 W.</p>										
	<p>S. 89° 59' W., bet. secs. 1 and 12.</p>										
	<p>Over rolling terrain, along abandoned Reno-Salt Creek Road.</p>										
36.50	<p>Ridge, bears N. and S.</p>										
39.00	<p>Fence, bears N. and S.</p>										
40.29	<p>The 1/4 sec. cor. of secs. 1 and 12, identical with unnumbered station of abandoned Reno-Salt Creek Road, extending E. and W., from which right-of-way monuments established by Jesse E. Spielman, Campbell County Surveyor, in 1924</p>										
	<p>A broken sandstone, 15x6x3 ins., base portion firmly set 2 ins. below the surface of the ground, no mks. visible, bears NORTH, 50 lks. dist.</p>										

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	<p>A broken sandstone, 18x9x4 ins., base portion firmly set flush with the surface of the ground, no mks. visible, bears SOUTH, 50 lks. dist.</p>
	<p>This position is accepted as a reestablishment of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T42N R74W S 1 1/4 ——— S 12 1997</p>
	<p>Bury the stone monuments in place and set a steel fence post alongside the iron post.</p>
	<hr style="width: 20%; margin: auto;"/> <p>N. 89° 59' W., beginning new measurement.</p>
	<p>Over rolling terrain, along abandoned Reno-Salt Creek road.</p>
33.20	<p>Wyoming State Highway No. 387, bears ENE. and WSW.</p>
40.30	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/>
	<p>N. 0° 24' W., bet. secs. 1 and 2.</p>
	<p>Over rolling to broken terrain.</p>
36.60	<p>Ridge, bears SE. and NW.</p>
40.32	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T42N R74W 1/4 S 2 S 1 1998</p>
	<p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, a position established by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, bears S. 88° 34' E., 48 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. T42N R74W 1/4 1 2 LS2327 1979, as filed in the Campbell County Clerk's Office. This position is not utilized during the course of this resurvey.</p>
75.40	Belle Fourche River, 10 lks. wide, course ENE.
80.29	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1992 field notes of the dependent resurvey, T. 43 N., R. 74 W.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 41 N., R. 74 W., executed concurrently under this same group.</p> <p>N. 0° 19' W., bet. secs. 34 and 35.</p> <p>Over rolling terrain.</p>
40.255	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T42N R74W 1/4 S 34 S 35 1997</p> </div> <p>Set a steel fence post alongside the iron post.</p>
47.40	Bates Creek, 20 lks. wide, course ESE.
80.51	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T42N R74W S 27 S 26 ----- S 34 S 35 1997</p> </div>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the iron post.
	From the cor. of secs. 25, 26, 35 and 36.
	S. 89° 44' W., bet. secs. 26 and 35.
	Over rolling terrain, along fence.
12.60	Ridge, bears SE. and NW.
40.24	Point for the 1/4 sec. cor. of secs. 26 and 35, determined longitudinally by proportionate measurement and latitudinally by fence extending E. and W.; there is no remaining evidence of the original monument.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T42N R74W S 26 1/4 ——— S 35 1997
	S. 89° 26' W., beginning new measurement.
	Over rolling terrain, along fence.
1.50	Leave fence, bears E. and WNW.
40.24	The cor. of secs. 26, 27, 34 and 35.
	N. 0° 13' W., bet. secs. 26 and 27.
	Over rolling terrain.
1.10	Fence, bears E. and W.
34.80	Ridge, bears ESE. and WNW.
40.255	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T42N R74W 1/4 S 27 S 26 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
80.51	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance, falls in or near fading fence scar extending N. and S.; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T42N R74W S 22 S 23 ----- S 27 S 26 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p>
	<p>N. 89° 53' W., bet. secs. 23 and 26.</p>
	<p>Over rolling terrain.</p>
1.20	<p>Fence, bears N. and S.</p>
37.50	<p>Wash, 5 lks. wide, drain SW.</p>
39.855	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T42N R74W S 23 1/4 ——— S 26 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
41.30	<p>North Bates Creek, 10 lks. wide, course SSE.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
79.71	The cor. of secs. 22, 23, 26 and 27.
	N. 0° 22' E., bet. secs. 22 and 23.
	Over rolling terrain, along fading fence scar.
22.90	Spur, slopes SSE.
40.255	Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance, falls in or near fading fence scar extending N. and S.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T42N R74W
	1/4
	S 22 S 23
	1997
	Set a steel fence post alongside the iron post.
80.51	The cor. of secs. 14, 15, 22 and 23, monumented by Daniel A. Siek, Wyoming Registered Land Surveyor No. 2097, with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, at cor. of abandoned fence extending N. and S., other direction(s) indeterminate, as filed in the Campbell County Clerk's Office, with brass cap mkd.
	T42N R74W
	S 15 S 14
	S 22 S 23
	1984
	RLS 2097
	This position is accepted as the best available evidence of the original cor. position.
	From the cor. of secs. 13, 14, 23 and 24.
	N. 89° 28' W., bet. secs. 14 and 23.
	Over rolling terrain.
39.13	Point for the 1/4 sec. cor. of secs. 14 and 23, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R74W S 14 1/4 ——— S 23 1998</p> <hr/> <p>N. 89° 28' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
27.40	Ridge, bears SSE. and NNW.
40.13	The cor. of secs. 14, 15, 22 and 23.
	<hr/> <p>N. 0° 33' W., bet. secs. 14 and 15.</p> <p>Over rolling terrain, along fading fence scar.</p>
5.00	Spur, slopes SW.
40.02	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance, falls in trail road extending N. and S.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R74W 1/4 S 15 S 14 1998</p>
80.04	<p>Set a steel fence post 5 lks. E. of the iron post.</p> <p>The cor. of secs. 10, 11, 14 and 15, monumented by Edward C. Fry, Wyoming Professional Engineer and Land Surveyor No. 662, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 18 ins. in the ground, in fence extending E. and W., with aluminum cap inscribed CIVIL ENGR SER and mkd. 10 11 14 15 662, as filed in the Campbell County Clerk's Office. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS											
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T42N</td><td>R74W</td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 15</td><td>S 14</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div>	T42N	R74W	S 10	S 11	<hr/>		S 15	S 14	1998	
T42N	R74W										
S 10	S 11										
<hr/>											
S 15	S 14										
1998											
	<p>Deposit the steel reinforcement rod inside the iron post.</p> <p>From this point, a position established by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, bears S. 64° 57' E., 1.63 chs. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. T42N R74W 10 11 14 15 LS2327 1979, as filed in the Campbell County Clerk's Office. This position is not utilized during the course of this resurvey.</p>										
	<hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89° 55' W., bet. secs. 11 and 14.</p> <p>Over rolling to broken terrain, along fence.</p>										
24.70	Spur, slopes S.										
38.46	<p>The 1/4 sec. cor. of secs. 11 and 14, at intersection of fences extending N., E. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T42N</td><td>R74W</td></tr> <tr><td>S 11</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 14</td><td></td></tr> <tr><td colspan="2">1997</td></tr> </table> </div>	T42N	R74W	S 11		1/4	—	S 14		1997	
T42N	R74W										
S 11											
1/4	—										
S 14											
1997											
	<hr/> <p>S. 89° 49' W., beginning new measurement.</p> <p>Over rolling to broken terrain, along fence.</p>										
31.00	Ridge, bears S. and NW.										

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
42.36	The cor. of secs. 10, 11, 14 and 15.
	N. 1° 36' E., bet. secs. 10 and 11.
	Over rolling terrain.
16.10	Ridge, bears SE. and NW.
39.77	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T42N R74W
	1/4
	S 10 S 11
	1998
	Set a steel fence post alongside the iron post.
	From this point, a Wyoming State Highway Department right-of-way monument bears N. 70° W., 12.8 lks. dist., a concrete post, 6 ins. sq., firmly set, projecting 1 in. above the ground, with brass tablet inscribed STATE HIGHWAY DEPT. REFERENCE MARKER and mkd. PT 970+21.79 Elev. 5266.52.
42.00	Wyoming State Highway No. 387, bears ENE. and WSW.
79.54	The cor. of secs. 2, 3, 10 and 11, monumented by Edward C. Fry, Wyoming Professional Engineer and Land Surveyor No. 662, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 21 ins. in the ground, in center of abandoned Reno-Salt Creek Road, extending E. and W., with aluminum cap inscribed CIVIL ENGR SER and mkd. 2 3 10 11 662, as filed in the Campbell County Clerk's Office. This position is accepted as a careful and faithful determination of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T42N R74W
	S 3 S 2
	S 10 S 11
	1997

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	<p>Deposit the steel reinforcement rod inside the iron post.</p>
	<p>From this point, a position established by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, bears N. 87° 03' W., 19.3 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. T42N R74W 2 3 10 11 LS2327 1979, as filed in the Campbell County Clerk's Office. This position is not utilized during the course of this resurvey.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p>
	<p>N. 89° 57' W., bet. secs. 2 and 11.</p>
	<p>Over rolling terrain, along abandoned Reno-Salt Creek Road.</p>
37.90	<p>Spur, slopes N.</p>
40.56	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, with a steel reinforcement rod, 20 ins. long, 5/8 in. diam., firmly set 17 ins. in the ground, in center of abandoned Reno-Salt Creek Road, extending E. and W., with aluminum cap mkd. T42N R74W 1/4 2 11 LS2327 1979, as filed in the Campbell County Clerk's Office, from which a right-of-way monument established by Jesse. E. Spielman, Campbell County Surveyor, in 1924</p>
	<p>A sandstone, 8x7x4 ins., lying loose, plainly mkd. CR on a face, bears SOUTH, 50 lks. dist.</p>
	<p>This position is accepted as a reestablishment of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>T42N R74W</p>
	<p>S 2</p>
	<p>1/4 ———</p>
	<p>S 11</p>
	<p>1997</p>
	<p>Deposit the steel reinforcement rod inside and bury the county road stone and set a steel fence post alongside the iron post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	S. 89° 58' W., beginning new measurement.
	Over rolling terrain, along abandoned Reno-Salt Creek Road.
12.18	From this point, a U.S. Coast and Geodetic Survey benchmark bears NORTH, 43 lks. dist., monumented with a standard brass tablet seated in a concrete post, 6 ins. sq., firmly set, projecting 11 ins. above the ground, mkd. L58 1934.
40.00	The cor. of secs. 2, 3, 10 and 11.
	N. 0° 50' W., bet. secs. 2 and 3.
	Over rolling to broken terrain.
29.20	Belle Fourche River, 15 lks. wide, course ENE.
40.08	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T42N R74W 1/4 S 3 S 2 1998
	Set a steel fence post alongside the iron post.
	From this point, a position established by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, bears N. 81° 57' E., 83.5 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap inscribed ANC and mkd. T42N R74W 1/4 3 2 LS2327 1979, as filed in the Campbell County Clerk's Office. This position is not utilized during the course of this resurvey.
79.97	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1992 field notes of the dependent resurvey, T. 43 N., R. 74 W.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 41 N., R. 74 W., executed concurrently under this same group.

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS											
	N. 0° 14' E., bet. secs. 33 and 34.										
	Over rolling terrain, along fence.										
27.80	Spur, slopes ESE.										
40.85	The 1/4 sec. cor. of secs. 33 and 34, at intersection of fences extending S. and W., and abandoned fence extending N. This position is accepted as the best available evidence of the original cor. position.										
	At the corner point										
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T42N</td><td>R74W</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td>S 33</td><td> S 34</td></tr> <tr><td></td><td>1997</td></tr> </table>	T42N	R74W		1/4	S 33	S 34		1997		
T42N	R74W										
	1/4										
S 33	S 34										
	1997										
	N. 0° 11' E., beginning new measurement.										
	Over rolling terrain, along abandoned fence.										
2.70	Spur, slopes SE.										
39.98	The cor. of secs. 27, 28, 33 and 34, at intersection of abandoned fences extending N., E. and S. This position is accepted as the best available evidence of the original cor. position.										
	At the corner point										
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T42N</td><td>R74W</td></tr> <tr><td>S 28</td><td> S 27</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 33</td><td> S 34</td></tr> <tr><td></td><td>1997</td></tr> </table>	T42N	R74W	S 28	S 27	<hr/>		S 33	S 34		1997
T42N	R74W										
S 28	S 27										
<hr/>											
S 33	S 34										
	1997										
	Set a steel fence post alongside the iron post.										

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89° 40' W., bet. secs. 27 and 34.</p> <p>Over rolling terrain.</p>
40.06	<p>The 1/4 sec. cor. of secs. 27 and 34, at intersection of fence extending N. and S. and abandoned fence extending W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T42N R74W</p> <p>S 27</p> <p>1/4 ———</p> <p>S 34</p> <p>1997</p> </div> <p>Cor. is located 1.55 chs. S. of intersection of fences extending E. and S. and abandoned fence extending N.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 28' W., beginning new measurement.</p> <p>Over rolling terrain, along abandoned fence.</p>
36.00	Bates Creek, 15 lks. wide, course SW.
39.94	The cor. of secs. 27, 28, 33 and 34.
2.00	<p>N. 0° 18' E., bet. secs. 27 and 28.</p> <p>Over rolling terrain, along abandoned fence.</p>
40.25	<p>Bates Creek, 10 lks. wide, course ENE.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 28, determined latitudinally by proportionate measurement and longitudinally by abandoned fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T42N R74W 1/4 S 28 S 27 1997</p>
	<p>Set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 0° 01' E., beginning new measurement.</p> <p>Over rolling terrain, along dilapidated fence.</p>
20.70	<p>Ridge, bears SE. and NW.</p>
40.25	<p>Point for the cor. of secs. 21, 22, 27 and 28, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T42N R74W S 21 S 22 <hr style="width: 20%; margin: auto;"/> S 28 S 27 1997</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89° 33' W., bet. secs. 22 and 27.</p> <p>Over rolling to broken terrain.</p>
39.74	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T42N R74W S 22 1/4 ——— S 27 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS					
79.48	The cor. of secs. 21, 22, 27 and 28.				
	N. 0° 10' W., bet. secs. 21 and 22.				
	Over rolling to broken terrain, along fence.				
1.60	Abandoned fence, bears W.				
40.25	Point for the 1/4 sec. cor. of secs. 21 and 22, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.				
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.				
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T42N R74W</td></tr> <tr><td>1/4</td></tr> <tr><td>S 21 S 22</td></tr> <tr><td>1997</td></tr> </table>	T42N R74W	1/4	S 21 S 22	1997
T42N R74W					
1/4					
S 21 S 22					
1997					
	N. 0° 07' E., beginning new measurement.				
	Over rolling terrain, along fence.				
40.25	Point for the cor. of secs. 15, 16, 21 and 22, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.				
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.				
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T42N R74W</td></tr> <tr><td>S 16 S 15</td></tr> <tr><td>S 21 S 22</td></tr> <tr><td>1997</td></tr> </table>	T42N R74W	S 16 S 15	S 21 S 22	1997
T42N R74W					
S 16 S 15					
S 21 S 22					
1997					
	From the cor. of secs. 14, 15, 22 and 23.				
	S. 89° 33' W., bet. secs. 15 and 22.				
	Over rolling to broken terrain.				
15.00	North Bates Creek, course SSE.				

350

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
40.02	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R74W S 15 1/4 ——— S 22 1997</p> <p>Set a steel fence post alongside the iron post.</p>
80.04	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 0° 02' E., bet. secs. 15 and 16.</p> <p>Over rolling terrain, along fence.</p>
40.25	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R74W 1/4 S 16 S 15 1997</p> <hr/> <p>N. 0° 07' E., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p>
40.25	<p>The cor. of secs. 9, 10, 15 and 16, monumented by Edward C. Fry, Wyoming Professional Engineer and Land Surveyor No. 662, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 21 ins. in the ground, at cor. of fences extending E. and S., with aluminum cap inscribed CIVIL ENGR SER and mkd. 9 10 15 16 662, as filed in the Campbell County Clerk's Office. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS											
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T42N</td><td>R74W</td></tr> <tr><td>S 9</td><td> S 10</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 16</td><td> S 15</td></tr> <tr><td colspan="2">1997</td></tr> </table> </div> <p>Deposit the steel reinforcement rod inside the iron post.</p> <p>From this point, a position established by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, as filed in the Campbell County Clerk's Office, falls in cultivated field. Monumentation searched for and not found.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89° 50' W., bet. secs. 10 and 15.</p> <p>Over rolling terrain, along fence.</p>	T42N	R74W	S 9	S 10	<hr/>		S 16	S 15	1997	
T42N	R74W										
S 9	S 10										
<hr/>											
S 16	S 15										
1997											
38.86	<p>The 1/4 sec. cor. of secs. 10 and 15, at intersection of fences extending N., E. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T42N</td><td>R74W</td></tr> <tr><td>S 10</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 15</td><td></td></tr> <tr><td colspan="2">1997</td></tr> </table> </div> <p>From this point, a position established by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, bears S. 16° 22' W., 75 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. T42N R74W 1/4 10 15 LS2327 1979, as filed in the Campbell County Clerk's Office. This position is not utilized during the course of this resurvey.</p> <hr/> <p>S. 89° 55' W., beginning new measurement.</p>	T42N	R74W	S 10		1/4	—	S 15		1997	
T42N	R74W										
S 10											
1/4	—										
S 15											
1997											

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	<p>Over rolling terrain, along fence.</p>
21.80	Ridge, bears SE. and NW.
40.31	The cor. of secs. 9, 10, 15 and 16.
	<hr/> <p>N. 0° 27' E., bet. secs. 9 and 10.</p> <p>Over rolling terrain.</p>
19.90	Ridge, bears ENE. and WSW.
26.20	Wyoming State Highway No. 387, bears ENE. and WSW.
39.83	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R74W 1/4 S 9 S 10 1997</p>
	Set a steel fence post alongside the iron post.
62.10	Spur, slopes NW.
79.66	<p>The cor. of secs. 3, 4, 9 and 10, identical with unnumbered station of abandoned Reno-Salt Creek Road, extending E. and WNW., from which a right-of-way monument established by Jesse E. Spielman, Campbell County Surveyor, in 1924</p> <p style="padding-left: 40px;">A broken sandstone, 14x8x4 ins., base portion firmly set 2 ins. below the surface of the ground, upper portion lying loose nearby, dimly mkd. CR on a face, bears N. 8° 16' E., 50.5 lks. dist.</p> <p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

353

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS											
	<table border="1" style="margin: auto;"> <tr> <td colspan="2">T42N R74W</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> <tr> <td colspan="2" style="text-align: center;">1997</td> </tr> </table>	T42N R74W		S 4	S 3			S 9	S 10	1997	
T42N R74W											
S 4	S 3										
S 9	S 10										
1997											
	Bury upper portion of county road stone alongside base.										
	From this point, a position established by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, bears N. 64° 30' E., 4.1 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap inscribed ANC and mkd. T42N R74W 3 4 9 10 LS2327 1979, as filed in the Campbell County Clerk's Office. This position is not utilized during the course of this resurvey.										
	From this same point, a position established by Edward C. Fry, Wyoming Registered Land Surveyor No. 662, bears N. 81° 37' E., 10.8 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 7 ins. above the ground, with aluminum cap inscribed CIVIL ENGR SER and mkd. 3 4 9 10 663, and a steel fence post alongside, as filed in the Campbell County Clerk's Office. This position is not utilized during the course of this resurvey.										
	From the cor. of secs. 2, 3, 10 and 11.										
	WEST, bet. secs. 3 and 10.										
	Over rolling terrain, along abandoned Reno-Salt Creek Road.										
37.80	Ridge, bears SSE. and NNW.										
40.39	The 1/4 sec. cor. of secs. 3 and 10, reestablished by Jesse E. Spielman, Campbell County Surveyor, in 1924, and remonumented by Albert L. Forsyth, Wyoming Registered Land Surveyor No. 2327, with a steel reinforcement rod, 20 ins. long, 5/8 in. diam., firmly set 19 ins. in the ground, in center of abandoned Reno-Salt Creek Road, extending E. and W., with aluminum cap inscribed ANC and mkd. T42N R74W 3 10 LS2327 1979, as filed in the Campbell County Clerk's Office, from which a right-of-way monument established by Mr. Spielman										
	A sandstone, firmly set, projecting 7x5x5 ins. above the ground, plainly mkd. CR on S. face, bears NORTH, 50 lks. dist.										

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	<p>This position is accepted as a reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R74W S 3 1/4 ——— S 10 1997</p> <p>Deposit the steel reinforcement rod inside and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 57' W., beginning new measurement.</p> <p>Over rolling terrain, along abandoned Reno-Salt Creek Road.</p>
33.90	Ridge, bears N. and S.
40.37	The cor. of secs. 3, 4, 9 and 10.
	<hr/> <p>N. 0° 45' W., bet. secs. 3 and 4.</p> <p>Over rolling terrain.</p>
24.00	Belle Fourche River, 10 lks. wide, course E.
39.47	The 1/4 sec. cor. of secs. 3 and 4, at cor. of abandoned fences extending S., other direction(s) indeterminate. This position is accepted as the best available evidence of the original cor. position.
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R74W 1/4 S 4 S 3 1997</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 N., R. 74 W., sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set a steel fence post alongside the iron post.</p> <hr/> <p>N. 0° 55' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
40.21	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1992 field notes of the dependent resurvey, T. 43 N., R. 74 W.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 41 N., R. 74 W., executed concurrently under this same group.</p> <p>N. 0° 22' E., bet. secs. 32 and 33.</p> <p>Over rolling terrain, along fading fence scar.</p>
20.10	<p>Cor. of fences extending N. and SSW.; thence along fence.</p>
40.01	<p>The 1/4 sec. cor. of secs. 32 and 33, at intersection of fences extending N., E. and S. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T42N R74W 1/4 S 32 S 33 1997</p> </div> <hr/> <p>N. 0° 56' E., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p>
39.92	<p>Point for the cor. of secs. 28, 29, 32 and 33, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>