

Dependent Resurvey, Portion of the North Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.25	<p>Cor. is located 49 lks. N. of fence extending irregularly E. and W.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T48N R65W S 33 1/4 ——— S 4 T47N 1997</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, a position monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears N. 71° 48' E., 85.2 lks. dist., a steel reinforcement rod, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, with a small steel sign post lying alongside. This position was established using inappropriate methods and is not accepted as a careful and faithful reestablishment of the original cor. position.</p>
80.50	<p>Cor. is located 80 lks. N. of fence extending irregularly E. and W.</p> <p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T48N R65W S 32 S 33 ————— S 5 S 4 T47N 1997</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 1.68 chs. N. of fence extending irregularly E. and W.</p> <hr/>

Dependent Resurvey, Portion of the North Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>S. 88° 56' W., bet. secs. 5 and 32.</p> <p>Over gently rolling terrain.</p>
20.125	<p>Point for the E. 1/16 sec. cor. of secs. 5 and 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T48N R65W S 32 E1/16— S 5 T47N 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 2.35 chs. N. of fence extending irregularly E. and W.</p>
25.70	<p>Fence, bears N. and S.</p>
40.25	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T48N R65W S 32 1/4 — S 5 T47N 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, a position shown on water development application plats by E. W. Cowley, Wyoming Professional Engineer and Land Surveyor No. 263, in 1940, and by B. A. Howell, Wyoming Professional Engineer and Land Surveyor No. 194, in 1950, bears S. 76° 23' W., 5.63 chs. dist., a projected cor. of abandoned fences from the S. and W., with fence cor. post lying alongside. This position is not accepted as the best available evidence of the original cor. position.</p>

Dependent Resurvey, Portion of the North Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS										
80.50	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T48N R65W</p> <table style="margin: auto;"> <tr> <td>S 31</td> <td> </td> <td>S 32</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 6</td> <td> </td> <td>S 5</td> </tr> </table> <p>T47N 1997</p> </div> <p>Cor. is located 4.5 lks. N. of fence extending irregularly E. and W.</p> <hr/> <p>S. 88° 56' W., bet. secs. 6 and 31.</p> <p>Over rolling terrain.</p>	S 31		S 32				S 6		S 5
S 31		S 32								
S 6		S 5								
40.25	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T48N R65W</p> <table style="margin: auto;"> <tr> <td>S 31</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 6</td> <td></td> </tr> </table> <p>T47N 1997</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 46 lks. N. of fence extending irregularly E. and W.</p>	S 31		1/4	—	S 6				
S 31										
1/4	—									
S 6										
79.395	<p>The cor. of Tps. 47 and 48 N., Rs. 65 and 66 W., at projected intersection of abandoned fences from the N. and W. and existing E. and WSW., falls under gate. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>									

Dependent Resurvey, Portion of the North Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T48N R66W R65W S 36 S 31</p> <hr style="width: 50%; margin: auto;"/> <p>S 1 S 6 T47N 1997</p> </div>
	<hr/> <p>Dependent Resurvey, Portion of the Subdivisional Lines, T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming</p> <hr/>
	<p style="text-align: center;">(Restoring the survey executed by F. W. Weisshaar, Jr. in 1882)</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0° 10' E., bet. secs. 35 and 36.</p> <p>Over rolling terrain.</p>
40.28	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W 1/4 S 35 S 36 1997</p> </div>
80.56	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 25, 26, 35 and 36, at cor. of fences extending N. and E. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T47N</td><td>R65W</td></tr> <tr><td>S 26</td><td>S 25</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td colspan="2">1997</td></tr> </table> </div>	T47N	R65W	S 26	S 25	<hr/>		S 35	S 36	1997	
T47N	R65W										
S 26	S 25										
<hr/>											
S 35	S 36										
1997											
39.38	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 88° 50' W., bet. secs. 24 and 25.</p> <p>Over gently rolling terrain.</p> <p>The 1/4 sec. cor. of secs. 24 and 25, at intersection of abandoned fences extending N., E. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T47N</td><td>R65W</td></tr> <tr><td>S 24</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 25</td><td></td></tr> <tr><td colspan="2">1997</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 88° 34' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>	T47N	R65W	S 24		1/4	—	S 25		1997	
T47N	R65W										
S 24											
1/4	—										
S 25											
1997											
40.03	<p>The cor. of secs. 23, 24, 25 and 26, at intersection of abandoned fences extending E., S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R65W S 23 S 24 ----- S 26 S 25 1997</p>
	<p>Set a steel fence post alongside the iron post.</p> <hr/>
	<p>N. 0° 19' W., bet. secs. 23 and 24.</p>
	<p>Over gently rolling terrain.</p>
25.75	<p>Cor. of fences extending N. and SE.</p>
39.55	<p>Intersection of fences extending N., S. and W.</p>
40.46	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R65W 1/4 S 23 S 24 1997</p> <hr/>
	<p>N. 0° 14' E., beginning new measurement.</p>
	<p>Over nearly level terrain, along fence.</p>
20.23	<p>Point for the N. 1/16 sec. cor. of secs. 23 and 24.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T47N R65W N1/16 S 23 S 24 1997</p> <p>Cor. is located 1.8 lks. E. of fence extending N. and S.</p> <p>20.40 Intersection of fences extending N., E. and S.</p> <p>40.46 The cor. of secs. 13, 14, 23 and 24, at cor. of fences extending S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 14 S 13 ----- S 23 S 24 1997</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>S. 88° 59' W., bet. secs. 13 and 24.</p> <p>Over gently rolling terrain.</p> <p>39.90 The 1/4 sec. cor. of secs. 13 and 24, monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, with a steel reinforcement rod, 19 ins. long, 1/2 in. diam., firmly set 11 ins. in the ground, with a small steel sign post lying alongside. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 13 1/4 ——— S 24 1997</p>
--------	---

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Deposit the steel reinforcement rod inside and set a steel fence post alongside the iron post.</p> <hr/>
	<p>S. 89° 00' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
19.93	<p>The W. 1/16 sec. cor. Of secs. 13 and 24, monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, with a steel reinforcement rod, 1/2 in. diam., firmly set, projecting 7 ins. above the ground. This position is accepted as a careful and faithful determination of the cor. position.</p> <hr/>
	<p>S. 89° 00' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
19.93	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/>
	<p>N. 0° 12' W., bet. secs. 13 and 14.</p> <p>Over rolling terrain.</p>
18.90	<p>Ridge, bears SE. and NW.</p>
20.16	<p>The S. 1/16 sec. cor. of secs. 13 and 14, monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, with a steel reinforcement rod, 1/2 in. diam., firmly set, projecting 11 ins. above the ground, with a broken steel sign post lying alongside, on N. face of ridge extending SE. and NW. This position is accepted as a careful and faithful determination of the cor. position.</p> <hr/>
	<p>N. 0° 12' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
20.16	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, with a steel reinforcement rod, 18 ins. long, 1/2 in. diam., firmly set 9 ins. in the ground. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R65W 1/4 S 14 S 13 1997</p>
	<p>Deposit the steel reinforcement rod inside and set a steel fence post alongside the iron post.</p>
	<p style="text-align: center;">_____</p> <p>N. 0° 14' W., beginning new measurement.</p>
	<p>Over gently rolling terrain.</p>
20.17	<p>The N. 1/16 sec. cor. of secs. 13 and 14, monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, with a steel reinforcement rod, 1/2 in. diam., firmly set flush with the surface of the ground, with a steel sign post alongside. This position is accepted as a careful and faithful determination of the cor. position.</p>
	<p style="text-align: center;">_____</p> <p>N. 0° 14' W., beginning new measurement.</p>
	<p>Over gently rolling terrain.</p>
20.17	<p>The cor. of secs. 11, 12, 13 and 14, monumented by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, at cor. of fences extending N. and E., with brass cap mkd.</p>
	<p style="text-align: center;">T47N R65W S 11 S 12 ----- S 14 S 13 1967 L.S.450</p>
	<p>This position was filed at the Weston County Court House and is accepted as the best available evidence of the original cor. position.</p>
	<p style="text-align: center;">_____</p> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>S. 89° 03' W., bet. secs. 12 and 13.</p> <p>Over gently rolling terrain, along fence.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, determined longitudinally by proportionate measurement and latitudinally by fence extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R65W S 12 1/4 ——— S 13 1997</p> <hr style="width: 30%; margin: auto;"/>
	<p>S. 89° 04' W., beginning new measurement.</p> <p>Over gently rolling terrain, along fence.</p>
40.17	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr style="width: 100%;"/>
	<p>N. 0° 36' E., bet. secs. 11 and 12.</p> <p>Over gently rolling terrain, gradually leaving fence.</p>
20.57	<p>The S. 1/16 sec. cor. of secs. 11 and 12, monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, with a steel reinforcement rod, 18 ins. long, 1/2 in. diam., firmly set 10 ins. in the ground. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R65W S 1/16 S 11 S 12 1997</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Deposit the steel reinforcement rod inside and set a steel fence post alongside the iron post.</p> <p>Cor. is located N. 6½° E., 2.02 chs. dist., from intersection of fences extending N., S. and W., and S. 24¼° E., 56.1 lks. dist., from cor. of fences, currently under construction, extending E. and S.</p> <hr/> <p>N. 0° 36' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
20.57	<p>True point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate measurement, falls in bentonite reclaim reservoir where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.</p>
21.57	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T47N R65W 1/4 S 11 S 12 1997</p> </div>
59.25	<p>Set a steel fence post alongside the iron post.</p> <p>The witness cor. to the cor. of secs. 1, 2, 11 and 12, established by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, encircled by a vehicle tire, with an iron pipe alongside projecting 36 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC 162.5 S T47N S 2 S 1 ----- S 11 S 12 R65W 1967 L.S.450</p> </div>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
61.71	<p>True point for the cor. of secs. 1, 2, 11 and 12, determined by projecting the line bet. secs. 11 and 12, through the Price witness cor., at his record dist., falls in bentonite reclaim reservoir, where it is impracticable to establish a permanent monument. This method or restoration was determined to be the most applicable, was filed in the Weston County Court House and is accepted as a careful and faithful reestablishment of the original corner position.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp. S. 88° 08' W., bet. secs. 1 and 12.</p> <p>Over gently rolling terrain, through scattered timber.</p>
1.00	<p>Double line railroad tracks, bear ESE. and WNW.</p>
40.015	<p>The 1/4 sec. cor. of secs. 1 and 12, monumented by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, 1.5 lks. N. of intersection of fences extending N., S. and irregularly E., with brass cap mkd.</p> <p style="text-align: center;">1/4 S 1 — S 12 1967 L.S.450</p> <p>This position was filed at the Weston County Court House and is accepted as the best available evidence of the original cor. position.</p> <hr/> <p>N. 87° 40' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
39.945	<p>True point for the cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 3° 48' E., bet. secs. 1 and 2.</p> <p>Over nearly level terrain.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
41.26	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, at cor. of fences extending E. and S., with an iron pipe alongside projecting 48 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 2 S 1 1967 L.S.450</p> <p>This position was filed at the Weston County Court House and is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 3° 48' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
20.04	<p>A monument established by Gary L. Davis, Wyoming Registered Land Surveyor No. 2079, a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground. This position was not utilized during the course of this resurvey.</p>
20.60	<p>A monument for the N. 1/16 sec. cor. of secs. 1 and 2, established by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, a steel reinforcement rod, 18 ins. long, 5/8 in. diam., with aluminum cap mkd. N1/16 1 2 T47N R65W LS450, was found lying loose on the surface of the ground. Nevertheless, this position is accepted as a careful and faithful determination of the cor. position.</p>
23.70	<p>Double line railroad tracks, bears SE. and NW.</p>
41.10	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.</p> <p>N. 1° 04' E., bet. secs. 34 and 35.</p> <p>Over rolling terrain, gradually converging with Upton-Fairview Road extending N. and S.</p>
40.345	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R65W 1/4 S 34 S 35 1997</p>
	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 19.7 lks. W. of western right-of-way fence extending N. and S.</p>
80.69	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance, there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. below the surface of the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R65W S 27 S 26 ----- S 34 S 35 1997</p>
	<p>Cor. is located in W. ditch of Upton-Fairview Road, 30 lks. E. of western right-of-way fence extending N. and S.</p>
	<hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p>
	<p>S. 88° 58' W., bet. secs. 26 and 35.</p>
	<p>Over gently rolling terrain, along increasing evidence of abandoned fence.</p>
39.44	<p>The 1/4 sec. cor. of secs. 26 and 35, at projected intersection of abandoned fences from the N., E. and W. This position is accepted as the best available evidence of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T47N R65W S 26 1/4 ——— S 35 1997</p> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 45' W., beginning new measurement.</p> <p>Over gently rolling terrain, along fading abandoned fence.</p>
40.06	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/>
	<p>N. 0° 17' E., bet. secs. 26 and 27.</p> <p>Over gently rolling terrain, along Upton-Fairview Road right-of-way.</p>
40.34	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance, falls in center line of Upton-Fairview Road extending N. and S; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R65W 1/4 S 27 S 26 1997</p>
	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 42½° E., 103.0 lks. dist., with brass cap mkd. RM T47N R65W S26 68.0 FT. TO COR. 1997 and an arrow pointing to the cor.</p>
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 40¾° W., 85.4 lks. dist., with brass cap mkd. RM T47N R65W S27 56.4 FT. TO COR. 1997 and an arrow pointing to the cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS											
80.68	<p>Point for the cor. of secs. 22, 23, 26 and 27, determined longitudinally by proportionate measurement and latitudinally by projection of fence from the E.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. below the surface of the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T47N R65W</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td colspan="2">-----</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td colspan="2">1997</td> </tr> </table> </div> <p>Cor. is located in E. ditch of Upton-Fairview Road, 42 lks. W. of eastern right-of-way fence extending N. and S.</p>	T47N R65W		S 22	S 23	-----		S 27	S 26	1997	
T47N R65W											
S 22	S 23										

S 27	S 26										
1997											
	<hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89° 51' W., bet. secs. 23 and 26.</p> <p>Over gently rolling terrain, along abandoned fence.</p>										
2.70	<p>Creek, drains SW. On W. bank of creek is intersection of fences extending SE., W. and abandoned E.</p>										
39.97	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T47N R65W</td> </tr> <tr> <td colspan="2">S 23</td> </tr> <tr> <td>1/4</td> <td>-----</td> </tr> <tr> <td colspan="2">S 26</td> </tr> <tr> <td colspan="2">1997</td> </tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located in projections of fences from the E. and W.</p>	T47N R65W		S 23		1/4	-----	S 26		1997	
T47N R65W											
S 23											
1/4	-----										
S 26											
1997											
79.94	<hr/> <p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0° 05' E., bet. secs. 22 and 23.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.08	<p>Over rolling terrain, along Upton-Fairview Road right-of-way.</p> <p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W 1/4 S 22 S 23 1997</p> <p>Cor. is located in E. ditch of Upton-Fairview Road, 11 lks. W. of eastern right-of-way fence extending N. and S.; thence gradually leave road right-of-way.</p>
60.12	<p>Point for the N. 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W N1/16 S 22 S 23 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located N. 25° E., 41.7 lks. dist., from intersection of fences extending E., S. and W.</p>
80.16	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 15 S 14 ----- S 22 S 23 1997</p> <p>Set a steel fence post alongside the iron post.</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89° 18' W., bet. secs. 14 and 23.</p> <p>Over nearly level terrain, gradually leaving fence.</p> <p>19.93 Point for the E. 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 14 E1/16 ——— S 23 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, a monument established by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears N. 10° 29' W., 40.7 lks. dist., a steel reinforcement rod, 3/8 in. diam., firmly set, projecting 5 ins. above the ground. This position was established using inappropriate methods and is not accepted as a careful and faithful determination of the cor. position.</p> <p>Cor. is located S. 71½° W., 1.09 chs. dist., from cor. of fences extending N. and E.</p>
39.86	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 14 1/4 ——— S 23 1997</p> <p>Set a steel fence post alongside the iron post.</p>
59.79	<p>Point for the W. 1/16 sec. cor. of secs. 14 and 23.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	<p style="text-align: center;">T47N R65W S 14 W1/16 ——— S 23 1997</p>
	Set a steel fence post alongside the iron post.
60.20	Fence, bears N. and S.
79.72	The cor. of secs. 14, 15, 22 and 23.
	<hr/> N. 0° 57' W., bet. secs. 14 and 15.
	Over gently rolling terrain.
19.83	Fence, bears E. and W.
20.045	Point for the S. 1/16 sec. cor. of secs. 14 and 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	<p style="text-align: center;">T47N R65W S1/16 S 15 S 14 1997</p>
40.09	The 1/4 sec. cor. of secs. 14 and 15, determined longitudinally at midpoint between the right-of-way fences of abandoned road extending N. and S. and latitudinally on the projection of fence from the E. This position is in agreement with a position shown on the plat of Sheldon and Soda Hole Road, surveyed in 1910 by John Berry, Weston County Surveyor, and realigned in 1929 by B. A. Howell, Weston County Surveyor, as filed in the Weston County Court House and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T47N R65W 1/4 S 15 S 14 1997</p>
	<p>Set a steel fence post alongside the an iron post.</p> <p>From this point, a U.S. Geological Survey benchmark monument bears S. 21° 27' W., 7.65 chs. dist., a concrete post, 7 ins. square, firmly set, projecting 10 ins. above the ground, with standard brass disk mkd. 4214.1 FEET ELEVATION ABOVE SEA 32ARD 1954.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 0° 39' E., beginning new measurement.</p> <p>Over rolling terrain, along abandoned roadbed, gradually converging with Upton-Fairview Road right-of-way.</p>
21.34	<p>From this point, an approximate position attributed to the offset for the N. 1/16 sec. cor. of secs. 14 and 15, established by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears EAST, 32.0 lks. dist., of which there is remaining only a small steel sign post with no evidence of a steel reinforcement rod found. Nevertheless, this position was established utilizing inappropriate control and inappropriate methods and is not accepted as a careful and faithful determination of the cor. position.</p>
40.075	<p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 10 S 11 <hr style="width: 20%; margin: 0 auto;"/> S 15 S 14 1997</p>
	<p>Cor. is located in E. ditch of Upton-Fairview Road.</p>