

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.80	<p>From this point, an approximate position attributed to the offset for the cor. of secs. 10, 11, 14 and 15, established by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears N. 29½° E., 1.46 chs. dist., of which there is remaining only two small steel sign posts, with no evidence of a steel reinforcement rod found, in jog of eastern right-of-way fence extending irregularly N. and S. Nevertheless, this position was established utilizing inappropriate control and is not accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 88° 56' W., bet. secs. 11 and 14.</p> <p>Over gently rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 11 1/4 ——— S 14 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>Evidence of abandoned fence extending E. and W. in vicinity, exact location indeterminate.</p>
79.60	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0° 23' E., bet. secs. 10 and 11.</p> <p>Over gently rolling terrain, gradually leaving Upton-Fairview Road right-of-way.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
21.04	<p>From this point, an offset position for the S. 1/16 sec. cor. of secs. 10 and 11, established by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears EAST, 6.0 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with unmkd. yellow plastic cap, with a small steel sign post alongside, in eastern right-of-way fence extending N. and S. This position was established utilizing inappropriate control and inappropriate methods and is not accepted as a careful and faithful determination of the cor. position.</p>
40.075	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W 1/4 S 10 S 11 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 10.5 lks. E. of eastern right-of-way fence extending N. and S.</p>
80.15	<p>Point for the cor. of secs. 2, 3, 10 and 11, determined longitudinally by proportionate distance and latitudinally utilizing distance based on field evidence of survey executed by George G. Ross, Wyoming Registered Land Surveyor No. 150; there is no remaining evidence of the original monument nor of Ross's monument. This method of restoration was determined to be the most applicable to reestablish the original cor. position.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 3 S 2 ----- S 10 S 11 1997</p> <p>Set a steel fence post, with survey marker sign attached, alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, a monument established by person(s) unknown, attributed to bentonite mining activity, bears S. 13° 32' W., 1.42 chs. dist., a steel reinforcement rod, 5/8 in. diam., firmly set projecting 2 ins. above the ground, with unmkd. yellow plastic cap, with a steel reinforcement rod, 3/8 in. diam., set flush alongside, with a wooden post, 4 ins. square, lying alongside with metal tag attached mkd. SEC. COR. 2 3 10 11 T47N R65W POST NO 304. This position is not accepted as the best available evidence of the original cor. position.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 83° 56' W., bet. secs. 2 and 11.</p> <p>Over nearly level terrain.</p>
40.12	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, with an iron post, 2½ ins. diam., firmly set, projecting 11 ins. above the ground, in a collar of stone, encircled with a vehicle tire, with a steel fence post alongside, in projection of abandoned fence from the N., with brass cap mkd.</p> <p style="text-align: center;">1/4 S 2 ----- S 11 1967 L.S.450</p> <p>This position was filed in the Weston County Court House and is accepted as the best available evidence of the original cor. position.</p>
	<p>N. 89° 05' W., beginning new measurement.</p> <p>Over nearly level terrain, through bentonite mining reclaim area.</p>
39.99	<p>The cor. of secs. 2, 3, 10 and 11.</p>
4.95	<p>N. 3° 08' E., bet. secs. 2 and 3.</p> <p>Over rolling terrain.</p> <p>Wyoming State Highway No. 116, bears NNE. and SSW.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
21.185	<p>The S. 1/16 sec. cor. of secs. 2 and 3, monumented by George G. Ross, Wyoming Registered Land Surveyor No. 150, with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd. PROP. COR. BCI LS 150, with a steel fence post and a wooden fence post set alongside. This position is accepted as a careful and faithful determination of the cor. position.</p> <hr/> <p>N. 3° 09' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
21.185	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented by George G. Ross, Wyoming Registered Land Surveyor No. 150, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd. PROP. COR. BCI LS 150, with a steel sign post alongside. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W 1/4 S 3 S 2 1997</p> <p>Deposit the steel reinforcement rod inside and set a steel fence post alongside the iron post.</p> <p>Cor. is located on W. edge of dirt bike riding course.</p> <hr/> <p>N. 3° 09' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
14.70	<p>Bentonite access road, on ridge, bears SE. and NW.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
21.20	<p>The N. 1/16 sec. cor. of secs. 2 and 3, monumented by George G. Ross, Wyoming Registered Land Surveyor No. 150, with a steel reinforcement rod, 5/8 in. diam., firmly set 6 ins. below the surface of the ground, with aluminum cap mkd. PROP. COR. BCI LS 150, with a steel fence post lying alongside, 7.5 lks. S. of wooden fence post. This position is accepted as a careful and faithful determination of the cor. position.</p> <hr/> <p>N. 3° 09' E., beginning new measurement.</p> <p>Descend over gently rolling terrain</p>
21.03	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.</p> <p>N. 3° 08' E., bet. secs. 33 and 34.</p> <p>Over rolling terrain.</p>
41.33	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with a sandstone, 9X9X3 ins., firmly set 7 ins. in the ground, upper portion badly weathered and crumbled, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W 1/4 S 33 S 34 1997</p> <p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p> <p>Cor. is located approximately 50 lks. E. of abandoned fence extending SSE. and NNW., exact location indeterminate.</p> <hr/> <p>N. 0° 01' E., beginning new measurement.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS											
	Over rolling terrain.										
20.30	Fence, bears E. and W.										
40.17	Point for the cor. of secs. 27, 28, 33 and 34, determined longitudinally by proportionate measurement and latitudinally by abandoned fence extending E. and W.; there is no remaining evidence of the original monument.										
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">T47N</td> <td style="padding: 2px;">R65W</td> </tr> <tr> <td style="padding: 2px;">S 28</td> <td style="padding: 2px;">S 27</td> </tr> <tr> <td style="padding: 2px;">S 33</td> <td style="padding: 2px;">S 34</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1997</td> </tr> </table>	T47N	R65W	S 28	S 27	S 33	S 34	1997			
T47N	R65W										
S 28	S 27										
S 33	S 34										
1997											
	Set a steel fence post alongside the iron post.										
	From the cor. of secs. 26, 27, 34 and 35.										
	N. 89° 52' W., bet. secs. 27 and 34.										
	Over rolling terrain.										
39.00	Draw, drains ESE.										
39.93	Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original cor.										
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">T47N</td> <td style="padding: 2px;">R65W</td> </tr> <tr> <td style="padding: 2px;">S 27</td> <td style="padding: 2px;">—</td> </tr> <tr> <td style="padding: 2px;">1/4</td> <td style="padding: 2px;">—</td> </tr> <tr> <td style="padding: 2px;">S 34</td> <td style="padding: 2px;">—</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1997</td> </tr> </table>	T47N	R65W	S 27	—	1/4	—	S 34	—	1997	
T47N	R65W										
S 27	—										
1/4	—										
S 34	—										
1997											
	Set a steel fence post alongside the iron post and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Evidence of abandoned fences extending S. and W. in vicinity of cor., exact location indeterminate. Evidence of abandoned fence extending W. gradually increases along line.</p>
79.86	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0° 10' E., bet. secs. 27 and 28.</p> <p>Over rolling terrain.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T47N R65W 1/4 S 28 S 27 1997</p> </div> <p>Set a steel fence post alongside the iron post.</p>
80.08	<p>The cor. of secs. 21, 22, 27 and 28, monumented by person(s) unknown, with an iron pipe, 24 ins. long, 2 ins. diam., firmly set 20 ins. in the ground, with a fragmented sandstone buried alongside. This position is attributed to the 1908 irrigation application survey of Gose's Desert and Reservoir, executed by C. E. Schenck, Weston County Surveyor, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T47N R65W S 21 S 22 <hr/>S 28 S 27 1997</p> </div> <p>Deposit the iron pipe inside, bury the sandstone fragments and set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Cor. is located S. 3° W., 2.00 chs. dist., from cor. of abandoned fences extending SE. and W.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p>
	<p>S. 89° 43' W., bet. secs. 22 and 27.</p>
	<p>Over nearly level terrain.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R65W S 22 1/4 ——— S 27 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
80.02	<p>The cor. of secs. 21, 22, 27 and 28.</p>
	<p>N. 0° 20' E., bet. secs. 21 and 22.</p>
	<p>Over nearly level terrain.</p>
39.905	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R65W 1/4 S 21 S 22 1997</p>
	<p>Set a steel fence post alongside the iron post.</p>
40.14	<p>South Branch Beaver Creek, course ESE.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS											
79.81	<p>The cor. of secs. 15, 16, 21 and 22, monumented by person(s) unknown, with an iron pipe, 19 ins. long, 2 ins. diam., firmly set 15 ins. in the ground, at intersection of fences extending N., W. and abandoned E. This position is attributed to the 1908 irrigation application survey of Gose's Desert and Reservoir, executed by C. E. Schenck, Weston County Surveyor, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T47N</td> <td>R65W</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1997</td> </tr> </table> <p>Deposit the iron pipe inside the iron post.</p>	T47N	R65W	S 16	S 15			S 21	S 22	1997	
T47N	R65W										
S 16	S 15										
S 21	S 22										
1997											
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89° 27' W., bet. secs. 15 and 22.</p> <p>Over gently rolling terrain.</p>										
10.00	Weston County Road No. 59, bears N. and S. on a curve.										
19.50	Lonetree Creek, course S.										
19.915	<p>Point for the E. 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T47N</td> <td>R65W</td> </tr> <tr> <td>S 15</td> <td>—</td> </tr> <tr> <td>E1/16</td> <td>—</td> </tr> <tr> <td>S 22</td> <td>—</td> </tr> <tr> <td colspan="2" style="text-align: center;">1997</td> </tr> </table>	T47N	R65W	S 15	—	E1/16	—	S 22	—	1997	
T47N	R65W										
S 15	—										
E1/16	—										
S 22	—										
1997											
	Set a steel fence post alongside the iron post.										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.83	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 15 1/4 — S 22 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 1.80 chs. N. of fence extending ESE. and WNW.</p>
79.66	<p>The cor. of secs. 15, 16, 21 and 22.</p>
40.08	<p>N. 1° 13' W., bet. secs. 15 and 16.</p> <p>Over rolling terrain, along fence.</p> <p>The 1/4 sec. cor. of secs. 15 and 16, at intersection of fences extending N., E. and S. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W 1/4 S 16 S 15 1997</p>
40.46	<p>N. 0° 29' E., beginning new measurement.</p> <p>Over gently rolling terrain, along fence.</p> <p>The cor. of secs. 9, 10, 15 and 16, at intersection of fences extending N., E. and S., on E. side of livestock corral. This position is accepted as the best available evidence of the original cor. position.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T47N R65W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black; text-align: center;">1997</td> </tr> </table> </div> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89° 36' W., bet. secs. 10 and 15.</p> <p>Over rolling terrain, along gradually increasing evidence of abandoned fence.</p> <p>39.97 The 1/4 sec. cor. of secs. 10 and 15, at old cor. post of abandoned fences extending N. and E. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T47N R65W</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 10</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4 ———</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 15</td> </tr> <tr> <td colspan="2" style="text-align: center;">1997</td> </tr> </table> </div> <p>Cor. is located 14 lks. S. of existing fence extending E. and W.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>S. 89° 00' W., beginning new measurement.</p> <p>Over gently rolling terrain, gradually converging with fence.</p> <p>4.90 Beaver Creek, course S.</p> <p>39.97 The cor. of secs. 9, 10, 15 and 16.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0° 28' E., bet. secs. 9 and 10.</p>	T47N R65W		S 9	S 10	1997		T47N R65W		S 10		1/4 ———		S 15		1997	
T47N R65W																	
S 9	S 10																
1997																	
T47N R65W																	
S 10																	
1/4 ———																	
S 15																	
1997																	

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over gently rolling terrain, along fence.
19.91	Approximate position for the S. 1/16 sec. cor. of secs. 9 and 10, utilized by Theodore J. Vore, Wyoming Professional Engineer No. 1088, was searched for, not found. Nevertheless, this position was established utilizing inappropriate control and is not accepted as a careful and faithful determination of the cor. position.
33.00	Wyoming State Highway No. 116, bears NE. and SW.
39.35	Beaver Creek, course ESE.
40.29	The 1/4 sec. cor. of secs. 9 and 10, at projected cor. of fences from the S. and W. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	<p style="text-align: center;">T47N R65W 1/4 S 9 S 10 1997</p>
	Set a steel fence post alongside the iron post.
	<hr style="width: 20%; margin: auto;"/>
	N. 0° 28' E., beginning new measurement.
	Over rolling terrain.
0.15	Beaver Creek, course WSW.
2.65	Beaver Creek, course SSE.
19.47	From this point, a position for the N. 1/16 sec. cor. of secs. 9 and 10, established by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears EAST, 1.7 lks. dist., monumented with a steel reinforcement rod, 1/2 in. diam., firmly set, projecting 4 ins. above the ground, with a steel sign post and a wooden post, 4 ins. square, lying alongside. This position was established utilizing inappropriate control to the S. and is not accepted as a careful and faithful determination of the cor. position.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS											
39.385	<p>The cor. of secs. 3, 4, 9 and 10, monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, with a steel reinforcement rod, 3/8 in. diam., firmly set, projecting 10 ins. above the ground, with wooden post, 4 ins. square, alongside, with evidence of abandoned fence(s) in vicinity, exact location indeterminate. This position has been locally accepted as the cor. position and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T47N R65W</td> </tr> <tr> <td style="text-align: center;">S 4</td> <td style="text-align: center;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 9</td> <td style="text-align: center;">S 10</td> </tr> <tr> <td colspan="2" style="text-align: center;">1997</td> </tr> </table> <p>Deposit the steel reinforcement rod inside the iron post.</p> <hr/>	T47N R65W		S 4	S 3	-----		S 9	S 10	1997	
T47N R65W											
S 4	S 3										

S 9	S 10										
1997											
2.58	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89° 23' W., bet. secs. 3 and 10.</p> <p>Over nearly level terrain.</p>										
11.50	<p>Wyoming State Highway No. 116, bears N. 30° E. and S. 30° W.</p> <p>Coyote Creek, course SE.</p>										
19.95	<p>Point for the E. 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T47N R65W</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 3</td> </tr> <tr> <td style="text-align: center;">E1/16</td> <td style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 10</td> </tr> <tr> <td colspan="2" style="text-align: center;">1997</td> </tr> </table> <p>Set a steel fence post alongside the iron post.</p>	T47N R65W		S 3		E1/16	-----	S 10		1997	
T47N R65W											
S 3											
E1/16	-----										
S 10											
1997											

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, a monument set by person(s) unknown, attributed to power line surveys, bears S. 15° 58' W., 1.07 chs. dist., a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. BHP&L 1062, with a wooden post, 4 ins. square, lying alongside, with metal tag attached mkd. POST 313 GOVT LEASE. This position was established utilizing inappropriate control and is not accepted as a careful and faithful determination of the cor. position.</p>
36.70	Power line, bears SE. and NW.
39.90	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 3 1/4 — S 10 1997</p>
	Set a steel fence post alongside the iron post.
45.00	Fence, bears SE. and NW.
59.85	<p>Point for the W. 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 3 W1/16 — S 10 1997</p>
	<p>Set a steel fence post alongside the iron post.</p> <p>From this point, a monument established by person(s) unknown, attributed to bentonite mining activity, bears S. 14° 38' W., 35.6 lks. dist., a steel reinforcement rod, 1/2 in. diam., firmly set, projecting 12 ins. above the ground, with a wooden fence post, 4 ins. square, set alongside. This position was established using inappropriate control and is not accepted as a careful and faithful determination of the cor. position.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
79.80	The cor. of secs. 3, 4, 9 and 10.
	<hr/> <p>N. 2° 42' E., bet. secs. 3 and 4.</p> <p>Over gently rolling terrain.</p>
21.01	<p>From this point, a position for the S. 1/16 sec. cor. of secs. 3 and 4, established by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears EAST, 13.5 lks. dist., monumented with a steel reinforcement rod, 1/2 in. diam., firmly set, projecting 4 ins. above the ground, with wooden post, 4 ins. square, and a broken steel fence post lying alongside. This position was established using inappropriate methods and inappropriate control and is not accepted as a careful and faithful determination of the cor. position.</p>
42.08	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W 1/4 S 4 S 3 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, a position monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears S. 85° 02' E., 22.7 lks. dist., a steel reinforcement rod, 1/2 in. diam., firmly set, projecting 8 ins. above the ground, with wooden post, 4 ins. square, and a broken steel fence post lying alongside. This position was established using inappropriate methods and inappropriate control and is not accepted as a careful and faithful reestablishment of the original cor. position.</p>
56.25	Fence, bears SE. and NW.
63.12	<p>Point for the N. 1/16 sec. cor. of secs. 3 and 4.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
83.96	<p style="text-align: center;">T47N R65W N1/16 S 4 S 3 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, a position monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears S. 87° 19' E., 36.4 lks. dist., a steel reinforcement rod, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, with wooden post, 4 ins. square, and a broken steel fence post lying alongside. This position was established using inappropriate methods and inappropriate control and is not accepted as a careful and faithful determination of the cor. position.</p> <p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.</p>
40.61	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.</p> <p>N. 2° 18' E., bet. secs. 32 and 33.</p> <p>Over gently rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
81.22	<p style="text-align: center;">T47N R65W 1/4 S 32 S 33 1997</p> <p>Set a steel fence post alongside the iron post and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p> <p>The cor. of secs. 28, 29, 32 and 33, monumented with a sandstone, 12X8X3 ins., broken in two, lower portion firmly set flush with the surface of the ground, upper portion lying alongside, dimly mkd. 2 faint grooves on E. face, no other mks. visible.</p> <p>At the corner point</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T47N</td> <td style="padding: 0 5px;">R65W</td> </tr> <tr> <td style="padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 32</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 33</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1997</td> </tr> </table> </div> <p>Bury the original corner stone alongside and set a steel fence post alongside the iron post.</p> <p>From this point, the water well casing on windmill bears N. 54° 40' W., 2.87 chs. dist.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89° 10' W., bet. secs. 28 and 33.</p> <p>Over rolling terrain.</p> <p>39.93 The 1/4 sec. cor. of secs. 28 and 33, monumented with a sandstone, 14X11X3 ins., firmly set 11 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T47N</td> <td style="padding: 0 5px;">R65W</td> </tr> <tr> <td style="padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td style="padding: 0 5px;">S 33</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1997</td> </tr> </table> </div> <p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p> <p>From this point, the water well casing on windmill bears N. 75° 13' W., 14.96 chs. dist.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>S. 89° 15' W., beginning new measurement.</p>	T47N	R65W	S 29	S 28	S 32	S 33	1997		T47N	R65W	S 28	—	1/4	—	S 33	—	1997	
T47N	R65W																		
S 29	S 28																		
S 32	S 33																		
1997																			
T47N	R65W																		
S 28	—																		
1/4	—																		
S 33	—																		
1997																			

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Over rolling terrain.</p>
19.20	<p>Fence, bears N. and S.</p>
40.08	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0° 32' E., bet. secs. 28 and 29.</p> <p>Over gently rolling terrain.</p>
40.08	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with a broken sandstone, 12X6X3 ins., loosely set 8 ins. in the ground, no mks. visible, at cor. of fences extending E. and WNW. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T47N R65W 1/4 S 29 S 28 1997</p> </div> <p>Cor. is located S. 73¼° E., 2.32 chs. dist., from intersection of more recently constructed fences extending N., ESE. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 31' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
40.26	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T47N R65W S 20 S 21 <hr style="width: 50%; margin: 0 auto;"/>S 29 S 28 1997</p> </div>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 11 lks. E. of projection of abandoned fence from the S., on E. edge of trail road on ridge extending N. and S.</p> <hr/>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89° 41' W., bet. secs. 21 and 28.</p> <p>Over rolling terrain.</p>
39.82	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a sandstone, 24X20X3 ins., firmly set 10 ins. in the ground, no mks. visible. This position is depicted on the 1908 irrigation application survey of Gose's Desert and Reservoir, executed by C. E. Schenck, Weston County Surveyor, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>S 21</p> <p>1/4 ———</p> <p>S 28</p> <p>1997</p> </div>
	<p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p> <p>From this point, a position established by person(s) unknown for unknown purposes, bears N. 63° 18' W., 8.85 chs. dist., an iron pipe, 2½ ins. diam., firmly set, projecting 16 ins. above the ground. This position was not utilized during the course of this resurvey.</p> <hr/>
	<p>S. 89° 06' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
39.66	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 0° 29' E., bet. secs. 20 and 21.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.26	<p>Over rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W 1/4 S 20 S 21 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, a monument established by person(s) unknown, bears S. 4° 35' E., 2.65 chs. dist., an iron pipe, 2½ ins. diam., firmly set, projecting 24 ins. above the ground, at cor. of fences extending E. and S. This position is not accepted as the best available evidence of the original cor. position.</p>
80.52	<p>Point for the cor. of secs. 16, 17, 20 and 21, determined longitudinally by proportionate measurement and latitudinally by fence extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W S 17 S 16 ----- S 20 S 21 1997</p> <p>Cor. is located in projection of fence from the N.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89° 52' W., bet. secs. 16 and 21.</p> <p>Over gently rolling terrain, along fence.</p>