

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

219

FIELD NOTES

OF THE
DEPENDENT RESURVEY
OF THE
THE SUBDIVISIONAL LINES,
TOWNSHIP 50 NORTH, RANGE 74 WEST,
OF THE SIXTH PRINCIPAL MERIDIAN,
IN THE STATE OF WYOMING.

EXECUTED BY

JOEL T. EBNER

CADASTRAL SURVEYOR

Under Special Instructions dated MARCH 24, 1997, approved MARCH 28, 1997, which provided for the surveys included under Group Number 634, and assignment instructions dated MARCH 28, 1997.

Survey commenced JULY 13, 1998

Survey completed JUNE 28, 1999

INDEX DIAGRAM

220

Township 50 North, Range 74 West

6	44 5	34 4	27 3	18 2	9 1
43	43	34	26	17	8
7	42 8	33 9	25 10	16 11	7 12
42	41	33	24	16	7
18	40 17	31 16	23 15	15 14	6 13
40	39	31	23	14	5
19	38 20	30 21	21 22	13 23	4 24
38	37	29	21	12	4
30	37 29	28 28	20 27	11 26	3 25
36	36	28	19	10	2
31	35 32	27 33	18 34	9 35	2 36

T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS

The following field notes are those of the dependent resurvey of the subdivisional lines, Township 50 North, Range 74 West, Sixth Principal Meridian, Wyoming.

Louis F. Stahle surveyed the exterior boundaries and the subdivisional lines in 1883. James D. Claflin dependently resurveyed the west boundary in 1986-87. Michael E. Whitmore dependently resurveyed the east boundary in 1990-91. Matthew J. Kurchinski and James D. Claflin dependently resurveyed the north boundary in 1998. The south boundary was dependently resurveyed by Joel T. Ebner during the dependent resurvey of T. 49 N., R. 74 W., executed concurrently under this same group.

Numerous local surveys have been executed by private surveyors throughout the area.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 634, Wyoming, dated March 24, 1997.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data were thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

The survey was executed with a Global Positioning System (GPS) TRIMBLE Model 4700 receivers, WILD Model T1000 theodolite, WILD Model DI5S electronic distance meter and by chaining methods. The instruments were maintained in proper adjustment at all times. The directions of all lines refer to the true meridian, determined by hour angle observations of the sun at various points along the lines of survey and carried forward by sustained angulation, and by GPS observations.

The geographic position of the southeast corner of the township, based on NAD 27 and determined by Global Positioning System methods is:

Latitude 44° 15' 34.19" N., Longitude 105° 41' 32.01" W.

The mean magnetic declination is 11¼° E.

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">(Restoring the survey executed by Louis F. Stahle in 1883)</p> <hr/> <p>Beginning at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 49 N., R. 74 W., executed concurrently under this same group.</p> <p>N. 0° 04' E., bet. secs. 35 and 36.</p> <p>Over rolling terrain.</p> <p>41.39 Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W 1/4 S 35 S 36 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>82.78 The cor. of secs. 25, 26, 35 and 36, remonumented by Daniel A. Siek, Wyoming Registered Land Surveyor No. 2097, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with a steel fence post alongside, with aluminum cap inscribed SIEK SURVEYING R.L.S. 2097 and mkd.</p> <p style="text-align: center;">T50N R74W S 26 S 25 <hr/>S 35 S 36 1985</p> <p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1990-91 field notes of the dependent resurvey, T. 50 N., R. 73 W.</p> <p>S. 89° 48' W., bet. secs. 25 and 36.</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	Over rolling terrain.
32.40	East Fork Wild Horse Creek, course NW.
42.07	The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, remonumented by Daniel A. Siek, Wyoming Registered Land Surveyor No. 2097, with an aluminum post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above the ground, with a steel fence post alongside, with aluminum cap inscribed SIEK SURVEYING R.L.S. 2097 and mkd.
	T50N R74W S 25 1/4 ——— S 36 1985
	This position is accepted as a careful and faithful perpetuation of the original cor. position.
	—————
	N. 89° 29' W., beginning new measurement.
	Over rolling terrain.
35.30	Wash, drains NW.
40.27	The cor. of secs. 25, 26, 35 and 36.
	—————
	N. 2° 26' E., bet. secs. 25 and 26.
	Over gently rolling terrain.
40.49	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T50N R74W 1/4 S 26 S 25 1999
	Set a steel fence post alongside the iron post.
42.40	Wash, drains NE.
52.60	East Fork Wild Horse Creek, course NNW.

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS						
58.80	Montgomery Road, bears E. and W.					
80.98	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td>T50N R74W</td></tr> <tr><td>S 23 S 24</td></tr> <tr><td>— —</td></tr> <tr><td>S 26 S 25</td></tr> <tr><td>1999</td></tr> </table> </div> Set a steel fence post alongside the iron post.	T50N R74W	S 23 S 24	— —	S 26 S 25	1999
T50N R74W						
S 23 S 24						
— —						
S 26 S 25						
1999						
	<hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1990-91 field notes of the dependent resurvey, T. 50 N., R. 73 W.</p> <p>N. 89° 55' W., bet. secs. 24 and 25.</p> <p>Over rolling terrain.</p>					
40.33	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td>T50N R74W</td></tr> <tr><td>S 24</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S 25</td></tr> <tr><td>1999</td></tr> </table> </div> Set a steel fence post alongside the iron post.	T50N R74W	S 24	1/4 —	S 25	1999
T50N R74W						
S 24						
1/4 —						
S 25						
1999						
75.80	Creek, course SW.					
80.66	The cor. of secs. 23, 24, 25 and 26. <hr/> <p>N. 1° 46' E., bet. secs. 23 and 24.</p> <p>Over rolling terrain.</p>					

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.49	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W 1/4 S 23 S 24 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on steep S. facing slope.</p>
79.90	Wash, drains NW.
80.98	<p>The cor. of secs. 13, 14, 23 and 24, monumented with an embedded mound of stone, 3 ft. base, no mkd. stone found. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W S 14 S 13 ----- S 23 S 24 1999</p> <p>Set a steel fence post alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., as described in the 1990-91 field notes of the dependent resurvey, T. 50 N., R. 73 W.</p> <p>S. $89^{\circ} 42'$ W., bet. secs. 13 and 24.</p> <p>Over rolling terrain.</p>
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W S 13 1/4 ——— S 24 1999</p> <p>Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located 31 lks. N. of fence extending irregularly E. and W.</p>
79.98	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/>
	<p>N. 0° 04' W., bet. secs. 13 and 14.</p> <p>Over rolling and broken terrain.</p>
39.535	<p>Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W 1/4 S 14 S 13 1999</p> <p>Set a steel fence post alongside the iron post.</p>
60.07	<p>From this point, intersection of fences extending N., SSE. and W., bears EAST, 88 lks. dist.</p>
79.07	<p>The cor. of secs. 11, 12, 13 and 14, at intersection of fences extending N. and S. with abandoned fence extending E. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

307

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<div style="text-align: center;"> <p>T50N R74W S 11 S 12 <hr style="width: 50%; margin: 0 auto;"/>S 14 S 13 1999</p> </div> <p>From this point, a position established by Richard T. Doyle, Wyoming Registered Land Surveyor No. 2333, bears N. 89° 35' E., 3.06 chs. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with plastic cap mkd. RLS 2333, as filed in the Campbell County Clerk's Office. Mr. Doyle remonumented an unmarked fragmented stone, at the location of tie down wires in an abandoned E-W fence, ignoring the remaining evidence of the fence intersection, which more closely matches the original record to surrounding corners. Therefore, this position is not accepted as a careful and faithful perpetuation of the original corner.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1990-91 field notes of the dependent resurvey, T. 50 N., R. 73 W.</p> <p>S. 88° 43' W., bet. secs. 12 and 13.</p> <p>Over rolling terrain.</p> <p>39.76 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T50N R74W S 12 1/4 ——— S 13 1999</p> </div> <p>Set a steel fence post alongside the iron post and raise a mound raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>79.52 The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 1° 55' W., bet. secs. 11 and 12.</p> <p>Over rolling terrain.</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
38.60	Echeta Road, bears E. and W.
40.385	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T50N R74W $\frac{1}{4}$ S 11 S 12 1999 </div> Set a steel fence post alongside the iron post. Cor. is located 25 lks. W. of fence extending irregularly N. and S.
62.20	Fence, bears E. and W.
80.77	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T50N R74W S 2 S 1 <hr style="width: 50%; margin: 0 auto;"/> S 11 S 12 1999 </div> Set a steel fence post alongside the iron post.
	<hr/> From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., as described in the 1990-91 field notes of the dependent resurvey, T. 50 N., R. 73 W. S. $88^{\circ} 21'$ W., bet. secs. 1 and 12. Over rolling terrain.
29.50	Hay Creek, course NW.
34.50	Burlington Northern Santa Fe Railway, bears SE. and NW.

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.78	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W S 1 1/4 ——— S 12 1999</p> <p>Set a steel fence post alongside the iron post.</p>
81.56	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. $0^{\circ} 17'$ E., bet. secs. 1 and 2.</p> <p>Over rolling terrain.</p>
40.36	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W 1/4 S 2 S 1 1999</p> <p>Set a steel fence post alongside the iron post.</p>
59.60	Hay Creek, course NW.
64.60	Burlington Northern Santa Fe Railway, bears SE. and NW.
80.87	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., as described in the 1998 field notes of the dependent resurvey, T. 51 N., R. 74 W.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., as described in the field notes of the dependent resurvey, T. 49 N., R. 74 W., executed concurrently under this same group.</p> <p>N. $0^{\circ} 04'$ W., bet. secs. 34 and 35.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling terrain.
41.765	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T50N R74W
	1/4
	S 34 S 35
	1999
	Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
	Cor. is located 1.42 chs. E. of fence extending irregularly N. and S.
83.53	The cor. of secs. 26, 27, 34 and 35, monumented with a sandstone, 9x7x5 ins., firmly set 4 ins. in the ground, at intersection of fences extending N. and irregularly S. with abandoned fence extending W., no mks. visible. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T50N R74W
	S 27 S 26
	S 34 S 35
	1999
	Bury the unmkd. stone alongside the iron post.
	From the cor. of secs. 25, 26, 35 and 36.
	S. 89° 50' W., bet. secs. 26 and 35.
	Over gently rolling terrain.
36.90	Force Road, bears SE. and NW.
40.33	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W S 26 1/4 ——— S 35 1999</p> <p>Set a steel fence post alongside the iron post.</p>
80.66	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/>
	<p>N. 0° 12' W., bet. secs. 26 and 27.</p> <p>Over rolling terrain, along fence.</p>
37.14	<p>Cor. of fences extending S. and NW.</p>
40.55	<p>The ¼ sec. cor. of secs. 26 and 27, at projected cor. of fences from the S. and W. This position is accepted as the best available evidence of the original cor. position.</p>
	<p style="text-align: center;">T50N R74W 1/4 S 27 S 26 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located S. 88½° E., 3.30 chs. dist. from cor. of fences extending SE. and W.</p> <hr/>
	<p>N. 4° 42' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
19.50	<p>Montgomery Road, bears E. and W.</p>
40.01	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<div style="text-align: center;"> T50N R74W S 22 S 23 ----- S 27 S 26 1999 </div> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89° 30' W., bet. secs. 23 and 26.</p> <p>Over rolling terrain.</p>
26.80	East Fork Wild Horse Creek, course NE.
40.475	<p>Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T50N R74W S 23 1/4 ----- S 26 1999 </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 1.01 chs. S. of fence extending irregularly E. and W.</p>
60.712	<p>Point for the W. 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T50N R74W S 23 W1/16 ----- S 26 1999 </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located S. 65½° E., 3.66 chs. dist. from intersection of fences extending N., S. and irregularly E.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
80.95	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/>
	<p>N. 0° 46' E., bet. secs. 22 and 23.</p> <p>Over rolling terrain.</p>
39.88	<p>Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W 1/4 S 22 S 23 1999</p> <p>Set a steel fence post alongside the iron post.</p>
40.70	<p>East Fork Wild Horse Creek, course NNW.</p>
59.82	<p>Point for the N. 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W N1/16 S 22 S 23 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 1.40 chs. E. of fence extending N. and S.</p>
79.76	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an embedded mound of stone, 3 ft. base, with a steel fence post alongside, no mkd. stone found. This position has been filed with the Campbell County Clerk's Office, has been locally accepted and utilized for a number of years and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T50N R74W</td></tr> <tr><td>S 15 S 14</td></tr> <tr><td>-----</td></tr> <tr><td>S 22 S 23</td></tr> <tr><td>1999</td></tr> </table> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 1.92 chs. E. of fence extending N. and S.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 88° 41' W., bet. secs. 14 and 23.</p> <p>Over rolling terrain.</p>	T50N R74W	S 15 S 14	-----	S 22 S 23	1999
T50N R74W						
S 15 S 14						

S 22 S 23						
1999						
38.26	Fence, bears N. and S.					
41.19	<p>Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T50N R74W</td></tr> <tr><td>S 14</td></tr> <tr><td>1/4 -----</td></tr> <tr><td>S 23</td></tr> <tr><td>1999</td></tr> </table> <p>Set a steel fence post alongside the iron post.</p>	T50N R74W	S 14	1/4 -----	S 23	1999
T50N R74W						
S 14						
1/4 -----						
S 23						
1999						
61.785	<p>Point for the W. 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T50N R74W</td></tr> <tr><td>S 14</td></tr> <tr><td>W1/16 -----</td></tr> <tr><td>S 23</td></tr> <tr><td>1999</td></tr> </table> <p>Set a steel fence post alongside the iron post.</p>	T50N R74W	S 14	W1/16 -----	S 23	1999
T50N R74W						
S 14						
W1/16 -----						
S 23						
1999						
82.38	The cor. of secs. 14, 15, 22 and 23.					

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 3° 03' W., bet. secs. 14 and 15.</p>
	<p>Over rolling terrain.</p>
42.24	<p>The ¼ sec. cor. of secs. 14 and 15, monumented with a lava stone, 8x8x5 ins., embedded horizontally 4 ins. in the ground, plainly mkd. 1/4 on bottom face, with a lava stone, 11x8x6 ins., lying loose alongside, plainly mkd. 4 on bottom face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T50N R74W 1/4 S 15 S 14 1999</p>
	<p>Bury the original cor. stones and set a steel fence post alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>
	<p>From this point, a position established by Robert J. Timm, Wyoming Professional Engineer and Land Surveyor No. 2457, bears S. 52° 09' E., 1.40 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. T50N R74W 1/4 S15 S14 PELS 2457 1981, as filed in the Campbell County Clerk's Office. This position is not accepted as a careful and faithful reestablishment of the original cor.</p>
	<p>Cor. is located S. 18½° E., 32 lks. dist. from intersection of fences fence extending N., E. and S.</p>
	<hr style="width: 20%; margin: auto;"/>
	<p>N. 0° 05' W., beginning new measurement.</p>
	<p>Over rolling terrain.</p>
19.80	<p>From this point, a position established by Robert J. Timm, Wyoming Professional Engineer and Land Surveyor No. 2457, bears EAST, 55 lks. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. T50N R74W N1/16 S15 S14 PELS 2457 1981, as filed in the Campbell County Clerk's Office. This position was established by proportionate measurement from an erroneous position of controlling corner south and is not accepted as a careful and faithful determination of the cor. position.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS						
40.46	<p>The cor. of secs. 10, 11, 14 and 15, remonumented by Robert J. Timm, Wyoming Professional Engineer and Land Surveyor No. 2457, as filed in the Campbell County Clerk's Office, with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post and a sandstone, 12x8x3 ins., firmly set 5 ins. in the ground alongside, no mks. visible, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T50N R74W</td></tr> <tr><td>S 10 S 11</td></tr> <tr><td>S 15 S 14</td></tr> <tr><td>PELS 2457 1981</td></tr> </table> </div> <p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>Bury the unmkd. stone alongside the iron post.</p>	T50N R74W	S 10 S 11	S 15 S 14	PELS 2457 1981	
T50N R74W						
S 10 S 11						
S 15 S 14						
PELS 2457 1981						
	<hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 88° 52' W., bet. secs. 11 and 14.</p> <p>Over rolling terrain.</p>					
42.28	<p>Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T50N R74W</td></tr> <tr><td>S 11</td></tr> <tr><td>1/4 ———</td></tr> <tr><td>S 14</td></tr> <tr><td>1999</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p>	T50N R74W	S 11	1/4 ———	S 14	1999
T50N R74W						
S 11						
1/4 ———						
S 14						
1999						
84.56	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0° 17' E., bet. secs. 10 and 11.</p> <p>Over rolling terrain.</p>					

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.49	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W 1/4 S 10 S 11 1999</p> <p>Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>
80.98	<p>The cor. of secs. 2, 3, 10 and 11, monumented with an embedded mound of stone, 3 ft. base, 1 ft. high, no mkd. stone found. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W S 3 S 2 ----- S 10 S 11 1999</p> <p>Set a steel fence post alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>The monument established in 1988 by Richard T. Doyle, Wyoming Registered Land Surveyor No. 2333, as filed in the Campbell County Clerk's Office, was searched for and not found.</p>
40.725	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. $88^{\circ} 39'$ W., bet. secs. 2 and 11.</p> <p>Over rolling terrain.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T50N R74W S 2 1/4 ——— S 11 1999
	Set a steel fence post alongside the iron post.
76.30	Echeta Road, bears SSE. and NNW.
81.45	The cor. of secs. 2, 3, 10 and 11.
	N. 1° 12' E., bet. secs. 2 and 3. Over rolling terrain.
14.80	Echeta Road, bears SE. and NW.
39.06	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T50N R74W 1/4 S 3 S 2 1999
	Set a steel fence post alongside the iron post.
78.40	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1998 field notes of the dependent resurvey, T. 51 N., R. 74 W.
	From the true point for the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., witnessed by an aluminum post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 49 N., R. 74 W., executed concurrently under this same group. N. 0° 04' W., bet. secs. 33 and 34. Over rolling terrain.
40.16	Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.49	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W 1/4 S 10 S 11 1999</p> <p>Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>
80.98	<p>The cor. of secs. 2, 3, 10 and 11, monumented with an embedded mound of stone, 3 ft. base, 1 ft. high, no mkd. stone found. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T50N R74W S 3 S 2 ----- S 10 S 11 1999</p> <p>Set a steel fence post alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>The monument established in 1988 by Richard T. Doyle, Wyoming Registered Land Surveyor No. 2333, as filed in the Campbell County Clerk's Office, was searched for and not found.</p>
40.725	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. $88^{\circ} 39'$ W., bet. secs. 2 and 11.</p> <p>Over rolling terrain.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 50 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T50N R74W S 2 1/4 ——— S 11 1999
	Set a steel fence post alongside the iron post.
76.30	Echeta Road, bears SSE. and NNW.
81.45	The cor. of secs. 2, 3, 10 and 11.
	<hr/> N. 1° 12' E., bet. secs. 2 and 3. Over rolling terrain.
14.80	Echeta Road, bears SE. and NW.
39.06	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T50N R74W 1/4 S 3 S 2 1999
	Set a steel fence post alongside the iron post.
78.40	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1998 field notes of the dependent resurvey, T. 51 N., R. 74 W.
	<hr/> From the true point for the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., witnessed by an aluminum post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 49 N., R. 74 W., executed concurrently under this same group. N. 0° 04' W., bet. secs. 33 and 34. Over rolling terrain.
40.16	Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.