

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.51	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W S 9 1/4 ——— S 16 1998</p> <p>Set a steel fence post alongside the iron post.</p>
79.02	<p>The cor. of secs. 8, 9, 16, and 17.</p> <hr/> <p>N. $8^{\circ} 01'$ W., bet. secs. 8 and 9.</p> <p>Over rolling to broken terrain.</p>
20.19	<p>Point for the S. $\frac{1}{16}$ sec. cor. of secs. 8 and 9.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W S $\frac{1}{16}$ S 8 S 9 1998</p> <p>Set a steel fence post alongside the iron post.</p>
40.38	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W 1/4 S 8 S 9 1998</p> <p>Set a steel fence post alongside the iron post.</p>
56.90	<p>Barker Draw, drains N. 35° W.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
80.76	<p>Point for the cor. of secs. 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T51N</td><td>R74W</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Cor. is located on N. facing slope of draw, drains N. 75° W.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>S. 85° 44' W., bet. secs. 4 and 9.</p> <p>Over rolling terrain.</p>	T51N	R74W	S 5	S 4			S 8	S 9	1998	
T51N	R74W										
S 5	S 4										
S 8	S 9										
1998											
20.13	<p>Point for the E. 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T51N</td><td>R74W</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>E1/16</td><td>—</td></tr> <tr><td>S 9</td><td></td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T51N	R74W	S 4		E1/16	—	S 9		1998	
T51N	R74W										
S 4											
E1/16	—										
S 9											
1998											
40.26	<p>Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T51N</td><td>R74W</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 9</td><td></td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T51N	R74W	S 4		1/4	—	S 9		1998	
T51N	R74W										
S 4											
1/4	—										
S 9											
1998											

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
60.39	<p>Point for the W. 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W S 4 W1/16— S 9 1998</p>
80.52	<p>The cor. of secs. 4, 5, 8, and 9.</p> <hr/> <p>N. 6° 36' E., bet. secs. 4 and 5.</p> <p>Over broken terrain.</p>
2.40	<p>Ravine, drains N. 75° W.</p>
20.13	<p>Point for the S. 1/16 sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W S1/16 S 5 S 4 1998</p> <p>Set a steel fence post alongside the iron post.</p>
25.20	<p>Draw, drains S. 55° W.</p>
40.26	<p>Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W 1/4 S 5 S 4 1998</p> <p>Set a steel fence post alongside the iron post.</p>
60.39	<p>Point for the N. 1/16 sec. cor. of secs. 8 and 9.</p>

203

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W N1/16 S 5 S 4 1998</p>
	<p>Set a steel fence post alongside the iron post.</p>
80.68	<p>The cor. of secs. 4 , 5, 32, and 33, on the N. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp.</p> <p>N. 9° 55' W., bet. secs. 31 and 32.</p> <p>Over rolling terrain.</p>
9.00	Wild Horse Creek, course NE.
17.00	Wild Horse Creek, course W.
28.00	Wild Horse Creek, course E.
31.00	Wild Horse Creek, course NW.
44.60	<p>Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate distance; falls in cultivated field, there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W 1/4 S 31 S 32 1998</p> <p>from which</p> <p style="padding-left: 40px;">A power line pole bears N. 16½° E., 5.09 chs. dist.</p> <p style="padding-left: 40px;">A power line pole bears N. 74½° W., 2.27 chs. dist.</p>
50.00	Private road, bears WNW.

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
89.20	<p>True point for the cor. of secs. 29, 30, 31, and 32, determined at record bearing and distance from the witness cor. established by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, falls in Wild Horse Creek, course ESE., where it is impracticable to establish a permanent monument, from which the witness cor.</p> <p>An aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. T51N R74W 50' W WC S25 S3 S1 S3 BER LS 538 1984, bears WEST, 75.8 lks. dist.</p> <p>Witness cor. is located 3.5 lks. N. of fence extending irregularly E. and W.</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 87° 46' W., bet. secs. 29 and 32.</p> <p>Over rolling terrain.</p>
40.39	<p>Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W S 29 1/4 ——— S 32 1998</p> <p>Set a steel fence post alongside the iron post.</p>
79.50	Wild Horse Creek, course NE.
80.78	True point for the cor. of secs. 29, 30, 31, and 32.
	<hr/> <p>S. 89° 25' W., bet. secs. 30 and 31.</p> <p>Over rolling terrain.</p>
7.20	Wild Horse Creek, course NE.

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.28	<p>The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, at cor. of fences extending N. and E., with an aluminum post, 2$\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T51N R74W S 30 1/4 ——— S 31 BER LS538 1984</p> <p>This position is accepted as the best available evidence of the original cor. position.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 71° 37' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
24.86	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a 2$\frac{1}{2}$ ins. diam. iron post, as described in the 1986 field notes of the dependent resurvey, T. 51 N., R. 75 W.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 1° 31' E., bet. secs. 29 and 30.</p> <p>Over rolling terrain.</p>
5.00	Wild Horse Creek, course NW.
34.35	Wild Horse Creek, course S. 84° W.
39.93	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W 1/4 S 30 S 29 1998</p> <p>Set a steel fence post alongside the iron post.</p>
21.00	Wild Horse Creek, course NNE.

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>79.86</p> <p>32.90</p> <p>39.85</p> <p>63.20</p> <p>79.70</p>	<p>The cor. of secs. 19, 20, 29, and 30, monumented with a mound of stone, 2 ft. base, 1 ft. high, no mkd. stone found, at cor. of abandoned fences extending S. and W., with a wood cor. post, projecting 9x5x72 ins. above the ground, alongside. This position is accepted as the best available evidence of the original cor. position.</p> <p>At corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T51N R74W</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td colspan="2">1998</td> </tr> </table> </div> <p>Rebuild the mound of stone, 2½ ft. base, 1½ ft. high, W. of cor. and retain the wood cor. post.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>S. 89° 29' W., bet. secs. 20 and 29.</p> <p>Over rolling terrain.</p> <p>Hay Creek, course N. 36° W.</p> <p>Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T51N R74W</td> </tr> <tr> <td colspan="2">S 20</td> </tr> <tr> <td>1/4</td> <td><hr/></td> </tr> <tr> <td colspan="2">S 29</td> </tr> <tr> <td colspan="2">1998</td> </tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Echeta Road, gravel surfaced, 50 lks. wide, bears N. 4° E. and S. 4° W.</p> <p>The cor. of secs. 19, 20, 29, and 30.</p>	T51N R74W		S 19	S 20	<hr/>		S 30	S 29	1998		T51N R74W		S 20		1/4	<hr/>	S 29		1998	
T51N R74W																					
S 19	S 20																				
<hr/>																					
S 30	S 29																				
1998																					
T51N R74W																					
S 20																					
1/4	<hr/>																				
S 29																					
1998																					

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>S. 83° 03' W., bet. secs. 19 and 30.</p>
	<p>Over rolling terrain.</p>
19.90	<p>Wild Horse Creek, course N. 65° E.</p>
33.29	<p>Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original cor. position.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T51N R74W S 19 1/4 ——— S 30 1998</p>
	<p>Set a steel fence post alongside the iron post.</p>
66.17	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1986 field notes of the dependent resurvey, T. 51 N., R. 75 W.</p>
	<hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p>
	<p>N. 1° 05' E., bet. secs. 19 and 20.</p>
	<p>Over rolling terrain.</p>
8.00	<p>Wild Horse Creek, course N. 82° E.</p>
28.70	<p>Wild Horse Creek, course N. 75° W.</p>
39.69	<p>Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T51N R74W 1/4 S 19 S 20 1998</p>
	<p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
45.30	Echeta Road, bears SE. and NW.										
50.10	Burlington Northern Railroad, bears SE. and NW.										
79.38	<p>The cor. of secs. 17, 18, 19, and 20, monumented with an embedded mound of stone, no mkd. stone found. This position was recovered by Campbell County Surveyor Jessie E. Spielman, date unknown, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T51N R74W</td> </tr> <tr> <td style="text-align: center;">S 18</td> <td style="text-align: center;">S 17</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 19</td> <td style="text-align: center;">S 20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S. 89° 14' W., bet. secs. 17 and 20.</p> <p>Over rolling terrain.</p>	T51N R74W		S 18	S 17	-----		S 19	S 20	1998	
T51N R74W											
S 18	S 17										

S 19	S 20										
1998											
40.01	<p>The ¼ sec. cor. of secs. 17 and 20, monumented with a sandstone, 17x9x3 ins., firmly set 10 ins. in the ground, no mks. visible, in an embedded collar of stone. This position was recovered by Campbell County Surveyor Jessie E. Spielman and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T51N R74W</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 17</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4 -----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table>	T51N R74W		S 17		1/4 -----		S 20		1998	
T51N R74W											
S 17											
1/4 -----											
S 20											
1998											

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Bury the unmkd. stone and set a steel fence post alongside the iron post.
	S. 89° 07' W., beginning new measurement.
	Over rolling terrain.
38.45	The cor. of secs. 17, 18, 19, and 20.
	S. 83° 42' W., bet. secs. 18 and 19.
	Over rolling terrain.
23.90	Burlington Northern Railroad, bears N. 25° W. and S. 25° E.
33.57	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T51N R74W S 18 1/4 ——— S 19 1998</p>
	Set a steel fence post alongside the iron post.
37.70	Echeta Road, bears N. 55° W. and S. 55° E.
46.90	Wild Horse Creek, course N. 65° W.
66.99	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., as described in the 1986 field notes of the dependent resurvey, T. 51 N., R. 75 W.
	From the cor. of secs. 17, 18, 19, and 20.
	N. 8° 14' E., bet. secs. 17 and 18.
	Over rolling to broken terrain.
27.00	Felix Draw, drains NW.

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
41.58	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W 1/4 S 18 S 17 1998</p> <p>Set a steel fence post alongside the iron post.</p>
62.37	<p>Point for the N. $1/16$ sec. cor. of secs. 17 and 18.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W N1/16 S 18 S 17 1998</p> <p>Set a steel fence post alongside the iron post.</p>
83.16	<p>Point for the cor. of secs. 7, 8, 17, and 18, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W S 7 S 8 ----- S 18 S 17 1998</p> <p>Set a steel fence post alongside the iron post.</p>
	<hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>N. $89^{\circ} 07' W.$, bet. secs. 8 and 17.</p> <p>Over broken terrain.</p>
39.30	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T51N R74W S 8 1/4 ——— S 17 1998</p>
	Set a steel fence post alongside the iron post.
78.60	The cor. of secs. 7, 8, 17, and 18.
	S. 83° 03' W., bet. secs. 7 and 18.
	Over broken terrain.
19.86	Point for the E. 1/16 sec. cor. of secs. 7 and 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a steel fence post, with brass cap mkd.
	<p style="text-align: center;">T51N R74W S 7 E1/16 ——— S 18 1998</p>
	Cor. is located on S. edge of ravine, drains S. 80° W.
39.72	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T51N R74W S 7 1/4 ——— S 18 1998</p>
	Set a steel fence post alongside the iron post.
59.58	Point for the W. 1/16 sec. cor. of secs. 7 and 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T51N R74W S 7 W1/16— S 18 1998</p> <p>Set a steel fence post alongside the iron post.</p>
79.65	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron pipe, 2 ins. diam., as described in the 1986 field notes of the dependent resurvey, T. 51 N., R. 75 W.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 9° 14' W., bet. secs. 7 and 8.</p> <p>Over broken terrain, through scattered juniper and pine.</p>
20.85	<p>Point for the S. 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W S1/16 S 7 S 8 1998</p> <p>Set a steel fence post alongside the iron post.</p>
41.70	<p>Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W 1/4 S 7 S 8 1998</p> <p>Set a steel fence post alongside the iron post.</p>
62.55	<p>Point for the N. 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a steel fence post, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T51N R74W N1/16 S 7 S 8 1998</p>
	<p>Cor. is located on E. facing slope of ravine, drains N. 11° E.</p>
79.70	<p>Barker Draw, drains W.</p>
83.40	<p>The cor. of secs. 5, 6, 7, and 8, monumented with the bottom portion of a broken sandstone, 5x4x2 ins. firmly set 5 ins. in the ground, at cor. of fences extending N. 10° E. and S. 85° W., top portion of the broken sandstone, 6x4x2 ins., lying loose alongside, plainly mkd. 3 notches on one edge, no other mks. visible.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T51N R74W S 6 S 5 ----- S 7 S 8 1998</p>
	<p>Bury the remains of the original stone alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 4, 5, 8, and 9.</p>
	<p>N. 87° 30' W., bet. secs. 5 and 8.</p>
	<p>Over rolling to broken terrain.</p>
40.38	<p>Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T51N R74W S 5 1/4 ——— S 8 1998</p>
	<p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
60.57	<p>Point for the W. 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W S 5 W1/16— S 8 1998</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located at base of a 60 ft. high bluff in bottom of draw, drains S. 30° E.</p>
80.76	<p>The cor. of secs. 5, 6, 7, and 8.</p> <hr/> <p>S. 80° 50' W., bet. secs. 6 and 7.</p> <p>Over broken terrain.</p>
19.00	<p>Barker Draw, drains W.</p>
33.27	<p>Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W S 6 1/4 — S 7 1998</p> <p>Set a steel fence post alongside the iron post.</p>
49.91	<p>Point for the W. 1/16 sec. cor. of secs. 6 and 7.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W S 6 W1/16— S 7 1998</p>

Dependent Resurvey of the Subdivisional Lines,
T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
66.94	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1986 field notes of the dependent resurvey, T. 51 N., R. 75 W.</p> <hr/>
	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 9° 29' E., bet. secs. 5 and 6.</p> <p>Over rolling to broken terrain.</p>
18.24	<p>Point for the S. 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W S1/16 S 6 S 5 1998</p>
36.48	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 5.3 lks. W. of fence extending N. and S.</p> <p>Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T51N R74W 1/4 S 6 S 5 1998</p>
73.22	<p>Set a steel fence post alongside the iron post and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.</p> <p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp.</p> <hr/>

T. 51 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	GENERAL DESCRIPTION
	<p>The area embraced by this survey is situated in the west central portion of Campbell County, approximately 10 miles west-northwest of Gillette, Wyoming. The terrain varies from rolling to mountainous, with elevation from about 4,100 feet to about 4,700 feet above sea level. The soil varies from sandy loam to areas of exposed bedrock. Timber consists of scattered juniper and pine in the northwest quarter of the township and scattered stands of cottonwoods along the major drainages.</p> <p>Primary drainage is provided by Wild Horse Creek and Hay Creek draining northerly through the township, aided by Barker Draw, Felix Draw, and numerous smaller draws. There are two working ranches and several abandoned homesteads within the area surveyed. There is evidence of extensive oil and gas exploration, past and present.</p> <p>Access is provided by improved private roads and trails which are accessible from the Echeta Road, which traverses through the southwest quarter of the township, and from the McKenzie Road.</p>

CERTIFICATE OF SURVEY

We, James D. Claflin, Cadastral Surveyor, and Matthew J. Kurchinski, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 10th day of May 27, 1998, we have dependently resurveyed the south boundary and north boundaries, and the subdivisional lines, Township 51 North, Range 74 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUL 30 2001

(Date)

James D. Claflin
(Not Available For Signature)
 (Cadastral Surveyor)

JUL 30 2001

(Date)

Matthew J. Kurchinski
(Not Available For Signature)
 (Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of the south and north boundaries, and the subdivisional lines, Township 51 North, Range 74 West, Sixth Principal Meridian, Wyoming, executed by James D. Claflin, Cadastral Surveyor and Matthew J. Kurchinski, Surveying Technician, having been critically examined and found correct, are hereby approved.

JUL 30 2001

(Date)


(Signature of Authorized Officer)