

643

001

**ORIGINAL**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD NOTES**

OF THE  
DEPENDENT RESURVEY  
OF  
THE WEST BOUNDARY  
AND  
THE SUBDIVISIONAL LINES,  
TOWNSHIP 52 NORTH, RANGE 74 WEST,  
OF THE SIXTH PRINCIPAL MERIDIAN,  
IN THE STATE OF WYOMING.

**EXECUTED BY**

RICHARD A. KOHLER

CADASTRAL SURVEYOR

Under Special Instructions dated MAY 27, 1998, approved JUNE 1, 1998, which provided for the surveys included under Group Number 653, and assignment instructions dated JULY 31, 1998.

Survey commenced JULY 31, 1998

Survey completed SEPTEMBER 15, 1999

INDEX DIAGRAM

002

Township 52 North, Range 74 West

004

7	6 56	56 5 55	43 4 42	33 3 33	24 2 23	15 1 15
6	7 53	54 8 53	42 9 41	32 10 31	22 11 22	14 12 13
5	18 51	52 17 50	40 16 40	30 15 29	21 14 21	12 13 11
4	19 49	49 20 48	38 21 38	28 22 28	20 23 19	11 24 10
3	30 47	47 29 46	37 28 35	27 27 26	18 26 18	9 25 9
2	31	44 32	35 33	25 34	17 35	8 36

## T. 52 N., R., 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>The following field notes are those of the dependent resurvey of the west boundary and the subdivisional lines, Township 52 North, Range 74 West, Sixth Principal Meridian, Wyoming.</p> <p>Louis F. Stahle surveyed the Thirteenth Standard Parallel North (north boundary), the remaining exterior boundaries and the subdivisional lines in 1883. Dell Cazier and Dale C. Wilson dependently resurveyed the east boundary in 1978. Joel T. Ebner dependently resurveyed the north boundary in 1996. James D. Claflin and Matthew J. Kurchinski dependently resurveyed the south boundary during the dependent resurvey of T. 51 N., R. 74 W., executed concurrently under this same group.</p> <p>Several county and local surveys have been executed throughout the area and acceptance of these surveys is detailed herein.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 653, Wyoming, dated May 27, 1998.</p> <p>Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data was thoroughly verified and only true line field notes are given herein, which refer to the completed survey.</p> <p>The survey was executed with a LIETZ Model SET4 electronic total station, a WILD Model T-16 theodolite and by chaining methods. The instruments were maintained in proper adjustment at all times. The directions of all lines refer to the true meridian, determined by hour angle observations of the sun at various points along the lines of survey and carried forward by sustained angulation.</p> <p>The geographic position of the southeast corner of the township, based on NAD 83 and determined by Global Positioning System satellite observation, is:</p> <p>Latitude 44° 26' 04.24" N., Longitude 105° 41' 38.57" W.</p> <p>The mean magnetic declination is 11½° E.</p> <hr/>
--------	---

Dependent Resurvey of the West Boundary,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>(Restoring the survey executed by Louis F. Stahle in 1883)</p> <hr/>
	<p>Beginning at the cor. of Tps. 51 and 52 N., Rs. 74 and 75 W., monumented with an aluminum post, 2½ ins. diam., as described in the 1986 field notes of the dependent resurvey, T. 51 N., R. 75 W.</p>
	<p>N. 0° 57' W., bet. secs. 31 and 36.</p>
	<p>Over rolling to broken terrain.</p>
32.50	Ridge, bears NE. and SW.
43.85	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T52N R75W R74W 1/4 S 36   S 31 1998</p> </div>
	<p>Set a steel fence post alongside the iron post.</p>
65.70	Spur, slopes NW.
86.30	Wash, 30 lks. wide, drains NNW.
87.70	<p>Point for the cor. of secs. 25, 30, 31 and 36, determined longitudinally by proportionate measurement and latitudinally by abandoned fence extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T52N R75W R74W S 25   S 30 <hr/>S 36   S 31 1998</p> </div>

Dependent Resurvey of the West Boundary,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the iron post.
	N. 0° 57' W., bet. secs. 25 and 30.
	Over rolling to broken terrain.
39.84	Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T52N R75W R74W 1/4 S 25   S 30 1998
	Set a steel fence post alongside the iron post.
55.60	Ridge, bears SE. and NW.
59.76	Point for the N. 1/16 sec. cor. of secs. 25 and 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T52N R75W R74W N1/16 S 25   S 30 1998
	Set a steel fence post alongside the iron post.
74.30	Wash, 5 lks. wide, drains NW.
79.68	The cor. of secs. 19, 24, 25 and 30, monumented with a broken sandstone, 16x13x11 ins., loosely set 8 ins. in the ground, plainly mkd. 1 groove on N. face, no other mks. visible.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base, to top, with brass cap mkd.

Dependent Resurvey of the West Boundary,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T52N R75W R74W S 24   S 19 <hr/>S 25   S 30 1998</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr/> <p>N. 0° 53' W., bet. secs. 19 and 24.</p> <p>Over rolling to broken terrain.</p> <p>41.01 Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R75W R74W 1/4 S 24   S 19 1998</p> <p>Set a steel fence post alongside the iron post.</p> <p>60.00 Ridge, bears ESE. and NNW.</p> <p>82.02 Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R75W R74W S 13   S 18 <hr/>S 24   S 19 1998</p> <p>Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <hr/>

Dependent Resurvey of the West Boundary,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 0° 53' W., bet. secs. 13 and 18.
	Over rolling to broken terrain, along E. slope of ridge.
20.505	Point for the S. 1/16 sec. cor. of secs. 13 and 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R75W R74W S1/16 S 13   S 18 1998</p>
	Set a steel fence post alongside the iron post.
41.01	Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R75W R74W 1/4 S 13   S 18 1998</p>
	Set a steel fence post alongside the iron post and raise a mound of stone, 3½ ft. base, 2 ft. high, W. of the cor.
59.80	Twentymile Creek, 20 lks. wide, course W.
61.515	Point for the N. 1/16 sec. cor. of secs. 13 and 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R75W R74W N1/16 S 13   S 18 1998</p>
	Set a steel fence post alongside the iron post.
82.02	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey of the West Boundary,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS													
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T52N</td></tr> <tr><td>R75W</td><td>R74W</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2">1998</td></tr> </table>	T52N		R75W	R74W	S 12	S 7	<hr/>		S 13	S 18	1998	
T52N													
R75W	R74W												
S 12	S 7												
<hr/>													
S 13	S 18												
1998													
	Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.												
	N. 0° 53' W., bet. secs. 7 and 12.												
	Over rolling to broken terrain.												
41.01	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original cor.												
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T52N</td></tr> <tr><td>R75W</td><td>R74W</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1998</td></tr> </table>	T52N		R75W	R74W	1/4		S 12	S 7	<hr/>		1998	
T52N													
R75W	R74W												
1/4													
S 12	S 7												
<hr/>													
1998													
	Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.												
66.00	Ridge, bears E. and W.												
80.00	Wash, 50 lks. wide, dains NW.												
82.02	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original cor.												
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T52N</td></tr> <tr><td>R75W</td><td>R74W</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2">1998</td></tr> </table>	T52N		R75W	R74W	S 1	S 6	<hr/>		S 12	S 7	1998	
T52N													
R75W	R74W												
S 1	S 6												
<hr/>													
S 12	S 7												
1998													

Dependent Resurvey of the West Boundary,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the iron post.
	N. 0° 53' W., bet. secs. 1 and 6.
	Over rolling to broken terrain.
41.01	Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T52N R75W R74W 1/4 S 1   S 6 1998</p>
	Set a steel fence post alongside the iron post.
83.21	Point for the closing cor. of Tps. 52 N., Rs. 74 and 75 W., at intersection with the Thirteenth Standard Parallel North, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T53N R74W S 31</p>
	<p style="text-align: center;">S 1   S 6 R75W R74W T52N C C 1998</p>
	Set a steel fence post alongside the iron post.
	From this point, the standard cor. of Tps. 53 N., Rs. 74 and 75 W., bears S. 89° 19' W., 13.38 chs. dist., monumented with an iron post, 2½ ins. diam., as described in the 1994-95 field notes of the dependent resurvey, T. 53 N., R. 75 W.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>(Restoring the survey executed by Louis F. Stahle in 1883)</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 51 N., R. 74 W., executed concurrently under this same group.</p>
	<p>N. 1° 13' W., bet. secs. 35 and 36.</p>
	<p>Over rolling to broken terrain.</p>
10.00	Ridge, bears ENE. and WSW.
36.60	Spur, slopes NE.
39.81	Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p>T52N R74W 1/4 S 35   S 36 1999</p>
	<p>Set a steel fence post alongside the iron post.</p>
40.20	Wash, 15 lks. wide, drains ENE.
74.20	Ridge, bears E. and SW.
79.62	The cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 18x12x3 ins., firmly set 9 ins. in the ground, no mks. visible, with a mound of stone, 2 ft. base, ½ ft. high, W. of the cor., in abandoned fence extending E. and W. This position is accepted as the best available evidence of the original cor. position.
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>T52N R74W S 26   S 25 <hr/>S 35   S 36 1999</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Bury the unmkd. stone and set a steel fence post alongside the iron post. Rebuild the mound of stone, 3 ft. base, 1½ ft. high, W. of the cor.</p> <hr/>
40.40	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1978 field notes of the dependent resurvey, T. 52 N., R. 73 W.</p> <p>N. 89° 46' W., bet. secs. 25 and 36.</p> <p>Over rolling to broken terrain, along abandoned fence.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance, falls in abandoned fence extending E. and W.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W S 25 1/4 ——— S 36 1999</p>
80.80	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/>
26.80	<p>N. 0° 03' W., bet. secs. 25 and 26.</p> <p>Over rolling to broken terrain.</p> <p>Ridge, bears SE. and NW.</p>
40.25	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W 1/4 S 26   S 25 1999</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
	Set a steel fence post alongside the iron post.										
80.50	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a sandstone, 20x17x5 ins., firmly set 11 ins. in the ground, plainly mkd. 2 grooves on S. face, no other mks. visible, with an embedded mound of stone W. of the cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T52N R74W</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td colspan="2">-----</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> </div> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p>	T52N R74W		S 23	S 24	-----		S 26	S 25	1999	
T52N R74W											
S 23	S 24										
-----											
S 26	S 25										
1999											
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1978 field notes of the dependent resurvey, T. 52 N., R. 73 W.</p>										
	N. 89° 02' W., bet. secs. 24 and 25.										
	Over rolling to broken terrain.										
40.46	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T52N R74W</td> </tr> <tr> <td colspan="2">S 24</td> </tr> <tr> <td>1/4</td> <td>-----</td> </tr> <tr> <td colspan="2">S 25</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T52N R74W		S 24		1/4	-----	S 25		1999	
T52N R74W											
S 24											
1/4	-----										
S 25											
1999											
80.92	The cor. of secs. 23, 24, 25 and 26.										

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 1° 18' E., bet. secs. 23 and 24.
	Over rolling to broken terrain.
11.10	Spur, slopes E.
27.90	Top of ridge, bears N. and SW.
37.20	Leave ridge, bears S. and NW.
39.90	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R74W 1/4 S 23   S 24 1999</p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
64.40	Jamison Prong Wildcat Creek, 5 lks. wide, course ENE.
79.80	Point for the cor. of secs. 13, 14, 23 and 24, determined latitudinally by proportionate measurement and longitudinally at projection of fence from the N.; there is no remaining evidence of the original monument.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R74W S 14   S 13 ----- S 23   S 24 1999</p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
	<hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1978 field notes of the dependent resurvey, T. 52 N., R. 73 W.</p>
	S. 89° 09' W., bet. secs. 13 and 24.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over nearly level terrain.
0.90	Jamison Prong Wildcat Creek, 10 lks. wide, course N.
39.60	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W S 13 1/4 ——— S 24 1999</p>
79.20	The cor. of secs. 13, 14, 23 and 24.
	<hr/> <p>N. 0° 30' W., bet. secs. 13 and 14.</p>
	Over rolling to broken terrain.
3.30	Ridge, bears E. and W.
16.10	Wash, 5 lks. wide, drains SSE.
19.00	Cor. of fences extending N. and SSE.; thence along fence.
39.90	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W 1/4 S 14   S 13 1999</p> <hr/>
	N. 0° 48' W., beginning new measurement.
	Over rolling to broken terrain, along fence.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS						
39.90	<p>The cor. of secs. 11, 12, 13 and 14, at intersection of fences extending E., S. and NNW., and abandoned fence extending N. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T52N R74W</td></tr> <tr><td>S 11   S 12</td></tr> <tr><td>— —</td></tr> <tr><td>S 14   S 13</td></tr> <tr><td>1999</td></tr> </table> </div>	T52N R74W	S 11   S 12	— —	S 14   S 13	1999
T52N R74W						
S 11   S 12						
— —						
S 14   S 13						
1999						
	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1978 field notes of the dependent resurvey, T. 52 N., R. 73 W.</p> <p>S. 88° 42' W., bet. secs. 12 and 13.</p> <p>Over rolling to broken terrain.</p>					
38.00	Wash, 20 lks. wide, drains ESE.					
40.10	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, determined longitudinally by proportionate measurement and latitudinally by fence extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T52N R74W</td></tr> <tr><td>S 12</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S 13</td></tr> <tr><td>1999</td></tr> </table> </div>	T52N R74W	S 12	1/4 —	S 13	1999
T52N R74W						
S 12						
1/4 —						
S 13						
1999						
	<p>S. 88° 56' W., beginning new measurement.</p> <p>Over rolling to broken terrain.</p>					
40.10	The cor. of secs. 11, 12, 13 and 14.					

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 0° 16' E., bet. secs. 11 and 12.
	Over rolling to broken terrain, along abandoned fence.
32.90	Ridge, bears E. and W.
38.96	Point selected for the witness cor. to the 1/4 sec. cor. of secs. 11 and 12.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">WC T52N R74W 1/4 ↑ S 11   S 12 1999</p>
	Witness cor. is located 20 lks. E. of abandoned fence extending irregularly N. and S.
39.66	True point for the 1/4 sec. cor. of secs. 11 and 12, determined longitudinally by proportionate measurement and latitudinally at projection of abandoned fence from the W., falls on steep E. slope of dirt bank where it is impracticable to establish a permanent monument; there is no remaining evidence of the original monument.
	<hr style="width: 20%; margin: 0 auto;"/> <p>N. 0° 16' E., beginning new measurement.</p>
	Over rolling to broken terrain, along abandoned fence.
40.07	The cor. of secs. 1, 2, 11 and 12, monumented by person(s) unknown with a wooden hub, 8 ins. long, 2 ins. square, firmly set 5 ins. in the ground, with a lava stone, 13x9x7 ins., lying loose, no mks. visible, and a steel fence post alongside, at projection of abandoned fence from the S. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<table border="1"> <tr><td colspan="2">T52N R74W</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 11</td><td>S 12</td></tr> <tr><td colspan="2">1999</td></tr> </table>	T52N R74W		S 2	S 1	<hr/>		S 11	S 12	1999	
T52N R74W											
S 2	S 1										
<hr/>											
S 11	S 12										
1999											
	Deposit the wooden hub inside and bury the unmkd. stone alongside the iron post.										
	<hr/>										
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1978 field notes of the dependent resurvey, T. 52 N., R. 73 W.										
	N. 89° 06' W., bet. secs. 1 and 12.										
	Over rolling to broken terrain.										
34.90	Ridge, bears SSE. and NNW.										
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original cor.										
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.										
	<table border="1"> <tr><td colspan="2">T52N R74W</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 12</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table>	T52N R74W		S 1		1/4	—	S 12		1999	
T52N R74W											
S 1											
1/4	—										
S 12											
1999											
	Cor. is located 90 lks. N. of abandoned fence extending E. and W.										
80.00	The cor. of secs. 1, 2, 11 and 12.										
	<hr/>										
	N. 4° 16' E., bet. secs. 1 and 2.										
	Over rolling to broken terrain.										
46.78	Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original cor.										
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.										

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T52N R74W 1/4 S 2   S 1 1999</p> <p>Cor. is located near head of small wash, 5 lks. wide, drains SSE.</p> <p>94.42 Point for the closing cor. of secs. 1 and 2, at intersection with the Thirteenth Standard Parallel North, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T53N R76W S 36 ----- S 2   S 1 T52N R76W C C 1998</p> <p>Cor. is located 5 lks. N. of fence extending E. and W.</p> <p>From this point, the standard cor. of secs. 35 and 36, T. 53 N., R. 74 W., bears S. 89° 47' W., 15.54 chs. dist., monumented with an aluminum post, 2½ ins. diam., as described in the 1996 field notes of the dependent resurvey, T. 53 N., R. 74 W.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 1 only, T. 52 N., R. 74 W., is at midpoint on the N. bdy. of sec. 1.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T53N R74W ----- 1/4 S 1 T52N R74W 1998</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, the standard 1/4 sec. cor. of sec. 36, T. 53 N., R. 74 W., bears S. 89° 47' W., 15.48 chs. dist., monumented with an aluminum post, 2½ ins. diam., as described in the 1996 field notes of the dependent resurvey, T. 53 N., R. 74 W.</p> <hr/>
--------	---

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 51 N., R. 74 W., executed concurrently under this same group.</p>
	<p>N. 0° 36' W., bet. secs. 34 and 35.</p>
	<p>Over rolling to broken terrain.</p>
12.50	<p>Spur, slopes SE.</p>
39.10	<p>Ridge, bears SE. and NW.</p>
39.66	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T52N R74W 1/4 S 34   S 35 1999</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>
77.10	<p>Ridge, bears E. and W.</p>
79.32	<p>The cor. of secs. 26, 27, 34 and 35, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with a steel reinforcement rod, 18 ins. long, ¾ in. diam., firmly set 17 ins. in the ground, in an embedded mound of stone, with plastic cap inscribed B. E. RUMPH LS 538. This position is accepted as the best available evidence of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T52N R74W S 27   S 26 ----- S 34   S 35 1999</p>
	<p>Deposit the steel reinforcement rod inside the iron post and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89° 48' W., between secs. 26 and 35.</p> <p>Over rolling to broken terrain.</p>
40.00	<p>The 1/4 sec. cor. of secs. 26 and 35, at intersection of abandoned fences extending N., E. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T52N R74W</p> <p>S 26</p> <p>1/4 ———</p> <p>S 35</p> <p>1999</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 89° 48' W., beginning new measurement.</p> <p>Over gently rolling terrain, along fading fence scar.</p>
40.16	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 0° 02' W., bet. secs. 26 and 27.</p> <p>Over rolling to broken terrain.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T52N R74W</p> <p>1/4</p> <p>S 27   S 26</p> <p>1999</p> </div>

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS								
	Cor. is located on steep NW. slope of wash, 30 lks. wide, drains ENE.							
41.10	Spur, slopes SE.							
75.10	Wash, 50 lks. wide, drains ENE.							
80.08	<p>The cor. of secs. 22, 23, 26 and 27, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, in an embedded mound of stone, at cor. of abandoned fences extending N. and E., as shown on well location plat prepared by Mr. Rumph and obtained from the Wyoming Oil and Gas Commission, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T52N R74W</td></tr> <tr><td>S 22   S 23</td></tr> <tr><td>— —</td></tr> <tr><td>S 27   S 26</td></tr> <tr><td>B.E.R.</td></tr> <tr><td>L.S. 538</td></tr> <tr><td>1981</td></tr> </table> <p>This position is accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89° 53' W., bet. secs. 23 and 26.</p> <p>Over rolling to broken terrain.</p>	T52N R74W	S 22   S 23	— —	S 27   S 26	B.E.R.	L.S. 538	1981
T52N R74W								
S 22   S 23								
— —								
S 27   S 26								
B.E.R.								
L.S. 538								
1981								
40.06	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T52N R74W</td></tr> <tr><td>S 23</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S 26</td></tr> <tr><td>1999</td></tr> </table>	T52N R74W	S 23	1/4 —	S 26	1999		
T52N R74W								
S 23								
1/4 —								
S 26								
1999								
41.50	Ridge, bears ENE. and WSW.; thence along abandoned fence.							
55.60	Wash, 15 lks. wide, drains WNW.							