

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
67.20	Spur, slopes N.
76.60	Wash, 80 lks. wide, drains N.
80.12	The cor. of secs. 22, 23, 26 and 27.
	N. 0° 56' E., bet. secs. 22 and 23.
	Over rolling to broken terrain, leaving fading abandoned fence.
23.70	Ridge, bears ESE. and WNW.
41.54	Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R74W 1/4 S 22   S 23 1999</p>
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.
	Cor. is located approximately 70 lks. E. of line of down fence posts extending N. and S.
53.50	Wash, 80 lks. wide, drains NE.
57.00	Wash, 15 lks. wide, drains SE.
62.31	Point for the N. 1/16 sec. cor. of secs. 22 and 23.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R74W N1/16 S 22   S 23 1999</p>
76.80	Ridge, bears SE. and NW.
83.08	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T52N</td><td>R74W</td></tr> <tr><td>S 15</td><td>  S 14</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 22</td><td>  S 23</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div>	T52N	R74W	S 15	S 14	<hr/>		S 22	S 23	1999	
T52N	R74W										
S 15	S 14										
<hr/>											
S 22	S 23										
1999											
<p>40.31</p>	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 87° 47' W., bet. secs. 14 and 23.</p> <p>Over rolling to broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T52N</td><td>R74W</td></tr> <tr><td>S 14</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 23</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p>	T52N	R74W	S 14		1/4	—	S 23		1999	
T52N	R74W										
S 14											
1/4	—										
S 23											
1999											
<p>80.62</p> <p>8.60</p> <p>41.54</p>	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 0° 42' E., bet. secs. 14 and 15.</p> <p>Over rolling to broken terrain.</p> <p>Wash, 40 lks. wide, drains SSE.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T52N</td><td>R74W</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 15</td><td>  S 14</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div>	T52N	R74W	1/4		S 15	S 14	1999			
T52N	R74W										
1/4											
S 15	S 14										
1999											

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.										
42.80	Ridge, bears SE. and NW.										
83.08	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original cor.										
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T52N R74W</td></tr> <tr><td>S 15</td><td>S 14</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 22</td><td>S 23</td></tr> <tr><td colspan="2">1999</td></tr> </table>	T52N R74W		S 15	S 14	-----		S 22	S 23	1999	
T52N R74W											
S 15	S 14										
-----											
S 22	S 23										
1999											
	From the cor. of secs. 11, 12, 13 and 14.										
	N. 85° 21' W., bet. secs. 11 and 14.										
	Over rolling to broken terrain.										
34.00	Ridge, bears N. and S.										
39.43	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original cor.										
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T52N R74W</td></tr> <tr><td colspan="2">S 11</td></tr> <tr><td>1/4</td><td>-----</td></tr> <tr><td colspan="2">S 14</td></tr> <tr><td colspan="2">1999</td></tr> </table>	T52N R74W		S 11		1/4	-----	S 14		1999	
T52N R74W											
S 11											
1/4	-----										
S 14											
1999											
	Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.										
77.10	Wash, 15 lks. wide, drains NW.										
78.86	The cor. of secs. 10, 11, 14 and 15.										
	N. 0° 08' W., bet. secs. 10 and 11.										
	Over rolling to broken terrain.										
0.80	Wash, 15 lks. wide, drains NW.										

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
33.20	Spur, slopes WNW.; thence along W. slope of ridge.
41.54	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T52N R74W 1/4 S 10   S 11 1999
83.08	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T52N R74W S 3   S 2 ----- S 10   S 11 1999
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
	From the cor. of secs. 1, 2, 11 and 12.
	N. 82° 59' W., bet. secs. 2 and 11.
	Over mountainous terrain.
16.60	Ridge, bears SE. and NW.
34.30	Wash, 20 lks. wide, drains NW.
39.86	Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T52N R74W S 2 1/4 ——— S 11 1999

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.
44.60	Ridge, bears N. and S.
79.72	The cor. of secs. 2, 3, 10 and 11.
	<hr/> N. 3° 43' E., bet. secs. 2 and 3.  Over mountainous terrain.
41.62	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor.  Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">             T52N R74W              1/4              S 3   S 2              1999           </div>
	Set a steel fence post alongside the iron post.  Cor. is located on ridge, N. 60° E., 1.70 chs. dist., from cor. of fences extending ESE. and WSW.
84.28	True point for the closing cor. of secs. 2 and 3, T. 52 N., R. 74 W., at proportionate distance, falls on steep E. slope of small wash, drains SW., where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.
	From this point, the point selected for the witness cor. to the closing cor. of secs. 2 and 3, bears N. 89° 47' E., 60 lks. dist.  Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">             WC              T53N R76W              S 35              ←—————              S 3   S 2              T52N R76W              C C              1998           </div>
	Set a steel fence post alongside the iron post.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the true point for the closing cor. of secs. 2 and 3, the standard cor. of secs. 34 and 35, T. 53 N., R. 74 W., bears S. 89° 47' W., 15.20 chs. dist., monumented with an iron post, 2½ ins. diam., as described in the 1996 field notes of the dependent resurvey, T. 53 N., R. 74 W.</p>
	<p>The point for the 1/4 sec. cor. of sec. 2 only, T. 52 N., R. 74 W., is at midpoint on the N. bdy. of sec. 2.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T53N R74W</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 2 T52N R74W 1998</p>
	<p>Set a steel fence post alongside the iron post and raise a mound of stone, 2½ ft. base, 1½ ft. high, S. of the cor.</p> <p>From this point, the standard 1/4 sec. cor. of sec. 35, T. 53 N., R. 74 W., bears S. 89° 47' W., 15.37 chs. dist., monumented with an aluminum post, 2½ ins. diam., as described in the 1996 field notes of the dependent resurvey, T. 53 N., R. 74 W.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1998 field notes of the dependent resurvey, T. 51 N., R. 74 W.</p> <p>N. 3° 35' W., bet. secs. 33 and 34.</p> <p>Over rolling to broken terrain.</p>
30.50	Twentymile Creek, 30 lks. wide, course NW.
40.22	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T52N R74W</p> <p style="text-align: center;">1/4 S 33   S 34 1999</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.
44.80	Wash, 80 lks. wide, drains SSW.
60.33	Point for the N. 1/16 sec. cor. of secs. 33 and 34.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R74W N1/16 S 33   S 34 1999</p>
	Raise a mound of stone, 4 ft. base, 2 ft. high, W. of the cor.
	Cor. is located on ridge, bears N. and WSW.
80.44	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R74W S 28   S 27 ----- S 33   S 34 1999</p>
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.
	Cor. is located 1 ch. N. of draw, 5 lks. wide, drains NW.
	<hr/>
	From the cor. of secs. 26, 27, 34 and 35.
	N. 89° 23' W., bet. secs. 27 and 34.
	Over rolling to broken terrain.
3.40	Ridge, bears SSE. and NNW.
40.31	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T52N R74W S 27 1/4 ——— S 34 1999
42.30	Enter wash, 80 lks. wide, drains E.
47.50	Leave wash, 40 lks. wide, drains SW.
66.60	Ridge, bears N. and S.
80.62	The cor. of secs. 27, 28, 33 and 34.
	<hr/> N. 1° 49' E., bet. secs. 27 and 28.  Over rolling to broken terrain.
15.80	Ridge, bears SE. and NW.
40.16	Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original cor.  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T52N R74W 1/4 S 28   S 27 1999
	Cor. is located on spur, slopes NW.
64.50	Ridge, bears SSE. and NNW.
80.32	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; there is no remaining evidence of the original cor.  Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T52N R74W S 21   S 22 ———— S 28   S 27 1999

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Cor. is located in wash, 80 lks. wide, drains NW.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 89° 13' W., bet. secs. 22 and 27.
	Over rolling to broken terrain.
39.00	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T52N R74W S 22 1/4 ——— S 27 1999</p>
42.80	Spur, slopes NW.
78.00	The cor. of secs. 21, 22, 27 and 28.
	N. 0° 49' W., bet. secs. 21 and 22.
	Over rolling to broken terrain.
12.00	Spur, slopes NW.
20.07	Point for the S. 1/16 sec. cor. of secs. 21 and 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R74W S 1/16 S 21   S 22 1999</p>
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.
20.60	Wash, 20 lks. wide, drains SW.
40.14	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R74W 1/4 S 21   S 22 1999</p>
41.30	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor. Ridge, bears NE. and SW.
60.21	Point for the N. 1/16 sec. cor. of secs. 21 and 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T52N R74W N1/16 S 21   S 22 1999</p>
75.40	Spur, slopes NW.
80.28	The cor. of secs. 15, 16, 21 and 22, at intersection of fences extending N. and W., and abandoned fence extending S. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T52N R74W S 16   S 15 ----- S 21   S 22 1999</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 88° 46' W., bet. secs. 15 and 22.</p> <p>Over rolling to broken terrain.</p>
7.00	Spur, slopes SE.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.24	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W S 15 1/4 ——— S 22 1999</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.</p>
53.60	Spur, slopes SE.
69.00	Ridge, bears S. and NNW.
80.48	The cor. of secs. 15, 16, 21 and 22.
	<hr/> <p>N. 0° 37' W., bet. secs. 15 and 16.</p> <p>Over rolling to broken terrain, along fence.</p>
19.94	<p>Point for the S. 1/16 sec. cor. of secs. 15 and 16.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W S1/16 S 16   S 15 1999</p> <p>Cor. is located 8 lks. W. of fence extending N. and S.</p>
29.40	Wash, 30 lks. wide, drains NW.
39.88	<p>The 1/4 sec. cor. of secs. 15 and 16, at cor. of fences extending E. and S. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T52N R74W 1/4 S 16   S 15 1999
	<hr style="width: 30%; margin: auto;"/>
	N. 4° 40' E., beginning new measurement.
	Over rolling to broken terrain.
2.90	Spur, slopes NW.
37.00	Ridge, bears E. and W.
42.05	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T52N R74W S 9   S 10 <hr style="width: 10%; margin: auto;"/> S 16   S 15 1999
	<hr style="width: 80%; margin: auto;"/>
	From the cor. of secs. 10, 11, 14 and 15.
	S. 87° 48' W., bet. secs. 10 and 15.
	Over rolling to broken terrain.
39.26	Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T52N R74W S 10 1/4 ——— S 15 1999
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.
56.60	Fence, on ridge, bears SE. and NW.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
58.89	<p>Point for the W. 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W S 10 W1/16 ——— S 15 1999</p>
78.52	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>The cor. of secs. 9, 10, 15 and 16.</p>
0.40	<p>N. 0° 39' W., bet. secs. 9 and 10.</p> <p>Over rolling to broken terrain.</p> <p>Wash, 20 lks. wide, drains WSW.</p>
21.80	<p>Ridge, bears SE. and NW.</p>
41.92	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W 1/4 S 9   S 10 1999</p>
	<p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 55° E, 10 lks. dist., mkd. 1/4 S10 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 78° W, 61 lks. dist., mkd. 1/4 S9 BT.</p>
42.90	<p>Wash, 40 lks. wide, drains ESE.</p>
83.84	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T52N</td><td>R74W</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 9</td><td>S 10</td></tr> <tr><td colspan="2">1999</td></tr> </table>	T52N	R74W	S 4	S 3	<hr/>		S 9	S 10	1999	
T52N	R74W										
S 4	S 3										
<hr/>											
S 9	S 10										
1999											
	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on ridge, 1 ch. N. of fence extending ENE. and WSW.</p>										
	<hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 88° 21' W., bet. secs. 3 and 10.</p> <p>Over mountainous terrain.</p>										
38.50	Spur, slopes SSE.										
39.62	Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original cor.										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T52N</td><td>R74W</td></tr> <tr><td>S 3</td><td></td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td>S 10</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table>	T52N	R74W	S 3		1/4	<hr/>	S 10		1999	
T52N	R74W										
S 3											
1/4	<hr/>										
S 10											
1999											
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.										
71.70	Spur, slopes SE.										
79.24	The cor. of secs. 3, 4, 9 and 10.										
	<hr/> <p>N. 1° 40' E., bet. secs. 3 and 4.</p> <p>Over mountainous terrain.</p>										
41.93	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance, falls on steep NE. slope of hill; there is no remaining evidence of the original cor.										

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T52N R74W 1/4 S 4   S 3 1999</p>
84.79	<p>Point for the closing cor. of secs. 3 and 4, at intersection with the Thirteenth Standard Parallel North, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T53N R74W S 34 ----- S 4   S 3 T52N R74W C C 1999</p>
	<p>Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of the cor.</p>
	<p>From this point, the standard cor. of secs. 33 and 34, T. 53 N., R. 74 W., bears S. 88° 40' W., 15.42 chs. dist., monumented with an aluminum post, 2½ ins. diam., as described in the 1996 field notes of the dependent resurvey, T. 53 N., R. 74 W.</p>
	<p>The point for the 1/4 sec. cor. of sec. 3 only, T. 52 N., R. 74 W., is at midpoint on the N. bdy. of sec. 3.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T53N R74W ----- 1/4 S 3 T52N R74W 1998</p>
	<p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, the standard 1/4 sec. cor. of sec. 34, T. 53 N., R. 74 W., bears S. 88° 40' W., 15.31 chs. dist., monumented with an aluminum post, 2½ ins. diam., as described in the 1996 field notes of the dependent resurvey, T. 53 N., R. 74 W.</p> <hr/>
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 51 N., R. 74 W., executed concurrently under this same group.</p>
	<p>N. 6° 37' W., bet. secs. 32 and 33.</p>
	<p>Over rolling to broken terrain.</p>
40.59	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T52N R74W 1/4 S 32   S 33 1999</p>
	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of the cor.</p>
42.90	<p>Spur, slopes NW.</p>
81.18	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T52N R74W S 29   S 28 <hr/>S 32   S 33 1999</p>
	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p> <hr/>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p>
	<p>N. 89° 49' W., bet. secs. 28 and 33.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling to broken terrain.
20.195	<p>Point for the E. 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W S 28 E1/16 ——— S 33 1999</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p>
35.40	Wash, 40 lks. wide, drains SSW.
40.39	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W S 28 1/4 ——— S 33 1999</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>
57.60	Twentymile Creek, 5 lks. wide, course N.
60.585	<p>Point for the W. 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W S 28 W1/16 ——— S 33 1999</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.</p>
73.90	Spur, slopes NW.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
80.78	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/>
	<p>N. 3° 56' E., bet. secs. 28 and 29.</p> <p>Over rolling to broken terrain.</p>
40.41	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W 1/4 S 29   S 28 1999</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, E. (downhill side) of the cor.</p>
60.615	<p>Point for the N. 1/16 sec. cor. of secs. 28 and 29, falls in Twentymile Creek, 1.8 chs. wide, course NNW.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W N1/16 S 29   S 28 1999</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p>
80.82	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W S 20   S 21 <hr/>S 29   S 28 1999</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89° 32' W., bet. secs. 21 and 28.
	Over rolling to broken terrain.
11.60	Spur, slopes NW.
19.44	Point for the E. 1/16 sec. cor. of secs. 21 and 28, falls in wash, 30 lks. wide, drains NW.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">           T52N R74W                      S 21            E1/16 ———                      S 28                      1999         </div>
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.
24.00	Spur, slopes NNW.
38.88	Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">           T52N R74W                      S 21            1/4 ———                      S 28                      1999         </div>
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.
44.40	Wash, 60 lks. wide, drains NNW.
53.70	Spur, slopes NNW.
77.76	The cor. of secs. 20, 21, 28 and 29.
	<hr/> N. 2° 41' W., bet. secs. 20 and 21.
	Over rolling to broken terrain.

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
12.10	Wash, 80 lks. wide, drains SW.
20.18	<p>Point for the S. 1/16 sec. cor. of secs. 20 and 21, falls on W. slope of small draw, 50 lks. wide, drains SSE.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W S1/16 S 20 S 21 1999</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., with multiple trunks, bears N. 80° E., 56 lks. dist., mkd. S1/16 S21 BT on W. trunk.</p>
40.36	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T52N R74W 1/4 S 20 S 21 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on ridge, 1.6 chs. W. of fence extending NE. and SW.</p>
80.72	<p>The cor. of secs. 16, 17, 20 and 21, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with a steel reinforcement rod, 24 ins. long, ¾ in. diam., firmly set 20 ins. in the ground, in an embedded mound of stone, no mkd. stone found, as shown on well location plat prepared by Mr. Rumph and obtained from the Wyoming Oil and Gas Commission, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd. T52N R74W S16 S17 S20 S21 PLS 538 1998. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 52 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T52N</td><td>R74W</td></tr> <tr><td>S 17</td><td>S 16</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 20</td><td>S 21</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit the reinforcement rod inside and set a steel fence post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89° 20' W., bet. secs. 16 and 21.</p> <p>Over rolling to broken terrain, along fence.</p>	T52N	R74W	S 17	S 16	<hr/>		S 20	S 21	1999	
T52N	R74W										
S 17	S 16										
<hr/>											
S 20	S 21										
1999											
38.10	Spur, slopes NNW.										
40.19	Point for the 1/4 sec. cor. of secs. 16 and 21, determined longitudinally by proportionate measurement and latitudinally by fence extending E. and W.; there is no remaining evidence of the original monument.										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T52N</td><td>R74W</td></tr> <tr><td>S 16</td><td></td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td>S 21</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <hr/> <p>N. 89° 15' W., beginning new measurement.</p> <p>Over rolling to broken terrain, along fence.</p>	T52N	R74W	S 16		1/4	<hr/>	S 21		1999	
T52N	R74W										
S 16											
1/4	<hr/>										
S 21											
1999											
28.30	Leave fence, bears E. and SSE., on ridge, bears SE. and NW.										
40.19	The cor. of secs. 16, 17, 20 and 21.										
	<hr/> <p>N. 3° 12' E., bet. secs. 16 and 17.</p> <p>Over rolling to broken terrain.</p>										