

ORIGINAL

Bureau of Land Management

Cadastral Survey

U.S. Public Land Survey System

Corner Recordation Certificate

6040.

Vol. 642 Page 153

- A.) The ¼ sec. cor. of Secs. 27 and 34, T. 52 N., R. 93 W., 6th Principal Meridian Wyoming.
- B.) HISTORY OF SURVEYS: E. A. LaPeire surveyed the subdivisional lines in 1883; subsequently cancelled. Edward F. Stahle surveyed the private land claims and subdivisional lines in 1904. Set a sandstone 15x12x4 ins., 10 ins. in the ground, for ¼ sec. cor., mkd. 1/4 on N. face; dug pits, 18x18x12 ins., E. and W. of stone, 3 ft. dist., and raised a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
- C.) DESCRIPTION OF EVIDENCE FOUND, INCLUDING ACCESSORIES: Monumented with a sandstone, 16x4x3 ins., firmly set 11 ins. in the ground, plainly mkd. ¼ on N. face, with a steel fence post alongside.
- D.) DESCRIPTION OF REMONUMENTED CORNER, INCLUDE NEW ACCESSORIES, DISPOSITION OF EVIDENCE AND A LOCATION STATEMENT:

Set an iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, with brass cap mkd.

Bury the original corner stone alongside the iron post.



I, Michael D. Londe, Geodesist, HEREBY CERTIFY upon honor that, in pursuance of special instructions for Group No. 540, Wyoming, dated June 11, 1990, and assignment instructions dated October 31, 1994, I have remonumented the corner herein described on November 3, 1994, in strict conformity with said special instructions and the Manual of Instructions for the Survey of the Public Lands of the United States.

APR 23 2001

(Date)

Michael D. Londe

(Geodesist)

The description of the remonumentation of the corner herein described, executed by Michael D. Londe, Geodesist, having been critically examined and found correct, is hereby approved.

APR 23 2001

(Date)

John P. Lee

(Chief Cadastral Surveyor for Wyoming)