

640-6021

01

**ORIGINAL**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD NOTES**

OF THE

DEPENDENT RESURVEY

OF A PORTION OF

THE NINTH AUXILIARY MERIDIAN WEST,  
THROUGH TOWNSHIP 54 NORTH, BETWEEN RANGES 76 AND 77 WEST,  
A PORTION OF THE SOUTH BOUNDARY,  
THE EAST AND NORTH BOUNDARIES,  
AND A PORTION OF THE  
SUBDIVISIONAL LINES,  
TOWNSHIP 54 NORTH, RANGE 76 WEST,  
OF THE SIXTH PRINCIPAL MERIDIAN,  
IN THE STATE OF WYOMING.

**EXECUTED BY**

RICHARD A. KOHLER

CADASTRAL SURVEYOR

Under Special Instructions dated FEBRUARY 12, 1988, approved FEBRUARY 12, 1988, which provided for the surveys included under Group Number 511, and assignment instructions dated AUGUST 1, 1988.

Survey commenced AUGUST 10, 1988

Survey completed JULY 26, 1989

# INDEX DIAGRAM

100

Township 54 North, Range 76 West

22		21		20		19		18		17		
3	6	68	5	57	4	49	3	41	2	31	1	15
		67		56		49		40		31		
2	7	66	8	56	9	48	10	38	11	30	12	14
		65		55		47		38		29		
<b>18</b>		64	<b>17</b>	54	<b>16</b>	46	<b>15</b>	37	<b>14</b>	28	<b>13</b>	13
		63		54		46		36		27		
<b>19</b>		61	<b>20</b>	53	<b>21</b>	45	<b>22</b>	35	<b>23</b>	26	<b>24</b>	12
		61		52		44		34		26		
<b>30</b>		60	<b>29</b>	51	<b>28</b>	43	<b>27</b>	33	<b>26</b>	24	<b>25</b>	11
		59		50		42		33		24		
<b>31</b>		58	<b>32</b>	50	<b>33</b>	41	<b>34</b>	32	<b>35</b>	23	<b>36</b>	10
		9		8		7		6		5		

## T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the Ninth Auxiliary Meridian West through Township 54 North, between Ranges 76 and 77 West, a portion of the south boundary, the east and north boundaries and a portion of the subdivisional lines, Township 54 North, Range 76 West, Sixth Principal Meridian, Wyoming.

The history of surveys pertaining to this resurvey is as follows:

Charles Holcomb surveyed the Ninth Auxiliary Meridian West (west boundary), and the north and south boundaries in 1883. Mortimer N. Grant surveyed the east boundary in 1883. Charles Holcomb retraced the east boundary and surveyed the subdivisional lines in 1883. Mark M. Kelley retraced a portion of the west boundary in 1914. Russell C. MacDonald dependently resurveyed a portion of the west boundary in 1946 and a portion of the south boundary and the subdivisional lines in 1947.

Jesse E. Spielman, Campbell County Surveyor, surveyed Miller Road, renamed Middle Prong Road in 1921 and Middle Prong Road Extension in 1923 as recorded at the Campbell County Courthouse. That portion of Miller Road extending north is presently known as Barton Road and that portion of Miller Road extending east and west is presently known as Middle Prong Road. The original road names were utilized in the following field notes when referring to the Spielman record.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 511, Wyoming, dated February 12, 1988.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data was thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

The survey was executed with a LIETZ SET4 electronic Total Station and by chaining methods. The instrument was maintained in proper adjustment at all times. The directions of all lines refer to the true meridian, determined by direct hour angle observations of the sun at various points along the lines of survey and carried forward by sustained angulation.

T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS

The geographic position of the southeast corner of the township, based on NAD 27 and determined by GPS satellite observation, is:

Latitude 44° 36' 28.15" N. and Longitude 105° 56' 21.41" W.

The mean magnetic declination is 12½° E.

---

Dependent Resurvey,  
Portion of the Ninth Auxiliary Meridian West,  
between Ranges 76 and 77 West,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

---

(Restoring the dependent resurvey executed by  
Russell C. MacDonald in 1946)

---

Beginning at the cor. of secs. 7, 12, 13 and 18, mkd. by the memorial to the cor., a brown glass bottle, found broken and buried 24 ins. below the surface of the ground, with the remains of a wooden post alongside. The 1946 resurvey monument, an iron post, 3 ft. long, 2 ins. diam., with brass cap mkd. T54N R76W R77W S7 S12 S13 S18 1946, was found bent and lying loose nearby.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. below the surface of cultivated field, with brass cap mkd.

T54N	
R77W R76W	
S 12	S 7
-----	
S 13	S 18
1988	

Bury the 1946 iron post and the remains of the glass bottle, and set a steel fence post alongside the stainless steel post.

N. 0° 06' W., bet. secs. 7 and 12.

Over gently rolling terrain.

39.70

The ¼ sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.

Dependent Resurvey,  
Portion of the Ninth Auxiliary Meridian West,  
between Ranges 76 and 77 West,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	$\frac{1}{4}$ S 12   S 7 1946
	Cor. is located at intersection of fences extending N. and S., with fence scar extending W.
	<hr/> (Restoring the survey executed by Charles Holcomb in 1883) <hr/>
	N. 0° 33' W., beginning new measurement.
	Over rolling terrain.
39.27	The cor. of secs. 1, 6, 7 and 12, monumented with an embedded mound of stone, in fence extending N. and S. This position agrees with a cor. tie shown in the field notes of the Gillette-Arvada State Highway, surveyed by the Wyoming State Highway Department in 1921 and recorded on page 154 of the County Road Plat Book in the Sheridan County Courthouse, and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T54N R77W R76W S 1   S 6 <hr/> S 12   S 7 1989
	N. 0° 17' W., bet. secs. 1 and 6.
	Over rolling terrain, along fence.
17.60	North Prong Wild Horse Creek, 15 lks. wide, course SSW.
21.30	Sheridan County Road No. 40, bears NE and SW.
39.60	The ¼ sec. cor. of secs. 1 and 6, determined at intersection of fences extending N. and S., with fence scar extending W. This position is accepted as the best available evidence of the original cor. position.

Dependent Resurvey,  
 Portion of the Ninth Auxiliary Meridian West,  
 between Ranges 76 and 77 West,  
 T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N        R77W R76W        1/4        S 1   S 6        1989</p> <hr style="width: 20%; margin: auto;"/> <p>N. 8° 20' W., beginning new measurement.</p> <p>Over rolling terrain, leaving fence.</p> <p>40.04 True point for the cor. of Tps. 54 and 55 N., Rs. 76 and 77 W., from which the reference monument, an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T54N T55N R76W R77W S1 S6 S31 S36 RM 1946 and an arrow pointing to the cor., bears N. 1° 54' W., 0.56 chs. dist., on line with the witness cor. to the cor. of secs. 30 and 31, T. 55 N., R. 76 W. This reference monument was subsequently destroyed during road construction along a portion of U.S. Highway No. 14-16, and the true point monumented upon completion of the new roadway.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N        R77W R76W        S 36   S 31        ————        S 1   S 6        T54N        1989</p> <p>from which</p> <p>A Wyoming State Highway Dept. right-of-way monument, bears N. 8½° W., 72 lks. dist., a brass tablet, 3 ins. diam., seated in a concrete post, 6 ins. square, projecting 4 ins. above the ground, mkd. STA 398+12.09 EL 3920.52 SEC LINE 75.</p>
--------	---

Dependent Resurvey,  
Portion of the Ninth Auxiliary Meridian West,  
between Ranges 76 and 77 West,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

## CHAINS

Set two steel fence posts alongside the iron post.

Cor. is located 42 lks. N. of center of U.S. Highway No. 14-16, asphalt surface, 50 lks. wide extending ENE. and WSW.

---

Dependent Resurvey, Portion of the South Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

---

(Restoring the survey executed by  
Charles Holcomb in 1883)

---

From the cor. of Tps. 53 and 54 N., Rs. 75 and 76 W., monumented with an iron wagon lead, 14 ins. long, firmly set 8 ins. in the ground, with scattered sandstone fragments and a steel fence post alongside. This position was identified by adjacent landowner J. A. McCue, now deceased, in conversations with private land surveyors and United States Geological Survey field personnel and is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T54N	
R76W	R75W
S 36	S 31
-----	
S 1	S 6
T53N	
1989	

Bury the iron wagon lead alongside the iron post.

Cor. is located N. 1¾° E., 1.94 chs. dist., from an intersection of fences extending S. and W., with a fence scar extending E.

S. 88° 48' W., bet. secs. 1 and 36.

Over rolling terrain.

40.025

Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey, Portion of the South Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W S 36 1/4 — S 1 T53N 1989</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located N. 9° E., 1.61 chs. dist., from a cor. of fences extending N. and E.</p>
80.05	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W S 35   S 36 —   — S 2   S 1 T53N 1989</p> <p>Cor. is located N. 38½° E., 1.48 chs. dist., from a cor. of fences extending N. and E.</p>
10.80	<p>S. 88° 48' W., bet. secs. 2 and 35.</p> <p>Over rolling to broken terrain.</p> <p>Ridge, bears N. and S.</p>
40.025	<p>Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W S 35 1/4 — S 2 T53N 1989</p>

Dependent Resurvey, Portion of the South Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the iron post.
45.20	Ridge, bears SE. and NW.
60.038	Point for the W. 1/16 sec. cor. of secs. 2 and 35.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">           T54N R76W            S 35            W1/16 ———            S 2            T53N            1989         </div>
	Set a steel fence post alongside the iron post.
80.05	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">           T54N R76W            S 34   S 35            ————            S 3   S 2            T53N            1989         </div>
	Set a steel fence post alongside the iron post.
	S. 88° 48' W., bet. secs. 3 and 34.
	Over rolling terrain.
40.025	Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">           T54N R76W            S 34            1/4 ———            S 3            T53N            1989         </div>

20

Dependent Resurvey, Portion of the South Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS															
80.05	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located in draw, 1.40 chs. wide, drains SW.</p> <p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T54N</td><td>R76W</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2" style="text-align: center;">T53N</td></tr> <tr><td colspan="2" style="text-align: center;">1989</td></tr> </table> </div> <p>Set a steel well casing, 9 ft. long, 4 ins. diam., 3 ft. in the ground alongside the iron post.</p> <p>Cor. is located 2.65 chs. N. of fence extending E. and W.</p> <hr/> <p>S. 88° 48' W., bet. secs. 4 and 33.</p> <p>Over gently rolling terrain.</p>	T54N	R76W	S 33	S 34			S 4	S 3			T53N		1989	
T54N	R76W														
S 33	S 34														
S 4	S 3														
T53N															
1989															
40.025	<p>Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate distance, falls in west borrow pit of Echeta Road, 30 lks. wide, bears N. and S.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T54N</td><td>R76W</td></tr> <tr><td>S 33</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2" style="text-align: center;">T53N</td></tr> <tr><td colspan="2" style="text-align: center;">1989</td></tr> </table> </div>	T54N	R76W	S 33		1/4	—	S 4				T53N		1989	
T54N	R76W														
S 33															
1/4	—														
S 4															
T53N															
1989															
80.05	<p>Set two steel fence posts alongside the iron post.</p> <p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p>														

Dependent Resurvey, Portion of the South Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T54N</td><td>R76W</td></tr> <tr><td>S 32</td><td>S 33</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2">T53N</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on E. side of trail road extending N. and S.</p> <hr/> <p>S. 88° 48' W., bet. secs. 5 and 32.</p> <p>Over rolling terrain.</p>	T54N	R76W	S 32	S 33	<hr/>		S 5	S 4	T53N		1989	
T54N	R76W												
S 32	S 33												
<hr/>													
S 5	S 4												
T53N													
1989													
5.60	Wild Horse Creek, 30 lks. wide, course NW.												
40.025	<p>The ¼ sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>S 32</td></tr> <tr><td>1/4 ———</td></tr> <tr><td>S 5</td></tr> <tr><td>1947</td></tr> </table> </div> <p>Add the mks. 1988 to the brass cap and set a steel fence post alongside the iron post.</p> <hr/> <p style="text-align: center;">(Restoring the dependent resurvey executed by Russell C. MacDonald in 1947)</p> <hr/> <p>S. 88° 05' W., beginning new measurement.</p> <p>Over rolling to broken terrain.</p>	S 32	1/4 ———	S 5	1947								
S 32													
1/4 ———													
S 5													
1947													
1.70	Burlington Northern Railroad, bears SSE. and NNW.												
20.20	Ridge, bears N. and S.												
32.60	Ridge, bears SE. and NW.												

Dependent Resurvey, Portion of the South Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS													
39.06	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T54N</td><td>R76W</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">T53N</td></tr> <tr><td colspan="2">1947</td></tr> </table> </div> <hr/> <p style="text-align: center;">Dependent Resurvey of the East Boundary, T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Mortimer N. Grant in 1883 and the subsequent retracement by Charles Holcomb in 1883)</p> <hr/> <p>From the cor. of Tps. 53 and 54 N., Rs. 75 and 76 W. N. 0° 21' W., bet. secs. 31 and 36. Over gently rolling terrain.</p>	T54N	R76W	S 31	S 32			S 6	S 5	T53N		1947	
T54N	R76W												
S 31	S 32												
S 6	S 5												
T53N													
1947													
40.02	<p>Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T54N</td><td></td></tr> <tr><td>R76W</td><td>R75W</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 36</td><td>S 31</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T54N		R76W	R75W			S 36	S 31	1989			
T54N													
R76W	R75W												
S 36	S 31												
1989													
60.03	<p>Point for the N. 1/16 sec. cor. of secs. 31 and 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T54N</td><td></td></tr> <tr><td>R76W</td><td>R75W</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>N1/16</td><td></td></tr> <tr><td>S 36</td><td>S 31</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div>	T54N		R76W	R75W			N1/16		S 36	S 31	1989	
T54N													
R76W	R75W												
N1/16													
S 36	S 31												
1989													

Dependent Resurvey of the East Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set a steel fence post alongside the iron post.</p>												
72.10	<p>Middle Prong Wild Horse Creek, 5 lks. wide, course W.</p>												
80.04	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T54N</td></tr> <tr><td>R76W</td><td>R75W</td></tr> <tr><td style="border-right: 1px solid black;">S 25</td><td>S 30</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black;">S 36</td><td>S 31</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 85 lks. S. of abandoned fence extending E. and W.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 0° 21' W., bet. secs. 25 and 30.</p> <p>Over nearly level terrain.</p>	T54N		R76W	R75W	S 25	S 30			S 36	S 31	1989	
T54N													
R76W	R75W												
S 25	S 30												
S 36	S 31												
1989													
35.00	<p>Middle Prong Road, 30 lks. wide, bears SE. and NW.</p>												
40.02	<p>The ¼ sec. cor. of secs. 25 and 30, determined at intersection of fence scars extending N., S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T54N</td></tr> <tr><td>R76W</td><td>R75W</td></tr> <tr><td style="border-right: 1px solid black;">1/4</td><td></td></tr> <tr><td style="border-right: 1px solid black;">S 25</td><td>S 30</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 30%; margin: 10px auto;"/>	T54N		R76W	R75W	1/4		S 25	S 30	1989			
T54N													
R76W	R75W												
1/4													
S 25	S 30												
1989													

Dependent Resurvey of the East Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 0° 24' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
20.055	<p>Point for the N. 1/16 sec. cor. of secs. 25 and 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W R75W N1/16 S 25   S 30 1989</p> <p>Set a steel fence post alongside the iron post.</p>
40.11	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W R75W S 24   S 19 ----- S 25   S 30 1989</p> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p>N. 0° 24' E., bet. secs. 19 and 24.</p> <p>Over rolling to broken terrain.</p>
40.11	<p>Point for the ¼ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W R75W 1/4 S 24   S 19 1989</p>

Dependent Resurvey of the East Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the iron post.
60.165	Point for the N. 1/16 sec. cor. of secs. 19 and 24.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R76W R75W N1/16 S 24   S 19 1989</p>
	Set a steel fence post alongside the iron post.
80.22	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R76W R75W S 13   S 18 ----- S 24   S 19 1989</p>
	Set a steel fence post alongside the iron post.
	N. 0° 24' E., bet. secs. 13 and 18.
	Over rolling to broken terrain.
40.11	Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R76W R75W 1/4 S 13   S 18 1989</p>
	Set a steel fence post alongside the iron post.

Dependent Resurvey of the East Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
51.60	Spur, slopes E.
60.165	Point for the N. 1/16 sec. cor. of secs. 13 and 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R76W R75W N1/16 S 13   S 18 1989</p>
	Set a steel fence post alongside the iron post.
80.22	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R76W R75W S 12   S 7 ----- S 13   S 18 1989</p>
	Set a steel fence post alongside the iron post.
	N. 0° 24' E., bet. secs. 7 and 12.
	Over rolling to broken terrain.
20.055	Point for the S. 1/16 sec. cor. of secs. 7 and 12.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R76W R75W S1/16 S 12   S 7 1989</p>
	Set a steel fence post alongside the iron post.

Dependent Resurvey of the East Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.11	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W R75W 1/4 S 12   S 7 1989</p> <p>Set a steel fence post alongside the iron post.</p>
60.165	<p>Point for the N. 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W R75W N1/16 S 12   S 7 1989</p> <p>Set a steel fence post alongside the iron post.</p>
80.22	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W R75W S 1   S 6 <hr/>S 12   S 7 1989</p> <p>Set a steel fence post alongside the iron post and raise a mound of stone, 3½ ft. base, 1½ ft. high, W. of the cor.</p> <hr/> <p>N. 0° 24' E., bet. secs. 1 and 6.</p> <p>Over rolling to broken terrain.</p>

Dependent Resurvey of the East Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.055	<p>Point for the S. 1/16 sec. cor. of secs. 1 and 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W R75W S 1/16 S 1   S 6 1989</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located along E. edge of draw, drains NW.</p>
40.11	<p>Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W R75W 1/4 S 1   S 6 1989</p> <p>Set a steel fence post alongside the iron post.</p>
58.60	<p>Larey Draw, drains SW.</p>
60.165	<p>Point for the N. 1/16 sec. cor. of secs. 1 and 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R76W R75W N1/16 S 1   S 6 1989</p> <p>Set a steel fence post alongside the iron post.</p>
80.22	<p>The cor. of Tps. 54 and 55 N., Rs. 75 and 76 W., monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with unmkd. sandstone fragments alongside, in fence scar extending E. and W., with brass cap mkd.</p>

Dependent Resurvey of the East Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	<div style="text-align: center; margin-bottom: 10px;"> <p>T55N R76W R75W S 36   S 31 ----- S 1   S 6 T54N LS 538 1973</p> </div> <p>This position is accepted as the best available evidence of the original cor. position.</p> <p>Cor. is located 30 lks. W. of fence extending irregularly N. and S.</p> <hr/> <div style="text-align: center; margin-bottom: 10px;"> <p>Dependent Resurvey of the North Boundary, T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming</p> </div> <hr/> <div style="text-align: center; margin-bottom: 10px;"> <p>(Restoring the survey executed by Charles Holcomb in 1883)</p> </div> <hr/> <p>From the cor. of Tps. 54 and 55 N., Rs. 75 and 76 W.</p> <p>S. 88° 01' W., bet. secs. 1 and 36.</p> <p>Over rolling terrain.</p> <p>40.36 The ¼ sec. cor. of secs. 1 and 36, determined at intersection of fences extending S., E. and W., with a sandstone, 16x14x3 ins., no mks. visible, lying loose alongside. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 10px;"> <p>T55N R76W S 36 1/4 ——— S 1 T54N 1989</p> </div> <p>Bury the unmkd. sandstone alongside the iron post.</p> <hr/>
--------	---

20

Dependent Resurvey of the North Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<p>S. 88° 00' W., beginning new measurement.</p> <p>Over gently rolling terrain, along fence.</p>												
40.32	<p>The cor. of secs. 1, 2, 35 and 36, determined at cor. of fences extending N. and E. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T55N</td><td>R76W</td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">T54N</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div> <hr/>	T55N	R76W	S 35	S 36			S 2	S 1	T54N		1989	
T55N	R76W												
S 35	S 36												
S 2	S 1												
T54N													
1989													
	<p>S. 88° 02' W., bet. secs. 2 and 35.</p> <p>Over gently rolling terrain.</p>												
17.60	<p>U.S. Highway No. 14-16, 33 lks. wide, bears NE. and SW.</p>												
40.32	<p>The ¼ sec. cor. of secs. 2 and 35, determined at single fence post with sandstone fragments alongside, in dim fence scar extending W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T55N</td><td>R76W</td></tr> <tr><td>S 35</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">T54N</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div> <p>Set steel fence post alongside the iron post.</p> <hr/>	T55N	R76W	S 35		1/4	—	S 2		T54N		1989	
T55N	R76W												
S 35													
1/4	—												
S 2													
T54N													
1989													

Dependent Resurvey of the North Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS													
	S. 87° 57' W., beginning new measurement.												
	Over rolling terrain.												
40.36	<p>The cor. of secs. 2, 3, 34 and 35, remonumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, in fence extending E. and W., with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T55N R76W</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2">T54N R76W</td> </tr> <tr> <td colspan="2">LS 538 1973</td> </tr> </table>	T55N R76W		S 34	S 35	-----		S 3	S 2	T54N R76W		LS 538 1973	
T55N R76W													
S 34	S 35												
-----													
S 3	S 2												
T54N R76W													
LS 538 1973													
	<p>This monumentation is filed with the Campbell County Clerk on a Certified Land Corner Recordation, and is accepted as a careful and faithful perpetuation of the original cor. recovered by Campbell County Surveyor Jesse E. Spielman during his survey of Miller Road in 1921.</p>												
	<p>Cor. is located 1.70 chs. W. of cor. of fences extending S. and W.</p>												
	<hr/> <p>S. 88° 07' W., bet. secs. 3 and 34.</p>												
	Over nearly level terrain, leaving fence.												
40.205	<p>Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T55N R76W</td> </tr> <tr> <td colspan="2">S 34</td> </tr> <tr> <td>1/4</td> <td>-----</td> </tr> <tr> <td colspan="2">S 3</td> </tr> <tr> <td colspan="2">T54N</td> </tr> <tr> <td colspan="2">1989</td> </tr> </table>	T55N R76W		S 34		1/4	-----	S 3		T54N		1989	
T55N R76W													
S 34													
1/4	-----												
S 3													
T54N													
1989													
	Set a steel fence post alongside the iron post.												
	<p>Cor. is located 5 lks. E. of newly constructed fence extending N. and S.</p>												

Dependent Resurvey of the North Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS													
80.41	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an aluminum rod, 24 ins. long, 5/8 in. diam., 18 ins. below the surface of the ground, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T55N</td> <td>R76W</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T54N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> </div> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 62¼° W., 128.5 lks. dist., with brass cap mkd. RM T54N R76W S4 84.8 FT. TO COR 1989 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 63° W., 113 lks. dist., with brass cap mkd. RM T55N R76W S33 74.6 FT. TO COR 1989 and an arrow pointing to the cor.</p> <p>Reference monuments are located along E. edge of trail road extending N. and S.</p> <hr/> <p>S. 88° 07' W., bet. secs. 4 and 33.</p> <p>Over rolling terrain.</p>	T55N	R76W	S 33	S 34			S 4	S 3	T54N		1989	
T55N	R76W												
S 33	S 34												
S 4	S 3												
T54N													
1989													
40.205	<p>Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an aluminum rod, 24 ins. long, 5/8 in. diam., 18 ins. below the surface of the ground, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T55N</td> <td>R76W</td> </tr> <tr> <td>S 33</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 4</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">T54N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> </div>	T55N	R76W	S 33		1/4	—	S 4		T54N		1989	
T55N	R76W												
S 33													
1/4	—												
S 4													
T54N													
1989													

Dependent Resurvey of the North Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set a steel fence post above the aluminum rod.</p>												
80.41	<p>Point for the cor. of secs. 4, 5, 32 and 33, determined latitudinally by proportionate measurement and longitudinally by a fence extending N. and S., there is no remaining evidence of the original monument. The pile of stones referred to in a metes and bounds legal description in U.S. District Court Case No. 5730, of record in Civil Appearance Docket Book 19, page 119, Office of Clerk of District Court, Sheridan County, Wyoming, as being shown on Plan and Profile Sheet No. 9, State Highway Federal Aid Project No. 206B, and as being the cor. common to secs. 4, 5, 32 and 33, Tps. 54 and 55 N., Rs. 76 W., was found loose and scattered nearby, disturbed by highway construction and fence rebuilding.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T55N R76W</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> <tr> <td colspan="2">-----</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td colspan="2">T54N</td> </tr> <tr> <td colspan="2">1989</td> </tr> </table> </div>	T55N R76W		S 32	S 33	-----		S 5	S 4	T54N		1989	
T55N R76W													
S 32	S 33												
-----													
S 5	S 4												
T54N													
1989													
	<p>S. 88° 07' W., bet. secs. 5 and 32.</p> <p>Over gently rolling terrain.</p>												
4.90	<p>U.S. Highway No. 14-16, 45 lks. wide, bears ESE. and WNW.</p>												
41.88	<p>Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance, falls in hay meadow; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T55N R76W</td> </tr> <tr> <td colspan="2">S 32</td> </tr> <tr> <td colspan="2">1/4 ———</td> </tr> <tr> <td colspan="2">S 5</td> </tr> <tr> <td colspan="2">T54N</td> </tr> <tr> <td colspan="2">1989</td> </tr> </table> </div>	T55N R76W		S 32		1/4 ———		S 5		T54N		1989	
T55N R76W													
S 32													
1/4 ———													
S 5													
T54N													
1989													
62.82	<p>Set a steel fence post alongside the iron post.</p> <p>Point for the W. 1/16 sec. cor. of secs. 5 and 32.</p>												

Dependent Resurvey of the North Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T55N R76W S 32 W1/16—— S 5 T54N 1989</p>
	Set a steel fence post alongside the iron post.
	Cor. is located 20 lks. W. of wash, 5 lks. wide, drains S.
73.70	Sheridan County Road No. 40, 30 lks. wide, bears SE. and NW.
83.76	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance, falls on S. slope of U.S. Highway No. 14-16, extending ENE. and WSW.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T55N R76W S 31   S 32 ——— ——— S 6   S 5 T54N 1989</p>
	from which
	<p style="text-align: center;">A Wyoming State Highway Dept. right-of-way monument, bears N. 57¾° E., 80.8 lks. dist. a brass tablet, 3 ins. diam., seated in a concrete post, 6 ins. square, projecting 4 ins. above the ground, mkd. STA 451+50.00 EL 3899.96 150.</p>
	Set a steel fence post alongside the iron post.
	S. 88° 07' W., bet. secs. 6 and 31.
	Over rolling terrain.
41.88	Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey of the North Boundary,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T55N R76W S 31 1/4 — S 6 T54N 1989</p>
	Set a steel fence post alongside the iron post.
	Cor. is located 6 lks. N. of south right-of-way fence of U.S. Highway No. 14-16.
69.20	U.S. Highway No. 14-16, 45 lks. wide, bears ENE. and WSW.
80.20	The cor. of Tps. 54 and 55 N., Rs. 76 and 77 W.
<hr/> <p>Dependent Resurvey, Portion of the Subdivisional Lines, T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming</p> <hr/>	
<p>(Restoring the survey executed by Charles Holcomb in 1883)</p> <hr/>	
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.
	N. 0° 06' W., bet. secs. 35 and 36.
	Over rolling terrain.
39.855	Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R76W 1/4 S 35   S 36 1989</p>
	Set a steel fence post alongside the iron post.

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>Cor. is located N. 71° W., 2.67 chs. dist., from an intersection of fences extending N., S. and W.</p>										
79.71	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p>										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T54N R76W</td> </tr> <tr> <td style="text-align: center;">S 26</td> <td style="text-align: center;">S 25</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 35</td> <td style="text-align: center;">S 36</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table>	T54N R76W		S 26	S 25	-----		S 35	S 36	1989	
T54N R76W											
S 26	S 25										
-----											
S 35	S 36										
1989											
	<p>Set a steel fence post alongside the iron post.</p>										
	<p>Cor. is located on N. slope of dike extending E. and W.</p>										
	<hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.</p>										
	<p>S. 88° 33' W., bet. secs. 25 and 36.</p>										
	<p>Over gently rolling terrain.</p>										
39.845	<p>Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p>										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T54N R76W</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 25</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 36</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table>	T54N R76W		S 25		1/4	-----	S 36		1989	
T54N R76W											
S 25											
1/4	-----										
S 36											
1989											
	<p>Set a steel fence post alongside the iron post.</p>										
	<p>Cor. is located 30 lks. N. of fence extending E. and W.</p>										
79.69	<p>The cor. of secs. 25, 26, 35 and 36.</p>										
	<hr/> <p>N. 0° 02' W., bet. secs. 25 and 26.</p>										
	<p>Over rolling terrain.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 54 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
36.20	Middle Prong Wild Horse Creek, 5 lks. wide, course NW.
39.855	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R76W 1/4 S 26   S 25 1989</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 90 lks. W. of trail road and 40 lks. E. of overhead power line extending N. and S.</p>
79.71	<p>Point for the cor. of secs. 23, 24, 25 and 26, determined longitudinally in projection of fence from the N., and latitudinally by Middle Prong Road, 30 lks. wide, extending ESE. and W.; there is no remaining evidence of the original monument.</p> <p>At the corner point</p> <p>Set an aluminum rod, 24 ins. long, <math>\frac{5}{8}</math> in. diam., 16 ins. below the surface of the road, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T54N R76W S 23   S 24 ----- S 26   S 25 1989</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., set 24 ins. in the ground, for a reference monument, bears S. <math>41\frac{1}{2}^\circ</math> W., 71.3 lks. dist., with brass cap mkd. RM T54N R76W S26 47.1 FT. TO COR 1989 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., set 24 ins. in the ground, for a reference monument, bears N. <math>45\frac{1}{2}^\circ</math> W., 67.6 lks. dist., with brass cap mkd. RM T54N R76W S23 44.6 FT. TO COR 1989 and an arrow pointing to the cor.</p>