

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
DEPENDENT RESURVEY
OF
THE WEST BOUNDARY
AND PORTIONS OF
THE SOUTH AND NORTH BOUNDARIES
AND SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF CERTAIN SECTIONS,
TOWNSHIP 54 NORTH, RANGE 91 WEST,
OF THE SIXTH PRINCIPAL MERIDIAN,
IN THE STATE OF WYOMING.

EXECUTED BY

JOEL T. EBNER

CADASTRAL SURVEYOR

Under Special Instructions dated JUNE 2, 1998, approved JUNE 3, 1998, and Supplemental Special Instructions dated AUGUST 25, 1999, approved AUGUST 26, 1999 which provided for the surveys included under Group Number 654, and assignment instructions dated JUNE 2, 1998, and AUGUST 26, 1999.

Survey commenced JUNE 9, 1998

Survey completed JUNE 29, 2000

INDEX DIAGRAM

Township 54 North, Range 91 West

16		15				
14	6	45	5	29	4	3
						2
						1
	44		43		29	
				28		
12	7	42	8		9	10
						11
						12
	41		41		28	
11	18	40	17	27	16	19
						15
						14
						13
	39		38		26	
8	19	38	20	25	21	18
						22
						23
						24
	37		36		24	
6	30	35	29	22	28	17
						27
						26
						25
	33		32		21	
5	31	31	32	20	33	34
						35
						36
	4		2			

Subdivision of Section 4.....Page 49
 Subdivision of Section 5.....Page 52
 Subdivision of Section 6.....Page 56
 Subdivision of Section 7.....Page 57
 Subdivision of Section 8.....Page 61
 Subdivision of Section 16.....Page 63
 Subdivision of Section 17.....Page 64
 Subdivision of Section 18.....Page 65
 Subdivision of Section 19.....Page 68
 Subdivision of Section 20.....Page 70
 Subdivision of Section 21.....Page 73
 Subdivision of Section 28.....Page 76
 Subdivision of Section 29.....Page 79
 Subdivision of Section 30.....Page 82
 Subdivision of Section 31.....Page 86
 Subdivision of Section 32.....Page 91

T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>The following field notes are those of the dependent resurvey of the west boundary and portions of the south and north boundaries and subdivisional lines, and the subdivision of certain sections, Township 54 North, Range 91 West, Sixth Principal Meridian, Wyoming.</p> <p>John E. Shannon surveyed the north, south and west boundaries and a portion of the subdivisional lines in 1890. Max J. Meyer and Edward F. Stahle retraced the north boundary, portions of the south and west boundaries and a portion of the subdivisional lines and surveyed a portion of the subdivisional lines in 1895. William H. Thorn resurveyed a portion of the south boundary and subdivisional lines in 1901. Frank Motech resurveyed a portion of the subdivisional lines and surveyed an additional portion of the subdivisional lines in 1937. Carl R. Oslund resurveyed a portion of the south boundary and surveyed a portion of the east boundary in 1937. Elmer C. Lenhart dependently resurveyed a portion of the north boundary in 1942. Marvin J. Lytle retraced and resurveyed a portion of the subdivisional lines and surveyed the remainder of the east boundary and the remainder of the subdivisional lines in 1942. Paul D. Dennis and Jack A. Eaves dependently resurveyed a portion of the west boundary in 1959. Paul D. Dennis dependently resurveyed a portion of the south boundary in 1959. Joe N. LaRue dependently resurveyed portions of the north boundary and subdivisional lines in 1967. Richard A. Kohler dependently resurveyed a portion of the subdivisional lines and subdivided section 9 in 1991.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 654, Wyoming, dated June 2, 1998, and the Supplemental Special Instructions for Group No. 654, Wyoming, dated August 26, 1999.</p> <p>Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data was thoroughly verified and only true line field notes are given herein, which refer to the completed survey.</p>
--------	--

T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>The survey was executed with TRIMBLE Model 4700 Global Positioning System (GPS) receivers, a WILD Model T1000 theodolite, WILD Model DI5S electronic distance meter and by chaining methods. The instruments were maintained in proper adjustment at all times. The directions of all lines refer to the true meridian, determined by hour angle observations of the sun at various points along the lines of survey and carried forward by sustained angulation, and by GPS observations.</p> <p>The geographic position of the of cor. of sections 4, 5, 32 and 33, on the S. bdy. of the Tp., based on NAD 83(1993) and determined by Global Positioning System methods, is:</p> <p>Latitude 44° 36' 25.94" N., Longitude 107° 49' 19.16" W.</p> <p>The mean magnetic declination is 13° E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Portion of the South Boundary, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Paul D. Dennis in 1959)</p> <hr/> <p>Beginning at the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above the ground, at cor. of fences extending S. and NW., with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T54N</td> <td style="padding: 0 5px;">R91W</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> </tr> <tr> <td colspan="4" style="text-align: center; padding: 0 5px;">T53N</td> </tr> <tr> <td colspan="4" style="text-align: center; padding: 0 5px;">1959</td> </tr> <tr> <td colspan="4" style="text-align: center; padding: 0 5px;">1967</td> </tr> </table> <p>N. 89° 20' W., bet. secs. 5 and 32.</p> <p>Over rolling and broken terrain.</p> <p>16.00 Red Canyon Creek, course S.</p> <p>19.36 Point for the E. 1/16 sec. cor. of secs. 5 and 32, falls in cultivated field.</p>	T54N	R91W			S 32	S 33			S 5	S 4			T53N				1959				1967			
T54N	R91W																								
S 32	S 33																								
S 5	S 4																								
T53N																									
1959																									
1967																									

Dependent Resurvey, Portion of the South Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. below the surface of the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W</p>
	<p style="text-align: center;">S 32</p>
	<p style="text-align: center;">E1/16 ———</p>
	<p style="text-align: center;">S 5</p>
	<p style="text-align: center;">T53N</p>
	<p style="text-align: center;">2000</p>
	<p>22.10 Fence, bears irregularly NE. and SW.</p>
	<p>22.20 Irrigation ditch, drains SW.</p>
	<p>22.70 Road, gravel surfaced, bears NE. and SW.</p>
	<p>38.72 The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, E. of the cor., with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W</p>
	<p style="text-align: center;">S 32</p>
	<p style="text-align: center;">1/4 ———</p>
	<p style="text-align: center;">S 5</p>
	<p style="text-align: center;">T53N</p>
	<p style="text-align: center;">1959</p>
	<p>N. 89° 28' W., beginning new measurement.</p>
	<p>Over rolling and broken terrain.</p>
	<p>20.02 Point for the W. 1/16 sec. cor. of secs. 5 and 32, falls in cultivated field.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 9 ins. below the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W</p>
	<p style="text-align: center;">S 32</p>
	<p style="text-align: center;">W1/16 ———</p>
	<p style="text-align: center;">S 5</p>
	<p style="text-align: center;">T53N</p>
	<p style="text-align: center;">2000</p>
	<p>24.00 Beaver Creek, course S.</p>

Dependent Resurvey, Portion of the South Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
35.30	Beaver Creek Road, bears SE. and NW.
39.29	<p>The witness cor. to the cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a steel fence post alongside and a mound of stone, 3 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T54N R91W S 31 S 32 ←——— S 6 S 5 T53N 1967 1959</p> <hr style="width: 20%; margin: 10px auto;"/> </div> <p>N. 89° 28' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p>
0.75	<p>True point for the cor. of secs. 5, 6, 31 and 32, on the projection of sec. line from the E., at record dist., falls in creek, course SSE., where it is impracticable to establish a permanent monument.</p> <hr style="width: 100%;"/> <p>N. 89° 28' W., bet. secs. 6 and 31.</p> <p>Over rolling terrain.</p>
40.06	<p>The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R91W S 31 1/4 ——— S 6 T53N 1959</p> </div> <p>Set a fiberglass sign post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 24' W., beginning new measurement.</p> <p>Over rolling terrain.</p>

Dependent Resurvey, Portion of the South Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.175	<p>Point for the W. 1/16 sec. cor. of secs. 6 and 31.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 31 W1/16 ——— S 6 T53N 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
39.48	<p>The cor. of Tps. 53 and 54 N., Rs. 91 and 92 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a mound of stone, 5 ft. base, 1 ft. high, S. of the cor., with brass cap mkd.</p> <p style="text-align: center;">T54N R92W R91W S 36 S 31 ————— S 1 S 6 T53N 1959</p>
<p>Dependent Resurvey of the West Boundary, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p>	
<p>(Restoring the survey executed by Paul D. Dennis and Jack A. Eaves in 1959)</p>	
<p>N. 0° 01' E., on the W. bdy. of sec. 31.</p> <p>Over rolling and broken terrain.</p>	
19.85	<p>Point for the S. 1/16 sec. cor. of sec. 31 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R92W R91W S1/16 S 31 2000</p>

Dependent Resurvey of the West Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located on very steep NE. slope.</p>												
39.70	<p>The 1/4 sec. cor. of sec. 31 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, E. of the cor., with brass cap mkd.</p>												
	<p style="text-align: center;"> <table border="0"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">T54N</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">R91W</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 31</td></tr> <tr><td style="padding-left: 10px;">1959</td></tr> </table> </p>	T54N	R91W	1/4	S 31	1959							
T54N													
R91W													
1/4													
S 31													
1959													
	<p style="text-align: center;">_____</p> <p>N. 1° 41' E., beginning new measurement.</p> <p>Over rolling terrain.</p>												
0.87	<p>The 1/4 sec. cor. of sec. 36 only, T. 54 N., R. 92 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, in a collar of stone, with brass cap mkd.</p>												
	<p style="text-align: center;"> <table border="0"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">T54N</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">R92W</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S36</td></tr> <tr><td style="padding-left: 10px;">1959</td></tr> </table> </p>	T54N	R92W	1/4	S36	1959							
T54N													
R92W													
1/4													
S36													
1959													
40.52	<p>The cor. of secs. 30 and 31 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a mound of stone, 3 ft. base, 2 ft. high, E. of the cor., with brass cap mkd.</p>												
	<p style="text-align: center;"> <table border="0"> <tr><td style="padding-right: 10px;">T54N</td><td style="border-right: 1px solid black; padding-right: 5px;"></td></tr> <tr><td style="padding-right: 10px;">R92W</td><td style="border-right: 1px solid black; padding-right: 5px;">R91W</td></tr> <tr><td style="padding-right: 10px;"></td><td style="border-right: 1px solid black; padding-right: 5px;">S 30</td></tr> <tr><td style="padding-right: 10px;"></td><td style="border-right: 1px solid black; padding-right: 5px;">S 31</td></tr> <tr><td style="padding-right: 10px;">1959</td><td></td></tr> <tr><td style="padding-right: 10px;">1967</td><td></td></tr> </table> </p>	T54N		R92W	R91W		S 30		S 31	1959		1967	
T54N													
R92W	R91W												
	S 30												
	S 31												
1959													
1967													
	<p>N. 0° 41' E., on the W. bdy. of sec. 30.</p> <p>Over rolling terrain.</p>												

Dependent Resurvey of the West Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
0.94	<p>The closing cor. of secs. 25 and 36, T. 54 N., R. 92 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, W. of the cor., with brass cap mkd.</p>
	<p style="text-align: center;">T54N R92W R91W S 25 CC ——— S 36 1959</p>
26.00	<p>Beaver Creek Road, bears SSE. and NNW.</p>
40.87	<p>The 1/4 sec. cor. of sec. 30 only, monumented with a granite stone, 18x12x7 ins., firmly set flush with the ground, plainly mkd. 1/4 on W. face. This position was remonumented by Paul D. Dennis and Jack A. Eaves in 1959. The 1959 monumentation was not recovered. A Certified Land Corner Recordation is filed at the Big Horn County Clerk's Office, by Wesley W. Reid, Wyoming Registered Land Surveyor No. 537 in 1979, attesting the iron post monument was in place at that time, with a side note from William C. Heatley, Wyoming Registered Land Surveyor No. 3510 in 1987, explaining that the iron post monument had been disturbed, with the cap knocked off, but the monument was still in place at that time.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R92W R91W 1/4 S 30 2000</p>
	<p>Bury the original cor. stone alongside the iron post.</p>
	<p>Cor. is located 5 lks. W. of intersection of fences extending N., E. and S.</p>
	<p>N. 0° 26' E., beginning new measurement.</p>
	<p>Over rolling and broken terrain.</p>

Dependent Resurvey of the West Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
0.72	<p>The 1/4 sec. cor. of sec. 25 only, T. 54 N., R. 92 W., bears EAST, 0.01 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set 14 ins. in the ground, bent over and leaning S., with brass cap mkd.</p> <p style="text-align: center;">T54N R92W 1/4 S25 1959</p> <p>Reset the iron post 24 ins. in the ground.</p> <p>Cor. is located 5 lks. W. of intersection of fences extending N., E. and S.</p>
13.10	Creek, course E.
19.81	<p>Point for the N. 1/16 sec. cor. of sec. 30 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R92W R91W N1/16 S 30 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. falls 19 lks. W. of fence extending N. and S.</p>
26.70	Beaver Creek, course ESE.
39.62	<p>True point for the cor. of secs. 19 and 30 only, on the projection of sec. line from the N., at record dist., falls on steep slope, where it is impracticable to establish a permanent monument.</p> <hr/> <p>N. 1° 00' E., on the W. bdy. of sec. 19.</p> <p>Over rolling and broken terrain.</p>
1.50	<p>The witness cor. to the cor. of secs. 19 and 30 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of the West Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R92W R91W WC S 19 ↓ S 30 1959 1967</p> <p>Cor. is located 38 lks. W. of fence extending SSE. and NNW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 00' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
0.31	<p>The closing cor. of secs. 24 and 25, T. 54 N., R. 92 W., bears EAST, 0.04 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R92W R91W S 24 CC ——— S 25 1959</p> <p>Cor. is located 30 lks. W. of fence extending SSE. and NNW.</p>
37.67	<p>The 1/4 sec. cor. of sec. 19 only, at proportionate dist. by method of irregularly boundary adjustment; falls on E. edge of Beaver Creek Road extending N. and S. This position was reestablished by Paul D. Dennis and Jack A. Eaves in 1959. The 1959 monument was found lying loose nearby as filed in the Big Horn County Clerk's Office.</p> <p>Reset the 1959 iron post, 30 ins. long, 2½ ins. diam., 8 ins. below the surface of the road, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W 1/4 S 19 1959</p>

Dependent Resurvey of the West Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 50½° E., 104.2 lks. dist., with brass cap mkd. RM T54N R91W S19 68.8 FT TO COR 2000 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 48½° E., 96.7 lks. dist., with brass cap mkd. RM T54N R91W S19 63.8 FT TO COR 2000 and an arrow pointing to the cor.</p> <p>Cor. is located 25 lks. W. of fence extending N. and S.</p> <p>From this point, the monument set in 1959 for the 1/4 sec. cor. of sec. 24 only, T. 54 N., R. 92 W., bears N. 9° 30' E., 1.68 chs. dist., an iron post, 2½ ins. diam., 30 ins. long, disturbed and lying loose on the ground, in fence extending N. and S., as filed in the Big Horn County Clerk's Office, with brass cap mkd. T54N R92W 1/4 S24 1959.</p> <hr/> <p>N. 0° 48' E., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>20.125 Point for the N. 1/16 sec. cor. of sec. 19 only, falls in Beaver Creek Road extending N. and S.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. below the surface of the road, with brass cap mkd.</p> <p style="text-align: center;">T54N R92W R91W N1/16 S 19 2000</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 49½° E., 111.8 lks. dist., with brass cap mkd. RM T54N R91W S19 73.8 FT TO COR 2000 and an arrow pointing to the cor.</p>
--------	--

Dependent Resurvey of the West Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 43¾° E., 113.2 lks. dist., with brass cap mkd. RM T54N R91W S19 74.7 FT TO COR 2000 and an arrow pointing to the cor.</p> <p>Cor. is located 42 lks. W. of fence extending N. and S.</p> <p>22.10 Leave Beaver Creek Road, bears NE. and S.</p> <p>39.60 Beaver Creek, course SW.</p> <p>40.25 The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T54N</td></tr> <tr><td>R92W</td><td>R91W</td></tr> <tr><td style="border-right: 1px solid black;">S 13</td><td>S 18</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black;">S 24</td><td>S 19</td></tr> <tr><td colspan="2">1959</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>Cor. is located N. 33½° E., 96 lks. dist., from intersection of fences extending N. 8° E. and irregularly E. and W.</p> <hr style="border: 0.5px solid black;"/> <p>N. 0° 50' E., bet. secs. 13 and 18.</p> <p>Ascend, over rolling terrain.</p> <p>15.40 Driveway, dirt surfaced, bears N. and SW.</p> <p>19.84 Point for the S. 1/16 sec. cor. of secs. 13 and 18, falls in driveway, dirt surfaced, extending N. and S.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T54N</td></tr> <tr><td>R92W</td><td>R91W</td></tr> <tr><td colspan="2">S1/16</td></tr> <tr><td style="border-right: 1px solid black;">S 13</td><td>S 18</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Cor. is located 41 lks. W. of fence extending N. and S.</p>	T54N		R92W	R91W	S 13	S 18			S 24	S 19	1959		1967		T54N		R92W	R91W	S1/16		S 13	S 18	1998	
T54N																									
R92W	R91W																								
S 13	S 18																								
S 24	S 19																								
1959																									
1967																									
T54N																									
R92W	R91W																								
S1/16																									
S 13	S 18																								
1998																									

Dependent Resurvey of the West Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.68	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 2½ ins. diam., firmly set flush with the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R92W R91W 1/4 S 13 S 18 1959</p> <p>Cor. is located 14 lks. W. of wooden post, 4 ins. square, firmly set projecting 12 ins. above the ground; 24 lks. W. of irrigation ditch, drains S.; 44 lks. W. of driveway extending N. and S.; and 79 lks. W. of fence extending N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 47' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
39.00	Enter hay field, bears ESE. and WNW.
39.81	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2½ ins. diam., firmly set 10 ins. below the surface of the field, with brass cap mkd.</p> <p style="text-align: center;">T54N R92W R91W S 12 S 7 <hr style="width: 10%; margin: 0 auto;"/> S 13 S 18 1959</p> <p>from which the 1959 bearing object</p> <p style="text-align: center;">A limestone, firmly set, projecting 12x7x6 ins. above the ground, bears S. 55° 33' W., 119 lks. dist., plainly mkd. X on NE. face.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 1° 06' E., on the W. bdy. of sec. 7.</p> <p>Over rolling terrain.</p>
19.935	<p>Point for the S. 1/16 sec. cor. of sec. 7 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the West Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R92W R91W S1/16 S 7 2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located N. 71¼° E., 1.12 chs. dist., from intersection of fences extending E., SSW. and abandoned W.</p>
39.87	<p>The 1/4 sec. cor. of sec. 7 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 11 ins. above the ground, in a collar of stone, in fence extending E. and W., with brass cap mkd.</p> <p style="text-align: center;"> T54N R91W 1/4 S 7 1959</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 1° 00' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
0.65	<p>The 1/4 sec. cor. of sec. 12 only, T. 54 N., R. 92 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor., with brass cap mkd.</p> <p style="text-align: center;">1/4 T54N R91W R92W S12 1959</p>
39.22	<p>The cor. of secs. 6 and 7 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T54N R92W R91W S 6 S 7 1959 1967</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey of the West Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p>	<p>N. 0° 39' E., on the W. bdy of sec. 6.</p> <p>Over rolling and broken terrain.</p> <p>2.07 The closing cor. of secs. 1 and 12, T 54 N., R. 92 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor., with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R92W R91W S 1 CC ——— S 12 1959</p> </div> <p>40.45 The 1/4 sec. cor. of sec. 6 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, with a mound of stone, 3 ft. base, 1½ ft. high, E. of the cor., with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R91W 1/4 S 6 1959</p> <hr style="width: 20%; margin: 10px auto;"/> </div> <p>N. 0° 51' E., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>1.86 The 1/4 sec. cor. of sec. 1 only, T. 54 N., R. 92 W., bears EAST, 0.03 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a mound of stone, 3 ft. base, 1½ ft. high, W. of the cor., with brass cap mkd.</p> <div style="text-align: center;"> <p>1/4 T54N R91W R92W S 1 1959</p> </div> <p>39.24 The cor. of Tps. 54 and 55 N., Rs. 91 and 92 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, with a steel fence post alongside and a mound of stone, 2 ft. base, 1½ ft. high, S. of the cor., with brass cap mkd.</p>
---------------	--

Dependent Resurvey of the West Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>T55N R92W R91W S 36 S 31</p> <hr style="width: 50%; margin: auto;"/> <p>S 1 S 6 T54N 1959 1967</p>
<hr/> <p>Dependent Resurvey, Portion of the North Boundary, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p> <hr/>	
<p>(Restoring the survey executed by Joe N. LaRue in 1967)</p> <hr style="width: 20%; margin: auto;"/>	
<p>From the cor. of secs. 32 and 33 only, T. 55 N., R. 91 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 55 N., R. 91 W., executed concurrently under this same group.</p> <p>N. 89° 29' W., on the S. bdy. of sec. 32.</p> <p>Over rolling and broken terrain.</p>	
4.14	Point for the closing cor. of secs. 4 and 5, T. 54 N., R. 91 W., hereinafter described.
14.00	Road, dirt surfaced, bears SSE. and NNW.
24.13	Point for the E. 1/16 sec. cor. of sec. 5 only, T. 54 N., R. 91 W., hereinafter described.
31.00	South Beaver Creek, course SW.
40.01	The 1/4 sec. cor. of sec. 32 only, T. 55 N., R. 91 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, in fence extending E. and W., with brass cap mkd.
<p>T55N R91W 1/4 S 32</p> <hr style="width: 50%; margin: auto;"/> <p>1967</p>	

Dependent Resurvey, Portion of the North Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS											
	N. 89° 40' W., beginning new measurement. Over broken terrain.										
4.11	Point for the 1/4 sec. cor. of sec. 5 only, T. 54 N., R. 91 W., hereinafter described.										
24.10	Point for the W. 1/16 sec. cor. of sec. 5 only, T. 54 N., R. 91 W., hereinafter described.										
40.15	The cor. of secs. 31 and 32 only, T. 55 N., R. 91 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.										
	<table border="1"> <tr> <td>T55N R91W</td> <td></td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 5</td> </tr> <tr> <td colspan="2" style="text-align: center;">T54N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1967</td> </tr> </table>	T55N R91W		S 31	S 32	S 5		T54N		1967	
T55N R91W											
S 31	S 32										
S 5											
T54N											
1967											
	N. 89° 35' W., on the S. bdy of sec. 31. Over rolling and broken terrain.										
1.20	Road, dirt surfaced, bears N. and S.										
3.94	Point for the closing cor. of secs. 5 and 6, T. 54 N., R. 91 W., hereinafter described.										
13.70	North Beaver Creek, course SE.										
23.78	Point for the E. 1/16 sec. cor. of sec. 6 only, T. 54 N., R. 91 W., hereinafter described.										
38.73	The 1/4 sec. cor. of sec. 31 only, T. 55 N., R. 91 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 11 ins. above the ground, in a collar of stone, with a steel fence post alongside, with brass cap mkd.										
	<table border="1"> <tr> <td>T55N R91W</td> </tr> <tr> <td>1/4 S 31</td> </tr> <tr> <td style="text-align: center;">1967</td> </tr> </table>	T55N R91W	1/4 S 31	1967							
T55N R91W											
1/4 S 31											
1967											

Dependent Resurvey, Portion of the North Boundary,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 89° 43' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>4.89 Point for the 1/4 sec. cor. of sec. 6 only, T. 54 N., R. 91 W., hereinafter described.</p> <p>39.90 The cor. of Tps. 54 and 55 N., Rs. 91 and 92 W.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Portion of the Subdivisional Lines, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Joe N. LaRue in 1967)</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T54N</td><td>R91W</td></tr> <tr><td>S 28</td><td>S 27</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td colspan="2">1967</td></tr> </table> <p>Cor. is located 3 lks. W. of fence extending N. and S.</p> <p>From this point, Big Horn Forest Reserve Boundary Post No. 59, bears S. 2° 07' E., 0.06 chs. dist., monumented with an iron post, 4 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap missing.</p> <p>N. 0° 53' E., bet. secs. 27 and 28.</p> <p>Over rolling terrain.</p> <p>39.98 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post alongside and a mound of stone, 5 ft. base, 3 ft. high, W. of the cor., with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T54N</td><td>R91W</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 28</td><td>S 27</td></tr> <tr><td colspan="2">1967</td></tr> </table> <hr/>	T54N	R91W	S 28	S 27	<hr/>		S 33	S 34	1967		T54N	R91W	1/4		S 28	S 27	1967	
T54N	R91W																		
S 28	S 27																		
<hr/>																			
S 33	S 34																		
1967																			
T54N	R91W																		
1/4																			
S 28	S 27																		
1967																			

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>N. 0° 02' E., beginning new measurement.</p>										
	<p>Over rolling terrain.</p>										
39.99	<p>Big Horn Forest Reserve Boundary Post No. 58, bears EAST, 0.01 chs. dist., monumented with an iron post, 4 ins. diam., firmly set, projecting 9 ins. above the ground, in a collar of stone, with brass cap missing.</p>										
40.07	<p>The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post alongside and a mound of stone, 4 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T54N R91W</td></tr> <tr><td>S 21</td><td>S 22</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 28</td><td>S 27</td></tr> <tr><td colspan="2">1967</td></tr> </table>	T54N R91W		S 21	S 22	-----		S 28	S 27	1967	
T54N R91W											
S 21	S 22										

S 28	S 27										
1967											
	<p>N. 0° 23' W., on the E. bdy. of sec. 21.</p>										
	<p>Over rolling terrain.</p>										
38.99	<p>The 1/4 sec. cor. of sec. 22 only, bears WEST, 0.04 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above the ground, with a mound of stone, 4 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td> 1/4</td></tr> <tr><td> S 22</td></tr> <tr><td> </td></tr> <tr><td>1967</td></tr> <tr><td>1942</td></tr> </table>	1/4	S 22		1967	1942					
1/4											
S 22											
1967											
1942											
40.42	<p>The 1/4 sec. cor. of sec. 21 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground, with a steel fence post alongside and a mound of stone, 4 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T54N R91W</td></tr> <tr><td>1/4</td><td> </td></tr> <tr><td>S 21</td><td> </td></tr> <tr><td colspan="2">1967</td></tr> </table>	T54N R91W		1/4		S 21		1967			
T54N R91W											
1/4											
S 21											
1967											
	<p>N. 0° 13' E., beginning new measurement.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS															
	Over rolling terrain.														
38.58	<p>The closing cor. of secs. 15 and 22, bears EAST, 0.02 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with a mound of stone, 5 ft. base, 3 ft. high, W. of the cor., with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T54N</td><td></td></tr> <tr><td> R91W</td><td></td></tr> <tr><td> S 15</td><td></td></tr> <tr><td> -----</td><td>CC</td></tr> <tr><td> S 22</td><td></td></tr> <tr><td>1967</td><td></td></tr> <tr><td>1942</td><td></td></tr> </table> </div>	T54N		R91W		S 15		-----	CC	S 22		1967		1942	
T54N															
R91W															
S 15															
-----	CC														
S 22															
1967															
1942															
39.88	<p>Big Horn Forest Reserve Boundary Post No. 57, monumented with an iron post, 4 ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with brass cap mkd. U.S. FOREST RESERVE BIG HORN BOUNDARY POST NO. 57 1901.</p>														
39.93	<p>The cor. of secs. 16 and 21 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post alongside and a mound of stone, 3 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T54N R91W</td><td></td></tr> <tr><td> S 16</td><td></td></tr> <tr><td> -----</td><td>S 15</td></tr> <tr><td> S 21</td><td></td></tr> <tr><td>1967</td><td></td></tr> </table> </div>	T54N R91W		S 16		-----	S 15	S 21		1967					
T54N R91W															
S 16															
-----	S 15														
S 21															
1967															
	<p>N. 1° 20' E., on the E. bdy. of sec. 16.</p>														
	Over rolling and broken terrain.														
38.64	<p>The 1/4 sec. cor. of sec. 15 only, bears EAST, 0.04 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with a mound of stone, 5 ft. base, 4 ft. high, E. of the cor., with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td> 1/4</td><td></td></tr> <tr><td> S 15</td><td></td></tr> <tr><td>1967</td><td></td></tr> <tr><td>1942</td><td></td></tr> </table> </div>	1/4		S 15		1967		1942							
1/4															
S 15															
1967															
1942															

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.64	<p>The 1/4 sec. cor. of sec. 16 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W 1/4 S 16 1967</p> <hr style="width: 20%; margin: auto;"/> <p>N. 2° 57' E., beginning new measurement.</p> <p>Over mountainous terrain.</p>
39.13	<p>The closing cor. of secs. 10 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, W. of the cor., with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 10 ----- CC S 15 1967 1942</p>
39.95	<p>The cor. of secs. 9 and 16 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 9 ----- S 10 S 16 1967</p> <p>From this point, Big Horn Forest Reserve Boundary Post No. 56, bears N. 0° 04' E., 3.12 chs. dist., monumented with an iron post, 4 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with brass cap mkd. U.S. FOREST RESERVE BIG HORN BOUNDARY POST NO. 56 1901.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp. N. 0° 35' E., bet. secs. 32 and 33.</p> <p>Over rolling terrain.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.72	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W 1/4 S 32 S 33 1967</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 1° 15' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
39.65	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor. or the cor. monument described in the 1967 field notes.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W S 29 S 28 ----- S 32 S 33 2000</p> <hr style="width: 30%; margin: auto;"/>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89° 59' W., bet. secs. 28 and 33.</p> <p>Over rolling and broken terrain.</p>
40.04	<p>The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground, with a steel fence post in a mound of stone, 3 ft. base, 1 ft. high, N. of the cor., with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W S 28 1/4 ——— S 33 1967</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 89° 36' W., beginning new measurement.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling and broken terrain.
19.455	Point for the W. 1/16 sec. cor. of secs. 28 and 33.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T54N R91W
	S 28
	W1/16 ———
	S 33
	2000
	Set a fiberglass sign post alongside the iron post.
35.40	Road, dirt surfaced, bears NE. and SW.
35.60	Irrigation ditch, flows SW.
38.91	The cor. of secs. 28, 29, 32 and 33.
	N. 0° 47' W., bet. secs. 28 and 29.
	Over gently rolling terrain.
18.00	Red Canyon Creek, course WSW.
19.80	Irrigation ditch, flows WSW.
20.16	Point for the S. 1/16 sec. cor. of secs. 28 and 29.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W
	S1/16
	S 29 S 28
	2000
	Set a fiberglass sign post alongside the iron post.
37.30	Trail road, bears NE. and SW.
40.32	The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 14 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R91W 1/4 S 29 S 28 1967</p> <hr/>
19.98	<p>N. 0° 04' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>The N. 1/16 sec. cor. of secs. 28 and 29, monumented by Sherman B. Allred, Wyoming Professional Engineer and Land Surveyor No. 2920, as filed in the Big horn County Clerk's Office, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. ALLRED PE&LS 2920 54-91 N1/16 S29 S28 1999 DONNELL&ALLRED, with a steel fence post alongside. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W N1/16 S 29 S 28 2000</p> <hr/> <p>Deposit the steel reinforcement rod inside the iron post.</p>
19.98	<p>N. 0° 04' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, with a steel fence post alongside and a mound of stone, 4 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W S 20 S 21 <hr/>S 29 S 28 1967</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89° 57' W., bet. secs. 21 and 28.
	Over rolling terrain.
34.10	Ridge, bears NE. and SW.
36.91	The point erroneously reestablished for the 1/4 sec. cor. of secs. 21 and 28, during the 1967 resurvey, bears SOUTH, 0.06 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 14 ins. above the ground, in a mound of stone, 3 ft. base, to top, as filed in the Big Horn County Clerk's Office, with brass cap mkd. T54N R91W 1/4 S21 S28 1967. Add the mks. AM 2000 and bury in place, 8 ins. below the surface of the ground.
40.16	The 1/4 sec. cor. of secs. 21 and 28, remonumented by Sherman B. Allred, Wyoming Professional Engineer and Land Surveyor No. 2920, as filed in the Big Horn County Clerk's Office, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, in a collar of stone, with aluminum cap mkd. ALLRED PE&LS 2920 54-91 1/4 S21 S28 1999 DONNELL&ALLRED, and with a limestone, 12x9x7 ins., lying loose alongside, plainly mkd. 1/4 on a face. This position is accepted as a careful and faithful perpetuation of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R91W S 21 1/4 ——— S 28 2000</p>
	Bury the original cor. stone alongside and deposit the steel reinforcement rod inside the iron post.
	N. 89° 18' W., beginning new measurement.
	Over rolling terrain.
11.00	Red Canyon Creek, course S.
16.10	Trail road, bears N. and S.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.00	<p>The W. 1/16 sec. cor. of secs. 21 and 28, monumented by Sherman B. Allred, Wyoming Professional Engineer and Land Surveyor No. 2920, as filed in the Big horn County Clerk's Office, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. ALLRED PE&LS 2920 54-91 S21 W1/16 S28 1999 DONNELL&ALLRED, with a steel fence post alongside. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 21 W1/16 ——— S 28 2000</p> <p>Deposit the steel reinforcement rod inside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 19' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
20.00	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>NORTH, bet. secs. 20 and 21.</p> <p>Over rolling terrain.</p>
39.78	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a steel fence post in a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor., with brass cap mkd.</p> <p style="text-align: center;">T54N R91W 1/4 S 20 S 21 1967</p> <hr style="width: 20%; margin: auto;"/> <p>N. 1° 07' E., beginning new measurement.</p> <p>Over rolling terrain.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.09	<p>Point for the N. 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set a brass tablet, 3¼ ins. diam., 3 in. stem, in drill hole of exposed bedrock, with top mkd.</p> <p style="text-align: center;">T54N R91W N1/16 S 20 S 21 2000</p> <p>Set a fiberglass sign post alongside.</p>
40.18	<p>The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2½ ins. diam., firmly set, projecting 20 ins. above the ground, in mound of stone, 5 ft. base, to top, with a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 17 S 16 ----- S 20 S 21 1967</p> <hr/> <p>From the cor. of secs. 16 and 21 only.</p> <p>S. 89° 37' W., bet. secs. 16 and 21.</p> <p>Over rolling terrain.</p>
19.32	<p>Point for the E. 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 16 E1/16 ——— S 21 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located on steep NW. facing slope.</p>
31.30	Red Canyon Creek, course SSE.
32.00	Trail road, bears N. and S.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
38.64	<p>The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 16 1/4 ——— S 21 1967</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 89° 26' W., beginning new measurement.</p>
	<p>Over rolling and broken terrain.</p>
20.31	<p>Point for the W. 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 16 W1/16 ——— S 21 2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p>
40.62	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr style="width: 100%;"/>
	<p>N. 1° 03' E., bet. secs. 16 and 17.</p>
	<p>Over rolling terrain.</p>
39.55	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post in a mound of stone, 3 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.</p> <p style="text-align: center;">T54N R91W 1/4 S 17 S 16 1967</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 1° 12' E., beginning new measurement.</p>