

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS											
	Over rolling terrain.										
39.76	The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2½ ins. diam., as described in the 1991 field notes of the dependent resurvey, T. 54 N., R. 91 W.										
	From the cor. of secs. 9 and 16 only.										
	WEST, bet. secs. 9 and 16.										
	Over rolling and broken terrain.										
0.80	Red Canyon Creek, course SW.										
19.80	Creek, course SSW.										
39.58	The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 2½ ins. diam., as described in the 1991 field notes of the dependent resurvey, T. 54 N., R. 91 W.										
	From the 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 2½ ins. diam., as described in the 1991 field notes of the dependent resurvey, T. 54 N., R. 91 W.										
	N. 2° 04' W., bet. secs. 8 and 9.										
	Over rolling terrain.										
40.39	The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post set in a mound of stone, 3 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T54N R91W</td> </tr> <tr> <td style="text-align: center;">S 5</td> <td style="text-align: center;">S 4</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 8</td> <td style="text-align: center;">S 9</td> </tr> <tr> <td colspan="2" style="text-align: center;">1967</td> </tr> </table>	T54N R91W		S 5	S 4	-----		S 8	S 9	1967	
T54N R91W											
S 5	S 4										

S 8	S 9										
1967											
	From the 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post set in a mound of stone, 3 ft. base, 1 ft. high, N. of the cor., with brass cap mkd.										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R91W S 4 1/4 ——— S 9 1967</p> <p>S. 89° 21' W., bet. secs. 4 and 9.</p> <p>Over mountainous terrain.</p>
2.00	London Ditch, flows S.
3.00	Cedar Creek, drains S.
20.97	<p>Point for the W. 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 4 W1/16 ——— S 9 1998</p> <p>Set a steel fence post alongside the iron post.</p>
41.94	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0° 26' E., bet. secs. 4 and 5.</p> <p>Over mountainous terrain.</p>
19.62	<p>Point for the S. 1/16 sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S1/16 S 5 S 4 1998</p> <p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.24	<p>The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W 1/4 S 5 S 4 1967</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 49' E., beginning new measurement.</p> <p>Over mountainous terrain.</p>
20.94	<p>Point for the N. 1/16 sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W N1/16 S 5 S 4 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
29.40	Fence, bears E. and W.
35.70	Beaver Creek Road, bears NNE. and SSW.
40.60	<p>The original closing cor. of secs. 4 and 5, remonumented in 1967 with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, at cor. of abandoned fences extending E. and S., with brass cap mkd. T55N S32 S4 S5 T54N 1967. Add the mks. AM 1999 and bury in place 6 ins. below the surface of the ground.</p>
40.65	<p>Point for closing cor. of secs. 4 and 5, at intersection with the S. bdy. of sec. 32, T. 55 N., R. 91 W.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R91W S 32 <hr style="width: 10%; margin: auto;"/>S 5 S 4 T54N R91W CC 1999</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From this point, the cor. of secs. 32 and 33 only, T. 55 N., R. 91 W., bears S. 89° 29' E., 4.14 chs. dist.
	From the true point for the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.
	N. 0° 01' E., bet. secs. 31 and 32.
	Over rolling terrain.
8.40	Beaver Creek Road, bears SE. and NW.
16.00	Beaver Creek, course SE.
20.18	Point for the S. 1/16 sec. cor. of secs. 31 and 32.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T54N R91W S1/16 S 31 S 32 2000
	Set a fiberglass sign post alongside the iron post.
38.40	Fence, bears SE. and NW.
40.36	The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with brass cap mkd.
	T54N R91W 1/4 S 31 S 32 1967
	N. 0° 12' W., beginning new measurement.
	Over rolling terrain.
19.61	Point for the N. 1/16 sec. cor. of secs. 31 and 32.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R91W N1/16 S 31 S 32 2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p> <p>From this point, a local monument of unknown origin, bears N. 46° 44' E., 0.22 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 26 ins. above the ground, in a collar of stone, with a steel fence post alongside. This position is not accepted during the course of this survey.</p>
39.22	<p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with a steel fence post alongside, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W S 30 S 29 ----- S 31 S 32 1967</p>
	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89° 15' W., bet. secs. 29 and 32.</p> <p>Over rolling and broken terrain.</p>
6.00	<p>Red Canyon Creek, course SSW.</p>
20.035	<p>Point for the E. 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W S 29 E1/16 ——— S 32 2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p>
21.30	<p>Irrigation ditch, flows SSW.</p>
21.50	<p>Fence, bears NNE. and SSW.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
21.70	Road, bladed dirt, bears NNE. and SSW.
40.07	Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W S 29 1/4 ——— S 32 2000
	Set a fiberglass sign post alongside the iron post.
	From this point, the point erroneously reestablished for the 1/4 sec. cor. of secs. 29 and 32, during the 1967 resurvey, bears N. 70° 20' W., 25 lks. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T54N R91W 1/4 S29 S32 1967. Add the mks. AM 2000 and bury in place, 4 ins. below the surface of the ground.
80.14	The cor. of secs. 29, 30, 31 and 32.
	N. 89° 02' W., bet. secs. 30 and 31.
	Over rolling terrain.
18.99	Point for the E. 1/16 sec. cor. of secs. 30 and 31.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W S 30 E1/16 ——— S 31 2000
	Set a fiberglass sign post alongside the iron post.
	From this point, a local monument of unknown origin, bears S. 84° 57' W., 98 lks. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above the ground, with a steel fence post alongside. This position is not accepted during the course of this survey.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
37.98	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, at intersection of fences extending ESE., W. and NNW., with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 30 1/4 ——— S 31 1967</p> <p>From this point, a local monument of unknown origin, bears S. 83° 18' W., 1.90 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 17 ins. above the ground, in a collar of stone. This position is not accepted during the course of this survey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 54' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
12.30	Beaver Creek, course SSE.
20.67	<p>The W. 1/16 sec. cor. of secs. 30 and 31, monumented by Sherman B. Allred, Wyoming Professional Engineer and Land Surveyor No. 2920, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. ALLRED PE&LS 2920 S30 S31 16 DONNELL&ALLRED. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 30 W1/16 ——— S 31 2000</p> <p>Deposit the steel reinforcement rod inside and set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located N. 86¼° W., 1.70 chs. dist., from intersection of fences extending E., SSE. and NNW.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 88° 57' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
10.20	<p>Beaver Creek Road, bears SE. and NW.</p>
19.55	<p>The cor. of secs. 30 and 31 only, on the W. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 1° 57' E., bet. secs. 29 and 30.</p> <p>Over rolling terrain.</p>
19.865	<p>Point for the S. 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S1/16 S 30 S 29 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
39.73	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, with a steel fence post in a mound of stone, 3 ft. base, 1 ft. high, W. of the cor., with brass cap mkd.</p> <p style="text-align: center;">T54N R91W 1/4 S 30 S 29 1967</p> <hr/> <p>N. 0° 24' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
40.09	<p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post alongside, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T54N R91W S 19 S 20 <hr style="width: 50%; margin: 0 auto;"/> S 30 S 29 1967
	<hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89° 56' W., bet. secs. 20 and 29.</p> <p>Over rolling terrain.</p>
19.93	<p>Point for the E. 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	T54N R91W S 20 E1/16 ——— S 29 2000
	<p>Set a fiberglass sign post alongside the iron post.</p>
39.86	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p>
	T54N R91W S 20 1/4 ——— S 29 1967
	<p>Set a fiberglass sign post alongside the iron post.</p> <hr style="width: 20%; margin: 0 auto;"/>
	<p>N. 89° 14' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
19.01	<p>Point for the W. 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R91W S 20 W1/16 ——— S 29 2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p>
38.02	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/>
	<p>N. 89° 27' W., bet. secs. 19 and 30.</p>
	<p>Over rolling terrain.</p>
39.29	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, with a steel fence post alongside, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W S 19 1/4 ——— S 30 1967</p> <hr/>
	<p>N. 87° 32' W., beginning new measurement.</p>
	<p>Over rolling terrain.</p>
19.70	<p>Fence, bears N. and S.</p>
20.52	<p>Point for the W. 1/16 sec. cor. of secs. 19 and 30.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W S 19 W1/16 ——— S 30 2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p>
39.76	<p>True point for the cor. of secs. 19 and 30 only, on the W. bdy. of the Tp.</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 16' E., bet. secs. 19 and 20.</p> <p>Over rolling and broken terrain.</p>
19.86	<p>Point for the S. 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S1/16 S 19 S 20 2000</p>
39.72	<p>Set a fiberglass sign post alongside the iron post.</p> <p>The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W 1/4 S 19 S 20 1967</p>
	<p>N. 0° 04' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
40.19	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post in a mound of stone, 3 ft. base, 1 ft. high, W. of the cor., with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 18 S 17 ----- S 19 S 20 1967</p>
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89° 57' W., bet. secs. 17 and 20.</p> <p>Over rolling and broken terrain.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.23	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 20 ins. above the ground, supported by a mound of stone, 4 ft. base, to top, with a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 17 1/4 ——— S 20 1967</p> <p>Cor. is located on top of ridge, bears N. and S.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 19' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p>
39.19	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>N. 89° 55' W., bet. secs. 18 and 19.</p> <p>Over rolling and broken terrain.</p>
39.88	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 2½ ins. diam., firmly set, projecting 16 ins. above the ground, supported by a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 18 1/4 ——— S 19 1967</p> <hr/> <p>N. 87° 43' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
20.25	<p>Point for the W. 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T54N R91W S 18 W1/16 ——— S 19 1998
	Set a fiberglass sign post alongside the iron post.
22.50	Beaver Creek Road, gravel surfaced, bears NNE. and SSW.
37.60	Beaver Creek, course SSW.
38.12	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.
	<hr/> From the cor. of secs. 17, 18, 19 and 20. N. 0° 01' W., bet. secs. 17 and 18. Over rolling and broken terrain.
40.04	The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post alongside, with brass cap mkd.
	T54N R91W 1/4 S 18 S 17 1967
	<hr/> N. 0° 01' E., beginning new measurement. Over rolling and broken terrain.
40.08	The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with a steel fence post alongside and a mound of stone, 3 ft. base, 1 ft. high, W. of the cor., with brass cap mkd.
	T54N R91W S 7 S 8 ———— S 18 S 17 1967

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89° 03' W., bet. secs. 8 and 17.</p> <p>Over rolling and broken terrain.</p>
19.98	<p>Point for the E. 1/16 sec. cor. of secs. 8 and 17.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 8 E1/16 ——— S 17 1999</p> <p>Set a fiberglass sign post alongside the iron post.</p>
39.96	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 8 1/4 ——— S 17 1999</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, the point erroneously reestablished for the 1/4 sec. cor. of secs. 8 and 17, during the 1967 resurvey, bears S. 79° 45' W., 21 lks. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. T54N R91W 1/4 S8 S17 1967. Add the mks. AM 1999 and bury in place, 4 ins. below the surface of the ground.</p>
79.92	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 89° 12' W., bet. secs. 7 and 18.</p> <p>Over rolling terrain.</p>
3.50	<p>Cedar Creek, course SW.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
12.40	Beaver Creek Road, bears N. and S.
19.50	Beaver Creek, course SE.
21.63	Point for the E. 1/16 sec. cor. of secs. 7 and 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W S 7 E1/16 ——— S 18 1998
	Set a steel fence post alongside the iron post.
22.10	Irrigation ditch, flows S.
43.26	The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above the ground, in a collar of stone, with brass cap mkd.
	T54N R91W S 7 1/4 ——— S 18 1967
	N. 87° 21' W., beginning new measurement.
	Over rolling terrain.
33.65	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0° 38' E., bet. secs. 7 and 8.
	Over rolling terrain.
0.70	Cedar Creek, course W.
40.28	The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with a steel fence post set in a mound of stone, 3 ft. base, 1 ft. high, W. of the cor., with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R91W 1/4 S 7 S 8 1967</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 0° 08' W., beginning new measurement. Over rolling terrain.</p>
19.835	<p>Point for the N. 1/16 sec. cor. of secs. 7 and 8. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, supported by a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W N1/16 S 7 S 8 2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p>
39.67	<p>The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post set in a mound of stone, 3 ft. base, 1½ ft. high, W. of the cor., with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W S 6 S 5 <hr style="width: 10%; margin: auto;"/> S 7 S 8 1967</p>
	<p>From the cor. of secs. 4, 5, 8 and 9. N. 88° 25' W., bet. secs. 5 and 8. Over rolling terrain.</p>
38.78	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground, in a collar of stone, with a steel fence post alongside, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T54N R91W S 5 1/4 ——— S 8 1967 <hr style="width: 30%; margin: 10px auto;"/>
	N. 89° 53' W., beginning new measurement.
	Over rolling and broken terrain.
20.17	Point for the W. 1/16 sec. cor. of secs. 5 and 8, falls at base of steel fence post, with a mound of stone, 4 ft. base, 2 ft. high, to the E.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W S 5 W1/16 ——— S 8 2000
	Retain the steel fence post and rebuild the mound of stone, 4 ft. base, 2 ft. high, N. of the cor.
40.34	The cor. of secs. 5, 6, 7 and 8.
	S. 89° 50' W., bet. secs. 6 and 7.
	Over rolling and broken terrain.
3.90	South Beaver Creek, course S.
4.40	Beaver Creek Road, bears N. and S.
12.20	Road, bladed dirt, bears SSE. and NNW.
17.00	North Beaver Creek, course SSW.
20.06	Point for the E. 1/16 sec. cor. of secs. 6 and 7.
	Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R91W S 6 El/16 ——— S 7 2000</p>
40.12	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with the bottom portion of a broken sandstone, 14x12X3 ins., firmly set flush with the ground, top portion of broken sandstone, 14x9x3 ins., lying loose alongside, plainly mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S 6 1/4 ——— S 7 1999</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>From this point, the point erroneously reestablished for the 1/4 sec. cor. of secs. 6 and 7, during the 1967 resurvey, bears N. 88° 00' W., 1.22 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. T54N R91W 1/4 S6 S7 1967. Add the mks. AM 1999 and bury in place, 6 ins. below the surface of the ground.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 43' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p>
35.63	<p>The cor. of secs. 6 and 7 only, on the W. bdy. of the Tp.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0° 07' E., bet. secs. 5 and 6.</p> <p>Over rolling and broken terrain.</p>
3.70	<p>South Beaver Creek, course W.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
5.70	Beaver Creek Road, bears E. and W.
20.10	<p>The S. 1/16 sec. cor. of secs. 5 and 6, monumented by William K. Miller, Wyoming Professional Engineer and Land Surveyor No. 2593, with a steel reinforcement rod, 20 ins. long, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. T54 R91W 5 6 S1/16 2593, with a steel fence post alongside. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W S1/16 S 6 S 5 2000</p> <p>Deposit the steel reinforcement rod inside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 07' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
19.30	Abandoned road, bears SSE. and NNW.
20.09	<p>The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, with a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W 1/4 S 6 S 5 1967</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 08' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
27.10	Road, dirt surfaced, bears NNE. and SSW.
39.12	<p>The closing cor. of secs. 5 and 6, at intersection with the S. bdy. of sec. 31, T. 55 N., R. 91 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post alongside, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T55N R91W S 31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 6 S 5 C C T54N 1967</p> <p>From this point, the cor. of secs. 31 and 32 only, T. 55 N., R. 91 W., bears S. 89° 35' E., 3.94 chs. dist.</p> <hr/> <p>The 1/4 sec. cor. of sec. 5 only, T. 54 N., R. 91 W., is at midpoint on the N. bdy. of sec. 5, monumented with an iron post, 2½ ins. diam., loosely set, projecting 12 ins. above the ground, leaning SW. on steep S. facing slope, with brass cap mkd.</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 5 T54N R91W 1967</p> <p>Reset the iron post 14 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base, to top.</p> <p>From this point, the 1/4 sec. cor. of sec. 32 only, T. 55 N., R. 91 W., bears S. 89° 40' E., 4.11 chs. dist.</p> <hr/> <p>The point for the E. 1/16 sec. cor. of sec. 5 only, T. 54 N., R. 91 W., is at midpoint bet. the closing cor. of secs. 4 and 5 and the 1/4 sec. cor. of sec. 5 only, on the N. bdy. of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R91W</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">E1/16 S 5 T54N R91W 2000</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of the cor.</p> <p>Cor. is located 37 lks. S. of fence extending irregularly E. and W.</p>
--------	--

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS

From this point, the 1/4 sec. cor. of sec. 32 only, T. 55 N., R. 91 W., bears N. 89° 29' W., 15.88 chs. dist.

The point for the W. 1/16 sec. cor. of sec. 5 only, T. 54 N., R. 91 W., is at midpoint bet. the closing cor. of secs. 5 and 6 and the 1/4 sec. cor. of sec. 5 only, on the N. bdy. of sec. 5.

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base, to top, with brass cap mkd.

T55N R91W

W1/16 S 5
T54N R91W
2000

Set a fiberglass sign post alongside the iron post.

From this point, the cor. of secs. 31 and 32 only, T. 55 N., R. 91 W., bears N. 89° 40' W., 16.05 chs. dist.

The point for the 1/4 sec. cor. of sec. 6 only, T. 54 N., R. 91 W., is at proportionate distance on the N. bdy. of sec. 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T55N R91W

1/4 S 6
T54N R91W
1999

Set a steel fence post alongside the iron post.

From this point, the point erroneously reestablished for the 1/4 sec. cor. of sec. 6 only, during the 1967 resurvey, bears N. 87° 50' E., 1.61 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. 1/4 S6 T54N R91W 1967. Add the mks. AM 1999 and bury in place, 6 ins. below the surface of the ground.

From this same point, the 1/4 sec. cor. of sec. 31 only, T. 55 N., R. 91 W., bears S. 89° 43' E., 4.89 chs. dist.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>The point for the E. 1/16 sec. cor. of sec. 6 only, T. 54 N., R. 91 W., is at midpoint bet. the closing cor. of secs. 5 and 6 and the 1/4 sec. cor. of sec. 6 only, on the N. bdy. of sec. 6.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R91W</p>
	<p style="text-align: center;">E1/16 S 6</p>
	<p style="text-align: center;">T54N R91W</p>
	<p style="text-align: center;">2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p>
	<p>From this point, the 1/4 sec. cor. of sec. 31 only, T. 55 N., R. 91 W., bears N. 89° 35' W., 14.95 chs. dist.</p>
	<p style="text-align: center;">Subdivision of Section 4, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p>
	<p>From the 1/4 sec. cor. of secs. 4 and 9.</p>
	<p>N. 1° 14' W., on the N. and S. center line of sec. 4.</p>
	<p>Over rolling and broken terrain.</p>
19.61	<p>Point for the center S. 1/16 sec. cor. of sec. 4.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W</p>
	<p style="text-align: center;">C</p>
	<p style="text-align: center;">S1/16 S 4</p>
	<p style="text-align: center;">C</p>
	<p style="text-align: center;">1998</p>
	<p>Set a steel fence post alongside the iron post.</p>
22.00	<p>Cedar Creek, drains SSW.</p>
36.70	<p>Fence, bears NNE. and SSW.</p>
39.22	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line.</p>

Subdivision of Section 4,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W
	C1/4 S 4
	1998
	Set a steel fence post alongside the iron post.
78.50	Fence, bears irregularly NE. and SW.
78.81	Point for the 1/4 sec. cor. of sec. 4 only, on the N. bdy. of the Tp., determined SOUTH, 1.00 ch. dist. from the point erroneously established for the 1/4 sec. cor. of sec. 4 during the 1967 resurvey. This method of restoration was determined to be the most applicable to reestablish the cor. position.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R91W
	1/4 S 4
	T54N R91W
	1998
	Set a steel fence post alongside the iron post.
	From this point, the point erroneously established for the 1/4 sec. cor. of sec. 4, during the 1967 resurvey, bears NORTH, 1.00 ch. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. 1/4 S4 T54N R91W 1967. Add the marks AM 1998 on the brass cap and bury in place, 6 ins. below the surface of the ground.
	From this same point, the 1/4 sec. cor. of sec. 33 only, T. 55 N., R. 91 W., bears S. 88° 59' E., 4.55 chs. dist., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey of a portion of T. 55 N., R. 91 W., executed concurrently under this same group.
	From the 1/4 sec. cor. of sec. 4 only, on the E. bdy. of sec. 4, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with a steel fence post set in a mound of stone, 3 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.

Subdivision of Section 4,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T54N R91W 1/4 S 4 1967
	S. 89° 24' W., on the E. and W. center line of sec. 4. Over steep and broken terrain.
33.00	Cedar Creek, drains SSW.
39.80	The center 1/4 sec. cor. of sec. 4.
50.30	Fence, bears N. and S.
51.40	London Ditch, flows S.
51.70	Trail Road, bears N. and S.
60.21	Point for the center W. 1/16 sec. cor. of sec. 4. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W W1/16 C———C S 4 1998
	Set a steel fence post alongside the iron post.
80.62	The 1/4 sec. cor. of secs. 4 and 5.
	From the W. 1/16 sec. cor. of secs. 4 and 9. N. 0° 24' W. on the N. and S. center line of the SW¼ of sec. 4. Over steep and rolling terrain.
19.62	Point for the SW. 1/16 sec. cor. of sec. 4, at intersection with the E. and W. center line of the SW¼. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 4,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T54N R91W
	SW1/16 S 4
	1998
	Set a steel fence post alongside the iron post.
39.24	The center W. 1/16 sec. cor. of sec. 4.
	From the center S. 1/16 sec. cor. of sec. 4.
	S. 89° 22' W., on the E. and W. center line of the SW¼ of sec. 4.
	Over steep and rolling terrain.
1.00	Cedar Creek, drains SSW.
10.00	London Ditch, flows SSE.
20.69	The SW. 1/16 sec. cor. of sec. 4.
41.38	The S. 1/16 sec. cor. of secs. 4 and 5.
	Subdivision of Section 5, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming
	From the 1/4 sec. cor. of secs. 5 and 8.
	N. 0° 15' W., on the N. and S. center line of sec. 5.
	Over rolling and broken terrain.
19.605	Point for the center S. 1/16 sec. cor. of sec. 5.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T54N R91W
	C
	S1/16 S 5
	C
	2000
	Set a fiberglass sign post alongside the iron post.

Subdivision of Section 5,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.21	<p>Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W</p> <p style="text-align: center;">C1/4 S 5</p> <p style="text-align: center;">2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
56.80	Beaver Creek Road, bears NE. and SW.
59.55	<p>Point for the center N. 1/16 sec. cor. of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W</p> <p style="text-align: center;">C</p> <p style="text-align: center;">N1/16 S 5</p> <p style="text-align: center;">C</p> <p style="text-align: center;">2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
70.00	Beaver Creek, course WSW.
79.16	The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.
	<hr/> <p>From the 1/4 sec. cor. of secs. 4 and 5.</p> <p>N. 88° 29' W., on the E. and W. center line of sec. 5.</p> <p>Over rolling and broken terrain.</p>
19.62	<p>Point for the center E. 1/16 sec. cor. of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W</p> <p style="text-align: center;">E1/16</p> <p style="text-align: center;">C ——— C</p> <p style="text-align: center;">S 5</p> <p style="text-align: center;">2000</p>

Subdivision of Section 5,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a fiberglass sign post alongside the iron post.
39.24	The center 1/4 sec. cor. of sec. 5.
53.80	Beaver Creek Road, bears NNE. and SSW.
56.00	Beaver Creek, course S.
59.28	Point for the center W. 1/16 sec. cor. of sec. 5.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R91W W1/16 C———C S 5 2000</p>
	Set a fiberglass sign post alongside the iron post.
79.32	The 1/4 sec. cor. of secs. 5 and 6.
	<hr/> <p>From the center E. 1/16 sec. cor. of sec. 5.</p> <p>N. 0° 17' E. on the N. and S. center line of the NE¼ of sec. 5.</p> <p>Over rolling terrain.</p>
20.64	Point for the NE. 1/16 sec. cor. of sec. 5, at intersection with the E. and W. center line of the NE¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R91W NE1/16 S 5 2000</p>
	Set a fiberglass sign post alongside the iron post.
32.90	Beaver Creek Road, bears E. and W.
40.30	The E. 1/16 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.
	<hr/>

Subdivision of Section 5,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the N. 1/16 sec. cor. of secs. 4 and 5. N. 89° 22' W., on the E. and W. center line of the NE¼ of sec. 5. Over rolling terrain.</p>
19.81	The NE. 1/16 sec. cor. of sec. 5.
37.30	Beaver Creek Road, bears NE. and SW.
39.62	The center N. 1/16 sec. cor. of sec. 5.
	<hr/> <p>From the W. 1/16 sec. cor. of secs. 5 and 8. N. 0° 04' W. on the N. and S. center line of the SW¼ of sec. 5. Over rolling and broken terrain.</p>
19.85	<p>Point for the SW. 1/16 sec. cor. of sec. 5, at intersection with the E. and W. center line of the SW¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W</p> <p style="text-align: center;">SW1/16 S 5</p> <p style="text-align: center;">2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p> <p>From this point, a local monument of unknown origin, bears N. 37° 04' W., 18 lks. dist., monumented with a steel reinforcement rod, ½ in. diam., firmly set, projecting 4 ins. above the ground. This position is not accepted during the course of this survey.</p>
27.62	A property cor., established by William E. Dickinson, Wyoming Professional Engineer and Land Surveyor No. 637, bears WEST, 15 lks. dist., monumented with a steel reinforcement rod, ½ in. diam., firmly set, projecting 4 ins. above the ground, with red plastic cap mkd. PELS 637.
28.30	Beaver Creek, course WSW.
31.80	Beaver Creek Road, bears ENE. and WSW.

Subdivision of Section 5,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.70	The center W. 1/16 sec. cor. of sec. 5.
	<hr/> From the center S. 1/16 sec. cor. of sec. 5. N. 89° 11' W., on the E. and W. center line of the SW¼ of sec. 5. Over rolling and broken terrain.
20.10	The SW. 1/16 sec. cor. of sec. 5.
28.80	Beaver Creek, course SW.
32.30	Beaver Creek Road, NNE. and SSW.
40.20	The S. 1/16 sec. cor. of secs. 5 and 6.
	<hr/> From the center W. 1/16 sec. cor. of sec. 5. N. 0° 12' W., on the N. and S. center line of the NW¼ of sec. 5. Over rolling and broken terrain.
39.53	The W. 1/16 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.
	<hr/> <p style="text-align: center;">Subdivision of Section 6, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p> <hr/>
	From the 1/4 sec. cor. of secs. 6 and 7. N. 0° 19' E., on the N. and S. center line of sec. 6. Over rolling terrain.
40.47	Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, supported by a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T54N R91W
	C1/4 S 6
	2000

Subdivision of Section 6,
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a fiberglass sign post alongside the iron post.
79.69	The 1/4 sec. cor. of sec. 6 only, on the N. bdy. of the Tp.
	From the 1/4 sec. cor. of secs. 5 and 6.
	N. 89° 45' W., on the E. and W. center line of sec. 6.
	Over rolling and broken terrain.
6.00	Road, bladed dirt, bears SSE. and NNW.
8.40	North Beaver Creek, course SSW.
19.99	Point for the center E. 1/16 sec. cor. of sec. 6.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W E1/16 C———C S 6 2000
	Set a fiberglass sign post alongside the iron post.
39.98	The center 1/4 sec. cor. of sec. 6.
75.37	The 1/4 sec. cor. of sec. 6 only, on the W. bdy. of the Tp.
	From the center E. 1/16 sec. cor. of sec. 6.
	N. 0° 05' E., on the N. and S. center line of the NE¼ of sec. 6.
	Over rolling and broken terrain.
39.18	The E. 1/16 sec. cor. of sec. 6 only, on the N. bdy. of the Tp.
	Subdivision of Section 7, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming
	From the 1/4 sec. cor. of secs. 7 and 18.
	N. 2° 29' E., on the N. and S. center line of sec. 7.