

Subdivision of Section 7,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling terrain.
20.61	Point for the center S. 1/16 sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W
	C
	S1/16   S 7
	C
	2000
	Set a fiberglass sign post alongside the iron post.
40.20	Fence, bears E. and W.
41.22	Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W
	C1/4 S 7
	2000
	Set a fiberglass sign post alongside the iron post.
60.87	Point for the center N. 1/16 sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W
	C
	N1/16   S 7
	C
	2000
	Set a fiberglass sign post alongside the iron post.
80.52	The 1/4 sec. cor. of secs. 6 and 7.
	From the 1/4 sec. cor. of secs. 7 and 8.

Subdivision of Section 7,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 89° 37' W., on the E. and W. center line of sec. 7.
	Over rolling and broken terrain.
7.60	Beaver Creek Road, bears SSE. and NNW.
20.96	True point for the center E. 1/16 sec. cor. of sec. 7, falls in Beaver Creek, course NNE., where it is impracticable to establish a permanent monument.
21.40	Beaver Creek, course SSE.
23.29	Point selected for the witness cor. to the center E. 1/16 sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, supported by a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">WC T54N R91W E1/16 C———C —→ S 7 2000</p>
	Set a fiberglass sign post alongside the iron post.
	Cor. is located on ridge extending SSE. and NNW., 23 lks. N. of fence extending E. and W.
41.92	The center 1/4 sec. cor. of sec. 7.
76.54	The 1/4 sec. cor. of sec. 7 only, on the W. bdy. of the Tp.
	<hr/> <p>From the true point for the center E. 1/16 sec. cor. of sec. 7. N. 1° 10' E. on the N. and S. center line of the NE¼ of sec. 7. Over rolling and broken terrain.</p>
18.40	Beaver Creek, course W.
19.74	Point for the NE. 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the NE¼.

Subdivision of Section 7,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, supported by a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T54N R91W
	NE1/16 S 7
	2000
	Set a fiberglass sign post alongside the iron post.
33.00	North Beaver Creek, course ESE.
38.00	North Beaver Creek, course WNW.
39.48	The E. 1/16 sec. cor. of secs. 6 and 7.
	From the N. 1/16 sec. cor. of secs. 7 and 8.
	N. 89° 53' W., on the E. and W. center line of the NE¼ of sec. 7.
	Over rolling and broken terrain.
13.60	Beaver Creek Road, bears NNE. and SSW.
16.90	Beaver Creek, course SSW.
20.51	The NE. 1/16 sec. cor. of sec. 7.
41.02	The center N. 1/16 sec. cor. of sec. 7.
	From the E. 1/16 sec. cor. of secs. 7 and 18.
	N. 1° 33' E., on the N. and S. center line of the SE¼ of sec. 7.
	Over rolling terrain.
7.00	Beaver Creek, course SSE.
32.00	Same Creek, course SSW.
40.74	True point for the center E. 1/16 sec. cor. of sec. 7.
	From the center S. 1/16 sec. cor. of sec. 7.

Subdivision of Section 7,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
34.13	<p>N. 88° 31' W., on the E. and W. center line of the SW<math>\frac{1}{4}</math> of sec. 7. Over rolling terrain.</p> <p>The S. 1/16 sec. cor. of sec. 7 only, on the W. bdy. of the Tp.</p>
<p>Subdivision of Section 8, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p>	
20.01	<p>From the 1/4 sec. cor. of secs. 8 and 17.</p> <p>N. 0° 31' E., on the N. and S. center line of sec. 8. Over rolling and broken terrain.</p> <p>Point for the center S. 1/16 sec. cor. of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W C S1/16   S 8 C 1999</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 7 lks. S. of fence extending E. and W.</p>
20.50	Cedar Creek, course SW.
40.02	<p>Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 16 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W  C1/4 S 8  1999</p> <p>Set a fiberglass sign post alongside the iron post.</p>

Subdivision of Section 8,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
80.52	<p>The 1/4 sec. cor. of secs. 5 and 8.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 9. N. 88° 41' W., on the E. and W. center line of sec. 8. Over rolling and broken terrain.</p>
20.30	<p>Point for the center E. 1/16 sec. cor. of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W E1/16 C———C S 8 1999</p> <p>Set a fiberglass sign post alongside the iron post.</p>
40.60	The center 1/4 sec. cor. of sec. 8.
80.49	<p>The 1/4 sec. cor. of secs. 7 and 8.</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 8 and 17. N. 0° 59' E. on the N. and S. center line of the SE¼ of sec. 8. Over rolling and broken terrain.</p>
19.95	<p>Point for the SE. 1/16 sec. cor. of sec. 8, at intersection with the E. and W. center line of the SE¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W SE1/16 S 8 2000</p> <p>Set a fiberglass sign post alongside the iron post. Cor. is located 11 lks. S. of ridge, bears ENE. and WSW.</p>

Subdivision of Section 8,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, a position established by William E. Dickinson, Wyoming Professional Engineer and Land Surveyor No. 637, bears N. 88° 49' E., 32 lks. dist., monumented with a steel reinforcement rod, ½ in. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with red plastic cap mkd. PELS 637. This position is not accepted as a careful and faithful determination of the cor. position.</p>
27.70	Cedar Creek, course WSW.
39.90	The center E. 1/16 sec. cor. of sec. 8.
	<hr/> <p>From the S. 1/16 sec. cor. of secs. 8 and 9, monumented with an iron post, 2½ ins. diam., as described in the 1991 field notes of the dependent resurvey, T. 54 N., R. 91 W.</p>
	N. 88° 52' W., on the E. and W. center line of the SE¼ of sec. 8.
	Over rolling and broken terrain.
20.14	The SE. 1/16 sec. cor. of sec. 8.
40.28	The center S. 1/16 sec. cor. of sec. 8.
	<hr/> <p style="text-align: center;">Subdivision of Section 16, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p> <hr/>
	From the 1/4 sec. cor. of secs. 16 and 21.
	N. 1° 28' E., on the N. and S. center line of sec. 16.
	Over rolling and broken terrain.
39.93	Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E. and W. center line.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	T54N R91W
	C1/4 S 16
	2000

Subdivision of Section 16,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a fiberglass sign post alongside the iron post.
79.82	The 1/4 sec. cor. of secs. 9 and 16.
	From the 1/4 sec. cor. of sec. 16 only.
	N. 89° 58' W., on the E. and W. center line of sec. 16.
	Over broken terrain.
20.20	Red Canyon Creek, course SSW.
38.54	The center 1/4 sec. cor. of sec. 16.
79.43	The 1/4 sec. cor. of secs. 16 and 17.
	<p style="text-align: center;">Subdivision of Section 17, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p>
	From the 1/4 sec. cor. of secs. 17 and 20.
	N. 0° 35' E., on the N. and S. center line of sec. 17.
	Over rolling terrain.
40.02	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T54N R91W
	C1/4 S 17
	2000
	Set a fiberglass sign post alongside the iron post.
	From this point, an embedded mound of stone, 2 ft. base, with a wood post, 4 ins. square, and location can, lying loose alongside, bears S. 52° 10' W., 2 lks. dist.
79.94	The 1/4 sec. cor. of secs. 8 and 17.

Subdivision of Section 17,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>N. 89° 17' W., on the E. and W. center line of sec. 17.</p> <p>Over rolling and broken terrain.</p>
19.77	<p>Point for the center E. 1/16 sec. cor. of sec. 17.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W E1/16 C———C S 17 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>From this point, a position established by William E. Dickinson, Wyoming Professional Engineer and Land Surveyor No. 637, bears S. 1° 46' W., 5 lks. dist., monumented with a steel reinforcement rod, ½ in. diam., firmly set, projecting 6 ins. above the ground, with red plastic cap mkd. PELS 637. This position is not accepted as a careful and faithful determination of the cor. position.</p>
39.54	The center 1/4 sec. cor. of sec. 17.
79.13	The 1/4 sec. cor. of secs. 17 and 18.
	<hr/> <p>From the center E. 1/16 sec. cor. of sec. 17.</p> <p>N. 0° 53' E., on the N. and S. center line of the NE¼ of sec. 17.</p> <p>Over rolling terrain.</p>
39.84	The E. 1/16 sec. cor. of secs. 8 and 17.
	<hr/> <p style="text-align: center;">Subdivision of Section 18, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 18 and 19.</p> <p>N. 2° 26' W., on the N. and S. center line of sec. 18.</p>

Subdivision of Section 18,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling and broken terrain.
20.33	Point for the center S. 1/16 sec. cor. of sec. 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R91W C S1/16   S 18 C 1998</p>
	Set a steel fence post alongside the iron post.
40.66	Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R91W C1/4 S 18 1998</p>
	Set a steel fence post and a fiberglass sign post alongside the iron post.
42.40	Beaver Creek Road, bears NE. and SW.
48.70	Beaver Creek, course WSW.
79.51	The 1/4 sec. cor. of secs. 7 and 18.
	<hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>N. 89° 06' W., on the E. and W. center line of sec. 18.</p> <p>Over rolling to broken terrain.</p>
20.80	Point for the center E. 1/16 sec. cor. of sec. 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Subdivision of Section 18,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T54N R91W E1/16 C———C S 18 1998
	Set a steel fence post alongside the iron post.
41.60	The center 1/4 sec. cor. of sec. 18.
42.50	Beaver Creek Road, bears NNE. and SSW.
52.30	Beaver Creek, course SW.
60.78	Point for the center W. 1/16 sec. cor. of sec. 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W W1/16 C———C S 18 1998
	Set a steel fence post alongside the iron post.
77.40	The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.
	From the center E. 1/16 sec. cor. of sec. 18.
	N. 1° 11' W., on the N. and S. center line of the NE¼ of sec. 18.
	Over rolling and broken terrain.
18.30	Beaver Creek Road, bears NE. and SW.
24.00	Beaver Creek, course SW.
39.46	The E. 1/16 sec. cor. of secs. 7 and 18.
	From the W. 1/16 sec. cor. of secs. 18 and 19.
	N. 0° 56' W., on the N. and S. center line of the SW¼ of sec. 18.
	Over rolling terrain.

Subdivision of Section 18,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
3.00	Beaver Creek Road, bears NE. and SW.
3.30	Fence, bears NE. and SW.
20.06	Point for the SW. 1/16 sec. cor. of sec. 18, at intersection with the E. and W. center line of the SW $\frac{1}{4}$ .
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a collar of stone, with brass cap mkd.
	T54N R91W
	SW1/16 S 18
	1998
	Set a fiberglass sign post alongside the iron post.
31.00	Beaver Creek, course SW.
40.12	The center W. 1/16 sec. cor. of sec. 18.
	From the center S. 1/16 sec. cor. of sec. 18.
	N. 88° 23' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 18.
	Over rolling and broken terrain.
11.20	Beaver Creek Road, bears NNE. and SSW.
19.71	The SW. 1/16 sec. cor. of sec. 18.
29.00	Beaver Creek, course WSW.
36.96	The S. 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.
	Subdivision of Section 19, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming
	From the 1/4 sec. cor. of secs. 19 and 30.
	N. 0° 16' W., on the N. and S. center line of sec. 19.
	Over rolling and broken terrain.

Subdivision of Section 19,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.11	<p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, supported by a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W C1/4 S 19 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
59.85	<p>Point for the center N. 1/16 sec. cor. of sec. 19.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, supported by a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W C N1/16   S 19 C 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
79.59	<p>The 1/4 sec. cor. of secs. 18 and 19.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20.</p> <p>N. 88° 53' W., on the E. and W. center line of sec. 19.</p> <p>Over rolling to broken terrain.</p>
39.66	<p>The center 1/4 sec. cor. of sec. 19.</p>
60.00	<p>Point for the center W. 1/16 sec. cor. of sec. 19.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W W1/16 C———C S 19 2000</p>

Subdivision of Section 19,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
78.52	<p>The 1/4 sec. cor. of sec. 19 only, on the W. bdy. of the Tp.</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 19. N. 0° 08' W. on the N. and S. center line of the NW¼ of sec. 19. Over gently rolling terrain.</p>
19.95	<p>Point for the NW. 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the NW¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W NW1/16 S 19 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
39.90	<p>The W. 1/16 sec. cor. of secs. 18 and 19.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 19. N. 88° 19' W., on the E. and W. center line of the NW¼ of sec. 19. Over rolling terrain.</p>
20.30	<p>The NW. 1/16 sec. cor. of sec. 19.</p>
38.49	<p>The N. 1/16 sec. cor. of sec. 19 only, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Subdivision of Section 20, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 29. N. 1° 01' E., on the N. and S. center line of sec. 20. Over rolling and broken terrain.</p>
19.99	<p>Point for the center S. 1/16 sec. cor. of sec. 20.</p>

Subdivision of Section 20,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R91W C S1/16   S 20 C 2000</p>
	Set a fiberglass sign post alongside the iron post.
39.98	Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R91W C1/4 S 20 2000</p>
	Set a fiberglass sign post alongside the iron post.
79.95	The 1/4 sec. cor. of secs. 17 and 20.
	From the 1/4 sec. cor. of secs. 20 and 21.
	N. 89° 38' W., on the E. and W. center line of sec. 20.
	Over rolling to broken terrain.
19.58	Point for the center E. 1/16 sec. cor. of sec. 20.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R91W E1/16 C———C S 20 2000</p>
	Set a fiberglass sign post alongside the iron post.
39.16	The center 1/4 sec. cor. of sec. 20.
58.42	Point for the center W. 1/16 sec. cor. of sec. 20.

Subdivision of Section 20,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T54N R91W W1/16 C———C S 20 2000</p>
	Set a fiberglass sign post alongside the iron post.
77.68	The 1/4 sec. cor. of secs. 19 and 20.
	<hr/> <p>From the E. 1/16 sec. cor. of secs. 20 and 29. N. 0° 30' E., on the N. and S. center line of the SE¼ of sec. 20. Over rolling terrain.</p>
39.88	The center E. 1/16 sec. cor. of sec. 20.
	<hr/> <p>From the W. 1/16 sec. cor. of secs. 20 and 29. N. 0° 38' E., on the N. and S. center line of the SW¼ of sec. 20. Over rolling and broken terrain.</p>
19.92	Point for the SW. 1/16 sec. cor. of sec. 20, at intersection with the E. and W. center line of the SW¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R91W  SW1/16 S 20  2000</p>
	Set a fiberglass sign post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high W. of the cor.
39.84	The center W. 1/16 sec. cor. of sec. 20.
	<hr/> <p>From the center S. 1/16 sec. cor. of sec. 20. N. 89° 26' W., on the E. and W. center line of the SW¼ of sec. 20.</p>

Subdivision of Section 20,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Over rolling and broken terrain.</p> <p>19.14 The SW. 1/16 sec. cor. of sec. 20.</p> <p>38.28 The S. 1/16 sec. cor. of secs. 19 and 20.</p> <hr/> <p style="text-align: center;">Subdivision of Section 21, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 28.</p> <p>N. 1° 00' E., on the N. and S. center line of sec. 21.</p> <p>Over rolling and broken terrain.</p> <p>40.33 Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W C1/4 S 21 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located on steep W. slope.</p> <p>51.10 Red Canyon Creek, course WSW.</p> <p>53.90 Trail road, bears NE. and SW.</p> <p>60.19 Point for the center N. 1/16 sec. cor. of sec. 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W C N1/16   S 21 C 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
--------	---

Subdivision of Section 21,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
80.05	The 1/4 sec. cor. of secs. 16 and 21.
	<hr/> <p>From the 1/4 sec. cor. of sec. 21 only, on the E. bdy. of sec. 21.</p> <p>S. 89° 55' W., on the E. and W. center line of sec. 21.</p> <p>Over rolling to broken terrain.</p>
19.59	<p>Point for the center E. 1/16 sec. cor. of sec. 21.</p> <p>Set a brass tablet, 3¼ ins. diam., 3 in. stem, in drill hole of exposed bedrock, with top mkd.</p> <p style="text-align: center;">T54N R91W E1/16 C———C S 21 2000</p> <p>Set a fiberglass sign post alongside.</p>
39.18	The center 1/4 sec. cor. of sec. 21.
47.80	Red Canyon Creek, course SW.
48.50	Trail road, bears N. and S.
59.53	<p>Point for the center W. 1/16 sec. cor. of sec. 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W W1/16 C———C S 21 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
79.88	<p>The 1/4 sec. cor. of secs. 20 and 21.</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 21.</p> <p>N. 0° 36' E., on the N. and S. center line of the NE¼ of sec. 21.</p> <p>Over rolling and broken terrain.</p>

Subdivision of Section 21,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.83	The E. 1/16 sec. cor. of secs. 16 and 21.
	<hr/> From the W. 1/16 sec. cor. of secs. 21 and 28. N. 0° 30' E., on the N. and S. center line of the SW¼ of sec. 21. Over rolling and broken terrain.
40.05	The center W. 1/16 sec. cor. of sec. 21.
	<hr/> From the center W. 1/16 sec. cor. of sec. 21. N. 1° 04' E., on the N. and S. center line of the NW¼ of sec. 21. Over rolling and broken terrain.
19.98	Point for the NW. 1/16 sec. cor. of sec. 21, at intersection with the E. and W. center line of the NW¼.  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">             T54N R91W               NW1/16 S 21               2000           </div> Set a fiberglass sign post alongside the iron post.
39.96	The W. 1/16 sec. cor. of secs. 16 and 21.
	<hr/> From the center N. 1/16 sec. cor. of sec. 21. N. 89° 46' W., on the E. and W. center line of the NW¼ of sec. 21.  Over rolling and broken terrain.
20.33	The NW. 1/16 sec. cor. of sec. 21.
40.66	The N. 1/16 sec. cor. of secs. 20 and 21.
	<hr/>

Subdivision of Section 28,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>N. 0° 23' E., on the N. and S. center line of sec. 28.</p> <p>Over rolling and broken terrain.</p>
40.29	<p>The center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line, monumented by Sherman B. Allred, Wyoming Professional Engineer and Land Surveyor No. 2920, as filed in the Big horn County Clerk's Office, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. ALLRED PE&amp;LS 2920 54-91 C1/4 S28 1999 DONNELL&amp;ALLRED, with a steel fence post alongside. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W</p> <p style="text-align: center;">C1/4 S 28</p> <p style="text-align: center;">2000</p> <p>Deposit the steel reinforcement rod inside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 21' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
19.89	<p>The center N. 1/16 sec. cor. of sec. 28, monumented by Sherman B. Allred, Wyoming Professional Engineer and Land Surveyor No. 2920, as filed in the Big horn County Clerk's Office, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, flush with the ground, in trail road extending NE. and SW., with aluminum cap mkd. ALLRED PE&amp;LS 2920 54-91 CN 1/16 S28 1999 DONNELL&amp;ALLRED, with a steel fence post alongside. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p>

Subdivision of Section 28,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R91W C N1/16   S 28 C 2000</p>
	<p>Deposit the steel reinforcement rod inside the iron post.</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 0° 21' E., beginning new measurement.</p>
	<p>Over rolling terrain.</p>
19.89	<p>The 1/4 sec. cor. of secs. 21 and 28.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 27 and 28.</p>
	<p>N. 89° 33' W., on the E. and W. center line of sec. 28.</p>
	<p>Over rolling terrain.</p>
40.39	<p>The center 1/4 sec. cor. of sec. 28.</p> <hr/>
	<p>N. 89° 34' W., beginning new measurement.</p>
	<p>Over rolling terrain.</p>
19.86	<p>The center W. 1/16 sec. cor. of sec. 28, monumented by Sherman B. Allred, Wyoming Professional Engineer and Land Surveyor No. 2920, as filed in the Big horn County Clerk's Office, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, flush with the ground, in hay field, with aluminum cap mkd. ALLRED PE&amp;LS 2920 54-91 CW 1/16 S28 1999 DONNELL&amp;ALLRED. This position is accepted as a careful and faithful determination of the cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W W1/16 C ——— C S 28 2000</p>

Subdivision of Section 28,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Deposit the steel reinforcement rod inside and set a fiberglass sign post alongside the iron post.</p> <hr/> <p>N. 89° 33' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
13.00	Red Canyon Creek, course S.
15.00	Road, dirt surfaced, bears NE. and SW.
19.86	The 1/4 sec. cor. of secs. 28 and 29.
	<hr/> <p>From the W. 1/16 sec. cor. of secs. 28 and 33.</p> <p>N. 0° 12' W., on the N. and S. center line of the SW¼ of sec. 28.</p> <p>Over rolling terrain.</p>
40.30	The center W. 1/16 sec. cor. of sec. 28.
	<hr/> <p>From the center W. 1/16 sec. cor. of sec. 28.</p> <p>N. 0° 08' E., on the N. and S. center line of the NW¼ of sec. 28.</p> <p>Over nearly level terrain.</p>
19.94	<p>The NW. 1/16 sec. cor. of sec. 28, at intersection with the E. and W. center line of the NW¼, monumented by Sherman B. Allred, Wyoming Professional Engineer and Land Surveyor No. 2920, as filed in the Big horn County Clerk's Office, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, flush with the ground, in hay field, with aluminum cap mkd. ALLRED PE&amp;LS 2920 54-91 NW 1/16 S28 1999 DONNELL&amp;ALLRED, with a steel fence post alongside. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p>
	<p>T54N R91W</p> <p>NW1/16 S 28</p> <p>2000</p>

Subdivision of Section 28,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Deposit the steel reinforcement rod inside the iron post. <hr/>
	N. 0° 09' E., beginning new measurement. Over rolling terrain.
3.00	Red Canyon Creek, course SSW.
10.00	Road, dirt surfaced, bears NNE. and SSW.
19.94	The W. 1/16 sec. cor. of secs. 21 and 28. <hr/>
	From the center N. 1/16 sec. cor. of sec. 28. N. 89° 26' W., on the E. and W. center line of the NW¼ of sec. 28. Over rolling and broken terrain.
19.93	The NW. 1/16 sec. cor. of sec. 28. <hr/>
	N. 89° 26' W., beginning new measurement. Over rolling terrain.
2.20	Red Canyon Creek, course SSE.
4.00	Road, dirt surfaced, bears N. and S.
19.93	The N. 1/16 sec. cor. of secs. 28 and 29. <hr/>
	Subdivision of Section 29, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming <hr/>
	From the 1/4 sec. cor. of secs. 29 and 32. N. 0° 18' W., on the N. and S. center line of sec. 29. Over rolling and broken terrain.
20.01	Point for the center S. 1/16 sec. cor. of sec. 29.  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Subdivision of Section 29,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R91W C S1/16   S 29 C 2000</p>
	<p>Set a fiberglass sign post alongside the iron post. Cor. is located on steep E. slope.</p>
40.02	<p>Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W C1/4 S 29 2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p>
59.91	<p>Point for the center N. 1/16 sec. cor. of sec. 29. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W C N1/16   S 29 C 2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p>
79.80	<p>The 1/4 sec. cor. of secs. 20 and 29.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 28 and 29. N. 89° 41' W., on the E. and W. center line of sec. 29. Over rolling to broken terrain.</p>
19.86	<p>Point for the center E. 1/16 sec. cor. of sec. 29.</p>

Subdivision of Section 29,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R91W E1/16 C———C S 29 2000</p>
	Set a fiberglass sign post alongside the iron post.
39.72	The center 1/4 sec. cor. of sec. 29.
78.22	The 1/4 sec. cor. of secs. 29 and 30.
	<hr/> <p>From the center E. 1/16 sec. cor. of sec. 29. N. 0° 11' W., on the N. and S. center line of the NE¼ of sec. 29. Over rolling and broken terrain.</p>
19.935	Point for the NE. 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the NE¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T54N R91W NE1/16 S 29 2000</p>
	Set a fiberglass sign post alongside the iron post.
39.87	The E. 1/16 sec. cor. of secs. 20 and 29.
	<hr/> <p>From the N. 1/16 sec. cor. of secs. 28 and 29. N. 89° 48' W., on the E. and W. center line of the NE¼ of sec. 29. Over rolling and broken terrain.</p>
19.895	The NE. 1/16 sec. cor. of sec. 29.
26.10	Creek, course SSW.

Subdivision of Section 29,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.79	<p>The center N. 1/16 sec. cor. of sec. 29.</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 29 and 32. N. 0° 32' W., on the N. and S. center line of the SE<math>\frac{1}{4}</math> of sec. 29. Over rolling and broken terrain.</p>
20.085	<p>Point for the SE. 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the SE<math>\frac{1}{4}</math>.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W SE1/16 S 29 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
40.17	<p>The center E. 1/16 sec. cor. of sec. 29.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 28 and 29. N. 89° 28' W., on the E. and W. center line of the SE<math>\frac{1}{4}</math> of sec. 29. Over rolling and broken terrain.</p>
19.945	<p>The SE. 1/16 sec. cor. of sec. 29.</p>
39.89	<p>The center S. 1/16 sec. cor. of sec. 29.</p> <hr/> <p style="text-align: center;">Subdivision of Section 30, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>From the 1/4 sec. cor. of secs. 30 and 31. N. 0° 13' E., on the N. and S. center line of sec. 30. Over rolling and broken terrain.</p>
20.165	<p>Point for the center S. 1/16 sec. cor. of sec. 30.</p>

Subdivision of Section 30,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W C S1/16   S 30 C 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>From this point, a local monument of unknown origin, bears N. 5° 18' E., 0.90 chs. dist., monumented with a steel reinforcement rod, ½ in. diam., firmly set, projecting 1 in. above the ground, at end of new fence extending W. This position is not accepted during the course of this survey.</p>
40.33	<p>Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W C1/4 S 30 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>From this point, a local monument of unknown origin, bears N. 3° 43' E., 1.37 chs. dist., monumented with a steel reinforcement rod, ½ in. diam., firmly set, projecting 3 ins. above the ground. This position is not accepted during the course of this survey.</p>
59.93	<p>Point for the center N. 1/16 sec. cor. of sec. 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W C N1/16   S 30 C 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>

Subdivision of Section 30,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Cor. is located 5 lks. E. of small wash, drains SSW.
79.53	The 1/4 sec. cor. of secs. 19 and 30.
	From the 1/4 sec. cor. of secs. 29 and 30.
	N. 88° 09' W., on the E. and W. center line of sec. 30.
	Over rolling and broken terrain.
19.59	Point for the center E. 1/16 sec. cor. of sec. 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, supported by a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T54N R91W E1/16 C———C S 30 2000</p>
	Set a fiberglass sign post alongside the iron post.
39.18	The center 1/4 sec. cor. of sec. 30.
59.21	Point for the center W. 1/16 sec. cor. of sec. 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R91W W1/16 C———C S 30 2000</p>
	Set a fiberglass sign post alongside the iron post.
	Cor. is located 3 lks. N. of fence extending E. and W.
67.00	Beaver Creek, course SSE.
79.08	The 1/4 sec. cor. of sec. 30 only, on the W. bdy. of the Tp.
	From the E. 1/16 sec. cor. of secs. 30 and 31.

Subdivision of Section 30,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 1° 05' E., on the N. and S. center line of the SE<math>\frac{1}{4}</math> of sec. 30. Over rolling and broken terrain.</p>
20.015	<p>Point for the SE. 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the SE<math>\frac{1}{4}</math>.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W SE1/16 S 30 2000</p>
	<p>Set a fiberglass sign post alongside the iron post.</p> <p>From this point, a local monument of unknown origin, bears S. 76° 21' W., 1.14 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 7 ins. above the ground, in a collar of stone. This position is not accepted during the course of this survey.</p>
40.03	<p>The center E. 1/16 sec. cor. of sec. 30.</p>
	<hr/> <p>From the S. 1/16 sec. cor. of secs. 29 and 30.</p> <p>N. 88° 35' W., on the E. and W. center line of the SE<math>\frac{1}{4}</math> of sec. 30.</p>
	<p>Over rolling and broken terrain.</p>
19.29	<p>The SE. 1/16 sec. cor. of sec. 30.</p>
38.58	<p>The center S. 1/16 sec. cor. of sec. 30.</p>
	<hr/> <p>From the center W. 1/16 sec. cor. of sec. 30.</p> <p>N. 0° 28' W. on the N. and S. center line of the NW<math>\frac{1}{4}</math> of sec. 30.</p> <p>Over gently terrain.</p>
19.715	<p>Point for the NW. 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the NW<math>\frac{1}{4}</math>.</p>

Subdivision of Section 30,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T54N R91W
	NW1/16 S 30
	2000
	Set a fiberglass sign post alongside the iron post.
39.43	The W. 1/16 sec. cor. of secs. 19 and 30.
	From the center N. 1/16 sec. cor. of sec. 30.
	N. 87° 51' W., on the E. and W. center line of the NW¼ of sec. 30.
	Over rolling terrain.
20.27	The NW. 1/16 sec. cor. of sec. 30.
36.80	Beaver Creek, course SSW.
39.82	The N. 1/16 sec. cor. of sec. 30 only, on the W. bdy. of the Tp.
	Subdivision of Section 31, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming
	From the 1/4 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.
	N. 1° 24' E., on the N. and S. center line of sec. 31.
	Over rolling and broken terrain.
20.035	Point for the center S. 1/16 sec. cor. of sec. 31.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R91W
	C
	S1/16   S 31
	C
	2000

Subdivision of Section 31,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a fiberglass sign post alongside the iron post.
40.07	<p>The center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. center line, monumented by Sherman B. Allred, Wyoming Professional Engineer and Land Surveyor No. 2920, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. ALLRED PE&amp;LS 2920 C1/4 S31 DONNELL&amp;ALLRED. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W</p> <p style="text-align: center;">C1/4 S 31</p> <p style="text-align: center;">2000</p> <p>Deposit the steel reinforcement rod inside and set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 27 lks. N. of fence extending E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 24' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
8.50	Beaver Creek Road, bears SE. and NW.
19.91	<p>Point for the center N. 1/16 sec. cor. of sec. 31.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W</p> <p style="text-align: center;">C</p> <p style="text-align: center;">N1/16   S 31</p> <p style="text-align: center;">C</p> <p style="text-align: center;">2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
21.70	Beaver Creek, course ESE.
22.00	Same Creek, course SW.

Subdivision of Section 31,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
34.00	Same Creek, course SE.
39.82	The 1/4 sec. cor. of secs. 30 and 31.
	<hr/> <p>From the 1/4 sec. cor. of secs. 31 and 32. N. 89° 55' W., on the E. and W. center line of sec. 31. Over rolling terrain.</p>
8.50	Beaver Creek, course SW.
19.54	<p>Point for the center E. 1/16 sec. cor. of sec. 31, falls in alfalfa field.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R91W E1/16 C———C S 31 2000</p>
	Cor. is located 44 lks. N. of fence extending E. and W.
29.70	Beaver Creek Road, bears SSE. and NNW.
39.08	The center 1/4 sec. cor. of sec. 31.
	<hr/> <p>N. 89° 55' W., beginning new measurement. Over gently rolling terrain.</p>
20.72	<p>The center W. 1/16 sec. cor. of sec. 31, monumented by Sherman B. Allred, Wyoming Professional Engineer and Land Surveyor No. 2920, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. ALLRED PE&amp;LS 2920 C-W1/16 S31 DONNELL&amp;ALLRED. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 31,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R91W W1/16 C———C S 31 2000</p>
	<p>Deposit the steel reinforcement rod inside and set a fiberglass sign post alongside the iron post.</p>
	<p>Cor. is located 7 lks. N. of fence extending SE. and NW.</p> <hr style="width: 20%; margin: 0 auto;"/>
	<p>N. 89° 55' W., beginning new measurement.</p>
	<p>Over gently rolling terrain.</p>
19.72	<p>The 1/4 sec. cor. of sec. 31 only, on the W. bdy. of the Tp.</p> <hr/>
	<p>From the center E. 1/16 sec. cor. of sec. 31.</p>
	<p>N. 0° 36' E., on the N. and S. center line of the NE<math>\frac{1}{4}</math> of sec. 31.</p>
	<p>Over rolling and broken terrain.</p>
16.00	<p>Beaver Creek, course E.</p>
19.76	<p>Point for the NE. 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the NE<math>\frac{1}{4}</math>, falls on S. face of shale ledge.</p>
	<p>Set an iron pipe, 14 ins. long, 5/8 in. diam., flush with the surface of the ground, with aluminum cap inscribed BLM CADASTRAL SURVEY and mkd.</p>
	<p style="text-align: center;">T54N R91W NE1/16 S 31 2000</p>
	<p>Set a steel fence post alongside the iron pipe.</p>
39.52	<p>The E. 1/16 sec. cor. of secs. 30 and 31.</p> <hr/>
	<p>From the N. 1/16 sec. cor. of secs. 31 and 32.</p>

Subdivision of Section 31,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 89° 29' W., on the E. and W. center line of the NE<math>\frac{1}{4}</math> of sec. 31.</p> <p>Over rolling and broken terrain.</p>
19.265	The NE. 1/16 sec. cor. of sec. 31.
29.90	Beaver Creek, course SE.
38.53	The center N. 1/16 sec. cor. of sec. 31.
	<hr/> <p>From the W. 1/16 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.</p> <p>N. 0° 37' E., on the N. and S. center line of the SW<math>\frac{1}{4}</math> of sec. 31.</p> <p>Over rolling and broken terrain.</p>
19.94	Point for the SW. 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the SW $\frac{1}{4}$ .
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W</p> <p style="text-align: center;">SW1/16 S 31</p> <p style="text-align: center;">2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
39.88	The center W. 1/16 sec. cor. of sec. 31.
	<hr/> <p>From the center S. 1/16 sec. cor. of sec. 31.</p> <p>N. 89° 40' W., on the E. and W. center line of the SW<math>\frac{1}{4}</math> of sec. 31.</p> <p>Over rolling and broken terrain.</p>
20.45	The SW. 1/16 sec. cor. of sec. 31.
39.96	The S. 1/16 sec. cor. of sec. 31 only, on the W. bdy. of the Tp.
	<hr/> <p>From the center W. 1/16 sec. cor. of sec. 31.</p>

Subdivision of Section 31,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 1° 28' E., on the N. and S. center line of the NW¼ of sec. 31. Over rolling terrain.</p> <p>23.50 Beaver Creek Road, bears SE. and NW.</p> <p>40.18 The W. 1/16 sec. cor. of secs. 30 and 31.</p> <hr/> <p style="text-align: center;">Subdivision of Section 32, T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0° 04' W., on the N. and S. center line of sec. 32. Over broken terrain along steep W. slope.</p> <p>20.00 Point for the center S. 1/16 sec. cor. of sec. 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W C S1/16   S 32 C 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>40.00 The center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W C S 1/4 S 32 2000</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>79.44 The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/>
--------	---

Subdivision of Section 32,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>N. 88° 56' W., on the E. and W. center line of sec. 32.</p> <p>Over broken terrain.</p>
11.10	Red Canyon Creek, course S.
19.58	<p>Point for the center E. 1/16 sec. cor. of sec. 32, falls in cultivated field.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W E1/16 C——C S 32 2000</p>
22.40	Fence, bears NNE. and SSW.
22.60	Road, gravel surfaced, bears NNE. and SSW.
39.16	The center 1/4 sec. cor. of sec. 32.
59.155	<p>Point for the center W. 1/16 sec. cor. of sec. 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W W1/16 C——C S 32 2000</p>
79.15	<p>The 1/4 sec. cor. of secs. 31 and 32.</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 32.</p> <p>N. 0° 35' E., on the N. and S. center line of the NE¼ of sec. 32.</p> <p>Over nearly level terrain.</p>
4.00	Road, gravel surfaced, bears E. and W.

Subdivision of Section 32,  
T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.54	The E. 1/16 sec. cor. of secs. 29 and 32.
	<hr/> <p>From the E. 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0° 15' E., on the N. and S. center line of the SE<math>\frac{1}{4}</math> of sec. 32.</p> <p>Over nearly level terrain, across cultivated fields.</p>
39.86	The center E. 1/16 sec. cor. of sec. 32.
	<hr/> <p>From the W. 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0° 02' W., on the N. and S. center line of the SW<math>\frac{1}{4}</math> of sec. 32.</p> <p>Over gently rolling terrain.</p>
20.095	<p>Point for the SW. 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the SW<math>\frac{1}{4}</math>.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R91W</p> <p style="text-align: center;">SW1/16 S 32</p> <p style="text-align: center;">2000</p> <p>Set a fiberglass sign post alongside the iron post.</p>
40.19	The center W. 1/16 sec. cor. of sec. 32.
	<hr/> <p>From the center S. 1/16 sec. cor. of sec. 32.</p> <p>N. 89° 12' W., on the E. and W. center line of the SW<math>\frac{1}{4}</math> of sec. 32.</p> <p>Over rolling and broken terrain.</p>
20.01	The SW. 1/16 sec. cor. of sec. 32.
40.02	The S. 1/16 sec. cor. of secs. 31 and 32.
	<hr/>

T. 54 N., R. 91 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area embraced by this survey is situated in eastern portion of Big Horn County, approximately 6 miles north of Shell, Wyoming. The terrain varies from nearly level to mountainous, with elevation ranging from 4,500 feet to 6,500 feet above sea level. The soil is primarily sandy loam accompanied by areas of clay and bentonite. There is a lot of exposed rock especially in the higher elevations. The vegetation consists of sagebrush and native grasses with areas of scattered cedar. The timber consists of patches of cottonwood and pine along the major drainages.</p> <p>Drainage of the area is provided by Beaver, Cedar and Red Canyon Creeks which flow in a south-southwesterly direction. In addition, London Ditch flows through section 4, in a southerly direction diverting water from South Beaver Creek into Red Canyon Creek. There are several active ranching operations in the area surveyed. No mineral deposits or mining activity were noted, but there are numerous active dinosaur bone dig sites.</p> <p>Access is provided by Beaver Creek Road along with several trail roads.</p>
--------	---



## CERTIFICATE OF SURVEY

I, Joel T. Ebner, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of June, 1998 and supplemental special instructions bearing date of the 26th day of August, 1999, I have dependently resurveyed the west boundary and portions of the south and north boundaries and subdivisional lines, and subdivided certain sections, Township 54 North, Range 91 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

**SEP 28 2001**

(Date)

  
 (Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
 Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of the west boundary and portions of the south and north boundaries and subdivisional lines, and the subdivision of certain sections, Township 54 North, Range 91 West, Sixth Principal Meridian, Wyoming, executed by Joel T. Ebner, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

**SEP 28 2001**

(Date)

  
 (Signature of Authorized Officer)