

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.57	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, determined at intersection of fences extending E. and W., with projection of a fence from the S. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W 1/4 S 3 S 2 1989</p> <hr style="width: 30%; margin: auto;"/> <p>N. $0^{\circ} 59'$ E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
4.10	Ridge, bears SE. and NW.
38.92	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., as described in the field notes of the dependent resurvey, T. 56 N., R. 76 W., executed concurrently under this same group.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., as described in the field notes of the dependent resurvey, T. 54 N., R. 76 W., executed concurrently under this same group.</p> <p>N. $11^{\circ} 23'$ W., bet. secs. 33 and 34.</p> <p>Over rolling terrain.</p>
39.845	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W 1/4 S 33 S 34 1989</p> <p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
79.69	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T55N R76W</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> <tr> <td colspan="2">1989</td> </tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <hr/>	T55N R76W		S 28	S 27	<hr/>		S 33	S 34	1989	
T55N R76W											
S 28	S 27										
<hr/>											
S 33	S 34										
1989											
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89° 56' W., bet. secs. 27 and 34.</p> <p>Over rolling terrain.</p>										
39.245	<p>Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T55N R76W</td> </tr> <tr> <td colspan="2">S 27</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td colspan="2">S 34</td> </tr> <tr> <td colspan="2">1989</td> </tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T55N R76W		S 27		1/4	—	S 34		1989	
T55N R76W											
S 27											
1/4	—										
S 34											
1989											
78.49	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0° 29' W., bet. secs. 27 and 28.</p> <p>Over broken terrain.</p>										
39.06	<p>Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W 1/4 S 28 S 27 1989</p>
78.12	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 21, 22, 27 and 28, determined at cor. of abandoned fences extending S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 21 S 22 ----- S 28 S 27 1989</p>
	<p>Set a steel fence post alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89° 45' W., bet. secs. 22 and 27.</p> <p>Over rolling to broken terrain.</p>
39.355	<p>Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 22 1/4 ——— S 27 1989</p>
78.71	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 0° 12' W., bet. secs. 21 and 22.</p>
	<p>Over rolling to broken terrain.</p>
3.10	<p>Ridge, bears E. and W.</p>
39.365	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R76W 1/4 S 21 S 22 1989</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on steep N. side of draw, drains NW.</p>
78.73	<p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R76W S 16 S 15 ----- S 21 S 22 1989</p> </div> <p>From this point, a sandstone, 12x12x3 ins., firmly set 10 ins. in the ground, no mks. visible, bears S. 83° W., 3.75 chs. dist.</p> <p>From this same point, a sandstone, 12x12x3 ins., firmly set 10 ins. in the ground, no mks. visible, bears S. 83¾° W., 4.06 chs. dist.</p> <p>Cor. is located N. 66¾° E. 4.56 chs. dist., from an intersection of fences extending N., SE. and W.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89° 32' W., bet. secs. 15 and 22.</p> <p>Over rolling terrain, along fence.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
2.36	Leave fence, bears E. and NW.
39.77	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R76W S 15 $\frac{1}{4}$ ——— S 22 1989
	Set a steel fence post alongside the iron post.
64.40	Ridge, bears SE. and NW.
79.54	The cor. of secs. 15, 16, 21 and 22.
	<hr/> N. $0^{\circ} 50'$ W., bet. secs. 15 and 16.
	Over rolling terrain.
39.37	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R76W $\frac{1}{4}$ S 16 S 15 1989
	Set a steel fence post alongside the iron post.
	Cor. is located S. $7\frac{1}{2}^{\circ}$ E., 1.31 chs. dist. from an intersection of fences extending N., E. and S.
43.10	Ridge, bears SE. and NW.
78.74	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T55N R76W S 9 S 10 <hr style="width: 50%; margin: 0 auto;"/> S 16 S 15 1989
	<p>Cor. is located N. $87\frac{1}{2}^\circ$ W., 3.12 chs. dist. from an intersection of fences extending E., S. and W.</p> <p>Cor. is located S. $85\frac{1}{2}^\circ$ E., 2.90 chs. dist. from an intersection of fences extending N., E. and W.</p> <p>Cor is located 6 lks. S. of fence extending E. and W.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. $88^\circ 26'$ W., bet. secs. 10 and 15.</p> <p>Over rolling to broken terrain.</p>
39.95	<p>The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, determined latitudinally by proportionate measurement and longitudinally by a fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	T55N R76W S 10 1/4 ——— S 15 1989
	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located NORTH 3.54 chs. dist. from a cor. of fences extending N. and W.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. $88^\circ 26'$ W., beginning new measurement</p> <p>Over rolling to broken terrain.</p>
9.60	Ridge, bears N. and S.
40.00	The cor. of secs. 9, 10, 15 and 16.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
	N. 0° 23' E., bet. secs. 9 and 10.										
	Over gently rolling terrain.										
39.365	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.										
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. below the surface of the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T55N R76W</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 9</td><td style="text-align: center;">S 10</td></tr> <tr><td colspan="2" style="text-align: center;">1989</td></tr> </table>	T55N R76W		1/4		S 9	S 10	1989			
T55N R76W											
1/4											
S 9	S 10										
1989											
	Set a steel fence post over the iron post.										
	Cor. is located 22 lks. W. of fence extending N. and S.										
78.73	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.										
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T55N R76W</td></tr> <tr><td style="text-align: center;">S 4</td><td style="text-align: center;">S 3</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 9</td><td style="text-align: center;">S 10</td></tr> <tr><td colspan="2" style="text-align: center;">1989</td></tr> </table>	T55N R76W		S 4	S 3	-----		S 9	S 10	1989	
T55N R76W											
S 4	S 3										

S 9	S 10										
1989											
	Set a steel fence post alongside the iron post.										
	From the cor. of secs. 2, 3, 10 and 11.										
	S. 88° 12' W., bet. secs. 3 and 10.										
	Over rolling to broken terrain.										
39.875	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original cor.										
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W S 3 1/4 ——— S 10 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
79.75	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/>
	<p>N. 1° 28' E., bet. secs. 3 and 4. Over rolling to broken terrain.</p>
39.38	<p>Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W 1/4 S 4 S 3 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
78.75	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 56 N., R. 76 W., executed concurrently under this same group.</p> <hr/>
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 54 N., R. 76 W., executed concurrently under this same group.</p>
	<p>N. 9° 34' W., bet. secs. 32 and 33.</p>
	<p>Over rolling terrain.</p>
40.39	<p>Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W 1/4 S 32 S 33 1989</p>
	<p style="text-align: center;">Set a steel fence post alongside the iron post.</p>
80.78	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 29 S 28 ----- S 32 S 33 1989</p>
	<p style="text-align: center;">Set a steel fence post alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p>
	<p>S. 89° 10' W., bet. secs. 28 and 33.</p>
	<p>Over rolling to broken terrain.</p>
39.035	<p>Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 28 1/4 ——— S 33 1989</p>
	<p style="text-align: center;">Set a steel fence post alongside the iron post.</p>
45.00	<p>Ridge, bears N. and S.</p>
78.07	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 0° 23' W., bet. secs. 28 and 29.
	Over rolling to broken terrain.
39.83	Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate distance, falls in draw, drains W.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T55N R76W 1/4 S 29 S 28 1989</p>
	from which
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 39½° E., 68.3 lks. dist., with brass cap mkd. RM T55N R76W ¼ S28 45.1 FT. TO COR 1989 and an arrow pointing to the cor.</p>
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 18½° W., 96.4 lks. dist., with brass cap mkd. RM T55N R76W ¼ S29 63.6 FT. TO COR 1989 and an arrow pointing to the cor.</p>
	Set a steel fence post alongside the iron post.
56.40	Ridge, bears E. and W.
79.66	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T55N R76W S 20 S 21 ----- S 29 S 28 1989</p>
	Set a steel fence post alongside the iron post.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89° 42' W., bet. secs. 21 and 28.
	Over rolling to broken terrain, along fading abandond fence.
38.965	Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R76W S 21 1/4 ——— S 28 1989
	Set a steel fence post alongside the iron post.
41.50	Ridge, bears N. and S.
77.93	The cor. of secs. 20, 21, 28 and 29.
	N. 1° 26' W., bet. secs. 20 and 21.
	Over rolling to broken terrain.
31.50	Ridge, bears NE. and SW.
39.845	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R76W 1/4 S 20 S 21 1989
	Set a steel fence post alongside the iron post.
77.90	Ridge, bears SE. and NW.
79.69	The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, at intersection of fences, extending N., E. and W., with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>T55N R76W</td></tr> <tr><td>S 17 S 16</td></tr> <tr><td>-----</td></tr> <tr><td>S 20 S 21</td></tr> <tr><td>1948</td></tr> </table>	T55N R76W	S 17 S 16	-----	S 20 S 21	1948
T55N R76W						
S 17 S 16						

S 20 S 21						
1948						
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89° 03' W., bet. secs. 16 and 21.</p> <p>Over rolling to broken terrain.</p>					
39.84	<p>Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>T55N R76W</td></tr> <tr><td>S 16</td></tr> <tr><td>1/4 ———</td></tr> <tr><td>S 21</td></tr> <tr><td>1989</td></tr> </table>	T55N R76W	S 16	1/4 ———	S 21	1989
T55N R76W						
S 16						
1/4 ———						
S 21						
1989						
	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located N. 58½° W., 2.19 chs. dist. from an intersection of fences extending E., S. and W.</p> <p>Cor. is located on E. side of Joe Creek, 1.3 chs. wide, course N.</p>					
79.68	<p>The cor. of secs. 16, 17, 20 and 21.</p>					
	<p>N. 0° 55' W., bet. secs. 16 and 17.</p> <p>Over rolling to broken terrain.</p>					
39.925	<p>Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W 1/4 S 17 S 16 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>Cor. is located N. $35\frac{1}{4}^{\circ}$ E., 1.53 chs. dist. from an intersection of fences extending S. and W., with abandoned fence extending N.</p>
77.60	<p>Ridge, bears SE. and NW.</p>
	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 8 S 9 ----- S 17 S 16 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>Cor. is located S. 38° E., 2.79 chs. dist. from an intersection of abandoned fences extending E., S. and W.</p>
	<hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. $88^{\circ} 15'$ W., bet. secs. 9 and 16.</p> <p>Over rolling terrain.</p>
39.91	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 9 1/4 ——— S 16 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
79.82	<p>Cor. is located S. $56\frac{1}{2}^\circ$ W., 2.12 chs. dist. from an intersection of fences extending N. and E., with abandoned fence extending W.</p> <p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/>
39.92	<p>N. $0^\circ 01'$ W., bet. secs. 8 and 9.</p> <p>Over rolling to broken terrain.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a steel fence post, in a collar of stone, with brass cap mkd.</p>
53.30	<p style="text-align: center;">T55N R76W 1/4 S 8 S 9 1989</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on N. side of draw, drains W.</p> <p>Ridge, bears SE. and NW.</p>
79.84	<p>Point for the cor. of secs. 4, 5, 8 and 9, determined longitudinally by proportionate measurement and latitudinally by a fence extending E. and W., falls on sandstone outcrop; there is no remaining evidence of the original monument.</p> <p>Set a brass tablet, $3\frac{1}{2}$ ins. diam., 3 in. stem, in drill hole in sandstone outcrop, mkd.</p>
	<p style="text-align: center;">T55N R76W S 5 S 4 ----- S 8 S 9 1989</p> <p>from which</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. $34\frac{1}{2}^\circ$ W., 87 lks. dist., with brass cap mkd. RM T55N R76W S8 57.4 FT. TO COR 1989 and an arrow pointing to the cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 49½° W., 82 lks. dist., with brass cap mkd. RM T55N R76W S5 54.1 FT. TO COR 1989 and an arrow pointing to the cor.</p>
	<p>Set steel fence posts alongside the reference monuments.</p>
	<p>Cor. is located S. 89½° W., 5.46 chs. dist. from an intersection of fences extending E. and W., with abandoned fence extending N.</p>
	<hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p>
	<p>N. 84° 24' W., bet. secs. 4 and 9.</p>
	<p>Over broken terrain.</p>
40.34	<p>Point for the ¼ sec. cor. of secs. 4 and 9, determined longitudinally by proportionate measurement and latitudinally by a fence extending E. and W.; there is no remaining evidence of the original monument.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 4 1/4 ——— S 9 1989</p>
	<hr/> <p>S. 89° 27' W., beginning new measurement.</p>
	<p>Over rolling terrain, along fence.</p>
18.50	<p>Ridge, bears SE. and NW.</p>
40.15	<p>The cor. of secs. 4, 5, 8 and 9.</p>
	<hr/> <p>N. 4° 34' E., bet. secs. 4 and 5.</p>
	<p>Over rolling to broken terrain.</p>
36.55	<p>Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W 1/4 S 5 S 4 1989</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located S. 43½° W., 4.07 chs. dist. from an intersection of abandoned fences extending N., E. and S.</p>
52.50	Ridge, bears SE. and NW.
73.21	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 56 N., R. 76 W., executed concurrently under this same group.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 54 N., R. 76 W., executed concurrently under this same group.</p> <p>N. 5° 45' W., bet. secs. 31 and 32.</p> <p>Over rolling terrain.</p>
2.70	U.S. Highway No. 14-16, 50 lks. wide, bears ENE. and WSW.
40.445	<p>Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W 1/4 S 31 S 32 1989</p> <p>Set a steel fence post alongside the iron post.</p>
80.89	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 30 S 29 ----- S 31 S 32 1989</p>
	<p>Set a steel fence post alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 28, 29, 32 and 33.</p>
	<p>S. 88° 35' W., bet. secs. 29 and 32.</p>
	<p>Over rolling to broken terrain.</p>
39.215	<p>Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 29 1/4 ——— S 32 1989</p>
78.43	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/>
	<p>S. 86° 54' W., bet. secs. 30 and 31.</p>
	<p>Over rolling to broken terrain.</p>
39.13	<p>Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 30 1/4 ——— S 31 1989</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
74.78	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on ridge, bears SE. and NW.</p> <p>True point for the cor. of secs. 30 and 31 only, on the W. bdy. of the Tp.</p> <hr/>
40.245	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0° 22' W., bet. secs. 29 and 30.</p> <p>Over rolling to broken terrain.</p> <p>Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R76W 1/4 S 30 S 29 1989</p> </div>
80.49	<p>Set a steel fence post alongside the iron post.</p> <p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R76W S 19 S 20 <hr/>S 30 S 29 1989</p> </div>
30.70	<p>Set a steel fence post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89° 11' W., bet. secs. 20 and 29.</p> <p>Over rolling to broken terrain.</p> <p>Ridge, bears SE. and NW.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.185	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W S 20 1/4 ——— S 29 1989</p> <p>Set a steel fence post alongside the iron post.</p>
58.777	<p>Point for the W. $1/16$ sec. cor. of secs. 20 and 29.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W S 20 W1/16 ——— S 29 1989</p> <p>Set a steel fence post alongside the iron post.</p>
61.90	Ridge, bears SE. and NW.
78.37	The cor. of secs. 19, 20, 29 and 30.
35.70	<p>S. $86^{\circ} 17' W.$, bet. secs. 19 and 30.</p> <p>Over rolling to broken terrain.</p>
39.21	<p>Ridge, bears SE. and NW.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W S 19 1/4 ——— S 30 1989</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the iron post.
58.815	Point for the W. 1/16 sec. cor. of secs. 19 and 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T55N R76W S 19 W1/16— S 30 1989</p>
	Set a steel fence post alongside the iron post.
	Cor. is located in draw, drains NW.
75.15	The cor. of secs. 19 and 30 only, on the W. bdy. of the Tp.
	<hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p>
	N. 3° 35' W., bet. secs. 19 and 20.
	Over rolling to broken terrain.
20.16	Point for the S. 1/16 sec. cor. of secs. 19 and 20.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T55N R76W S1/16 S 19 S 20 1989</p>
	Set a steel fence post alongside the iron post.
30.20	Ridge, bears SE. and NW.
40.32	Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T55N R76W 1/4 S 19 S 20 1989</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
	Set a steel fence post alongside the iron post.										
80.64	The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T55N R76W</td> </tr> <tr> <td style="text-align: center;">S 18</td> <td style="text-align: center;">S 17</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 19</td> <td style="text-align: center;">S 20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1948</td> </tr> </table>	T55N R76W		S 18	S 17	-----		S 19	S 20	1948	
T55N R76W											
S 18	S 17										

S 19	S 20										
1948											
	from which the 1948 bearing trees										
	A juniper, 6 ins. diam., bears S. 26½° E., 50 lks. dist., with no scribing visible on partially healed blaze.										
	A juniper, 5 ins. diam., bears N. 2¼° W., 81 lks. dist., mkd. BT on partially healed blaze.										
<hr/> <p>(Restoring the resurvey executed by Ernest Parker and Roswell M. Humphrey in 1948)</p> <hr/>											
	From the cor. of secs. 16, 17, 20 and 21.										
	S. 89° 46' W., bet. secs. 17 and 20.										
	Over rolling terrain.										
1.90	Ridge, bears SE. and NW.										
40.73	The ¼ sec. cor. of secs. 17 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">S 17</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1948</td> </tr> </table>	S 17		1/4	-----	S 20		1948			
S 17											
1/4	-----										
S 20											
1948											
<hr/>											
	S. 89° 49' W., beginning new measurement.										
	Over rolling to broken terrain.										
20.34	Point for the W. 1/16 sec. cor. of secs. 17 and 20.										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.68	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W S 17 W1/16— S 20 1989</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 82 lks. E. of fence extending N. and S.</p> <p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/>
18.44	<p>S. 85° 38' W., bet. secs. 18 and 19.</p> <p>Over rolling to broken terrain.</p> <p>Point for the E. 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W S 18 E1/16— S 19 1989</p>
36.88	<p>Set a steel fence post alongside the iron post.</p> <p>The ¼ sec. cor. of secs. 18 and 19, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 18 1/4 — S 19 1948</p> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0° 14' E., bet. secs. 17 and 18.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over broken terrain.
19.79	Point for the S. 1/16 sec. cor. of secs. 17 and 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R76W
	S1/16
	S 18 S 17
	1989
	Set a steel fence post alongside the iron post.
39.58	The ¼ sec. cor. of secs. 17 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.
	1/4
	S 18 S 17
	1948
	Cor. is located N. 31° E., 85 lks. dist., from an intersection of fences extending N., S. and E.
	N. 0° 12' E., beginning new measurement.
	Over rolling terrain.
19.89	Point for the N. 1/16 sec. cor. of secs. 17 and 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R76W
	N1/16
	S 18 S 17
	1989
	Set a steel fence post alongside the iron post.
	Cor. is located 80 lks. E. of fence extending N. and S.
39.78	The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<table border="1" style="margin: auto;"> <tr><td>T55N</td><td>R76W</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 18</td><td>S 17</td></tr> <tr><td colspan="2" style="text-align: center;">1948</td></tr> </table>	T55N	R76W	S 7	S 8			S 18	S 17	1948	
T55N	R76W										
S 7	S 8										
S 18	S 17										
1948											
	Cor. is located 1.03 chs. E. of fence extending N. and S.										
	<hr/> <p>(Restoring the survey executed by Charles Holcomb in 1883)</p> <hr/>										
	From the cor. of secs. 8, 9, 16 and 17.										
	S. 89° 28' W., bet. secs. 8 and 17.										
	Over rolling to broken terrain.										
39.925	Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original cor.										
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table border="1" style="margin: auto;"> <tr><td>T55N</td><td>R76W</td></tr> <tr><td>S 8</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 17</td><td></td></tr> <tr><td colspan="2" style="text-align: center;">1989</td></tr> </table>	T55N	R76W	S 8		1/4	—	S 17		1989	
T55N	R76W										
S 8											
1/4	—										
S 17											
1989											
	Set a steel fence post alongside the iron post.										
40.80	Ridge, bears N. and S.										
79.85	The cor. of secs. 7, 8, 17 and 18.										
	<hr/>										
	From the cor. of secs. 4, 5, 8, and 9.										
	S. 88° 29' W., bet. secs. 5 and 8.										
	Over rolling to broken terrain, along fence.										
39.90	Point for the ¼ sec. cor. of secs. 5 and 8, determined longitudinally by proportionate measurement and latitudinally by an abandoned fence extending E. and W.; there is no remaining evidence of the original monument.										

CERTIFICATE OF SURVEY

I, Richard A. Kohler, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 12th day of February, 1988, I have dependently resurveyed a portion of the Ninth Auxiliary Meridian West, through Township 55 North, between Ranges 76 and 77 West, the east boundary and a portion of the subdivisional lines, Township 55 North, Range 76 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAY 18 2000

(Date)

Richard A. Kohler
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of the Ninth Auxiliary Meridian West, through Township 55 North, between Ranges 76 and 77 West, the east boundary and a portion of the subdivisional lines, Township 55 North, Range 76 West, Sixth Principal Meridian, Wyoming, executed by Richard A. Kohler, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAY 18 2000

(Date)

John P. Lee
(Signature of Authorized Officer)