

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
DEPENDENT RESURVEY
OF A PORTION OF THE
NINTH AUXILIARY MERIDIAN WEST,
THROUGH TOWNSHIP 55 NORTH, BETWEEN RANGES 76 AND 77 WEST,
THE EAST BOUNDARY
AND A
PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 55 NORTH, RANGE 76 WEST,
OF THE SIXTH PRINCIPAL MERIDIAN,
IN THE STATE OF WYOMING.

EXECUTED BY

RICHARD A. KOHLER

CADASTRAL SURVEYOR

Under Special Instructions dated FEBRUARY 12, 1988, approved FEBRUARY 12, 1988, which provided for the surveys included under Group Number 511, and assignment instructions dated AUGUST 1, 1988.

Survey commenced SEPTEMBER 6, 1988

Survey completed OCTOBER 25, 1989

INDEX DIAGRAM

Township 55 North, Range 76 West

6	5	42 4	34 3	27 2	18 1	8
	50	41	34	26	18	
7	8	40 9	33 10	26 11	17 12	7
	50	39	32	25	16	
18	49 17	39 16	31 15	24 14	16 13	6
48	47	38	31	23	15	
19	46 20	37 21	30 22	23 23	14 24	5
3 46	45	37	30	22	13	
30	44 29	36 28	29 27	21 26	12 25	5
44	43	35	28	20	11	
2 31	42 32	35 33	28 34	19 35	9 36	4

T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS

The following field notes are those of the dependent resurvey of a portion of the Ninth Auxiliary Meridian West, through Township 55 North, between Ranges 76 and 77 West, the east boundary, and a portion of the subdivisional lines, Township 55 North, Range 76 West, Sixth Principal Meridian, Wyoming.

The history of surveys pertaining to this resurvey is as follows:

Charles Holcomb surveyed the Ninth Auxiliary Meridian West (west boundary) the north, east and south boundaries, and the subdivisional lines in 1883. Mark M. Kelley dependently resurveyed the west boundary in 1914. Russell C. MacDonald dependently resurveyed a portion of the north boundary in 1947. Ernest Parker and Roswell M. Humphrey dependently resurveyed a portion of the west boundary, and a portion of the subdivisional lines in 1948.

Extensive obliteration of corners of the original survey is apparent as far back as the 1920's as records of county road surveys executed by County Surveyors, on file at the Campbell County Courthouse, Gillette, Wyoming, show few ties to original corners. Where possible, these surveys were utilized to fix points of local control.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 511, Wyoming, dated February 12, 1988.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data was thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

The survey was executed with a LIETZ SET4 electronic Total Station and by chaining methods. The instrument was maintained in proper adjustment at all times. The directions of all lines refer to the true meridian, determined by direct hour angle observations of the sun at various points along the lines of survey and carried forward by sustained angulation.

T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS					
	<p>The geographic position of the southeast corner of the township, based on NAD 27 and determined by G.P.S. satellite observation is:</p> <p>Latitude 44° 41' 41.57" N. and Longitude 105° 56' 19.79" W.</p> <p>The mean magnetic declination is 12½° E.</p>				
	<p style="text-align: center;">Dependent Resurvey, Portion of the Ninth Auxiliary Meridian West, T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming</p>				
	<p style="text-align: center;">(Restoring the resurvey executed by Mark M. Kelley in 1914)</p>				
	<p>Beginning at the cor. of Tps. 54 and 55 N., Rs. 76 and 77 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 54 N., R. 76 W., executed concurrently under this same group.</p> <p>N. 1° 54' W., on the W. bdy. of sec. 31.</p> <p>Over rolling to broken terrain.</p>				
39.56	<p>Point for the ¼ sec. cor. of sec. 31 only, at proportionate distance; the 1914 monument, an iron post, 36 ins. long, 1 in. diam., with brass cap mkd. ¼ S 31 1914, was found lying loose nearby.</p> <p>Reset the iron post, 30 ins. in the ground, in a collar of stone, and add the mks. 1989 to the brass cap.</p>				
76.12	<p>The witness cor. to the cor. of secs. 30 and 31 only, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R77W</p> <p>WC</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S</td> <td style="padding-left: 5px;">30</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S</td> <td style="padding-left: 5px;">31</td> </tr> </table> <p>R76W 1914</p> </div> <p>Set a steel fence post alongside the iron post.</p>	S	30	S	31
S	30				
S	31				

Dependent Resurvey,
Portion of the Ninth Auxiliary Meridian West,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
3.00	<p>From this point, U.S. Geological Survey triangulation station POWDER, bears N. 89° 08' W., 15.60 chs. dist., monumented with a standard aluminum tablet, 3 ins. diam., cemented in stone, inscribed U.S. GEOLOGICAL SURVEY and a triangle.</p> <hr/> <p>N. 1° 54' W., beginning new measurement.</p> <p>Over rolling to broken terrain.</p> <p>True point for the cor. of secs. 30 and 31 only, at record dist., falls in deep wash, drains N., where it is impracticable to establish a permanent monument</p> <hr/>
19.86	<p>From the cor. of secs. 19 and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N S 19 S 30 R77W R76W 1914</p> </div> <p>N. 0° 12' W., on the W. bdy. of sec. 19 only.</p> <p>Over rolling to broken terrain.</p> <p>Point for the S. 1/16 sec. cor. of sec. 19 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T55N R76W S1/16 S 19 1989</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on N. side of stock dam.</p>
39.72	<p>The ¼ sec. cor. of sec. 19 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, in fence extending E. and W., with brass cap mkd.</p>

Dependent Resurvey,
Portion of the Ninth Auxiliary Meridian West,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">1/4 S 19 1914</p>
	<p style="text-align: center;">Dependent Resurvey of the East Boundary, T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming</p>
	<p style="text-align: center;">(Restoring the survey executed by Charles Holcomb in 1883)</p>
	<p>From the cor. of Tps. 54 and 55 N., Rs. 75 and 76 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 54 N., R. 76 W., executed concurrently under this same group.</p> <p>N. 19° 11' W., bet. secs. 31 and 36.</p> <p>Over rolling to broken terrain.</p>
35.00	<p>Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W R75W 1/4 S 36 S 31 1989</p>
70.00	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 25, 30, 31 and 36, determined at small pile of loose stones, in fence scar extending E. and W., located from cor. tie contained in the field notes of the right-of-way survey of Custer Battlefield Highway, by J.C. Harvey, Deputy County Surveyor, in 1920. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the East Boundary,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W R75W S 25 S 30 <hr/>S 36 S 31 1989</p>
	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located in small draw, drains W.</p> <hr/>
	<p>N. 1° 44' E., bet. secs. 25 and 30.</p> <p>Over rolling terrain.</p>
39.655	<p>Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W R75W 1/4 S 25 S 30 1989</p>
	<p>Set two steel fence posts alongside the iron post.</p>
45.70	<p>U.S. Highway No. 14-16, 30 lks. wide, bears ENE. and WSW.</p>
79.31	<p>Point for the cor. of secs. 19, 24, 25 and 30, determined at projection of fences from the N. and W., falls 1.20 chs. E. of West Fork of South Prong Spotted Horse Creek, course NE. This position is in close agreement with the distance tie in the field notes of the right-of-way survey of Custer Battlefield Highway, by J.C. Harvey, Deputy County Surveyor, in 1920, and is accepted as the best available evidence of the original cor. position.</p> <p>At corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the East Boundary,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W R75W S 24 S 19 <hr style="width: 50%; margin: auto;"/>S 25 S 30 1989</p>
	<p>Set a steel fence post alongside the iron post.</p> <hr/>
	<p>N. 0° 55' E., bet. secs. 19 and 24.</p>
	<p>Over nearly level terrain, along fence.</p>
5.50	<p>Cor. of fences extending N. and SW.; thence along fence.</p>
41.81	<p>The ¼ sec. cor. of secs. 19 and 24, monumented with a sandstone, 11x9x3 ins., firmly set 2 ins. below the surface of the ground, no mks. visible, in fence extending N. and S., and in projection of a fence from the E., and identified by landowner Darrell A. Drake as the cor. monument shown to him by a previous landowner. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W R75W 1/4 S 24 S 19 1989</p>
	<p>Bury the unmkd. stone alongside the iron post.</p> <hr/>
	<p>N. 1° 22' E., beginning new measurement.</p>
	<p>Over rolling terrain, along fence.</p>
40.17	<p>The cor. of secs. 13, 18, 19 and 24, determined at cor. of abandoned fences extending S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>

Dependent Resurvey of the East Boundary,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T55N</td></tr> <tr><td>R76W</td><td>R75W</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td colspan="2">1989</td></tr> </table> <p>Cor. is located in South Prong Spotted Horse Creek, course NW.</p> <hr/>	T55N		R76W	R75W	S 13	S 18	<hr/>		S 24	S 19	1989	
T55N													
R76W	R75W												
S 13	S 18												
<hr/>													
S 24	S 19												
1989													
39.85	<p>N. 0° 02' E., bet. secs. 13 and 18.</p> <p>Over rolling to broken terrain.</p> <p>The ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 12x8x3 ins., firmly set 10 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T55N</td></tr> <tr><td>R76W</td><td>R75W</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2">1989</td></tr> </table> <p>Bury the unmkd. stone alongside the iron post.</p> <p>Cor. is located 11 lks. N. of intersection of fences extending N., E. and W.</p> <hr/>	T55N		R76W	R75W	1/4		S 13	S 18	1989			
T55N													
R76W	R75W												
1/4													
S 13	S 18												
1989													
40.15	<p>N. 0° 03' E., beginning new measurement.</p> <p>Over rolling to broken terrain, along fence.</p> <p>The cor. of secs. 7, 12, 13 and 18, determined from cor. tie in the field notes of the survey of Tompkins Road (abandoned) by Jesse E. Spielman, County Surveyor, in 1917, falls at post of abandoned fence extending S.; there is no remaining evidence of the original monument.</p>												

Dependent Resurvey of the East Boundary,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T55N</td></tr> <tr><td>R76W</td><td>R75W</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2">1989</td></tr> </table> <p>From this point, a sandstone, 19x18x4 ins., lying loose on top of the ground, plainly mkd. CR 77 on a face, bears S. 27° 30' W., 8.08 chs. dist.</p>	T55N		R76W	R75W	S 12	S 7	<hr/>		S 13	S 18	1989	
T55N													
R76W	R75W												
S 12	S 7												
<hr/>													
S 13	S 18												
1989													
	<p>N. 0° 09' E., bet. secs. 7 and 12.</p>												
	<p>Over rolling to broken terrain.</p>												
40.225	<p>The ¼ sec. cor. of secs. 7 and 12, monumented with a granite stone, 11x7x5 ins., firmly set 9 ins. in the ground, no mks. visible, at gate in fence extending E. and W. This position is accepted as the best available evidence of the original cor. position.</p>												
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T55N</td></tr> <tr><td>R76W</td><td>R75W</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2">1989</td></tr> </table>	T55N		R76W	R75W	1/4		S 12	S 7	1989			
T55N													
R76W	R75W												
1/4													
S 12	S 7												
1989													
	<p>Bury the unmkd. stone alongside the iron post.</p>												
	<p>Cor. is located S. 88½° E., 4.07 chs. dist., from a cor. of fences extending N. and E.</p>												
	<p>N. 0° 13' E., beginning new measurement.</p>												
	<p>Over rolling terrain.</p>												
14.30	<p>Ridge, bears SE. and NW.</p>												

Dependent Resurvey of the East Boundary,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS													
40.345	<p>The cor. of secs. 1, 6, 7 and 12, determined at cor. of fences extending S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T55N</td></tr> <tr><td>R76W</td><td>R75W</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2">1989</td></tr> </table>	T55N		R76W	R75W	S 1	S 6	<hr/>		S 12	S 7	1989	
T55N													
R76W	R75W												
S 1	S 6												
<hr/>													
S 12	S 7												
1989													
	<p>N. 0° 12' E., bet. secs. 1 and 6.</p> <p>Over rolling to broken terrain.</p>												
29.20	Ridge, bears E. and W.												
39.60	<p>The ¼ sec. cor. of secs. 1 and 6, monumented with a sandstone, 9x7x2 ins., firmly set 6 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T55N</td></tr> <tr><td>R76W</td><td>R75W</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">1989</td></tr> </table>	T55N		R76W	R75W	1/4		S 1	S 6	1989			
T55N													
R76W	R75W												
1/4													
S 1	S 6												
1989													
	<p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p>												
	<p>N. 0° 01' E., beginning new measurement.</p> <p>Over rolling terrain.</p>												
18.30	Ridge, bears SE. and NW.												

Dependent Resurvey of the East Boundary,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.28	<p>The cor. of Tps. 55 and 56 N., Rs. 75 and 76 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 56 N., R. 76 W., executed concurrently under this same group.</p>
	<hr/> <p>Dependent Resurvey, Portion of the Subdivisional Lines, T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming</p> <hr/>
	<p>(Restoring the survey executed by Charles Holcomb in 1883)</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 54 N., R. 76 W., executed concurrently under this same group.</p> <p>N. 15° 13' W., bet. secs. 35 and 36.</p> <p>Over rolling terrain.</p>
11.60	<p>U.S. Highway No. 14-16, 36 lks. wide, bears NE. and SW.</p>
38.795	<p>Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W 1/4 S 35 S 36 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
58.192	<p>Point for the N. 1/16 sec. cor. of secs. 35 and 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W N1/16 S 35 S 36 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.										
77.59	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T55N</td> <td>R76W</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table>	T55N	R76W	S 26	S 25			S 35	S 36	1989	
T55N	R76W										
S 26	S 25										
S 35	S 36										
1989											
	from which										
	An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 65½° W., 97.4 lks. dist., with brass cap mkd. RM T55N R76W S35 64.3 FT. TO COR 1989 and an arrow pointing to the cor.										
	An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 40½° W., 103.5 lks. dist., with brass cap mkd. RM T55N R76W S26 68.3 FT. TO COR 1989 and an arrow pointing to the cor.										
	Set a steel fence post alongside the iron post.										
	Cor. is located on steep W. side of draw, drains N.										
	From this point, United States Coast and Geodetic Survey triangulation station ARVADA bears N. 58° 08' W., 40.12 chs. dist., monumented with steel pipe, 4 ins. diam., firmly set, projecting 5 ins. above the ground, with brass disk mkd. ARVADA 1934 and a triangle.										
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.										
	N. 88° 52' W., bet. secs. 25 and 36.										
	Over rolling terrain, along fence.										
20.70	U.S. Highway No. 14-16, 36 lks. wide, bears N. and S.										
39.00	Point for the ¼ sec. cor. of secs. 25 and 36, determined longitudinally by proportionate measurement and latitudinally by a fence scar extending E. and W.; there is no remaining evidence of the original monument.										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 25 1/4 ——— S 36 1989</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 82° 28' W., beginning new measurement.</p>
	<p>Over rolling to broken terrain.</p>
19.665	<p>Point for the W. 1/16 sec. cor. of secs. 25 and 36.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 25 W1/16 ——— S 36 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>Cor. is located on ridge, bears SE. and NW.</p>
39.33	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr style="width: 60%; margin: auto;"/>
	<p>N. 0° 38' E., bet. secs. 25 and 26.</p>
	<p>Over rolling to broken terrain.</p>
18.72	<p>Point for the S. 1/16 sec. cor. of secs. 25 and 26.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S1/16 S 26 S 25 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>Cor. is located on E. side of draw, drains NE.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
37.44	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W 1/4 S 26 S 25 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
74.88	<p>Point for the cor. of secs. 23, 24, 25 and 26, determined longitudinally by proportionate measurement and latitudinally by a fence extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 23 S 24 ----- S 26 S 25 1989</p>
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.</p> <p>N. $88^{\circ} 56'$ W., bet. secs. 24 and 25.</p> <p>Over nearly level terrain.</p>
6.00	<p>Cor. of fences extending NE. and W.; thence along fence.</p>
34.50	<p>Ivy Creek Road, 30 lks. wide, bears SSE. and W., in a curve; thence along road.</p>
39.77	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, determined longitudinally by proportionate measurement and latitudinally by Ivy Creek Road, extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set an aluminum rod, 24 ins. long, $\frac{5}{8}$ in. diam., 18 ins. below the surface of the road, with magnetic aluminum cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W S 24 1/4 ——— S 25 1989</p>
	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 50½° E., 75.8 lks. dist., with brass cap mkd. RM T55N R76W ¼ S24 50.0 FT. TO COR 1989 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 46½° W., 72.4 lks. dist., with brass cap mkd. RM T55N R76W ¼ S24 47.8 FT. TO COR 1989 and an arrow pointing to the cor.</p> <hr/> <p>N. 88° 52' W., beginning new measurement.</p> <p>Over nearly level terrain, along Ivy Creek Road.</p>
19.10	<p>Leave Ivy Creek Road, bears E. and N., in a curve, thence along fence.</p>
39.77	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0° 54' E., bet. secs. 23 and 24.</p> <p>Over rolling terrain.</p>
40.14	<p>Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W 1/4 S 23 S 24 1989</p> <p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
80.28	<p>The cor. of secs. 13, 14, 23 and 24, determined at the intersection of Ivy Creek Road, extending E. and W., with the projection of a fence from the N. This position is identical with Station 82 of the right-of-way survey of Tompkins Road (abandoned) by Jesse E. Spielman, County Surveyor, in 1917, and is accepted as the best available evidence of the original cor. position.</p> <p>At corner point</p> <p>Set an aluminum rod, 24 ins. long, 5/8 in. diam., 18 ins. below the surface of the road, with magnetic aluminum cap mkd.</p> <table data-bbox="870 726 1016 877" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T55N R76W</td> </tr> <tr> <td style="text-align: center;">S 14</td> <td style="text-align: center;">S 13</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 23</td> <td style="text-align: center;">S 24</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 38° E., 81.7 lks. dist., with brass cap mkd. RM T55N R76W S24 53.9 FT. TO COR 1989 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 37½° W., 82 lks. dist., with brass cap mkd. RM T55N R76W S23 54.1 FT. TO COR 1989 and an arrow pointing to the cor.</p>	T55N R76W		S 14	S 13	-----		S 23	S 24	1989	
T55N R76W											
S 14	S 13										

S 23	S 24										
1989											
39.88	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>S. 89° 52' W., bet. secs. 13 and 24.</p> <p>Over rolling terrain, along fence.</p> <p>The ¼ sec. cor. of secs. 13 and 24, determined at intersection of fences extending E., S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W S 13 1/4 ——— S 24 1989</p>
	<p>Cor. is located 36 lks. E. of intersection of fences extending N., E. and W.</p> <hr/> <p>S. 89° 53' W., beginning new measurement.</p> <p>Over nearly level terrain, along fence.</p>
19.30	<p>Leave fence, enter Ivy Creek Road, 30 lks. wide, bears S. and W., in a curve, thence along Ivy Creek Road.</p>
39.97	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/>
	<p>N. 0° 24' W., bet. secs. 13 and 14.</p> <p>Over nearly level terrain, along fence.</p>
38.82	<p>The ¼ sec. cor. of secs. 13 and 14, determined at intersection of fences extending N., E. and S. This position is identical with Station 81 of the right-of-way survey of Tompkins Road (abandoned) by Jesse E. Spielman, County Surveyor, in 1917, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W 1/4 S 14 S 13 1989</p> <hr/>
	<p>N. 0° 05' E., beginning new measurement.</p> <p>Over nearly level terrain, along fence.</p>
40.14	<p>The cor. of secs. 11, 12, 13 and 14, determined at cor. of fences extending E. and S. This position is accepted as the best available evidence of the original cor. position.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T55N R76W</td></tr> <tr><td>S 11</td><td>S 12</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 14</td><td>S 13</td></tr> <tr><td colspan="2">1989</td></tr> </table>	T55N R76W		S 11	S 12	-----		S 14	S 13	1989	
T55N R76W											
S 11	S 12										

S 14	S 13										
1989											
	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p> <p>S. 89° 08' W., bet. secs. 12 and 13.</p> <p>Over rolling to nearly level terrain.</p>										
40.055	<p>Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T55N R76W</td></tr> <tr><td colspan="2">S 12</td></tr> <tr><td>1/4</td><td>-----</td></tr> <tr><td colspan="2">S 13</td></tr> <tr><td colspan="2">1989</td></tr> </table>	T55N R76W		S 12		1/4	-----	S 13		1989	
T55N R76W											
S 12											
1/4	-----										
S 13											
1989											
	<p>Set a steel fence post alongside the iron post.</p>										
80.11	<p>The cor. of secs. 11, 12, 13 and 14.</p>										
	<p>N. 0° 06' E., bet. secs. 11 and 12.</p> <p>Over nearly level terrain.</p>										
40.545	<p>Point for the ¼ sec. cor. of secs. 11 and 12, determined longitudinally by proportionate measurement and latitudinally by a fence extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W 1/4 S 11 S 12 1989</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 0° 06' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
40.02	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 2 S 1 <hr style="width: 10%; margin: auto;"/> S 11 S 12 1989</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 40 lks. N. of fence extending E. and W.</p> <hr style="width: 80%; margin: auto;"/>
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>S. 89° 07' W., bet. secs. 1 and 12.</p> <p>Over rolling terrain.</p>
40.095	<p>Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 1 1/4 ——— S 12 1989</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 40 lks. S. of fence extending E. and W.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
80.19	The cor. of secs. 1, 2, 11 and 12.
	N. 1° 11' W., bet. secs. 1 and 2.
	Over nearly level terrain.
40.03	The ¼ sec. cor. of secs. 1 and 2, determined at intersection of fences extending N., E. and irregularly W. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T55N R76W
	1/4
	S 2 S 1
	1989
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.
	N. 3° 45' E., beginning new measurement.
	Over rolling to broken terrain, along fence.
39.36	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 56 N., R. 76 W., executed concurrently under this same group.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 54 N., R. 76 W., executed concurrently under this same group.
	N. 13° 06' W., bet. secs. 34 and 35.
	Over rolling terrain.
38.795	Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W 1/4 S 34 S 35 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
58.192	<p>Point for the N. 1/16 sec. cor. of secs. 34 and 35.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W N1/16 S 34 S 35 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
77.59	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance, falls in draw, on sandstone outcrop; there is no remaining evidence of the original cor.</p>
	<p>Set a brass tablet, 3½ ins. diam., 3 in. stem, in drill hole in sandstone outcrop, mkd.</p>
	<p style="text-align: center;">T55N R76W S 27 S 26 ----- S 34 S 35 1989</p>
	<p>from which</p>
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45¾° W., 91.4 lks. dist., with brass cap mkd. RM T55N R76W S34 60.3 FT. TO COR 1989 and an arrow pointing to the cor.</p>
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 68½° W., 122 lks. dist., with brass cap mkd. RM T55N R76W S27 80.5 FT. TO COR 1989 and an arrow pointing to the cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 88° 26' W., bet. secs. 26 and 35.</p> <p>Over rolling to broken terrain.</p>
38.93	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W S 26 1/4 ——— S 35 1989</p> <p>Set a steel fence post alongside the iron post.</p>
58.395	<p>Point for the W. 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W S 26 W1/16 ——— S 35 1989</p> <p>Set a steel fence post alongside the iron post.</p>
77.86	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/>
32.50	<p>N. 1° 47' W., bet. secs. 26 and 27.</p> <p>Over rolling to broken terrain.</p> <p>Ridge, bears SE. and NW.</p>
37.805	<p>The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented by person(s) unknown, with a wood post, 8 ins. diam., firmly set, projecting 3½ ft. above the ground. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>

157

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W 1/4 S 27 S 26 1989</p> <hr/> <p>N. 1° 05' E., beginning new measurement.</p> <p>Over rolling to broken terrain.</p>
39.88	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W S 22 S 23 <hr/>S 27 S 26 1989</p> <p>Set a steel fence post alongside the iron post.</p> <hr/>
38.30	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 88° 42' W., bet. secs. 23 and 26.</p> <p>Over rolling to broken terrain, along fence.</p>
40.00	<p>Ridge, bears SE. and NW.</p> <p>The ¼ sec. cor. of secs. 23 and 26, determined at intersection of fences extending E. and SSW., with an abandoned fence extending N. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W S 23 1/4 ——— S 26 1989</p> <hr/>
	<p>S. 89° 37' W., beginning new measurement. Over broken terrain.</p>
19.535	<p>Point for the W. 1/16 sec. cor. of secs. 23 and 26. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 23 W1/16 ——— S 26 1989</p>
	<p>Set a steel fence post alongside the iron post. Cor. is located on W. side of narrow draw, drains SSW.</p>
39.07	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/>
	<p>N. 0° 25' E., bet. secs. 22 and 23. Over rolling to broken terrain.</p>
21.10	<p>Ridge, bears SE. and NW.</p>
39.875	<p>Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W 1/4 S 22 S 23 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
79.75	<p>Point for the cor. of secs. 14, 15, 22 and 23, determined longitudinally by proportionate measurement and latitudinally by a fence extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T55N</td><td>R76W</td></tr> <tr><td>S 15</td><td>S 14</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 22</td><td>S 23</td></tr> <tr><td colspan="2" style="text-align: center;">1989</td></tr> </table>	T55N	R76W	S 15	S 14			S 22	S 23	1989	
T55N	R76W										
S 15	S 14										
S 22	S 23										
1989											
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89° 41' W., bet. secs. 14 and 23.</p>										
	<p>Over gently rolling terrain, along Ivy Creek Road.</p>										
32.30	<p>Leave Ivy Creek Road, bears E. and NW., in a curve.</p>										
39.875	<p>The ¼ sec. cor. of secs. 14 and 23, identical with Station 83 of the right-of-way survey of Tompkins Road (abandoned), extending S. and E, by Jesse E. Spielman, Campbell County Surveyor, in 1917, from which a right-of-way monument,</p>										
	<p style="padding-left: 40px;">A sandstone, 24x18x6 ins., firmly set, projecting 10 ins. above the ground, plainly mkd. CR on a face and 83 on opppsite face, bears N. 45½° W., 70.6 lks dist.</p>										
	<p>This position is accepted as the best available evidence of the original cor. position.</p>										
	<p>At corner point</p>										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T55N</td><td>R76W</td></tr> <tr><td>S 14</td><td>—</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 23</td><td>—</td></tr> <tr><td colspan="2" style="text-align: center;">1989</td></tr> </table>	T55N	R76W	S 14	—	1/4	—	S 23	—	1989	
T55N	R76W										
S 14	—										
1/4	—										
S 23	—										
1989											
	<p>Set a steel fence post alongside the iron post.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Cor. is located in fence extending SE. and NW.
	N. 89° 30' W., beginning new measurement.
	Over rolling terrain.
23.60	Ridge, bears N. and S.
39.85	The cor. of secs. 14, 15, 22 and 23.
	N. 0° 31' W., bet. secs. 14 and 15.
	Over rolling terrain.
20.20	Ridge, bears SE. and NW.
40.14	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T55N R76W 1/4 S 15 S 14 1989</p>
	Set a steel fence post alongside the iron post.
80.28	Point for the cor. of secs. 10, 11, 14 and 15, determined longitudinally by proportionate measurement and latitudinally by a fence extending E. and W.; there is no remaining evidence of the original monument.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T55N R76W S 10 S 11 ----- S 15 S 14 1989</p>

101

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 88° 24' W., bet. secs. 11 and 14.</p> <p>Over nearly level terrain.</p>
40.16	<p>Point for the ¼ sec. cor. of secs. 11 and 14, determined at projected cor. of Ivy Creek Road extending S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T55N R76W S 11 1/4 ——— S 14 1989</p> <p>Cor. is located 50 lks. S. of N. right-of-way fence and 50 lks. W. of E. right-of-way fence.</p> <hr/> <p>N. 89° 33' W., beginning new measurement.</p> <p>Over nearly level terrain, along Ivy Creek Road.</p>
20.10	<p>Leave Ivy Creek Road, bears N. and E., in a curve; thence along fence.</p>
40.08	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0° 15' E., bet. secs. 10 and 11.</p> <p>Over rolling terrain.</p>
19.40	<p>Ridge, bears SE. and NW.</p>
39.525	<p>Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 55 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R76W 1/4 S 10 S 11 1989</p>
79.05	<p>Set a steel fence post alongside the iron post.</p> <p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 3 S 2 ----- S 10 S 11 1989</p> <p>Set a steel fence post alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89° 57' W., bet. secs. 2 and 11.</p> <p>Over gently rolling terrain.</p>
40.005	<p>Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R76W S 2 1/4 ——— S 11 1989</p> <p>Set a steel fence post alongside the iron post.</p>
80.01	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 2° 44' W., bet. secs. 2 and 3.</p> <p>Over rolling terrain.</p>