

# ORIGINAL

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD NOTES

OF THE  
DEPENDENT RESURVEY  
OF  
PORTIONS  
OF THE  
SOUTH AND WEST BOUNDARIES  
AND PORTIONS OF  
THE SUBDIVISIONAL LINES,  
TOWNSHIP 56 NORTH, RANGE 73 WEST,  
OF THE SIXTH PRINCIPAL MERIDIAN,  
IN THE STATE OF WYOMING.

### EXECUTED BY

JOEL T. EBNER

CADASTRAL SURVEYOR

Under Special Instructions dated FEBRUARY 26, 2001, approved FEBRUARY 26, 2001, which provided for the surveys included under Group Number 686, and assignment instructions dated FEBRUARY 26, 2001.

Survey commenced MAY 22, 2001

Survey completed JULY 25, 2001

# INDEX DIAGRAM

Township 56 North, Range 73 West

<p>6</p> <p>54</p>	<p>5</p>	<p>4</p>	<p>3</p> <p>35</p>	<p>2</p> <p>27</p>	<p>1</p>
<p>15 7</p> <p>52</p>	<p>53 8</p> <p>51</p>	<p>42 9</p> <p>42</p>	<p>35 10</p> <p>34</p>	<p>26 11</p> <p>25</p>	<p>17 12</p>
<p>14 18</p> <p>50</p>	<p>50 17</p> <p>49</p>	<p>40 16</p> <p>40</p>	<p>33 15</p> <p>32</p>	<p>24 14</p> <p>25</p>	<p>13</p>
<p>13 19</p> <p>48</p>	<p>48 20</p> <p>47</p>	<p>39 21</p> <p>38</p>	<p>31 22</p> <p>31</p>	<p>22 23</p> <p>22</p>	<p>24</p>
<p>13 30</p> <p>45</p>	<p>46 29</p> <p>45</p>	<p>37 28</p> <p>37</p>	<p>30 27</p> <p>29</p>	<p>20 26</p> <p>20</p>	<p>16 25</p>
<p>31</p> <p>12</p>	<p>43 32</p> <p>9</p>	<p>36 33</p> <p>5</p>	<p>28 34</p> <p>2</p>	<p>19 35</p>	<p>36</p>

## T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>The following field notes are those of the dependent resurvey of portions of the south and west boundaries and portions of the subdivisional lines, Township 56 North, Range 73 West, Sixth Principal Meridian, Wyoming.</p> <p>The history of surveys pertaining to this resurvey is as follows:</p> <p>Mortimer N. Grant surveyed the south and west boundaries and the subdivisional lines in 1883. Mark D. King dependently resurveyed the south boundary in 1921 and dependently resurveyed the west boundary and a portion of the subdivisional lines and surveyed certain private land claims in 1922.</p> <p>Numerous local surveys have been conducted in the area and acceptance of these surveys is detailed herein.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 686, Wyoming, dated February 26, 2001.</p> <p>Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data were thoroughly verified and only true line field notes are given herein, which refer to the completed survey.</p> <p>The survey was executed with TRIMBLE Model 4700 Global Positioning System (GPS) receivers and by chaining methods. The instruments were maintained in proper adjustment at all times. The directions of all lines refer to the true meridian, based on geodetic north, as determined by GPS observations. GPS control network and supporting data are contained in the official group file.</p> <p>The geographic position of the corner of sections 34 and 35 only, on the South Boundary of the township, based on NAD 83(1993) and determined by Global Positioning System methods is:</p> <p>Latitude 44° 46' 58.99" N., Longitude 105° 36' 57.44" W.</p> <p>The mean magnetic declination is 11½° E.</p> <hr/>
--------	--

Dependent Resurvey, Portion of the South Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS								
	<p>(Restoring the resurvey executed by Mark D. King in 1921)</p> <hr/>							
	<p>Beginning at the cor. of secs. 34 and 35 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above the ground, with a mound of stone, 4 ft. base, 2 ft. high, N. of the cor., with brass cap mkd.</p>							
	<table border="0"> <tr><td>T56N R73W</td></tr> <tr><td>S 34   S 35</td></tr> <tr><td>-----</td></tr> <tr><td>S 2</td></tr> <tr><td>T55N R73W</td></tr> <tr><td>1921</td></tr> </table>	T56N R73W	S 34   S 35	-----	S 2	T55N R73W	1921	
T56N R73W								
S 34   S 35								
-----								
S 2								
T55N R73W								
1921								
	<p>S. 88° 57' W., on the S. bdy. of sec. 34.</p> <p>Over gently rolling terrain.</p>							
0.64	<p>The closing cor. of secs. 2 and 3, T. 55 N., R. 73 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd.</p>							
	<table border="0"> <tr><td>T56N R73W</td></tr> <tr><td>S 34</td></tr> <tr><td>-----</td></tr> <tr><td>S 3   S 2</td></tr> <tr><td>T55N R73W</td></tr> <tr><td>C C</td></tr> <tr><td>1921</td></tr> </table>	T56N R73W	S 34	-----	S 3   S 2	T55N R73W	C C	1921
T56N R73W								
S 34								
-----								
S 3   S 2								
T55N R73W								
C C								
1921								
20.12	<p>Cor. No. 2, Tract 43, identical with Cor. No. 1, Tract 46, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.</p>							
	<table border="0"> <tr><td>T55N R73W</td></tr> <tr><td>-----</td></tr> <tr><td>1   2</td></tr> <tr><td>TR 46   TR 43</td></tr> <tr><td>1921</td></tr> </table> <hr/>	T55N R73W	-----	1   2	TR 46   TR 43	1921		
T55N R73W								
-----								
1   2								
TR 46   TR 43								
1921								
	<p>S. 88° 58' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>							
8.10	<p>White Tail Creek (dry), drains SE.</p>							

Dependent Resurvey, Portion of the South Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.14	<p>The 1/4 sec. cor. of sec. 34 only, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, N. of the cor., with brass cap mkd.</p>
	<p style="text-align: center;">S 34 1/4 ——— 1921</p> <hr style="width: 30%; margin: auto;"/>
	<p>S. 89° 05' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
20.25	<p>Cor. No. 2, Tract 46, identical with Cor. No. 1, Tract 47, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R73W ————— 1   2 TR 47   TR 46 1921</p> <hr style="width: 30%; margin: auto;"/>
	<p>S. 89° 22' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
4.40	<p>Bay Horse Road, on curve, bears N. and W.; thence along road.</p>
19.98	<p>The closing cor. of secs. 3 and 4, T. 55 N., R. 73 W., bears SOUTH, 0.3 lks. dist., remonumented by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, with a steel reinforcement rod, 5/8 in. diam., firmly set 8 ins. below the surface of the ground, in Bay Horse Road extending E. and W., as filed in the Campbell County Clerk's Office, with aluminum cap mkd.</p>
	<p style="text-align: center;">JONES PELS 4250 T56N R73W ————— S 4   S 3 C C T55N 2001</p>

Dependent Resurvey, Portion of the South Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>20.22</p>	<p>from which</p> <p>A reference monument established by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, bears S. 45¼° E., 1.06 chs. dist., with aluminum cap mkd. JONES PELS 4250 RM 70.0 S3 S4 CC 2001.</p> <p>A reference monument established by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, bears S. 44½° W., 1.06 chs. dist., with aluminum cap mkd. JONES PELS 4250 RM 70.0 S3 S4 CC 2001.</p> <p>The cor. of secs. 33 and 34 only, monumented with an iron post, 36 ins. long, 2 ins. diam., firmly set 12 ins. below the surface of the ground, in Bay Horse Road extending E. and W., top portion of post badly bent, with brass cap lying loose alongside, mks. illegible, and with a steel reinforcement rod, 18 ins. long, 5/8 in. diam., firmly set alongside, as filed in the Campbell County Clerk's Office.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. below the surface of the road, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T56N</td> <td>R73W</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 4</td> </tr> <tr> <td>T55N</td> <td>R73W</td> </tr> <tr> <td colspan="2" style="text-align: center;">2001</td> </tr> </table> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45° E., 70.8 lks. dist., with brass cap mkd. RM T56N R73W S34 46.7 FT. TO COR. 2001 and an arrow pointing to the cor.</p>	T56N	R73W	S 33	S 34	S 4		T55N	R73W	2001	
T56N	R73W										
S 33	S 34										
S 4											
T55N	R73W										
2001											

Dependent Resurvey, Portion of the South Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45° W., 68.3 lks. dist., with brass cap mkd. RM T56N R73W S33 45.1 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>Remove the bent 36 in. iron post from the field, deposit the brass cap and steel reinforcement rod alongside the stainless steel post.</p> <hr/> <p>S. 89° 15' W., on the S. bdy. of sec. 33.</p> <p>Over gently rolling terrain, along Bay Horse Road.</p> <p>20.37 Cor. No. 2, Tract 47, identical with Cor. No. 1, Tract 48, remonumented by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, with a steel reinforcement rod, 5/8 in. diam., firmly set 8 ins. below the surface of the ground, in Bay Horse Road extending E. and W., with aluminum cap mkd.</p> <p style="text-align: center;">JONES PELS 4250 T56N R73W</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-top: 1px solid black; border-right: 1px solid black; padding: 0 5px;">1</td> <td style="border-top: 1px solid black; padding: 0 5px;">2</td> </tr> <tr> <td style="padding: 0 5px;">TR 48</td> <td style="padding: 0 5px;">TR 47</td> </tr> <tr> <td style="padding: 0 5px;">T55N</td> <td style="padding: 0 5px;">2001</td> </tr> </table> <p>from which</p> <p>A Geological Survey vertical control benchmark, bears N. 67½° E., 1.36 chs. dist., monumented with an iron post, 1 in. diam., firmly set flush with the surface of the ground, with brass cap mkd. US DEPARTMENT OF INTERIOR GEOLOGICAL SURVEY ELEV. FT. ABOVE SEA 16GRS 1971.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 47½° W., 72.9 lks. dist., with brass cap mkd. RM T56N R73W S33 48.1 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>This position is filed in the Campbell County Clerk's Office, and is accepted as a careful and faithful perpetuation of the 1921 cor. position.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/>	1	2	TR 48	TR 47	T55N	2001
1	2						
TR 48	TR 47						
T55N	2001						

Dependent Resurvey, Portion of the South Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>S. 89° 09' W., beginning new measurement.</p> <p>Over gently rolling terrain, along Bay Horse Road.</p>
20.385	<p>Point for the 1/4 sec. cor. of sec. 33 only, at proportionate distance, falls in Bay Horse Road extending E. and W.; there is no remaining evidence of the 1921 cor. position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. below the surface of the road, with brass cap mkd.</p> <p style="text-align: center;">T56N R73W 1/4 S 33 ----- T55N 2001</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45° E., 70.0 lks. dist., with brass cap mkd. RM T56N R73W S33 46.2 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45° W., 68.0 lks. dist., with brass cap mkd. RM T56N R73W S33 44.9 FT. TO COR. 2001 and an arrow pointing to the cor.</p>
40.77	<p>Cor. No. 2, Tract 48, identical with Cor. No. 1, Tract 49, monumented by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, with a steel reinforcement rod, 5/8 in. diam., firmly set 14 ins. below the surface of the ground, in Bay Horse Road extending E. and W., with aluminum cap mkd.</p> <p style="text-align: center;">JONES PELS 4250 T56N R73W S 33 ----- 1   2 TR 49   TR 48 T55N 2001</p>

Dependent Resurvey, Portion of the South Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p>	<p>from which</p> <p>A reference monument established by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, bears S. 45¼° E., 75.8 lks. dist., with aluminum cap mkd. JONES PELS 4250 RM 50.0 1 TR49 2 TR48 2001.</p> <p>A reference monument established by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, bears S. 44½° W., 75.8 lks. dist., with aluminum cap mkd. JONES PELS 4250 RM 50.0 1 TR49 2 TR48 2001.</p> <p>and new reference monuments</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45¼° E., 93.0 lks. dist., with brass cap mkd. RM T55N R73W S4 61.4 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45½° W., 90.0 lks. dist., with brass cap mkd. RM T55N R73W S4 59.4 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>This position is filed in the Campbell County Clerk's Office, and is accepted as a careful and faithful reestablishment of the 1921 cor. position.</p> <hr/> <p>S. 89° 09' W., beginning new measurement.</p> <p>Over gently rolling terrain, along Bay Horse Road.</p> <p>18.61 The closing cor. of secs. 4 and 5, T. 55 N., R. 73 W., monumented by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, with a steel reinforcement rod, 5/8 in. diam., firmly set 12 ins. below the surface of the ground, in Bay Horse Road extending E. and W., as filed in the Campbell County Clerk's Office, with aluminum cap mkd.,</p>
---------------	---

Dependent Resurvey, Portion of the South Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS							
	<p style="text-align: center;">JONES PELS 4250 T56N R73W S 33</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">C C</td> <td style="padding: 0 5px;">C C</td> </tr> </table> <p style="text-align: center;">T55N TR 49 2001</p> <p>from which</p> <p>A reference monument established by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, bears S. 45¼° E., 75.8 lks. dist., with aluminum cap mkd. JONES PELS 4250 RM 50.0 S4 S5 CC 2001.</p> <p>A reference monument established by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, bears S. 44¾° W., 75.8 lks. dist., with aluminum cap mkd. JONES PELS 4250 RM 50.0 S4 S5 CC 2001.</p> <p>From this point, the closing cor. of secs. 4 and 5 established in 1921, bears S. 31° 56' E., 58 lks. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. T56N R73W S33 S5 S4 CC T55N R73W 1921. This monument has been disturbed and reset incorrectly by person(s) unknown presumably during road construction activities. I add the marks AM 2001 and bury in place 8 ins. below the surface of the ground.</p> <p>20.39 The cor. of secs. 32 and 33 only, monumented by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, with a steel reinforcement rod, 5/8 in. diam., firmly set 10 ins. below the surface of the ground, in Bay Horse Road extending E. and W., with aluminum cap mkd.</p> <p style="text-align: center;">JONES PELS 4250 T56N R73W S C</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> </table> <p style="text-align: center;">T55N TR 49 2001</p>	S 5	S 4	C C	C C	S 32	S 33
S 5	S 4						
C C	C C						
S 32	S 33						

Dependent Resurvey, Portion of the South Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p>	<p>from which</p> <p>A reference monument established by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, bears N. 44½° E., 90.9 lks. dist., with aluminum cap mkd. JONES PELS 4250 S32 S33 RM 60.0 2001.</p> <p>A reference monument established by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, bears N. 45¼° W., 90.9 lks. dist., with aluminum cap mkd. JONES PELS 4250 S32 S33 RM 60.0 2001.</p> <p>and new reference monuments</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 44½° E., 92.4 lks. dist., with brass cap mkd. RM T56N R73W S33 61.0 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45E W., 92.7 lks. dist., with brass cap mkd. RM T55N R73W S32 61.2 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>This position is filed in the Campbell County Clerk's Office, and is accepted as a careful and faithful reestablishment of the 1921 cor. position.</p> <hr/> <p>S. 89° 03' W., on the S. bdy. of sec. 32.</p> <p>Over gently rolling terrain, along Bay Horse Road.</p> <p>20.335 Point for Cor. No. 2, Tract 49, identical with Cor. No. 1, Tract 50, at proportionate distance, falls in Bay Horse Road extending E. and W.; there is no remaining evidence of the 1921 cor. position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. below the surface of the road, with brass cap mkd.</p>
---------------	--

Dependent Resurvey, Portion of the South Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T56N R73W S 32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1   2 TR 50 TR 49 T55N R73W 2001</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45° E., 68.6 lks. dist., with brass cap mkd. RM T55N R73W S5 45.3 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45° W., 69.4 lks. dist., with brass cap mkd. RM T55N R73W S5 45.8 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>40.67 The 1/4 sec. cor. of sec. 32 only, identical with Cor. No. 2, Tract 50 and Cor. No. 1, Tract 52, remonumented by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, with a steel reinforcement rod, 5/8 in. diam., firmly set 8 ins. below the surface of the ground, in Bay Horse Road extending E. and W., with aluminum cap mkd.</p> <p style="text-align: center;">JONES PELS 4250 T56N R73W S 32 1/4 — SC T55N 2001</p> <p>from which</p> <p>A reference monument established by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, bears N. 44¾° E., 90.9 lks. dist., with aluminum cap mkd. JONES PELS 4250 1/4 S32 RM 60.0' 2001.</p>

Dependent Resurvey, Portion of the South Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>A reference monument established by Kevin D. Jones, Wyoming Professional Engineer and Land Surveyor No. 4250, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, bears N. 44½° W., 90.9 lks. dist., with aluminum cap mkd. JONES PELS 4250 1/4 S32 RM 60.0' 2001.</p> <p>and new reference monuments</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 44½° E., 92.6 lks. dist., with brass cap mkd. RM T56N R73W S32 61.1 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 44¼° W., 92.4 lks. dist., with brass cap mkd. RM T55N R73W S32 61.0 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>This position is filed in the Campbell County Clerk's Office, and is accepted as a careful and faithful perpetuation of the 1921 cor. position.</p> <hr/> <p>S. 89° 03' W., beginning new measurement.</p> <p>Over gently rolling terrain, along Bay Horse Road.</p> <p>22.80 Leave Bay Horse Road, bears E. and WSW.</p> <p>40.63 Point for the cor. of secs. 31 and 32 only, identical with Cor. No. 2, Tract 52 and Cor. No. 1, Tract 53, at proportionate distance; there is no remaining evidence of the 1921 cor. position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T56N R73W</td> <td></td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 6</td> </tr> <tr> <td colspan="2" style="text-align: center;">T55N R73W</td> </tr> <tr> <td colspan="2" style="text-align: center;">2001</td> </tr> </table> </div>	T56N R73W		S 31	S 32	S 6		T55N R73W		2001	
T56N R73W											
S 31	S 32										
S 6											
T55N R73W											
2001											

Dependent Resurvey, Portion of the South Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45½° E., 68.0 lks. dist., with brass cap mkd. RM T56N R73W S32 44.9 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 41° W., 81.1 lks. dist., with brass cap mkd. RM T56N R73W S31 53.5 FT. TO COR. 2001 and an arrow pointing to the cor.</p> <p>Cor. is located 4 lks. N. of N. edge of Bay Horse Road extending irregularly E. and W., and S. 6½° E., 51 lks. dist., from cor. of fences extending irregularly N. and E.</p>
	<p>S. 89° 03' W., on the S. bdy. of sec. 31.</p>
	<p>Over gently rolling terrain.</p>
10.50	<p>Recluse Road, bears NE. and SW.</p>
40.63	<p>The 1/4 sec. cor. of sec. 31 only, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S 31 1/4 ——— 1921</p>
	<p>Dependent Resurvey, Portion of the West Boundary, T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming</p>
	<p style="text-align: center;">(Restoring the resurvey executed by Mark D. King in 1922)</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the West Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	T56N R74W R73W S 25   S 30 <hr style="width: 50%; margin: 0 auto;"/> S 36   S 31 1922
	N. 0° 19' W., bet. secs. 25 and 30.
	Over rolling and broken terrain.
8.90	Draw, drains NE.
36.70	Ridge, bears SE. and NW.
40.41	The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with a mound of stone, 4 ft. base, 3 ft. high, W. of the cor., with brass cap mkd.
	1/4 S 25   S 30 1922
	<hr style="width: 50%; margin: 0 auto;"/>
	N. 0° 03' E., beginning new measurement.
	Over rolling and broken terrain.
29.80	Bitter Creek (dry), course WNW.
40.60	The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with a wooden post, 8 ins. diam., firmly set alongside, with brass cap mkd.
	T56N R74W R73W S 24   S 19 <hr style="width: 50%; margin: 0 auto;"/> S 25   S 30 1922
	<hr style="width: 50%; margin: 0 auto;"/>
	N. 0° 16' W., bet. secs. 19 and 24.
	Over rolling and broken terrain.

Dependent Resurvey, Portion of the West Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.27	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, W. of the cor., with brass cap mkd.</p>
	<p style="text-align: center;">1/4 S 24   S 19 1922</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 0° 10' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
39.83	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T56N R74W R73W S 13   S 18 <hr style="width: 10%; margin: auto;"/> S 24   S 19 1922</p> <hr style="width: 80%; margin: auto;"/>
	<p>N. 0° 11' E., bet. secs. 13 and 18.</p> <p>Over rolling terrain.</p>
19.86	<p>Point for the S. 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T56N R74W R73W S 1/16 S 13   S 18 2001</p>
	<p>Cor. is located 2 lks. W. of fence extending N. and irregularly S.</p>
39.72	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance, falls in draw drains W.; there is no remaining evidence of the 1922 cor. position.</p>

Dependent Resurvey, Portion of the West Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R74W R73W 1/4 S 13   S 18 2001</p> <p>Cor. is located in fence extending N. and S.</p>
79.44	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R74W R73W S 12   S 7 <hr/>S 13   S 18 1922</p> <p>Cor. is located 1 lk. E. of fence extending N. and S. and in projection of fence from the W.</p>
	<p>N. 0° 30' E., bet. secs. 7 and 12.</p> <p>Over rolling terrain.</p>
40.06	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, W. of the cor., with brass cap mkd.</p> <p style="text-align: center;">1/4 S 12   S 7 1922</p>
	<p>N. 0° 13' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
20.04	<p>Point for the N. 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the West Boundary,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T56N R74W R73W N1/16 S 12   S 7 2001</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>40.08 The cor. of secs. 1, 6, 7 and 12, identical with Cor. No. 3, Tract 55, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, W. of the cor., with brass cap mkd.</p> <p style="text-align: center;">T56N R74W R73W S 1   S 6 ----- S 12   S 7 1922</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Portion of the Subdivisional Lines, T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the resurvey executed by Mark D. King in 1922)</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36, identical with Cor. No. 3, Tract 70, and Cor. No. 2, Tract 71, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R73W S 26   S 25 ----- S 35   S 36 1922</p> <p>N. 0° 04' E., bet. secs. 25 and 26.</p> <p>Over nearly level terrain.</p> <p>20.235 Point for the S. 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
--------	--

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T56N R73W S1/16 S 26   S 25 2001</p> <p>Set a steel fence post alongside the stainless steel post.</p>
40.47	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 26   S 25 1922</p> <hr style="width: 30%; margin: auto;"/> <p>N. 0° 10' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
9.00	<p>Elk Creek Road, bears ENE. and WSW.</p>
40.58	<p>The cor. of secs. 23, 24, 25 and 26, identical with Cor. No. 2, Tract 70, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R73W S 23   S 24 <hr style="width: 10%; margin: auto;"/> S 26   S 25 1922</p> <hr style="width: 80%; margin: auto;"/> <p>From the cor. of secs. 11, 12, 13 and 14, identical with Cor. No. 3, Tract 62, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, at intersection of fences extending E., W. and N., with brass cap mkd.</p> <p style="text-align: center;">T56N R73W S 11   S 12 <hr style="width: 10%; margin: auto;"/> S 14   S 13 1922</p> <p>N. 0° 09' E., bet. secs. 11 and 12.</p> <p>Over rolling terrain, along fence.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS									
20.17	<p>Cor. No. 2, Tract 62, identical with Cor. No. 5, Tract 59, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, in fence extending N. and S., with brass cap mkd.</p>								
	<div style="text-align: center;"> <p>T56N R73W</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 11</td><td style="padding-left: 5px;">TR 59</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding-left: 5px;">5</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding-left: 5px;">2</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding-left: 5px;">TR 62</td></tr> </table> <p>1922</p> <hr style="width: 30%; margin: 10px auto;"/> </div>	S 11	TR 59		5		2		TR 62
S 11	TR 59								
	5								
	2								
	TR 62								
	<p>N. 0° 13' E., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p>								
20.07	<p>The 1/4 sec. cor. of secs. 11 and 12, identical with Cor. No. 4, Tract 59 and Cor. No. 5, Tract 60, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, in fence extending N. and S., with brass cap mkd.</p>								
	<div style="text-align: center;"> <p>1/4</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 11</td><td style="padding-left: 5px;">S 12</td></tr> </table> <p>1922</p> <hr style="width: 30%; margin: 10px auto;"/> </div>	S 11	S 12						
S 11	S 12								
	<p>N. 0° 11' E., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p>								
20.19	<p>Cor. No. 4, Tract 60, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p>								
	<div style="text-align: center;"> <p>T56N R73W</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 11</td><td style="padding-left: 5px;">S 12</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding-left: 5px;">4</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding-left: 5px;">TR 60</td></tr> </table> <p>1922</p> <hr style="width: 30%; margin: 10px auto;"/> </div>	S 11	S 12		4		TR 60		
S 11	S 12								
	4								
	TR 60								
	<p>Cor. is located 3 lks. W. of fence extending N. and S.</p> <p>N. 0° 19' E., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p>								

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS											
20.10	<p>The cor. of secs. 1, 2, 11 and 12, identical with Cor. No. 3, Tract 44 and Cor. No. 4, Tract 46, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, in fence extending N. and S., with a mound of stone, 3 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T56N R73W</td></tr> <tr><td style="text-align: center;">S 2</td><td style="text-align: center;">S 1</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 11</td><td style="text-align: center;">S 12</td></tr> <tr><td colspan="2" style="text-align: center;">1922</td></tr> </table>	T56N R73W		S 2	S 1	-----		S 11	S 12	1922	
T56N R73W											
S 2	S 1										
-----											
S 11	S 12										
1922											
	<p>Cor. is located 2 lks. S. of intersection of fences extending irregularly N., ESE. and S.</p>										
	<hr/> <p>From the cor. of secs. 34 and 35 only, on the S. bdy of the Tp. N. 0° 57' W., bet. secs. 34 and 35.  Over rolling terrain.</p>										
40.25	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, at cor. of fences extending N. and W., with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T56N R73W</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 34</td><td style="text-align: center;">S 35</td></tr> <tr><td colspan="2" style="text-align: center;">1922</td></tr> </table>	T56N R73W		1/4		S 34	S 35	1922			
T56N R73W											
1/4											
S 34	S 35										
1922											
	<hr/> <p>N. 0° 57' W., beginning new measurement.  Over gently rolling terrain, along fence.</p>										
40.27	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above the ground, at cor. of fences extending S. and W., with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T56N R73W</td></tr> <tr><td style="text-align: center;">S 27</td><td style="text-align: center;">S 26</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 34</td><td style="text-align: center;">S 35</td></tr> <tr><td colspan="2" style="text-align: center;">1922</td></tr> </table>	T56N R73W		S 27	S 26	-----		S 34	S 35	1922	
T56N R73W											
S 27	S 26										
-----											
S 34	S 35										
1922											

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 25, 26, 35 and 36, identical with Cor. No. 3, Tract 70 and Cor. No. 2, Tract 71.
	S. 89° 59' W., bet. secs. 26 and 35.
	Over gently rolling terrain.
2.80	Wash, drains SSE.
20.00	Point for the E. 1/16 sec. cor. of secs. 26 and 35.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R73W S 26 E1/16— S 35 2001</p>
	Set a steel fence post alongside the stainless steel post.
40.00	The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R73W S 26 1/4 — S 35 1922</p>
	N. 89° 59' W., beginning new measurement.
	Over gently rolling terrain.
40.63	The cor. of secs. 26, 27, 34 and 35.
	<hr/> <p>(Restoring the survey executed by Mortimer N. Grant in 1883)</p> <hr/>
	N. 0° 05' W., bet. secs. 26 and 27.
	Over nearly level terrain.
20.09	Point for the S. 1/16 sec. cor. of secs. 26 and 27.

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R73W S1/16 S 27   S 26 2001</p>
	Set a steel fence post alongside the stainless steel post.
37.50	Elk Creek Road, bears E. and W.
40.18	The 1/4 sec. cor. of secs. 26 and 27, monumented with a scoria stone, 10x8x7 ins., firmly set 5 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R73W 1/4 S 27   S 26 2001</p>
	Bury the unmkd. stone and set a steel fence post alongside the stainless steel post.
	<hr style="width: 30%; margin: auto;"/> <p>N. 0° 08' W., beginning new measurement.</p>
	Over rolling terrain.
38.30	East Fork Bitter Creek (dry), course NW.
39.69	The cor. of secs. 22, 23, 26 and 27, monumented by person(s) unknown, with a steel reinforcement rod, 18 ins. long, 5/8 in. diam., firmly set 16 ins. in the ground, with unmkd. aluminum cap, at cor. of abandoned fences extending E. and S. This position is filed in the Campbell County Clerk's Office and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T56N R73W S 22   S 23 ----- S 27   S 26 2001</p>
	<p>Deposit the steel reinforcement rod inside and set a steel fence post alongside the stainless steel post.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26, identical with Cor. No. 2, Tract 70.</p>
	<p>S. 89° 10' W., bet. secs. 23 and 26.</p>
	<p>Over gently rolling terrain.</p>
40.46	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T56N R73W S 23 1/4 ——— S 26 2001</p>
	<p>Set a steel fence post alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p>
80.92	<p>The cor. of secs. 22, 23, 26 and 27.</p>
	<p>N. 0° 34' E., bet. secs. 22 and 23.</p>
	<p>Over rolling terrain.</p>
40.665	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T56N R73W 1/4 S 22   S 23 2001</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS											
	Set a steel fence post alongside the stainless steel post.										
48.70	Bay Horse Road, bears ENE. and WSW.										
81.315	The witness cor. to the cor. of secs. 14, 15, 22 and 23, established by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, as filed in the Campbell County Clerk's Office, monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd. RUMPH SURVEYS GILLETTE WYOMING WC 1' S 14 15 22 23 LS 538 1986.										
81.33	The cor. of secs. 14, 15, 22 and 23, monumented with a red sandstone, 12x8x3 ins., firmly set 8 ins. in the ground, no mks. visible, with a steel fence post and a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 3 ins. above the ground alongside. This position is accepted as the best available evidence of the original cor. position.										
	At the corner point										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T56N R73W</td></tr> <tr><td>S 15</td><td>S 14</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 22</td><td>S 23</td></tr> <tr><td colspan="2">2001</td></tr> </table>	T56N R73W		S 15	S 14	-----		S 22	S 23	2001	
T56N R73W											
S 15	S 14										
-----											
S 22	S 23										
2001											
	Deposit the steel reinforcement rod inside and bury the unmkd. stone alongside the stainless steel post.										
	Cor. is located 21 lks. W. of fence extending N. and S.										
	From the cor. of secs. 13, 14, 23 and 24, identical with Cor. No. 5, Tract 65 and Cor. No. 2, Tract 67, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with a mound of stone, 4 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T56N R73W</td></tr> <tr><td>S 14</td><td>S 13</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 23</td><td>S 24</td></tr> <tr><td colspan="2">1922</td></tr> </table>	T56N R73W		S 14	S 13	-----		S 23	S 24	1922	
T56N R73W											
S 14	S 13										
-----											
S 23	S 24										
1922											
	S. 89° 48' W., bet. secs. 14 and 23.										

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Over rolling terrain.
39.65	The 1/4 sec. cor. of secs. 14 and 23, monumented with a mound of stone, 4 ft. base, 1 ft. high, no mkd. stone found. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R73W S 14 1/4 ——— S 23 2001</p>
	Set a steel fence post alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of the cor.
	<p style="text-align: center;">—————</p>
	S. 89° 10' W., beginning new measurement.
	Over rolling terrain.
26.70	Bay Horse Road, bears N. and S.
40.49	The cor. of secs. 14, 15, 22 and 23.
	<p style="text-align: center;">—————</p>
	N. 0° 46' E., bet. secs. 14 and 15.
	Over rolling terrain.
40.485	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R73W 1/4 S 15   S 14 2001</p>
	Set a steel fence post alongside the stainless steel post.

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>From this point, a property cor., established by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, bears N. 58° 16' E., 2.36 chs. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, at intersection of fences extending N., E. and S., with plastic cap mkd. B.E. RUMPH.</p> <p>80.97 The cor. of secs. 10, 11, 14 and 15, monumented by person(s) unknown, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 11 ins. above the ground, in fence extending E. and W., with a sandstone, 12x6x4 ins., lying loose alongside, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T56N R73W</td> </tr> <tr> <td style="text-align: center;">S 10</td> <td style="text-align: center;">S 11</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 15</td> <td style="text-align: center;">S 14</td> </tr> <tr> <td colspan="2" style="text-align: center;">2001</td> </tr> </table> <p>Deposit the steel reinforcement rod inside and bury the unmkd. stone alongside the stainless steel post.</p> <p>Cor. is located S. 88¾° W., 3.71 chs. dist., from cor. of fences extending W. and S.</p> <p>From this point, a property cor., established by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, bears S. 74° 46' E., 3.80 chs. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, at intersection of fences extending N., E. and S., with plastic cap mkd. B.E. RUMPH.</p>	T56N R73W		S 10	S 11	-----		S 15	S 14	2001	
T56N R73W											
S 10	S 11										
-----											
S 15	S 14										
2001											
39.66	<p>From the cor. of secs. 11, 12, 13 and 14, identical with Cor. No. 3, Tract 62.</p> <p>S. 89° 41' W., bet. secs. 11 and 14.</p> <p>Over rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original cor.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R73W S 11 1/4 ——— S 14 2001</p>
	Set a steel fence post alongside the stainless steel post.
	Cor. is located 58 lks. N. of fence extending E. and W.
48.10	Bay Horse Road, bears NE. and SW.
79.32	The cor. of secs. 10, 11, 14 and 15.
	N. 0° 26' W., bet. secs. 10 and 11.
	Over rolling terrain.
39.965	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R73W 1/4 S 10   S 11 2001</p>
	Set a steel fence post alongside the stainless steel post.
73.60	Chalk Prong Bitter Creek (dry), course NW.
79.93	Point for the cor. of secs. 2, 3, 10 and 11, identical with Cor. No. 4, Tract 48, determined longitudinally by proportionate measurement and latitudinally at record dist. from Cor. No. 1, Tract 48, identical with Cor. No. 2, Tract 47, falls in W. borrow ditch of Bay Horse Road extending N. and SSE.; there is no remaining evidence of the 1922 cor. position.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T56N R73W S 3   S 2 ----- S 10   S 11 2001</p> <p>Cor. is located 42 lks. W. of center of Bay Horse Road extending N. and SSE.</p> <p>From this point, Cor. No. 1, Tract 48, identical with Cor. No. 2, Tract 47, bears N. 0° 31' W., 80.00 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R73W S 3   S 2 ----- 1   2 TR 48   TR 47 1922</p> <p>This control line was fully retraced and a careful search was made for the intervening cors., none of which were found.</p> <hr/> <p style="text-align: center;">(Restoring the resurvey executed by Mark D. King in 1922)</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12, identical with Cor. No. 3, Tract 44 and Cor. No. 4, Tract 46.</p> <p>S. 89° 14' W., bet. secs. 2 and 11.</p> <p>Over rolling terrain.</p> <p>40.14 The 1/4 sec. cor. of secs. 2 and 11, identical with Cor. 3, Tract 46, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, N. of the cor., with brass cap mkd.</p> <p style="text-align: center;">S 2 1/4 ——— S 11 1922</p> <hr/> <p>S. 89° 18' W., beginning new measurement.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 56 N., R. 73 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.07	<p>Over rolling terrain.</p> <p>The cor. of secs. 2, 3, 10 and 11, identical with Cor. No. 4, Tract 48.</p>
39.61	<hr/> <p style="text-align: center;">(Restoring the survey executed by Mortimer N. Grant in 1883)</p> <hr/> <p>From the cor. of secs. 33 and 34 only, on the S. bdy. of the Tp. N. 0° 01' W., bet. secs. 33 and 34.</p> <p>Over rolling terrain.</p> <p>The 1/4 sec. cor. of secs. 33 and 34, monumented with a sandstone, 16x13x3 ins., firmly set 16 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R73W 1/4 S 33   S 34 2001</p> <p>Bury the unmkd. stone and set a steel fence post alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located 14 lks. E. of fence extending N. and S.</p>
40.28	<hr/> <p>N. 2° 35' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>