

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T56N R76W S 14 E1/16—— S 23 1989</p> <p>from which a bearing object</p> <p style="padding-left: 40px;">A sandstone boulder, 18x17x5 ft., bears S. 6° W., 23.0 lks. dist., mkd. X B0.</p> <p>Set a steel fence post alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located on S. facing slope of ridge extending ESE. and WNW.</p>
39.86	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R76W S 14 1/4 —— S 23 1989</p>
59.79	<p>Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located in bottom of draw, drains SW.</p> <p>Point for the W. 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
79.72	<p style="text-align: center;">T56N R76W S 14 W1/16—— S 23 1989</p> <p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 0° 03' E., bet. secs. 14 and 15.</p> <p>Over rolling to broken terrain.</p>
20.21	<p>Point for the S. 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T56N R76W S1/16 S 15 S 14 1989</p>
	<p>Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.</p>
40.42	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T56N R76W 1/4 S 15 S 14 1989</p>
	<p>Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.</p>
	<p>Cor. is located on E. edge of draw, drains NNE.</p>
80.84	<p>The cor. of secs. 10, 11, 14 and 15, determined at cor. of abandoned fences extending N. and E. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T56N R76W S 10 S 11 ----- S 15 S 14 1989</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>WEST, bet. secs. 11 and 14.</p> <p>Over rolling to broken terrain, through scattered timber.</p>
19.94	<p>Point for the E. 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R76W S 11 E1/16 — S 14 1989</p> <p>Set a steel fence post alongside the iron post.</p>
39.88	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R76W S 11 1/4 — S 14 1989</p> <p>Set a steel fence post alongside the iron post.</p>
79.76	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/>
43.66	<p>N. 0° 55' E., bet. secs. 10 and 11.</p> <p>Over broken terrain, through scattered timber.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R76W 1/4 S 10 S 11 1989</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
87.32	<p>Set a steel fence post alongside the iron post.</p> <p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T56N</td><td>R76W</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div>	T56N	R76W	S 3	S 2	<hr/>		S 10	S 11	1989	
T56N	R76W										
S 3	S 2										
<hr/>											
S 10	S 11										
1989											
20.02	<p>Set a steel fence post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 84° 53' W., bet. secs. 2 and 11.</p> <p>Over rolling terrain.</p> <p>Point for the E. 1/16 sec. cor. of secs. 2 and 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T56N</td><td>R76W</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>E1/16</td><td>—</td></tr> <tr><td>S 11</td><td></td></tr> <tr><td colspan="2">1989</td></tr> </table> </div>	T56N	R76W	S 2		E1/16	—	S 11		1989	
T56N	R76W										
S 2											
E1/16	—										
S 11											
1989											
40.04	<p>Set a steel fence post alongside the iron post.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T56N</td><td>R76W</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 11</td><td></td></tr> <tr><td colspan="2">1989</td></tr> </table> </div>	T56N	R76W	S 2		1/4	—	S 11		1989	
T56N	R76W										
S 2											
1/4	—										
S 11											
1989											

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
80.08	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/>
	<p>N. 7° 25' W., bet. secs. 2 and 3.</p> <p>Over rolling terrain.</p>
44.03	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T56N R76W 1/4 S 3 S 2 1989</p>
66.05	<p>Set a steel fence post alongside the iron post.</p> <p>Point for the N. 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T56N R76W N1/16 S 3 S 2 1989</p>
88.16	<p>Set a steel fence post alongside the iron post.</p> <p>Point for the closing cor. of secs. 2 and 3, at intersection with the Fourteenth Standard Parallel North, at proportionate measurement; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T57N R75W S 34 ----- S 3 S 2 T56N R76W C C 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, the angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 35, T. 57 N., R. 76 W., bears N. 89° 08' E., 14.20 chs. dist.</p>
	<p>The point for the 1/4 sec. cor. of sec. 2 only, T. 56 N., R. 76 W., is at midpoint on the N. bdy. of sec. 2.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T57N R76W ----- 1/4 S 2 T56N R76W 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>From this point, the angle point marking the restored position of the original standard cor. of secs. 35 and 36, T. 57 N., R. 76 W., bears N. 89° 44' E., 14.22 chs. dist.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.</p>
	<p>N. 1° 13' W., bet. secs. 33 and 34.</p>
	<p>Over broken terrain.</p>
39.77	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T56N R76W 1/4 S 33 S 34 1989</p>
	<p>Set a steel fence post alongside the iron post.</p> <p>From this point an intersection of abandoned fences extending N., S. and W., bears N. 45° W., 4.95 chs. dist.</p>
79.54	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T56N</td> <td>R76W</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table>	T56N	R76W	S 28	S 27			S 33	S 34	1989	
T56N	R76W										
S 28	S 27										
S 33	S 34										
1989											
	<p>Set a steel fence post alongside the iron post.</p> <p>From this point an intersection of fences extending E. and S., with abandoned fence extending N., bears S. 81° E., 3.73 chs. dist.</p> <hr/>										
	<p>From the cor. of secs. 26, 27, 34 and 35.</p>										
	<p>S. 89° 30' W., bet. secs. 27 and 34.</p>										
	<p>Over gently rolling terrain.</p>										
40.02	<p>The 1/4 sec. cor. of secs. 27 and 34, determined at intersection of fences extending E., S. and W. This position is accepted as the best available evidence of the original cor. position.</p>										
	<p>At the corner point</p>										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T56N</td> <td>R76W</td> </tr> <tr> <td>S 27</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 34</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table>	T56N	R76W	S 27		1/4	—	S 34		1989	
T56N	R76W										
S 27											
1/4	—										
S 34											
1989											
	<p>Set a steel fence post alongside the iron post.</p> <hr/>										
	<p>S. 87° 56' W., beginning new measurement.</p>										
	<p>Over rolling to broken terrain.</p>										
37.64	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 2° 30' E., bet. secs. 27 and 28.
	Over rolling terrain.
39.80	Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R76W 1/4 S 28 S 27 1989</p>
	Set a steel fence post alongside the iron post.
79.60	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.
	Set an aluminum rod, 24 ins. long, 5/8 in. diam., 18 ins. below the surface of the ground, with magnetic aluminum cap mkd.
	<p style="text-align: center;">T56N R76W S 21 S 22 ----- S 28 S 27 1989</p>
	From the cor. of secs. 22, 23, 26 and 27.
	S. 87° 49' W., bet. secs. 22 and 27.
	Over rolling terrain.
39.38	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R76W S 22 1/4 ——— S 27 1989</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
78.76	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>N. 1° 00' W., bet. secs. 21 and 22.</p> <p>Over gently rolling terrain.</p>
19.88	<p>Point for the S. 1/16 sec. cor. of secs. 21 and 22, falls in cultivated field.</p>
	<p>Set an aluminum rod, 24 ins. long, 5/8 in. diam., 16 ins. below the surface of the ground, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T56N R76W S1/16 S 21 S 22 1989</p>
	<p>Cor. is located 11 lks. S. of fence extending E. and W.</p>
39.76	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T56N R76W 1/4 S 21 S 22 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
59.64	<p>Point for the N. 1/16 sec. cor. of secs. 21 and 22.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R76W N1/16 S 21 S 22 1989</p>
	<p>Set a steel fence post alongside the iron post.</p>
79.52	<p>The cor. of secs. 15, 16, 21 and 22, determined at intersection of fences extending N., S., E. and W. This position is accepted as the best available evidence of the original cor. position.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS						
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T56N R76W</td> </tr> <tr> <td style="text-align: center;">S 16 S 15</td> </tr> <tr> <td style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 21 S 22</td> </tr> <tr> <td style="text-align: center;">1989</td> </tr> </table>	T56N R76W	S 16 S 15	-----	S 21 S 22	1989
T56N R76W						
S 16 S 15						

S 21 S 22						
1989						
	<hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 86° 53' W., bet. secs. 15 and 22.</p> <p>Over rolling terrain.</p>					
19.84	<p>Point for the E. 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T56N R76W</td> </tr> <tr> <td style="text-align: center;">S 15</td> </tr> <tr> <td style="text-align: center;">E1/16 ———</td> </tr> <tr> <td style="text-align: center;">S 22</td> </tr> <tr> <td style="text-align: center;">1989</td> </tr> </table>	T56N R76W	S 15	E1/16 ———	S 22	1989
T56N R76W						
S 15						
E1/16 ———						
S 22						
1989						
39.68	<p>Set a steel fence post alongside the iron post.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p>					
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T56N R76W</td> </tr> <tr> <td style="text-align: center;">S 15</td> </tr> <tr> <td style="text-align: center;">1/4 ———</td> </tr> <tr> <td style="text-align: center;">S 22</td> </tr> <tr> <td style="text-align: center;">1989</td> </tr> </table>	T56N R76W	S 15	1/4 ———	S 22	1989
T56N R76W						
S 15						
1/4 ———						
S 22						
1989						
79.36	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/>					

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
38.73	<p>N. 0° 06' E., bet. secs. 15 and 16.</p> <p>Over rolling terrain, along fence.</p> <p>The 1/4 sec. cor. of secs. 15 and 16, determined at intersection of fences extending N., S. and E. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R76W 1/4 S 16 S 15 1989</p> <hr style="width: 20%; margin: auto;"/> </div>
19.53	<p>N. 0° 43' W., beginning new measurement.</p> <p>Over rolling to broken terrain.</p> <p>Point for the N. 1/16 sec. cor. of secs. 15 and 16.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R76W N1/16 S 16 S 15 1989</p> </div>
39.06	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p> <p>Cor. is located 28 lks. W. of fence extending N. and S.</p> <p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R76W S 9 S 10 <hr style="width: 20%; margin: auto;"/> S 16 S 15 1947</p> <hr style="width: 80%; margin: auto;"/> </div>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 84° 44' W., bet. secs. 10 and 15.</p> <p>Over broken terrain, through scattered timber.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R76W S 10 1/4 ——— S 15 1989</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on ridge extending SE. and NW.</p> <p>80.00 The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p style="text-align: center;">(Restoring the resurvey executed by Russell C. MacDonald in 1947)</p> <hr/> <p>N. 0° 59' E., bet. secs. 9 and 10.</p> <p>Over broken terrain.</p> <p>40.00 The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.</p> <p style="text-align: center;">1/4 S 9 S 10 1947</p> <hr/> <p>N. 1° 00' E., beginning new measurement.</p> <p>Over broken terrain.</p>
--------	--

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
40.05	<p>The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2 ins. diam., firmly set 42 ins. below the surface of the ground in bottom of draw, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T56N</td> <td>R76W</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> <tr> <td colspan="2">1947</td> </tr> </table> </div> <p>from which new bearing trees</p> <p>A juniper, 7 ins. diam., bears S. 55° W., 24.5 lks. dist., mkd. X BT.</p> <p>A juniper, 8 ins. diam., bears N. 81½° W., 57.0 lks. dist., mkd. T56N R76W S4 BT.</p> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Charles Holcomb in 1883)</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 79° 36' W., bet. secs. 3 and 10.</p> <p>Over broken terrain.</p>	T56N	R76W	S 4	S 3	<hr/>		S 9	S 10	1947	
T56N	R76W										
S 4	S 3										
<hr/>											
S 9	S 10										
1947											
40.50	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T56N</td> <td>R76W</td> </tr> <tr> <td>S 3</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 10</td> <td></td> </tr> <tr> <td colspan="2">1989</td> </tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T56N	R76W	S 3		1/4	—	S 10		1989	
T56N	R76W										
S 3											
1/4	—										
S 10											
1989											
81.00	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">(Restoring the resurvey executed by Russell C. MacDonald in 1947)</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 01' E., bet. secs. 3 and 4.</p> <p>Over broken terrain.</p> <p>40.25 The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with a mound of stone, 2 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td></td><td style="text-align: center;">1/4</td><td></td></tr> <tr><td style="text-align: center;">S</td><td style="text-align: center;">4 S</td><td style="text-align: center;">3</td></tr> <tr><td></td><td style="text-align: center;">1947</td><td></td></tr> </table> </div> <hr style="width: 20%; margin: auto;"/> <p>N. 10° 24' W., beginning new measurement.</p> <p>Over broken terrain.</p> <p>62.15 The closing cor. of secs. 3 and 4, at intersection with the Fourteenth Standard Parallel North, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above the ground, with a mound of stone, 3 ft. base, 2 ft. high, S. of the cor., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td></td><td style="text-align: center;">S</td><td style="text-align: center;">4</td><td style="text-align: center;">S</td><td style="text-align: center;">3</td></tr> <tr><td></td><td style="text-align: center;">T56N</td><td style="text-align: center;"> </td><td style="text-align: center;">R76W</td><td></td></tr> <tr><td></td><td style="text-align: center;">C</td><td style="text-align: center;">C</td><td></td><td></td></tr> <tr><td></td><td style="text-align: center;">1947</td><td></td><td></td><td></td></tr> </table> </div> <p>From this point, the angle point marking the restored position of the original standard 1/4 sec. cor. of sec. 34, T. 57 N., R. 76 W., bears N. 89° 39' E., 14.80 chs. dist.</p> <hr style="width: 20%; margin: auto;"/> <p>The point for the 1/4 sec. cor. of sec. 3 only, T. 56 N., R. 76 W., is at midpoint on the N. bdy. of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td></td><td style="text-align: center;">T57N</td><td style="text-align: center;">R76W</td><td></td></tr> <tr><td></td><td style="text-align: center;">1/4</td><td style="text-align: center;">S</td><td style="text-align: center;">3</td></tr> <tr><td></td><td style="text-align: center;">T56N</td><td style="text-align: center;">R76W</td><td></td></tr> <tr><td></td><td style="text-align: center;">1989</td><td></td><td></td></tr> </table> </div>		1/4		S	4 S	3		1947			S	4	S	3		T56N		R76W			C	C				1947					T57N	R76W			1/4	S	3		T56N	R76W			1989		
	1/4																																													
S	4 S	3																																												
	1947																																													
	S	4	S	3																																										
	T56N		R76W																																											
	C	C																																												
	1947																																													
	T57N	R76W																																												
	1/4	S	3																																											
	T56N	R76W																																												
	1989																																													

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set a steel fence post alongside the iron post.</p> <p>From this point, the angle point marking the restored position of the original standard cor. of secs. 34 and 35, T. 57 N., R. 76 W., bears N. 89° 42' E., 14.91 chs. dist.</p> <hr/> <p>The point for the E. 1/16 sec. cor. of sec. 3 only, T. 56 N., R. 76 W., is at midpoint bet. the closing cor. of secs. 2 and 3 and the 1/4 sec. cor. of sec. 3 only, on the N. bdy. of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T57N R76W ----- E1/16 S 3 T56N R76W 1989</p> <p>From this point, the angle point marking the restored position of the original standard cor. of secs. 34 and 35, T. 57 N., R. 76 W., bears S. 89° 08' W., 4.96 chs. dist.</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Charles Holcomb in 1883)</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.</p> <p>N. 0° 33' W., bet. secs. 32 and 33.</p> <p>Over rolling to broken terrain.</p> <p>38.79 Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R76W 1/4 S 32 S 33 1989</p> <p>Set a steel fence post alongside the iron post.</p>
--------	--

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
77.58	<p>The cor. of secs. 28, 29, 32 and 33, monumented with a fragmented sandstone, 8x6x2 ins., loosely set 4 ins. in the ground, plainly mkd. 4 notches on E. edge, no other mks. visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="878 625 1024 779" style="margin-left: auto; margin-right: auto;"> <tr> <td>T56N</td> <td>R76W</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr/>	T56N	R76W	S 29	S 28			S 32	S 33	1989	
T56N	R76W										
S 29	S 28										
S 32	S 33										
1989											
37.80	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 86° 50' W., bet. secs. 28 and 33.</p> <p>Over broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="878 1325 1024 1478" style="margin-left: auto; margin-right: auto;"> <tr> <td>T56N</td> <td>R76W</td> </tr> <tr> <td>S 28</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 33</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> <p>Set a steel fence post alongside the iron post.</p>	T56N	R76W	S 28		1/4	—	S 33		1989	
T56N	R76W										
S 28											
1/4	—										
S 33											
1989											
75.60	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0° 01' E., bet. secs. 28 and 29.</p> <p>Over broken terrain.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.18	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, determined longitudinally by proportionate measurement and latitudinally by an abandoned fence extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R76W 1/4 S 29 S 28 1989</p> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 01' E., beginning new measurement.</p> <p>Over broken terrain.</p>
40.47	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R76W S 20 S 21 <hr style="width: 10%; margin: auto;"/> S 29 S 28 1989</p> <p>from which a bearing object</p> <p style="padding-left: 40px;">A sandstone outcrop, bears S. 24° E., 0.62 chs. dist., mkd. X B0.</p> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 87° 04' W., bet. secs. 21 and 28.</p> <p>Over gently rolling terrain.</p>
19.76	<p>Point for the E. 1/16 sec. cor. of secs. 21 and 28.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R76W S 21 E1/16 ——— S 28 1989</p>
	Set a steel fence post alongside the iron post.
	Cor. is located 64 lks. W. of fence extending N. and S.
39.52	Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R76W S 21 1/4 ——— S 28 1989</p>
	Set a steel fence post alongside the iron post.
79.04	The cor. of secs. 20, 21, 28 and 29.
	N. 1° 18' W., bet. secs. 20 and 21.
	Over rolling to broken terrain.
40.48	Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T56N R76W 1/4 S 20 S 21 1989</p>
80.96	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS						
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T56N R76W</td></tr> <tr><td>S 17 S 16</td></tr> <tr><td>— —</td></tr> <tr><td>S 20 S 21</td></tr> <tr><td>1989</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <hr/>	T56N R76W	S 17 S 16	— —	S 20 S 21	1989
T56N R76W						
S 17 S 16						
— —						
S 20 S 21						
1989						
20.36	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89° 54' W., bet. secs. 16 and 21.</p> <p>Over rolling to broken terrain, along fence.</p> <p>Point for the E. 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T56N R76W</td></tr> <tr><td>S 16</td></tr> <tr><td>E1/16 —</td></tr> <tr><td>S 21</td></tr> <tr><td>1989</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located in abandoned fence extending E. and W.</p>	T56N R76W	S 16	E1/16 —	S 21	1989
T56N R76W						
S 16						
E1/16 —						
S 21						
1989						
40.72	<p>The 1/4 sec. cor. of secs. 16 and 21, determined at intersection of abandoned fence extending E. and W., with fence extending S. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T56N R76W</td></tr> <tr><td>S 16</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S 21</td></tr> <tr><td>1989</td></tr> </table> <hr/> </div>	T56N R76W	S 16	1/4 —	S 21	1989
T56N R76W						
S 16						
1/4 —						
S 21						
1989						

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>S. 86° 13' W., beginning new measurement.</p> <p>Over broken terrain.</p>
38.68	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/>
	<p>N. 2° 13' E., bet. secs. 16 and 17.</p> <p>Over rolling terrain.</p>
40.50	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R76W 1/4 S 17 S 16 1989</p> </div> <p>Set a steel fence post alongside the iron post.</p>
81.00	<p>The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above the ground, at intersection of fences extending N. and W., with abandoned fences extending S. and E., with brass cap mkd.</p> <div style="text-align: center;"> <p>T56N R76W S 8 S 9 ----- S 17 S 16 1947</p> </div> <hr/> <p style="text-align: center;">(Restoring the resurvey executed by Russell C. MacDonald in 1947)</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89° 39' W., bet. secs. 9 and 16.</p> <p>Over rolling terrain.</p>
38.21	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above the ground, at cor. of abandoned fences extending N. and S., with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">S 9 1/4 ——— S 16 1947</p>
	<p>Cor. is located 1.10 chs. N. of intersection of fences extending E., S., with abandoned fence extending N.</p> <hr style="width: 30%; margin: auto;"/> <p>N. 89° 31' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
37.51	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr style="width: 60%; margin: auto;"/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.</p> <p>N. 0° 54' E., bet. secs. 31 and 32.</p> <p>Over broken terrain.</p>
20.08	<p>Point for the S. 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T56N R76W S1/16 S 31 S 32 1989</p> <p>Set a steel fence post alongside the iron post.</p>
40.16	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 31 S 32 1947</p> <hr style="width: 30%; margin: auto;"/> <p>N. 1° 07' E., beginning new measurement.</p> <p>Over broken terrain.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS											
39.97	<p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T56N</td> <td>R76W</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> <tr> <td colspan="2">1947</td> </tr> </table> </div> <hr/> <p style="text-align: center;">(Restoring the survey executed by Charles Holcomb in 1883)</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 87° 56' W., bet. secs. 29 and 32.</p> <p>Over broken terrain.</p>	T56N	R76W	S 30	S 29	<hr/>		S 31	S 32	1947	
T56N	R76W										
S 30	S 29										
<hr/>											
S 31	S 32										
1947											
39.56	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T56N</td> <td>R76W</td> </tr> <tr> <td>S 29</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 32</td> <td></td> </tr> <tr> <td colspan="2">1989</td> </tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T56N	R76W	S 29		1/4	—	S 32		1989	
T56N	R76W										
S 29											
1/4	—										
S 32											
1989											
79.12	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p style="text-align: center;">(Restoring the resurvey executed by Russell C. MacDonald in 1947)</p> <hr/> <p>N. 0° 05' E., bet. secs. 29 and 30.</p> <p>Over broken terrain.</p>										
39.98	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<div style="text-align: center;"> $\frac{1}{4}$ S 30 S 29 1947 </div> <hr/>
	<p>N. 0° 01' E., beginning new measurement.</p>
	<p>Over broken terrain.</p>
39.78	<p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> T56N R76W S 19 S 20 <hr style="width: 50%; margin: 0 auto;"/> S 30 S 29 1947 </div> <hr/>
	<div style="text-align: center;"> (Restoring the survey executed by Charles Holcomb in 1883) </div> <hr/>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p>
	<p>N. 87° 51' W., bet. secs. 20 and 29.</p>
	<p>Over rolling to broken terrain.</p>
39.52	<p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate measurement; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> T56N R76W S 20 1/4 ——— S 29 1989 </div>
	<p>Set a steel fence post alongside the iron post.</p>
79.04	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<p>(Restoring the resurvey executed by Russell C. MacDonald in 1947)</p> <hr/>												
	<p>N. 0° 11' E., bet. secs. 19 and 20.</p> <p>Over rolling terrain.</p>												
39.93	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 19</td><td style="text-align: center;"> S 20</td></tr> <tr><td colspan="2" style="text-align: center;">1947</td></tr> </table> </p> <hr/>	1/4		S 19	S 20	1947							
1/4													
S 19	S 20												
1947													
	<p>N. 0° 06' E., beginning new measurement.</p> <p>Over broken terrain.</p>												
34.75	<p>The witness cor. to the cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T56N R76W</td></tr> <tr><td colspan="2" style="text-align: center;">W C</td></tr> <tr><td style="text-align: center;">S 18</td><td style="text-align: center;"> S 17</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 19</td><td style="text-align: center;"> S 20</td></tr> <tr><td colspan="2" style="text-align: center;">1947</td></tr> </table> </p> <hr/>	T56N R76W		W C		S 18	S 17	-----		S 19	S 20	1947	
T56N R76W													
W C													
S 18	S 17												

S 19	S 20												
1947													
	<p>N. 0° 06' E., beginning new measurement</p> <p>Over broken terrain.</p>												
5.26	<p>True point for the cor. of secs. 17, 18, 19 and 20, at record dist., falls on steep slope where it is impracticable to establish a permanent monument.</p> <hr/>												
	<p>(Restoring the survey executed by Charles Holcomb in 1883)</p> <hr/>												
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 88° 33' W., bet. secs. 17 and 20.</p>												

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
38.48	<p>Over broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
76.96	<p style="text-align: center;">T56N R76W S 17 1/4 ——— S 20 1989</p> <p>Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located on W. edge of draw, drains SSW.</p> <p>True point for the cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p style="text-align: center;">(Restoring the resurvey executed by Russell C. MacDonald in 1947)</p> <hr/> <p>N. 0° 36' E., bet. secs. 17 and 18.</p> <p>Over broken terrain.</p>
20.98	<p>Point for the S. 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
41.96	<p style="text-align: center;">T56N R76W S1/16 S 18 S 17 1989</p> <p>Set a steel fence post alongside the iron post and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <p>The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<div style="text-align: center;"> <p>1/4 S 18 S 17 1947</p> <hr/> </div>
38.52	<p>N. 0° 12' W., beginning new measurement.</p> <p>Over broken terrain.</p> <p>The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T56N R76W S 7 S 8 <hr/>S 18 S 17 1947</p> <hr/> </div>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89° 06' W., bet. secs. 8 and 17.</p> <p>Over rolling terrain.</p>
40.00	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with petrified wood, firmly set, projecting 16x10x8 ins. above the ground alongside, no mks. visible, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>S 8 1/4 ——— S 17 1947</p> <hr/> </div>
	<p>N. 88° 44' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
39.77	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/>

T. 56 N., R. 76 W., Sixth Principal Meridian, Wyoming

CHAINS

GENERAL DESCRIPTION

The area embraced by this survey is situated in Sheridan and Campbell Counties, approximately 40 miles northwest of Gillette, Wyoming. The terrain varies from rolling to broken, with the elevation ranging from about 3,600 feet to about 4,195 feet above sea level. The soil varies from sandy loam to bedrock. The timber primarily consists of cottonwoods along the major drainages, with scattered stands of pinon pine and juniper. The vegetation consists of a light to moderate growth of sagebrush and native grasses.

Primary drainage is provided by Spotted Horse Creek and Ivy Creek, both flowing northwest to the Powder River, aided by numerous other creeks and draws throughout the area. There are four working ranches within the area surveyed. The area is utilized for grazing and cultivation of bottomland and mesas. There is evidence of past oil and gas exploration in the area.

Access is provided by U.S. Highway No. 14/16 and the S-A, Matz, and Ivy Creek Roads, all of which are assisted by numerous other roads and trails throughout the township.

CERTIFICATE OF SURVEY

We, Bruce M. Mortimer, Cadastral Surveyor, and Mark L. Bush, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 12th day of February, 1988, we have dependently resurveyed a portion of the Fourteenth Standard Parallel North, through Range 76 West, a portion of the south boundary, the east boundary and portions of the subdivisional lines, Township 56 North, Range 76 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAY 18 2000

(Date)

Bruce M. Mortimer
 (Not Available for Signature)
 (Cadastral Surveyor)

MAY 18 2000

(Date)

Mark L. Bush
 (Not Available for Signature)
 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of a portion of the Fourteenth Standard Parallel North, through Range 76 West, a portion of the south boundary, the east boundary and portions of the subdivisional lines, Township 56 North, Range 76 West, Sixth Principal Meridian, Wyoming, executed by Bruce M. Mortimer and Mark L. Bush, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

MAY 18 2000

(Date)

John P. Lee
 (Signature of Authorized Officer)