

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
DEPENDENT RESURVEY
OF A PORTION
OF THE SUBDIVISIONAL LINES,
AND THE
SUBDIVISION OF SECTIONS 10 AND 11,
TOWNSHIP 18 NORTH, RANGE 82 WEST,
OF THE SIXTH PRINCIPAL MERIDIAN,
IN THE STATE OF WYOMING.

EXECUTED BY

LYNN A. FORBES

CADASTRAL SURVEYOR

Under Special Instructions dated MAY 30, 2001, approved MAY 30, 2001, which provided for the surveys included under Group Number 694, and assignment instructions dated MAY 30, 2001.

Survey commenced JULY 9, 2001

Survey completed JULY 10, 2002

INDEX DIAGRAM

Township 18 North, Range 82 West

6	5	4	3	2	1
			18	15	
7	8	9	17 10	13 11	10 12
			16	11	
18	17	16	15	14	8 13
19	20	21	22	23	6 24
30	29	28	27	26	4 25
					2
31	32	33	34	35	36

T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 10 and 11, Township 18 North, Range 82 West, Sixth Principal Meridian, Wyoming.</p> <p>Lewis M. Lampton surveyed the exterior boundaries in 1878, and the subdivisional lines in 1878. Mark D. King dependently resurveyed the east and north boundaries in 1939. Thomas W. Crawford remonumented certain original corners in 1960.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 694, Wyoming, dated May 30, 2001.</p> <p>Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data was thoroughly verified and only true line field notes are given herein, which refer to the completed survey.</p> <p>The survey was executed with a Global Positioning System (GPS) TRIMBLE Model 4700 receiver, a LEICA Total Station Model TC-800 and by chaining methods. The instruments were maintained in proper adjustment at all times. The directions, distances and geographic positions were determined by G.P.S.</p> <p>The geographic position of the corner of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., based on NAD 83 (1993) and determined by satellite positioning methods, is:</p> <p>Latitude 41° 29' 48.506" N., Longitude 106° 33' 16.727" W.</p> <p>The magnetic declination is 11° E.</p> <hr/>
--------	---

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS																							
	<p>(Restoring the survey executed by Lewis M. Lampton in 1878)</p> <hr/> <p>Beginning at the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with a mound of stone, 2 ft. base, 1 ft. high, W. of the cor., with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T18N</td></tr> <tr><td style="text-align: center;">R82W</td><td style="text-align: center;">R81W</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 36</td><td style="text-align: center;">S 31</td></tr> <tr><td colspan="2" style="text-align: center;">1939</td></tr> </table> <p>S. 89° 55' W., bet. secs. 25 and 36.</p> <p>Over mountainous terrain, through pine timber.</p> <p>25.00 Enter logged area.</p> <p>40.13 Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T18N R82W</td></tr> <tr><td colspan="2" style="text-align: center;">S 25</td></tr> <tr><td style="text-align: center;">1/4</td><td style="text-align: center;">-----</td></tr> <tr><td colspan="2" style="text-align: center;">S 36</td></tr> <tr><td colspan="2" style="text-align: center;">2002</td></tr> </table> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 14° W., 31 lks. dist., mkd. 1/4 S36 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 46° W., 18 lks. dist., mkd. 1/4 S25 BT.</p> <p>Set an aluminum sign post alongside the stainless steel post.</p> <p>Thence through intermittent pine timber and logged areas.</p> <p>80.26 Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p>	T18N		R82W	R81W	S 25	S 30	-----		S 36	S 31	1939		T18N R82W		S 25		1/4	-----	S 36		2002	
T18N																							
R82W	R81W																						
S 25	S 30																						

S 36	S 31																						
1939																							
T18N R82W																							
S 25																							
1/4	-----																						
S 36																							
2002																							

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T18N R82W</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 26</td> <td style="text-align: center;">S 25</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black;">S 35 S 36</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table> <p>from which</p> <p style="margin-left: 40px;">A pine, 10 ins. diam., bears N. 48° E., 36 lks. dist., mkd. T18N R82W S25 BT.</p> <p style="margin-left: 40px;">A pine, 12 ins. diam., bears S. 36° E., 8 lks. dist., mkd. T18N R82W S36 BT.</p> <p style="margin-left: 40px;">A pine, 10 ins. diam., bears S. 68° W., 20 lks. dist., mkd. T18N R82W S35 BT.</p> <p style="margin-left: 40px;">A pine, 12 ins. diam., bears N. 7° W., 14 lks. dist., mkd. T18N R82W S26 BT.</p> <p>Set an aluminum sign post alongside the stainless steel post.</p> <p>From this point, the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., bears S. 1° 50' E., 78.83 chs. dist., monumented with a granite stone, 18x10x10 ins., firmly set 12 ins. in the ground, plainly mkd. 1 groove on E. face and 5 grooves on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T18N R82W</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 35</td> <td style="text-align: center;">S 36</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black;">S 2 S 1</td> </tr> <tr> <td colspan="2" style="text-align: center;">T17N</td> </tr> <tr> <td colspan="2" style="text-align: center;">2001</td> </tr> </table> <p>Bury the original cor. stone and set a steel fence post alongside the stainless steel post.</p> <p>The control line was fully retraced and no evidence of the intervening cor. was found.</p>	T18N R82W		S 26	S 25	S 35 S 36		2002		T18N R82W		S 35	S 36	S 2 S 1		T17N		2001	
T18N R82W																			
S 26	S 25																		
S 35 S 36																			
2002																			
T18N R82W																			
S 35	S 36																		
S 2 S 1																			
T17N																			
2001																			

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS																
	<p>From this same point, the cor. of secs. 27, 28, 33 and 34, bears N. 89° 32' W., 160.29 chs dist., monumented with a granite stone, 16x12x5 ins., firmly set 8 ins. in the ground, plainly mkd. 3 notches on E. edge and 1 groove on S. face.</p>															
	<p>At the corner point</p>															
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>															
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">T18N</td> <td style="padding: 0 10px;">R82W</td> <td></td> </tr> <tr> <td style="padding: 0 10px;">S 28</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 27</td> <td></td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black;"></td> </tr> <tr> <td style="padding: 0 10px;">S 33</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 34</td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 10px;">2001</td> </tr> </table>	T18N	R82W		S 28	S 27					S 33	S 34		2001		
T18N	R82W															
S 28	S 27															
S 33	S 34															
2001																
	<p>from which new bearing trees</p>															
	<p>A pine, 16 ins. diam., bears N. 40° E., 55 lks. dist., mkd. T18N R82W S27 BT.</p>															
	<p>A fir, 9 ins. diam., bears S. 50° E., 25 lks. dist., mkd. T18N R82W S34 BT.</p>															
	<p>A pine, 12 ins. diam., bears S. 70° W., 44 lks. dist., mkd. t18N R82W S33 BT.</p>															
	<p>A fir, 8 ins. diam., bears N. 20° W., 28 lks. dist., mkd. T18N R82W S28 BT.</p>															
	<p>No remains of the original bearing trees were found.</p>															
	<p>Bury the original cor. stone alongside the stainless steel post.</p>															
	<p>The control line was fully retraced and no evidence of the intervening cors. were found.</p>															
	<hr/> <p>N. 1° 13' W., bet. secs. 25 and 26.</p>															
	<p>Over mountainous terrain, through pine timber.</p>															
<p>39.40</p>	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p>															
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>															

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T18N R82W 1/4 S 26 S 25 2002</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 66° E., 8 lks. dist., mkd. 1/4 S25 BT.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 32° W., 20 lks. dist., mkd. 1/4 S26 BT.</p> <p>Set an aluminum sign post alongside the stainless steel post.</p> <p>78.80 Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18N R82W S 23 S 24 ----- S 26 S 25 2002</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 50° E., 15 lks. dist., mkd. T18N R82W S24 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 11° E., 3 lks. dist., mkd. T18N R82W S25 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 34° W., 10 lks. dist., mkd. T18N R82W S26 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 77° W., 31 lks. dist., mkd. T18N R82W S23 BT.</p> <p>Set an aluminum sign post alongside the stainless steel post.</p> <p>From this point, the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp. bears N. 89° 44' E., 80.92 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p>
--------	--

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	<div style="text-align: center; margin-bottom: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T18N</td></tr> <tr><td>R82W</td><td>R81W</td></tr> <tr><td style="border-right: 1px solid black;">S 24</td><td>S 19</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black;">S 25</td><td>S 30</td></tr> <tr><td colspan="2">1939</td></tr> </table> </div> <p>No remains of the 1939 bearing trees were found.</p> <p>The control line was fully retraced and no evidence of the intervening cor. was found.</p> <p>From this same point, the cor. of secs. 21, 22, 27 and 28, bears S. 89° 30' W., 161.69 chs dist., at cor. of fences extending N. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T18N R82W</td></tr> <tr><td style="border-right: 1px solid black;">S 21</td><td>S 22</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black;">S 28</td><td>S 27</td></tr> <tr><td colspan="2">2002</td></tr> </table> </div> <p>The control line was fully retraced and no evidence of the intervening cors. were found.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0° 03' W., bet. secs. 23 and 24.</p> <p>Over mountainous terrain, through pine timber.</p> <p>39.39 Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T18N R82W</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td style="border-right: 1px solid black;">S 23</td><td>S 24</td></tr> <tr><td colspan="2">2002</td></tr> </table> </div>	T18N		R82W	R81W	S 24	S 19			S 25	S 30	1939		T18N R82W		S 21	S 22			S 28	S 27	2002		T18N R82W		1/4		S 23	S 24	2002	
T18N																															
R82W	R81W																														
S 24	S 19																														
S 25	S 30																														
1939																															
T18N R82W																															
S 21	S 22																														
S 28	S 27																														
2002																															
T18N R82W																															
1/4																															
S 23	S 24																														
2002																															

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS																						
	<p>from which</p> <p>A pine, 12 ins. diam., bears S. 54° E., 30 lks. dist., mkd. 1/4 S24 BT.</p> <p>A pine, 10 ins. diam., bears N. 72° W., 26 lks. dist., mkd. 1/4 S23 BT.</p> <p>Set an aluminum sign post alongside the stainless steel post.</p>																					
77.80	Leave timber; thence over open sagebrush.																					
78.78	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T18N R82W</td></tr> <tr><td>S 14</td><td>S 13</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 23</td><td>S 24</td></tr> <tr><td colspan="2">2002</td></tr> </table> <p>Set an aluminum sign post alongside the stainless steel post.</p> <p>From this point, the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp. bears N. 89° 20' E., 80.02 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T18N</td></tr> <tr><td>R82W R81W</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td colspan="2">1939</td></tr> </table> <p>from which the 1939 bearing trees</p> <p>A pine, 14 ins. diam., bears N. 70° E., 31 lks. dist., mkd. T18N R81W S18 BT on open blaze.</p> <p>A aspen, 8 ins. diam., bears S. 65° E., 29 lks. dist., bark scribed T18N R81W S19 BT.</p> <p>A aspen 6 ins. diam., bears S. 24° W., 12 lks. dist., bark scribed T18N R81W S24 BT.</p>	T18N R82W		S 14	S 13	-----		S 23	S 24	2002		T18N		R82W R81W	S 13	S 18	-----		S 24	S 19	1939	
T18N R82W																						
S 14	S 13																					

S 23	S 24																					
2002																						
T18N																						
R82W R81W																						
S 13	S 18																					

S 24	S 19																					
1939																						

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS									
	<p>The control line was fully retraced and no evidence of the intervening cor. was found.</p> <p>From this same point, the cor. of secs. 15, 16, 21 and 22, bears S. 88° 36' W., 160.02 chs dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T18N R82W</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black;">S 16</td> <td style="border-bottom: 1px solid black;">S 15</td> </tr> <tr> <td style="border-right: 1px solid black;">S 21</td> <td>S 22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1960</td> </tr> </table> <p>from which the 1960 bearing trees</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears N. 47° E., 20 lks. dist., with visible scribing on partially healed blaze. (Record: N. 49½° E., 20.5 lks.)</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 27° E., 26 lks. dist., mkd. T18N R82W S22 BT on open blaze. (Record: S. 35½° E.)</p> <p style="padding-left: 40px;">A dead pine, 6 ins. diam., bears S. 67° W., 42 lks. dist., mkd. T18N R82W S21 BT on open blaze. (Record: S. 64½° W.)</p> <p style="padding-left: 40px;">A pine stump, 12 ins. diam., bears N. 4° W., 15 lks. dist., with dead trunk lying alongside mkd. T18N R82W S16 BT on open blaze. (Record: N. 5° W., 14.5 lks.)</p> <p>No remains of the original bearing trees were found.</p> <p>The control line was fully retraced and no evidence of the intervening cors. were found.</p> <hr/> <p>N. 1° 20' W., bet. secs. 13 and 14.</p> <p>Over mountainous terrain.</p> <p>30.30 Enter pine timber.</p> <p>38.00 Leave timber.</p> <p>39.40 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original cor.</p>	T18N R82W		S 16	S 15	S 21	S 22	1960	
T18N R82W									
S 16	S 15								
S 21	S 22								
1960									

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T18N R82W 1/4 S 14 S 13 2002</p>
	<p>Cor. is located on steep S. slope.</p>
	<p>Set an aluminum sign post alongside the stainless steel post.</p>
44.50	<p>Enter pine timber.</p>
78.80	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a granite stone, 16x10x7 ins., firmly set 5 ins. in the ground, plainly mkd. 1 notch on E. edge and 4 notches on S. edge.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T18N R82W S 11 S 12 ----- S 14 S 13 2001</p>
	<p>from which</p>
	<p>A pine, 12 ins. diam., bears N. 56° E., 8 lks. dist., mkd. T18N R82W S12 BT.</p>
	<p>A pine, 8 ins. diam., bears S. 46° E., 19 lks. dist., mkd. T18N R82W S13 BT.</p>
	<p>A pine, 10 ins. diam., bears S. 70° W., 17 lks. dist., mkd. T18N R82W S14 BT.</p>
	<p>A pine, 10 ins. diam., bears N. 15° W., 24 lks. dist., mkd. T18N R82W S11 BT.</p>
	<p>Deposit the original cor. stone in the collar of stone and set an aluminum sign post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	
	N. 2° 32' W., bet. secs. 11 and 12.
	Over mountainous terrain.
0.68	Fence extending E., and W. 2 chs. to cor. of fences extending NNE., E. and S.
19.495	Point for the S. 1/16 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T18N R82W S1/16 S 11 S 12 2002</p>
	from which
	<p style="padding-left: 40px;">An aspen, 10 ins. diam., bears S. 58° E., 28 lks. dist., bark scribed S 1/16 S12 BT.</p>
	<p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 36° W., 33 lks. dist., mkd. S 1/16 S11 BT.</p>
	Cor. is located S. 69° W., 94 lks. dist. from intersection of fences extending N., S. and W.
	Set a steel fence post alongside the stainless steel post.
	Thence along fence.
32.88	Cor. of fences extending E. and S.; thence through scattered timber and open sagebrush.
38.99	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T18N R82W 1/4 S 11 S 12 2002</p>
	from which
	<p style="padding-left: 40px;">An aspen, 12 ins. diam., bears N. 63° E., 15 lks. dist., bark scribed 1/4 S12 BT.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>A pine, 15 ins. diam., bears S. 62° W., 6 lks. dist., mkd. 1/4 S11 BT.</p> <p>Set a steel fence post alongside the iron post.</p>										
39.14	Drainage, (wet) 5 lks. wide, course NE.										
77.98	<p>The cor. of secs. 1, 2, 11 and 12, remonumented by Martin A. Pedersen, Wyoming Registered Land Surveyor No. 544, with a steel reinforcement rod, 24 ins. long, 5/8 ins. diam., firmly set, projecting 4 ins. above the ground, with a mound of stone, 3 ft. base to top, S. of the cor., with aluminum cap mkd. S1 S2 S11 S12 LS544. This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="1" style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="padding: 2px;">T18N R82W</td> </tr> <tr> <td style="padding: 2px;">S 2</td> <td style="padding: 2px;">S 1</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding: 2px;"></td> </tr> <tr> <td style="padding: 2px;">S 11</td> <td style="padding: 2px;">S 12</td> </tr> <tr> <td colspan="2" style="padding: 2px;">2001</td> </tr> </table> </div> <p>from which bearing objects established by Pedersen</p> <p>A limestone outcrop, 3x2x1 ft., bears S. 34° W., 59 lks dist., mkd. X BO on top.</p> <p>A limestone outcrop, 5x4x4 ft., bears N. 2° W., 30 lks. dist., mkd X BO on top.</p> <p>Deposit the steel reinforcement rod alongside the iron post and retain the mound of stone, 3 ft. base, 3 ft. high, S. of the cor.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of sec. 11, 12, 13 and 14.</p> <p>S. 89° 55' W., bet. secs. 11 and 14.</p> <p>Over mountainous terrain, through pine timber.</p>	T18N R82W		S 2	S 1			S 11	S 12	2001	
T18N R82W											
S 2	S 1										
S 11	S 12										
2001											
2.00	Intersection of fences, extending N., E., and S.										
38.01	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original cor.										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T18N R82W S 11 1/4 ——— S 14 2002</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 9° E., 5 lks. dist., mkd. 1/4 S14 BT.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 9° W., 11 lks. dist., mkd. 1/4 S11 BT.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>76.02 Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T18N R82W S 10 S 11 ——— ——— S 15 S 14 2002</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 71° E., 85 lks. dist., mkd. T18N R82W S11 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 27° E., 64 lks. dist., mkd. T18N R82W S14 BT.</p> <p>No other trees within limits.</p> <p>From this point, the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., bears S. 1° 00' E., 317.10 chs. dist., monumented with a dead standing fir, 9 ins. diam., hacked smooth on W. face with 4 notches and hacked smooth on E. face, no other mks. found.</p> <p>At the corner point</p>
--------	---

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, at base of fir tree, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T18N R82W</td> </tr> <tr> <td style="border-right: 1px solid black;">S 34</td> <td>S 35</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td style="border-right: 1px solid black;">S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T17N</td> </tr> <tr> <td colspan="2" style="text-align: center;">2001</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">An aspen stump, 12 ins. diam., bears S. 74° E., 15 lks. dist., with hack marks on an open blaze. (Record N. 86° E., 16 lks.)</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 22° E., 17 lks. dist., mkd. T18N R82W S35 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 68° E., 46 lks. dist., mkd. T17N R82W S2 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 28° W., 22 lks. dist., mkd. T17N R82W S3 BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 41° W., 31 lks. dist., mkd. T18N R82W S34 BT.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>The control line was fully retraced and no evidence of the intervening cors. were found.</p> <hr/> <p>N. 5° 27' W., bet. secs. 10 and 11.</p> <p>Over mountainous terrain, through scattered patches of pine timber.</p> <p>19.15 Fence, bears E. and W.</p> <p>19.30 Trail road, bears E. and W.</p> <p>19.91 Point for the S. 1/16 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>	T18N R82W		S 34	S 35			S 3	S 2	T17N		2001	
T18N R82W													
S 34	S 35												
S 3	S 2												
T17N													
2001													

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T18N R82W S1/16 S 10 S 11 2002</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 60° W., 30 lks. dist., mkd. S 1/16 S10 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 12° W., 17 lks. dist., mkd. S 1/16 S10 BT.</p> <p>Set a steel fence post alongside the iron post.</p> <p>39.82 The 1/4 sec. cor. of secs. 10 and 11, remonumented by person(s) unknown, with a steel reinforcement rod, 18 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, with a limestone, 18x15x6 ins., firmly set 9 ins. in the ground, plainly mkd. 1/4 on W. face alongside. This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18N R82W 1/4 S 10 S 11 2001</p> <p>from which</p> <p style="padding-left: 40px;">An aspen, 12 ins. diam., bears S. 86° E., 18 lks. dist., bark scribed 1/4 S11 BT.</p> <p style="padding-left: 40px;">An aspen, 10 ins. diam., bears S. 71° W., 12 lks. dist., bark scribed 1/4 S10 BT.</p> <p>Deposit the steel reinforcement rod and bury the original cor. stone alongside the iron post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 0° 04' W., beginning new measurement.</p> <p>Over mountainous terrain.</p> <p>28.30 Dirt road, bears NE. and SW.</p>
--------	--

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS											
39.32	<p>The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T18N R82W</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td colspan="2">1960</td></tr> </table>	T18N R82W		S 3	S 2	-----		S 10	S 11	1960	
T18N R82W											
S 3	S 2										

S 10	S 11										
1960											
	<p>Cor. is located in fence extending E. and W., 45 lks. E. of trail road extending SE. and NW.</p>										
	<hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p>										
	<p>N. 87° 55' W., bet. secs. 2 and 11.</p>										
	<p>Over mountainous terrain.</p>										
0.70	<p>Dirt road, bears NE. and SW.</p>										
36.06	<p>Cor. of fences, bears NE. and W.; thence along fence.</p>										
36.55	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented with a limestone, 17x10x3 ins., lying embedded 6 ins. in the ground, plainly mkd. 1/4 on a face.</p>										
	<p>At the corner point</p>										
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T18N R82W</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>-----</td></tr> <tr><td>S 11</td><td></td></tr> <tr><td colspan="2">2001</td></tr> </table>	T18N R82W		S 2		1/4	-----	S 11		2001	
T18N R82W											
S 2											
1/4	-----										
S 11											
2001											
	<p>Deposit the original cor. stone alongside the stainless steel post, in the mound of stone.</p>										
	<p>Cor. is located 3 lks. N. of fence extending E. and W.</p>										
	<hr/> <p>S. 89° 26' W., beginning new measurement.</p>										
	<p>Over rolling terrain, along fence.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.87	The cor. of secs. 2, 3, 10 and 11.
	<hr/> From the cor. of secs. 10, 11, 14 and 15. N. 89° 30' W., bet. secs. 10 and 15. Over mountainous terrain.
38.00	The 1/4 sec. cor. of secs. 10 and 15, monumented with a granite stone, 15x8x8 ins., firmly set 8 ins. in the ground, no mks. visible. This monument was utilized by Robert Jack Smith, Wyoming Registered Land Surveyor No. 398, during the survey of the Cherokee Trail Subdivision in 1972. This position is accepted as the best available evidence of the original cor. position.
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	<div style="text-align: center;"> T18N R82W S 10 1/4 ——— S 15 2001 </div>
	Bury the unmkd. stone and set a steel fence post alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> S. 86° 56' W., beginning new measurement. Over mountainous terrain.
41.43	The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> T18N R82W S 9 S 10 ——— ——— S 16 S 15 1960 </div>
	Cor. is located 2 lks. E. of fence extending N. and S.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 1° 03' E., bet. secs. 9 and 10.</p> <p>Over rolling terrain, along fence.</p>
19.55	<p>The S. 1/16 sec. cor. of secs. 9 and 10, established by Robert Jack Smith, Wyoming Registered Land Surveyor No. 398, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T18N R82W S1/16 S 9 S 10 1972</p> <p>This position is accepted as a careful and faithful determination of the cor. position.</p> <p>Cor. is located 15 lks. W. of fence extending N. and S.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>N. 1° 01' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
19.55	<p>The 1/4 sec. cor. of secs. 9 and 10, perpetuated by Robert Jack Smith, Wyoming Registered Land Surveyor No. 398, with a steel reinforcement rod, 18 ins. long, 5/8 ins. diam., firmly set, projecting 6 ins. above the ground, with an unmkd. granite stone, 12x10x8 ins., firmly set 8 ins. in the ground, alongside. This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, supported by a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T18N R82W 1/4 S 9 S 10 2001</p> <p>Deposit the steel reinforcement rod and the unmkd. stone alongside the stainless steel post, in the mound of stone.</p> <p>Cor. is located in fence extending N. and S.</p> <hr style="width: 30%; margin: 10px auto;"/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>38.94</p> <p>37.15</p>	<p>N. 0° 14' E., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p> <p>The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T18N</td><td>R82W</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>S 9</td><td>S 10</td></tr> <tr><td colspan="2">1960</td></tr> </table> </div> <p>Cor. is located at intersection of fences extending N., E., S. and W.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 82° 46' W., bet. secs. 3 and 10.</p> <p>Over mountainous terrain, along fence.</p> <p>The 1/4 sec. cor. of secs. 3 and 10, perpetuated by Robert Jack Smith, Wyoming Registered Land Surveyor No. 398, with a steel reinforcement rod, 18 ins. long, 1/2 in. diam., firmly set, projecting 6 ins. above the ground. This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, supported by a mound of stone, 1 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T18N</td><td>R82W</td></tr> <tr><td>S 3</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 10</td><td></td></tr> <tr><td colspan="2">2001</td></tr> </table> </div> <p>Deposit the steel reinforcement rod alongside the stainless steel post.</p> <p>Cor. is located at intersection fences extending E., S. and W.</p> <hr/>	T18N	R82W	S 4	S 3	S 9	S 10	1960		T18N	R82W	S 3		1/4	—	S 10		2001	
T18N	R82W																		
S 4	S 3																		
S 9	S 10																		
1960																			
T18N	R82W																		
S 3																			
1/4	—																		
S 10																			
2001																			

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 87° 09' W., beginning new measurement.</p> <p>Over mountainous terrain, along fence.</p> <p>37.85 The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p style="text-align: center;">Subdivision of Section 10, T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N. 2° 05' W., on the N. and S. center line of sec. 10</p> <p>Over mountainous terrain.</p> <p>17.75 Intersection of fences, extending N., E., and W.; thence along fence.</p> <p>17.85 Trail road, bears E. and W.</p> <p>19.09 Point for the center S. 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18N R82W C S1/16 S 10 C 2002</p> <p>Set an aluminum sign post alongside the stainless steel post.</p> <p>Cor. is located 25 lks. W. of fence extending N. and S.</p> <p>From this point, an iron post 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T18N R82W C-S 1/16 SEC 10 RJS 398 1972, bears N. 78° 07' E., 0.51 chs. dist. This position was established by Robert Jack Smith, Wyoming Registered Land Surveyor No. 398, during the survey of the Cherokee Trail Subdivision and is not accepted as a careful and faithful determination or the cor. position.</p> <p>38.18 Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line. Point not monumented due to the fact that there is no federal interest at this point and may be confused with property corners of the Cherokee Trail Subdivision.</p>
--------	--

Subdivision of Section 10,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T18N R82W C 1/4 SEC 10 RJS 398 1972, bears N. 74° 01' E., 0.44 chs. dist. This position was established by Robert Jack Smith, Wyoming Registered Land Surveyor No. 398, during the survey of the Cherokee Trail Subdivision and is not accepted as a careful and faithful determination of the cor. position.</p>
74.00	<p>The 1/4 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>S. 88° 10' W., on the E. and W. center line of sec. 10.</p> <p>Over mountainous terrain, through pine timber.</p>
35.62	<p>The point for the center 1/4 sec. cor. of sec. 10; thence through Cherokee Trail Subdivision.</p>
74.91	<p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 10 and 11.</p> <p>S. 89° 22' W., on the E. and W. center line of the SE¼ of sec. 10.</p> <p>Over rolling terrain, through pine and aspen timber.</p>
36.81	<p>The center S. 1/16 sec. cor. of sec. 10.</p> <hr/> <p>S. 87° 32' W., on the E. and W. center line of the SW¼ of sec. 10.</p> <p>Over rolling terrain; through scattered patches of timber and open sagebrush. Enter Cherokee Trail Subdivision.</p>
20.79	<p>From this point, the NE. cor. of cabin, 30x14 ft., bears SOUTH, 0.04 chs. dist. Long side bears S. 82° W.</p>
40.35	<p>The S. 1/16 sec. cor. of secs. 9 and 10.</p> <hr/>

Subdivision of Section 11,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 1° 25' W., on the N. and S. center line of sec. 11.</p> <p>Over mountainous terrain through scattered pine timber.</p>
19.30	Fence, bears E. and W.
19.45	Trail road, bears E. and W.
19.64	<p>Point for the center S. 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T18N R82W C S1/16 S 11 C 2002</p> <p>Set an aluminum sign post alongside the stainless steel post.</p>
39.28	<p>Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T18N R82W C1/4 S 11 2002</p> <p>Set a steel fence post alongside the stainless steel post.</p>
52.30	Dirt road, bears SE. and NW.
79.30	The 1/4 sec. cor of secs. 2 and 11.
	<hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12.</p> <p>N. 89° 35' W., on the E. and W. center line of sec. 11.</p> <p>Over mountainous terrain.</p>

Subdivision of Section 11,
T. 18 N., R. 82 W., Sixth Principal Meridian, Wyoming


CHAINS	
37.26	The center 1/4 sec. cor. of sec. 11.
78.08	The 1/4 sec. cor. of secs. 10 and 11.
	<hr/> <p>From the S. 1/16 sec. cor. of secs. 11 and 12.</p> <p>N. 89° 51' W, on the E. and W. center line of the SE¼ of sec. 11.</p> <p>Over mountainous terrain, through patches of pine and aspen timber along fence.</p>
17.00	Cross fence, bears ENE. and WSW.
37.63	The center S. 1/16 sec. cor. of sec. 11.
	<hr/> <p>N. 89° 50' W., on the E. and W. center line of sec. 11.</p> <p>Over mountainous terrain, through patches of pine and aspen timber.</p>
39.41	The S. 1/16 sec. cor. of secs. 10 and 11.
	<hr/> <p>GENERAL DESCRIPTION</p> <p>The area embraced by this survey is situated in the southeast portion of Carbon County, appoximately 12 miles southwest of the town of Elk Mountain, Wyoming. The terrain is mountainous with an average elevation of about 8,500 feet above sea level. The soil is mostly rocky and vegetation consists of stands of pine, fir, aspen and sagebrush. Drainage of the area is easterly into Rankin Creek and northerly into Pass Creek in sections 10 and 11. Access is provided by Carbon County Road No. 404, and by numerous dirt roads and trails in the area. There are two ranches on the eastern portion of the job and the Cherokee Trail Subdivision is situated in the west half of section 10. There was no evidence of mineral activity in the area however a logging operation was recently completed in the area of sections 25 and 36.</p>

CERTIFICATE OF SURVEY

I, Lynn A. Forbes, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day of May, 2001, I have dependently resurveyed a portion of the subdivisional lines, and subdivided sections 10 and 11, Township 18 North, Range 82 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

DEC 31 2002

 (Date)



 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

 BUREAU OF LAND MANAGEMENT
 Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 10 and 11, Township 18 North, Range 82 West, Sixth Principal Meridian, Wyoming, executed by Lynn A. Forbes, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

DEC 31 2002

 (Date)



 (Signature of Authorized Officer)