

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
DEPENDENT RESURVEY OF
A PORTION OF THE
SIXTH STANDARD PARALLEL NORTH, THROUGH RANGE 118 WEST,
AND THE
METES AND BOUNDS SURVEY OF LOT 9, SECTION 35,
TOWNSHIP 25 NORTH, RANGE 118 WEST,
OF THE SIXTH PRINCIPAL MERIDIAN,
IN THE STATE OF WYOMING.

EXECUTED BY

LYNN A. FORBES
DONNA S. MALLECK

CADASTRAL SURVEYOR
CADASTRAL SURVEYOR

Under Special Instructions dated AUGUST 2, 2001, approved AUGUST 2, 2001, which provided for the surveys included under Group Number 696, and assignment instructions dated AUGUST 2, 2001, and SEPTEMBER 10, 2001.

Survey commenced AUGUST 14, 2001

Survey completed SEPTEMBER 19, 2001

INDEX DIAGRAM

Township 25 North, Range 118 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36
			4	3	2

SIXTH STANDARD PARALLEL NORTH

T. 25 N., R. 118 W., Sixth Principal Meridian, Wyoming

CHAINS

The following field notes are those of the dependent resurvey of a portion of the Sixth Standard Parallel North, through Range 118 West, and the metes and bounds survey of Lot 9, section 35, Township 25 North, Range 118 West, Sixth Principal Meridian, Wyoming.

The history of earlier surveys pertaining to this resurvey is as follows:

James E. Woods surveyed the Sixth Standard Parallel North in 1888. John L. McCoy and James E. Woods surveyed the subdivisional lines in 1888. These surveys were subsequently canceled. Frank M. Johnson and Herman Jaeckel independently resurveyed the south boundary and subdivisional lines 1907.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 696, Wyoming, dated August 2, 2001.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data was thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

The survey was executed with a Global Position System (GPS) TRIMBLE Model 4700 receiver, a LEICA total station Model TC-800 and by chaining methods. The instruments were maintained in proper adjustment at all times. The direction of all lines referring to the true meridian and the geographic positions were determined by Global Positioning System methods.

The geographic position of the standard 1/4 cor. of sec. 36, based on NAD 83 (1993) and determined by Global Positioning System methods, is:

Latitude 42° 06' 04.85" N., Longitude 110° 48' 16.71" W.

The magnetic declination is 13¾° E.

Dependent Resurvey, Portion of the Sixth Standard Parallel North,
Through Range 118 West, Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">(Restoring the resurvey executed by Frank M. Johnson and Herman Jaeckel in 1907)</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the standard 1/4 sec. cor. of sec. 36, monumented with a sandstone, 10x10x10 ins., firmly set 6 ins. in the ground, plainly mkd. SC 1/4 on N. face, with a mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T25N R118W <u>1/4 S 36</u></p> <p style="text-align: center;">2001</p> <p>Bury the 1907 resurvey cor. stone alongside the iron post, and rebuild the mound of stone, 2 ft. base, 1 ft. high, N. of the cor.</p> <p>N. 89° 12' W., on the S. bdy. of sec. 36.</p> <p>Over mountainous terrain.</p> <p>22.19 The closing cor. of secs. 3 and 4, T. 24 N., R. 118 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 24 N. T. 118 W., executed concurrently under this same group.</p> <p>39.27 The standard cor. of secs. 35 and 36, monumented with a granite stone, 17x8x7 ins., firmly set 12 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, supported by a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S C T25N R118W <u>S 35 S 36</u></p> <p style="text-align: center;">2001</p>
--------	--

Dependent Resurvey, Portion of the Sixth Standard Parallel North,
Through Range 118 West, Sixth Principal Meridian, Wyoming

CHAINS	
	Bury the unmkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.
	S. 89° 15' W., on the S. bdy. of sec. 35.
	Over mountainous terrain.
3.07	Point for the E. 1/16 sec. cor. of sec. 4 only, T. 24 N., R. 118 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 24 N., R. 118 W., executed concurrently under this same group.
13.08	Point for the W-E 1/64 sec. cor. of sec. 4 only, T. 24 N., R. 118 W., identical with Cor. No. 12, Lot No. 9, T. 25 N., R. 118 W., hereinafter described.
23.09	The 1/4 sec. cor. of sec. 4 only, T. 24 N., R. 118 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 24 N., R. 118 W., executed concurrently under this same group.
40.16	The standard 1/4 sec. cor. of sec. 35, monumented with a broken limestone, 12x10x6 ins., firmly set 5 ins. in the ground, plainly mkd. S 1/4 on a face, no other mks. visible, with a mound of stone, 3 ft. base, 3 ft. high, N. of the cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	S C T25N R118W <u>1/4 S 35</u>
	2001
	Bury the 1907 resurvey cor. stone and set a steel fence post alongside the iron post, and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of the cor.
	S. 89° 53' W., beginning new measurement.
	Over mountainous terrain.


Dependent Resurvey, Portion of the Sixth Standard Parallel North,
Through Range 118 West, Sixth Principal Meridian, Wyoming

CHAINS	
22.98	The closing cor. of secs. 4 and 5, T. 24 N., R. 118 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 24 N. T. 118 W., executed concurrently under this same group.
27.96	Point for the E-E-E 1/256 sec. cor. of sec. 5 only, T. 24 N., R. 118 W., identical with Cor. No. 10, Lot 9, T. 25 N., R. 118 W., hereinafter described.
39.96	<p>The standard cor. of secs. 34 and 35, monumented with a limestone, 12x6x5 ins., firmly set 8 ins. in the ground, plainly mkd. SC on N. face, 2 grooves on E. face and 4 grooves on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T25N R118W <u>S 34 S 35</u></p> <p style="text-align: center;">2001</p> <p>Bury the 1907 resurvey cor. stone and set a steel fence post alongside the iron post.</p> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 38° E., 14 lks. dist., mkd. SC on partially healed blaze.</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 36° W., 22 lks. dist., mkd. T25N R118W S34 BT.</p> <hr/> <p>N. 89° 50' W., on the S. bdy. of sec. 34.</p> <p>Over mountainous terrain.</p>
2.935	The E. 1/16 sec. cor. of sec. 5 only, T. 24 N., R. 118 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 24 N., R. 118 W., executed concurrently under this same group.


Dependent Resurvey, Portion of the Sixth Standard Parallel North,
Through Range 118 West, Sixth Principal Meridian, Wyoming

CHAINS	
22.84	The 1/4 sec. cor. of sec. 5 only, T. 24 N., R. 118 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 24 N., R. 118 W., executed concurrently under this same group.
39.07	<p>The standard 1/4 sec. cor. of sec. 34, monumented with a sandstone, 13x12x4 ins., firmly set 6 ins. in the ground, plainly mkd. 1/4 on N. face, in a mound of stone, 3 ft. base, 2 ft. high.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S C T25N R118W <u>1/4 S 34</u></p> <p style="text-align: center;">2001</p> <p>Bury the 1907 resurvey cor. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 1.5 ft. high, S. of the cor.</p> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 9¼° W., 16 lks. dist., mkd. SC 1/4 BT on open blaze.</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 58° W., 15 lks. dist., mkd. X at breast height and BT at base.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>S. 89° 29' W., beginning new measurement.</p> <p>Over mountainous terrain.</p>
23.62	The closing cor. of secs. 5 and 6, T. 24 N., R. 118 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 24 N. T. 118 W., executed concurrently under this same group.
40.00	<p>Point for the standard cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Sixth Standard Parallel North,
Through Range 118 West, Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">S C T25N R118W <u>S 33 S 34</u></p> <p style="text-align: center;">2001</p> <p>Set a steel fence post alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>From this point, the standard cor. of secs. 32 and 33, bears S. 89° 29' W., 80.00 chs. dist., monumented with a sandstone, 11x10x8 ins., firmly set 8 ins. in the ground, plainly mkd. SC on N. face, 4 notches on E. edge, no other mks. visible, with a mound of stone, 4 ft. base, 1 ft. high, N. of the cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S C T25N R118W <u>S 32 S 33</u></p> <p style="text-align: center;">2001</p> <p>Bury the 1907 resurvey cor. stone and set a steel fence post alongside the iron post, and rebuild the mound of stone, 3 ft. base, 1 ft. high, E. of the cor.</p> <p>This control line was fully retraced and no evidence of the intervening cor. was found.</p> <hr/> <p style="text-align: center;">Metes and Bounds Survey of Lot 9, Section 35, T. 25 N., R. 118 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>Beginning at the point for Cor. No. 1, Lot 9, sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R118W  1 S 35 LOT 9</p> <p style="text-align: center;">2001</p>
--------	--


Metes and Bounds Survey of Lot 9, Section 35,
T. 25 N., R. 118 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which</p> <p>A fir, 20 ins. diam., bears S. 7° W., 70 lks. dist., mkd. X at breast height and BT at base.</p> <p>A fir, 10 ins. diam., bears S. 21° W., 77 lks. dist., mkd. LOT 9 C1 BT.</p> <p>N. 89° 38' W., on line 1-2, Lot 9.</p> <p>Over mountainous terrain, through pine timber.</p> <p>26.18 Point for Cor. No. 2, Lot 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R118W</p> <p>S 35</p> <hr style="width: 10%; margin: 0 auto;"/> <p>2</p> <p>LOT 9</p> <p>2001</p> </div> <p>Set steel fence post alongside iron post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 81° 10' W., on line 2-3, Lot 9.</p> <p>Over nearly level terrain, along N. edge of parking lot of ski area.</p>
1.25	<p>Point for Cor. No. 3, Lot 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R118W</p> <p>S 35</p>  <p>3</p> <p>LOT 9</p> <p>2001</p> </div> <p>Set steel fence post alongside iron post.</p> <hr style="width: 30%; margin: 10px auto;"/>

Metes and Bounds Survey of Lot 9, Section 35,
T. 25 N., R. 118 W., Sixth Principal Meridian, Wyoming

CHAINS	
3.15	<p>S. 36° 05' W., on line 3-4, Lot 9.</p> <p>Over nearly level terrain, along E. edge of parking lot of ski area.</p> <p>Point for Cor. No. 4, Lot 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R118W</p> <p>S 35 /</p> <p>4</p> <p>LOT 9</p> <p>2001</p> </div> <p>Set steel fence post alongside iron post.</p> <p>Cor. is located 20 lks. E. of Pine Creek, course SW.</p> <hr style="width: 20%; margin: 10px auto;"/>
2.39	<p>S. 12° 47' W., on line 4-5, Lot 9.</p> <p>Across parking area.</p> <p>Point for Cor. No. 5, Lot 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R118W</p> <p>S 35 /</p> <p>5</p> <p>LOT 9</p> <p>2001</p> </div> <p>Set steel fence post alongside iron post.</p> <p>Cor. is located on W. edge of parking lot, next to power pole.</p>



Metes and Bounds Survey of Lot 9, Section 35,
T. 25 N., R. 118 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which</p> <p>The NW. cor. of a house, bears N. $52\frac{1}{2}^{\circ}$ E., 135.5 ft. The face of the house bears S. 66° E., 20 ft., and is 25 ft. deep.</p> <p>The NW. cor. of a concrete block building bears N. $67\frac{3}{4}^{\circ}$ E., 149 ft. The face of the building bears S. $22\frac{1}{2}^{\circ}$ E., 25 ft., and is 15 ft. deep.</p> <p>The NW. cor. of the ski lodge bears S. $13\frac{3}{4}^{\circ}$ E., 172 ft. The N. face of the building, bears S. $78\frac{3}{4}^{\circ}$ E. 66 ft. The W. face bears S. $11\frac{1}{2}^{\circ}$ W., 81. ft.</p> <p>The base tower for the ski lift bears S. 86° E., 109 ft. and the lift extends S. 28° E.</p> <hr/>
	<p>S. $18^{\circ} 17'$ W., on line 5-6, Lot 9.</p>
	<p>Over nearly level terrain.</p>
2.64	<p>Point for Cor. No. 6, Lot 9.</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T25N R118W</p>  <p>2001</p> </div>
	<p>Set steel fence post alongside iron post.</p> <hr/>
	<p>S. $46^{\circ} 41'$ W., on line 6-7, Lot 9.</p>
	<p>Over mountainous terrain, enter pine timber.</p>
2.37	<p>Point for Cor. No. 7, Lot 9.</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>

Metes and Bounds Survey of Lot 9, Section 35,
T. 25 N., R. 118 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T25N R118W</p> <p style="text-align: center;">S 35 / 7 LOT 9</p> <p style="text-align: center;">2001</p> <p>Set steel fence post alongside iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 55° E., 39 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 2° E., 55 lks. dist., mkd. LOT 9 C7 BT.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>S. 49° 28' W., on line 7-8, Lot 9.</p> <p>Over mountainous terrain, through pine timber.</p> <p>2.15 Point for Cor. No. 8, Lot 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R118W</p> <p style="text-align: center;">S 35 / 8 LOT 9</p> <p style="text-align: center;">2001</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 66° E., 42 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 22° W., 63 lks. dist., mkd. LOT 9 C8 BT.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>S. 60° 59' W., on line 8-9, Lot 9.</p> <p>Over mountainous terrain, through pine timber.</p>
--------	---

Metes and Bounds Survey of Lot 9, Section 35,
T. 25 N., R. 118 W., Sixth Principal Meridian, Wyoming

CHAINS	
3.95	<p>Point for Cor. No. 9, Lot 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>T25N R118W S 35 9 LOT 9</p> </div> <p style="text-align: center;">2001</p> <p>Set steel fence post alongside iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 82° E., 13 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 50° E. 22 lks. dist., mkd. LOT 9 C9 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 5° 21' E., on line 9-10, Lot 9.</p> <p>Over mountainous terrain, through pine timber.</p>
4.67	<p>True point for Cor. No. 10, Lot 9, at intersection with the Sixth Standard Parallel North, identical with the E-E-E 1/256 sec. cor. of sec. 5 only, T. 24 N., R. 118 W., at proportionate distance on the N. bdy. of sec. 5, falls on face of steep granite outcrop 10x10x10 ft., where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for the witness cor. to Cor. No. 10, identical with the E-E-E 1/256 sec. cor. of sec. 5 only, bears S. 89° 53' W., 0.23 chs. dist.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>W C T25N R118W S 35 E-E-E 1/256 S 5 T24N R118W</p> </div> <p style="text-align: center;">2001</p>

Metes and Bounds Survey of Lot 9, Section 35,
T. 25 N., R. 118 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which</p> <p>A fir, 10 ins. diam., bears S. 72° E., 44 lks. dist., mkd. X BT at breast height.</p> <p>A fir, 6 ins. diam., bears S. 64° W., 33 lks. dist., mkd. X BT at breast height.</p> <p>Cor. is located on steep N. slope.</p> <hr/> <p>N. 89° 53' E., on line 10-11, Lot 9, identical in part with the S. bdy. of sec. 35 and the Sixth Standard Parallel North.</p> <p>Over mountainous terrain, through pine timber.</p>
4.98	The closing cor. of secs. 4 and 5, T. 24 N., R. 118 W., monumented with an iron post, 2½ ins. diam., as described in the field notes of the dependent resurvey, T. 24 N. T. 118 W., executed concurrently under this same group.
8.00	Trail road, bears N. and S.
10.25	Ski lift, bears S. 28° E. and N. 28° W.
27.96	Cor. No. 11, Lot 9, identical with the standard 1/4 sec. cor. of sec. 35 only.
	<hr/> <p>N. 89° 15' E., on line 11-12, Lot 9, identical in part with the S. bdy. of sec. 35 and the Sixth Standard Parallel North.</p> <p>Over mountainous terrain, through pine timber.</p>
27.08	Cor. No. 12, Lot 9, at intersection with the Sixth Standard Parallel North, identical with the W-E 1/64 sec. cor. of sec. 4 only, T. 24 N., R. 118 W, at proportionate distance on the N. bdy. of sec. 4, and on the Sixth Standard Parallel North.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R118W S 35 ----- W-E 1/64 S 4 T24N R118W</p> <p style="text-align: center;">2001</p>

Metes and Bounds Survey of Lot 9, Section 35,
T. 25 N., R. 118 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>from which</p> <p>A fir, 8 ins. diam., bears S. 89° W., 8 lks. dist., mkd. W E 1/64 S4 BT.</p> <hr/> <p>N. 57° 10' W., on line 12-13, Lot 9.</p> <p>Over mountainous terrain, through pine timber.</p>
3.65	<p>Point for Cor. No. 13, Lot 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R118W</p> <p style="text-align: center;">13</p> <p style="text-align: center;">LOT 9 S 35</p> <p style="text-align: center;">2001</p> <p>Set steel fence post alongside the iron post.</p>
3.86	<p>from which</p> <p>A fir, 30 ins. diam., bears WEST, 87 lks. dist., mkd. X at breast height and BT at base.</p> <p>A fir, 36 ins. diam., bears N. 50° W., 76 lks. dist., mkd. LOT 9 C 13 BT.</p> <hr/> <p>N. 45° 40' W., on line 13-1, Lot 9.</p> <p>Over mountainous terrain, through pine timber.</p> <p>From this point, Cor. No. 3, Tract 37, bears N. 44° 20' E., 4.38 chs. dist., monumented with a granite stone, 18x15x4 ins., lying embedded 4 ins. in the ground, plainly mkd. 3/37 on a face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>

Metes and Bounds Survey of Lot 9, Section 35,
T. 25 N., R. 118 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T25N R118W S 35 TR 37 3</p> <p style="text-align: center;">2001</p> <p>Bury the original cor. stone alongside the iron post.</p> <p>20.91 Cor. No. 1, Lot 9, the point of beginning; said lot contains 70.10 acres, more or less.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area embraced by this survey is situated in the southwestern portion of Lincoln County, approximately 10 miles east of Cokeville, Wyoming. The terrain is mostly mountainous with an average elevation of about 7,000 feet above sea level. The soil is sandy loam and rocky with the vegetation consisting of sagebrush and native grasses. Timber consists of stands of pine, fir and aspen. Drainage of the area is northerly into Pine Creek by numerous creeks and draws. Access is provided by Wyoming State Highway No. 232, Lincoln County Road No. 204 and by numerous trails in the area. The area is uninhabited except a ski lodge with outbuildings in the southwest portion of Lot 9. There was no evidence of mineral activity in the area, however a logging operation was in the area south of Lot 9.</p>
--------	---

CERTIFICATE OF SURVEY

We, Lynn A. Forbes and Donna S. Malleck, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 2nd day of August, 2001, we have dependently resurveyed a portion of the Sixth Standard Parallel North through Range 118 West, and executed the metes and bounds survey of Lot 9, Section 35, Township 25 North, Range 118 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUL 26 2002

(Date)

Lynn A. Forbes
(Cadastral Surveyor)

JUL 26 2002

(Date)

Donna S. Malleck
(Not Available for Signature)
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, through Range 118 West, and the metes and bounds survey of Lot 9, Section 35, Township 25 North, Range 118 West, Sixth Principal Meridian, Wyoming, executed by Lynn A. Forbes and Donna S. Malleck, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

JUL 29 2002

(Date)

John P. Lee
(Signature of Authorized Officer)