

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
DEPENDENT RESURVEY
OF A PORTION OF THE
EIGHTH STANDARD PARALLEL NORTH, THROUGH RANGE 53 WEST,
PORTIONS OF THE WEST AND NORTH BOUNDARIES,
AND A
PORTION OF THE SUBDIVISIONAL LINES,
AND THE
SUBDIVISION OF CERTAIN SECTIONS,
TOWNSHIP 33 NORTH, RANGE 53 WEST,
OF THE SIXTH PRINCIPAL MERIDIAN,
IN THE STATE OF NEBRASKA.

EXECUTED BY

LYNN A. FORBES

CADASTRAL SURVEYOR

CARL W. SUMPTER

CADASTRAL SURVEYOR(U.S.F.S.)

Under Special Instructions dated MARCH 15, 1996, approved MARCH 20, 1996, which provided for the surveys included under Group Number 139, and assignment instructions dated MARCH 15, 1996.

Survey commenced APRIL 1, 1996

Survey completed SEPTEMBER 27, 1997

INDEX DIAGRAM

Township 33 North, Range 53 West

6	5	4	3	2	1
7 6	8	28 9	10	11	12
6 18 38	17 37	26 16 26	15 21	14	13
19 35	36 20 34	24 21 24	19 22 18	15 23 14	24
4 30 32	33 29 30	23 28 22	17 27 16	13 26 12	10 25 8
31	30 32	21 33	34	11 35	36

3 3 2

EIGHTH STANDARD PARALLEL NORTH

Subdivision of Section 19.....	Page 38
Subdivision of Section 20.....	Page 40
Subdivision of Section 21.....	Page 42
Subdivision of Section 22.....	Page 45
Subdivision of Section 26.....	Page 46
Subdivision of Section 27.....	Page 49
Subdivision of Section 28.....	Page 51
Subdivision of Section 29.....	Page 53
Subdivision of Section 30.....	Page 56
Subdivision of Section 32.....	Page 60

T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS

The following field notes are those of the dependent resurvey of a portion of the Eighth Standard Parallel North, through Range 53 West, portions of the west and north boundaries, and a portion the subdivisional lines, and the subdivision of certain sections, Township 33 North, Range 53 West, Sixth Principal Meridian, Nebraska.

Robert Harvey surveyed the Eighth Standard Parallel North (south boundary) in 1880. Frank S. Wood surveyed the remaining exterior boundaries and the subdivisional lines in 1882. James W. Hardison and Russell C. MacDonald dependently resurveyed the Eighth Standard Parallel North (south boundary), in addition to F. Wayne Forest and Elmer C. Lenhart surveying the remaining exterior boundaries in 1936.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 139, Nebraska, dated March 15, 1996.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners.

The survey was executed with a Trimble Model 4000 GPS receiver, a WILD Model T-1000 theodolite and a WILD Model DI-2000 electronic distance measuring instrument and by chaining methods. The instruments were maintained in proper adjustment at all times. The direction of all lines refer to the true meridian, determined by GPS observations and carried forward by GPS measurements. GPS control network and supporting data is contained in the official group file. The retracement data was thoroughly verified, and only true line notes are given herein, which refer to the completed field survey.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position of the cor. of secs. 25, 30, 31 and 36, on the E. bdy of the Tp., was determined by Global Positioning System (GPS), based on NAD 83(1995) is:

T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	<p>Latitude 42° 47' 57.50" N., Longitude 103° 30' 11.60" W.</p> <p>The magnetic declination is 10½° E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Eighth Standard Parallel North, through Range 53 West, Sixth Principal Meridian, Nebraska</p> <hr/> <p style="text-align: center;">(Restoring the dependent resurvey executed by James W. Hardison and Russell C. MacDonald in 1936)</p> <hr/> <p>Beginning at the standard 1/4 sec. cor. of sec. 34, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S C 1/4 S 34 <hr/>1936</p> <p>S. 89° 51' W., on the S. bdy. of sec. 34.</p> <p>Over rolling terrain.</p> <p>40.40 Milford Road, bears N. and S.</p> <p>41.48 Point for the standard cor. of secs. 33 and 34, at proportionate distance, by method of irregular boundary adjustment; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">S C T33N R53W S 33 S 34 <hr/>1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located 4 lks. S. of fence extending E. and W.</p> <hr/>
--------	---

Dependent Resurvey of a Porion of the
Eighth Standard Parallel North, Through
Range 53 West, Sixth Principal Meridian, Nebraska

CHAINS	
39.67	<p>S. 89° 59' W., on the S. bdy. of sec. 33.</p> <p>Over rolling terrain, along fence.</p> <p>The standard 1/4 sec. cor. of sec. 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S C 1/4 S 33 ----- 1936</p> <p>Cor. is located at cor. of fences, extending N. and W.</p> <hr/> <p>From the standard cor. of secs. 32 and 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 20 ins. above the ground, supported by a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S C T33N R53W S 32 S 33 ----- 1936</p>
39.27	<p>N. 89° 45' W., on the S. bdy. of sec. 32.</p> <p>Over rolling terrain, through pine timber.</p> <p>The standard 1/4 sec. cor. of sec. 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T33N R53W 1/4 S 32 ----- 1936</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A dead pine snag, 20 ins. diam., bears S. 46° E., 45 lks. dist., mkd. 1/4 W on partially healed blaze, no other mks. visible. (1936 Record: S. 50½° E.)</p>

Dependent Resurvey of a Porion of the
Eighth Standard Parallel North, Through
Range 53 West, Sixth Principal Meridian, Nebraska

CHAINS	<p>A pine. 24 ins. diam., bears N. 56° W., 38 lks. dist.. mkd. 1/4 SWT, on open blaze. (1936 Record: N. 56° W., 35 lks.)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 50' W., beginning new measurement.</p> <p>Over rolling terrain, through pine timber.</p> <p>41.14 The standard cor. of secs. 31 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in an embedded mound of stone, 3 ft. base, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>S</td><td>C</td></tr> <tr><td>T33N</td><td>R53W</td></tr> <tr><td>S 31</td><td> S 32</td></tr> <tr><td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td colspan="2">1936</td></tr> </table> </div> <p>from which the original bearing tree</p> <p>A pine. 24 ins. diam., bears N. 71° E., 25 lks. dist., mkd. T33N S32 on partially healed blaze, no other mks. visible. (1936 Record: N. 78° 20' E., 24 lks.)</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Dependent Resurvey, Portion of the West Boundary, T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">(Restoring the dependent resurvey executed by F. Wayne Forest and Elmer C. Lenhart in 1936)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with evidence of the NW. pit, the outline of which is clearly visible, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T33N</td><td></td></tr> <tr><td>R54W</td><td>R53W</td></tr> <tr><td>S 25</td><td> S 30</td></tr> <tr><td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td>S 36</td><td> S 31</td></tr> <tr><td colspan="2">1936</td></tr> </table> </div>	S	C	T33N	R53W	S 31	S 32	<hr style="width: 50%; margin: 0 auto;"/>		1936		T33N		R54W	R53W	S 25	S 30	<hr style="width: 50%; margin: 0 auto;"/>		S 36	S 31	1936	
S	C																						
T33N	R53W																						
S 31	S 32																						
<hr style="width: 50%; margin: 0 auto;"/>																							
1936																							
T33N																							
R54W	R53W																						
S 25	S 30																						
<hr style="width: 50%; margin: 0 auto;"/>																							
S 36	S 31																						
1936																							

Dependent Resurvey, Portion of the West Boundary,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>Cor. is located 2.5 lks. W. of intersection of fences, extending E., S. and W.</p> <p>N. 0° 17' W., bet. secs. 25 and 30.</p> <p>Over rolling terrain.</p>
38.86	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 25 S 30 1936</p> <p>from which the 1936 bearing trees</p> <p style="padding-left: 40px;">A dead pine snag, 16 ins. diam., bears N. 42½° E., 36 lks. dist., mkd. 1/4 S 30 BT on open blaze.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 62½° W., 72 lks. dist., with healed blaze.</p>
	<p>N. 0° 02' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
19.455	<p>Point for the N. 1/16 sec. cor. of secs. 25 and 30. Point not monumented.</p>
38.91	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above the ground, with visible pits N., E. and W. of the cor., with brass cap mkd.</p> <p style="text-align: center;">T33N R64W R53W S 24 S 19 ----- S 25 S 30 1936</p> <p>from which the remains of the 1936 bearing trees</p> <p style="padding-left: 40px;">A dead pine snag, 16 ins. diam., bears S. 41½° E., 125 lks. dist., mkd. T33N R53W S30 BT on open blaze. (Record dist. 127 lks.)</p>

Dependent Resurvey, Portion of the West Boundary,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS													
	<p>A pine stump, 16 ins. diam., bears S. 25° W., 74 lks. dist., no mks. visible.</p>												
	<p>From the cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T33N</td></tr> <tr><td>R54W</td><td>R53W</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td colspan="2">1936</td></tr> </table>	T33N		R54W	R53W	S 13	S 18	-----		S 24	S 19	1936	
T33N													
R54W	R53W												
S 13	S 18												

S 24	S 19												
1936													
	<p>N. 0° 10' W., bet. secs. 13 and 18.</p>												
	<p>Over rolling terrain.</p>												
39.735	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the 1936 resurvey monument. Point not monumented.</p>												
79.47	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the 1936 resurvey monument.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T33N</td></tr> <tr><td>R54W</td><td>R53W</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2">1997</td></tr> </table>	T33N		R54W	R53W	S 12	S 7	-----		S 13	S 18	1997	
T33N													
R54W	R53W												
S 12	S 7												

S 13	S 18												
1997													
	<p>Set a fiberglass "carsonite" post alongside the aluminum post.</p>												
	<p>Cor. is located in wash, drains NW.</p>												
	<p>N. 0° 10' W., bet. secs. 7 and 12.</p>												
	<p>Over rolling terrain.</p>												

Dependent Resurvey, Portion of the West Boundary,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
39.73	<p>The 1/4 cor. of secs. 7 and 12, monumented with an iron post. 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 12 S 7 1936</p>
<p>Dependent Resurvey, Portion of the North Boundary, T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska</p>	
<p>(Restoring the dependent resurvey executed by F. Wayne Forest and Elmer C. Lenhart in 1936)</p>	
	<p>From the 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 32 1/4 ——— S 5 1936</p> <p>S. 88° 45' W., bet. secs. 5 and 32.</p> <p>Over rolling terrain.</p>
39.68	<p>True point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance, by method of irregular boundary adjustment, falls in badlands where it is impracticable to establish a permanent monument; there is no remaining evidence of the 1936 resurvey monument.</p>
	<p>S. 89° 11' W., bet. secs. 6 and 31.</p> <p>Over rolling terrain.</p>
1.00	<p>Point selected for the witness cor. to the cor. of secs. 5, 6, 31 and 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, 8 ins. high, atop a white DEEP-1 magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the North Boundary,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS

W C	
T34N R53W	
S 31 S 32	
—————>	
S 6 S 5	
T33N	
1997	

Witness cor. is located in fence, extending E. and W., on grassy hummock in badlands area.

- 40.00 Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the 1936 resurvey monument. Point not monumented.
- 79.17 The cor. of Tps. 33 and 34 N., Rs. 53 and 54 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T34N	
R54W R53W	
S 36 S 31	
—————	
S 1 S 6	
T33N	
1936	

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

(Restoring the survey executed by
Frank S. Wood in 1882)

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.

T33N	
R53W R52W	
S 25 S 30	
—————	
S 36 S 31	
1936	

N. 89° 33' W., bet. secs. 25 and 36.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	Over rolling terrain.
40.345	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T33N R53W S 25 1/4 ——— S 36 1997</p>
	<p>Set an aluminum sign post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p>
	<p>Cor. is located 5 lks. E. of ravine, drains NE.</p>
80.69	<p>The cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T33N R53W S 26 S 25 ————— S 35 S 36 1997</p>
	<p>Set an aluminum sign post alongside the aluminum post.</p>
	<p>From this point. the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., bears S. 1° 13' E., 79.99 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground. with brass cap mkd.</p>
	<p style="text-align: center;">S C T33N R53W S 35 S 36 ————— 1936</p>
	<p>The control line was fully retraced and no evidence of the intervening cor. was found.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	N. 0° 11' W., bet. secs. 25 and 26.
	Over rolling terrain.
39.985	Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.
	<p style="text-align: center;">T33N R53W 1/4 S 26 S 25 1997</p>
	Set a steel fence post alongside the aluminum post.
	Cor. is located 25 lks. S. of Sand Creek Road (gravel) extending E. and SW.
79.97	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, atop a white DEEP-1 magnetic marker, in a mound of stone, 1½ ft. base to top, with magnetic aluminum cap mkd.
	<p style="text-align: center;">T33N R53W S 23 S 24 ----- S 26 S 25 1997</p>
	Set a fiberglass "carsonite" post alongside the aluminum post.
	From this point, the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., bears S. 89° 13' E., 79.96 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.
	<p style="text-align: center;">T33N R53W R52W S 24 S 19 ----- S 25 S 30 1936</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	<p>The control line was fully retraced and no evidence of the intervening cor. was found.</p> <p>From this point, the cor. of secs. 11, 12, 13 and 14, bears N. 0° 20' W., 159.95 chs. dist., monumented with a sandstone, 12x6x5 ins., firmly set 8 ins. in the ground, plainly mkd. 1 groove on E. face, and 4 grooves on S. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T33N R53W</td></tr> <tr><td>S 11</td><td>S 12</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 14</td><td>S 13</td></tr> <tr><td colspan="2">1997</td></tr> </table> <p>Bury the original cor. stone and set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>The control line was fully retraced and no evidence of the intervening cors. were found.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35, at intersection of fences, extending NE., S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T33N R53W</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 34</td><td>S 35</td></tr> <tr><td colspan="2">1997</td></tr> </table> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>N. 1° 13' W., bet. secs. 34 and 35.</p> <p>Over rolling terrain.</p> <p>36.00 Milford Road, bears NE. and SW.</p>	T33N R53W		S 11	S 12	<hr/>		S 14	S 13	1997		T33N R53W		1/4		S 34	S 35	1997	
T33N R53W																			
S 11	S 12																		
<hr/>																			
S 14	S 13																		
1997																			
T33N R53W																			
1/4																			
S 34	S 35																		
1997																			

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

<p>CHAINS</p> <p>39.99</p> <p>10.072</p> <p>20.145</p> <p>40.29</p>	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance: there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground. atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T33N R53W</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> <tr> <td colspan="2">1997</td> </tr> </table> </div> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located 85 lks. S. of Sand Creek, course E.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89° 35' W., bet. secs. 26 and 35.</p> <p>Over rolling terrain.</p> <p>Point for the E-E 1/64 sec. cor. of secs. 26 and 35.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground. atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T33N R53W</td> </tr> <tr> <td colspan="2">S 26</td> </tr> <tr> <td>E-E 1/64</td> <td><hr style="width: 50%; margin: 0 auto;"/></td> </tr> <tr> <td colspan="2">S 35</td> </tr> <tr> <td colspan="2">1997</td> </tr> </table> </div> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located N. 77½° E., 78 lks. dist., from intersection of fences. extending N., E. and SW.</p> <p>Point for the E. 1/16 sec. cor. of secs. 26 and 35. Point not monumented.</p> <p>The 1/4 sec. cor. of secs. 26 and 35, monumented with a sandstone. 12x8x2 ins., firmly set, 7 ins. in the ground, dimly mkd. 1/4 on N. face.</p> <p>At the corner point</p>	T33N R53W		S 27	S 26	<hr style="width: 50%; margin: 0 auto;"/>		S 34	S 35	1997		T33N R53W		S 26		E-E 1/64	<hr style="width: 50%; margin: 0 auto;"/>	S 35		1997	
T33N R53W																					
S 27	S 26																				
<hr style="width: 50%; margin: 0 auto;"/>																					
S 34	S 35																				
1997																					
T33N R53W																					
S 26																					
E-E 1/64	<hr style="width: 50%; margin: 0 auto;"/>																				
S 35																					
1997																					

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.
	<p style="text-align: center;">T33N R53W S 26 1/4 ——— S 35 1997</p>
	Bury the original cor. stone and set an aluminum sign post alongside the aluminum post.
	Cor. is located N. 26½° E., 11 lks. dist., from cor. of fences, extending N. and W.
	<p style="text-align: center;">—————</p>
	N. 89° 23' W., beginning new measurement.
	Over rolling terrain.
37.00	Milford Road, bears NE. and SW.
40.07	The cor. of secs. 26, 27, 34 and 35.
	<p style="text-align: center;">—————</p>
	N. 0° 01' E., bet. secs. 26 and 27.
	Over rolling terrain.
7.50	Sand Creek Road, bears SE. and NW.
19.97	Point for the S. 1/16 sec. cor. of secs. 26 and 27.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base to top, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.
	<p style="text-align: center;">T33N R53W S1/16 S 27 S 26 1997</p>
	Set an aluminum sign post alongside the aluminum post.
39.94	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey. Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base to top, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W 1/4 S 27 S 26 1997</p> <p>Cor. is located 4.5 chs. N. of dry creek bed, drains E.</p>
79.88	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 22 S 23 ----- S 27 S 26 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p>
40.025	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89° 58' W., bet. secs. 23 and 26.</p> <p>Over rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 23 1/4 ——— S 26 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
80.05	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 1° 14' W., bet. secs. 22 and 23.</p> <p>Over rolling terrain.</p>
39.94	<p>The 1/4 sec. cor. of secs. 22 and 23, remonumented by Rollin Curd, Nebraska Registered Land Surveyor No. 109, with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, as filed in the Sioux County Clerk's Office, with aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W 1/4 S 22 S 23 1967 LS 109</p> <p>Set an aluminum sign post alongside the aluminum post.</p> <hr/> <p>N. 0° 50' E., beginning new measurement.</p> <p>Over rolling terrain.</p>
39.89	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 15 S 14 <hr/>S 22 S 23 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located 91 lks. N. of fence extending E. and W., and 76 lks. E. of powerline, extending N. and S.</p> <p>From this point, the cor. of secs. 2, 3, 10 and 11, bears N. 0° 19' E., 159.56 chs. dist., reestablished by Rollin Curd, Nebraska Registered Land Surveyor No. 109, with an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. below the surface of the ground, as filed in the Sioux County Clerk's Office, with magnetic aluminum cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p style="text-align: center;">T33N R53W S 3 S 2 <hr style="width: 50%; margin: auto;"/>S 10 S 11 1980 LS 109</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located in a cultivated field.</p> <p>The control line was fully retraced and no evidence of the intervening cors. was found.</p> <p>From this same point. the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., bears S. 89° 39' E., 160.07 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R53W R52W S 13 S 18 <hr style="width: 50%; margin: auto;"/>S 24 S 19 1936</p> <p>The control line was fully retraced and no evidence of the intervening cors. was found.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89° 31' W., bet. secs. 27 and 34.</p> <p>Over rolling terrain.</p> <p>19.887 Point for the E. 1/16 sec. cor. of secs. 27 and 34. Point not monumented.</p> <p>39.775 Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines.
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
79.55	<p style="text-align: center;">T33N R53W S 27 1/4 ——— S 34 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located S. 26° W., 113 lks. dist., from cor. of fences, extending N. and W.</p> <p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T33N R53W S 28 S 27 ————— S 33 S 34 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located 20 lks. S. of fence extending E. and W.</p> <p>From this point, the standard cor. of secs. 33 and 34, bears S. 0° 47' W., 79.76 chs. dist.</p> <p>The control line was fully retraced and no evidence of the intervening cor. was found.</p> <hr/> <p>N. 0° 02' E., bet. secs. 27 and 28.</p> <p>Over rolling terrain.</p>
39.875	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p style="text-align: center;">T33N R53W 1/4 S 28 S 27 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located 53 lks. N. of Sand Creek Road (gravel) extending SE. and NW.</p> <p>79.75 Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 21 S 22 ----- S 28 S 27 1997</p> <p>Set a wooden fence post alongside the aluminum post.</p>
	<hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89° 26' W., bet. secs. 22 and 27.</p> <p>Over rolling terrain.</p> <p>39.755 True point for the 1/4 sec. cor. of secs. 22 and 27, falls in badlands where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.</p> <p>From this point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 22 and 27, bears N. 78° 15' W., 1.94 chs. dist.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">W C T33N R53W S 22 1/4 —————> S 27 1997</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian. Nebraska

CHAINS	
59.632	<p>True point for the W. 1/16 sec. cor. of secs. 22 and 27, falls in badlands where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for the witness cor. to the W. 1/16 sec. cor. of secs. 22 and 27, bears SOUTH, 1.28 chs. dist.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>W C 33N R53W S 22 W1/16— S 27 1997</p> </div> <p>Set a steel fence post alongside the aluminum post.</p>
79.51	<p>The cor. of secs. 21, 22, 26 and 27.</p> <hr/> <p>N. 0° 09' W., bet. secs. 21 and 22.</p> <p>Over rolling terrain.</p>
19.937	<p>Point for the S. 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T33N R53W S1/16 S 21 S 22 1997</p> </div> <p>Set an aluminum post alongside the aluminum post.</p>
39.875	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian. Nebraska

CHAINS	
	<p style="text-align: center;">T33N R53W 1/4 S 21 S 22 1997</p>
	<p>Set an aluminum post alongside the aluminum post.</p> <p>Cor. is located S. $72\frac{1}{2}^{\circ}$ E., 82 lks. dist., from cor. of fences, extending S. and W.</p>
59.812	<p>Point for the N. 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground. atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T33N R53W N1/16 S 21 S 22 1997</p>
79.75	<p>Set an aluminum sign post alongside the aluminum post.</p> <p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground. atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T33N R53W S 16 S 15 <hr/>S 21 S 22 1997</p>
	<p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located N. $78\frac{1}{2}^{\circ}$ E., 92 lks. dist., from intersection of fences, extending N., E., S. and W.</p> <p>From this point the cor. of secs. 9, 10, 15 and 16, bears N. $0^{\circ} 32'$ W., 79.76 chs., at intersection of fences, extending S., E. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS											
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T33N R53W</td> </tr> <tr> <td style="text-align: center;">S 9</td> <td style="text-align: center;">S 10</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 16</td> <td style="text-align: center;">S 15</td> </tr> <tr> <td colspan="2" style="text-align: center;">1997</td> </tr> </table>	T33N R53W		S 9	S 10	-----		S 16	S 15	1997	
T33N R53W											
S 9	S 10										

S 16	S 15										
1997											
	<p>The control line was fully retraced and no evidence of the intervening cor. was found.</p>										
	<hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p>										
	<p>S. 89° 23' W., bet. secs. 15 and 22.</p>										
	<p>Over rolling terrain.</p>										
39.71	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original cor.</p>										
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T33N R53W</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 15</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1997</td> </tr> </table>	T33N R53W		S 15		1/4	-----	S 22		1997	
T33N R53W											
S 15											
1/4	-----										
S 22											
1997											
	<p>Set a fiberglass "carsonite" post alongside the aluminum post.</p>										
	<p>Cor. is 53 lks. N. of fence extending E. and W.</p>										
79.42	<p>The cor. of secs. 15, 16, 21 and 22.</p>										
	<hr/> <p>From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp.</p>										
	<p>N. 0° 19' W., bet. secs. 32 and 33.</p>										
	<p>Over rolling terrain.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
39.81	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with a sandstone, 12x6x4 ins., firmly set, 10 ins. in the ground, plainly mkd. 1/4 on E. face.</p> <p>At the corner point</p> <p>Set an aluminum post. 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W 1/4 S 32 S 33 1997</p> <p>Bury the original cor. stone and set a steel fence post alongside the aluminum post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 02' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
36.00	Milo Road, bears E. and W.
39.79	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 29 S 28 <hr style="width: 10%; margin: auto;"/> S 32 S 33 1997</p> <hr style="width: 80%; margin: auto;"/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89° 53' W., bet. secs. 28 and 33.</p> <p>Over rolling terrain.</p>
39.90	Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey, Portion of the Subdivisional Lines.
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>Set an aluminum post. 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker. with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 28 1/4 ——— S 33 1997</p>
79.80	<p>Set an aluminum sign post alongside the aluminum post.</p> <p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0° 05' W., bet. secs. 28 and 29.</p> <p>Over rolling terrain.</p>
19.895	<p>Point for the S. 1/16 sec. cor. of secs. 28 and 29.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S1/16 S 29 S 28 1997</p>
34.00	<p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located 7 lks. S. of fence extending E. and W.</p> <p>Sand Creek, course SE.</p>
37.39	<p>Point selected for the witness cor. of the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">W C T33N R53W 1/4 ↑ S 29 S 28 1997</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	<p>Set an aluminum sign post alongside the aluminum post.</p>
39.79	<p>True point for the 1/4 sec. cor. of secs. 28 and 29, falls in ravine where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.</p>
79.58	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T33N R53W S 20 S 21 ----- S 29 S 28 1997</p> </div> <p>Set an aluminum sign post alongside the aluminum post.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89° 45' W., bet. secs. 21 and 28.</p> <p>Over rolling terrain.</p>
39.975	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T33N R53W S 21 1/4 ——— S 28 1997</p> </div>
43.50	<p>Sand Creek Road, bears SSE. and NNW.</p>
79.95	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 0° 21' W., bet. secs. 20 and 21.</p> <p>Over rolling terrain.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
15.50	Sand Creek Road, bears E. and W.
19.895	<p>Point for the S. 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S1/16 S 20 S 21 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located N. 58° E., 47 lks. dist., from cor. of fences, extending N. and W.</p>
39.79	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W 1/4 S 20 S 21 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located 67 lks. E. of fence extending N. and S.</p>
59.685	<p>Point for the N. 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W N1/16 S 20 S 21 1997</p> <p>Set a steel fence post alongside the aluminum post.</p> <p>Cor. is located 3 lks. N. of fence extending SE. and NW.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
79.58	<p>True point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance, falls in ravine where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89° 38' W., bet. secs. 16 and 21.</p> <p>Over rolling terrain.</p>
20.052	<p>Point for the E. 1/16 sec. cor. of secs. 16 and 21. Point not monumented.</p>
40.105	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 16 1/4 ——— S 21 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located in abandoned fence, extending E. and W.</p>
60.16	<p>Point for the W. 1/16 sec. cor. of secs. 16 and 21, falls in badlands where it is impracticable to establish a permanent monument. Point not monumented.</p>
80.21	<p>The true point for the cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0° 29' W., bet. secs. 16 and 17.</p> <p>Over rolling terrain.</p>
0.50	<p>Point selected for the witness cor. to the cor. of secs. 16, 17, 20 and 21.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
39.79	<div style="text-align: center;"> <p>W C T33N R53W S 17 S 16 ----- S 20 S 21 ↓ 1997</p> </div> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
76.93	<div style="text-align: center;"> <p>T33N R53W 1/4 S 17 S 16 1997</p> </div> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Point selected for the witness cor. to the cor. of secs. 8, 9, 16 and 17.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
79.58	<div style="text-align: center;"> <p>W C T33N R53W ↑ S 8 S 9 ----- S 17 S 16 1997</p> </div> <p>Set an aluminum post alongside the aluminum post.</p> <p>True point for the cor. of secs. 8, 9, 16 and 17, falls in badlands where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.</p> <p>From this point, the cor. of secs. 9, 10, 15 and 16, bears N. 89° 30' E., 80.11 chs. dist.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian. Nebraska

CHAINS													
	<p>From this same point, the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., bears S. 88° 57' W., 160.07 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T33N</td><td></td></tr> <tr><td>R54W R53W</td><td></td></tr> <tr><td>S 12 S 7</td><td></td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 13 S 18</td><td></td></tr> <tr><td>1936</td><td></td></tr> </table> </div> <p>The control line was fully retraced and no evidence of the intervening cor. was found.</p>	T33N		R54W R53W		S 12 S 7		<hr/>		S 13 S 18		1936	
T33N													
R54W R53W													
S 12 S 7													
<hr/>													
S 13 S 18													
1936													
	<hr/> <p>N. 0° 35' W., bet. secs. 8 and 9.</p> <p>Over rolling terrain.</p>												
<p>39.79</p>	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T33N R53W</td><td></td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 8 S 9</td><td></td></tr> <tr><td>1997</td><td></td></tr> </table> </div> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p>	T33N R53W		1/4		S 8 S 9		1997					
T33N R53W													
1/4													
S 8 S 9													
1997													
<p>79.58</p>	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T33N R53W</td><td></td></tr> <tr><td>S 5 S 4</td><td></td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 8 S 9</td><td></td></tr> <tr><td>1997</td><td></td></tr> </table> </div> <p>Set a steel fence post alongside the aluminum post.</p>	T33N R53W		S 5 S 4		<hr/>		S 8 S 9		1997			
T33N R53W													
S 5 S 4													
<hr/>													
S 8 S 9													
1997													

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS

Cor. is located 21 lks. E. of fence extending N. and S., and 212 lks. S. of Toadstool Park access road.

From this point, the 1/4 sec. cor. of secs. 4 and 9, bears N. 87° 54' E., 39.90 chs. dist., remonumented by Rollin Curd, Nebraska Registered Land Surveyor No. 109, with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, as filed in the Sioux County Clerk's Office, with aluminum cap mkd.

T33N R53W
S 4
1/4 ———
S 9
1967
LS 109

This position is accepted as a careful and faithful perpetuation of the original cor. position.

From this same point, the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., bears S. 88° 56' W., 159.46 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T33N
R54W R53W
S 1 | S 6
—————
S 12 | S 7
1936

The control line was fully retraced and no evidence of the intervening cors. was found.

From this same point, the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., bears N. 0° 32' W., 78.94 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

T34N R53W
S 32 | S 33
—————
S 5 | S 4
T33N
1936

The control line was full retraced and no evidence of the intervening cor. was found.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
39.52	<p>From the standard cor. of secs. 31 and 32. on the S. bdy. of the Tp.</p> <p>N. 0° 03' E., bet. secs. 31 and 32.</p> <p>Over rolling terrain, through pine timber.</p> <p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W 1/4 S 31 S 32 1997</p> <p>Set a steel fence post alongside the aluminum post.</p>
79.04	<p>The cor. of secs. 29, 30, 31 and 32, monumented with a sandstone, 14x8x4 ins., firmly set, 14 ins. in the ground, plainly mkd. 5 grooves on E. face and 1 groove on S. face, in an embedded mound of stone, 1½ ft. base.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, in a collar of stone, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 30 S 29 ----- S 31 S 32 1997</p> <p>Bury the original cor. stone and set an aluminum sign post alongside the aluminum post.</p>
17.50	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89° 38' W., bet. secs. 29 and 32.</p> <p>Over rolling terrain.</p> <p>Milo Road, bears SE. and NW.</p>

Dependent Resurvey, Portion of the Subdivisional Lines.
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
20.01	<p>Point for the E. 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 29 E1/16—— S 32 1997</p> <p>Cor. is located 1.5 lks. E. of fence extending N., and S., 32 lks. to cor. of fences, extending N. and W.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 1½ ft. base to top, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 29 1/4 —— S 32 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located N. 14° E., 21 lks. dist., from cor. of fences, extending E. and S.</p>
60.03	<p>Point for the W. 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 29 W1/16—— S 32 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located 5 lks. W. of fence extending N. and S.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
80.04	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>S. 89° 36' W., bet. secs. 30 and 31.</p> <p>Over rolling terrain, through scattered pine timber.</p>
20.01	<p>Point for the E. 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 30 E1/16 ——— S 31 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located on steep N. slope.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a mound of stone, 1½ ft. base to top, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 30 1/4 ——— S 31 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p>
80.53	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R54W R53W S 25 S 30 ————— S 36 S 31 1936</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0° 13' E., bet. secs. 29 and 30.</p> <p>Over rolling terrain.</p>
19.84	<p>Point for the S. 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S1/16 S 30 S 29 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located 18 lks. S. of fence extending E. and W.</p>
39.68	<p>Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W 1/4 S 30 S 29 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p>
59.52	<p>Point for the N. 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W N1/16 S 30 S 29 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located 55 lks. S. of fence extending E. and W.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
79.36	<p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. below the surface of the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>T33N R53W S 19 S 20</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 30 S 29 1997</p> </div> <p>Cor. is located in hay meadow, 24 lks. W. of fence extending N. and S.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89° 29' W., bet. secs. 20 and 29.</p> <p>Over rolling terrain.</p>
18.905	<p>Point selected for the witness cor. to the E. 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <div style="text-align: center;"> <p>W C T33N R53W S 20 ← E1/16 — S 29 1997</p> </div> <p>Cor. is located S. 32° E., 91 lks dist., from cor. of fences, extending N. and W.</p>
19.905	<p>True point for the E. 1/16 sec. of secs. 20 and 29, falls on cliff, 12 ft. high, above E. side of Sand Creek, course S., where it is impracticable to establish a permanent monument.</p>
39.81	<p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T33N R53W S 20 1/4 ——— S 29 1997</p>
	<p>Set a fiberglass "carsonite" post alongside the aluminum post.</p>
	<p>Cor. is located S. 28¼° E., 76 lks. dist., from cor. of fences, extending E. and S.</p>
61.50	<p>Milo Road, bears NNE. and SSW.</p>
79.62	<p>The cor. of secs. 19, 20, 29 and 30.</p>
	<hr/> <p>S. 88° 28' W., bet. secs. 19 and 30.</p>
	<p>Over rolling terrain.</p>
19.96	<p>The point for the E. 1/16 sec. cor. of secs. 19 and 30. Point not monumented.</p>
39.92	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T33N R53W S 19 1/4 ——— S 30 1997</p>
	<p>Set an aluminum sign post alongside the aluminum post.</p>
	<p>Cor. is located on steep N. slope; thence through scattered timber.</p>
59.88	<p>Point for the W. 1/16 sec. cor. of secs. 19 and 30.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, in a collar of stone, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 19 W1/16— S 30 1997</p> <p>Cor. is located on steep S. slope.</p>
81.07	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R54W R53W S 24 S 19 — — S 25 S 30 1936</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 17' W., bet. secs. 19 and 20.</p> <p>Over rolling terrain.</p>
19.84	<p>Point for the S. 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S1/16 S 19 S 20 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located 10 lks. N. of fence extending E. and W.</p>
30.00	<p>Dirt road, bears SE. and NE.</p>
39.68	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original cor.</p>

Dependent Resurvey. Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
79.36	<p>Set an aluminum post. 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W 1/4 S 19 S 20 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post. 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 18 S 17 ----- S 19 S 20 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located in SW. cor. of Hudson-Meng Bison Kill construction area.</p> <p>From this point, the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., bears N. 0° 35' W., 237.77 chs. dist.</p>
39.755	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89° 20' W., bet. secs. 17 and 20.</p> <p>Over rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post. 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 17 1/4 ——— S 20 1997</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	<p>Set an aluminum sign post alongside the aluminum post.</p>
79.51	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>S. 88° 40' W., bet. secs. 18 and 19.</p> <p>Over rolling terrain.</p>
34.00	<p>Dirt road, bears SE. and NW.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 18 1/4 ——— S 19 1997</p>
81.04	<p>Set an aluminum sign post alongside the aluminum post.</p> <p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R54W R53W S 13 S 18 ————— S 24 S 19 1936</p> <hr/> <p style="text-align: center;">Subdivision of Section 19, T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 0° 22' W., on the N. and S. center line of sec. 19</p> <p>Over rolling terrain, through scattered pine timber.</p>
19.88	<p>Point for the center S. 1/16 sec. cor. of sec. 19.</p>

Subdivision of Section 19,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W C S1/16 S 19 C 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located 90 lks. S. of fence extending ENE. and WSW.</p>
39.76	<p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. center line.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W C1/4 S 19 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>Leave timber.</p>
79.52	<p>The 1/4 sec. cor. of secs. 18 and 19.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20.</p> <p>S. 88° 33' W., on the E. and W. center line of sec. 19.</p> <p>Over rolling terrain, through scattered pine timber.</p>
39.98	<p>The center 1/4 sec. cor. of sec. 19.</p>
81.07	<p>The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp.</p> <hr/>

Subdivision of Section 20,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 20, and 29. N. 0° 19' W., on the N. and S. center line of sec. 20. Over rolling terrain.</p>
17.40	Sand Creek Road, bears ESE. and WNW.
19.87	Point for the center S. 1/16 sec. cor. of sec. 20.
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T33N R53W C S1/16 S 20 C 1997</p>
	Set an aluminum sign post alongside the aluminum post.
39.74	Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line.
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T33N R53W C1/4 S 20 1997</p>
	<p>Set a fiberglass "carsonite" post alongside the aluminum post. Cor. is located S. 12° E., 130 lks. dist., from cor. of fences, extending E. and S.</p>
79.48	The 1/4 sec. cor. of secs. 17 and 20.
	<hr/> <p>From the 1/4 sec. cor. of secs. 20 and 21. S. 89° 24' W., on the E. and W. center line of sec. 20. Over rolling terrain.</p>

Subdivision of Section 20,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
19.89	The point for the center E. 1/16 sec. cor. of sec. 20. Point not monumented.
39.78	The center 1/4 sec. cor. of sec. 20.
79.56	The 1/4 sec. cor. of secs. 19 and 20.
	<hr/>
	From the true point for the E. 1/16 sec. cor. of secs. 20 and 29. N. 0° 20' W. on the N. and S. center line of the SE¼ of sec. 20. Over rolling terrain.
16.10	Sand Creek Road, bears E. and W.
19.88	Point for the SE. 1/16 sec. cor. of sec. 20, at intersection with the E. and W. center line of the SE¼. Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd. T33N R53W SE 1/16 S 20 1997 Set a fiberglass "carsonite" post alongside the aluminum post.
39.76	The point for the center E. 1/16 sec. cor. of sec. 20.
	<hr/>
	From the S. 1/16 sec. cor. of secs. 20 and 21. S. 89° 27' W., on the E. and W. center line of the SE¼ of sec. 20. Over rolling terrain.
19.90	The SE. 1/16 sec. cor. of sec. 20.
39.80	The center S. 1/16 sec. cor of sec. 20.
	<hr/>

Subdivision of Section 21,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 21 and 28.</p> <p>N. 0° 15' W., on the N. and S. center line of sec. 21.</p> <p>Over rolling terrain.</p>
39.83	<p>True point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line, falls in badlands where it is impracticable to establish a permanent monument.</p>
39.93	<p>The point selected for the witness cor. to the center 1/4 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">W C T33N R53W C1/4 S 21 ↓ 1997</p> <p>Set a steel fence post alongside the aluminum post.</p>
59.745	<p>Point for the center N. 1/16 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W C N1/16 S 21 C 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located 20 lks. S. of fence extending E. and W.</p>
79.66	<p>The 1/4 sec. cor. of secs. 16 and 21.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 22.</p> <p>S. 89° 42' W., on the E. and W. center line of sec. 21.</p> <p>Over rolling terrain.</p>

Subdivision of Section 21.
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
20.02	<p>Point for the center E. 1/16 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W E1/16 C————C S 21 1997</p> <p>Cor. is located 5 lks. S. of fence extending E. and W.</p>
40.04	<p>The center 1/4 sec. cor. of sec. 21.</p>
60.06	<p>Point for the center W. 1/16 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W W1/16 C————C S 21 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located S. 63½° E., 40 lks. dist., from cor. of fences, extending N. and E.</p>
80.08	<p>The 1/4 sec. cor. of secs. 20 and 21.</p>
	<hr/> <p>From the center E. 1/16 sec. cor. of sec. 21.</p> <p>N. 0° 12' W., on the N. and S. center line of the NE¼ of sec. 21.</p> <p>Over rolling terrain.</p>
19.925	<p>Point for the NE. 1/16 sec. cor. of sec. 21, at intersection with the E. and W. center line of the NE¼.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>

Subdivision of Section 21.
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>T33N R53W</p> <p>NE 1/16 S 21</p> <p>1997</p>
39.85	<p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located on narrow ridge in badlands, extending E. and W.</p> <p>The E. 1/16 sec. cor. of secs. 16 and 21.</p> <hr/>
20.035	<p>From the N. 1/16 sec. cor. of secs. 21 and 22.</p> <p>S. 89° 40' W., on the E. and W. center line of the NE¼ of sec. 21.</p> <p>Over rolling terrain.</p> <p>The NE. 1/16 sec. cor. of sec. 21.</p>
40.07	<p>The center N. 1/16 sec. cor. of sec. 2.</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 21.</p> <p>N. 0° 18' W., on the N. and S. center line of the NW¼ of sec. 21.</p> <p>Over rolling terrain.</p>
19.905	<p>Point for the NW. 1/16 sec. cor. of sec. 21, falls in badlands where it is impracticable to establish a permanent monument. Point not monumented.</p>
39.81	<p>The point for the W. 1/16 sec. cor. of secs. 16 and 21.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 21.</p> <p>S. 89° 40' W., on the E. and W. center line of the NW¼ of sec. 21.</p> <p>Over rolling terrain.</p>
20.035	<p>The point for the NW. 1/16 sec. cor. of sec. 21.</p>
40.07	<p>The N. 1/16 sec. cor. of secs. 20 and 21.</p> <hr/>

Subdivision of Section 22,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>From the true point for the 1/4 sec. cor. of secs. 22 and 27. N. 0° 10' W., on the N. and S. center line of sec. 22. Over rolling terrain.</p>
19.955	Point for the center S. 1/16 sec. cor. of sec. 22. Point not monumented.
39.91	Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line.
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker. with magnetic aluminum cap mkd.</p>
	T33N R53W
	C1/4 S 22
	1997
	<p>Set an aluminum sign post alongside the aluminum post. Cor. is located 15 lks. N. of draw, drains NE.</p>
79.79	The 1/4 sec. cor. of secs. 15 and 22.
	<p>From the 1/4 sec. cor. of secs. 22 and 23. S. 89° 23' W., on the E. and W. center line of sec. 22. Over rolling terrain.</p>
39.02	The center 1/4 sec. cor. of sec. 22.
58.885	The point for the center W. 1/16 sec. cor. of sec. 22. Point not monumented.
78.75	The 1/4 sec. cor. of secs. 21 and 22.
	<p>From the true point for the W. 1/16 sec. cor. of secs. 22 and 27. N. 0° 10' W., on the N. and S. center line of the SW¼ of sec. 22. Over rolling terrain.</p>

Subdivision of Section 22.
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
19.95	<p>Point for the SW. 1/16 sec. cor. of sec. 22, at intersection with the E. and W. center line of the SW$\frac{1}{4}$.</p> <p>Set an aluminum post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W</p> <p style="text-align: center;">SW 1/16 S 22</p> <p style="text-align: center;">1997</p>
39.90	<p>Set an aluminum sign post alongside the aluminum post.</p> <p>The point for the center W. 1/16 sec. cor. of sec. 22.</p> <hr/>
19.87	<p>From the center S. 1/16 sec. cor. of sec. 22.</p> <p>S. 89° 24' W., on the E. and W. center line of the SW$\frac{1}{4}$ of sec. 22.</p> <p>Over rolling terrain.</p>
39.74	<p>The SW. 1/16 sec. cor. of sec. 22.</p> <p>The S. 1/16 sec. cor. of secs. 21 and 22.</p> <hr/>
	<p style="text-align: center;">Subdivision of Section 26, T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska</p> <hr/>
7.50	<p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>NORTH, on the N. and S. center line of sec. 26.</p> <p>Over rolling terrain.</p>
20.16	<p>Sand Creek Road, bears NE. and SW.</p>
40.32	<p>Point for the center S. 1/16 sec. cor. of sec. 26. Point not monumented.</p>
40.32	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line.</p>

Subdivision of Section 26,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
80.28	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W C1/4 S 26 1997</p> <p>Set an aluminum sign post alongside the aluminum post.</p> <p>Cor. is located 250 lks. S. of cor. of fences, extending N. and E.</p> <p>The 1/4 sec. cor. of secs. 23 and 26.</p>
20.08	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>N. 89° 56' W., on the E. and W. center line of sec. 26.</p> <p>Over rolling terrain.</p> <p>Point for the center E. 1/16 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, supported by a mound of stone, 2½ ft. base to top, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W E1/16 C———C S 26 1997</p>
40.16	<p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located S. 74° E., 101 lks. dist., from cor. of fences, extending S. and W.</p> <p>The center 1/4 sec. cor. of sec. 26.</p>
80.21	<p>The 1/4 sec. cor. of secs. 26 and 27.</p> <hr/> <p>From the point for the E. 1/16 sec. cor. of secs. 26 and 35.</p>

Subdivision of Section 26,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>N. 0° 06' W., on the N. and S. center line of the SE$\frac{1}{4}$ of sec. 26. Over rolling terrain.</p>
10.04	<p>Point for the center S-SE. 1/64 sec. cor. of sec. 26. Point not monumented.</p>
20.08	<p>Point for the SE. 1/16 sec. cor. of sec. 26, at intersection with the E. and W. center line of the SE$\frac{1}{4}$.</p> <p>Set an aluminum post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W SE 1/16 S 26 1997</p>
29.00	<p>Set an aluminum sign post alongside the aluminum post. Sand Creek Road, bears NE. and SW.</p>
40.16	<p>The center E. 1/16 sec. cor. of sec. 26</p> <hr/>
10.06	<p>From the S. 1/16 sec. cor. of secs. 25 and 26. S. 89° 50 W., on the E. and W. center line of the SE$\frac{1}{4}$ of sec. 26. Over rolling terrain.</p>
10.06	<p>Point for the center E-SE. 1/64 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W S 26 C-E-SE 1/64 1997</p> <p>Set an aluminum sign post alongside the aluminum post. Cor. is located 35 lks. E. of fence extending N. and S.</p>

Subdivision of Section 26,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
20.12	The SE. 1/16 sec. cor. of sec. 26.
27.00	Sand Creek Road, bears NE. and SW.
40.24	The point for the center S. 1/16 sec. cor. of sec. 26.
<hr/>	
	From the E-E 1/64 sec. cor. of secs. 26 and 35.
	N. 0° 08' W., on the N. and S. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 26.
	Over rolling terrain.
20.04	The center E-SE 1/64 sec. cor. of sec. 26.
<hr/>	
Subdivision of Section 27, T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska	
<hr/>	
	From the 1/4 sec. cor. of secs. 27 and 34.
	N. 0° 02' E., on the N. and S. center line of sec 27.
	Over rolling terrain.
14.50	Sand Creek Road, bears SE. and NW.
19.955	Point for the center S. 1/16 sec. cor. of sec. 27. Point not monumented.
39.91	Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. center line.
	Set an aluminum post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.
	T33N R53W
	C1/4 S 27
	1997
	Set an aluminum sign post alongside the aluminum post.
79.81	The 1/4 sec. cor. of secs. 22 and 27.
<hr/>	

Subdivision of Section 27,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 26 and 27. S. 89° 29' W., on the E. and W. center line of sec. 27. Over rolling terrain.</p>
19.88	<p>Point for the center E. 1/16 sec. cor. of sec. 27. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base to top, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W E1/16 C———C S 27 1997</p> <p>Set an aluminum sign post alongside the aluminum post. Cor. is located on steep W. slope in badlands.</p>
39.76	The center 1/4 sec. cor. of sec. 27.
79.52	The 1/4 sec. cor. of secs. 27 and 28.
11.00	<p>From the E. 1/16 sec. cor. of secs. 27 and 34. N. 0° 02' E., on the N. and S. center line of the SE¼ of sec. 27. Over rolling terrain.</p>
19.96	Sand Creek Road, bears NE. and SW.
19.96	True point for the SE. 1/16 sec. cor. of sec. 27, at intersection with the E. and W. center line of the SE¼., falls in badlands where it is impracticable to establish a permanent monument.
39.92	The center E. 1/16 sec. cor. of sec. 27.
	<p>From the S. 1/16 sec. cor. of secs. 26 and 27. S. 89° 30' W., on the E. and W. center line of the SE¼ of sec. 27. Over rolling terrain.</p>

Subdivision of Section 27.
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
19.885	Point for the true point of the SE. 1/16 of sec. 27.
20.885	Point selected for the witness cor. to the SE. 1/16 sec. cor. of sec. 27.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.
	W C
	T33N R53W
	SE 1/16 S 27
	1997
	Set an aluminum sign post alongside the aluminum post.
39.77	The point for center S. 1/16 sec. cor. of sec. 27.
<hr/> Subdivision of Section 28, T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska <hr/>	
	From the 1/4 sec. cor. of secs. 28 and 33.
	N. 0° 01' W., on the N. and S. center line of sec. 28.
	Over rolling terrain.
18.065	Point selected for the witness cor. to the center S. 1/16 sec. cor. of sec. 28.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 29 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.
	T33N R53W
	C
	S1/16 S 28
	C
	1997
	Set a fiberglass "carsonite" post alongside the aluminum post.
	Cor. is located on ridge, extending E. and W.

Subdivision of Section 28,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
19.915	True point for the center S. 1/16 sec. cor. of sec. 28, falls in badlands where it is impracticable to establish a permanent monument.
23.00	Sand Creek, drains E.
39.83	Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line. Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd. T33N R53W C1/4 S 28 1997 Set an aluminum sign post alongside the aluminum post.
59.00	Sand Creek Road, bears SE. and NW.
79.66	The 1/4 sec. cor. of secs. 21 and 28. <hr/>
	From the 1/4 sec. cor. of secs. 27 and 28. S. 89° 49' W., on the E. and W. center line of sec. 28. Over rolling terrain.
39.94	The center 1/4 sec. cor. of sec. 28.
79.88	The 1/4 sec. cor. of secs. 28 and 29. <hr/>
	From the true point for the center S. 1/16 sec. cor. of sec. 28. S. 89° 51' W., on the E. and W. center line of the SW¼ of sec. 28. Over rolling terrain.
39.92	The S. 1/16 sec. cor. of secs. 28 and 29. <hr/>

Subdivision of Section 29.
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	From the 1/4 sec. cor. of secs. 29 and 32.
	N. 0° 04' E., on the N. and S. center line of sec. 29.
	Over rolling terrain.
15.00	Milo Road, bears N. and SE.; thence along road.
19.87	Point for the center S. 1/16 sec. cor. of sec. 29. Point not monumented.
39.74	Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line.
	Set a steel reinforcement rod, 18 ins. long, 5/8 in. diam., 18 ins. below the surface of Milo Road, with 2½ ins. diam. aluminum cap mkd.
	T33N R53W
	C1/4 S 29
	1997
	from which
	An aluminum post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 53½° E., 76.2 lks. dist., with brass cap mkd. RM T33N R53W S29 50.26 FT 1997 and an arrow pointing to the cor., with a fiberglass "carsonite" post alongside.
	An aluminum post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 55° W., 69.8 lks. dist., with brass cap mkd. RM T33N R53W S29 46.08 FT 1997 and an arrow pointing to the cor., with a fiberglass "carsonite" post alongside.
50.00	Milo Road, bears S. and NW.; leave road.
59.61	Point for the center N. 1/16 sec. cor. of sec. 29.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.

Subdivision of Section 29,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	T33N R53W C N1/16 S 29 C 1997
	Set an aluminum sign post alongside the aluminum post.
	Cor. is located 16 lks. S of intersection of fences, extending N., E. and W.
79.48	The 1/4 sec. cor. of secs. 20 and 29.
	<hr/> From the true point for the 1/4 sec. cor. of secs. 28 and 29. S. 89° 33' W., on the E. and W. center line of sec. 29. Over rolling terrain.
19.96	Point for the center E. 1/16 sec. cor. of sec. 29. Point not monumented.
39.92	The center 1/4 sec. cor. of sec. 29.
59.88	Point for the center W. 1/16 sec. cor. of sec. 29. Point not monumented.
79.84	The 1/4 sec. cor. of secs. 29 and 30.
	<hr/> From the E. 1/16 sec. cor. of secs. 29 and 32. N. 0° 01' W., on the N. and S. center line of the SE¼ of sec. 29. Over rolling terrain.
2.50	Milo Road, bears SE. and NW.
19.88	Point for the SE. 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the SE¼.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.

Subdivision of Section 29,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>T33N R53W</p> <p>SE 1/16 S 29</p> <p>1997</p>
	<p>Set an aluminum sign alongside the aluminum post.</p> <p>Cor. is located S. 74° W., 14.6 lks. dist., from cor. of fences, extending E. and S.</p>
39.76	<p>The point for the center E. 1/16 sec. cor. of sec. 29.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 28 and 29.</p> <p>S. 89° 36' W., on the E. and W. center line of the SE¼ of sec. 29.</p> <p>Over rolling terrain.</p>
19.99	<p>The SE. 1/16 sec. cor. of sec. 29.</p>
39.98	<p>The point for the center S. 1/16 sec. cor. of sec. 29.</p> <hr/> <p>From the W. 1/16 sec. cor. of secs. 29 and 32.</p> <p>N. 0° 08' E., on the N. and S. center line of the SW¼ of sec. 29.</p> <p>Over rolling terrain.</p>
19.86	<p>Point for the SW. 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the SW¼.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p>T33N R53W</p> <p>SW 1/16 S 29</p> <p>1997</p>
	<p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located S. 35° E., 12 lks. dist. from cor. of fences, extending S. and W.</p>

Subdivision of Section 29,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
39.72	The point for the center W. 1/16 sec. cor. of sec. 29.
	<hr/> From the center S. 1/16 sec. cor. of sec. 29. S. 89° 36' W., on the E. and W. center line of the SW¼ of sec. 29.
19.99	The SW. 1/16 sec. cor. of sec. 29.
39.98	The S. 1/16 sec. cor. of secs. 29 and 30.
	<hr/> <p style="text-align: center;">Subdivision of Section 30, T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska</p> <hr/>
	From the 1/4 sec. cor. of secs. 30 and 31.
	N. 0° 18' E., on the N. and S. center line of sec. 30.
	Over rolling terrain, through scattered pine timber.
19.645	Point for the center S. 1/16 sec. cor. of sec. 30. Point not monumented.
39.29	Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.
	T33N R53W
	C1/4 S 30
	1997
	Set a fiberglass "carsonite" post alongside the aluminum post.
58.94	Point for the center N. 1/16 sec. cor. of sec. 30.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.

Subdivision of Section 30,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p style="text-align: center;">T33N R53W C N1/16 S 30 C 1997</p>
78.59	<p>Set a steel fence post alongside the aluminum post.</p> <p>The 1/4 sec. cor. of secs. 19 and 30.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>S. 89° 00' W., on the E. and W. center line of sec. 30.</p> <p>Over rolling terrain.</p>
19.98	<p>Point for the center E. 1/16 sec. cor. of sec. 30.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p style="text-align: center;">T33N R53W E1/16 C———C S 30 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located S. 14° W., 70 lks. dist., from cor. of fences, extending N. and W.</p> <p>Thence through scattered timber.</p>
39.96	<p>The center 1/4 sec. cor. of sec. 30.</p>
59.98	<p>Point for the center W. 1/16 sec. cor. of sec. 30. Point not monumented.</p>
80.87	<p>The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.</p> <hr/>
	<p>From the center E. 1/16 sec. cor. of sec. 30.</p> <p>N. 0° 15' E., on the N. and S. center line of the NE¼ of sec. 30.</p> <p>Over rolling terrain.</p>

Subdivision of Section 30.
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
19.75	<p>Point for the NE. 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the NE¼.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W</p> <p style="text-align: center;">NE 1/16 S 30</p> <p style="text-align: center;">1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located S. 26½° E., 89.4 lks. dist. from cor. of fences, extending E. and S.</p>
39.50	<p>The point for the E. 1/16 sec. cor. of secs. 19 and 30.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 29 and 30.</p> <p>S. 88° 44' W., on the E. and W. center line of the NE¼ of sec. 30.</p> <p>Over rolling terrain.</p>
19.97	<p>The NE. 1/16 sec. cor. of sec. 30; thence through scattered pine timber.</p>
39.94	<p>The center N. 1/16 sec. cor. of sec. 30.</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 0° 15' E., on the N. and S. center line of the SE¼ of sec. 30.</p> <p>Over rolling terrain, through scattered pine timber.</p>
19.74	<p>Point for the SE. 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the SE¼.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>

Subdivision of Section 30,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
	<p>T33N R53W</p> <p>SE 1/16 S 30</p> <p>1997</p>
	<p>Set a fiberglass "carsonite" post alongside the aluminum post. Cor. is located 45 lks. S. of fence extending E. and W.</p>
39.48	<p>The center E. 1/16 sec. cor. of sec. 30.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 29 and 30. S. 89° 18' W., on the E. and W. center line of the SE¼ of sec. 30. Over rolling terrain.</p>
19.99	<p>The SE. 1/16 sec. cor. of sec. 30; thence through scattered pine timber.</p>
39.98	<p>The point for the center S. 1/16 sec. cor. of sec. 30.</p> <hr/> <p>From the point for the center W. 1/16 sec. cor. of sec. 30. N. 0° 24' E., on the N. and S. center line of the NW¼ of sec. 30. Over rolling terrain, through pine timber.</p>
19.56	<p>Point for the NW. 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the NW¼. Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p>
	<p>T33N R53W</p> <p>NW 1/16 S 30</p> <p>1997</p>
	<p>Set a steel fence post alongside the aluminum post.</p>
39.12	<p>The W. 1/16 sec. cor. of secs. 19 and 30.</p> <hr/>

Subdivision of Section 30,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	
<p>19.99</p> <p>41.03</p>	<p>From the center N. 1/16 sec. cor. of sec. 30.</p> <p>S. 88° 44' W., on the E. and W. center line of sec. 30.</p> <p>Over rolling terrain, through pine timber.</p> <p>The NW. 1/16 sec. cor. of sec. 30.</p> <p>The point for the N. 1/16 sec. cor. of secs. 25 and 25, on the W. bdy. of the Tp.</p>
<p>Subdivision of Section 32 T. 33 N., R. 53 W., Sixth Principal Meridian, Wyoming</p>	
<p>39.52</p> <p>79.17</p>	<p>From the 1/4 sec. cor. of sec. 32, on the S. bdy. of the Tp.</p> <p>N. 0° 44' W., on the N. and S. center line of sec. 32.</p> <p>Over rolling terrain, through pine timber.</p> <p>Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W</p> <p style="text-align: center;">C1/4 S 32</p> <p style="text-align: center;">1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. is located S. 51° E., 64 lks. dist., from cor. of fences, extending N. and W.</p> <p>Leave timber.</p> <p>The 1/4 sec. cor. of secs. 29 and 32.</p>
<p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>S. 89° 49' W., on the E. and W. center line of sec. 32.</p>	

Subdivision of Section 32,
T. 33 N., R. 53 W., Sixth Principal Meridian, Nebraska

CHAINS	<p>Over rolling terrain.</p> <p>39.54 The center 1/4 sec. cor. of sec. 30; enter pine timber.</p> <p>59.83 Point for the center W. 1/16 sec. cor. of sec. 32.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, atop a white DEEP-1 magnetic marker, with magnetic aluminum cap mkd.</p> <p style="text-align: center;">T33N R53W W1/16 C——C S 32 1997</p> <p>Set a fiberglass "carsonite" post alongside the aluminum post.</p> <p>Cor. falls on steep N. slope.</p> <p>80.12 The 1/4 sec. cor. of secs. 31 and 32.</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 32.</p> <p>N. 0° 20' W., on the N. and S. center line of the NW¼ of sec. 32.</p> <p>Over rolling terrain, through pine timber.</p> <p>39.58 The W. 1/16 sec. cor. of secs. 29 and 32.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area embraced by this survey is situated in the northeast portion of Sioux County, approximately 25 miles north of Crawford, Nebraska. The terrain consists of grasslands, and badlands in the northeast portion of the township, with the elevation ranging from about 3,700 feet to about 4,700 feet above sea level. The soil is primarily sandy, with vegetation consisting of native grasses and some pine timber in the southeast portion. Drainage of the area is easterly by numerous draws and ravines. There are a few inhabitants in the township. There was no evidence of mineral activity at the time of the survey.</p> <p>Access is provided by Nebraska State Highway Nos. 2 and 71, Milford Road, Milo Road, Sand Creek Road and Toadstool Road, and numerous other roads and trails throughout the township.</p>
--------	--

CERTIFICATE OF SURVEY

We, Lynn A. Forbes and Carl W. Sumpter, Cadastral Surveyors. HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day of March, 1996, we have dependently resurveyed a portion of the Eighth Standard Parallel North, through Range 53 West, portions of the west and north boundaries, and a portion of the subdivisional lines, and subdivided certain sections, Township 33 North, Range 53 West, of the Sixth Principal Meridian, in the State of Nebraska, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAY 31 2002

(Date)

Lynn A. Forbes
(Cadastral Surveyor)

MAY 31 2002

(Date)

Carl W. Sumpter
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of a portion of the Eighth Standard Parallel North, through Range 53 West, portions of the west and north boundaries, and a portion of the subdivisional lines, and the subdivision of certain sections, Township 33 North, Range 53 West, of the Sixth Principal Meridian, in the State of Nebraska, executed by Lynn A. Forbes and Carl W. Sumpter, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

MAY 31 2002

(Date)

John P. Lee
(Signature of Authorized Officer)