

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A

PORTION OF THE FOURTEENTH AUXILIARY MERIDIAN WEST,
THROUGH TOWNSHIP 41 NORTH, BETWEEN RANGES 116 AND 117 WEST,
PORTIONS OF THE NORTH BOUNDARY AND SUBDIVISIONAL LINES,
AND A PORTION OF THE
ADJUSTED MEANDER LINE OF THE RIGHT BANK OF THE SNAKE RIVER,
THE SUBDIVISION OF SECTION 6,
THE SURVEY OF THE RIPARIAN PARTITION LINES,
AND A PORTION OF THE
PRESENT RIGHT AND LEFT BANKS OF THE SNAKE RIVER,
TOWNSHIP 41 NORTH, RANGE 116 WEST,
OF THE SIXTH PRINCIPAL MERIDIAN,
IN THE STATE OF WYOMING.

EXECUTED BY

LYNN A. FORBES

CADASTRAL SURVEYOR

Under Special Instructions dated APRIL 2, 1998, approved APRIL 6, 1998, which provided for the surveys included under Group Number 652, and assignment instructions dated April 2, 1998.

Survey commenced APRIL 30, 1998

Survey completed MAY 20, 1998

INDEX DIAGRAM

33

Township 41 North, Range 116 West

5

2	6	7	5	4	3	2	1
7	8	9	10	11	12	13	14
18	17	16	15	14	13	12	11
19	20	21	22	23	24	25	26
30	29	28	27	26	25	24	23
31	32	33	34	35	36	37	38

Dependent Resurvey, Portion of the Adjusted Meander Line
of the Right Bank of the Snake River.....Page 8
Subdivision of Section 6.....Page 9
Survey of the Riparian Partition Lines.....Page 14
Survey, Portion of the Present Right Bank of the Snake River.....Page 15
Survey, Portion of the Present Left Bank of the Snake River.....Page 16

T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS

The following field notes are those of the dependent resurvey of a portion of the Fourteenth Auxiliary Meridian West, through Township 41 North, between Ranges 116 and 117 West, portions of the north boundary and subdivisional lines, and a portion of the adjusted meander line of the right bank of the Snake River, the subdivision of section 6, the survey of the riparian partition lines, and a portion of the present right bank of the Snake River, Township 41 North, Range 116 West, Sixth Principal Meridian, Wyoming.

The history of surveys pertaining to this resurvey is as follows:

William O. Owen surveyed the Fourteenth Auxiliary Meridian West, (west boundary) the north boundary, the subdivisional lines and meandered the Snake River in 1892. Newell J. Burnham resurveyed a portion of west boundary in 1902. Hans D. Voigt resurveyed a portion of the west boundary in 1918. Jack A. Eaves dependently resurveyed a portion of the west boundary in 1963. Dennis D. Bland and Wayne M. Gardner dependently resurveyed portions of the west and north boundaries, and subdivisional lines and the meanders of the Snake River in 1971. A survey of riparian lands was prepared by photogrammetric methods using 1974 aerial photography, accepted August 21, 1987.

Local surveyors have conducted numerous surveys in the area from the 1960's to the present time, and the acceptance of such surveys is detailed herein.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 652, Wyoming, dated April 2, 1998.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data was thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS							
	<p>The survey was executed with a WILD model T-1000 theodolite, a WILD model DI-2000 electronic distance meter and by chaining methods. The instruments were maintained in proper adjustment at all times. The direction of all lines refer to the true meridian, determined by hour angle observations of the sun at various points along the lines of survey and carried forward by sustained angulation.</p> <p>The geographic position of the cor. of Tps. 41 and 42 N., Rs. 116 and 117 W., based on NAD 83 and determined by satellite positioning methods, is:</p> <p>Latitude 43° 32' 59.8" N., Longitude 110° 49' 00.8" W.</p> <p>The magnetic declination is 14½° E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the West Boundary, T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the dependent resurvey executed by Dennis D. Bland and Wayne M. Gardner in 1971)</p> <hr/> <p>Beginning at the cor. of secs. 6 and 7 only, T. 41 N., R. 116 W., on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T41N</td></tr> <tr><td> S 6</td></tr> <tr><td>—</td></tr> <tr><td> S 7</td></tr> <tr><td>R116W</td></tr> <tr><td>1963</td></tr> </table> </div> <p>NORTH, bet. secs. 1 and 6, on the W. bdy. of sec. 6.</p> <p>Over nearly level terrain.</p> <p>1.45 Irrigation ditch, 8 lks. wide, bears E. and W.</p> <p>5.91 Gravel access road, bears E. and W.</p> <p>17.96 The S. 1/16 sec. cor. of sec. 1 only, T. 41 N., R. 117 W., established by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, monumented with an iron post, 2½ ins. diam., firmly set, flush with the surface of the ground, with brass cap inscribed PAUL N. SCHERBEL BIG PINEY WYOMING RLS 164 and mkd.</p>	T41N	S 6	—	S 7	R116W	1963
T41N							
S 6							
—							
S 7							
R116W							
1963							

Dependent Resurvey of a Portion of the West Boundary,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T41N R117W R116W S1/16 S 1 1974</p> <p>This position is accepted as a careful and faithful determination of the cor. position.</p> <p>Cor. is located on E. edge of Wyoming State Highway No. 390, extending N. and SW.</p> <hr style="width: 20%; margin: 10px auto;"/>
2.15	<p>NORTH, beginning new measurement, along highway.</p> <p>The S. 1/16 sec. cor. of sec. 6 only, established by Peter M. Jorgensen, Wyoming Professional Engineer and Land Surveyor No. 2612, monumented with a concrete nail, firmly set, flush with the asphalt surface of the road. This position is accepted as a careful and faithful determination of the cor. position.</p> <hr style="width: 20%; margin: 10px auto;"/>
17.80	<p>NORTH, beginning new measurement.</p> <p>Over nearly level terrain, along highway.</p> <p>The ¼ sec. cor. of sec. 1 only, T. 41 N., R. 117 W., reestablished by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, with a mound of stone, 3 ft. base, 6 ins. high, W. of the cor., with brass cap inscribed PAUL N. SCHERBEL BIG PINEY WYOMING RLS 164 and mkd.</p> <p style="text-align: center;">T41N R117W R116W 1/4 S 1 1971</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located in buck rail fence, extending N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>NORTH, beginning new measurement.</p> <p>Over nearly level terrain.</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
2.31	<p>The $\frac{1}{4}$ sec. cor. of sec. 6 only, T. 41 N., R. 116 W., reestablished by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 3 ins. above the ground, in a mound of stone, 2.5 ft. diam. to top, with brass cap inscribed PAUL N. SCHERBEL BIG PINEY WYOMING RLS 164 and mkd.</p> <p style="text-align: center;">T41N R117W R116W 1/4 S 6 1971</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located in buck rail fence, extending N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 06'$ E., beginning new measurement.</p> <p>Over nearly level terrain, along highway.</p>
20.11	<p>The N. $1/16$ sec. cor. of sec. 6 only, established by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, monumented with a concrete nail, firmly set, flush with the asphalt surface of the road, 3 ft. W. of center line of Wyoming State Highway No. 90, bears N. and S. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 06'$ E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
20.11	<p>The cor. of Tps. 41 and 42 N., Rs. 116 and 117 W., reestablished by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, in 1971, perpetuated by the Wyoming Highway Department, monumented with a $1\frac{1}{2}$ in. diam. aluminum cap inscribed WYOMING HIGHWAY. This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <hr style="width: 80%; margin: 10px auto;"/>

Dependent Resurvey, Portion of the North Boundary,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">(Restoring the survey executed by Dennis D. Bland and Wayne M. Gardner in 1971)</p> <hr/> <p>From the true point for the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., at proportionate distance, by the method of irregular boundary, falls on rock bar between the levees of the Snake River where is impracticable to establish a permanent monument; there is no remaining evidence of the 1971 witness cor., S. 88° 45' E., 1.15 chs. dist.</p> <p>From this point, the meander cor. of secs. 5 and 32, on the left bank of the Snake River, bears S. 88° 47' E., 36.58 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, flush with the surface of the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T42N R116W M / S 32 C / S 5 T41N 1971</p> </div> <p>Cor. is located 5 lks. S. of barb wire fence extending E., and W., 51 lks. to a channel of the Snake River.</p> <p>The control line was fully retraced and no evidence of the intervening cors. was found.</p> <p>N. 89° 55' W., bet. secs. 6 and 31.</p> <p>Over nearly level terrain, across a channel of the Snake River.</p> <p>3.35 Point selected for a new witness cor. to the cor. of secs. 5, 6, 31 and 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C T42N R116W S 31 S 32 -----> S 6 S 5 T41N 1998</p> </div>
--------	--


Dependent Resurvey, Portion of the North Boundary,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Cor. is located on top of levee, extending NE. and SW., 25 lks. N. of buck rail fence extending W.; thence along fence.</p>
20.24	<p>The E. 1/16 sec. cor. of secs. 6 and 31, established by Scott R. Pierson, Wyoming Registered Land Surveyor No. 3831, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap inscribed PIERSON LAND SURVEYS RLS 3831 and mkd.</p>
	<p style="text-align: center;">T42N R116W S 31 E1/16 ——— S 6 T41N 1987</p>
	<p>This position is accepted as a careful and faithful determination of the cor. position.</p>
	<p>Cor. is located under buck rail fence.</p>
	<p style="text-align: center;">—————</p> <p>N. 89° 56' W., beginning new measurement.</p>
	<p>Over nearly level terrain, along buck rail fence.</p>
20.25	<p>The ¼ sec. cor. of secs. 6 and 31, remonumented by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap inscribed PAUL N. SCHERBEL BIG PINEY WYOMING RLS 164 and mkd.</p>
	<p style="text-align: center;">T42N R116W S 31 1/4 ——— S 6 T41N R116W 1965</p>
	<p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p>
	<p>Cor. is located at cor. of buck rail fences extending E. and S.</p>
	<p style="text-align: center;">—————</p> <p>S. 89° 53' W., beginning new measurement.</p>
	<p>Over nearly level terrain.</p>

Dependent Resurvey, Portion of the North Boundary,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.23	<p>The W. 1/16 sec. cor. of secs. 6 and 31, established by Frank J. Grimes, Wyoming Professional Engineer and Registered Land Surveyor No. 2892, monumented with an iron post, 2½ ins. diam., firmly set, top bent over to ground, brass cap missing. This position is accepted as a careful and faithful determination of the cor. position.</p> <hr/> <p>S. 89° 53' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
19.46	<p>The cor. of Tps. 41 and 42 N., Rs. 116 and 117 W.</p> <hr/> <p>Dependent Resurvey, Portion of the Subdivisional Lines, T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>(Restoring the survey executed by Dennis D. Bland and Wayne M. Gardner in 1971)</p> <hr/> <p>From the meander cor. of secs. 5 and 6, on the right bank of the Snake River, monumented with an iron post, 2½ ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd.</p> <div data-bbox="860 1165 1031 1386" style="text-align: center;"> <p>T41N R116W</p> </div> <p>N. 0° 48' E., bet. secs. 5 and 6.</p> <p>Over nearly level terrain, across rock bars and the Snake River.</p>
14.69	<p>The true point for the cor. of secs. 5, 6, 31 and 32.</p> <hr/>

Dependent Resurvey of a Portion of the Adjusted Meander Line,
of the Right Bank of the Snake River,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>(Restoring the survey executed by Dennis D. Bland and Wayne M. Gardner in 1971)</p> <hr/> <p>From angle point No. 11, sec. 6, on the right bank of the Snake River, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T41N R116W</p>  <p>S 6 AP 11 1971</p> </div>
	N. 44° 04' E., 3.64 chs.
	Upstream, over rock bars and channels of the Snake river.
3.64	Point for angle point No. 12, falls in the Snake River, there is no remaining evidence of the 1971 monument.
	N. 23° 42' E., 1.52 chs.
1.52	Point for angle point No. 13, falls in the Snake River, there is no remaining evidence of the 1971 monument.
	N. 48° 29' E., 2.53 chs.
2.53	Point for angle point No. 14, falls in the Snake River, there is no remaining evidence of the 1971 monument.
	N. 10° 24' E., 3.33 chs.
3.33	Point for angle point No. 15, falls in the Snake River, there is no remaining evidence of the 1971 monument.
	N. 30° 23' W., 0.03 chs.
0.03	The true point for the special meander cor. at intersection with the E. and W. center line of sec. 6, falls in the Snake River, where it is impracticable to establish a permanent monument.

Dependent Resurvey of a Portion of the Adjusted Meander Line,
of the Right Bank of the Snake River,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>2.51</p>	<p>Angle point No. 16, monumented with an iron post 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T41N R116W</p> <p>S 6 /</p> <p> AP</p> <p> 16</p> <p>1971</p> </div> <hr/> <p style="text-align: center;">Subdivision of Section 6, T. 41 N., R. 116 W. Sixth Principal Meridian, Wyoming</p> <hr/> <p>From the point for the special meander cor. on the N. and S. center line of sec. 6, at intersection with the adjusted meander line of the right bank of the Snake River, falls in river, where it is impracticable to establish a permanent monument.</p> <p>From this point, angle point No. 9, bears N. 49° 02' E., 18.33 chs., monumented with an iron post, firmly set, projecting 6 ins. above the ground, in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T41N R116W</p> <p>S 6 /</p> <p> AP</p> <p> 9</p> <p>1971</p> </div> <p>From this same point, angle point No. 4, bears N. 72° 36' W., 2.51 chs., monumented with an iron post, firmly set, projecting 4 ins. above the ground, in a collar of stone, with a steel fence post alongside, with brass cap mkd.</p> <div style="text-align: center;"> <p>T41N R116W</p> <p>S 6 /</p> <p> AP</p> <p> 4</p> <p>1971</p> </div> <p>The control line was fully retraced and no evidence of the intervening cors. was found, having been washed out by the river.</p> <p>N. 0° 21' E., on the N. and S. center line of sec. 6, across flood plane of the Snake River</p>
---------------------------	---

Subdivision of Section 6,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
2.00	<p>Approximate present right Bank of the Snake River, bears E. and W.; thence over nearly level terrain, through John Dodge subdivision.</p>
6.44	<p>The center S. 1/16 sec. cor. of sec. 6, established by Peter M. Jorgensen, Wyoming Professional Engineer and Registered Land Surveyor No. 2612, with an aluminum post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with a steel fence post alongside, with aluminum cap inscribed PETER M. JORGENSEN PE+LS 2612, and mkd.</p> <p style="text-align: center;">T41N R116W S 6 CS1/16 1981</p> <p>This position is accepted as a careful and faithful determination of the cor. position.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 21' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
20.20	<p>The center ¼ sec. cor. of sec. 6, established by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, with an iron post, 2½ ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap inscribed PAUL N. SCHERBEL RLS 164 BIG PINEY WYOMING, and mkd.</p> <p style="text-align: center;">T41N R116W C1/4 SEC 6 1978</p> <p>This position is accepted as a careful and faithful determination of the cor. position.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 21' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
20.17	<p>The center N. 1/16 sec. cor. of sec. 6, established by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap inscribed PAUL N. SCHERBEL RLS 164 BIG PINEY WYOMING, and mkd.</p>

Subdivision of Section 6,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T41N R116W SEC 6 CN 1/16 1978</p>
	<p>This position is accepted as a careful and faithful determination of the cor. position.</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 0° 21' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
20.14	<p>The ¼ sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp.</p> <hr/>
	<p>From the true point for the special meander cor. on the E. and W. center line of sec. 6, at intersection with the adjusted meander line of the right bank of the Snake River.</p> <p>N. 89° 59' W., on the E. and W. center line of sec. 6.</p> <p>Over rock bars and the Snake River.</p>
1.57	<p>True point for the center E. 1/16 sec. cor. of sec. 6, determined at record dist. from the witness cor. established by Scott R. Pierson, hereinafter described, falls in channel of Snake River, where it is impracticable to establish a permanent monument.</p>
2.08	<p>Edge of channel of Snake River, thence over nearly level terrain.</p>
2.33	<p>Point selected for the witness cor. to the special meander cor. on the E. and W. center line of sec. 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>W C T41N R116W SMC C ——— C-> S 6 1998</p> </div>
2.86	<p>The witness cor. to the center E. 1/16 sec. cor. of sec. 6, established by Scott R. Pierson, Wyoming Registered Land Surveyor No. 3831, monumented with an aluminum post, 2½ ins. diam., firmly set, flush with the surface of the ground, with aluminum cap inscribed PIERSON LAND SURVEYS JACKSON WYOMING, and mkd.</p>


Subdivision of Section 6,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
	WC T41N R116W CE1/16 <hr/> SECTION 6 1987 <hr/>
	N. 89° 59' W., beginning new measurement. Over nearly level terrain.
18.95	The center $\frac{1}{4}$ sec. cor. of sec. 6. <hr/>
	N. 89° 59' W., beginning new measurement. Over nearly level terrain.
20.08	The center W. 1/16 sec. cor. of sec. 6, established by Paul N. Scherbel, Wyoming Registered Land Surveyor No. 164, with an iron post, 2½ ins. diam., firmly set, projecting 1 ins. above the ground, with brass cap mkd.
	T41N R116W W1/16 C—C S 6 1974
	This position is accepted as a careful and faithful determination of the cor. position. <hr/>
	N. 89° 59' W., beginning new measurement. Over nearly level terrain.
19.43	The $\frac{1}{4}$ sec. cor. of sec. 6 only, on the W. bdy. of the Tp. <hr/>
	From the true point for the center E. 1/16 sec. cor. of sec. 6. N. 0° 21' E., on the N. and S. center line of the NE¼ of sec. 6. Over gravel bars across channel of Snake River.
0.25	Edge of channel of Snake River, thence over levee and nearly level terrain.

Subdivision of Section 6,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.15	<p>The NE. 1/16 sec. cor. of sec. 6, established by Scott R. Pierson, Wyoming Registered Land Surveyor No. 3831, with an aluminum post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap inscribed PIERSON LAND SURVEYS JACKSON WYOMING, and mkd.</p> <p style="text-align: center;">T41N R116W NE 1/16 SECTION 6 1987</p> <p>This position is accepted as a careful and faithful determination of the cor. position.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 22' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
20.15	<p>The E. 1/16 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp.</p> <hr style="width: 80%; margin: auto;"/> <p>From the special meander cor. on the E. and W. center line of the NE¼ sec. 6, at intersection with the adjusted meander line of right bank of the Snake River, established by Albert L. Nelson, Professional Engineer and Registered Land Surveyor No. 578, with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R116W SEC 6 LOT 1</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">LOT 6 1979 PE LS 578</p> <p>This position is accepted as a careful and faithful determination of the cor. position.</p> <p>N. 89° 53' W., on the E. and W. center line of the NE¼ sec. 6.</p> <p>Over nearly level terrain.</p>
18.62	<p>The NE. 1/16 sec. cor. of sec. 6.</p> <hr style="width: 20%; margin: auto;"/>

Subdivision of Section 6,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>N. 89° 54' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
20.24	<p>The center N. 1/16 sec. cor., sec. 6.</p> <hr/> <p style="text-align: center;">Survey of the Riparian Partition Lines, T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>The riparian partition lines to lot 6, section 6, have been fixed by stipulated agreement approved in United State District Court for the District of Wyoming, United States of America v. Donald Albrecht., ET AL., C79-113K.</p> <hr/> <p>From the special meander cor. on the E. and W. center line of the NE$\frac{1}{4}$ of sec. 6, at the intersection with the adjusted meander line of the right bank of the Snake River.</p> <p>S. 68° 00' E., on the riparian partition line between original lots 1 and 6, sec. 6.</p>
8.72	<p>Point for the auxiliary meander cor. at intersection with the present right bank of the Snake River.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;">  </div>
11.33	<p>From the point for the special meander cor. on the E. and W. center line of sec. 6, at intersection with the adjusted meander line of the right bank of the Snake River.</p> <p>S. 26° 00'E., on the riparian partition line between original lots 6 and 7, sec. 6.</p> <p>Point for the auxiliary meander corner at intersection with the present right bank of the Snake River.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Riparian Partition Lines,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>T41N R116W</p>  <p>AMC 1998</p>
	<p>Survey of a Portion of the Present Right Bank of the Snake River, T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming</p>
	<p>From the auxiliary meander cor. on the present right bank of the Snake River, at intersection with the southerly partition line riparian to lot 6.</p>
	<p>N. 60° 59' E., upstream along the present right bank of the Snake River.</p>
6.80	<p>Point for an angle point, point not monumented.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>
	<p>N. 52° 35' E., beginning new measurement.</p>
2.85	<p>Point for an angle point, point not monumented</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>
	<p>N. 71° 23' E., beginning new measurement.</p>
3.06	<p>Point for an angle point, point not monumented.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>
	<p>S. 85° 21' E., beginning new measurement.</p>
2.68	<p>Point for an angle point, point not monumented</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>
	<p>N. 12° 13' E., beginning new measurement.</p>
3.67	<p>Point for an angle point, point not monumented</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>
	<p>N. 20° 46' E., beginning new measurement.</p>
2.84	<p>Point for an angle point, point not monumented.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

Survey of a Portion of the Present
Right Bank of the Snake River,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
	S. 35° 49' E., beginning new measurement.
6.81	Point for an angle point, point not monumented <hr/>
	N. 2° 12' E., beginning new measurement.
2.17	Point for an angle point, point not monumented <hr/>
	N. 8° 35' E., beginning new measurement.
2.11	Point for an angle point, point not monumented. <hr/>
	N. 0° 29' W., beginning new measurement.
2.98	Point for an angle point, point not monumented <hr/>
	N. 8° 02' E., beginning new measurement.
2.24	The auxiliary meander cor. on the present right bank of the Snake River, at intersection with the northerly partition line riparian to lot 6. <hr/>
	Survey of a Portion of the Present Left Bank of the Snake River, T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming <hr/>
	From Angle Point No. 9, sec. 7, T. 41 N., R. 116 W., on the left bank of the adjusted original meander line, reestablished by Scott A. Scherbel, Wyoming Registered Land Surveyor No. 3889, monumented with an iron post, 2½ ins. diam., firmly set, flush with the surface of the ground, with brass cap inscribed SCOTT A SCHERBEL JACKSON WYOMING and mkd.
	RLS 3889 T41N R116W AP 9 / S 7 1985
	This position is accepted as a careful and faithful reestablishment of the 1971 resurvey cor. position.
	N. 86° 14' W., downstream, along the present left bank, 8.59 chs.

Survey of a Portion of the Present Left Bank of the Snake River,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

CHAINS	
8.59	Point for an angle point, not monumented. _____
	S. 82° 47' W., 9.86 chs.
9.86	Point for an angle point, not monumented. _____
	S. 15° 47' W., 8.64 chs.
8.64	Point for an angle point, not monumented. _____
	S. 14° 55' E., 3.18 chs.
3.18	Point for an angle point, not monumented. _____
	S. 24° 07' E., 5.36 chs.
5.36	Point for an angle point, not monumented. _____
	S. 0° 47' E., 1.82 chs.
1.82	Point for an angle point, not monumented. _____
	S. 26° 50' W., 4.01 chs.
4.01	Point for an angle point, not monumented. _____
	S. 7° 33' W., 3.97 chs.
3.97	Point for an angle point, not monumented. _____
	S. 30° 51' W., 2.27 chs.
2.27	Point for an angle point, not monumented. _____
	S. 53° 45' W., 6.08 chs.
6.08	Point for an angle point, not monumented. _____

Survey of a Portion of the Present Left Bank of the Snake River,
T. 41 N., R. 116 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>3.70</p>	<p>S. 33° 54' W., 3.70 chs.</p> <p>Intersect the line bet. secs. 7 and 12, on the W. bdy. of the Tp., at a point from which the cor. of secs. 7 and 18 only, T. 41 N., R. 116 W., bears S. 0° 03' W., 8.97 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the field notes of the 1971 dependent resurvey.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area embraced by this survey is situated in the southwest portion of Teton County, approximately 5 miles north of Wilson Wyoming. The terrain is mostly level, with an average elevation of about 6,200 feet above sea level. The soil is sandy loam, cobble stone and gravel, with the vegetation consisting of scattered pine, willows and cottonwoods next to the Snake River, and native grasses.</p> <p>Drainage of the area is easterly into the Snake River, which flows southwesterly through the southeasterly portion of section 6. Section 6 is mostly inhabited, with a residential subdivision in most of the section.</p> <p>Access is provided by Wyoming State Highway No. 390, north from Wilson, Wyoming, roads within the subdivision and by boat on the Snake River.</p>
---------------------------	---

CERTIFICATE OF SURVEY

I, Lynn A. Forbes, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 2nd day of April, 1998, I have dependently resurveyed a portion of the Fourteenth Auxiliary Meridian West, through Township 41 North, between Ranges 116 and 117, portions of the north boundary and subdivisional lines, and a portion of the adjusted meander line of the right bank of the Snake River, subdivided section 6, surveyed the riparian partition lines and a portion of the present right and left banks of the Snake River, Township 41 North, Range 116 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

SEP 28 2001

(Date)

Lynn A. Forbes
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of a portion of the Fourteenth Auxiliary Meridian West, through Township 41 North, between Ranges 116 and 117, portions of the north boundary and subdivisional lines, and a portion of the adjusted meander line of the right bank of the Snake River, subdivided section 6, the survey of the riparian partition lines and a portion of the present right and left banks of the Snake River, Township 41 North, Range 116 West, of the Sixth Principal Meridian, in the State of Wyoming, executed by Lynn A. Forbes, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

SEP 28 2001

(Date)

John P. Lee
(Signature of Authorized Officer)