

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD NOTES**

OF THE

DEPENDENT RESURVEY

OF

THE WEST BOUNDARY,

A PORTION OF THE NORTH BOUNDARY,

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 54 NORTH, RANGE 74 WEST,

OF THE SIXTH PRINCIPAL MERIDIAN,

IN THE STATE OF WYOMING.

**EXECUTED BY**

JOEL T. EBNER

CADASTRAL SURVEYOR

Under Special Instructions dated MAY 4, 2000, approved MAY 4, 2000, which provided for the surveys included under Group Number 675, and assignment instructions dated MAY 4, 2000.

Survey commenced JULY 13, 2000

Survey completed SEPTEMBER 12, 2000

# INDEX DIAGRAM

Township 54 North, Range 74 West

10		9		8							
7	6	59	5	44	4	35	3	27	2	19	1
	59		58		44		35		26		18
6	7	56	8	43	9	34	10	25	11	17	12
	56		55		42		33		25		16
5	18	54	17	41	16	32	15	24	14	15	13
	53		52		41		32		23		15
4	19	50	20	39	21	31	22	22	23	14	24
	50		49		39		30		22		13
3	30	48	29	38	28	29	27	21	26	12	25
	47		46		37		29		20		12
2	31	45	32	36	33	28	34	20	35	11	36

## T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

## CHAINS

The following field notes are those of the dependent resurvey of the west boundary, a portion of the north boundary, and the subdivisional lines, Township 54 North, Range 74 West, of the Sixth Principal Meridian, Wyoming.

Mortimer N. Grant surveyed the exterior boundaries and the subdivisional lines in 1882. Mark M. Kelley resurveyed the north boundary in 1917. Dell Cazier and Dale C. Wilson remonumented the cor. of Tps. 53 and 54 N., Rs. 73 and 74 W., during the dependent resurvey of T. 53 N., R. 73 W., in 1978. Joel T. Ebner dependently resurveyed the east boundary in 1993-94 and south boundary in 1996.

Local surveyors have conducted numerous surveys in the area and acceptance of such surveys are detailed herein.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 675, Wyoming, dated May 4, 2000.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data were thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

The survey was executed with TRIMBLE Model 4700 Global Positioning System (GPS) receivers and by chaining methods. The instruments were maintained in proper adjustment at all times. The directions of all lines refer to the true meridian, based on geodetic north, as determined by GPS observations. GPS control network and supporting data are contained in the official group file.

The geographic position of the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., based on NAD 83(1993) and determined by Global Positioning System is:

Latitude 44° 36' 39.70" N., Longitude 105° 43' 00.25" W.

The mean magnetic declination is 11½ E.

Dependent Resurvey of the West Boundary,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">(Restoring the survey executed by Mortimer N. Grant in 1882)</p> <hr/> <p>Beginning at the cor. of Tps. 53 and 54 N., Rs. 74 and 75 W., monumented with an iron post, 2½ ins. diam., as described in the 1994-95 field notes of the dependent resurvey, T. 53 N., R. 74 W.</p> <p>N. 0° 16' E., bet. secs. 31 and 36.</p> <p>Over rolling and broken terrain.</p> <p>40.30 Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R75W R74W 1/4 S 36   S 31 2000</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located 80 lks. N. of Harper Draw, drains WNW.</p> <p>80.60 The cor. of secs. 25, 30, 31 and 36, remonumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLIAM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R75W R74W S 25   S 30 ----- S 36   S 31 1999 RLS NO. 2608 JOB NO. 99046</p> <p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <hr/>

Dependent Resurvey of the West Boundary,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 0° 04' E., bet. secs. 25 and 30.</p> <p>Over rolling and broken terrain.</p> <p>39.93 The 1/4 sec. cor. of secs. 25 and 30, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. JOB NO R75 R74 1/4 25 30 T54 1999 RLS 2608, with a steel fence post alongside, as filed in the Campbell County Clerk's Office. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R75W R74W 1/4 S 25   S 30 2000</p> <p>Deposit the steel reinforcement rod inside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 04' E., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>39.93 The cor. of secs. 19, 24, 25 and 30, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLIAM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R75W R74W S 24   S 19 ----- S 25   S 30 1999 RLS NO. 2608 JOB NO. 99046</p>
--------	---

Dependent Resurvey of the West Boundary,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>N. 0° 04' E., bet. secs. 19 and 24.</p> <p>Over rolling and broken terrain.</p> <p>39.93 The 1/4 sec. cor. of secs. 19 and 24, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, at cor. of fences extending N. and W., with wooden cor. post, 10 ins. diam., plainly mkd. 1/4 on E. face, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLIAM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R75W R74W S 24   S 19 1999 RLS NO. 2608 JOB NO. 99046</p> <p>This position is accepted as the best available evidence of the original cor. position.</p> <hr/> <p>N. 0° 04' W., beginning new measurement.</p> <p>Over rolling and broken terrain, along fence.</p> <p>36.70 Cor. of fences extending S. and ENE.; leave fence.</p> <p>39.50 Ravine, drains ESE.</p> <p>40.52 The cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 15x8x4 ins., loosely set in a mound of stone, 3 ft. base, 1 ft. high, on top of large sandstone slab, plainly mkd. 3 notches on one edge and 3 notches on the opposite edge, as filed in the Campbell County Clerk's Office.</p> <p>At the corner point</p> <p>Move the sandstone slab and set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
--------	--

Dependent Resurvey of the West Boundary,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<div style="text-align: center;"> <p>T54N R75W R74W S 13   S 18 ----- S 24   S 19 2000</p> </div> <p>Bury the original cor. stone and set a steel fence post alongside the iron post. Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located on N. edge of ravine, in projection of fences from the E. and S.</p> <hr/> <p>N. 0° 21' W., bet. secs. 13 and 18.</p> <p>Over rolling terrain.</p>
0.15	<p>The witness cor. to the cor. of secs. 13, 18, 19 and 24, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with a concrete post, 4 ins. diam., firmly set, projecting 2 ins. above the ground, with brass disk mkd. T54N R74W R75W W.C. 10 FT. NO. S.13 S.18 S.29 S.24 PLAINS ENGR. L.S. 538 1976, with a steel fence post alongside, as filed in the Campbell County Clerk's Office.</p>
40.58	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R75W R74W 1/4 S 13   S 18 2000</p> </div> <p>Set a steel fence post alongside the iron post.</p>
61.50	<p>Box Draw, drains WNW.</p>
81.16	<p>The cor. of secs. 7, 12, 13 and 18, remonumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with a concrete post, 4 ins. diam., firmly set, projecting 9 ins. above the ground, with a scoria stone, 10x7x6 ins., lying loose alongside, plainly mkd. 2 grooves on a face and 4 grooves on opposite face, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with brass disk mkd.</p>

Dependent Resurvey of the West Boundary,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R75W R74W S 12   S 7 <hr style="width: 50%; margin: auto;"/>S 13   S 18 PLAINS ENGR. L.S. 538 1976</p>
	<p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>Bury the original cor. stone alongside the concrete post.</p>
	<p>N. 0° 22' W., bet. secs. 7 and 12.</p> <p>Over rolling terrain.</p>
20.34	<p>Cor. of fences extending N. and E., bears WEST, 14 lks. dist.</p>
40.67	<p>The 1/4 sec. cor. of secs. 7 and 12, at intersection of fences extending N., S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R75W R74W 1/4 S 12   S 7 2000</p> <hr style="width: 50%; margin: auto;"/>
40.78	<p>N. 0° 03' W., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p> <p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the West Boundary,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R75W R74W S 1   S 6 ----- S 12   S 7 2000</p> <p>Cor. is located in fence extending N. and S.</p> <hr/> <p>N. 0° 03' W., bet. secs. 1 and 6.</p> <p>Over rolling terrain, along fence.</p> <p>40.78 The 1/4 sec. cor. of secs. 1 and 6, at intersection of fences extending N., S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R75W R74W 1/4 S 1   S 6 2000</p> <hr/> <p>N. 0° 03' W., beginning new measurement.</p> <p>Over gently rolling terrain, along fence.</p> <p>26.16 Cor. of fences extending S. and NNW.; leave fence.</p> <p>28.30 Spotted Horse Creek, course WNW.</p> <p>40.87 The cor. of Tps. 54 N., Rs. 74 and 75 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R74W S 31 ----- S 1   S 6 T54N R75W R74W 1917</p>

Dependent Resurvey of the West Boundary,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Cor. is located 2 lks. N. of fence extending ESE. and WNW.</p> <hr/> <p>Dependent Resurvey, Portion of the North Boundary, T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>(Restoring the resurvey executed by Mark M. Kelley in 1917)</p> <hr/> <p>From the 1/4 sec. cor. of sec. 4 only, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 ——— S 4 1917</p> <p>S. 88° 51' W., on the N. bdy. of sec. 4.</p> <p>Over rolling terrain.</p> <p>12.61 Cor. No. 4, Tract 83, T. 55 N., R. 74 W., bears SOUTH, 1 lk. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R74W TR 83   4   S 33 ————— S 4 T54N 1920</p> <p>20.105 Point for the W. 1/16 sec. cor. of sec. 4 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R74W ————— W1/16 S 4 T54N R74W 2000</p> <p>Set a steel fence post alongside the iron post.</p> <p>40.21 The cor. of secs. 4 and 5 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, in a collar of stone, with brass cap mkd.</p>
--------	--

Dependent Resurvey, Portion of the North Boundary,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T55N R74W S 33</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S 5   S 4 T54N 1917</p>
	<p>S. 88° 47' W., on the N. bdy. of sec. 5.</p> <p>Over rolling terrain.</p>
12.44	<p>The closing cor. of secs. 32 and 33, identical with Cor. No. 5, Tract 83, T. 55 N., R. 74 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R74W CC</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S 32   S 33</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">T54N 1917</p>
36.44	<p>The 1/4 sec. cor. of sec. 5 only, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">1/4 ——— S 5 1917</p> <hr style="width: 50%; margin: auto;"/>
	<p>S. 88° 46' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
36.02	<p>Cor. No. 8, Tract 83, T. 55 N., R. 74 W., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T55N R74W</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">TR 83   8</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S 5 T54N 1920</p>

Dependent Resurvey, Portion of the North Boundary,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
36.56	<p>The cor. of secs. 5 and 6 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R74W S 32</p> <hr style="width: 50%; margin: auto;"/> <p style="text-align: center;">S 6   S 5 T54N 1917</p> <hr/> <p>N. 89° 30' W., on the N. bdy. of sec. 6.</p> <p>Over rolling terrain.</p>
19.46	<p>The closing cor. of secs. 31 and 32, identical with Cor. No. 9, Tract 83, T. 55 N., R. 74 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of the cor., with brass cap mkd.</p> <p style="text-align: center;">T55N R74W CC</p> <hr style="width: 50%; margin: auto;"/> <p style="text-align: center;">S 31   S 32</p> <hr/> <p style="text-align: center;">S 5 T54N 1917</p>
40.81	<p>The 1/4 sec. cor. of sec. 6 only, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above the ground, with a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;">1/4 ——— S 6 1917</p> <hr/> <p>N. 89° 31' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
39.88	<p>The cor. of Tps. 54 N., Rs. 74 and 75 W.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	(Restoring the survey executed by Mortimer N. Grant in 1882)
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., as described in the 1996 field notes of the dependent resurvey, T. 53 N., R. 74 W.
	N. 0° 06' E., bet. secs. 35 and 36.
	Over nearly level terrain.
0.30	Middle Prong Road, bears ESE. and WNW.
31.80	Wash, drains WNW.
40.29	Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R74W 1/4 S 35   S 36 2000
	Set a steel fence post alongside the iron post.
	Cor. is located 57 lks. E. of fence extending N. and S.
64.00	Horse Creek, course NNE.
80.58	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T54N R74W S 26   S 25 ----- S 35   S 36 2000
	Set a steel fence post alongside the iron post.

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Cor. is located N. 34° E., 3.27 chs. dist., from cor. of fences extending S. and E., and N. 21½° E., 2.90 chs. dist., from intersection of fences extending N., E. and W.</p> <hr/>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1993-94 field notes of the dependent resurvey, T. 54 N., R. 73 W.</p>
	<p>N. 89° 10' W., bet. secs. 25 and 36</p>
	<p>Over rolling terrain.</p>
22.60	<p>U.S. Highway Nos. 14-16, bears SE. and NW.</p>
38.99	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R74W S 25 1/4 ——— S 36 2000</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>Cor. is located 1.34 chs. N. of fence extending E. and W.</p>
60.00	<p>Horse Creek, course N.</p>
77.98	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/>
	<p>N. 0° 24' W., bet. secs. 25 and 26.</p>
	<p>Over rolling terrain.</p>
40.29	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. below the surface of the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T54N R74W 1/4 S 26   S 25 2000</p> <p>Cor. is located 50 lks. E. of fence extending N. and S.</p> <p>80.58 The cor. of secs. 23, 24, 25 and 26, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, in a collar of stone, at cor. of fences extending S. and W., with brass cap mkd.</p> <p style="text-align: center;">T54N R74W S 23   S 24 ----- S 26   S 25 LS 538 1975</p> <p>This position is accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1993-94 field notes of the dependent resurvey, T. 54 N., R. 73 W.</p> <p>N. 89° 09' W., bet. secs. 24 and 25.</p> <p>Over rolling terrain, along fence.</p> <p>36.20 Ravine, drains SSE.</p> <p>39.15 The 1/4 sec. cor. of secs. 24 and 25, at cor. of fences extending N. and E. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W S 24 1/4 ——— S 25 2000</p> <hr style="width: 30%; margin: auto;"/>
--------	--

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 89° 12' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>34.00 U.S. Highway Nos. 14-16, bears SSE. and NNW.</p> <p>39.19 The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 1° 10' W., bet. secs. 23 and 24.</p> <p>Over rolling terrain.</p> <p>29.60 U.S. Highway Nos. 14-16, bears SSE. and NNW.</p> <p>40.24 Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 23   S 24 2000</p> <p>Cor. is located 1.10 chs. E. of fence extending SSE. and NNW.</p> <p>80.48 The cor. of secs. 13, 14, 23 and 24, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W S 14   S 13 ----- S 23   S 24 LS 538 1975</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>From the true point for the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., witnessed by an iron post, 2½ ins. diam., as described in the 1993-94 field notes of the dependent resurvey, T. 54 N., R. 73 W.</p>
--------	--

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 89° 32' W., bet. secs. 13 and 24.</p> <p>Over nearly level terrain.</p> <p>39.91 Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R74W S 13 1/4 ——— S 24 2000</p> </div> <p>79.82 The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0° 10' W., bet. secs. 13 and 14.</p> <p>Over gently rolling terrain.</p> <p>4.99 Cor. of fences extending N. and W.; thence along fence.</p> <p>20.12 Intersection of fences extending E., S. and W.; leave fence.</p> <p>40.235 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R74W 1/4 S 14   S 13 2000</p> </div> <p>Cor. is located 1.45 chs. W. of fence extending N. and S.</p> <p>79.71 The witness cor. to the cor. of secs. 11, 12, 13 and 14, established by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, monumented with a concrete post, 4 ins. diam., broken off flush with the ground, top portion, 17 ins. long, lying loose alongside, with brass disk mkd. T54N R74W W.C. 50 FT. SO. S.11 S.12 S.13 S.14 PLAINS ENGR. L.S. 538 1976, as filed in the Campbell County Clerk's Office.</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
80.47	<p>The cor. of secs. 11, 12, 13 and 14, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, as filed in the Campbell County Clerk's Office, with a steel reinforcement rod, 20 ins. long, 5/8 in. diam., firmly set, 7 ins. below the surface of the ground, in a road, scoria surfaced, extending E. and W., with aluminum cap illegibly mkd. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. below the surface of the ground, with brass cap mkd.</p> <table border="1" data-bbox="860 745 1015 913" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T54N R74W</td> </tr> <tr> <td style="text-align: center;">S 11</td> <td style="text-align: center;">S 12</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 14</td> <td style="text-align: center;">S 13</td> </tr> <tr> <td colspan="2" style="text-align: center;">2000</td> </tr> </table> <p>Deposit the steel reinforcement rod inside the iron post.</p> <p>Cor. is located 38 lks. S. of fence extending E. and W.</p> <p>From this point, a property corner, established by Robert L. St. Claire, Wyoming Registered Land Surveyor No. 584, bears N. 48° 05' E., 57 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, at intersection of fences extending N., E. and W., with yellow plastic cap mkd. EAGLE 584.</p>	T54N R74W		S 11	S 12	-----		S 14	S 13	2000	
T54N R74W											
S 11	S 12										
-----											
S 14	S 13										
2000											
39.895	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1993-94 field notes of the dependent resurvey, T. 54 N., R. 73 W.</p> <p>S. 89° 47' W., bet. secs. 12 and 13.</p> <p>Over gently rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T54N R74W S 12 1/4 ——— S 13 2000</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located. S. <math>61\frac{1}{4}^\circ</math> W., 1.39 chs. dist., from intersection of fences extending E., S. and W.</p> <p>79.79 The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. <math>0^\circ 48'</math> W., bet. secs. 11 and 12.</p> <p>Over gently rolling terrain.</p> <p>40.75 The 1/4 sec. cor. of secs. 11 and 12, monumented by Don A. Davis, Wyoming Registered Land Surveyor No. 4824, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 1 in. above the ground, in a collar of stone, in fence extending N. and S., with aluminum cap mkd. WLC 1/4 11 12 LS 4824 1998, with a sandstone, 16x11x4 ins., firmly set 14 ins. in the ground alongside, no mks. visible, and with a sandstone, 20x16x3 ins., firmly set 14 ins. in the ground alongside, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 11   S 12 2000</p> <p>Deposit the steel reinforcement rod inside and bury the unmkd. stones alongside the iron post.</p> <hr/> <p>N. <math>1^\circ 23'</math> W., beginning new measurement.</p> <p>Over gently rolling terrain, along fence.</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS									
39.97	<p>The cor. of secs. 1, 2, 11 and 12, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, at intersection of fences extending N., E. and S., with brass cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T54N R74W</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S 11</td><td>S 12</td></tr> </table> <p>PLS 538 1988</p> </div> <p>This position is accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the 1993 field notes of the dependent resurvey, T. 54 N., R. 73 W.</p> <p>N. 89° 33' W., bet. secs. 1 and 12.</p> <p>Over gently rolling terrain.</p>	T54N R74W		S 2	S 1	— —		S 11	S 12
T54N R74W									
S 2	S 1								
— —									
S 11	S 12								
8.80	Hay Creek, course SE.								
11.60	Hay Creek, course NE.								
13.10	Hay Creek, course SE.								
41.285	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T54N R74W</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 12</td><td></td></tr> </table> <p>2000</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located. S. 65½° E., 93 lks. dist., from intersection of fences extending E., S. and W.</p>	T54N R74W		S 1		1/4	—	S 12	
T54N R74W									
S 1									
1/4	—								
S 12									
82.57	The cor. of secs. 1, 2, 11 and 12.								

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 0° 20' W., bet. secs. 1 and 2.</p> <p>Over gently rolling terrain.</p> <p>40.12 The 1/4 sec. cor. of secs. 1 and 2, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 2   S 1 PLS 538 1991</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located. N. 14¾° E., 73 lks. dist., from intersection of fences extending ENE., S. and W., and 33 lks. W. of scoria surfaced road, extending SE. and NW, and 29 lks. S. of same road.</p> <hr/> <p>N. 0° 20' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>4.80 Recluse Road, paved surface, bears NNE. and SSW., in curve.</p> <p>39.70 The cor. of secs. 1 and 2 only, identical with Cor. No. 4, Tract 37, and Cor. No. 2, Tract 38, T. 55 N., R. 74 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R74W TR 38   TR 37 2   4 ----- S 2   S 1 T54N 1917</p> <p>Cor. is located 64 lks. W. of Recluse Road extending N. and S.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., as described in the 1996 field notes of the dependent resurvey, T. 53 N., R. 74 W.</p>
--------	--

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 1° 26' E., bet. secs. 34 and 35.</p> <p>Over gently rolling terrain.</p> <p>14.10 Middle Prong Road, gravel surfaced, bears ESE. and WNW.</p> <p>37.20 Creek, course WNW.</p> <p>38.45 Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R74W 1/4 S 34   S 35 2000</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>45.90 Horse Creek, course ENE.</p> <p>48.70 Horse Creek, course NW.</p> <p>50.60 Horse Creek, course ENE.</p> <p>76.90 The cor. of secs. 26, 27, 34 and 35, remonumented by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, with a steel fence post alongside, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R74W S 27   S 26 ----- S 34   S 35 1968 LS 450</p> </div> <p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 87° 23' W., bet. secs. 26 and 35.</p> <p>Over gently rolling terrain.</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.205	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W S 26 1/4 ——— S 35 2000</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 30 lks. E. of Dry Gulch, drains SSE.</p>
78.41	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 1° 48' W., bet. secs. 26 and 27.</p> <p>Over nearly level terrain.</p>
1.10	<p>Wash, drains ENE.</p>
4.00	<p>Dry Gulch, drains ESE.</p>
40.22	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 27   S 26 2000</p>
80.44	<p>The cor. of secs. 22, 23, 26 and 27, remonumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a lava stone, 12x12x8 ins., lying loose alongside, plainly mkd. 2 grooves on a face and 2 notches on an edge, as filed in the Campbell County Clerk's Office, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<div style="text-align: center;"> <p>T54N R74W 22   23 ----- 27   26 LS 538 1975</p> </div> <p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 87° 20' W., bet. secs. 23 and 26.</p> <p>Over rolling and broken terrain.</p> <p>40.185 Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R74W S 23 1/4 ——— S 26 2000</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on steep E. facing slope, 21 lks. N. of fence extending irregularly E. and W.</p> <p>From this point, U.S. Coast and Geodetic Survey Triangulation Station SLIDE, bears N. 8° 12' W., 23.00 chs. dist., monumented with a concrete post, 5 ins. diam., firmly set, projecting 6 ins. above the ground, with standard brass disk on top mkd. SLIDE 1949.</p> <p>41.20 Ridge, bears SSE. and NNW.</p> <p>80.37 The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 1° 26' W., bet. secs. 22 and 23.</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>40.275</p> <p>80.55</p> <p>8.90</p> <p>40.37</p>	<p>Over rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 22   S 23 2000</p> <p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 14, 15, 22 and 23, remonumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, in fence extending E. and W., with a sandstone, 21x19x3 ins., firmly set, projecting 8 ins. above the ground alongside, plainly mkd. 2 grooves on W. face, no other mks. visible, as filed in the Campbell County Clerk's Office, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W 15   14 ----- 22   23 LS 538 1975</p> <p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>Bury the original cor. stone alongside the iron post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 87° 23' W., bet. secs. 14 and 23.</p> <p>Over gently rolling terrain.</p> <p>U.S. Highway Nos. 14-16, bears SSE. and NNW.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p>
---	---

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. below the surface of the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R74W S 14 1/4 ——— S 23 2000</p>
59.56	Intersection of fences extending N., S. and W., bears SOUTH, 32 lks. dist.
80.74	The cor. of secs. 14, 15, 22 and 23.
	N. 0° 23' E., bet. secs. 14 and 15.
	Over rolling terrain.
1.00	Ridge, bears E. and W.
20.33	Point for the S. 1/16 sec. cor. of secs. 14 and 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R74W S 1/16 S 15   S 14 2000</p>
	Set a steel fence post alongside the iron post.
40.66	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R74W 1/4 S 15   S 14 2000</p>
	Cor. is located S. 21½° W., 2.79 chs. dist., from cor. of fences extending N. and E.

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
81.32	<p>The cor. of secs. 10, 11, 14 and 15, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T54N R74W</td> </tr> <tr> <td style="text-align: center;">10</td> <td style="text-align: center;">  11</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">15</td> <td style="text-align: center;">  14</td> </tr> <tr> <td colspan="2" style="text-align: center;">LS 538 1975</td> </tr> </table>	T54N R74W		10	11	-----		15	14	LS 538 1975	
T54N R74W											
10	11										
-----											
15	14										
LS 538 1975											
	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p>										
	<p>Cor. is located S. 18¼° W., 2.52 chs. dist., from intersection of fences extending E., S. and W.</p>										
	<hr/>										
	<p>From the cor. of secs. 11, 12, 13 and 14.</p>										
	<p>S. 87° 58' W., bet. secs. 11 and 14.</p>										
	<p>Over gently rolling terrain.</p>										
23.30	<p>U.S. Highway Nos. 14-16, bears N. and S.</p>										
39.955	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original cor.</p>										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T54N R74W</td> </tr> <tr> <td style="text-align: center;">S 11</td> <td style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 14</td> <td style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">2000</td> </tr> </table>	T54N R74W		S 11	-----	1/4	-----	S 14	-----	2000	
T54N R74W											
S 11	-----										
1/4	-----										
S 14	-----										
2000											
	<p>Set a steel fence post alongside the iron post.</p>										
	<p>Cor. is located 53 lks. S. of driveway, extending E. and W. and 1.39 chs. S. of fence extending E. and W.</p>										
79.91	<p>The cor. of secs. 10, 11, 14 and 15.</p>										
	<hr/>										
	<p>N. 0° 31' E., bet. secs. 10 and 11.</p>										
	<p>Over rolling terrain.</p>										

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
2.40	Wash, drains ESE.
42.30	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented by person(s) unknown, with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, at cor. of abandoned fence extending N., other directions indeterminate, with brass cap mkd.</p> <p style="text-align: center;">WLC T54N R74W 1/4 S 10   S 11 LS</p> <p>The firm of Worthington, Lenhart and Carpenter Inc. was contacted regarding this corner but was unable to provide any information about the monument. This position is accepted as the best available evidence of the original cor. position.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 01' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
37.20	Fence, bears E. and W.
40.11	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W S 3   S 2 <hr style="width: 20%; margin: 0 auto;"/> S 10   S 11 2000</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89° 10' W., bet. secs. 2 and 11.</p> <p>Over gently rolling terrain.</p>
39.32	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. below the surface of the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R74W S 2 1/4 ——— S 11 2000</p>
43.60	U.S. Highway Nos. 14-16, bears SSE. and NNW.
78.64	The cor. of secs. 2, 3, 10 and 11.
	N. 2° 05' W., bet. secs. 2 and 3.
	Over nearly level terrain, across cultivated fields.
36.90	U.S. Highway Nos. 14-16, bears SE. and NW.
40.13	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. below the surface of the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R74W 1/4 S 3   S 2 2000</p>
80.13	The cor. of secs. 2 and 3 only, identical with Cor. No. 2, Tract 40, T. 55 N., R. 74 W., monumented with an iron post, 2 ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd.
	<p style="text-align: center;">T55N R74W S 34 TR 40   TR 39 2   ——— S 3   S 2 T54N 1917</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., as described in the 1996 field notes of the dependent resurvey, T. 53 N., R. 74 W.</p>
	<p>N. 0° 35' E., bet. secs. 33 and 34.</p>
	<p>Over gently rolling terrain.</p>
25.20	<p>Middle Prong Road, bears ESE. and WNW.</p>
38.85	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLIAM H. SMITH &amp; ASSOC. P.C. and mkd.</p>
	<p style="text-align: center;">T54N R74W 1/4 S 33   S 34 1999 RLS NO. 2608 JOB NO. 99046</p>
	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p>
	<p style="text-align: center;">_____</p> <p>N. 0° 35' E., beginning new measurement.</p>
	<p>Over rolling terrain.</p>
12.00	<p>Horse Creek, course ESE.</p>
38.85	<p>The cor. of secs. 27, 28, 33 and 34, remonumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 14 ins. above the ground, in a collar of stone, at cor. of fences extending N. and SE., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLIAM H. SMITH &amp; ASSOC. P.C. and mkd.</p>
	<p style="text-align: center;">T54N R74W 28   27 ----- 33   34 1999 RLS NO. 2608 JOB NO. 99046</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89° 03' W., bet. secs. 27 and 34.</p> <p>Over nearly level terrain.</p> <p>40.88 Point for the 1/4 sec. cor. of secs. 27 and 34, determined latitudinally by proportionate measurement and longitudinally by a fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R74W S 27 1/4 ——— S 34 2000</p> <hr/> </div> <p>S. 89° 03' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>40.50 The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0° 35' W., bet. secs. 27 and 28.</p> <p>Over rolling terrain.</p> <p>40.42 The 1/4 sec. cor. of secs. 27 and 28, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <div style="text-align: center;"> <p>T54N R74W 1/4 S 28   S 27 1999 RLS NO. 2608 JOB NO. 99046</p> </div>
--------	---



Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>S. 89° 20' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>39.82 The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>N. 1° 23' W., bet. secs. 21 and 22.</p> <p>Over rolling terrain.</p> <p>40.42 The 1/4 sec. cor. of secs. 21 and 22, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post alongside, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 21   S 22 2000 RLS NO. 2608 JOB NO. 9946</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>N. 1° 23' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>40.43 The cor. of secs. 15, 16, 21 and 22, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R74W S 16   S 15 <hr/>S 21   S 22 2000 RLS NO. 2608 JOB NO. 9946</p>
--------	--

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p>
	<p>S. 89° 33' W., bet. secs. 15 and 22.</p>
	<p>Over broken terrain.</p>
11.23	<p>Cor. of fences extending E. and NW., bears SOUTH, 28 lks. dist.</p>
39.78	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post alongside, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p>
	<p style="text-align: center;">T54N R74W S 15 1/4 ——— S 22 2000 RLS NO. 2608 JOB NO. 9946</p>
	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/>
	<p>S. 89° 33' W., beginning new measurement.</p>
	<p>Over broken terrain.</p>
39.78	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/>
	<p>N. 0° 08' E., bet. secs. 15 and 16.</p>
	<p>Over rolling and broken terrain.</p>
2.00	<p>Wash, drains WNW.</p>
30.10	<p>Ravine, drains NW.</p>
40.415	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 16   S 15 2000</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 50 lks. W. of fence extending N. and S.</p>
80.83	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W S 9   S 10 ----- S 16   S 15 2000</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 52 lks. W. of fence extending N. and S.</p>
39.96	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89° 12' W., bet. secs. 10 and 15.</p> <p>Over rolling and broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W S 10 1/4 ——— S 15 2000</p> <p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Cor. is located S. $7\frac{3}{4}^{\circ}$ W., 2.38 chs. dist., from intersection of fences extending N., E. and W.
79.92	The cor. of secs. 9, 10, 15 and 16.
	N. $0^{\circ} 05'$ E., bet. secs. 9 and 10.
	Over broken terrain.
20.205	Point for the S. $1/16$ sec. cor. of secs. 9 and 10.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R74W S <math>1/16</math> S 9   S 10 2000</p>
	Set a steel fence post alongside the iron post.
	Cor. is located on steep N. facing slope, 20 lks. S. of wash, drains. W.
40.41	Point for the $1/4$ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T54N R74W <math>1/4</math> S 9   S 10 2000</p>
	Set a steel fence post alongside the iron post.
41.40	Ravine, drains W.
80.82	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<div style="text-align: center;"> <table border="0"> <tr><td>T54N</td><td>R74W</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 9</td><td>S 10</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div>	T54N	R74W	S 4	S 3	<hr/>		S 9	S 10	2000	
T54N	R74W										
S 4	S 3										
<hr/>											
S 9	S 10										
2000											
	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 63 lks. E. of fence extending irregularly N. and S.</p> <hr/>										
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 88° 04' W., bet. secs. 3 and 10.</p> <p>Over rolling and broken terrain.</p>										
39.745	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<div style="text-align: center;"> <table border="0"> <tr><td>T54N</td><td>R74W</td></tr> <tr><td>S 3</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 10</td><td></td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T54N	R74W	S 3		1/4	—	S 10		2000	
T54N	R74W										
S 3											
1/4	—										
S 10											
2000											
79.49	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/>										
	<p>N. 2° 47' W., bet. secs. 3 and 4.</p> <p>Over rolling and broken terrain.</p>										
40.46	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>										
	<div style="text-align: center;"> <table border="0"> <tr><td>T54N</td><td>R74W</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div>	T54N	R74W	1/4		S 4	S 3	2000			
T54N	R74W										
1/4											
S 4	S 3										
2000											

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set a steel fence post alongside the iron post.</p> <p>81.25 The cor. of secs. 3 and 4 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T55N R74W S 34</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S 4   S 3 T54N 1917</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., as described in the 1996 field notes of the dependent resurvey, T. 53 N., R. 74 W.</p> <p>N. 0° 50' E., bet. secs. 32 and 33.</p> <p>Over rolling terrain.</p> <p>11.50 Middle Prong Road, bears ENE. and WSW.</p> <p>39.46 The 1/4 sec. cor. of secs. 32 and 33, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 32   S 33 1999 RLS NO. 2608 JOB NO. 99046</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 50' E., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>17.00 Horse Creek, course E.</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS																	
39.46	<p>The cor. of secs. 28, 29, 32 and 33, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLIAM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T54N R74W</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center;">29</td> <td style="text-align: center;">28</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center;">32</td> <td style="text-align: center;">33</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> <tr> <td colspan="2" style="text-align: center;">RLS NO. 2608</td> </tr> <tr> <td colspan="2" style="text-align: center;">JOB NO. 99046</td> </tr> </table> <p>This position is accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89° 27' W., bet. secs. 28 and 33.</p> <p>Over rolling terrain.</p>	T54N R74W		29	28	32	33	1999		RLS NO. 2608		JOB NO. 99046					
T54N R74W																	
29	28																
32	33																
1999																	
RLS NO. 2608																	
JOB NO. 99046																	
40.07	<p>The 1/4 sec. cor. of secs. 28 and 33, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, in a collar of stone, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLIAM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T54N R74W</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 28</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 33</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> <tr> <td colspan="2" style="text-align: center;">RLS NO. 2608</td> </tr> <tr> <td colspan="2" style="text-align: center;">JOB NO. 99046</td> </tr> </table> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>S. 89° 26' W., beginning new measurement.</p> <p>Over rolling terrain.</p>	T54N R74W		1/4		S 28		-----		S 33		1999		RLS NO. 2608		JOB NO. 99046	
T54N R74W																	
1/4																	
S 28																	
-----																	
S 33																	
1999																	
RLS NO. 2608																	
JOB NO. 99046																	

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.06	The cor. of secs. 28, 29, 32 and 33.
	<hr/> N. 0° 24' W., bet. secs. 28 and 29.  Over rolling and broken terrain.
39.65	The 1/4 sec. cor. of secs. 28 and 29, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH & ASSOC. P.C. and mkd.
	<div style="text-align: center;">             T54N R74W              1/4              S 29   S 28              RLS NO. 2608              JOB NO. 99046           </div>
	This position is accepted as a careful and faithful reestablishment of the original cor. position.
	<hr/> N. 0° 24' W., beginning new measurement.
	Over rolling and broken terrain.
39.65	The cor. of secs. 20, 21, 28 and 29, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH & ASSOC. P.C. and mkd.
	<div style="text-align: center;">             T54N R74W              20   21  <hr style="width: 50%; margin: 0 auto;"/>             29   28              1999              RLS NO. 2608              JOB NO. 99046           </div>
	This position is accepted as a careful and faithful reestablishment of the original cor. position.
	<hr/> From the cor. of secs. 21, 22, 27 and 28.

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>S. 88° 21' W., bet. secs. 21 and 28.</p> <p>Over gently rolling terrain.</p> <p>39.94 The 1/4 sec. cor. of secs. 21 and 28, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground in cultivated field, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 21 ----- S 28 1999 RLS NO. 2608 JOB NO. 99046</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 88° 20' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>39.94 The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 1° 20' W., bet. secs. 20 and 21.</p> <p>Over rolling and broken terrain.</p> <p>39.66 The 1/4 sec. cor. of secs. 20 and 21, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 20   S 21 RLS NO. 2608 JOB NO. 99046</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located on ridge, bears SE. and NW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 20' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>18.80 Rose Creek, course W.</p> <p>19.83 Point for the N. 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">       T54N R74W        N1/16        S 20   S 21        2000     </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on steep S. facing slope.</p> <p>39.66 The cor. of secs. 16, 17, 20 and 21, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set flush with the surface of the ground, at cor. of abandoned fences extending N. and SE., with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd. T54N R74W S16 S17 S20 S21 PLS 538 1998, as filed in the Campbell County Clerk's Office. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">       T54N R74W        S 17   S 16  <hr style="width: 20%; margin: 0 auto;"/>       S 20   S 21        2000     </div> <p>Deposit the steel reinforcement rod inside the iron post.</p> <hr style="width: 80%; margin: 10px auto;"/>
--------	---

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 87° 15' W., bet. secs. 16 and 21.</p> <p>Over broken terrain.</p>
39.90	<p>The 1/4 sec. cor. of secs. 16 and 21, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with a steel fence post alongside, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R74W S 16 1/4 ——— S 21 2000 RLS NO. 2608 JOB NO. 9946</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>S. 87° 14' W., beginning new measurement.</p> <p>Over broken terrain.</p>
39.90	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0° 11' E., bet. secs. 16 and 17.</p> <p>Over broken terrain.</p>
36.30	<p>Spotted Horse Creek, course NW.</p>
40.825	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 17   S 16 2000</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
	Set a steel fence post alongside the iron post.										
81.65	<p>The cor. of secs. 8, 9, 16 and 17, monumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd. T54N R74W S8 S9 S16 S17 PLS 538 1998, with a steel fence post alongside, as filed in the Campbell County Clerk's Office. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p>										
	At the corner point										
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T54N R74W</td> </tr> <tr> <td style="text-align: center;">S 8</td> <td style="text-align: center;">S 9</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 17</td> <td style="text-align: center;">S 16</td> </tr> <tr> <td colspan="2" style="text-align: center;">2000</td> </tr> </table>	T54N R74W		S 8	S 9	-----		S 17	S 16	2000	
T54N R74W											
S 8	S 9										
-----											
S 17	S 16										
2000											
	Deposit the steel reinforcement rod inside the iron post.										
	From the cor. of secs. 9, 10, 15 and 16.										
	S. 87° 50' W., bet. secs. 9 and 16.										
	Over gently rolling terrain.										
19.915	Point for the E. 1/16 sec. cor. of secs. 9 and 16.										
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T54N R74W</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 9</td> </tr> <tr> <td style="text-align: center;">E1/16</td> <td style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 16</td> </tr> <tr> <td colspan="2" style="text-align: center;">2000</td> </tr> </table>	T54N R74W		S 9		E1/16	-----	S 16		2000	
T54N R74W											
S 9											
E1/16	-----										
S 16											
2000											
	Set a steel fence post alongside the iron post.										
37.40	T D Southwest Draw, drains NNW.										
39.83	Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original cor.										

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R74W S 9 1/4 ——— S 16 2000</p>
	Set a steel fence post alongside the iron post.
79.66	The cor. of secs. 8, 9, 16 and 17.
	N. 0° 28' E., bet. secs. 8 and 9.
	Over rolling terrain.
33.30	T D Southwest Draw, drains WNW.
40.82	Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T54N R74W 1/4 S 8   S 9 2000</p>
	Set a steel fence post alongside the iron post.
81.64	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T54N R74W S 5   S 4 ————— S 8   S 9 2000</p>
	Set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>From this point, a position established by Lawrence C. Kay, Wyoming Registered Land Surveyor No. 489, bears N. 6° 20' E., 9 lks. dist., monumented with a steel reinforcement rod, 30 ins. long, 3/4 in. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. UINTAH ENG &amp; LS T54N R74W S4 S5 S8 S9 1998 WYO 489, with a steel fence post alongside, as filed in the Campbell County Clerk's Office. This position was established by proportionate measurement using an erroneous distance and is not accepted as a careful and faithful reestablishment of the original cor. position. Mr. Kay granted permission to move his monument to the correct proportionate position, where it was deposited alongside the iron post.</p>
39.54	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 88° 24' W., bet. secs. 4 and 9.</p> <p>Over rolling and broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R74W</p> <p>S 4</p> <p>1/4 ———</p> <p>S 9</p> <p>2000</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 1 ch. N. of draw, drains. W.</p>
79.08	<p>The cor. of secs. 4, 5, 8 and 9.</p>
20.45	<p>N. 3° 44' W., bet. secs. 4 and 5.</p> <p>Over rolling terrain.</p> <p>Point for the S. 1/16 sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T54N R74W S1/16 S 5   S 4 2000</p> <p>Set a steel fence post alongside the iron post.</p> <p>40.90 Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 5   S 4 2000</p> <p>Set a steel fence post alongside the iron post.</p> <p>81.88 The cor. of secs. 4 and 5 only, on the N. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., as described in the 1996 field notes of the dependent resurvey, T. 53 N., R. 74 W.</p> <p>N. 0° 36' E., bet. secs. 31 and 32.</p> <p>Over rolling and broken terrain.</p> <p>39.90 Ravine, drains SE.</p> <p>39.95 The 1/4 sec. cor. of secs. 31 and 32, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 31   S 32 RLS NO. 2608 JOB NO. 99046</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p>
--------	--

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS															
	Cor. is located 49 lks. N. of fence extending E. and W.														
	<hr/> N. 0° 36' E., beginning new measurement.														
	Over rolling and broken terrain.														
8.60	Ridge, bears E. and W.														
39.95	The cor. of secs. 29, 30, 31 and 32, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, in a collar of stone, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH & ASSOC. P.C. and mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T54N R74W</td></tr> <tr><td>S 30</td><td>  S 29</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 31</td><td>  S 32</td></tr> <tr><td colspan="2">1999</td></tr> <tr><td colspan="2">RLS NO. 2608</td></tr> <tr><td colspan="2">JOB NO. 99046</td></tr> </table>	T54N R74W		S 30	S 29	<hr/>		S 31	S 32	1999		RLS NO. 2608		JOB NO. 99046	
T54N R74W															
S 30	S 29														
<hr/>															
S 31	S 32														
1999															
RLS NO. 2608															
JOB NO. 99046															
	This position is accepted as a careful and faithful reestablishment of the original cor. position.														
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.														
	Cor. is located 85 lks. S. of fence extending irregularly ESE. and WNW.														
	<hr/> From the cor. of secs. 28, 29, 32 and 33.														
	S. 89° 27' W., bet. secs. 29 and 32.														
	Over rolling terrain.														
20.27	Point for the E. 1/16 sec. cor. of secs. 29 and 32.														
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T54N R74W</td></tr> <tr><td colspan="2">S 29</td></tr> <tr><td>E1/16</td><td>—</td></tr> <tr><td colspan="2">S 32</td></tr> <tr><td colspan="2">2000</td></tr> </table>	T54N R74W		S 29		E1/16	—	S 32		2000					
T54N R74W															
S 29															
E1/16	—														
S 32															
2000															

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>40.54</p> <p>3.30</p> <p>40.53</p> <p>20.22</p>	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 1.21 chs. S. of fence extending E. and W.</p> <p>The 1/4 sec. cor. of secs. 29 and 32, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R74W S 29 1/4 ——— S 32 RLS NO. 2608 JOB NO. 99046</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located 1.50 chs. S. of fence extending E. and W.</p> <p style="text-align: center;">—————</p> <p>S. 89° 26' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>Wash, drains S.</p> <p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>S. 89° 15' W., bet. secs. 30 and 31.</p> <p>Over rolling and broken terrain.</p> <p>Point for the E. 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W S 30 E1/16 ——— S 31 2000</p> <p>Set a steel fence post alongside the iron post.</p>
--	---

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

<p>CHAINS</p> <p>40.44</p> <p>38.38</p> <p>39.95</p>	<p>Cor. is located S. <math>34\frac{3}{4}^{\circ}</math> W., 2.57 chs. dist., from cor. of fences extending E. and S.</p> <p>The 1/4 sec. cor. of secs. 30 and 31, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 2 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R74W S 30 1/4 ——— S 31 1999 RLS NO. 2608 JOB NO. 99046</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr style="width: 20%; margin: auto;"/> <p>S. <math>89^{\circ} 14'</math> W., beginning new measurement.</p> <p>Over broken terrain.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. <math>0^{\circ} 29'</math> E., bet. secs. 29 and 30.</p> <p>Over rolling and broken terrain.</p> <p>The 1/4 sec. cor. of secs. 29 and 30, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with a steel reinforcement rod, 24 ins. long, <math>\frac{5}{8}</math> in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. JOB NO 1/4 29 30 T54 R74 1999 RLS 2608, with a steel fence post alongside, as filed in the Campbell County Clerk's Office. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
--	---

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T54N R74W 1/4 S 30   S 29 2000</p> <p>Deposit the steel reinforcement rod inside the iron post.</p> <hr/> <p>N. 0° 29' E., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>38.00 Ridge, bears SE. and NW.</p> <p>39.95 The cor. of secs. 19, 20, 29 and 30, remonumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, in fence extending N. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <p style="text-align: center;">T54N R74W S 19   S 20 ----- S 30   S 29 1999 RLS NO. 2608 JOB NO. 99046</p> <p>This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>Cor. is located 42 lks. N. of cor. of fences extending N. and SE.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89° 52' W., bet. secs. 20 and 29.</p> <p>Over rolling and broken terrain.</p> <p>39.91 The 1/4 sec. cor. of secs. 20 and 29, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p>
--------	--

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T54N R74W S 20 1/4 ——— S 29 1999 RLS NO. 260 JOB NO. 990468</p>
39.91	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>S. 89° 51' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>The cor. of secs. 19, 20, 29 and 30.</p>
1.50	<p>S. 89° 13' W., bet. secs. 19 and 30.</p> <p>Over rolling and broken terrain.</p> <p>Ridge, bears SE. and NW.</p>
40.48	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p>
	<p style="text-align: center;">T54N R74W S 19 1/4 ——— S 30 1999 RLS NO. 2608 JOB NO. 99046</p>
2.00	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>S. 89° 13' W., beginning new measurement.</p> <p>Over rolling and broken terrain.</p> <p>Box Draw, drains NNW.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
38.91	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.
	<hr/> From the cor. of secs. 19, 20, 29 and 30. N. 1° 10' W., bet. secs. 19 and 20. Over rolling and broken terrain.
39.79	The 1/4 sec. cor. of secs. 19 and 20, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH & ASSOC. P.C. and mkd.
	<div style="text-align: center;">             T54N R74W              1/4              S 19   20              1999              RLS NO. 2608              JOB NO. 99046           </div>
	This position is accepted as a careful and faithful reestablishment of the original cor. position.
	Cor. is located 56 lks. W. of fence extending N. and S.
	<hr/> N. 1° 10' W., beginning new measurement. Over rolling and broken terrain.
6.40	Washout Draw, drains WNW.
19.895	Point for the N. 1/16 sec. cor. of secs. 19 and 20.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">             T54N R74W              N1/16              S 19   S 20              2000           </div>
	Set a steel fence post alongside the iron post.

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
39.79	<p>The cor. of secs. 17, 18, 19 and 20, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, in fence extending E. and W., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T54N</td> <td>R74W</td> </tr> <tr> <td>18</td> <td>17</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>19</td> <td>20</td> </tr> </table> <p style="text-align: center;">RLS NO. 2608 JOB NO. 99046</p> <p>This position is accepted as a careful and faithful determination of the original cor. position.</p> <p>Cor. is located 50 lks. S. of small ravine, drains E.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89° 56' W., bet. secs. 17 and 20.</p> <p>Over rolling and broken terrain.</p>	T54N	R74W	18	17			19	20		
T54N	R74W										
18	17										
19	20										
32.80	Rose Creek, course WNW.										
39.79	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap inscribed WILLIAM H. SMITH AND ASSOC. P.C. SURVEYING CONSULTANTS and mkd. T54N R74W 1/4 17 20 1999 RLS 2608 JOB NO. 99046, as filed in the Campbell County Clerk's Office. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T54N</td> <td>R74W</td> </tr> <tr> <td></td> <td>S 17</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 20</td> </tr> <tr> <td></td> <td>2000</td> </tr> </table>	T54N	R74W		S 17	1/4	—		S 20		2000
T54N	R74W										
	S 17										
1/4	—										
	S 20										
	2000										

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Deposit the steel reinforcement rod inside and set a steel fence post alongside the iron post.</p> <hr/>
	<p>N. 89° 57' W., beginning new measurement.</p>
	<p>Over rolling and broken terrain.</p>
22.67	<p>Cor. of fences extending W. and irregularly ENE., bears NORTH, 16 lks. dist.</p>
39.79	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/>
	<p>S. 89° 51' W., bet. secs. 18 and 19.</p>
	<p>Over rolling and broken terrain.</p>
19.81	<p>Point for the E. 1/16 sec. cor. of secs. 18 and 19.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R74W S 18 E1/16 ——— S 19 2000</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p>Cor. is located 74 lks. S. of fence extending irregularly E. and W.</p>
39.62	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented by John I.</p>
	<p>Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, in a collar of stone, with a steel fence post alongside, as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p>
	<p style="text-align: center;">T54N R74W 18 1/4 ——— 19 1999 RLS NO. 2608 JOB NO. 99046</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p>
	<p>Cor. is located 33 lks. N. of fence extending E. and W.</p> <hr/>
	<p>S. 89° 50' W., beginning new measurement.</p>
	<p>Over rolling terrain.</p>
5.60	<p>Washout Draw, drains WNW.</p>
20.10	<p>Box Draw, drains N.</p>
38.12	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.</p> <hr/>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p>
	<p>N. 0° 48' E., bet. secs. 17 and 18.</p>
	<p>Over rolling and broken terrain.</p>
39.00	<p>Rose Creek, course NNW.</p>
40.64	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap inscribed WILLIAM H. SMITH AND ASSOC. P.C. SURVEYING CONSULTANTS and mkd. T54N R74W 1/4 S17 S18 1999 RLS 2608 JOB NO. 99046, with a steel fence post alongside, as filed in the Campbell County Clerk's Office. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T54N R74W</p>
	<p style="text-align: center;">1/4</p>
	<p style="text-align: center;">S 18   S 17</p>
	<p style="text-align: center;">2000</p>
	<p>Deposit the steel reinforcement rod inside the iron post.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>N. 0° 48' E., beginning new measurement.</p> <p>Over rolling terrain.</p>														
40.64	<p>The cor. of secs. 7, 8, 17 and 18, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with an aluminum post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, in abandoned fence extending N. and S., as filed in the Campbell County Clerk's Office, with aluminum cap inscribed WILLAIM H. SMITH &amp; ASSOC. P.C. and mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T54N R74W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">S 17</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> <tr> <td colspan="2" style="text-align: center;">RLS NO. 2608</td> </tr> <tr> <td colspan="2" style="text-align: center;">JOB NO. 99046</td> </tr> </table> </div> <p>This position is accepted as a careful and faithful determination of the original cor. position.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89° 46' W., bet. secs. 8 and 17.</p> <p>Over rolling terrain.</p>	T54N R74W		S 7	S 8			S 18	S 17	1999		RLS NO. 2608		JOB NO. 99046	
T54N R74W															
S 7	S 8														
S 18	S 17														
1999															
RLS NO. 2608															
JOB NO. 99046															
36.10	<p>Spotted Horse Creek, course NNW.</p>														
39.34	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap inscribed WILLIAM H. SMITH AND ASSOC. P.C. SURVEYING CONSULTANTS and mkd. T54N R73W 1/4 8 17 1999 RLS 2608 JOB NO. 99046, with a steel fence post alongside, as filed in the Campbell County Clerk's Office. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T54N R74W</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 8</td> </tr> <tr> <td style="padding-right: 10px;">1/4</td> <td style="border-top: 1px solid black; width: 20px;"></td> </tr> <tr> <td colspan="2" style="text-align: center;">S 17</td> </tr> <tr> <td colspan="2" style="text-align: center;">2000</td> </tr> </table> </div>	T54N R74W		S 8		1/4		S 17		2000					
T54N R74W															
S 8															
1/4															
S 17															
2000															

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>Deposit the steel reinforcement rod inside the iron post.</p> <hr/> <p>S. 89° 46' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
39.34	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 89° 46' W., bet. secs. 7 and 18.</p> <p>Over gently rolling terrain.</p>
21.20	<p>Rose Creek, course NNW.</p>
40.32	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T54N R74W</p> <p>S 7</p> <p>1/4 ———</p> <p>S 18</p> <p>2000</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, a position established by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, bears N. 89° 29' E., 63.5 lks. dist., monumented with a steel reinforcement rod, 30 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap inscribed WILLIAM H. SMITH AND ASSOC. P.C. SURVEYING CONSULTANTS and mkd. T54N R74W 1/4 S7 S18 1999 RLS 2608, with a steel fence post alongside, as filed in the Campbell County Clerk's Office. This position was incorrectly reestablished at midpoint position between controlling corners E. and W., rather than at proportionate distance and is not accepted as a careful and faithful reestablishment of the original cor. position. Mr. Dolinar granted permission to move his monument to the correct proportionate position, where it was deposited alongside the iron post.</p>
79.37	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0° 37' E., bet. secs. 7 and 8.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Over rolling terrain.</p> <p>40.64 The 1/4 sec. cor. of secs. 7 and 8, monumented by John I. Dolinar, Wyoming Registered Land Surveyor No. 2608, with a steel reinforcement rod, 22 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap inscribed WILLIAM H. SMITH AND ASSOC. P.C. SURVEYING CONSULTANTS and mkd. T54N R74W 1/4 S7 S8 1999 RLS 2608 JOB NO. 99046, with a steel fence post alongside, as filed in the Campbell County Clerk's Office. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T54N R74W 1/4 S 7   S 8 2000</p> <p>Deposit the steel reinforcement rod inside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 37' E., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>12.60 Spotted Horse Creek, course NW.</p> <p>32.10 T D Southwest Draw, drains W.</p> <p>40.63 The cor. of secs. 5, 6, 7 and 8, remonumented by Bryce E. Rumph, Wyoming Registered Land Surveyor No. 538, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set flush with the surface of the ground, with aluminum cap inscribed RUMPH SURVEYS GILLETTE, WYOMING and mkd. T54N R74W 5 6 7 8 PLS 538 1998, with a scoria stone, 24x10x5 ins., firmly set, projecting 8 ins. above the ground alongside, plainly mkd. 5 grooves on E. face and 5 notches on S. edge, with a steel fence post alongside and a mound of stone, 3 ft. base, 2 ft. high, N. of the cor., as filed in the Campbell County Clerk's Office. This position is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p>
--------	--

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS											
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T54N</td><td>R74W</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Bury the original cor. stone alongside and deposit the steel reinforcement rod inside the iron post.</p>	T54N	R74W	S 6	S 5	S 7	S 8	2000			
T54N	R74W										
S 6	S 5										
S 7	S 8										
2000											
	<hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89° 30' W., bet. secs. 5 and 8.</p> <p>Over rolling terrain.</p>										
19.615	<p>Point for the E. 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T54N</td><td>R74W</td></tr> <tr><td>S 5</td><td></td></tr> <tr><td>E1/16</td><td>—</td></tr> <tr><td>S 8</td><td></td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T54N	R74W	S 5		E1/16	—	S 8		2000	
T54N	R74W										
S 5											
E1/16	—										
S 8											
2000											
39.23	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T54N</td><td>R74W</td></tr> <tr><td>S 5</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 8</td><td></td></tr> <tr><td colspan="2">2000</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p>	T54N	R74W	S 5		1/4	—	S 8		2000	
T54N	R74W										
S 5											
1/4	—										
S 8											
2000											
78.46	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/>										

Dependent Resurvey of the Subdivisional Lines,  
T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>S. 89° 54' W., bet. secs. 6 and 7.</p> <p>Over gently rolling terrain.</p> <p>18.30 Spotted Horse Creek, course NNE.</p> <p>40.76 Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R74W</p> <p>S 6</p> <p>1/4 ———</p> <p>S 7</p> <p>2000</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>80.51 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0° 05' E., bet. secs. 5 and 6.</p> <p>Over gently rolling terrain.</p> <p>40.09 Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T54N R74W</p> <p>1/4</p> <p>S 6   S 5</p> <p>2000</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>80.83 The cor. of secs. 5 and 6 only, on the N. bdy. of the Tp.</p> <hr/>
--------	--

## T. 54 N., R. 74 W., Sixth Principal Meridian, Wyoming

CHAINS	GENERAL DESCRIPTION
	<p>The area embraced by this survey is situated in the northwest portion of Campbell County, approximately 25 miles northwest of Gillette, Wyoming. The terrain varies from nearly level to rolling and broken, with the elevation ranging from about 4,000 feet to about 4,650 above sea level. The soil is primarily sandy loam and the vegetation consists of scattered sagebrush and native and domestic grasses.</p> <p>Drainage is provided by Horse Creek in the southeast and Spotted Horse Creek in the northwest portion of the township, aided by numerous draws, all of which flow intermittently. There are three active ranching operations with numerous areas under cultivation. The area is currently undergoing extensive gas exploration and development resulting in many wells being drilled and pipelines laid.</p> <p>Access is provided by U.S. Highway Nos. 14-16 and Middle Prong Road supplemented by trail roads and roads that service the gas fields.</p>



## CERTIFICATE OF SURVEY

I, Joel T. Ebner, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of May, 2000, I have dependently resurveyed the west boundary, a portion of the north boundary, and the subdivisional lines, Township 54 North, Range 74 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAY 31 2002

(Date)

  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of the west boundary, a portion of the north boundary, and the subdivisional lines, Township 54 North, Range 74 West, Sixth Principal Meridian, Wyoming, executed by Joel T. Ebner, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAY 31 2002

(Date)

  
(Signature of Authorized Officer)