

VOLUME 782

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
REMONUMENTATION
OF THE
1/4 SECTION CORNER
OF SECTIONS 31 AND 32,
TOWNSHIP 44 NORTH, RANGE 76 WEST,
OF THE SIXTH PRINCIPAL MERIDIAN,
IN THE STATE OF WYOMING.

EXECUTED BY

JAMES E. JACOB

CADASTRAL SURVEYOR

Under Special Instructions dated JUNE 13, 2011, approved JUNE 13, 2011, which provided for the surveys included under Group Number 850, Wyoming, and Assignment Instructions dated AUGUST 2, 2011.

Survey commenced SEPTEMBER 22, 2011

Survey completed SEPTEMBER 22, 2011

Remonumentation of the 1/4 Sec. Cor. of Secs. 31 and 32,
T. 44 N., R. 76 W., Sixth Principal Meridian, Wyoming

<p>Chains</p>	<p>The following field notes are those of the remonumentation of the 1/4 sec. cor. of secs. 31 and 32, Township 44 North, Range 76 West, Sixth Principal Meridian, Wyoming.</p> <p>The history of surveys pertaining to this resurvey is as follows:</p> <p>Frank Buckley surveyed the subdivisional lines in 1882 and Russell C. MacDonald dependently resurveyed these lines in 1956.</p> <hr/> <p style="text-align: center;">Remonumentation of the 1/4 Sec. Cor. of Secs. 31 and 32, T. 44 N., R. 76 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>The 1/4 sec. cor. of secs. 31 and 32, monumented with a bent iron post, 30 ins. long, 2½ ins. diam., firmly set 24 ins. in the ground, with a steel fence post set alongside, and brass cap lying loose alongside mkd. 1/4 S 31 S 32 1956.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T44N R76W 1/4 S 31 S 32 2011</p> <p>from which</p> <p style="padding-left: 40px;">An iron FENO® rod, 24 ins. long, ¾ in. diam., set flush with the surface of the ground, for a reference monument, bears S. 45° E., 1.00 chs. dist., with aluminum cap mkd. BLM RM T44N R76W 1/4 S 32 66.0 FT. TO COR. 2011 CADASTRAL SURVEY and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron FENO® rod, 24 ins. long, ¾ in. diam., set flush with the surface of the ground, for a reference monument, bears S. 45° W., 1.00 chs. dist., with aluminum cap mkd. BLM RM T44N R76W 1/4 S 31 66.0 FT. TO COR. 2011 CADASTRAL SURVEY and an arrow pointing to the cor.</p> <p>Remove the 1956 iron post and the brass cap from the area.</p>
----------------------	---

Remonumentation of the 1/4 Sec. Cor. of Secs. 31 and 32,
T. 44 N., R. 76 W., Sixth Principal Meridian, Wyoming

Chains	<p>Cor. is located immediately northwest of intersection of improved roads extending N., E. and W.</p> <p>The geographic position of the 1/4 sec. cor. of secs. 31 and 32, based on NAD 83 (2011)(EPOCH:2010) and determined by Global Positioning Methods, is:</p> <p>Latitude 43° 44' 41.342" N., Longitude 106° 01' 43.234" W.</p> <hr/>
---------------	---

CERTIFICATE OF SURVEY

I, James E. Jacob, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 13th day of June, 2011, I have remonumented the 1/4 sec. cor. of secs. 31 and 32, Township 44 North, Range 76 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 3, 2011

Date



James E. Jacob
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the remonumentation of the 1/4 sec. cor. of secs. 31 and 32, Township 44 North, Range 76 West, Sixth Principal Meridian, Wyoming, executed by James E. Jacob, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

November 3, 2011

Date



John P. Lee
Chief Cadastral Surveyor for Wyoming