

FIELD NOTES  
PUBLIC SURVEY

VOL. 465

07 - 4417

916 - 1921

I N D E X

VOL. 465

4407	Sur. Priv. Claims	T.	58 N., R.	74 W.
	Ind. Res. Subs.		"	"
4408	Sur. Priv. Claims			
	Ind. Res. Subs.	T.	13 N., R.	86 W.
4409	Bdys.	Ts. 13 &	14 N., R	87 W.
	Bdys.	T.	13 N., R.	86 W.
4410	Sur. Priv. Claims			
	Ind. Res. Subs.	T.	13 N., R.	87 W.
4411	Sup. Sur. & Sur. Tracts Sec. 34		56 N., R.	98 W.
4412	Subs. and Spec. Surs. Sec. 13		23 N., R.	63 W.
4413	Sur. Priv. Claims			
	Ind. Res. Subs.	T.	47 N., R.	103 W.
4414	Dep. Res. S. Bdy.	T.	48 N., R.	103 W.
	Ind. Res. E. S. & W. Bdys.	T.	47 N., R.	103 W.
4415	Subs. & Sur. Tracts Lot 46	T. 55 &	54 N., R.	99 W.
	Subs. & Sur. Tracts Lot 38	T.	55 N., R.	99 W.
4416	Dep. Res. Secs. 33 & 34	T.	33 N., R.	77 W.
4417	Sur. Priv. Claims			
	Ind. Res. Subs.	T.	14 N., R.	87 W.

FIELD NOTES

PUBLIC SURVEY

---

---

VOL. 465

4407 - 4417

1916 - 1921

---

Sample  
Marking  
for  
back

BOOK "D"

# FIELD NOTES

OF THE SURVEY OF THE

PRIVATE LAND CLAIM LINES

AND

INDEPENDENT RESURVEY OF THE

SUBDIVISION LINES

OF

TOWNSHIP NO. 13 NORTH, RANGE NO. 86 WEST,

INDEXED  
*[Signature]*

Of the SIXTH PRINCIPAL Meridian,

In the State of WYOMING

EXECUTED BY

EUGENE D. ADAMS AND LELAND S. SCHUCH

and U. S. Transitman,

In the capacity of U. S. Surveyor, under Special Instructions dated September 21, 1916,  
issued by the United States Surveyor General to govern surveys included in Group  
No. 31, which were approved by the Commissioner of the General Land  
Office, October 2, 1916, and Assignment Instructions dated June 16, 1919.

Survey commenced August 4, 1919.

Survey completed September 8, 1919.

*accepted Mar. 28, 1922*

4408

# INDEX DIAGRAM.

Township ..... 13 North ..... Range ..... 86 West .....

6	30	5	39	4	50	3	60	2	75	1
29		39		49		59		73		74
7	28	8	38	9	48	10	58	11	72	12
27		37		47		57		70		71
18	26	17	36	16	46	15	56	14	69	13
25		35		45		55		66		67
19	24	20	34	21	44	22	54	23	65	24
23		33		43		53		63		64
30	21	29	31	28	42	27	52	26	62	25
13		14		15		17		18		19
31	21	32	31	33	41	34	51	35	61	36

Index to Segregated Tracts.

Tract No. 37.....	Page 1
38 .....	3
39 .....	5
41 .....	11
42 .....	8

Transcriber - MGK


O. M. G. H.


T. H. G. O

Diagram Showing Lines Run by Each Surveyor:

T. 13 N. R. 86 W.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Eugene D. Adams, 

Ieland S. Schuch, 

Begun August 4, 1919 and completed September 8, 1919.

Survey of Private Land Claims in Resurvey T. 13 N., R. 86 W.

Chains.

Survey commenced August 4, 1919, and executed with Buff Transits Nos. 9793 and 9794, with solar attachments. The horizontal limbs are provided with two double verniers placed opposite to each other, reading to single minutes of arc; which is also the least count of the verniers of the latitude and declination arcs.

These instruments were examined and approved by the Asst. Supervisor of Surveys, conditionally upon a satisfactory field test.

The examination of the adjustments of the instruments, tests of the solar apparatuses and Polar observations will be found in the book of exteriors of Group 31, Wyoming.

---

Note: Survey of private land claims as originally located in accordance with the survey executed by G. W. Baker, U. S. Surveyor, in 1881.

---

Tract No. 37.

State of Wyoming. School Section 36. Grant.

Cor. No. 1, the NE. corner of Tract 37, is identical with the angle point on the E. bdy. of sec. 25, which marks the position of original cor. of secs. 25, 30, 31 and 36, described in the field notes of the reestablishment of the E. bdy. of T. 13 N., R. 86 W., Group 31.

From cor. No. 1/37,

S. 0° 18' E., on line 1-2, Tract 37; on E. bdy. of Tp.

3.19 Closing cor. for secs. 25 and 36, resurvey T. 13 N., R. 86 W.

4.41 Closing cor. for secs. 30 and 31, T. 13 N., R. 85 W.

39.85 Angle point, marking position of original  $\frac{1}{4}$  sec. cor. bet. secs. 31 and 36, described in field notes of reestablishment of E. bdy. T. 13 N., R. 86 W.

## Survey of Private Land Claims in Resurvey T. 13 N., R. 86 W.

## Chains.

- Thence  
S. 0° 36' E., on line 1-2, Tract 37; on E. bdy. of Tp.  
41.39 Cor. No. 2/37, which is identical with the restored  
Standard cor. of Ts. 12 and 13 N., R. 86 W., described  
in field notes of the reestablished Third Standard  
Parallel North, Group 31.
- Thence  
West, on line 2-3, Tract 37; on the Third Standard  
Parallel North.
- 37.82 The  $\frac{1}{4}$  sec. cor. bet. secs. 1 and 36.
- 41.04 Angle point, marking the position of original standard  
 $\frac{1}{4}$  sec. cor. bet. secs. 1 and 36, previously described.
- Thence  
N. 89° 48' W., on line 2-3, Tract 37; on the Third  
Standard Parallel North.
- 33.78 Closing cor. for secs. 35 and 36, resurvey T. 13 N., R.  
86W., and cor. of secs. 1 and 2, resurvey T. 12 N., R. 86 W.
- 37.78 Cor. No. 3/37, which is identical with the angle point  
on S. bdy. Sec. 35, marking the position of original  
standard cor. of secs. 1, 2, 35 and 36, described in  
field notes of reestablishment of the Third Standard  
Parallel North., Group 31.
- Thence  
North, on line 3-4, Tract 37.
- 81.44 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for cor. No. 4/37, with brass cap, mkd.
- T13N R86W  
S26  
4  
TR37  
1919
- Thence  
East, on line 4-1, Tract 37.
- 78.20 Cor. No. 1/37, the point of beginning.

Survey of Private Land Claims in Resurvey T. 13 N., R. 86 W.

Chains.

Tract No. 38.

Wm. S. Kuykendall, H.E. 09308, Patented.


SW $\frac{1}{4}$  NW $\frac{1}{4}$  NW $\frac{1}{4}$ , NW $\frac{1}{4}$  SW $\frac{1}{4}$  NW $\frac{1}{4}$ , S $\frac{1}{4}$  SW $\frac{1}{4}$  NW $\frac{1}{4}$ , W $\frac{1}{4}$  SW $\frac{1}{4}$ , Section 28.

SE $\frac{1}{4}$  NE $\frac{1}{4}$  NE $\frac{1}{4}$ , NE $\frac{1}{4}$  SE $\frac{1}{4}$  NE $\frac{1}{4}$  Section 29.

N $\frac{1}{4}$  NW $\frac{1}{4}$  NW $\frac{1}{4}$  Section 33.

Alongside of the point established by the U. S. Forest survey for NE. cor. of this tract, a pine post, 4 ins. square,


Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 1/38, with brass cap, mkd.



Thence

South, on line 1-2, Tract 38.


20.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 2/38, with brass cap, mkd.



Thence

East, on line 2-3, Tract 38.


10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 3/38, with brass cap, mkd.



Thence

South, on line 3-4, Tract 38.

60.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 4/38, with brass cap, mkd.




## Survey of Private Land Claims in Resurvey T. 13 N., R. 86 W.

Chains.

Thence

West, on line 4-5, Tract 38.


- 20.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 5/38, with brass cap, mkd.



Thence

North, on line 5-6, Tract 38.


- 60.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 6/38, with brass cap, mkd.



Thence

West, on line 6-7, Tract 38.

- 10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 7/38, with brass cap, mkd.



Thence

North, on line 7-8, Tract 38.

- 20.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 8/38, with brass cap, mkd.



Thence

East, on line 8-1, Tract 38.

- 20.00 Cor. No. 1/38, the point of beginning.

Survey of Private Land Claims in Resurvey T. 13 N., R. 86 W.

Chains.

Tract No. 39.

Rowland H. Harlow, H.E. 016715, Cancelled.


SE $\frac{1}{2}$ NE $\frac{1}{2}$ SE $\frac{1}{2}$ , S $\frac{1}{2}$ SW $\frac{1}{2}$ NE $\frac{1}{2}$ SE $\frac{1}{2}$ , N $\frac{1}{2}$ SE $\frac{1}{2}$ SE $\frac{1}{2}$ , N $\frac{1}{2}$ S $\frac{1}{2}$ SE $\frac{1}{2}$ SE $\frac{1}{2}$  Sec. 19.

S $\frac{1}{2}$ NW $\frac{1}{2}$ SW $\frac{1}{2}$ , N $\frac{1}{2}$ SW $\frac{1}{2}$ SW $\frac{1}{2}$ , N $\frac{1}{2}$ S $\frac{1}{2}$ SW $\frac{1}{2}$ SW $\frac{1}{2}$ , SE $\frac{1}{2}$ SW $\frac{1}{2}$ .

N $\frac{1}{2}$ SW $\frac{1}{2}$ SE $\frac{1}{2}$ , N $\frac{1}{2}$ SW $\frac{1}{2}$ SW $\frac{1}{2}$ SE $\frac{1}{2}$ , Sec. 20.

Alongside of a 4 in. pine post, established by the U. S. Forest Service for the SE. cor. of Tract 42, which is identical with cor. No. 3/39,


Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 3/39 and 6/42, with brass cap, mkd.



Thence

South, on line 3-4, Tract 39.


10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 4/39, with brass cap, mkd.



Thence

West, on line 4-5, Tract 39.

10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 5/39, with brass cap, mkd.




Thence

South, on line 5-6, Tract 39.

5.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 6/39, with brass cap, mkd.

Survey of Private Land Claims in Resurvey T. 13 N., R. 86 W.


Chains.



Thence

West, on line 6-7, Tract 39.

10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 7/39, with brass cap, mkd.



Thence

South, on line 7-8, Tract 39.


5.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 8/39, with brass cap, mkd.



Thence

West, on line 8-9, Tract 39.


20.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 9/39, with brass cap, mkd.



Thence

North, on line 9-10, Tract 39.

5.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 10/39, with brass cap, mkd.



Thence

Survey of Private Land Claims in Resurvey T. 13 N., R. 86 W.

Chains.

West, on line 10-11, Tract 39.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 11/39, with brass cap, mkd.



Thence

North, on line 11-12, Tract 39.

20.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 12/39, with brass cap, mkd.



Thence

East, on line 12-13, Tract 39.

10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 13/39, with brass cap, mkd.



Thence

North, on line 13-14, Tract 39.

5.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 14/39, with brass cap, mkd.




Thence

East, on line 14-1, Tract 39.

30.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 1/39, with brass cap, mkd.

## Survey of Private Land Claims in Resurvey T. 13 N., R. 86 W.

Chains.



Thence

South, on line 1-2, Tract 39.

10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 2/39, with brass cap, mkd.



Thence

East, on line 2-3, Tract 39.

15.00 Cor. No. 7/42.

Thence bet. Tracts 39 and 42.

40.00 Cor. No. 3/39 and 6/42, the point of beginning.


Tract No. 42.Charles T. Fletcher, H.E. 09017, Patented.

NW $\frac{1}{2}$ SE $\frac{1}{2}$ , SW $\frac{1}{2}$ NE $\frac{1}{2}$ , S $\frac{1}{2}$ NW $\frac{1}{2}$ NE $\frac{1}{2}$ , S $\frac{1}{2}$ N $\frac{1}{2}$ NW $\frac{1}{2}$ NE $\frac{1}{2}$ , SW $\frac{1}{2}$ SW $\frac{1}{2}$ NE $\frac{1}{2}$ NE $\frac{1}{2}$ ,  
NW $\frac{1}{2}$ NW $\frac{1}{2}$ SE $\frac{1}{2}$ NE $\frac{1}{2}$ , SE $\frac{1}{2}$ NE $\frac{1}{2}$ NE $\frac{1}{2}$ NW $\frac{1}{2}$ , E $\frac{1}{2}$ SE $\frac{1}{2}$ NE $\frac{1}{2}$ NW $\frac{1}{2}$ , NE $\frac{1}{2}$ NE $\frac{1}{2}$ SE $\frac{1}{2}$ NW $\frac{1}{2}$ ,  
S $\frac{1}{2}$ NE $\frac{1}{2}$ SE $\frac{1}{2}$ NW $\frac{1}{2}$ , SE $\frac{1}{2}$ NW $\frac{1}{2}$ SE $\frac{1}{2}$ NW $\frac{1}{2}$ , NE $\frac{1}{2}$ SW $\frac{1}{2}$ SE $\frac{1}{2}$ NW $\frac{1}{2}$ , SE $\frac{1}{2}$ SE $\frac{1}{2}$ NW $\frac{1}{2}$ ,  
NE $\frac{1}{2}$ NE $\frac{1}{2}$ SW $\frac{1}{2}$ , E $\frac{1}{2}$ SE $\frac{1}{2}$ NE $\frac{1}{2}$ SW $\frac{1}{2}$ , Sec. 20.

From cor. No. 6/42 and 3/39, described in field notes of Tract 39,

West, on line 6-7, Tract 42; bet. Tracts 42 and 39.

25.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 7/42, on line 2-3, Tract 39, with brass cap, mkd.



Thence

North, on line 7-8, Tract 42.

Survey of Private Land Claims in Resurvey T. 13 N., R. 86 W.

Chains.

10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 8/42, with brass cap, mkd.



Thence

West, on line 8-9, Tract 42.

5.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 9/42, with brass cap, mkd.



Thence

North, on line 9-10, Tract 42.

15.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 10/42, with brass cap, mkd.



Thence

West, on line 10-11, Tract 42.

5.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 11/42, with brass cap, mkd.




Thence

North, on line 11-12, Tract 42.

10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 12/42, with brass cap, mkd.

Survey of Private Land Claims in Resurvey T. 13 N., R. 86 W.


Chains.



Thence

East, on line 12-13, Tract 42.

10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 13/42, with brass cap, mkd.



Thence

North, on line 13-14, Tract 42.

20.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 14/42, with brass cap, mkd.



Thence

East, on line 14-1, Tract 42.

25.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 1/42, with brass cap, mkd.



Thence

South, on line 1-2, Tract 42.

10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 2/42, with brass cap, mkd.



Thence


Survey of Private Land Claims in T. 13 N., R. 86 W.

Chains.

Thence

East, on line 2-3, Tract 42.


- 5.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 3/42, with brass cap, mkd.



Thence

South, on line 3-4, Tract 42.


- 10.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 4/42, with brass cap, mkd.



Thence

West, on line 4-5, Tract 42.

- 5.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 5/42, with brass cap, mkd.



Thence

South, on line 5-6, Tract 42.

- 35.00 Cor. No. 6/42 and 3/39, the point of beginning.

Tract No. 41.

John H. Binger, H.E. 013521, Patented.

SE $\frac{1}{4}$ NE $\frac{1}{4}$ , E $\frac{1}{2}$ E $\frac{1}{2}$ SW $\frac{1}{2}$ NE $\frac{1}{4}$ , NE $\frac{1}{4}$ SE $\frac{1}{4}$ , E $\frac{1}{2}$ E $\frac{1}{2}$ NW $\frac{1}{2}$ SE $\frac{1}{4}$  Sec. 25.

T. 13 N., R. 87 W.

W $\frac{1}{2}$  Lot 2, W $\frac{1}{2}$ E $\frac{1}{2}$  Lot 2, W $\frac{1}{2}$  Lot 3, W $\frac{1}{2}$ E $\frac{1}{2}$  Lot 3, Sec. 30.


T. 13 N., R. 86 W.

At the recognized property cor. at cor. of N. and E. fences,

Survey of Private Land Claims in Resurvey T. 13 N., R. 86 W.

Chains.

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 3/41, with brass cap, mkd.



Thence

North, on line 3-4, Tract 41.


40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 4/41, with brass cap, mkd.



Thence

East, on line 4-1, Tract 41.


40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 1/41, with brass cap, mkd.



Thence

South, on line 1-2, Tract 41.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for cor. No. 2/41, with brass cap, mkd.



Thence

S. 89° 57' W., on line 2-3, Tract 41.

39.97 Cor. No. 3/41, the point of beginning.


Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Independent Resurvey superseding the survey executed by G. W. Baker, U. S. Surveyor, in 1881.

Beginning at the resurvey cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., previously described. East, bet. secs. 30 and 31, on Sectional Correction Line. Over rolling mountainous land; descend gently.

- 0.40 Rail fence, bears NW. and SE.
- 7.00 Road, bears NW. and SE.
- 18.20 Gulch, course SW., 26 ft. below sec. cor.; ascend.
- 24.00 Point of spur, slopes S., 18 ft. above gulch; ascend.
- 28.00 Spring branch, course SW., 9 ft. below spur.
- 29.00 Enter timber, bears N. and S.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



from which

A pine, 7 ins. dia., bears N. 3° E., 37 lks. dist., mkd.  $\frac{1}{4}$  S 30 B T.

A pine, 15 ins. dia., bears S. 70° E., 25 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T.

- 80.00 Point for sec. cor. falls on granite cliff. Mark a cross (X) at cor. point, on boulder, 10 ft. high, which is part of the cliff, to define the point for resurvey cor. of secs. 29, 30, 31 and 32. Raise a mound of stone, 4 ft. base, 2 ft. high, W. of boulder, marked X. Cor. is 135 ft. above spring branch. Land, rolling mountainous. Soil, dark loam; 2nd and 3rd rate. Vegetation, sage and grass. Timber, pine, aspen, balsam and spruce.


## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

East, bet. secs. 29 and 32; on Sectional Correction Line.  
Over rolling mountainous land; ascend through heavy  
timber.

20.30 Spur, bears S., 115 ft. below sec. cor.; descend.

40.00 Set an iron post; 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap,  
mkd.




raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N.  
of cor.

58.24 G. L. Nelson, Forest Monument, cor. No. 1, bears North,  
13.02 chs. dist.

71.00 Old road, bears N. and S.

74.20 Roaring Fork Creek, 2 lks. wide, 3 ins. deep, course  
S.  $10^{\circ}$  E., 570 ft. below spur; ascend.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in  
the ground, for resurvey cor. of secs. 28, 29, 32 and  
33, with brass cap, mkd.



from which

An aspen, 4 ins. dia., bears N.  $26\frac{3}{4}^{\circ}$  E., 138 lks.  
dist., mkd. T 13 N R 86 W S 28 B T.

An aspen, 6 ins. dia., bears S.  $33^{\circ}$  E., 14 lks.  
dist., mkd. T 13 N R 86 W S 33 B T.

An aspen, 5 ins. dia., bears S.  $56^{\circ}$  W., 28 lks.  
dist., mkd. T 13 N R 86 W S 32 B T.

A pine, 12 ins. dia., bears N.  $28\frac{1}{2}^{\circ}$  W., 150 lks.  
dist., mkd. T 13 N R 86 W S 29 B T.

Cor. is 56 ft. above creek.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Land, rolling mountainous.

Soil, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, grass, chokecherry and willows.

Timber, pine and aspen.

East, bet. secs. 28 and 33; on Sectional Correction Line.

Over rolling mountainous land; ascend through heavy timber.

8.00 Top of spur, bears S., 37 ft. above sec. cor.; descend.

11.26 Intersect the line 5-6, Tract 38, at a point, N., 20.50 chs. from cor. No. 5.

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for closing cor. of frac. secs. 28 and 33, with brass cap, mkd.




16.00 Branch of Roaring Fork, 10 lks. wide, 7 ins. deep, course S., 140 ft. below spur; ascend.

20.50 Top of spur, bears SW., bears SW., 84 ft. above creek; descend.

26.16 Road, bears NW. and SE.

31.26 Intersect line 3-4, Tract 38, at a point, N., 20.50 chs. from cor. No. 4.


Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for closing cor. of frac. secs. 28 and 33, with brass cap, mkd.



40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey 1/4 sec. cor., with brass cap, mkd.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.




from which

An aspen, 6 ins. dia., bears N.  $12\frac{3}{4}^{\circ}$  W., 103 lks.  
dist., mkd.  $\frac{1}{4}$  S 28 B T.

An aspen, 10 ins. dia., bears S.  $26^{\circ}$  W., 36 lks.  
dist., mkd.  $\frac{1}{4}$  S 33 B T.

- 43.20 Spring branch, 3 lks. wide, 3 ins. deep, course SW., 18 ft. below spur; ascend.
- 56.00 Point of spur, bears SW., 144 ft. above creek; descend.
- 62.34 Spring branch, 6 lks. wide, 3 ins. deep, course S.  $10^{\circ}$  E.; 40 ft. below spur; ascend.
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for resurvey cor. of secs. 27, 28, 33 and 34, with brass cap, mkd.



from which

A pine, 6 ins. dia., bears N.  $71\frac{1}{2}^{\circ}$  E., 19 lks.  
dist., mkd. T 13 N R 86 W S 27 B T.

A pine, 6 ins. dia., bears S.  $24\frac{1}{2}^{\circ}$  E., 27 lks.  
dist., mkd. T 13 N R 86 W S 34 B T.

A pine, 6 ins. dia., bears S.  $74^{\circ}$  W., 33 lks.  
dist., mkd. T 13 N R 86 W S 33 B T.

A pine, 6 ins. dia., bears N.  $51\frac{1}{2}^{\circ}$  W., 37 lks.  
dist., mkd. T 13 N R 86 W S 28 B T.

Cor. 170 ft. above spring branch.

Land, rough mountainous.

Soil, stony, sandy, clay loam; subsoil, same; 3rd and 4th rate.

Vegetation, grass, sage, willows, chokecherry and service brush.

Timber, pine and aspen.


Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

East, bet. secs. 27 and 34; on Sectional Correction Line.  
Over rough mountainous land; ascend through heavy timber.

6.70 Small spring branch, course N.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap,  
mkd.



from which


A pine, 4 ins. dia., bears North, 38 lks. dist.,  
mkd.  $\frac{1}{4}$  S 27 B T.

A pine, 4 ins. dia., bears S. 20° E., 7 lks. dist.,  
mkd.  $\frac{1}{4}$  S 34 B T.

Cor. is 555 ft. above sec. cor.

58.00 Top of ridge, bears NE. and SW., 316 ft. above  $\frac{1}{4}$  cor.;  
descend.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in  
the ground, for resurvey cor. of secs. 26, 27, 34 and  
35, with brass cap, mkd.



from which

An aspen, 5 ins. dia., bears N. 29 $\frac{1}{2}$ ° E., 30 lks.  
dist., mkd. T 13 N R 86 W S 26 B T.

An aspen, 6 ins. dia., bears S. 53 $\frac{1}{2}$ ° E., 7 lks.  
dist., mkd. T 13 N R 86 W S 35 B T.

An aspen, 5 ins. dia., bears S. 41° W., 24 lks.  
dist., mkd. T 13 N R 86 W S 34 B T.

An aspen, 6 ins. dia., bears N. 31° W., 17 lks.  
dist., mkd. T 13 N R 86 W S 27 B T.

Cor. is 312 ft. below ridge.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Land, rough mountainous.

Soil, stony, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, sage, grass, chokecherry and service brush.


Timber, pine and aspen.

East, bet. secs. 26 and 35; on Sectional Correction Line.

Over rough mountainous land; ascend through heavy timber.

10.40 Spring branch, 1 lk. wide, 1 in. deep, course S.; 173  
lks. below sec. cor.; ascend.

15.20 Spur, bears S., 48 ft. above spring branch; descend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap,  
mkd.

from which

An aspen, 7 ins. dia., bears N.  $23\frac{1}{4}^{\circ}$  E., 58 lks.  
dist., mkd.  $\frac{1}{4}$  S 26 B T.A fir, 18 ins. dia., bears S.  $19\frac{3}{4}^{\circ}$  E., 70 lks.  
dist., mkd.  $\frac{1}{4}$  S 35 B T.

Cor. 331 ft. below spur.

50.00 West Fork of North Fork of Little Snake River, 20 lks.  
wide, 8 ins. deep, course S.  $10^{\circ}$  W., 46 ft. below  $\frac{1}{4}$   
cor.; ascend.

55.00 Leave live timber and dead and fallen timber.

63.80 Spring, 50 lks. N. of line, course S.; 171 ft. above  
creek.


73.00 Top of spur, bears SW., 507 ft. above creek; descend.

76.10 Spring branch, 1 lk. wide, 1 in. deep, course SW.; ascend.


78.91 Intersect line 3-4, Tract 37, at a point, 3.18 chs., S.  
of cor. No. 4.Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for closing cor. of frac. secs. 26 and 35,  
with brass cap, mkd.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.



80.00 Set an iron post, 3 ft. long, 2 ins. dia., 18 ins. in the ground, on underlying rock, surrounded by a mound of stone, for resurvey cor. of secs. 25, 26, 35 and 36, with brass cap, mkd.



raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Cor. 31 ft. above spring branch.

Land, rough mountainous.

Soil, stony, sandy, clay loam; subsoil, same; 2nd and 3rd rate.

Vegetation, ferns, grass, willows and chokecherry brush.


Timber, pine, balsam, fir and aspen.

East, bet. secs. 25 and 36; on Sectional Correction Line. Over rough, mountainous land; ascend over fallen dead timber.

9.00 Enter green timber, bears NE. and SW.

27.00 Top of divide, between West and East prongs of the North Fork of Little Snake River, bears SW., 504 ft. above sec. cor.; descend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey 1/4 sec. cor., with brass cap, mkd.



from which

A fir, 6 ins. dia., bears N. 28° W., 71 lks.

dist., mkd. 1/4 S 25 B T.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

A fir, 15 ins. dia., bears S.  $78\frac{1}{2}^{\circ}$  W., 46 lks.  
dist., mkd.  $\frac{1}{2}$  S 36 B T.

Cor. is 154 ft. below spur.


44.10 Spring branch, 1 lk. wide, 1 in. deep, course S., 18 ft.  
below  $\frac{1}{2}$  cor.; descend.

49.50 Spring branch, 1 lk. wide, 1 in. deep, course SE., 135  
ft. below  $\frac{1}{2}$  cor.; descend.

72.00 Spring branch, 1 lk. wide, 1 in. deep, course S., 144 ft.  
below  $\frac{1}{2}$  cor.; ascend.

77.21 Intersect the E. bdy. of the Tp., at a point, S.  $0^{\circ}18'E.$ ,  
3.19 chs. from the angle point, marking the position  
of the original cor. of secs. 25, 30, 31 and 36, pre-  
viously described.

Set an iron post, 3 ft. long, 2 ins. dia., 10 ins. in  
the ground, on underlying rock, surrounded by a mound  
of stone, for closing cor. of secs. 25 and 36, with  
brass cap, mkd.



from which

A fir, 8 ins. dia., bears N.  $80^{\circ}$  W., 19 lks. dist.,  
mkd. CC T 13 N R 86 W S 25 B T.

A pine, 10 ins. dia., bears S.  $80^{\circ}$  W., 17 lks. dist.,  
mkd. CC T 13 N R 86 W S 36 B T.

Cor. 115 ft. above spring branch.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 3rd and  
4th rate.

Vegetation, sage, grass and chokecherry.

Timber, aspen, pine and balsam fir.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

From the cor. of secs. 29, 30, 31 and 32,  
South, on a random line, bet. secs. 31 and 32.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.


79.54 Fall 30 lks. E. of the reestablished standard cor. of  
secs. 5, 6, 31 and 32, previously described.

Thence

N.  $0^{\circ} 13' E.$ , on a true line, bet. secs. 31 and 32.

Over rolling mountainous land; ascend through heavy  
timber.

39.54 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap,  
mkd.



from which

A pine, 5 ins. dia., bears N.  $42^{\circ} E.$ , 19 lks.  
dist., mkd.  $\frac{1}{4}$  S 32 B T.

A pine, 7 ins. dia., bears N.  $81\frac{1}{2}^{\circ} W.$ , 28 lks.  
dist., mkd.  $\frac{1}{4}$  S 31 B T.

79.54 The cor. of secs. 29, 30, 31 and 32.

Cor. is 164 ft. above standard cor.

Land, rolling mountainous.

Soil, dark, sandy, clay loam; subsoil, same; 2nd and 3rd  
rate.

Vegetation, sage and grass.

Timber, pine, fir, aspen and balsam.

From the cor. of secs. 29, 30, 31 and 32,

N.  $0^{\circ} 01' E.$ , bet. secs. 29 and 30.

Over rough, mountainous land; ascend through heavy tim-  
ber.


1.70 Top of spur, bears W., 20 ft. above sec. cor.; descend.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

25.70 Road, bears E. and W.; in head of hollow, course S.;  
15 ft. below spur; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap,  
mkd.



from which

An aspen, 4 ins. dia., bears S. 50° E., 68 lks.  
dist., mkd.  $\frac{1}{2}$  S 29 B T.

An aspen, 6 ins. dia., bears S. 10° W., 24 lks.  
dist., mkd.  $\frac{1}{2}$  S 30 B T.


Cor. 50 ft. above draw.

56.00 Spur, bears W., 217 ft. above  $\frac{1}{2}$  cor.; descend abruptly.


74.50 Draw, course W., 287 ft. below spur; ascend very gently.

75.67 Intersect line 10-11, Tract 39, at a point, 6.74 chs.,  
E. of cor. No. 11.

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for closing cor. of frac. secs. 29 and 30,  
with brass cap, mkd.



80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in  
the ground, for resurvey cor. of secs. 19, 20, 29 and  
30, with brass cap, mkd.



from which

A pine, 6 ins. dia., bears N. 32 $\frac{1}{2}$ ° E., 50 lks.  
dist., mkd. T 13 N R 86 W S 20 B T.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

- A pine, 5 ins. dia., bears S.  $68\frac{1}{2}^{\circ}$  E., 87 lks.  
dist., mkd. T 13 N R 86 W S 29 B T.
- A pine, 8 ins. dia., bears S.  $61^{\circ}$  W., 132 lks.  
dist., mkd. T 13 N R 86 W S 30 B T.
- A pine, 12 ins. dia., bears N.  $65^{\circ}$  W., 156 lks.  
dist., mkd. T 13 N R 86 W S 19 B T.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, grass.

Timber, aspen and pine.

West, on a random line, bet. secs. 19 and 30.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.02 Intersect the W. bdy. of the Tp., 7 lks. S. of the resurvey cor. of secs. 19, 24, 25 and 30, previously described.

Thence


S.  $89^{\circ} 57'$  E., on a true line, bet. secs. 19 and 30.

Over rough, mountainous land; ascend along slopes, south of the South Fork of Battle Creek; through timber.

2.00 Dry gulch, course N.  $70^{\circ}$  W.; thence along bottom of gulch.

31.00 Leave gulch, from NE.; ascend gradually.

40.01 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



from which

An aspen, 6 ins. dia., bears N.  $1^{\circ}$  E., 87 lks.  
dist., mkd.  $\frac{1}{4}$  S 19 B T.

An aspen, 6 ins. dia., bears S.  $13^{\circ}$  W., 54 lks.  
dist., mkd.  $\frac{1}{4}$  S 30 B T.

Cor. 124 ft. above gulch.

47.00 Top of ascent, 66 ft. above  $\frac{1}{4}$  cor.; descend gradually.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

## Chains.

73.28 Intersect line 11-12, Tract 39, at a point, 4.33 chs.,  
N. of Cor. No. 11.

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for closing cor. of frac. secs. 19 and 30,  
with brass cap, mkd.

T13N	R86W
S19	
CO	TR39
S30	
	1919

78.80 Road, bears NE. and SW.

80.02 The cor. of secs. 19, 20, 29 and 30.

Land, rough mountainous.

Soil, black, sandy, clay loam; subsoil, same; 2nd rate.

Vegetation, grass.

Timber, aspen and pine.

N. 0° 01' E., bet. secs. 19 and 20.

Over rolling mountainous land; ascend gently, through  
dense timber.

15.67 Intersect line 12-13, Tract 39, at a point, 6.74 chs.,  
E. of cor. No. 12.

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for closing cor. of frac. secs. 19 and 20,  
with brass cap, mkd.

T13N	R86W
C C	
S19	S20
	TR39
	1919

26.70 Divide, between Battle Creek and Roaring Fork Creek,  
bears E. and S. 10° W.; 175 ft. above sec. cor.; desc.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap,  
mkd.

	$\frac{1}{2}$
S19	S20
	1919

from which

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.


Chains.

A pine, 10 ins. dia., bears E., 2 lks. dist.,  
mkd.  $\frac{1}{4}$  S 20 B T.

An aspen, 6 ins. dia., bears N. 70° W., 23 lks.  
dist., mkd.  $\frac{1}{4}$  S 19 B T.

46.00 Gulch, course SE., 80 ft. below spur; ascend.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in  
the ground, for resurvey cor. of secs. 17, 18, 19 and  
20, with brass cap, mkd.



from which

A pine, 18 ins. dia., bears S. 55° W., 2 lks.  
dist., mkd. T 13 N R 86 W S 19 B T.

Cor. 325 ft. above gulch.

Land, rough mountainous.

Soil, stony, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, grass.

Timber, aspen and pine.

N. 89° 57' W., on a random line, bet. secs. 18 and 19.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the W. bdy. of the Tp., 7 lks. N. of the re-  
survey cor. of secs. 13, 18, 19 and 24, previously de-  
scribed.

Thence

East, on a true line, bet. secs. 18 and 19.


Over rough, mountainous land; descend abruptly; through  
heavy timber.

27.50 Battle Creek, course SW., 350 ft. below sec. cor.;  
ascend very abrupt, broken NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap,  
mkd.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.



raise a mound of stone, 3 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

Cor. on broken, NW. slope, 360 ft. above creek.

77.00 Divide, between Battle Creek and Roaring Fork Creek, bears S.  $70^\circ$  W. and N.  $70^\circ$  E., 875 ft. above creek; descend.

80.00 The cor. of secs. 17, 18, 19 and 20.

Cor. is 95 ft. below ridge.

Land, rough mountainous.

Soil, sandy, clay loam; subsoil, same; 2nd and 3rd rate.

Timber, aspen and pine.

---


N.  $0^\circ 01'$  E., bet. secs. 17 and 18.

Over rough, mountainous land; ascend through heavy timber.

2.00 Top of divide, between Battle Creek and Roaring Fork Creek, bears NE. and SW.; descend.

38.40 Battle Creek, 50 lks. wide, 8 ins. deep, course SW.; 700 ft. below divide.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.




raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Ascend abruptly; through heavy timber.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for resurvey cor. of secs. 7, 8, 17 and 18, with brass cap, mkd.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.



from which

A pine, 12 ins. dia., bears N.  $46^{\circ}$  E., 23 lks.  
dist., mkd. T 13 N R 86 W S 8 B T.

A pine, 14 ins. dia., bears S.  $27\frac{1}{2}^{\circ}$  E., 68 lks.  
dist., mkd. T 13 N R 86 W S 17 B T.

An aspen, 10 ins. dia., bears N.  $28\frac{3}{4}^{\circ}$  W., 23 lks.  
dist., mkd. T 13 N R 86 W S 7 B T.

Cor. is 510 ft. above creek.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, grass, sage and willows.

Timber, pine and aspen.

West, on a random line, bet. sec's. 7 and 18.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.


79.98 Intersect the W. bdy. of the Tp., 23 lks. S. of the re-  
survey cor. of sec's. 7, 12, 13 and 18, previously de-  
scribed.

Thence

S.  $89^{\circ} 50'$  E., on a true line, bet. sec's. 7 and 18.Over rough, mountainous land; descend through heavy tim-  
ber.

17.00 Gulch, course S.; 87 ft. below sec. cor.; ascend.

39.99 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap,  
mkd..



from which

A pine, 8 ins. dia., bears N.  $14^{\circ}$  W., 62 lks.  
dist., mkd.  $\frac{1}{4}$  S 7 B T.

A fir, 7 ins. dia., bears S.  $69\frac{1}{2}^{\circ}$  W., 121 lks.  
dist., mkd.  $\frac{1}{4}$  S 18 B T.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

42.00 Top of spur, bears SW., 300 ft. above gulch; descend.

79.98 The cor. of secs. 7, 8, 17 and 18.

Cor. 550 ft. below spur.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, grass, chokecherry, service and sagebrush.

Timber, aspen, balsam, fir and pine.

N. 0° 01' E., bet. secs. 7 and 8.

Over rough, mountainous land; ascend through heavy timber.

17.50 Top of spur, bears SE., 230 ft. above sec. cor.; descend.

22.70 Head of draw, course SE., 10 ft. below spur; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



from which


A pine, 6 ins. dia., bears N.  $28\frac{1}{2}^{\circ}$  E., 218 lks. dist., mkd.  $\frac{1}{4}$  S 8 B T.

Dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

Cor. on top of large spur, bears N. and SW.; 160 ft. above head of draw.

Thence along gentle W. slope of spur.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for resurvey cor. of secs. 5, 6, 7 and 8, with brass cap, mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rough mountainous.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Soil, rocky, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, sage and grass.

Timber, pine and aspen.

N. 89° 50' W., on a random line, bet. secs. 6 and 7.

40.00 Set temp.  $\frac{1}{2}$  sec. cor.

79.96 Intersect the W. bdy. of the Tp., 13 lks. N. of the resurvey cor. of secs. 1, 6, 7 and 12, previously described.


Thence

S. 89° 55' E., on a true line, bet. secs. 6 and 7.

Over rough, mountainous land; descend through timber.

33.00 Divide, between Battle Creek and West Fork of Battle Creek, bears NE. and SW.

39.98 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



from which

An aspen, 6 ins. dia., bears N. 5° W., 32 lks. dist., mkd.  $\frac{1}{2}$  S 6 B T.

An aspen, 7 ins. dia., bears S. 12° E., 45 lks. dist., mkd.  $\frac{1}{2}$  S 7 B T.

56.00 Gulch, course SW., 235 ft. below  $\frac{1}{2}$  cor.; ascend.

79.96 The cor. of secs. 5, 6, 7 and 8.

Cor. is 170 ft. above creek.  
Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, sage and grass.

Timber, pine and aspen.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.


Chains.

N. 0° 01' E., on a true line, bet. secs. 5 and 6.

Over rough, mountainous land; descend through scattering timber.

22.50 Head of gulch, course SW., 50 ft. below sec. cor.; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.


Cor. on top of divide, between forks of Battle Creek, bears SW. and NE., 50 ft. above gulch.

52.00 Head of gulch, course W.; ascend.

65.00 Point of spur, bears W.; descend.

86.08 Intersect the S. bdy. of T. 14 N., R. 86 W., at a point, S. 89° 22' E., 4.44 chs., from the restored cor. of secs. 31 and 32, previously described.

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap, mkd.



from which

A pine, 4 ins. dia., bears S. 21° E., 23 lks. dist., mkd. CC T 13 N R 86 W S 5 B T.

A pine, 4 ins. dia., bears S. 52 1/2° W., 38 lks. dist., mkd. CC T 13 N R 86 W S 6 B T.

Land, rough mountainous.

Soil, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, sage and grass. Timber, pine and aspen.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

From the cor. of secs. 28, 29, 32 and 33,  
S. 0° 02' W., on a true line, bet. secs. 32 and 33.  
Over rough, mountainous land; descend.


6.30 Roaring Fork Creek, 3 lks. wide, 3 ins. deep, course SE.,  
20 ft. below sec. cor.; ascend.

17.40 Top of spur, bears SE., 40 ft. above creek; descend.

31.67 Fence, bears E. and W.

36.61 Fence, bears E. and W.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap,  
mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
of cor.

59.14 Roaring Fork Creek, 5 lks. wide, 6 ins. deep, course SW.,  
190 ft. below spur; ascend.

78.98 Intersect the Third Standard Parallel North, at the  
closing cor. of secs. 32 and 33, which is identical  
with the cor. of secs. 4 and 5, resurvey T. 12 N., R.  
86 W., described in field notes of reestablishment of  
the Third Standard Parallel North, Group 31. This cor.  
bears N. 89° 42' E., 80.36 chs. from the reestablished  
standard cor. of secs. 5, 6, 31 and 32.

Land, rough mountainous.

Soil, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, grass and sagebrush.

Timber, pine and aspen.

From the cor. of secs. 28, 29, 32 and 33,

N. 0° 02' E., bet. secs. 28 and 29.


Over rolling mountainous land; ascend gradually, through  
heavy timber.

Independent Resurvey of the Subdivisions of T. 13 N., R. 86 W.

Chains.

10.00 Spur, bears W.; descend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



from which

A pine, 10 ins. dia., bears S.  $33\frac{1}{2}^{\circ}$  E., 46 lks. dist., mkd.  $\frac{1}{2}$  S 28 B T.


A pine, 10 ins. dia., bears S.  $18^{\circ}$  W., 30 lks. dist., mkd.  $\frac{1}{2}$  S 29 B T.

52.00 Branch Roaring Fork Creek, 30 lks. wide, 6 ins. deep, course SW.; ascend.

59.00 School House, bears E., 125 lks. dist.

60.60 Road, bears NW. and SE.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 10 ins. in the ground, on underlying rock, surrounded by a mound of stone, for resurvey cor. of secs. 20, 21, 28 and 29, with brass cap, mkd.



from which

A pine, 10 ins. dia., bears N.  $49\frac{1}{2}^{\circ}$  E., 102 lks. dist., mkd. T 13 N R 86 W S 21 B T.

A pine, 5 ins. dia., bears S.  $36\frac{1}{2}^{\circ}$  E., 114 lks. dist., mkd. T 13 N R 86 W S 28 B T.

An aspen, 6 ins. dia., bears S.  $50^{\circ}$  W., 174 lks. dist., mkd. T 13 N R 86 W S 29 B T.

A pine, 12 ins. dia., bears N.  $34\frac{1}{2}^{\circ}$  W., 77 lks. dist., mkd. T 13 N R 86 W S 20 B T.

Land, rolling mountainous.

Soil, sandy, clay loam; subsoil, same; 3rd rate.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Vegetation, sage, grass and willows.  
Timber, pine and aspen.

West, on a random line, bet. secs. 20 and 29.

40.00 Set temp. 1/4 sec. cor.


80.08 Intersect the N. and S. line, 9 lks. S. of the cor. of  
secs. 19, 20, 29 and 30.

Thence

S. 89° 56' E., on a true line, bet. secs. 20 and 29.  
Over rolling mountainous land; descend through heavy  
timber.

2.00 Top of divide, bet. Roaring Fork and Battle Creeks,  
bears N. and S.

40.04 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey 1/4 sec. cor., with brass cap,  
mkd.



from which

A pine, 8 ins. dia., bears N. 30° W., 53 lks.  
dist., mkd. 1/4 S 20 B T.


A pine, 8 ins. dia., bears S. 5° W., 275 lks.  
dist., mkd. 1/4 S 29 B T.

48.50 Spring branch, course SE.

58.00 West Fork of Roaring Fork Creek, 5 lks. wide, 7 ins. deep,  
course S., 60 ft. below 1/4 cor.; ascend.

63.26 Intersect line 5-6, Tract 39, at a point, 0.69 chs., S.  
of cor. No. 5.

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for closing cor. of frac. secs. 20 and 29,  
with brass cap, mkd.



Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

- 70.00 Road, bears N. and S.
- 75.00 Roaring Fork Creek, 15 lks. wide, 8 ins. deep, course SW., 100 ft. below  $\frac{1}{4}$  sec. cor.; ascend.
- 80.08 The cor. of secs. 20, 21, 28 and 29.  
Land, rough mountainous and rolling mountainous.  
Soil, stony, sandy, dark, clay loam; subsoil, same; 2nd and 3rd rate.  
Vegetation, grass, sage, chokecherry and willows.  
Timber, aspen, pine and balsam fir.

N. 0° 02' E., bet. secs. 20 and 21.

Over rolling mountainous land; descend gradually over N. slope; through heavy timber.

- 20.30 Roaring Fork Creek, 10 lks. wide, 6 ins. deep, course SW.; 10 ft. below sec. cor.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.




from which

A pine, 10 ins. dia., bears S. 65° E., 42 lks. dist., mkd.  $\frac{1}{4}$  S 21 B T.

A pine, 10 ins. dia., bears S. 60 $\frac{1}{2}$ ° W., 23 lks. dist., mkd.  $\frac{1}{4}$  S 20 B T.

Cor. 32 ft. above creek.

- 57.10 Road, bears SW. and NE.
- 57.20 Spring branch, 3 lks. wide, 3 ins. deep, course W.
- 62.50 Irrigation ditch, 3 lks. wide, 8 ins. deep, course NW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for resurvey cor. of secs. 16, 17, 20 and 21, with brass cap, mkd.



from which

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

## Chains.

A pine, 5 ins. dia., bears N.  $54^{\circ}$  E., 8 lks.

dist., mkd. T 13 N R 86 W S 16 B T.

An aspen, 4 ins. dia., bears S.  $19\frac{1}{2}^{\circ}$  E., 42 lks.

dist., mkd. T 13 N R 86 W S 21 B T.

A pine, 7 ins. dia., bears S.  $62^{\circ}$  W., 40 lks.

dist., mkd. T 13 N R 86 W S 20 B T.

A pine, 7 ins. dia., bears N.  $22^{\circ}$  W., 5 lks.

dist., mkd. T 13 N R 86 W S 17 B T.

Cor. is 202 ft. above  $\frac{1}{2}$  cor.

Land, rolling mountainous.

Soil, light, gravelly, dark, clay loam; subsoil, same;  
2nd and 3rd rate.

Vegetation, sage, chokecherry, service and grass.

Timber, aspen, pine and balsam fir.

N.  $89^{\circ} 56'$  W., on a random line, bet. secs. 17 and 20.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.10 Intersect N. and S. line, 5 lks. N. of the cor. of secs.  
17, 18, 19 and 20.

Thence


S.  $89^{\circ} 58'$  E., on a true line, bet. secs. 17 and 20.

Over rolling mountainous land; descend through heavy  
timber.

24.70 Gulch, course SE., 247 ft. below sec. cor.; ascend.

37.50 Spur, bears S., 46 ft. above gulch; descend.

40.05 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap,  
mkd.



Cor. 30 ft. below spur.

60.00 Gulch, course SE., 90 ft. below  $\frac{1}{4}$  cor.; ascend.

80.10 The cor. of secs. 16, 17, 20 and 21.

Cor. 132 ft. above gulch.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Land, rolling mountainous.  
 Soil, dark, sandy, clay loam; subsoil, same; 2nd and 3rd rate.  
 Vegetation, sage, chokecherry and grass.  
 Timber, pine, balsam, fir and aspen.

N. 0° 02' E., bet. secs. 16 and 17.

Over rolling, mountainous land; ascend through heavy timber.

34.50 Top of divide, between Battle Creek and Roaring Fork Creek, bears NE. and SW., 450 ft. above sec. cor.; descend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.




from which

An aspen, 4 ins. dia., bears S.  $78\frac{1}{2}^\circ$  E., 13 lks. dist., mkd.  $\frac{1}{2}$  S 16 B T.

A fir, 8 ins. dia., bears S.  $45\frac{3}{4}^\circ$  W., 93 lks. dist., mkd.  $\frac{1}{2}$  S 17 B T.

Cor. on gentle NW. slope of ridge; descend N. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for resurvey cor. of secs. 8, 9, 16 and 17, with brass cap, mkd.



from which

A pine, 6 ins. dia., bears N.  $45\frac{1}{2}^\circ$  E., 30 lks. dist., mkd. T 13 N R 86 W S 9 B T.

A pine, 7 ins. dia., bears S.  $51^\circ$  E., 18 lks. dist., mkd. T 13 N R 86 W S 16 B T.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

A pine, 6 ins. dia., bears S. 80° W., 6 lks.

dist., mkd. T 13 N R 86 W S 17 B T.

A pine, 9 ins. dia., bears N. 10½° W., 18 lks.

dist., mkd. T 13 N R 86 W S 8 B T.

Cor. 314 ft. below ¼ cor.

Land, rolling mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 2nd to 4th rate.

Vegetation, grass, sage, chokecherry and service brush.

Timber, pine, aspen and balsam.

N. 89° 58' W., on a random line, bet. secs. 8 and 17.

40.00 Set temp. ¼ sec. cor.

80.04 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 7, 8, 17 and 18.


Thence

East, on a true line, bet. secs. 8 and 17.

Over rough, mountainous land; descend through heavy timber.

35.20 Battle Creek, 30 lks. wide, 16 ins. deep, course S.

40.02 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey ¼ sec. cor., with brass cap, mkd.



80.04 The cor. of secs. 8, 9, 16 and 17.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 3rd and 4th rate.

Vegetation, sage, grass, willows and service brush.

Timber, pine, aspen and balsam.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.


## Chains.

N.  $0^{\circ} 02'$  E., bet. secs. 8 and 9.

Over rolling mountainous land; descend through heavy timber.

20.00 Gulch, course W.; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



from which

A fir, 6 ins. dia., bears S.  $47^{\circ}$  E., 16 lks.

dist., mkd.  $\frac{1}{4}$  S 9 B T.

A pine, 12 ins. dia., bears S.  $45\frac{1}{2}^{\circ}$  W., 66 lks.

dist., mkd.  $\frac{1}{4}$  S 8 B T.

58.75 Top of spur, bears W.; descend.

74.40 Battle Creek, 15 lks. wide, 8 ins. deep, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for resurvey cor. of secs. 4, 5, 8 and 9, with brass cap, mkd.



from which

A pine, 8 ins. dia., bears N.  $3\frac{1}{2}^{\circ}$  E., 33 lks.

dist., mkd. T 13 N R 86 W S 4 B T.

An aspen, 6 ins. dia., bears S.  $11\frac{1}{2}^{\circ}$  E., 38 lks.

dist., mkd. T 13 N R 86 W S 9 B T.

A pine, 10 ins. dia., bears S.  $44\frac{1}{2}^{\circ}$  W., 48 lks.

dist., mkd. T 13 N R 86 W S 8 B T.

A pine, 12 ins. dia., bears N.  $63^{\circ}$  W., 43 lks.

dist., mkd. T 13 N R 86 W S 5 B T.

Land, rolling mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 3rd and 4th rate.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Vegetation, grass, sage, chokecherry, willows and service.  
Timber, pine, balsam, fir and aspen.

West, on a random line, bet. secs. 5 and 8.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.


80.00 Intersect N. and S. line, 12 lks. S. of the cor. of secs.  
5, 6, 7 and 8.

Thence

S.  $89^{\circ} 55'$  E., on a true line, bet. secs. 5 and 8.

Over rolling mountainous land; descend E. slope; through  
scattering timber.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap,  
mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N.  
of cor.

Cor. on spur, slopes S., 260 ft. below sec. cor.; descend  
abruptly.

61.10 Middle Fork of Battle Creek, 30 lks. wide, 8 ins. deep,  
course S.  $15^{\circ}$  W., 380 ft. below spur; ascend.

80.00 The cor. of secs. 4, 5, 8 and 9.

Cor. 160 ft. above creek.

Land, rolling mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, sage, grass, service and chokecherry brush.

Timber, pine and aspen.

N.  $0^{\circ} 02'$  E., on a true line, bet. secs. 4 and 5.

Over rough, broken mountainous land; ascend through  
heavy timber.

2.00 Top of spur, bears W., 30 ft. above sec. cor.; descend.


16.20 Middle Fork of Battle Creek, 25 lks. wide, 6 ins. deep,

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

course SW., 75 ft. below spur; ascend.

- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.




from which

A fir, 12 ins. dia., bears N.  $53\frac{1}{2}^{\circ}$  E., 68 lks.  
dist., mkd.  $\frac{1}{4}$  S 4 B T.

A fir, 12 ins. dia., bears N.  $12\frac{1}{2}^{\circ}$  W., 42 lks.  
dist., mkd.  $\frac{1}{4}$  S 5 B T.

- 85.10 Intersect the S. bdy. of T. 14 N., R. 86 W., at a point, N.  $89^{\circ} 12'$  E., 4.92 chs., from the restored cor. of secs. 32 and 33, previously described.

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap, mkd.



from which

A pine, 12 ins. dia., bears S.  $35^{\circ}$  E., 18 lks.  
dist., mkd. CCT13 N R 86 W S 4 B T.

A pine, 6 ins. dia., bears S.  $50^{\circ}$  W., 58 lks.  
dist., mkd. CCT13 N R 86 W S 5 B T

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, sage, grass, willows, chokecherry and service brush.

Timber, aspen, pine and balsam fir.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

## Chains.

From the cor. of secs. 27, 28, 33 and 34,


S.  $0^{\circ} 02' W.$ , on a true line, bet. secs. 33 and 34.

Over rough, mountainous land; ascend through heavy timber.

14.30 Spur, bears W., 292 ft. above sec. cor.; descend across swale; thence ascend along W. slope of ridge.

38.80 Spur, slopes SW., 156 ft. above last spur; descend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor.; with brass cap, mkd.



from which

A fir, 14 ins. dia., bears S.  $53^{\circ} E.$ , 25 lks.

dist., mkd.  $\frac{1}{4}$  S 34 B T.

A fir, 14 ins. dia., bears S.  $25\frac{1}{2}^{\circ} W.$ , 12 lks.

dist., mkd.  $\frac{1}{4}$  S 33 B T.

60.80 Road, bears NE. and SW.

65.00 Small spring branch, course SW., 310 ft. below spur; ascend.

78.56 Intersect the Third Standard Parallel North, at the closing cor. for secs. 33 and 34, which is identical with the cor. of secs. 3 and 4, resurvey T. 12 N., R. 86 W.; described in field notes of the reestablishment of the Third Standard Parallel North, Group 31. This cor. bears S.  $89^{\circ} 42' W.$ , 118.25 chs. from angle point on S. bdy. Sec. 35, marking position of original standard  $\frac{1}{4}$  cor. for secs. 2 and 35.

Land, rough mountainous.

Soil, stony, sandy, clay loam; subsoil, same; 2nd and 3rd rate.

Vegetation, grass, service and chokecherry brush.

Timber, aspen, pine and balsam fir.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W

## Chains.

From the cor. of secs. 27, 28, 33 and 34,

N.  $0^{\circ} 02'$  E., bet. secs. 27 and 28.

Over rough mountainous land; descend through heavy timber.

- 3.85 Small spring branch, course W.  
 5.65 Small spring branch, course W.  
 9.35 Creek, 3 lks. wide, 2 ins. deep, course SW.; ascend,  
 22.30 Top of spur, bears W., 27 ft. above creek; descend.  
 28.20 Draw, course W.; 80 ft. below spur; ascend.  
 35.80 Small spur, bears W., 85 ft. above draw; descend.  
 38.10 Spring branch, course W., 40 ft. below spur; descend.  
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
 the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap,  
 mkd.




from which

An aspen, 6 ins. dia., bears N.  $25\frac{1}{2}^{\circ}$  W., 20 lks.  
 dist., mkd.  $\frac{1}{2}$  S 28 B T.

An aspen, 8 ins. dia., bears S.  $23\frac{1}{2}^{\circ}$  E., 93 lks.  
 dist., mkd.  $\frac{1}{2}$  S 27 B T.

- 50.30 Creek, 3 lks. wide, 3 ins. deep, course W., 116 ft. be-  
 low  $\frac{1}{2}$  cor.; ascend.  
 71.30 Top of spur, slopes SW., 400 ft. above creek; ascend.  
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in  
 the ground, for resurvey cor. of secs. 21, 22, 27 and  
 28, with brass cap, mkd.



from which

An aspen, 6 ins. dia., bears N.  $49^{\circ}$  E., 20 lks.  
 dist., mkd. T 13 N R 86 W S 22 B T.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

An aspen, 6 ins. dia., bears S. 64° E., 10 lks. dist., mkd. T 13 N R 86 W S 27 B T.

An aspen, 6 ins. dia., bears S. 65° W., 43 lks. dist., mkd. T 13 N R 86 W S 28 B T.

An aspen, 6 ins. dia., bears N. 52° W., 21 lks. dist., mkd. T 13 N R 86 W S 21 B T.

Cor. on spur, bears SW., 100 ft. above last spur.

Land, rough mountainous.

Soil, sandy, clay loam; subsoil, same; 2nd and 3rd rate.

Vegetation, grass and chokecherry.

Timber, aspen and pine.

West, on a random line, bet. secs. 21 and 28.

40.00 Set temp. 1/4 sec. cor.


80.02 Intersect N. and S. line, 3 lks. N. of the cor. of secs. 20, 21, 28 and 29.

N. 89° 59' E., on a true line, bet. secs. 21 and 28.

Over rough, mountainous land; ascend through heavy timber.

36.00 Top of spur, bears SW.; descend.

40.01 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey 1/4 sec. cor., with brass cap, mkd.



from which

An aspen, 12 ins. dia., bears NE., 20 lks. dist., mkd. 1/4 S 21 B T.

An aspen, 12 ins. dia., bears SW., 11 lks. dist., mkd. 1/4 S 28 B T.

72.60 Dry gulch, course SW., 71 ft. below 1/4 cor.

80.02 The cor. of secs. 21, 22, 27 and 28.

Cor. 176 ft. above gulch.

Land, rough mountainous.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Soil, black, sandy, clay loam; subsoil, same; 2nd rate.


Vegetation, grass, ferns and chokecherry brush.

Timber, aspen and pine.

N. 0° 02' E., bet. secs. 21 and 22.

Over rough, mountainous land; ascend over ledges; through heavy timber.

- 1.20 Top of ascent; descend through sparse growth of timber.
- 8.00 Dry gulch, course SW., 20 ft. below top of ascent; ascend.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.




from which

A fir, 8 ins. dia., bears N.  $37\frac{1}{2}^\circ$  E., 30 lks. dist., mkd.  $\frac{1}{2}$  S 22 B T.

A pine, 6 ins. dia., bears N.  $37^\circ$  W., 81 lks. dist., mkd.  $\frac{1}{2}$  S 21 B T.

Cor. is 260 ft. above gulch.

- 42.20 Point of spur, bears W., 15 ft. above  $\frac{1}{2}$  cor.; descend through heavy pine.
- 69.50 Roaring Fork, 10 lks. wide, 6 ins. deep, course W., 530 ft. below spur; ascend.
- 78.10 Road, bears NE. and SW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for resurvey cor. of secs. 15, 16, 21 and 22, with brass cap, mkd.



from which

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

An aspen, 10 ins. dia., bears N.  $56\frac{1}{4}^{\circ}$  E., 62 lks.  
dist., mkd. T 13 N R 86 W S 15 B T.

An aspen, 6 ins. dia., bears S.  $57^{\circ}$  E., 22 lks.  
dist., mkd. T 13 N R 86 W S 22 B T.

An aspen, 6 ins. dia., bears S.  $22\frac{3}{4}^{\circ}$  W., 23 lks.  
dist., mkd. T 13 N R 86 W S 21 B T.

An aspen, 8 ins. dia., bears N.  $71^{\circ}$  W., 34 lks.  
dist., mkd. T 13 N R 86 W S 16 B T.

Cor. 160 ft. above creek.

Land, rough mountainous.

Soil, black, sandy, clay loam; subsoil, same; 2nd rate.

Vegetation, grass, service and huckleberry brush.

Timber, aspen, pine, balsam, fir and spruce.

S.  $89^{\circ} 59'$  W., on a random line, bet. secs. 16 and 21.

40.00 Set temp.  $\frac{1}{2}$  sec. cor.

80.04 Intersect N. and S. line, 10 lks. N. of the cor. of secs.  
16, 17, 20 and 21.

Thence


N.  $89^{\circ} 55'$  E., on a true line, bet. secs. 16 and 21.

Over rolling, mountainous land; descend through dense  
timber and undergrowth.

27.60 Road, bears NE. and SW.

32.50 Road, bears NW. and SE. (same road).

40.02 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap,  
mkd.



from which

An aspen, 5 ins. dia., bears S.  $03^{\circ}$  E., 28 lks.  
dist., mkd.  $\frac{1}{2}$  S 21 B T.

An aspen, 4 ins. dia., bears N.  $12^{\circ}$  W., 7 lks.  
dist., mkd.  $\frac{1}{2}$  S 16 B T.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

40.04 Road, bears N. and S.

80.04 The cor. of secs. 15, 16, 21 and 22.

Land, rolling mountainous.

Soil, stony, dark, sandy, clay loam; subsoil, same; 2nd rate.


Vegetation, sage, grass, service and chokecherry brush.

Timber, aspen, pine and balsam fir.

N. 0° 02' E., bet. secs. 15 and 16.

Over rough, mountainous land; ascend through heavy timber.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.




from which

A fir, 5 ins. dia., bears N.  $61\frac{1}{2}^\circ$  E., 37 lks. dist., mkd.  $\frac{1}{2}$  S 15 B T.

A fir, 4 ins. dia., bears S.  $82^\circ$  W., 11 lks. dist., mkd.  $\frac{1}{2}$  S 16 B T.

67.50 Divide, between Roaring Fork and Battle Creeks, bears E. and W., 115 ft. above  $\frac{1}{2}$  cor.; descend.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in a mound of stone, on solid ledge, for the resurvey cor. of secs. 9, 10, 15 and 16, with brass cap, mkd.



Cor. 210 ft. below ridge.

Land, rough and broken mountainous.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Soil, dark, sandy, clay loam; subsoil, same; 3rd and 4th rate.

Vegetation, sage, grass and chokecherry brush.

Timber, aspen, pine and balsam fir.

S. 89° 55' W., on a random line, bet. secs. 9 and 16.


40.00 Set temp.  $\frac{1}{2}$  sec. cor.

80.08 Intersect N. and S. line, 5 lks. S. of the cor. of secs. 8, 9, 16 and 17.

N. 89° 57' E., on a true line, bet. secs. 9 and 16.

Over rough mountainous N. slope; through heavy timber.

40.04 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



from which

A pine, 5 ins. dia., bears North, 31 lks. dist., mkd.  $\frac{1}{2}$  S 9 B T.

A pine, 10 ins. dia., bears South, 20 lks. dist., mkd.  $\frac{1}{2}$  S 16 B T.

50.00 Leave standing timber and enter fallen timber, bears N. and S.

80.08 The cor. of secs. 9, 10, 15 and 16.

Cor. is 431 ft. above  $\frac{1}{2}$  cor.

Land, rolling mountainous.

Soil, stony, sandy, clay loam; subsoil, same; 3rd and 4th rate.

Vegetation, sage and grass.

Timber, pine and aspen.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

N. 0° 02' E., bet. secs. 9 and 10.

Over rough, mountainous land; descend, broken rocky N. slope; through timber.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.




from which

A pine, 6 ins. dia., bears N. 44° E., 23 lks. dist., mkd.  $\frac{1}{4}$  S 10 B T.

A pine, 6 ins. dia., bears N. 35° W., 26 lks. dist., mkd.  $\frac{1}{4}$  S 9 B T.

Cor. is 475 ft. above sec. cor.; descend broken NW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for resurvey cor. of secs. 3, 4, 9 and 10, with brass cap, mkd.



from which

A pine, 15 ins. dia., bears N. 35° E., 40 lks. dist., mkd. T 13 N R 86 W S 3 B T.

A pine, 14 ins. dia., bears S. 62° E., 104 lks. dist., mkd. T 13 N R 86 W S 10 B T.

A fir, 8 ins. dia., bears S. 35° W., 16 lks. dist., mkd. T 13 N R 86 W S 9 B T.

A pine, 14 ins. dia., bears N. 33° W., 14 lks. dist., mkd. T 13 N R 86 W S 4 B T.

Cor. is 300 ft. below  $\frac{1}{4}$  cor.

Land, rough mountainous.

Soil, rocky, sandy loam; subsoil, same; 3rd and 4th rate.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Vegetation, grass.

Timber, pine, balsam, fir and aspen.

S. 89° 57' W., on a random line, bet. secs. 4 and 9.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.


79.94 Intersect N. and S. line, 21 lks. S. of the cor. of secs. 4, 5, 8 and 9.

Thence

S. 89° 54' E., on a true line, bet. secs. 4 and 9.

Over rough, mountainous S. slope; descend through timber.

39.97 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



from which

An aspen, 6 ins. dia., bears N. 54° E., 40 lks. dist., mkd.  $\frac{1}{4}$  S 4 B T.

An aspen, 6 ins. dia., bears S. 42° W., 22 lks. dist., mkd.  $\frac{1}{4}$  S 9 B T.

Cor. is 500 ft. below sec. cor.; descend SE. slope.

65.70 Battle Creek, 40 lks. wide, 3 ins. deep, course S. 70° W., 120 ft. below  $\frac{1}{2}$  cor.; ascend.

79.94 The cor. of secs. 3, 4, 9 and 10.

Cor. is 210 ft. above creek.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, sage, grass, willows, chokecherry and service.

Timber, pine, balsam, fir and aspen.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

N.  $0^{\circ} 02'$  E., on a true line, bet. secs. 3 and 4.

Over rough, mountainous land, NW. slope; through heavy timber.

6.40 Battle Creek, 15 lks. wide, 8 ins. deep, course SW.; 35 ft. below sec. cor.; ascend steep SW. slope.

40.00 Blaze and mark on E. and W. faces of a pine tree, 10 ins. dia., 50 ft. high, for resurvey  $\frac{1}{4}$  sec. cor. as follows.

$\frac{1}{4}$	$\frac{1}{4}$
S	S
4	3
B	B
T	T
1	1
9	9
1	1
9	9

from which


A pine, 6 ins. dia., bears N.  $45^{\circ}$  E., 20 lks. dist., mkd.  $\frac{1}{4}$  S 3 B T.

A pine, 6 ins. dia., bears N.  $87^{\circ}$  W., 18 lks. dist., mkd.  $\frac{1}{4}$  S 4 B T.

83.79 Cor. on top of ridge, bears NE. and SW., 280 ft. above creek. Intersect the S. bdy. of T. 14 N., R. 86 W., at a point,

East, 5.10 chs., of angle point, marking reestablished position of original cor. of secs. 3, 4, 33 and 34, previously described.

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for closing cor. of secs. 3, and 4, with brass cap, mkd.



from which

A fir, 6 ins. dia., bears S.  $15^{\circ}$  E., 16 lks. dist., mkd. CC T 13 N R 86 W S 3 B T.

A fir, 4 ins. dia., bears S.  $80^{\circ}$  W., 26 lks. dist., mkd. CC T 13 N R 86 W S 4 B T.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

The closing cor. of secs. 33 and 34, T. 14 N., R. 86 W., bears West, 4.25 chs. dist.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, grass, willows, chokecherry and service brush.

Timber, pine balsam, fir and aspen.


From the cor. of secs. 26, 27, 34 and 35,

S.  $0^{\circ} 03'$  W., on a true line, bet. secs. 34 and 35.

Over rough, mountainous land; descend through heavy timber.

31.50 Small spring branch, course SE., 525 ft. below sec. cor.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



from which

An aspen, 6 ins. dia., bears S.  $48\frac{1}{2}^{\circ}$  E., 45 lks. dist., mkd.  $\frac{1}{2}$  S 35 B T.

An aspen, 6 ins. dia., bears S.  $30\frac{3}{4}^{\circ}$  W., 27 lks. dist., mkd.  $\frac{1}{2}$  S 34 B T.

Cor. is 555 ft. below sec. cor.

65.10 Gulch, course SW., 163 ft. below  $\frac{1}{2}$  cor.; ascend.

68.60 Small spur, bears SW., 30 ft. above gulch; descend.

78.11 Intersect the Third Standard Parallel North, at the closing cor. of secs. 34 and 35, which is identical with the cor. of secs. 2 and 3, resurvey T. 12 N., R. 86 W., described in the field notes of the reestablishment of the Third Standard Parallel/ <sup>North,</sup> Group 31. This cor. is 38.38 chs., S.  $89^{\circ} 42'$  W., from the angle point on S. bdy. Sec. 35, marking the position of original standard  $\frac{1}{2}$  cor. for secs. 2 and 35.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

## Chains.

Land, rough mountainous.

Soil, black, sandy, clay loam; subsoil, same; 2nd rate.

Vegetation, sage, grass, chokecherry and service brush.

Timber, aspen and pine.

From the cor. of secs. 26, 27, 34 and 35,

N.  $0^{\circ} 03'$  E., bet. secs. 26 and 27.

Over rough, mountainous land; ascend through heavy timber.

6.70 Small spring branch, course SE.; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 14 ins. in the ground, on underlying ledge, surrounded by a mound of stone, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



Cor. on top of ridge, bears N. and SW., 630 ft. above sec. cor.; ascend along top of ridge.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 10 ins. in the ground, on underlying ledge, surrounded by a mound of stone, for resurvey cor. of secs. 22, 23, 26 and 27, with brass cap, mkd.



from which

A pine, 10 ins. dia., bears N.  $17\frac{3}{4}^{\circ}$  E., 119 lks.  
dist., mkd. T 13 N R 86 W S 23 B T.

A pine, 10 ins. dia., bears S.  $54^{\circ}$  E., 108 lks.  
dist., mkd. T 13 N R 86 W S 26 B T.

A pine, 10 ins. dia., bears S.  $80^{\circ}$  W., 37 lks.  
dist., mkd. T 13 N R 86 W S 27 B T.

A pine, 12 ins. dia., bears N.  $45^{\circ}$  W., 167 lks.  
dist., mkd. T 13 N R 86 W S 22 B T.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Cor. on top of ridge; 90 ft. above  $\frac{1}{2}$  cor.

Land, rough mountainous.

Soil, stony, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, grass, service and berry brush.

Timber, aspen, pine and balsam fir.

West, on a random line, bet. secs. 22 and 27.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.02 Intersect N. and S. line, 12 lks. S. of the cor. of secs. 21, 22, 27 and 28.

Thence


S.  $89^{\circ} 55'$  E., on a true line, bet. secs. 22 and 27.

Over rough, mountainous land; ascend through timber.

6.80 Top of spur, bears SW., 92 ft. above sec. cor.; descend.

31.50 Creek, 3 lks. wide, 2 ins. deep, course SW., 350 ft. below spur; ascend.

40.01 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the ground, on underlying rock, surrounded by a mound of stone, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



from which

An aspen, 6 ins. dia., bears N.  $10^{\circ}$  W., 11 lks. dist., mkd.  $\frac{1}{4}$  S 22 B T.

A pine, 8 ins. dia., bears S.  $30^{\circ}$  W., 19 lks. dist., mkd.  $\frac{1}{4}$  S 27 B T.

Cor. 222 ft. above creek.

80.02 The cor. of secs. 22, 23, 26 and 27.

Land, rough mountainous.

Soil, black, sandy, clay loam; subsoil, same; 2nd and 1st rate.

Vegetation, grass and chokecherry.

Timber, aspen and pine.


## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

## Chains.

N.  $0^{\circ} 03'$  E., bet. secs. 22 and 23.

Over rough, mountainous land, on top of ridge; descend through fallen and standing timber.

- 8.00 Leave top of ridge, bears S. and NE.; descend abruptly.  
 35.00 Gulch, course W., 400 ft. below sec. cor.; ascend.  
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



from which

An aspen, 6 ins. dia., bears East, 4 lks. dist.,  
 mkd.  $\frac{1}{4}$  S 23 B T.

A pine, 10 ins. dia., bears West, 13 lks. dist.,  
 mkd.  $\frac{1}{4}$  S 22 B T.

Cor. 90 ft. above gulch.

- 54.00 Top of spur, bears W., 350 ft. above  $\frac{1}{4}$  cor.; descend.  
 77.30 Creek, 7 lks. wide, 6 ins. deep, course W., 423 ft. below spur; ascend.  
 78.35 Road, bears E. and W.  
 80.00 Set an iron post, 3 ft. long, 1 in. dia., 4 ins. in the ground, on underlying rock, surrounded by a mound of stone, for resurvey cor. of secs. 14, 15, 22 and 23, with brass cap, mkd.



from which

A pine, 10 ins. dia., bears N.  $33^{\circ}$  E., 54 lks. dist., mkd. T 13 N R 86 W S 14 B T.

A pine, 16 ins. dia., bears S.  $5\frac{1}{2}^{\circ}$  E., 62 lks. dist., mkd. T 13 N R 86 W S 23 B T.

A pine, 6 ins. dia., bears S.  $23^{\circ}$  W., 56 lks. dist., mkd. T 13 N R 86 W S 22 B T.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

A pine, 12 ins. dia., bears N. 34° W., 60 lks. dist., mkd. T 13 N R 86 W S 15 B T.

Cor. is 8 ft. above creek.

Land, rough mountainous.

Soil, stony, sandy, clay loam; subsoil, same; 2nd rate.

Vegetation, grass, service and berry brush.

Timber, pine, aspen, spruce and balsam fir.

N. 89° 55' W., on a random line, bet. secs. 15 and 22.

40.00 Set temp. 1/4 sec. cor.

79.95 Intersect N. and S. line, 12 lks. S. of the cor. of secs. 15, 16, 21 and 22.


Thence

S. 89° 50' E., on a true line, bet. secs. 15 and 22.

Over rough mountainous land; ascend along S. slope and creek bottom of Roaring Fork Creek; through dense undergrowth and timber.

5.00 Road, bears NE. and SW.

39.97 1/2 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey 1/4 sec. cor., with brass cap, mkd.



from which

A spruce, 6 ins. dia., bears N. 55° W., 23 lks. dist., mkd. 1/4 S 15 B T.

A spruce, 6 ins. dia., bears S. 20° E., 69 lks. dist., mkd. 1/4 S 22 B T.

Cor. is 140 ft. above sec. cor.

43.50 Roaring Fork Creek, 20 lks. wide, 6 ins. deep, comes from the East and flows S. 70° W.; from this point, ascend up creek.

66.30 Leave creek, course N. 70° W.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

79.95 The cor. of secs. 14, 15, 22 and 23.

Cor. is 290 ft. above  $\frac{1}{4}$  cor.

Land, rough mountainous.

Soil, rocky, black, sandy, clay loam; subsoil, same; 1st and 2nd rate.

Vegetation, grass, chokecherry, willows and service.

Timber, aspen, pine, spruce and balsam fir.

N. 0° 03' E., bet. secs. 14 and 15.

Over rough, rocky, mountainous land; ascend through heavy timber.

28.10 Short spur, bears W., 492 ft. above sec. cor.; descend slightly.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the ground, on underlying rock, surrounded by a mound of stone, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



from which


A spruce, 14 ins. dia., bears S. 54° E., 83 lks. dist., mkd.  $\frac{1}{2}$  S 14 B T.

A spruce, 12 ins. dia., bears S. 84 $\frac{1}{2}$ ° W., 57 lks. dist., mkd.  $\frac{1}{2}$  S 15 B T.

Cor. is 17 ft. below spur.

53.70 Creek, 3 lks. wide, 2 ins. deep, course SW., 150 ft. below  $\frac{1}{2}$  cor.; ascend.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in mound of stone, for resurvey cor. of secs. 10, 11, 14 and 15, with brass cap, mkd.



from which

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

A fir, 10 ins. dia., bears N. 60° E., 33 lks.

dist., mkd. T 13 N R 86 W S 11 B T.

A fir, 6 ins. dia., bears S, 83° E., 31 lks.

dist., mkd. T 13 N R 86 W S 14 B T.

A fir, 6 ins. dia., bears S. 55° W., 73 lks.

dist., mkd. T 13 N R 86 W S 15 B T.

A fir, 8 ins. dia., bears N. 38° W., 67 lks.

dist., mkd. T 13 N R 86 W S 10 B T.

Cor. is 574 ft. above creek.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 2nd and 3rd rate.

Vegetation, grass and service brush.

Timber, aspen, spruce, pine and balsam fir.

N. 89° 50' W., on a random line, bet. secs. 10 and 15.

40.00 Set temp. 1/4 sec. cor.

79.98 Intersect N. and S. line, 33 lks. N. of the cor. of secs. 9, 10, 15 and 16.


Thence

N. 89° 56' E., on a true line, bet. secs. 10 and 15.

Over rough, mountainous NW. slope; descend; through heavy timber.

5.00 Small spring branch, course N.

39.99 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey 1/4 sec. cor., with brass cap, mkd.



from which

A fir, 6 ins. dia., bears N. 35° E., 36 lks.

dist., mkd. 1/4 S 10 B T.

A fir, 8 ins. dia., bears S. 43 1/2° W., 60 lks.

dist., mkd. 1/4 S 15 B T.

Cor. is 470 ft. above sec. cor.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

45.80 Top of divide, between Roaring Fork Creek and Battle Creek, bears NE. and S.  $60^{\circ}$  W., 30 ft. above  $\frac{1}{2}$  cor.; thence along top of ridge.

79.98 The cor. of secs. 10, 11, 14 and 15.

Land, rough mountainous.

Soil, stony, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, grasses and berry brush.


Timber, pine and balsam fir.

N.  $0^{\circ}$   $03'$  E., bet. secs. 10 and 11.

Over rough, mountainous land; ascend through timber.

32.14 Top of ridge, bears NE. and SW.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



72.00 Draw, course NW.; ascend.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 10 ins. in the ground, on underlying rock, surrounded by a mound of stone, for resurvey cor. of secs. 2, 3, 10 and 11, with brass cap, mkd.



from which

A pine, 6 ins. dia., bears N.  $25\frac{1}{2}^{\circ}$  E., 51 lks. dist., mkd. T 13 N R 86 W S 2 B T.

A pine, 6 ins. dia., bears S.  $52\frac{1}{2}^{\circ}$  E., 23 lks. dist., mkd. T 13 N R 86 W S 11 B T.

A pine, 6 ins. dia., bears S.  $73\frac{1}{2}^{\circ}$  W., 12 lks. dist., mkd. T 13 N R 86 W S 10 B T.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

A pine, 8 ins. dia., bears N.  $54\frac{1}{2}^{\circ}$  W., 45 lks.  
dist., mkd. T 13 N R 86 W S 3 B T.

Land, rough mountainous.

Soil, stony, sandy, clay loam; subsoil; 3rd rate.

Vegetation, grass and service brush.

Timber, pine, balsam, fir and aspen.

S.  $89^{\circ} 56'$  W., on a random line, bet. secs. 3 and 10.

40.00 Set temp.  $\frac{1}{2}$  sec. cor.


79.96 Intersect N. and S. line, 9 lks. N. of the cor. of secs.  
3, 4, 9 and 10.

Thence

N.  $89^{\circ} 52'$  E., on a true line, bet. secs. 3 and 10.

Over rough mountainous land; ascend through heavy timber.

39.98 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
a mound of stone, on solid rock, for resurvey  $\frac{1}{2}$  sec.  
cor., with brass cap, mkd.



from which

A pine, 10 ins. dia., bears N.  $15^{\circ}$  E., 42 lks.  
dist., mkd.  $\frac{1}{4}$  S 3 B T.

A fir, 8 ins. dia., bears S.  $87^{\circ}$  E., 13 lks.  
dist., mkd.  $\frac{1}{4}$  S 10 B T.

66.50 Top of spur, bears N., 300 ft. above  $\frac{1}{2}$  cor.; descend.

69.70 Creek, 2 lks. wide, 3 ins. deep, course N.  $10^{\circ}$  E.; 45  
ft. below spur; ascend.

71.70 Short spur, bears N., 25 ft. above creek; descend.

75.20 Gulch, course NW.; ascend 85 ft.

79.96 The cor. of secs. 2, 3, 10 and 11.

Land, rough mountainous.

Soil, stony, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, grass, service and berry brush.

Timber, aspen, pine and balsam fir.


## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

N.  $0^{\circ} 03' E.$ , on a true line, bet. secs. 2 and 3.

Over rough mountainous NW. slope; descend through timber.

- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



from which


A pine, 10 ins. dia., bears S.  $66^{\circ} E.$ , 22 lks. dist., mkd.  $\frac{1}{4}$  S 2 B T.

A pine, 18 ins. dia., bears S.  $45^{\circ} W.$ , 12 lks. dist., mkd.  $\frac{1}{4}$  S 3 B T.

- 43.10 Battle Creek, course S.  $60^{\circ} W.$ ; ascend broken SE. slope.

- 82.22 Intersect the S. bdy. of T. 14 N., R. 86 W., at a point, N.  $89^{\circ} 50' E.$ , 4.98 chs. from the angle point, marking position of original cor. of secs. 2, 3, 34 and 35, previously described.

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for closing cor. of secs. 2 and 3, with brass cap, mkd.



from which

A pine, 14 ins. dia., bears S.  $41\frac{1}{2}^{\circ} E.$ , 91 lks. dist., mkd. CC T 13 N R 86 W S 2 B T.

A pine, 12 ins. dia., bears S.  $75^{\circ} W.$ , 44 lks. dist., mkd. CC T 13 N R 86 W S 3 B T.

The closing cor. of secs. 34 and 35, T. 14 N., R. 86 W., bears S.  $89^{\circ} 50' W.$ , 4.38 chs. dist.

Land, rough mountainous.

Soil, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, grass, willows, service and weeds.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Timber, pine, balsam, fir, aspen and spruce.

From the cor. of secs. 25, 26, 35 and 36,


S. 0° 04' W., on a true line, bet. secs. 35 and 36.

Over rough, mountainous land; ascend rocky slope of spur.

13.40 Top of spur, bears SW., 113 ft. above sec. cor.; descend.

21.10 Head of draw, course NW., 128 ft. below spur; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 30 ins. in the ground, surrounded by a mound of stone, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Cor. is 134 ft. above head of draw.

42.50 Top of large spur, bears S. 60° W.; descend.

77.96 Intersect the Third Standard Parallel North, at the closing cor. of secs. 35 and 36, which is identical with the cor. of secs. 1 and 2, resurvey T. 12 N., R. 86 W., described in field notes of reestablishment of the Third Standard Parallel North, Group 31. This cor. is 1.00 ch., S. 89° 48' E., of angle point, marking position of original standard cor. of secs. 1, 2, 35 and 36.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, sage, grass and service brush.

Timber, none.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.


From the cor. of secs. 25, 26, 35 and 36,

N.  $0^{\circ} 04'$  E., bet. secs. 25 and 26.

Over rough, mountainous land; descend.

3.18 Intersect<sup>line</sup>/4-1, Tract 37, at a point, 1.09 chs., E. of cor. No. 4.

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for closing cor. of frac. secs. 25 and 26, with brass cap, mkd.




5.20 Spring branch, course SW., 2 lks. wide, 4 ins. deep, 36 ft. below sec. cor.; ascend.

15.00 Spur, bears SW., 100 ft. above spring; descend.

20.00 Enter timber.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



from which

A pine, 9 ins. dia., bears S.  $86\frac{1}{4}^{\circ}$  E., 28 lks. dist., mkd.  $\frac{1}{2}$  S 25 B T.

A pine, 5 ins. dia., bears S.  $87\frac{3}{8}^{\circ}$  W., 13 lks. dist., mkd.  $\frac{1}{2}$  S 26 B T.

Cor. is 200 ft. below spur.

49.20 East prong, of West Fork of North Fork of Little Snake River, course W., 12 lks. wide, 10 ins. deep, 25 ft. below  $\frac{1}{2}$  cor.; ascend.


66.30 Spur, bears SW., 100 ft. above creek; descend.

68.70 West prong of the West fork of North Fork of Little Snake River, 20 lks. wide, 12 ins. deep, course SW., 31 ft. below spur; ascend.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for resurvey cor. of secs. 23, 24, 25 and 26, with brass cap, mkd.



raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Cor. is 144 ft. above creek.

Land, rough mountainous.

Soil, rocky and sandy, clay loam; subsoil, same; 4th rate.

Vegetation, grass, sage and willows.

Timber, aspen and pine.

West, on a random line, bet. secs. 23 and 26.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 22, 23, 26 and 27.

Thence


S. 89° 57' E., on a true line, bet. secs. 23 and 26.

Over rough, mountainous land; descend through heavy timber.

18.00 Head of gulch, course S.; ascend.

34.00 Top of high, rocky spur, bears S.; descend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey 1/2 sec. cor., with brass cap, mkd.



from which

An aspen, 6 ins. dia., bears N. 45° E., 10 lks. dist., mkd. 1/4 S 23 B T.

An aspen, 5 ins. dia., bears S. 65° E., 4 lks. dist., mkd. 1/4 S 26 B T.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

## Chains.

80.00 The cor. of secs. 23, 24, 25 and 26.  
 Cor. is 131 ft. below  $\frac{1}{4}$  cor.  
 Land, rough mountainous.  
 Soil, rocky, sandy, clay loam; subsoil, same; 4th rate.  
 Vegetation, sage, grass and chokecherry brush.  
 Timber, aspen and pine.


East, On a true line, bet. secs. 24 and 25.

Over rough, mountainous land; descend through heavy timber.

11.80 West prong of West Fork of North Fork of Little Snake River, 25 lks. wide, 12 ins. deep, course SW., 84 ft. below sec. cor.; ascend.

38.00 Top of spur, bears SW., 441 ft. above creek; descend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



from which

A fir, 5 ins. dia., bears N.  $10^{\circ}$  W., 25 lks. dist., mkd.  $\frac{1}{4}$  S 24 B T.

A fir, 6 ins. dia., bears S.  $10^{\circ}$  W., 7 lks. dist., mkd.  $\frac{1}{4}$  S 25 B T.

Cor. is 13 ft. below spur.

70.60 West Fork of North Fork of Little Snake River, 8 lks. wide, 9 ins. deep, course SW.; ascend.


77.10 Intersect the E. bdy. of the Tp., at a point, S.  $0^{\circ} 02'$  E., 1.22 chs. from the angle point, marking the position of the original cor. of secs. 19, 24, 25 and 30, previously described.

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

## Chains.

the ground, for closing cor. of secs. 24 and 25, with brass cap, mkd.



from which

A fir, 7 ins. dia., bears N.  $70^{\circ}$  W., 17 lks.

dist., mkd. CC T 13 N R 86 W S 24 B T.

A pine, 16 ins. dia., bears S.  $22\frac{3}{4}^{\circ}$  W., 19 lks.

dist., mkd. CC T 13 N R 86 W S 25 B T.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 4th rate.

Timber, pine, aspen and balsam fir.

From the cor. of secs. 23, 24, 25 and 26,

N.  $0^{\circ} 04'$  E., bet. secs. 23 and 24.

Over rolling mountainous land; descend through heavy timber.

- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



from which

A pine, 12 ins. dia., bears S.  $35^{\circ}$  E., 40 lks.

dist., mkd.  $\frac{1}{4}$  S 24 B T.

A pine, 12 ins. dia., bears N.  $8^{\circ}$  W., 13 lks.

dist., mkd.  $\frac{1}{4}$  S 23 B T.


- 44.00 Top of low spur, bears SW.; descend.
- 51.30 Creek, 5 lks. wide, 3 ins. deep, course SW.; 338 ft. below sec. cor.; ascend.
- 73.50 Spring branch, flows south along line; 115 ft. below sec. cor.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

75.60 Spring flowing SW., bears W., 10 lks. dist.

80.00 Set an iron post, 3' ft. long, 2 ins. dia., 24 ins. in the ground, for resurvey cor. of secs. 13, 14, 23 and 24, with brass cap, mkd.



from which

A fir, 7 ins. dia., bears N.  $69\frac{1}{2}^{\circ}$  E., 43 lks. dist., mkd. T 13 N R 86 W S 13 B T.A spruce, 40 ins. dia., bears S.  $55\frac{1}{2}^{\circ}$  E., 38 lks. dist., mkd. T 13 N R 86 W S 24 B T.A spruce, 33 ins. dia., bears S.  $44\frac{1}{2}^{\circ}$  W., 20 lks. dist., mkd. T 13 N R 86 W S 23 B T.A spruce, 30 ins. dia., bears N.  $44^{\circ}$  W., 17 lks. dist., mkd. T 13 N R 86 W S 14 B T.

Land, rolling mountainous.

Soil, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, grass.

Timber, spruce, pine, aspen and balsam fir.

N.  $89^{\circ} 57'$  W., on a random line, bet. secs. 14 and 23.40.00 Set temp.  $\frac{1}{2}$  sec. cor.

79.96 Intersect N. and S. line, 7 lks. N. of the cor. of secs. 14, 15, 22 and 23.

Thence

East, on a true line, bet. secs. 14 and 23.

Over rough, broken, mountainous land; ascend along the S. slope of Roaring Creek Canyon; through heavy timber.


3.00 Road, bears SW. and NE.

4.30 Roaring Fork Creek, 8 lks. wide, 4 ins. deep, course SW. 15 ft. below sec. cor.; ascend.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

39.98 Set an iron post, 3 ft. long, 1 in. dia., 6 ins. in the ground, on underlying ledge, surrounded by a mound of stone, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



from which

A fir, 14 ins. dia., bears N. 10° E., 56 lks. dist., mkd.  $\frac{1}{2}$  S. 14 B T.

A pine, 12 ins. dia., bears S. 25 $\frac{1}{2}$ ° E., 67 lks. dist., mkd.  $\frac{1}{2}$  S. 23 B T.

Cor. is 547 ft. above creek.

NW. cor. of shaft, bears N. 30 $\frac{1}{2}$ ° E., 99 lks. dist.

48.00 Top of spur, bears SW., 46 ft. above  $\frac{1}{2}$  cor.; descend.

69.00 Gulch, course S., 45 ft. below spur; ascend.

79.96 The cor. of secs. 13, 14, 23 and 24.

Cor. 92 ft. above gulch.

Land, broken mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, sage, grass and willows.

Timber, pine, spruce, balsam, fir and aspen.

East, on a true line, bet. secs. 13 and 24.

Over rough, mountainous land; ascend through heavy timber.

9.24 Blaze a spruce tree, 18" in dia., on line.

19.80 Spur, bears N. and S., 128 ft. above sec. cor.; descend.

27.60 Spring, course S.


28.60 Creek, 3 lks. wide, 2 ins. deep, course SW., 33 ft. below spur; ascend.

39.40 Creek, 5 lks. wide, 2 ins. deep, course SW.; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.



from which

A spruce, 44 ins. dia., bears N. 19° E., 67 lks.  
dist., mkd. 1/2 S 13 B T.

A spruce, 22 ins. dia., bears S. 44° W., 50 lks.  
dist., mkd. 1/2 S 24 B T.

50.00 Top of spur, bears S., 159 ft. above creek; descend.

65.00 Gulch, course S., 127 ft. below spur; ascend.

77.10 Intersect the E. bdy. of the Tp., at a point, South,  
0.96 chs., from the angle point, marking the position  
for the original cor. of secs. 13, 18, 19 and 24, pre-  
viously described.

Set an iron post, 3 ft. long, 2 ins. dia., 36 ins. in  
a mound of stone, on solid rock, for closing cor. of  
secs. 13 and 24, with brass cap, mkd.



from which

A spruce, 7 ins. dia., bears N. 19° W., 27 lks.  
dist., mkd. CC T 13 N R 86 W S 13 B T.

A spruce, 18 ins. dia., bears S. 40° W., 54 lks.  
dist., mkd. CC T 13 N R 86 W S 24 B T.

Cor. 131 ft. above gulch.

Land, rough, broken and rocky mountainous.

Soil, rocky and stony, sandy, clay loam; subsoil, same;  
3rd and 4th rate.

Vegetation, grass.

Timber, aspen, pine, spruce and balsam fir.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.


From the cor. of secs. 13, 14, 23 and 24,

N. 0° 04' E., bet. secs. 13 and 14.

Over rough, mountainous land; ascend through heavy timber.

35.70 Top of divide, between Roaring Fork and West prong of North Fork of Little Snake River, bears SW. and NE., 343 ft. above sec. cor.; descend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



from which

A pine, 4 ins. dia., bears S. 61° E., 28 lks. dist., mkd.  $\frac{1}{2}$  S 13 B T.


A pine, 6 ins. dia., bears S. 88° W., 16 lks. dist., mkd.  $\frac{1}{2}$  S 14 B T.

Cor. 85 ft. below ridge.

60.10 Roaring Fork Creek, 5 lks. wide, 8 ins. deep, course SW. 218 ft. below  $\frac{1}{2}$  cor.; ascend.

Itmay mine shaft, bears West, 8 chs. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in a mound of stone, on solid rock, for resurvey cor. of secs. 11, 12, 13 and 14, with brass cap, mkd.



from which

A fir, 10 ins. dia., bears N. 65 $\frac{1}{2}$ ° E., 74 lks. dist., mkd. T 13 N R 86 W S 12 B T.

A fir, 8 ins. dia., bears S. 33° E., 63 lks. dist., mkd. T 13 N R 86 W S 13 B T.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

A fir, 11 ins. dia., bears S.  $81^{\circ}$  W., 38 lks.

dist., mkd. T 13 N R 86 W S 14 B T.

A pine, 10 ins. dia., bears N.  $62^{\circ}$  W., 80 lks.

dist., mkd. T 13 N R 86 W S 11 B T.

Cor. is 237 ft. above creek.

Note: Cor. No. 1, Mineral Survey No. 276, (Itmay Lode No. 3,) a granite stone, 6x8x14 ins. above ground, firmly set and marked cross (X) on top, with a 20 in. spruce bearing tree, bears S.  $64^{\circ}$  30' W., 6.25 chs. dist.

The data for this tie was obtained by Roy E. Chase, in 1921.

Land, rough mountainous.

Soil, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, grass, sage, chokecherry and service brush.

Timber, pine, aspen, spruce and balsam fir.

West, on a random line, bet. secs. 11 and 14.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.08 Intersect N. and S. line, 7 lks. N. of the cor. of secs. 10, 11, 14 and 15.


Thence

N.  $89^{\circ}$  57' E., on a true line, bet. secs. 11 and 14.

Over rough mountainous land; descend through heavy timber.

23.50 Creek, 12 lks. wide, 4 ins. deep, course S.; ascend.

40.04 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap, mkd.



from which

A fir, 10 ins. dia., bears N.  $54^{\circ}$  W., 66 lks.

dist., mkd.  $\frac{1}{4}$  S 11 B T.

A spruce, 17 ins. dia., bears S.  $70^{\circ}$  E., 60 lks.

dist., mkd.  $\frac{1}{4}$  S 14 B T.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

63.80 Road, bears N. and S.

74.10 Geological survey monument, 14x12x4 ins., in mound of stone, with cross (X) on top, bears S. 7½° E., 2.71 chs. dist.

74.30 Fall 7 lks. N. of pine stake, in mound of stone; no markings.

80.08 The cor. of secs. 11, 12, 13 and 14.

Land, rough mountainous.

Soil, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, sage, grass and service brush.

Timber, pine, spruce, aspen and balsam fir.


East, on a true line, bet. secs. 12 and 13.

Over rough, mountainous land; ascend through heavy timber.

5.00 Top of ascent, 15 ft. above sec. cor.; descend SE. slope.

19.90 Spring branch, course SW.; ascend gentle slope.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for resurvey ¼ sec. cor., with brass cap, mkd.



raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Cor. is 97 ft. above spring branch; Roaring Fork, bears S., 2 chs. dist.

49.90 Creek, course SW.; ascend.

56.59 NW. cor. of E Pluribus No. 2, bears N., 1.79 chs. dist.

77.00 Intersect the E. bdy. of the Tp., at a point, S.0°03'W., 65 lks. from the angle point, marking the position of original cor. of secs. 7, 12, 13 and 18, previously described.

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in a mound of stone, on solid rock, for closing cor. for

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

secs. 12 and 13, with brass cap, mkd.



from which

A fir, 8 ins. dia., bears S.  $71\frac{1}{2}^{\circ}$  W., 51 lks.  
dist., mkd. CC T 13 N R 86 W S 13 B T.

A fir, 8 ins. dia., bears N.  $34\frac{1}{2}^{\circ}$  W., 110 lks.  
dist., mkd. CC T 13 N R 86 W S12 B T.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, sage and grass.

Timber, pine and balsam fir.


From the cor. of secs. 11, 12, 13 and 14.

N.  $0^{\circ} 04'$  E., bet. secs. 11 and 12.

Over rough mountainous land; descend through heavy timber.

8.00 Spring branch, course SW., 30 ft. below sec. cor.; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap,  
mkd.



from which

A fir, 14 ins. dia., bears S.  $81\frac{1}{2}^{\circ}$  W., 47 lks.  
dist., mkd.  $\frac{1}{2}$  S 11 B T.

A fir, 8 ins. dia., bears N.  $63^{\circ}$  E., 69 lks.  
dist., mkd.  $\frac{1}{2}$  S 12 B T.

Cor. 200 ft. above spring branch.


53.00 Divide, between Roaring Fork and Battle Creek, bears E.  
and W., 92 ft. above  $\frac{1}{2}$  cor.; descend.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

the ground, for resurvey cor. of secs. 1, 2, 11 and 12, with brass cap, mkd.



from which

- A fir, 6 ins. dia., bears N.  $3\frac{1}{2}^{\circ}$  E., 21 lks. dist., mkd. T 13 N R 86 W S 1 B T.
- A fir, 6 ins. dia., bears S.  $31^{\circ}$  E., 26 lks. dist., mkd. T 13 N R 86 W S 12 B T.
- A fir, 8 ins. dia., bears S.  $56^{\circ}$  W., 52 lks. dist., mkd. T 13 N R 86 W S 11 B T.
- A fir, 10 ins. dia., bears N.  $30^{\circ}$  W., 86 lks. dist., mkd. T 13 N R 86 W S 2 B T.

Cor. is 70 ft. below ridge.

Land, rough mountainous.

Soil, sandy, clay loam; subsoil, same; 3rd rate.

Vegetation, sage, grass and service brush.

Timber, aspen, pine and balsam fir.

S.  $89^{\circ} 57'$  W., on a random line, bet. secs. 2 and 11.

40.00 Set temp.  $\frac{1}{2}$  sec. cor.


80.00 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 2, 3, 10 and 11.

Thence

N.  $69^{\circ} 58'$  E., on a true line, bet. secs. 2 and 11.

Over rolling, mountainous land; ascend through timber.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in a mound of stone, on solid rock, for resurvey  $\frac{1}{2}$  sec. cor. with brass cap, mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

## Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

Cor. is 630 ft. above sec. cor.

47.90 Top of ascent, 70 ft. above  $\frac{1}{4}$  cor.; descend.75.50 Spring branch, course N., 330 ft. below top of ascent;  
ascend.

80.00 The cor. of secs. 1, 2, 11 and 12.

Cor. is 82 ft. above spring branch.

Land, rolling mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, sage, grass, chokecherry and service brush.


Timber, pine, aspen and balsam fir.

East, on a true line, bet. secs. 1 and 12.

Over rough, mountainous land; ascend broken cliffs,  
through fallen timber.

24.10 Top of spur, bears NW., 705 ft. above sec. cor.; ascend.

29.60 Head of draw, course NW., 40 ft. above spur; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in  
the ground, on underlying rock, surrounded by a mound  
of stone, for resurvey  $\frac{1}{4}$  sec. cor., with brass cap,  
mkd.

from which

A fir, 6 ins. dia., bears N. 6° E., 49 lks.

dist., mkd.  $\frac{1}{4}$  S 1 B T.

A fir, 6 ins. dia., bears S. 23° E., 35 lks.

dist., mkd.  $\frac{1}{4}$  S 12 B T.

Cor. is 10 ft. above head of draw.


76.80 Intersect the E. bdy. of the Tp., at a point, S. 0° 17' E.,  
1.52 chs. from the angle point, marking the position  
of original cor. of secs. 1, 6, 7 and 12, previously  
described.

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in

Independent Resurvey of the Subdivisions of T. 13 N., R. 86 W.

Chains.

the ground, for closing cor. of secs. 1 and 12, with brass cap, mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, sage, grass, and service brush.

Timber, aspen and pine.


From the cor. of secs. 1, 2, 11 and 12,

N.  $0^{\circ} 04'$  E., on a true line, bet. secs. 1 and 2.

Over rough, mountainous land; ascend through heavy timber.

28.50 Top of spur, bears N.  $60^{\circ}$  W., 92 ft. above sec. cor.; descend.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 16 ins. in the ground, on underlying rock, surrounded by a mound of stone, for resurvey  $\frac{1}{2}$  sec. cor., with brass cap, mkd.



from which

A fir, 8 ins. dia. bears N.  $19^{\circ}$  E., 24 lks. dist., mkd.  $\frac{1}{2}$  S 1 B T.

A pine, 6 ins. dia., bears S.  $25^{\circ}$  W., 38 lks. dist., mkd.  $\frac{1}{2}$  S 2 B T.

Cor. is 120 ft. below spur.


68.90 Creek, 10 lks. wide, 8 ins. deep, course SW., 350 ft. below  $\frac{1}{2}$  cor.; ascend.

Independent Resurvey of the Subdivision of T. 13 N., R. 86 W.

Chains.

82.29 Intersect the S. bdy. of T. 14 N., R. 86 W., at a point, N. 89° 48' E., 4.92 chs. from the restored cor. of secs. 35 and 36, previously described.

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for closing cor. of secs. 1 and 2, with brass cap, mkd.



from which

A pine, 11 ins. dia., bears S. 20° E., 28 lks. dist., mkd. CC T 13 N R 86 W S 1 B T.

A pine, 7 ins. dia., bears S. 10° W., 22 lks. dist., mkd. CC T 13 N R 86 W S 2 B T.

Cor. is 70 ft. above creek.

Land, rough mountainous.

Soil, rocky, sandy, clay loam; subsoil, same; 4th rate.

Vegetation, sage, grass and service brush.

Timber, aspen, pine and balsam fir.

T. 13 N., R. 86 W.

General Description.

This township contains high, rough, rolling mountains, varying from eight to ten thousand feet in elevation above sea level. The general drainage is to the South, into the Little Snake River.

The soil rates from first to fourth and in the hollows it produces abundant crops.

The township is covered with a heavy growth of aspen, pine, spruce and balsam fir timber, and also is covered with grass, sage, chokecherry and service brush.

The rock is of a mineral bearing type and in sec. 14 extensive work has been done on the Itmay mining claims.

The township is well watered by the numerous mountainous streams, which are tributaries and headwaters of the Little Snake River. The water is pure and clear.

There are five settlers located in the southwestern part of the township and appear to be making substantial headway in agriculture.

This township is under the Forest Reserve and grazing is the most profitable industry, altho some mining and agriculture is carried on.

---



CERTIFICATE OF UNITED STATES SURVEYOR.

I, Roy E. Chase, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General for Wyoming bearing date of the 21st day of September, 1916, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of Connections to Mineral Surveys, Township 13 North, Range 86 West,

of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for Wyoming and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Battle Creek, Colorado.

October 25, 1921.

Roy E. Chase

U. S. Surveyor

Cadastral Engineer.

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

191

The foregoing field notes of the survey of

executed by under his special instructions dated 191, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above-described surveys in, has been correctly copied from the original notes on file in this office.

U. S. Surveyor General.



CERTIFICATE OF UNITED STATES SURVEYOR.

Transitman

I, Leland S. Schuch, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General for Wyoming bearing date of the 21st day of September, 1916, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of Boundaries of Private Land Claims and resurveyed subdivisions of T. 13 N., R. 86 W.,

of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for Wyoming and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Cheyenne, Wyoming, December 15, 1919.

Leland S. Schuch, U. S. Surveyor.

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

191

The foregoing field notes of the survey of

executed by under his special instructions dated 191, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above-described surveys in has been correctly copied from the original notes on file in this office.

U. S. Surveyor General.



## CERTIFICATE OF UNITED STATES SURVEYOR.

I, Eugene D. Adams, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General for Wyoming bearing date of the 21st day of September, 1916, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of Boundaries of Private Land Claims and resurveyed subdivisions of T. 13 N., R. 86 W.,

\_\_\_\_\_ of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for Wyoming and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

San Francisco, Cal.  
February 9, 1922.

Eugene D. Adams  
U. S. Surveyor

## APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Cheyenne, Wyoming, March 13, 1922.

The foregoing field notes of the survey of Private Land Claims and Independent resurvey of the Subdivision Lines of Township No. 13 North, Range No. 86 West, of the Sixth Principal Meridian, in the State of Wyoming,

executed by Eugene D. Adams, U.S. Surveyor, and Leland S. Schuch, U.S. Transitman under his special instructions dated September 21, 1916, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Clyde W. Atchley  
U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, has been correctly copied from the original notes on file in this office.