

PUBLIC SURVEY  
FIELD NOTES

VOL. 507  
4877 - 4886  
1936 - 1940

PUBLIC SURVEY

FIELD NOTES

VOL. 507

4877-4886

1936-1940

# FIELD NOTES

OF THE DEPENDENT RESURVEY

OF

THE EAST, SOUTH AND WEST BOUNDARIES,

AND

SUBDIVISION

OF

TOWNSHIP 38 NORTH, RANGE 82 WEST,

Of the SIXTH PRINCIPAL Meridian,

In the State of WYOMING

## EXECUTED BY

Elmer C. Lenhart, Public Land Surveyor, and

Chris Gras, Transitman,

(General Land Office).

Under special instructions dated August 25, 1936, which provided for the surveys included under Group No. 145, Wyo., bearing the approval of the Commissioner of the General Land Office under date of October 10, 1936 and assignment instructions dated August 25, 1936, and March 22, 1937.

Survey commenced September 9, 1936.

Survey completed May 4, 1937.

Accepted by Comml  
Nov 4, 1940

4883

## INDEX DIAGRAM.

Township 38 North, Range 82 West

13 6 49	49 5 48	39 4 39	33 3 32	27 2 26	20 1 19	5
12 7 46	47 8 46	38 9 38	32 10 31	25 11 25	19 12 18	5
12 18 45	45 17 44	37 16 37	30 15 30	24 14 23	17 13 17	4
11 19 43	43 20 42	36 21 35	29 22 29	23 23 22	16 24 15	3
10 20 41	42 29 41	35 28 34	28 27 28	22 26 21	15 25 14	3
10 31 9	40 30 8	33 33 8	27 34 7	20 35 6	14 33 6	2

6-161

Red indicates lines resurveyed by Elmer C. Lenhart.

Blue indicates lines resurveyed by Chris Gras.

Dependent resurvey, E., S. and W. bdrs. and subdivision, T. 38 N., R. 82 W.

A dependent resurvey of the east, south and west boundaries and subdivision of Township 38 North, Range 82 West, 6th Principal Meridian, Wyoming, is executed. The north boundary of the township was dependently resurveyed in 1936, the previously written record of which appears in the resurvey field notes of T. 39 N., R. 82 W.

The resurvey is executed with Gurley transit, No. 2349, and Buff transit, No. 9207. The instruments are the property of the General Land Office and conform to the standard instrumental requirements of the Cadastral Engineering Service. They are equipped with full vertical circles and improved Smith type solar attachments. All lines of the resurvey are transit lines, double centered when necessary. The exterior lines are carried by deflection from the previously established west boundary of T. 37 N., R. 81 W., the bearing of which was determined by elongation observation upon Polaris as recorded in the resurvey field notes of that township, and are checked against the meridian established September 9, 1936, following an eastern elongation observation upon Polaris, at the southeast corner of T. 39 N., R. 82 W., described in the field note record of T. 39 N., R. 82 W. The exterior lines of the resurvey are further verified by altitude observations upon the sun for meridian taken during the course of the field work and are at all times found in satisfactory agreement. The subdivisional lines of the township are carried by deflection from the south boundary, checked by deflection against the east, west and north boundaries, and are further verified by the following hour angle observation upon Polaris for meridian. All latitudinal lines are run as rhumb lines on the ground by correcting the tangents.

May 4, 1937, I set my watch correct with 105th meridian standard time by comparison with a Western Union telegraph clock at Casper, Wyoming. Later that evening, at the corner of sections 15, 16, 21 and 22, Township 38 North, Range 82 West, 6th Principal Meridian, Wyoming, in latitude  $43^{\circ} 15' N.$ , and longitude  $106^{\circ} 40.5' W.$ , at 7h 10m 18s p.m., l.m.t., I make an hour angle observation on Polaris, west of the meridian, two each with the telescope in direct and reversed positions, reading the horizontal deflection angle from a flag set on the true line between sections 15 and 16, about 10 chains N., in the direction N-W to Polaris.

Watch time of observation = 7h 17m 00s p.m.

Mean horizontal angle, Polaris to flag, =  $0^{\circ} 01'.5 W-N.$

Azimuth of Polaris =  $N.1^{\circ} 09'.1 W.$

True bearing of line =  $N.1^{\circ} 07'.6 W.$

Inasmuch as the bearing of this line as deflected from the south boundary was believed to be  $N. 1^{\circ} 08' W.$ , it is assumed that the bearings of the subdivisional lines are satisfactory.

Frequent tests of the transits are made during the course of the resurvey and they are at all times found to be in good adjustment.

Measurements are made with steel tapes, 5-chains in length, tested for accuracy by comparison with a Lufkin 66-ft. steel standard tape. Measurements are made on the slope, the vertical angles determined by clinometers in good adjustment and the slope measurements reduced to true horizontal distances which alone appear in the field note record.

The magnetic variation is observed at several points throughout the township and the mean of the several readings results in a mean variation of  $16^{\circ} 30' E.$

445

Dependent resurvey, E., S. and W. bdrs. and subdivision, T. 38 N., R. 82 W.

Chains.

Method of Procedure.

Pursuant to the approved special instructions the dependent method of resurvey is followed.

Preliminary to the resurvey, the lines of the original survey are retraced and diligent search is made for all original corners. Identified corners of the original survey are restored in their original positions and all missing corners are reestablished at proportionate positions based upon the official record of the original survey. The retracement data is thoroughly verified and to gain simplification the true line field notes alone are herein recorded.

Dependent resurvey, E. bdy., T. 38 N., R. 82 W.

Reestablishment of the survey executed by Curtis and Libby, U. S. Deputy Surveyors, in 1883.

Beginning at the cor. of Tps. 37 and 38 N., Ra. 81 and 82 W., in latitude 43° 12' 4 N., and longitude 106° 37' W., an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the resurvey field note record of T. 37 N., R. 81 W.

N. 0° 32' W., bet. secs. 31 and 36.

Over rolling land, through scattering sagebrush.

20.15 Dry drain, course S. of W.

28.00 Dry drain, course SW.

39.91 Proportionate distance. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for 1/4 sec. cor., with brass cap mkd.



dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

79.82 Proportionate distance. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with quart bottle deposited at base, for cor. of secs. 25, 30, 31 and 36, with brass cap mkd.



dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

Dependent resurvey, E. bdy., T. 38 N., R. 82 W.

Chains.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush.

N. 0° 32' W., bet. secs. 25 and 30.

Over rolling land, through scattering sagebrush.

0.70 Dry drain, course N. of W.

26.10 Dry drain, course W.

39.91 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with quart bottle deposited at base, for  $\frac{1}{2}$  sec. cor., with brass cap mkd.

$\frac{1}{2}$   
 S25 | S30  
 1936

18x18x12 ins., N. and S. of post, 3 ft. dist.

dig pits,

65.45 Dry drain, course W.

79.82 Proportionate distance.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 19, 24, 25 and 30, with brass cap mkd.

T38N  
 R82W R81W  
 S24 | S19  
 S25 | S30  
 1936

raise a mound  
of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush.

N. 0° 32' W., bet. secs. 19 and 24.

Over rolling and broken land, through scattering sagebrush.

18.90 Dry drain, course SW.

39.91 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with quart bottle deposited at base, for  $\frac{1}{2}$  sec. cor., with brass cap mkd.

$\frac{1}{2}$   
 S24 | S19  
 1936

dig pits,  
18x18x12 ins., N. and S. of post, 3 ft. dist.

447

Dependent resurvey, E. bdy., T. 38 N., R. 82 W.

Chains.	
58.30	Dry drain, course SW.
71.10	Dry drain, course SW.
79.82	Proportionate distance.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 13, 18, 19 and 24, with brass cap mkd.
	<p style="text-align: center;">T38N R82W R81W S13   S18 S24   S19 1936</p>
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, rolling and broken. Soil, sandy clay and gumbo; 3d rate. No timber; undergrowth, sagebrush.
	N. 0° 32' W., bet. secs. 13 and 18.
	Over rolling and broken land, through scattering sagebrush.
8.60	33-Mile Trail, a graded county road, following a low ridge, bears N. of W. and SE.
20.20	Dry drain, course NW.
39.91	Proportionate distance.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<p style="text-align: center;">↑ S13   S18 1936</p>
	raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.
56.70	Dry drain, course NW.
63.30	Dry drain, course W.
79.82	Proportionate distance.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 7, 12, 13 and 18, with brass cap mkd.
	<p style="text-align: center;">T38N R82W R81W S12   S7 S13   S18 1936</p>
	raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of cor.
	Land, rolling and broken. Soil, sandy clay and gumbo; 3d rate. No timber; undergrowth, sagebrush.

## Dependent resurvey, E. bdy., T. 38 N., R. 82 W.

Chains.

N. 0° 32' W., bet. secs. 7 and 12.

Over rolling and broken land, through scattering sagebrush.

13.70 Dry drain, course W.

25.80 Dry drain, course SW.

39.91 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S12 S7

1936

raise a mound

of stone, 2 $\frac{1}{2}$  ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor.

57.80 Dry drain, course W.

71.70 Dry drain, course SW.

79.82 Proportionate distance.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

T38N

R82W R81W

S1 S6

S12 S7

1936

raise a mound

of stone, 2 $\frac{1}{2}$  ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and broken.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, sagebrush.

N. 0° 32' W., bet. secs. 1 and 6.

Over rolling and broken land, through scattering sagebrush.

15.30 Dry drain, course S. of W.

39.91 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S1 S6

1936

dig pits,

18x18x12 ins., N. and S. of post, 3 ft. dist.

41.00 Dry drain, course W.

449

Dependent resurvey, E. bdy., T. 38 N., R. 82 W.

Chains.

50.50 Dry drain, course S. of W.

79.82 The cor. of Tps. 38 and 39 N., Rs. 81 and 82 W., an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the resurvey field note record of T. 39 N., R. 82 W.

Land, rolling and broken.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush.

Dependent resurvey, S. bdy., T. 38 N., R. 82 W.

Reestablishment of the survey executed by Curtis and Libby, U. S. Deputy Surveyors, in 1883.

From the cor. of Tps. 37 and 38 N., Rs. 81 and 82 W., hereinbefore noted.

N. 89° 53' W., bet. secs. 1 and 36.

Over rolling land, through scattering sagebrush.

40.22 Proportionate distances.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with quart bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{\frac{1}{4} S36}{S1}$$

1936

dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

75.50 Center of Cloud Creek, dry, a deep dry wash, course N.

80.44 Proportionate distance.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with pint bottle deposited at base, for cor. of secs. 1, 2, 35 and 36, with brass cap mkd.

$$\begin{array}{r} T38N R82W \\ S35 | S36 \\ \hline S2 | S1 \\ T37N \\ 1936 \end{array}$$

dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush.

N. 89° 53' W.; bet. secs. 2 and 35.

Over rolling land, through scattering sagebrush.

## Dependent resurvey, S. bdy., T. 38 N., R. 82 W.

Chains.

40.22 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S35}{S2}$$

1936

dig pits,  
18x18x12 ins., E. and W. of post, 3 ft. dist.

80.44 Proportionate distance.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with pint bottle deposited at base, for cor. of secs. 2, 3, 34 and 35, with brass cap mkd.

T38N R82W

$$\frac{S34}{S3} \frac{S35}{S2}$$

T37N  
1936

dig pits,  
18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush.

N. 89° 53' W., bet. secs. 3 and 34.

Over rolling land, through scattering sagebrush.

15.30 Dry drain, course NW.

21.50 Dry drain, course E. of N.

36.00 Dry drain, course NE.

40.22 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S34}{S3}$$

1936

dig pits,  
18x18x12 ins., E. and W. of post, 3 ft. dist.

80.44 Proportionate distance.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 3, 4, 33 and 34, with brass cap mkd.

T38N R82W

$$\frac{S33}{S4} \frac{S34}{S3}$$

T37N  
1936

raise a mound  
of stone, 3 ft. base, 2 ft. high, W. of cor.

451

## Dependent resurvey, S. bdy., T. 38 N., R. 82 W.

Chains.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush.

N. 89° 53' W., bet. secs. 4 and 33.

Over rolling land, through scattering sagebrush.

40.22 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} S33 \\ \frac{1}{4} S4 \\ \hline 1936 \end{array}$$

raise a mound

of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of cor.

69.70 Cloud Creek- Powder River Road, an unimproved county road, following ridge, bears N. and S.

80.44 Proportionate distance.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with quart brown jar deposited at base, for cor. of secs. 4, 5, 32 and 33, with brass cap mkd.

$$\begin{array}{r} T38N R82W \\ \hline S32 | S33 \\ \hline S5 | S4 \\ \hline T37N \\ \hline 1936 \end{array}$$

raise a mound

of stone, 3 ft. base, 3 ft. high, W. of cor.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush.

N. 89° 53' W., bet. secs. 5 and 32.

Over rolling land, through scattering sagebrush.

4.70 Dry drain, course N.

40.22 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} S32 \\ \frac{1}{4} S5 \\ \hline 1936 \end{array}$$

raise a mound

of stone,  $3\frac{1}{2}$  ft. base,  $2\frac{1}{2}$  ft. high, N. of cor.

79.70 Dry drain, course N.

80.44 Proportionate distance.

Dependent resurvey, S. bdy., T. 38 N., R. 82 W.

## Chains.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with pint bottle deposited at base, for cor. of secs. 5, 6, 31 and 32, with brass cap mkd.

T38N R82W

S31 | S32

S6 | S5

T37N

1936

No suitable accessories.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, sagebrush.

N. 89° 53' W., bet. secs. 6 and 31.

Over rolling land, through scattering sagebrush.

1.35 Dry drain, course N. of E.

40.22 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S31

$\frac{1}{4}$  S6

1936

18x18x12 ins., E. and W. of post, 3 ft. dist.

58.50 Dry drain, course NW.

79.94 Proportionate point.

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in ground, for cor. of Tps. 37 and 38 N., Rs. 82 and 83 W., with brass cap mkd.

T38N

R83W R82W

S36 | S31

S1 | S6

T37N

1936

18x18x12 ins., N., S., E. and W. of post, 3 ft. dist.

From this point the original  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, on E. bdy. of T. 37 N., R. 83 W., bears S. 1° 05' E., 118.68 chs. dist.

From the same point the original cor. of secs. 1, 2, 35 and 36, on S. bdy. of T. 38 N., R. 83 W., bears N. 87° 48' W., 80.50 chs. dist.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, sagebrush.

453

Dependent resurvey, W. bdy., T. 38 N., R. 82 W.

Chains.

Reestablishment of the survey executed by Curtis and Libby, U. S. Deputy Surveyors, in 1883.

From the cor. of Tps. 37 and 38 N., Rs. 82 and 83 W., hereinbefore described.


N. 1° 52' E., bet. secs. 31 and 36.

Over rolling and broken land, through scattering sagebrush.

22.70 Dry drain, course NW.

39.57 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for 1/4 sec. cor., with brass cap mkd.



18x18x12 ins., N. and S. of post, 3 ft. dist. dig pits,

49.00 Dry drain, course W.

79.14 The original cor. of secs. 25, 30, 31 and 36, which is a sandstone, 18x14x6 ins., marked with 1 notch on S. and 5 notches on N. edge, firmly set in ground.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with original corner stone alongside, for cor. of secs. 25, 30, 31 and 36, with brass cap mkd.



18x18x12 ins., in each sec., 3 ft. dist. dig pits,

Land, rolling and broken. Soil, sandy clay and gumbo; 3d rate. No timber; undergrowth, sagebrush.

N. 0° 19' W., bet. secs. 25 and 30.

Over rolling and broken land, through scattering sagebrush.

6.40 Dry drain, course SW.


25.90 Dry drain, course S. of W.

39.54 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with gallon glass jug deposited alongside, for 1/4 sec. cor., with brass cap mkd.

Dependent resurvey, W. bdy., T. 38 N., R. 82 W.

Chains.




18x18x12 ins., N. and S. of post, 3 ft. dist.

79.08 The original cor. of secs. 19, 24, 25 and 30, which is a sandstone, 18x16x4 ins., marked with 2 grooves on S. and 4 grooves on N. face, firmly set in ground.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with original corner stone alongside, for cor. of secs. 19, 24, 25 and 30, with brass cap mkd.



18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling and broken.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush.

N. 0° 45' W., bet. secs. 19 and 24.

Over rolling and broken land, through scattering sagebrush.

39.75 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for 1/2 sec. cor., with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

42.40 Dry drain, course NW.

64.30 Dry drain, course W.

68.00 Dry drain, course SW.

79.50 Proportionate distance.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with pint bottle deposited alongside, for cor. of secs. 13, 18, 19 and 24, with brass cap mkd.



455

Dependent resurvey, W. bdy., T. 38 N., R. 82 W.

Chains.

raise a mound  
of stone, 3 ft. base, 2 ft. high, W. of cor.


Land, rolling and broken.  
Soil, sandy clay and gumbo with sandstone exposures; 3d rate.  
No timber; undergrowth, sagebrush.

N. 0° 45' W., bet. secs. 13 and 18.

Over rolling land, through scattering sagebrush.

39.75 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with  
pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



Dig pits,  
18x18x12 ins., N. and S. of post, 3 ft. dist.

79.50 Proportionate distance.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with  
pint bottle deposited at base, for cor. of secs. 7, 12, 13 and 18,  
with brass cap mkd.



dig pits,  
18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush.


N. 0° 45' W., bet. secs. 7 and 12.

Over rolling land, through scattering sagebrush.

34.90 South Fork of Powder River, dry, 3 chains. wide, course NE.

39.75 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with  
quart bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



raise a mound  
of stone, 3 ft. base, 2 ft. high, W. of cor.

Dependent resurvey, W. bdy., T. 38 N., R. 82 W.

Chains.

79.50 The original cor. of secs. 1, 6, 7 and 12, which is a sandstone, 8x6x3 ins., marked with 5 notches on S. and 1 notch on N. face, firmly set in ground.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with original corner stone alongside and with pint bottle deposited at base, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

T38N  
R83W R82W  
S1 | S6  
S12 | S7  
1936

18x18x12 ins., in each sec., 3 ft. dist. dig pits,

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, sagebrush.

N. 2° 39' W., bet. secs. 1 and 6.

Over rolling land, through scattering sagebrush.

18.20 Dry drain, course SE.

28.20 Dry drain, course SE.

39.35 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for 1/4 sec. cor., with brass cap mkd.

1/4  
S1 | S6  
1936

dig pits,

18x18x12 ins., N. and S. of post, 3 ft. dist.

78.70 The cor. of Tps. 38 and 39 N., Rs. 82 and 83 W., an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the resurvey field note record of T. 39 N., R. 82 W.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, sagebrush.

457

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

Reestablishment of the survey executed by Curtis and Libby, U. S. Deputy Surveyors, in 1883.

From the cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp., herein before described.

N. 0° 12' W., bet. secs. 35 and 36.

Over rolling land, through scattering sagebrush.


20.80 Dry drain, course E.

27.40 Dry drain, course E.

38.80 Head of dry drain, course S. 70° E.

39.84 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for 1/4 sec. cor., with brass cap mkd.



raise a mound


of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.

64.80 Low ridge, bears SW. and N. 10° E.

69.00 Head of dry drain, course N. of W.

79.68 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with piece of cast iron, 10x7x2 ins., deposited at base, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.



raise a mound

of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush.

From the cor. of secs. 25, 30, 31 and 36, on E. bdy. of Tp., herein before described.

West, bet. secs. 25 and 36.

Over rolling land, through scattering sagebrush.

30.00 Right bank of Cloud Creek, water in pools, course E. of N.; banks of creek are about 30 ft. high.

33.80 Left bank of creek.

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

39.98 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with 2 half-pint bottles deposited at base and with buffalo skull along-side, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S25  
S36  
1937

raise a mound of stone, 2 $\frac{1}{2}$  ft. base, 2 ft. high, N. of cor.

78.15 Low ridge, bears SW. and N. 10° E.

79.96 The cor. of secs. 25, 26, 35 and 36.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush.

N. 0° 30' W., bet. secs. 25 and 26.

Over rolling land, through scattering sagebrush.

20.40 Dry drain, course N. of W.

39.60 Dry drain, course NW.

39.84 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S26 | S25  
1937

raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

73.00 Large dry drain, course NE.

79.68 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with quart bottle deposited at base, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.

T38N R82W  
S23 | S24  
S26 | S25  
1937

raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush.

From the cor. of secs. 19, 24, 25 and 30, on E. bdy. of Tp., herein-before described.

459

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

S. 89° 54' W., bet. secs. 24 and 25.

Over rolling land, through scattering sagebrush.

3.00 Right bank of Cloud Creek, water in pools, course NW.; banks of creek are from 20 to 30 ft. high.

9.10 Left bank of Creek.

18.10 Dry drain, course NE.

39.93 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} S24 \\ \frac{1}{4} S25 \\ 1937 \end{array}$$

raise a mound

of stone, 2 $\frac{1}{2}$  ft. base, 2 ft. high, N. of cor.

73.50 Large dry drain, course NE.

79.86 The cor. of secs. 23, 24, 25 and 26.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, sagebrush.

N. 0° 30' W., bet. secs. 23 and 24.

Over rolling land, through scattering sagebrush and cactus.

17.40 Dry drain, course S. 60° E.

39.84 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with quart bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ S23 \quad | \quad S24 \\ 1937 \end{array}$$

dig pits,

18x18x12 ins., N. and S. of post, 3 ft. dist.

55.00 Deep drain, course NE.

59.70 Left bank of Cloud Creek, water in pools, course NW.; banks of creek are from 20 to 30 ft. high.

61.90 Right bank of Creek.

79.68 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with half-pint bottle deposited at base, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

T38N R82W  
S14 | S13  
S23 | S24  
1937

raise a mound

of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling and broken.

Soil, sandy clay and gumbo; 3d. rate.

No timber; undergrowth, sagebrush and cactus.

From the cor. of secs. 13, 18, 19 and 24, on E. bdy. of Tp., herein-  
before described.

S. 89° 48' W., bet. secs. 13 and 24.

Over rolling and broken land, through scattering sagebrush and  
cactus.

1.50 Dry drain, course SW.

4.10 Dry drain, course S.

10.50 Dry drain, course S.

17.50 Dry drain, course S.

39.87 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  
¼ sec. cor., with brass cap mkd.

½ S13  
½ S24  
1937

dig pits,  
18x18x12 ins., E. and W. of post, 3 ft. dist.

55.50 Winding dry drain, general course S. 75° W.

65.90 Dry drain, course SW.

78.90 Abandoned county road, bears NW. and SE.; road has been graded.

79.74 The cor. of secs. 13, 14, 23 and 24.

Land, rolling and broken.

Soil, sandy clay and gumbo; 3d. rate.

No timber; undergrowth, sagebrush and cactus.

N. 0° 46' W., bet. secs. 13 and 14.

Over rolling land, through scattering sagebrush and cactus.

1.65 Abandoned county road which has been graded, bears NW. and SE.

17.40 Dry drain, course SW.

39.84½ Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with  
pint bottle deposited at base, for ½ sec. cor., with brass cap mkd.

461

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

$\frac{1}{2}$   
 S14 | S13  
 1937

raise a mound  
of stone, 2 ft. base, 2 ft. high, W. of cor.

- 41.10 Dry drain, course S. of W.
- 49.30 Head of dry drain, course SW.
- 51.55 33-Mile Trail, a graded county road, bears SE. and NW.; road follows low ridge, same bearing.
- 59.40 Land becomes more broken.
- 63.25 Dry drain, course NW.
- 76.40 Dry drain, course NE.
- 79.69 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with pieces of glass and an oil pipe collar, 10 ins. diam., deposited at base, for cor. of secs. 11, 12, 13 and 14, with brass cap mkd.

T38N R82W  
 S11 | S12  
 S14 | S13  
 1937

raise a mound  
of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling and broken.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush and cactus.

From the cor. of secs. 7, 12, 13 and 18, on E. bdy. of Tp., hereinbefore described.

S. 89° 41' W., bet. secs. 12 and 13.

Over rolling and broken land, through scattering sagebrush and cactus.

- 3.30 Dry drain, course N.
- 26.35 Dry drain, course N.
- 39.97 Proportionate distance.
- Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with quart bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S12  
 S13  
 1937

dig pits,  
18x18x12 ins., E. and W. of post, 3 ft. dist.

- 46.15 Dry drain, course N.

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

58.65 Dry drain, course N.

76.70 Dry drain, course N.

79.94 The cor. of secs. 11, 12, 13 and 14.

Land, rolling and broken.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, sagebrush and cactus.

N. 0° 41' W., bet. secs. 11 and 12.

Over broken land, through scattering sagebrush.

9.40 Dry drain, course E.

12.00 A point at W. side of tin lambing shed belonging to John Ellis.


19.65 Center of deep dry drain, 1.50 chs. wide, course NW.

23.30 Same drain, course N. of E.

38.00 Dry drain, course SE.

39.84 $\frac{1}{2}$  Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.




18x18x12 ins., N. and S. of post, 3 ft. dist.

58.80 Center of deep dry drain, 1 chain wide, course W.

79.69 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.



18x18x12 ins., in each sec., 3 ft. dist.

Land, broken.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 1, 6, 7 and 12, on E. bdy. of Tp., hereinbefore described.

S. 89° 35' W., bet. secs. 1 and 12.

Over broken and barren adobe hills.

36.30 Winding dry drain, course S. 70° W.

463

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

40.04 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\frac{1}{4} \frac{S1}{S12}$$

1937

dig pits,

18x18x12 ins., E. and W. of post, 3 ft. dist.

Leave adobe hills, bear N. and SE.; thence over rolling land, through scattering sagebrush.

52.80 Dry drain, course SW.

80.08 The cor. of secs. 1, 2, 11 and 12.

Land, rolling and broken.  
Soil, sandy clay and gumbo; 3d rate in W. half mile and barren adobe; 4th rate in E. half.  
No timber; undergrowth, scattering sagebrush in W. half mile.

N. 0° 50' W., bet. secs. 1 and 2.

Over rolling land, through scattering sagebrush, cactus and greasewood.

0.20 Dry drain, course W.

28.20 Dry drain, course W.

32.40 Dry drain, course SW.

35.20 Enter barren adobe hills, bear E. and W.

39.84 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\frac{1}{4} \frac{S2}{S1}$$

1937

dig pits,

18x18x12 ins., N. and S. of post, 3 ft. dist.

70.40 Dry drain, course W.; leave adobe hills, bear E. and W.; thence over rolling land, through thinly scattering sagebrush and cactus.

76.60 Dry drain, course SW.

79.88 The cor. of secs. 1, 2, 35 and 36, on N. bdy. of Tp., an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the resurvey field note record of T. 39 N., R. 82 W.

Land, rolling and broken.  
Soil, sandy clay and gumbo and adobe hills; 3d and 4th rate.  
No timber; undergrowth, scattering sagebrush, cactus and greasewood.

From the cor. of secs. 2, 3, 34 and 35, on S. bdy. of Tp., hereinbefore described.

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

N. 0° 09' E., bet. secs. 34 and 35.


Over rolling land, through scattering sagebrush and cactus.

15.50 Dry drain, course W.

31.30 Dry drain, course N. of W.

39.80 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in ground to underlying rock, with pint bottle deposited at base, and in mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.




42.10 Dry drain, course W.

51.00 Deep dry drain, course NE.

57.20 Dry drain, course E.

79.60 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with quart bottle deposited at base, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.



raise a mound  
of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 25, 26, 35 and 36.

N. 89° 56' W., bet. secs. 26 and 35.

Over rolling land, through scattering sagebrush and cactus.

17.70 Dry drain comes in from SE. and winds W. along line.

24.95 Drain turns to N.

25.85 Dry drain, course N.

40.00 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with quart bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



raise a mound

of stone, 2 ft. base, 2 ft. high, N. of cor.

465

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

58.50 Deep dry drain, course NE.

80.00 The cor. of secs. 26, 27, 34 and 35.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

N. 0° 24' W., bet. secs. 26 and 27.


Over rolling land, through scattering sagebrush and cactus.

10.90 Dry drain, course E.

32.00 Dry drain, course SE.

39.80 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with quart bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



raise a mound

of stone, 2 ft. base, 2 ft. high, W. of cor.


49.60 Low, broad ridge, bears NE. and SW.

59.90 Head of dry drain, course NW.

65.40 Dry drain, course W.

79.60 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with gallon jug deposited at base, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.



raise a mound

of stone, 2½ ft. base, 2 ft. high, W. of cor.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 23, 24, 25 and 26.

West, bet. secs. 23 and 26.

Over rolling land, through scattering sagebrush and cactus.

39.91 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

$\frac{1}{4}$  S23  
 $\frac{1}{4}$  S26  
 1937

dig pits,  
 18x18x12 ins., E. and W. of post, 3 ft. dist.

40.00 Summit of low broad ridge, bears NE. and SW.

63.05 Dry drain, course NW.

71.10 Dry drain, course N.

79.82 The cor. of secs. 22, 23, 26 and 27.

Land, rolling.  
 Soil, sandy clay and gumbo; 3d rate.  
 No timber; undergrowth, scattering sagebrush and cactus.


N. 0° 20' W., bet. secs. 22 and 23.

Over rolling land, through scattering sagebrush.

25.00 Deep dry drain, course NE.

39.80 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with quart milk bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



raise a mound  
 of stone, 2½ ft. base, 1½ ft. high, W. of cor.

50.60 Dry drain, course E.

71.00 Low ridge, bears NE. and SW.

79.60 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with pint bottle deposited at base, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.

T38N R82W  
 S15 | S14  
 S22 | S23  
 1937

raise a mound  
 of stone, 2½ ft. base, 1½ ft. high, W. of cor.

Land, rolling.  
 Soil, sandy clay and gumbo; 3d rate.  
 No timber; undergrowth, scattering sagebrush.

From the cor. of secs. 13, 14, 23 and 24.

S. 89° 56' W., bet. secs. 14 and 23.

467

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

Over rolling and broken land, through scattering sagebrush and cactus.

12.55 Dry drain, course S.

30.65 Right bank of Cloud Creek, water in pools, course N.; banks of creek are from 20 to 30 ft. high.

34.45 Left bank of Creek.

39.80 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S14  
S23  
1937

dig pits,

18x18x12 ins., E. and W. of post, 3 ft. dist.

43.10 Center of wide drain, 20 ft. deep, course N.

67.80 Low ridge, bears N. 30° E. and SW.

79.60 The cor. of secs. 14, 15, 22 and 23.

Land, rolling and broken.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

N. 0° 55' W., bet. secs. 14 and 15.

Over rolling and broken land, through scattering sagebrush.

17.70 Confluence of drains from E. and SW.; main drain courses N., winding along line.

36.90 Leave drain, course NE.

39.80 $\frac{1}{2}$  Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with glass telephone line insulator deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S15 S14  
1937

dig pits,

18x18x12 ins., N. and S. of post, 3 ft. dist.

59.70 Cloud Creek - Powder River Road, an unimproved county road, bears NE. and SW.

74.10 Dry drain, course NE.

79.61 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with quart bottle deposited at base, for cor. of secs. 10, 11, 14 and 15, with brass cap mkd.

T38N R82W  
S10|S11  
S15|S14  
1937

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

raise a mound

of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and broken.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush.

From the cor. of secs. 11, 12, 13 and 14.

S.  $89^{\circ} 53'$  W., bet. secs. 11 and 14.

Over rolling land, through scattering sagebrush and cactus.

13.00 33-Mile Trail, a graded county road, following low ridge, bears N. and S.

26.20 Dry drain, course SW.

39.90 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   $\frac{S11}{S14}$

1937

raise a mound

of stone, 3 ft. base, 2 ft. high, N. of cor.

46.80 Abandoned 33-Mile Trail, which has been graded, bears NW. and SE.

51.70 Dry drain, course NW., 1.50 chs. dist. to confluence with Cloud Creek.

55.47 The SW. end of a steel bridge on 33-Mile Trail over Cloud Creek, bears North, 8.30 chs. dist.

57.10 Right bank of Cloud Creek, water in pools, course generally N.; banks of creek are from 20 to 30 feet high.

58.70 Left bank of Creek.

65.60 Cloud Creek - Powder River Road, an unimproved county road, bears N. and SW.

74.20 Winding dry drain, course generally N.  $10^{\circ}$  E.

79.80 The cor. of secs. 10, 11, 14 and 15.

Land, rolling.  
Soil, sandy clay and gumbo.  
No timber; undergrowth, scattering sagebrush.

N.  $0^{\circ} 43'$  W., bet. secs. 10 and 11.

Over rolling land, through scattering sagebrush and cactus.

31.20 Dry drain, course NE.

39.80 $\frac{1}{2}$  Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

469

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.	
	<div style="text-align: center;"> </div> <p style="text-align: right;">raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.</p>
60.55	Deep dry drain, course E.
79.61	Proportionate point. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with quart bottle deposited at base, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.
	<div style="text-align: center;"> <p>T38N R82W</p> <p>S3   S2</p> <p>S10   S11</p> <p>1937</p> </div> <p style="text-align: right;">raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy clay and gumbo; 3d rate. No timber; undergrowth, scattering sagebrush and cactus.</p>
	From the cor. of secs. 1, 2, 11 and 12. S. 89° 45' W., bet. secs. 2 and 11. Over rolling land, through scattering sagebrush and cactus.
0.65	Winding dry drain, course SW.
26.90	Same drain, course NW.
34.90	Same drain, at bend, course NW. from NE.
36.20	Right bank of Cloud Creek, water in pools, course N.; banks of creek are from 20 to 30 feet high.
37.70	Left bank of Creek.
39.93	Proportionate distance. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for ¼ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> <p>¼ S2</p> <p>¼ S11</p> <p>1937</p> </div> <p style="text-align: right;">raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.</p>
62.80	Dry drain, course N. 60° E.
76.90	33-Mile Trail, a graded county road, bears N. and SE. at curva.
79.86	The cor. of secs. 2, 3, 10 and 11. Land, rolling. Soil, sandy clay and gumbo; 3d rate. No timber; undergrowth, scattering sagebrush and cactus.

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

N. 1° 20' W., bet. secs. 2 and 3.

Over rolling land, through scattering sagebrush and cactus.

16.05 33-Mile Trail, a graded county road, bears NW. and SE.

21.80 Dry drain, course NE.

39.81 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with two half-pint bottles deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S3 S2

1937

raise a mound  
of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

56.80 Dry drain, course NE.

67.18 A point at center of earth dam extending N. 30 $\frac{1}{2}$ ° W. and S. 30 $\frac{1}{2}$ ° E., 6.40 chains in length, bears West, 24.50 chs. dist.; water in reservoir of about 10 acres is impounded to SW. and a drain courses N. of E. from center of dam; the 33-Mile Trail, a graded county road, crosses on the dam.

74.40 Dry drain; from reservoir, course E.

79.71 The cor. of secs. 2, 3, 34 and 35, on N. bdy. of Tp., an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the resurvey field note record of T. 39 N., R. 82 W.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 3, 4, 33 and 34, on S. bdy. of Tp., hereinbefore described.

N. 0° 29' E., bet. secs. 33 and 34.

Over rolling land, through scattering sagebrush and cactus.

29.20 Dry drain, course N. 80° E.

39.76 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S33 S34

1937

dig pits,  
18x18x12 ins., N. and S. of post, 3 ft. dist.

53.00 A broad ridge, bears NE. and SW.

75.60 Deep dry drain, course E. of N.

471

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

79.52 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.

T38N R82W

S28 | S27

S33 | S34

1937

raise a mound  
of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 26, 27, 34 and 35.

N. 89° 58' W., bet. secs. 27 and 34.

Over rolling land, through scattering sagebrush, and cactus.

26.10 Dry drain, course SE.

38.20 Dry drain, course SE.

39.97 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with quart bottle deposited at base, for ¼ sec. cor., with brass cap mkd.

¼ S27

S34

1937

raise a mound  
of stone, 3 ft. base, 2 ft. high, N. of cor.

48.30 Summit of wide ridge, bears N. 20° E. and SW.

73.80 Dry drain, course NW.

78.05 Deep dry drain, course E. of N.

79.94 The cor. of secs. 27, 28, 33 and 34.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

N. 0° 16' W., bet. secs. 27 and 28.

Over rolling and broken land, through scattering sagebrush and cactus.

39.76 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for ¼ sec. cor., with brass cap mkd.

S28 | S27

1937

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

raise a mound  
of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

49.25 Summit of broad ridge, bears NE. and SW.

79.52 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

T38N R82W  
S21 | S22  
S28 | S27  
1937

raise a mound  
of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and broken hills.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 22, 23, 26 and 27.

S.  $89^{\circ} 53'$  W., bet. secs. 22 and 27.

Over rolling land, through scattering sagebrush and cactus.

13.40 Dry drain, course N.

18.30 Dry drain, course N.

31.00 Deep dry drain, course NE.

39.88 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S22  
S27  
1937

dig pits,  
18x18x12 ins., E. and W. of post, 3 ft. dist.

44.90 Dry drain, course S.

63.40 Summit of broad ridge, bears NE. and SW.

79.76 The cor. of secs. 21, 22, 27 and 28.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

N.  $0^{\circ} 18'$  W., bet. secs. 21 and 22.

Over rolling land, through scattering sagebrush and cactus.

9.30 Dry drain, course NW.


39.76 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

473

Dependent resurvey of subdivision, T. 38 N., R. 82 W.


Chains.



raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

- 60.00 Deep dry drain, course E. of N.
- 62.90 Deep dry drain, course E.; confluence of drains, bears E., 2 chs. dist.; main drain then courses NE.
- 79.52 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with pint bottle deposited at base, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.



raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.

Land, rolling hills. Soil, sandy clay and gumbo; 3d rate. No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 14, 15, 22 and 23. S. 89° 57' W., bet. secs. 15 and 22.

Over rolling land, through scattering sagebrush and cactus.

- 12.00 Dry drain, course NE.
  - 19.10 Dry drain, course N.
  - 36.70 Deep dry drain, course NE.
  - 39.84 Proportionate distance.
- Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for 1/4 sec. cor., with brass cap mkd.



dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

- 50.80 Dry drain, course S.
  - 79.68 The cor. of secs. 15, 16, 21 and 22.
- Land, rolling hills. Soil, sandy clay and gumbo; 3d rate. No timber; undergrowth, scattering sagebrush and cactus.

N. 1° 08' W., bet. secs. 15 and 16.


Over rolling land, through scattering sagebrush and cactus.

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

- 13.10 Broad ridge, bears S. of W. and falls gradually N. of E.  
 15.60 Cloud Creek - Powder River Road, an unimproved county road, bears N. 80° E. and S. 80° W.  
 39.20 Dry drain, course N. 60° E.  
 39.76½ Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for ¼ sec. cor., with brass cap mkd.




dig pits,  
 18x18x12 ins., N. and S. of post, 3 ft. dist.

- 74.60 Summit of broad ridge, bears NE. and SW.

- 79.53 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with pint bottle deposited at base, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.



raise a mound  
 of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 10, 11, 14 and 15.

S. 89° 55' W., bet. secs. 10 and 15.

Over rolling land, through scattering sagebrush and cactus.

- 34.00 Dry drain, course SE.

- 40.00 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for ¼ sec. cor., with brass cap mkd.



raise a mound  
 of stone, 2½ ft. base, 2 ft. high, N. of cor.

- 74.90 Summit of broad ridge, bears NE. and SW.

- 80.00 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

## 475 Dependent resurvey of subdivision, T. 38 N., R. 82 W.

## Chains.

N. 0° 34' W., bet. secs. 9 and 10.

Over rolling land, through scattering sagebrush and cactus.

29.60 Bend in dry drain, from N. along line to SW.

32.85 Leave drain, course S. from NE.

39.76 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S9 | S10  
 1937

raise a mound  
of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

49.80 Summit of wide ridge, bears NW. and SE.

73.10 Dry drain, course W. of N.

79.52 True proportionate point for cor. of secs. 3, 4, 9 and 10, falls on sloping E. bank of drain; a position unfavorable for permanency because of active erosion.

At a secure point, N. 89° 50' E., 0.50 chs. dist.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for witness cor. of secs. 3, 4, 9 and 10, with brass cap mkd.

T38N R82W  
 WC  $\frac{S4 | S3}{S9 | S10}$   
 1937

raise a mound  
of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, W. of post.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 2, 3, 10 and 11.

S. 89° 50' W., bet. secs. 3 and 10.

Over rolling land, through scattering sagebrush and cactus.

19.10 Dry drain, course N.

27.75 Dry drain, course NE.

36.00 Dry drain, course SE.

39.93 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S3  
 S10  
 1937

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

- raise a mound
- of stone, 3 ft. base, 2 ft. high, N. of cor.
- 47.80 Summit of an adobe knoll; land becomes more broken.
- 58.35 Deep dry drain, course NE.
- 74.40 Dry drain, course N.
- 79.36 The witness cor. of secs. 3, 4, 9 and 10, hereinbefore described.
- 79.86 The true point for the cor. of secs. 3, 4, 9 and 10.
- Land, rolling and broken.  
Soil, sandy clay and gumbo with adobe in W. half mile; 3d and 4th rate.  
No timber; undergrowth, scattering sagebrush and cactus.

Thence from the true point for the cor. of secs. 3, 4, 9 and 10.

N. 1° 45' W., bet. secs. 3 and 4.

Over rolling and broken land, through sparse sagebrush and cactus.

- 2.50 Dry drain, course NE.
- 17.00 Dry drain, course NE.
- 38.50 Dry drain, course NE.
- 39.78 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
 $\frac{1}{4}$ 

S4

S3

1937

raise a mound

of stone, 2½ ft. base, 2 ft. high, W. of cor.

- 60.70 Dry drain, course N. 70° W.
- 65.50 Dry drain, course W.
- 79.42 The cor. of secs. 3, 4, 33 and 34, on N. bdy. of Tp., an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the resurvey field note record of T. 39 N., R. 82 W.

Land, rolling and broken.  
Soil, sandy clay, gumbo and adobe; 3d and 4th rate.  
No timber; undergrowth, sparse sagebrush and cactus.

From the cor. of secs. 4, 5, 32 and 33, on S. bdy. of Tp., hereinbefore described.

N. 0° 58' E., bet. secs. 32 and 33.

Over rolling and broken land, through scattering sagebrush and cactus.


- 34.90 Dry drain, course SW.
- 39.81½ Proportionate distance.

477

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



dig pits,


18x18x12 ins., N. and S. of post, 3 ft. dist.

52.14 Cloud Creek - Powder River Road, an unimproved county road, following ridge, bears NW. and SE.

79.10 Dry drain, course N. 60° E.

79.63 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with pint bottle deposited at base, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.



raise a mound

of stone, 3 ft. base, 3 ft. high, W. of cor.

Land, rolling and broken hills.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 27, 28, 33 and 34.

N. 89° 50' W., bet. secs. 28 and 33.

Over rolling land, through scattering sagebrush and cactus.

32.90 Summit of broad ridge, bears NE. and S.

39.88 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



dig pits,

18x18x12 ins., E. and W. of post, 3 ft. dist.

40.50 Dry drain, course NW.

53.80 Dry drain, course N.

75.90 Dry drain, course NE.

79.76 The cor. of secs. 28, 29, 32 and 33.

Land, rolling hills.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

N. 0° 04' W., bet. secs. 28 and 29.

Over broken land, through scattering sagebrush and cactus.

2.30 Dry drain, course N. of E.

14.70 Dry drain, course N. of E.

18.80 Dry drain, course E.

39.81 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



of stone,  $3\frac{1}{2}$  ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.


51.60 Dry drain, course NE.

71.00 Dry drain, course E.

75.55 Dry drain, course N. of E.

79.62 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.



of stone, 2  $\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

Land, broken hills and slopes.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 21, 22, 27 and 28.

N. 89° 43' W., bet. secs. 21 and 28.

Over rolling and broken land, through scattering sagebrush and cactus.


9.70 Dry drain, course W. of N.

14.00 Deep dry drain, course N.

20.30 Dry drain, course E. of N.

39.79 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



479

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.	
	dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.
51.80	Dry drain, course E. of N.
59.40	Dry drain, course NE.
66.80	Dry drain, course NE.
79.58	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling and broken. Soil, sandy clay and gumbo; 3d rate. No timber; undergrowth, scattering sagebrush and cactus.
N. 0° 23' W., bet. secs. 20 and 21.	
Over rolling and broken land, through scattering sagebrush and cactus.	
14.70	Deep dry drain, course NE.
18.70	Dry drain, course S. of E.
30.60	Dry drain, course S. of E.
39.40	Dry drain, course SE.
39.81	Proportionate distance.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S20   S21 1937
	dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.
49.30	Cloud Creek - Powder River Road, an unimproved county road, following broad ridge, bears NE. and SW.
58.40	Dry drain, course N. of W.
79.62	The original cor. of secs. 16, 17, 20 and 21, which is a sandstone, 24x12x3 ins., marked with 3 grooves on S. and 4 grooves on E. face, firmly set in low mound of stone.
	At point for cor.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with original corner stone alongside, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.
	T38N R82W S17   S16 S20   S21 1937
	raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
	Land, rolling and broken hills. Soil, sandy clay and gumbo; 3d rate. No timber; undergrowth, scattering sagebrush and cactus.

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

## Chains.

From the cor. of secs. 15, 16, 21 and 22.

N. 89° 40' W., bet. secs. 16 and 21.

Over rolling land, through scattering sagebrush and cactus.

12.30 Dry drain, course SE.

39.85 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S16

S21

1937

raise a mound  
of stone, 3 ft. base, 2 ft. high, N. of cor.

63.20 Cloud Creek - Powder River Road, an unimproved county road following broad ridge, bears NE. and SW.

79.70 The cor. of secs. 16, 17, 20 and 21.

Land, rolling hills.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

N. 1° 12' W., bet. secs. 16 and 17.

Over rolling land, through scattering sagebrush and cactus.

5.00 Summit of broad ridge, bears E. and W.

35.00 A point near S. end of earth dam extending N. 20° E., about 3 chs., impounding water in reservoir to eastward, 3 chs. wide and 10 chs. long.

35.80 Dry drain from reservoir, course N. of W.

39.62 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S17 | S16

1937

raise a mound  
of stone, 2½ ft. base, 2½ ft. high, W. of cor.

62.40 Dry drain, course S. 80° W.

75.10 Dry drain, near head, course W.

78.60 Deep dry drain, course S. of W.

79.24 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 8, 9, 16 and 17, with brass cap mkd.

481

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

T38N R82W

S8|S9

S17|S16

1937

raise a mound

of stone, 3 ft. base, 3 ft. high, W. of cor.

Land, rolling hills.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 9, 10, 15 and 16.

N. 89° 53' W., bet. secs. 9 and 16.

Over rolling and broken land, through scattering undergrowth.

21.80 Dry drain, at head, course S. of W.

32.20 Same dry drain, course N. 70° W.

39.88 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S9  
S16

1937

raise a mound

of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.

64.80 Dry drain, near head, course N.

78.00 Deep dry drain, course S. of W.

79.76 The cor. of secs. 8, 9, 16 and 17.

Land, rolling and broken.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

N. 0° 36' W., bet. secs. 8 and 9.

Over broken land, through scattering sagebrush and cactus.

19.50 Dry drain, course S. 60° W.

30.80 Dry drain, course SW.

39.61 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for 1/4 sec. cor., with brass cap mkd.

1/4  
S8 S9

1937

raise a mound

of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

45.50 Dry drain, course S. of W.

58.30 Dry drain, course SW.

69.10 Summit of broad ridge, bears N. 60° E. and N. 60° W.

79.22 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.

T38N R82W

S5|S4

S8|S9

1937

raise a mound  
of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, rolling and broken.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, scattering sagebrush and cactus.

From the true point for the cor. of secs. 3, 4, 9 and 10.

S. 89° 55' W., bet. secs. 4 and 9.

Over broken adobe hills.

0.40 Dry drain, course N.

38.20 Broken ridge, bears SE. and W. along line.

39.90 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd. $\frac{1}{4}$  S4

S9

1937

raise a mound  
of stone, 3 ft. base, 3 ft. high, N. of cor.

47.70 Ridge turns to S. of W.

79.80 The cor. of secs. 4, 5, 8 and 9.

Land, broken hills.

Soil, sandy clay, gumbo and adobe; 3d and 4th rate.

No timber; undergrowth, sparse sagebrush and cactus.

N. 2° 15' W., bet. secs. 4 and 5.

Over broken adobe hills, through sparse sagebrush.

2.95 Deep drain, course NW.

14.10 Dry drain, course W.

20.80 An adobe knoll on line.


37.10 Dry drain, course E. of N.

483

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

- 38.80 Deep drain, course NW.
- 39.64 True proportionate point for  $\frac{1}{4}$  sec. cor., falls at N. side of above drain, a position unfavorable for permanency because of active erosion.
- 40.14 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for witness  $\frac{1}{4}$  sec. cor., with brass cap mkd.



dig pits,  
18x18x12 ins., N. and S. of post, 3 ft. dist.

Continue over broken land, through sparse undergrowth.

- 79.10 The cor. of secs. 4, 5, 32 and 33, on N. bdy. of Tp., an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the resurvey field note record of T. 39 N., R. 82 W.

Land, broken hills.


Soil, sandy clay, gumbo and adobe; 3d and 4th rate.  
No timber; undergrowth, sparse sagebrush.

From the cor. of secs. 5, 6, 31 and 32, on S. bdy. of Tp., hereinbefore described.

N.  $1^{\circ} 26'$  E., bet. secs. 31 and 32.

Over broken land, through scattering sagebrush and cactus.

- 0.50 Dry drain, course E.
- 13.90 Deep dry drain, course W. of N.
- 20.00 Same drain from W. of S., winds N. along line.
- 27.20 Confluence of above drain with deep drain from E.; main drain courses NW.
- 33.80 Dry drain, course S. of W.
- 39.75 True proportionate point for  $\frac{1}{4}$  sec. cor., falls in dry drain, course W.; a position unfavorable for permanency.
- 40.75 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for witness  $\frac{1}{4}$  sec. cor., with brass cap mkd.



dig pits,  
18x18x12 ins., N. and S. of post, 3 ft. dist.

- 47.14 Deep dry drain, course S. of W.
- 71.10 Dry drain, course W.
- 79.50 Proportionate point.

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with quart glass jar deposited at base, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

T38N R82W

S30|S29

S31|S32

1937

raise a mound

of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

Land, broken hills and slopes.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 28, 29, 32 and 33.

N.  $89^{\circ} 55'$  W., bet. secs. 29 and 32.

Over rolling and broken land, through scattering sagebrush and cactus.

21.70 Cloud Creek - Powder River Road, an unimproved county road, following broad ridge, bears NW. and SE.

39.89 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

 $\frac{1}{4}$  S29

S32

1937

raise a mound

of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, N. of cor.

62.90 Dry drain, course SW.

79.78 The cor. of secs. 29, 30, 31 and 32.

Land, rolling and broken.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

S.  $89^{\circ} 48'$  W., bet. secs. 30 and 31.

Over rolling and broken land, through scattering sagebrush and cactus.

17.70 Dry drain, course SW.

39.95 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

 $\frac{1}{4}$  S30

S31

1937

dig pits,

18x18x12 ins., E. and W. of post, 3 ft. dist.

58.00 Deep dry drain, course NW.

485

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.	
79.34	<p>The cor. of secs. 25, 30, 31, and 36, on W. bdy. of Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy clay and gumbo; 3d rate. No timber; undergrowth, scattering sagebrush and cactus.</p>
<p>Thence from the cor. of secs. 29, 30, 31 and 32.</p>	
<p>N. 0° 01' E., bet. secs. 29 and 30.</p>	
<p>Over rolling land, through scattering sagebrush and cactus.</p>	
10.60	<p>Dry drain, course S. of W.</p>
38.80	<p>Dry drain, course S. of W.</p>
39.74	<p>Proportionate distance.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for <math>\frac{1}{2}</math> sec. cor., with brass cap mkd.</p>
<p style="text-align: center;"> <math>\frac{1}{2}</math>        S30 S29        1937     </p>	
<p style="text-align: center;">dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.</p>	
56.70	<p>Dry drain, course NW.</p>
69.60	<p>Dry drain, course W.</p>
78.80	<p>Dry drain, course SW.</p>
79.48	<p>The original cor. of secs. 19, 20, 29 and 30, which is a sandstone, 24x12x2 ins., faintly marked with 2 notches on S. face, firmly set in ground.</p>
<p>At point for cor.</p>	
<p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with original corner stone alongside, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.</p>	
<p style="text-align: center;">       T38N R82W        S19 S20        S30 S29        1937     </p>	
<p style="text-align: center;">raise a mound of stone, 2<math>\frac{1}{2}</math> ft. base, 1<math>\frac{1}{2}</math> ft. high, W. of cor.</p>	
<p>Land, rolling. Soil, sandy clay and gumbo; 3d rate. No timber; undergrowth, scattering sagebrush and cactus.</p>	
<p>From the cor. of secs. 20, 21, 28 and 29.</p>	
<p>S. 89° 57' W., bet. secs. 20 and 29.</p>	
<p>Over rolling land, through scattering sagebrush and cactus.</p>	
39.77	<p>Proportionate distance.</p>

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with potsherd deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S20}{S29}$$

1937

raise a mound

of stone, 3 ft. base, 3 ft. high, N. of cor.

49.30 Cloud Creek - Powder River Road, an unimproved county road, bears NE. and SW.; road follows summit of broad ridge.

60.70 Head of dry drain, course NW.

78.60 Same dry drain, course SW.

79.54 The cor. of secs. 19, 20, 29 and 30.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

S. 89° 29' W., bet. secs. 19 and 30.

Over rolling and broken land, through scattering sagebrush and cactus.

23.40 Deep dry drain, course NW.

27.60 Dry drain, course E. of N.

40.16 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S19}{S30}$$

1937

dig pits,  
18x18x12 ins., E. and W. of post, 3 ft. dist.

79.76 The cor. of secs. 19, 24, 25 and 30, on W. bdy. of Tp., hereinbefore described.

Land, rolling and broken hills and slopes.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

Thence from the cor. of secs. 19, 20, 29 and 30.

N. 0° 59' W., bet. secs. 19 and 20.

Over rolling land, through scattering sagebrush and cactus.

4.50 Low ridge, bears E. and W.


39.58 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

487


Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.



18x18x12 ins., N. and S. of post, 3 ft. dist. dig pits,

- 64.00 Confluence of dry drains, from SE. and S. 80° E.; combined drain courses NW.
  - 78.00 Deep dry drain, course E. of N.
  - 79.16 True proportionate point for cor. of secs. 17, 18, 19 and 20 falls on eroding W. bank of above drain, a position unfavorable for permanency.
- At a secure point, S. 89° 45' W., 0.75 chs. dist.
- Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for witness cor. of secs. 17, 18, 19 and 20, with brass cap mkd.



raise a mound of stone, 3 ft. base, 3 ft. high, W. of post.

Land, rolling.  
Soil, sandy clay and gumbo; 3d rate.  
No timber; undergrowth, scattering sagebrush and cactus.

From the cor. of secs. 16, 17, 20 and 21.  
S. 89° 37' W., bet. secs. 17 and 20.  
Over rolling land, through scattering sagebrush and cactus.

- 0.40 Dry drain, at head, course W. along line.
- 5.00 Drain turns to N. of W.
- 13.40 Same drain, course S. 60° W.
- 27.20 Short dry drain, course W. of S.
- 40.16 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for 1/4 sec. cor., with brass cap mkd.



raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.

- 42.20 Short dry drain, course W. of S.
- 47.70 Short dry drain, course SW.
- 50.10 Short dry drain, course W. of S.
- 65.50 Deep dry drain, course N. 20° W.

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

- 79.65 Deep dry drain, course E. of N.
- 80.32 True point for the cor. of secs. 17, 18, 19 and 20.  
 Land, rolling.  
 Soil, sandy clay and gumbo; 3d rate.  
 No timber; undergrowth, scattering sagebrush and cactus.

---

- From true point for cor. of secs. 17, 18, 19 and 20.  
 S. 89° 45' W., bet. secs. 18 and 19.  
 Ascend over bank of drain.
- 0.75 The witness cor. of secs. 17, 18, 19 and 20, hereinbefore described.  
 Thence over rolling land, through scattering sagebrush and cactus.
- 35.50 Low broad spur, slopes NE.
- 38.00 Dry drain, course NE.
- 40.09 Proportionate distance.  
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with  
 pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.  

$$\frac{1}{4} \frac{S18}{S19}$$
 1937  
 dig pits,  
 18x18x12 ins., E. and W. of post, 3 ft. dist.
- 43.55 Dry drain, course NE.
- 56.00 Origin of wide spur, slopes gradually SE.
- 79.49 The cor. of secs. 13, 18, 19 and 24, on W. bdy. of Tp., hereinbefore  
 described.  
 Land, rolling.  
 Soil, sandy clay and gumbo; 3d rate.  
 No timber; undergrowth, scattering sagebrush and cactus.

---

- Thence from the true point for the cor. of secs. 17, 18, 19 and 20.  
 N. 1° 03' W., bet. secs. 17 and 18.  
 Over rolling and broken land, through scattering sagebrush and cactus.
- 1.00 Short dry drain, course E.
- 16.15 Dry drain, course E.
- 39.58 Proportionate distance.  
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with  
 quart jar deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.  

$$\frac{1}{4} \frac{S18}{S17}$$
 1937

489

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.	
	dig pits,
	18x18x12 ins., N. and S. of post, 3 ft. dist.
52.60	Short dry drain, course SE.
56.50	Dry drain, course NE.
68.25	Confluence of dry drains from NW. and SW.; combined drain courses E.
79.16	Proportionate point.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with pint bottle deposited at base, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.
	T38N R82W S7 S8 S18 S17 1937
	raise a mound
	of stone, 3 ft. base, 2½ ft. high, W. of cor.
	Land, rolling and broken.
	Soil, sandy clay and gumbo; 3d rate.
	No timber; undergrowth, scattering sagebrush and cactus.
	From the cor. of secs. 8, 9, 16 and 17.
	S. 89° 37' W., bet. secs. 8 and 17.
	Over rolling and broken land, through scattering sagebrush and cactus.
7.70	Short dry drain, course W. of S.
29.30	Deep dry drain, course NW.
40.02	Proportionate distance.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for ¼ sec. cor., with brass cap mkd.
	¼ S8 S17 1937
	dig pits,
	18x18x12 ins., E. and W. of post, 3 ft. dist.
46.80	Dry drain, course N.
56.50	Deep dry drain, course N. 30° E.
71.90	Dry drain, course S. of E.
80.04	The cor. of secs. 7, 8, 17 and 18.
	Land, rolling and broken hills and slopes.
	Soil, sandy clay and gumbo; 3d rate.
	No timber; undergrowth, scattering sagebrush and cactus.
	S. 89° 59' W., bet. secs. 7 and 18.
	Over rolling and broken land, through scattering undergrowth.
9.00	Dry drain, course SE.

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.	
16.80	Summit of broad ridge, bears N. 20° E. and S. 30° W.; thence over barren adobe hills.
36.20	Dry wash, course N. 30° W.; thence along badly eroded and caving N. slope.
39.94	True proportionate point for $\frac{1}{4}$ sec. cor., falls on eroding N. slope near confluence of drains; a position unfavorable for permanency.
40.80	Dry wash, course E. of N.
41.69	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4} \begin{matrix} S7 \\ S18 \end{matrix} WC$ 1937  dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.
63.20	Dry wash, course NW.
70.70	Dry drain, course E. of N.; land becomes more rolling; leave adobe.
79.18	The cor. of secs. 7, 12, 13 and 18, on W. bdy. of Tp., hereinbefore described.  Land, broken and rolling hills. Soil, sandy clay, gumbo and adobe; 3d and 4th rate. No timber; undergrowth, sparse sagebrush and cactus.
	Thence from the cor. of secs. 7, 8, 17 and 18. N. 0° 39' W., bet. secs. 7 and 8.  Over rolling and broken land, through sparse undergrowth.
8.10	Dry drain, course SE.
21.00	Broad spur, slopes gradually NE.
29.60	Dry drain, course W. of N.
39.58	Proportionate distance.  Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4} \begin{matrix} S7 \\ S8 \end{matrix}$ 1937  raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
42.10	Dry drain, course NE.
48.00	Dry drain, course NE.
75.55	Right bank of Powder River, water in pools, course E.; bank is from 20 to 30 feet high.
77.80	Sloping left bank of river; thence over low ground subject to inundation at flood periods.

491

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.	
79.16	<p>True proportionate point for cor. of secs. 5, 6, 7 and 8, falls on low ground subject to inundation at periods of flood; a position unfavorable for permanency.</p> <p>At a secure point, N. 2° 32' W., 1.00 chain dist.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, with pint bottle deposited at base, for witness cor. of secs. 5, 6, 7 and 8, with brass cap mkd.</p> <p style="text-align: center;">T38N R82W S6 S5 S7 S8 WC 1937</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <p>Land, rolling and broken.</p> <p>Soil, sandy clay, gumbo and adobe; 3d and 4th rate.</p> <p>No timber; undergrowth, sparse sagebrush and cactus.</p>
1.90	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89° 38' W., bet. secs. 5 and 8, (E. half mile).</p> <p>Over broken adobe hills, through sparse undergrowth.</p> <p>Dry wash; course N.</p>
15.00	<p>Spur, slopes NW.</p>
40.05	<p>The original ¼ sec. cor., which is a sandstone, 24x20x18 ins., marked ¼ on N. face, firmly set in ground.</p> <p>At point for cor.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with original corner stone alongside, for ¼ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">¼ S5 ¼ S8 1937</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 4 ft. base, 3½ ft. high, N. of cor.</p> <p>Thence</p> <p>S. 89° 27' W., bet. secs. 5 and 8, (W. half mile).</p> <p>Leave adobe hills, bear NE. and SW.; thence over rolling and broken land, through scattering undergrowth.</p>
8.20	<p>Head of dry drain, course SW.</p>
20.80	<p style="text-align: center;">S; Fork</p> <p>Right bank of Powder River, water in pools, course N. from S. of W.; bank is about 30 feet high; thence through channel bed.</p>
32.00	<p>Left bank of active channel, a low sloping bank; thence over low land, subject to inundation at extreme flood periods.</p>
40.04	<p>The true point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling, broken and level river bottom.</p> <p>Soil, sandy clay, gumbo and adobe; 3d and 4th rate.</p> <p>No timber; undergrowth, sparse sagebrush and cactus.</p>

Dependent resurvey of subdivision, T. 38 N., R. 82 W.

Chains.

Note: The river referred to in the following notes is correctly: South Fork of Powder River.

From the true point for the cor. of secs. 5, 6, 7 and 8.

N. 89° 52' W., bet. secs. 6 and 7.

Over low ground subject to inundation at extreme flood periods, at N. side of Powder River, through sparse undergrowth.

- 3.00 Sloping left bank of active channel, course S. of E.; water in pools.
- 7.80 Right bank of Powder River, a precipitous bank about 10 feet high, course SE.; thence over rolling land, through scattering undergrowth.

26.90 Right bank of same river, water in pools, course W. of N.; bank is about 12 feet high; thence through active channel of river.

28.30 Sloping left bank of river; thence over low land.

39.97 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{S6}{S7}$   
 1937

dig pits,  
 18x18x12 ins., E. and W. of post, 3 ft. dist.

Thence over low rolling land.

48.60 Ancient left flood bank of Powder River, about 30 feet high, faces E.

79.34 The cor. of secs. 1, 6, 7 and 12, on W. bdy. of Tp., hereinbefore described.

Land, level river bottom and low rolling hills.  
 Soil, sandy clay, gumbo and adobe; 3d and 4th rate.  
 No timber; undergrowth, sparse sagebrush and cactus.

Thence from the true point for the cor. of secs. 5, 6, 7 and 8.

N. 2° 32' W., bet. secs. 5 and 6.

Over low ground subject to inundation at extreme flood periods, at N. side of active channel of Powder River.

- 0.70 Ascend to higher ground; thence over rolling bottom land, through sparse undergrowth.
- 1.00 The witness cor. of secs. 5, 6, 7 and 8, hereinbefore described.
- 9.80 Ancient left flood bank of Powder River, about 40 feet high, faces W. of S.; thence over rolling land, through scattering undergrowth.
- 39.62 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, with pint bottle deposited at base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{S6}{S5}$   
 1937

dig pits,  
 18x18x12 ins., N. and S. of post, 3 ft. dist.

433

## Dependent resurvey of subdivision, T. 38 N., R. 82 W.

## Chains.

77.10 Low short ridge, bears SW. and E.

79.35 The cor. of secs. 5, 6, 31 and 32, on N. bdy. of Tp., an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the resurvey field note record of T. 39 N., R. 82 W.

Land, rolling bottom and hills.

Soil, sandy clay and gumbo; 3d rate.

No timber; undergrowth, sparse sagebrush and cactus.

General Description, T. 38 N., R. 82 W.

The surface of the township is generally rolling upland prairie cut by drains and dry water courses. Throughout the north tier of sections areas of adobe hills occur.

The drainage is generally to the north. During the greater part of the year the drains and water courses are dry but during the spring run-off and at periods of heavy rain fall the major drains evidently carry considerable water. There are two drainage systems within the township. Approximately the east two thirds of the township drains into Cloud Creek. This creek, containing water in pools at survey date, enters the township in the west half mile on the south boundary of section 36 and winds generally north leaving the township immediately west of the quarter section corner on the north boundary of section 2. Powder River, the principal water course within the township, enters the area near the quarter section corner on the west boundary of section 7 and winds generally northeast leaving the township in the east half mile on the north boundary of section 5. This river, containing water in holes at survey date, receives all run-off from approximately the west one third of the township through its tributary drains. There is no living water within the area. Reservoirs are located in sections 3 and 16. Surface run-off has been impounded following construction of earth dams.

The soil is generally sandy clay and gumbo of a third rate classification. It supports a scattering growth of sagebrush and cactus as well as a thin stand of native grasses. There is no timber. With sufficient moisture, the soil is productive; however the annual precipitation is usually too little to support agriculture and the area is best suitable for grazing for which purpose it is utilized largely during the spring and fall months.

The township is crossed by two units of the county road system. The 33-Mile Trail, a graded earth road, enters the township in the south half mile on the east boundary of section 13, winds northwesterly, and leaves in the east half mile on the north boundary of section 3. The Cloud Creek - Powder River Road, an unimproved road, enters in the west half mile on the south boundary of section 33 and proceeds through sections 33, 32, 29, 20, 21, 16, 15, 14 and 11 to its junction with the 33-Mile Trail in the last named section. A steel bridge on the 33-Mile Trail across Cloud Creek is located in the south east quarter of the south west quarter of section 11.

There are no inhabitants within the township.



495

CERTIFICATE OF UNITED STATES SURVEYOR

I, Chris Gras, Transitman, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of August, 1936 received from the district cadastral engineer for Wyoming, with assignment instructions dated 1936, and re March 22, 1937, I have surveyed all those parts or portions of the East, South and West Boundaries and Subdivisional Lines of Township No. 38 North, Range No. 82 West,

of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Casper, Wyoming,  
May 7, 1937

Chris Gras  
Transitman.

CERTIFICATE OF APPROVAL

OFFICE OF U.S. SUPERVISOR OF SURVEYS,  
....., 19.....

The foregoing field notes of the survey of .....  
.....  
.....  
executed by .....  
under special instructions dated ....., and assignment instructions dated ....., having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

.....  
U.S. Supervisor of Surveys.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in .....  
....., is a true copy of the original field notes on file in the public survey office.

.....  
U.S. Supervisor of Surveys.



## CERTIFICATE OF UNITED STATES SURVEYOR

I, Elmer C. Lenhart, Public Land Surveyor, \_\_\_\_\_, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of August, 1936, received from the district cadastral engineer for \_\_\_\_\_ Wyoming, with assignment instructions dated 1936, and re March 22, 1937, I have/surveyed all those parts or portions of the East, South and West Boundaries and Subdivisional Lines of Township No. 38 North, Range No. 82 West, \_\_\_\_\_

of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said ~~re~~ survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Casper, Wyoming, \_\_\_\_\_  
May 7, 1937 \_\_\_\_\_

*Elmer C. Lenhart*  
 \_\_\_\_\_  
 Public Land Surveyor.

## CERTIFICATE OF APPROVAL

OFFICE OF ~~THE~~ SUPERVISOR OF SURVEYS,denver, Colo. Sept. 23, 1939

The foregoing field notes of the <sup>re</sup> survey of the East, South and West Boundaries and Sub- divisional lines of Township No. 38 North, Range No. 82 West, of the Sixth Principal Meridian, Wyoming, \_\_\_\_\_

executed by Elmer C. Lenhart, Public Land Surveyor, and Chris Gras, Transitman, \_\_\_\_\_, under special instructions dated August 25, 1936, and assignment instructions dated March 22, 1937 and \_\_\_\_\_, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

*Samuel A. Johnson*  
 \_\_\_\_\_  
 Supervisor of Surveys.

## CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes on file in the public survey office.

\_\_\_\_\_  
 U. S. Supervisor of Surveys.