

TOWNSHIP 27 NORTH, RANGE 6 EAST, OF THE SIXTH PRINCIPAL MERIDIAN, NEBRASKA.

PERPETUATION OF CERTAIN CORNERS

SURVEY INFORMATION AND CERTIFICATE

The cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with the 1996 iron post, 2 1/2 ins. diam., firmly set flush with the surface of gravel roads extending N., E., S. and W.; with the brass cap sheared off.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of the roads, with brass cap mkd.

T27N R6E
S31 | S32
 S 6 | S 5
 T26N
 2010

Deposit the local monuments recovered in 1996 inside the stainless steel post and remove the remnants of the 1996 monument from the vicinity.

from which a new reference monument

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 39 1/4° W., 75.2 lks. dist., with brass cap mkd. RM T27N R6E S31 49.6 FT. TO COR. 2010 and an arrow pointing to the cor., with a fiberglass sign post set alongside.

The NE reference monument established in 1996 was recovered in place. Set a fiberglass sign post alongside the iron post.

The N. 1/16 sec. cor. of secs. 31 and 32, monumented with an iron post, 2 1/2 ins. diam., as described in the field notes of the 1996 dependent resurvey of a portion of T. 27 N., R. 6 E.

from which a new reference monument

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 47 1/4° W., 62.7 lks. dist., with brass cap mkd. RM T27N R6E S31 N1/16 41.4 FT. TO COR. 2010 and an arrow pointing to the cor., with a fiberglass sign post set alongside.

The SE reference monument established in 1996 was recovered in place. Set a fiberglass sign post alongside the iron post.

This plat represents the entire record of the perpetuation of certain corners and reference monuments between sections 31 and 32, T. 27 N., R. 6 E., Sixth Principal Meridian, Nebraska.

During the field work for the dependent resurvey of portions of T. 27 N., R. 6 E., executed under this same group, it was discovered that road reconstruction work along the subdivisional line between sections 31 and 32, had disturbed and/or destroyed section corner and reference monuments established along this line during the 1996 dependent resurvey executed by James D. Clafin and Ryan R. Lorenzen under Group No. 143, Nebraska. Reference should be made to the plat approved December 22, 1997, for survey information.

I, Ryan R. Lorenzen, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Supplemental Special Instructions dated July 6, 2010, for Group No. 170, Nebraska, I have perpetuated certain corners between sections 31 and 32, T. 27 N., R. 6 E., Sixth Principal Meridian, Nebraska, and that this plat in one sheet represents the entire record of this perpetuation. Field work executed July 7, 2010, has been made in strict conformity with the special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described hereon.



Ryan R. Lorenzen
 Cadastral Surveyor

April 26, 2011

Date

UNITED STATES DEPARTMENT OF THE INTERIOR
 BUREAU OF LAND MANAGEMENT

Cheyenne, Wyoming

April 26, 2011

This plat representing the entire record of this perpetuation of certain corners, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director



John P. Lee
 Chief Cadastral Surveyor for Nebraska