

TOWNSHIP 26 NORTH, RANGE 105 WEST, OF THE SIXTH PRINCIPAL MERIDIAN, WYOMING.

PERPETUATION OF CERTAIN CORNERS

Cor. No. 5, Parcel A, monumented with a stainless steel post, 2 1/2 ins. diam., as described in the 2000-02 field notes of the dependent resurvey of T. 26 N., R. 105 W.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground over a plastic encased magnetic marker, for a reference monument, bears S. 20° E., 37.0 lks. dist., with brass cap mkd. RM T26N R105W S 28 COR 5 PAR A 24.4 FT TO COR. 2005 and an arrow pointing to the cor. Set a steel fence post nearby.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground over a plastic encased magnetic marker, for a reference monument, bears S. 51° E., 39.2 lks. dist., with brass cap mkd. RM T26N R105W S 28 COR 5 PAR A 25.9 FT TO COR. 2005 and an arrow pointing to the cor. Set a steel fence post nearby.

Cor. No. 6, Parcel A, monumented with a stainless steel post, 2 1/2 ins. diam., as described in the 2000-02 field notes of the dependent resurvey of T. 26 N., R. 105 W.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground over a plastic encased magnetic marker, for a reference monument, bears N. 55° E., 34.8 lks. dist., with brass cap mkd. RM T26N R105W S 28 COR 6 PAR A 23.0 FT TO COR. 2005 and an arrow pointing to the cor. Set a steel fence post nearby.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground over a plastic encased magnetic marker, for a reference monument, bears S. 55° E., 26.8 lks. dist., with brass cap mkd. RM T26N R105W S 28 COR 6 PAR A 17.7 FT TO COR. 2005 and an arrow pointing to the cor. Set a steel fence post nearby.

Cor. No. 7, Parcel A, monumented with a stainless steel post, 2 1/2 ins. diam., as described in the 2000-02 field notes of the dependent resurvey of T. 26 N., R. 105 W.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground over a plastic encased magnetic marker, for a reference monument, bears N. 59° E., 24.1 lks. dist., with brass cap mkd. RM T26N R105W S 28 COR 7 PAR A 15.9 FT TO COR. 2005 and an arrow pointing to the cor. Set a steel fence post nearby.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground over a plastic encased magnetic marker, for a reference monument, bears S. 10° W., 25.5 lks. dist., with brass cap mkd. RM T26N R105W S 28 COR 7 PAR A 16.8 FT TO COR. 2005 and an arrow pointing to the cor. Set a steel fence post nearby.

SURVEY INFORMATION AND CERTIFICATE

This plat represents the entire record of the establishment of reference monuments for certain corners of Parcel A, Section 28, Township 26 North, Range 105 West, Sixth Principal Meridian, Wyoming.

At the request of Bernie Weynand, Assistant Field Manager, BLM Rock Springs Field Office, reference monuments were set to perpetuate the positions of certain monuments established during the metes and bounds survey of Parcel A, Section 28. These corners were at risk of being destroyed or displaced during the development of a BLM historic site located in Parcel A.

Lynn A. Forbes executed the metes and bounds survey of Parcel A, Section 28, under this same group in 2000-02. Reference should be made to the plat approved June 9, 2003, for survey information.

I, Ollian T. Shockley, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Supplemental Special Instructions dated July 15, 2005, and Assignment Instructions dated July 15, 2005, for Group No. 674, Wyoming, I have perpetuated certain corners of Parcel A, Section 28, Township 26 North, Range 105 West, Sixth Principal Meridian, Wyoming, and that this plat in one sheet represents the entire record of this perpetuation. Fieldwork executed July 18, 2005, and has been made in strict conformity with the special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described hereon.

Ollian T. Shockley
Ollian T. Shockley,
Cadastral Surveyor

January 30, 2008
Date

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Cheyenne, Wyoming

January 30, 2008

This plat representing the entire record of this perpetuation of certain corners, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

John P. Lee

John P. Lee
Chief Cadastral Surveyor for Wyoming