

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

PORTIONS OF THE WIND RIVER MERIDIAN (WEST BOUNDARY),

WIND RIVER BASE LINE (NORTH BOUNDARY), SOUTH BOUNDARY,

SUBDIVISIONAL LINES AND SUBDIVISION OF CERTAIN SECTIONS,

AND

THE SURVEY

OF THE

SUBDIVISION OF CERTAIN SECTIONS

AND

PARCELS A AND B OF SECTION 3,

TOWNSHIP 1 SOUTH, RANGE 1 EAST,

Of the WIND RIVER Meridian,

In the State of WYOMING.

EXECUTED BY

SANTIAGO T. CHAVEZ CADASTRAL SURVEYOR

Under special instructions dated AUGUST 6, 19 75, approved AUGUST 27, 1975.

AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED JUNE 14, 1979, APPROVED JULY 2,

1979, which provided for the surveys included under ~~U.S. Survey~~ Group

Number 376, and assignment instructions dated AUGUST 6, 19 75.

Survey commenced JUNE 21, 19 76

Survey completed JULY 14, 19 83

INDEX DIAGRAM

Township 1 South, Range 1 East,

4

3 3

2 6	5	4	5 8	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30 7	29	28	27	26	25
31 5	6 32 4	33	34	35	36

- Dependent Resurvey, Subdivision of Section 3 - page 8
- Dependent Resurvey, Subdivision of Section 6 - page 9
- Dependent Resurvey, Subdivision of Section 31 - pages 9 - 11
- Survey, Subdivision of Section 3 - page 11
- Survey, Subdivision of Section 6 - page 11
- Survey, Subdivision of Section 31 - page 11
- Survey, Parcel A, Section 3 - pages 12 - 13
- Survey, Parcel B, Section 3 - page 13

T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS

The following field notes are those of the dependent resurvey of portions of the Wind River Meridian (west boundary), Wind River Base Line (north boundary), south boundary, subdivisional lines and subdivision of certain sections and the survey of the subdivision of certain sections and Parcels A and B of section 3, Township 1 South, Range 1 East, Wind River Meridian, Wyoming.

The history of surveys pertaining to this resurvey is as follows:

The exterior boundaries, subdivisional lines and subdivision of sections were surveyed by James W. Miller in 1875. The resurvey of the exterior boundaries, subdivisional lines and subdivision of sections was executed by Robert A. Farmer and Frederick C. Miller in 1913.

The survey and resurvey were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated August 6, 1975, and Supplemental Special Instructions dated June 14, 1979, for Group No. 376, Wyoming.

Prior to the resurvey, the lines of the previous surveys were retraced and a diligent search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were restored and monumented at proportionate positions based on the official record. The retrace-ment data were thoroughly verified and only the true line field notes are given herein.

The directions of the lines were determined by solar and Polaris observations and refer to the true meridian.

The geographic position of the standard corner of Tps. 1 N., and 1 S., Rs. 1 E. and 1 W., identical with U. S. Coast and Geodetic Survey triangulation station GLO STATION 21, 1931, is:

Latitude $43^{\circ} 00' 41.07''$ N., Longitude $108^{\circ} 48' 49.35''$ W.

The mean magnetic declination is $14\frac{3}{4}^{\circ}$ E.

Dependent Resurvey, Portion of the
Wind River Meridian (West Boundary),
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

(Restoring the resurvey executed by Robert A. Farmer
and Frederick C. Miller in 1913)

Beginning at the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.

G L O
 $\frac{1}{4}$
S 1 | S 6
1913

Dependent Resurvey, Portion of the
Wind River Meridian (West Boundary),
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS	
19.97	<p>N. 0° 22' E., on the Wind River Meridian, bet. secs. 1 and 6.</p> <p>Over rolling land.</p> <p>The N. 1/16 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">G L O N 1/16 S 1 S 6 1913</p> <p>From this cor., U. S. Coast and Geodetic Survey triangulation station ETHETE, bears N. 18° 09' E., 18.38 chs. dist., monumented with a standard brass tablet, 3¼ ins. diam., firmly set in concrete, 12 ins. square, projecting 7 ins. above the ground, mkd. ETHETE 1931.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 09' E., beginning new measurement.</p> <p>Over gently rolling land.</p>
20.14	<p>The standard cor. of Tps. 1 N. and 1 S., Rs. 1 E. and 1 W., identical with the Initial Point for the Wind River Base Line and Meridian, and U. S. Coast and Geodetic Survey triangulation station GLO STATION 21, monumented with an iron post, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T1N R1W R1E S 36 S 31 S 1 S 6 T1S 1931 1913</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Dependent Resurvey, Portion of the Wind River Base Line (North Boundary), T. 1 S., R. 1 E., Wind River Meridian, Wyoming</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">(Restoring the resurvey executed by Robert A. Farmer and Frederick C. Miller in 1913)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the witness cor. to the standard W. 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, in fence extending E. and W., with brass cap mkd.</p> <p style="text-align: center;">G L O W C W 1/16 $\frac{S 34}{S 3}$ 1913</p>

Dependent Resurvey, Portion of the
Wind River Base Line (North Boundary),
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS	
	<p>S. 89° 26' W., on the Wind River Base Line, bet. secs. 3 and 34.</p> <p>Along fence.</p>
0.25	<p>True point for the standard W. 1/16 sec. cor. of secs. 3 and 34, identical with AP 1, Parcel B, at proportionate dist., falls in wash where it is impractical to establish a permanent monument.</p>
15.27	<p>Point for AP 1, Parcel A, identical with AP 2, Parcel B, hereinafter described.</p>
20.27	<p>Point for the standard cor. of secs. 3, 4, 33 and 34, identical with AP 2, Parcel A, at proportionate dist. by the method of irregular boundary, falls in paved road extending N. and S.; there is no remaining evidence of the original cor.</p> <p>Set a copper-coated steel stake, 30 ins. long, ½ in. diam., flush with the surface of the road, with brass cap, 1½ ins. diam., mkd.</p> <div style="text-align: center;"> <p>S C T1N R1E S 33 S 34 S 4 S 3 T1S PA AP 2 1976</p> </div> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 40³/₄° E., 83.2 lks. dist., with brass cap mkd. RM T1N R1E S34 54.9 FT 1976 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45¹/₂° E., 67.1 lks. dist., with brass cap mkd. RM T1S R1E S3 44.3 FT 1976 and an arrow pointing to the cor.</p>
20.00	<p>S. 89° 40' W., on the Wind River Base Line, bet. secs. 4 and 33.</p> <p>Over gently rolling land.</p> <p>The standard E. 1/16 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>G L O S C E 1/16 <u>S 33</u> S 4 1913</p> </div>

Dependent Resurvey, Portion of the
Wind River Base Line (North Boundary),
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS	
19.94	<p>From the standard W. 1/16 sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">G L O S C W 1/16 $\frac{S\ 31}{S\ 6}$ 1913</p> <p>S. 89° 53' W., on the Wind River Base Line, bet. secs. 6 and 31.</p> <p>Over gently rolling land.</p> <p>The standard cor. of Tps. 1 N. and 1 S., Rs. 1 E. and 1 W.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Portion of the South Boundary, T. 1 S., R. 1 E., Wind River Meridian, Wyoming</p> <hr/> <p style="text-align: center;">(Restoring the resurvey executed by Robert A. Farmer and Frederick C. Miller in 1913)</p> <hr/> <p>From the W. 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, in fence extending E. and W., with brass cap mkd.</p> <p style="text-align: center;">G L O W 1/16 $\frac{S\ 32}{S\ 5}$ 1913</p> <p>N. 89° 49' W., bet. secs. 5 and 32.</p> <p>Along fence.</p> <p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist. by the method of irregular boundary, falls in U. S. Highway No. 287 extending N. and S.; there is no remaining evidence of the original cor.</p> <p>Set a 60d nail flush with the surface of the highway.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 18 ins. in the ground, for a reference monument, bears N. 85° E., 94.8 lks. dist., with brass cap mkd. RM T1S R1E S32 62.6 FT 1983 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, for a reference monument, bears N. 61¼° W., 107.3 lks. dist., with brass cap mkd. RM T1S R1E S31 70.8 FT 1983 and an arrow pointing to the cor.</p>

Dependent Resurvey, Portion of the South Boundary,
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS

N. 89° 58' W., bet. secs. 6 and 31.

Over gently rolling land.

20.135 Point for the E. 1/16 sec. cor. of secs. 6 and 31, at proportionate dist., falls on edge of trail road extending N. and W.; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$E \frac{1}{16} \frac{S \ 31}{S \ 6}$$

1983

Along fence extending W. on N. side of trail road.

40.27 The ¼ sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, at intersection of fences, extending N., E. and W., with brass cap mkd.

G L O

$$\frac{1}{4} \frac{S \ 31}{S \ 6}$$

1913

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

(Restoring the resurvey executed by Robert A. Farmer
and Frederick C. Miller in 1913)

From the N. 1/16 sec. cor. of secs. 3 and 4, identical with AP 5, Parcel B, monumented with the remains of an iron post, 18 ins. long, 1 in. diam., firmly set 6 ins. below the surface of the ground on west edge of paved road, bears N. and S., with brass cap missing.

At the corner point

Set an aluminum rod, 24 ins. long, 5/8 in. diam., 8 ins. below the surface of the ground, with magnetic aluminum cap mkd.

$$\begin{array}{c} N \ 1/16 \\ | \\ PB \\ | \\ AP \ 5 \\ S \ 4 \ | \ S \ 3 \end{array}$$

1983

from which

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 65° E., 119.2 lks. dist., with brass cap mkd. RM N1/16 S3 78.7 FT 1983 and an arrow pointing to the cor.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS	
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 41½° W., 51.5 lks. dist., with brass cap mkd. RM N1/16 S4 34.0 FT 1983 and an arrow pointing to the cor.</p> <p>Bury the remains of the iron post alongside the aluminum rod.</p> <p>N. 0° 46' E., bet. secs. 3 and 4.</p> <p>Along paved road.</p>
13.75	<p>Point for AP 3, Parcel A, identical with AP 4, Parcel B, hereinafter described.</p>
18.75	<p>The standard cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.</p>
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.</p> <p>N. 0° 02' E., bet. secs. 31 and 32.</p> <p>Along U. S. Highway No. 287.</p>
19.93	<p>Point for the S. 1/16 sec. cor. of secs. 31 and 32, at proportionate dist. by the method of irregular boundary, falls in U. S. Highway No. 287; there is no remaining evidence of the original cor.</p> <p>Set a 60d nail flush with the surface of the highway.</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 53° E., 123.2 lks. dist., with brass cap mkd. RM S1/16 S32 81.3 FT 1983 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 31¾° W., 176.2 lks. dist., with brass cap mkd. RM S1/16 S31 116.3 FT 1983 and an arrow pointing to the cor.</p> <p>N. 0° 20' W., beginning new measurement.</p> <p>Along U. S. Highway No. 287.</p>
20.18	<p>Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate dist. by the method of irregular boundary, falls in U. S. Highway No. 287 and on line with fence extending W.; there is no remaining evidence of the original cor.</p> <p>Set a 60d nail flush with the surface of the highway.</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 44½° E., 147.1 lks. dist., with brass cap mkd. RM T1S R1E ¼ S32 97.1 FT 1983 and an arrow pointing to the cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS		
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 37¼° W., 148.9 lks. dist., with brass cap mkd. RM T1S R1E ¼ S31 98.3 FT. 1983 and an arrow pointing to the cor.</p> <hr/> <p>N. 0° 09' W., beginning new measurement.</p> <p>Along U. S. Highway No. 287.</p>	
20.05	<p>Point for the N. 1/16 sec. cor. of secs. 31 and 32, at proportionate dist., falls in U. S. Highway No. 287; there is no remaining evidence of the original cor.</p> <p>Set a 60d nail flush with the surface of the highway.</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 52¼° E., 128.0 lks. dist., with brass cap mkd. RM N1/16 S32 84.5 FT 1983 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 49° W., 125.8 lks. dist., with brass cap mkd. RM N1/16 S31 83.0 FT 1983 and an arrow pointing to the cor.</p>	
40.10	<p>The cor. of secs. 29, 30, 31 and 32, perpetuated by William C. Heatley, Wyoming Registered Land Surveyor No. 3510, with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of U. S. Highway No. 287, with aluminum cap, 1½ ins. diam., mkd.</p> <p style="text-align: center;">RLS 3510 30 29 31 32</p> <p>from which new reference monuments</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 46° E., 128.2 lks. dist., with brass cap mkd. RM T1S R1E S32 84.6 FT. 1983 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° W., 138.0 lks. dist., with brass cap mkd. RM T1S R1E S31 91.1 FT. 1983 and an arrow pointing to the cor.</p> <p>This position is harmoniously related with the connection made by the Wyoming State Highway Department, as shown on Plan and Profile Sheet No. 12, Project No. S-0702(6) and is accepted as a careful and faithful perpetuation of the original cor. position.</p> <hr/> <p>S. 89° 19' W., bet. secs. 30 and 31.</p> <p>Along S. side of unimproved road and along fence extending W.</p>	

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS	
20.08	<p>The E. 1/16 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, in fence, bears E. and W., with brass cap missing.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S\ 30}{S\ 31}$</p> <p style="text-align: center;">1976</p> <p>Deposit the remains of the 1913 monument inside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 20' W., beginning new measurement.</p> <p>Over rolling land.</p>
20.04	<p>The ¼ sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, at the intersection of fences, bears N. and W., with brass cap mkd.</p> <p style="text-align: center;">G L O</p> <p style="text-align: center;">¼ $\frac{S\ 30}{S\ 31}$</p> <p style="text-align: center;">1913</p>
<p>Dependent Resurvey, Subdivision of Section 3, T. 1 S., R. 1 E., Wind River Meridian, Wyoming</p>	
<p>(Restoring the resurvey executed by Robert A. Farmer and Frederick C. Miller in 1913)</p>	
<p>From the NW. 1/16 sec. cor. of sec. 3, identical with AP 6, Parcel B, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, in fence, bears E. and W., with brass cap mkd.</p> <p style="text-align: center;">G L O</p> <p style="text-align: center;">NW 1/16</p> <p style="text-align: center;">S 3</p> <p style="text-align: center;">1913</p>	
<p>N. 89° 47' W., on the E. and W. center line of the NW¼ of sec. 3.</p>	
<p>Along fence.</p>	
20.10	<p>The N. 1/16 sec. cor. of secs. 3 and 4, identical with AP 5, Parcel B.</p>

Dependent Resurvey, Subdivision of Section 6,
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS

(Restoring the resurvey executed by Robert A. Farmer
and Frederick C. Miller in 1913)

From the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, on the W. bdy. of
the Tp.

N. $89^{\circ} 36'$ E., on the E. and W. center line of sec. 6.

Over rolling land.

19.71 The center W. $\frac{1}{16}$ sec. cor. of sec. 6, monumented with
an iron post, 1 in. diam., firmly set, projecting 12 ins.
above the ground, with brass cap mkd.

G L O
 $\frac{1}{4}$ W $\frac{1}{16}$ $\frac{1}{4}$
S 6

1913

From the N. $\frac{1}{16}$ sec. cor. of secs. 1 and 6, on the W.
bdy. of the Tp.

EAST, on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 6.

Over rolling land.

19.77 The NW. $\frac{1}{16}$ sec. cor. of sec. 6, monumented with an
iron post, 1 in. diam., firmly set, projecting 8 ins.
above the ground, with brass cap mkd.

NW $\frac{1}{16}$
S 6

1913

Dependent Resurvey, Subdivision of Section 31,
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

(Restoring the resurvey executed by Robert A. Farmer
and Frederick C. Miller in 1913)

From the center W. $\frac{1}{16}$ sec. cor. of sec. 31, monumented
with an iron post, 1 in. diam., firmly set, projecting
12 ins. above the ground, in fence, bears E. and W.,
with brass cap mkd.

$\frac{1}{4}$ W $\frac{1}{16}$ $\frac{1}{4}$
S 31

1913

N. $89^{\circ} 36'$ E., on the E. and W. center line of sec. 31.

Over rolling land.

20.035 Point for the center $\frac{1}{4}$ sec. cor. of sec. 31, at propor-
tionate dist.; there is no remaining evidence of the
original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins.
in the ground, with brass cap mkd.

Dependent Resurvey, Subdivision of Section 31,
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS		
	<p style="text-align: center;">T1S R1E C ¼ S 31 1976</p>	
40.07	<p>The center E. 1/16 sec. cor. of sec. 31, monumented with an iron post, 30 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with brass cap missing.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C $\frac{E \ 1/16}{S \ 31}$ C 1976</p> <p>Deposit the remains of the 1913 monument inside the iron post and set a steel fence post alongside.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 46' E., beginning new measurement.</p> <p>Along fence extending irregularly E.</p>	
20.09	<p>The ¼ sec. cor. of secs. 31 and 32.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 31, monumented with a quartzite stone, 14x10x6 ins., mkd. 182 on S. face and 185 on N. face, firmly set at the intersection of fences extending N., S., E. and W. There is no remaining evidence of the 1913 monument.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 31 C 1976</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>N. 89° 22' E., on the E. and W. center line of the NE¼ of sec. 31.</p> <p>Along fence.</p>	
20.005	<p>Point for the NE. 1/16 sec. cor. of sec. 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 31 1983</p>	

Dependent Resurvey, Subdivision of Section 31,
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS	
40.01	<p>Set a steel fence post alongside the iron post.</p> <p>The N. 1/16 sec. cor. of secs. 31 and 32.</p>
<p>Survey of the Subdivision of Section 3, T. 1 S., R. 1 E., Wind River Meridian, Wyoming</p>	
19.05	<p>From the NW. 1/16 sec. cor. of sec. 3, identical with AP 6, Parcel B.</p> <p>N. 0° 24' E., on the N. and S. center line of the NW$\frac{1}{4}$ of sec. 3.</p>
19.05	<p>The true point for the standard W. 1/16 sec. cor. of secs. 3 and 34, identical with AP 1, Parcel B, on the N. bdy. of the Tp.</p>
<p>Survey of the Subdivision of Section 6, T. 1 S., R. 1 E., Wind River Meridian, Wyoming</p>	
19.83	<p>From the center W. 1/16 sec. cor. of sec. 6.</p> <p>N. 0° 31' E., on the N. and S. center line of the NW$\frac{1}{4}$ of sec. 6.</p> <p>Over rolling land.</p>
19.83	<p>The NW. 1/16 sec. cor. of sec. 6.</p> <p>N. 0° 39' E., beginning new measurement.</p> <p>Over rolling land.</p>
20.19	<p>The standard W. 1/16 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp.</p>
<p>Survey of the Subdivision of Section 31, T. 1 S., R. 1 E., Wind River Meridian, Wyoming</p>	
19.85	<p>From the center $\frac{1}{4}$ sec. cor. of sec. 31.</p> <p>N. 0° 14' E., on the N. and S. center line of sec. 31.</p> <p>Over rolling land.</p>
19.85	<p>The center N. 1/16 sec. cor. of sec. 31.</p> <p>N. 0° 30' W., beginning new measurement.</p> <p>Over rolling land.</p>
20.03	<p>The $\frac{1}{4}$ sec. cor. of secs. 30 and 31.</p>

Survey of Parcel A, Section 3,
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS

From the point for AP 1, Parcel A, identical with AP 2, Parcel B, on the N. bdy. of the Tp.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T1N R1E	
S 34	
AP 1	AP 2
PA	PB
S 3	
T1S	
1983	

Set a steel fence post alongside the iron post.

S. 89° 26' W., on line 1-2, Parcel A, identical in part with the line bet. secs. 3 and 34.

5.00 AP 2, Parcel A, identical with the standard cor. of secs. 3, 4, 33 and 34.

S. 0° 46' W., on line 2-3, Parcel A, identical in part with the line bet. secs. 3 and 4.

5.00 Point for AP 3, Parcel A, identical with AP 4, Parcel B, falls in paved road extending N. and S.

Set a 60d nail flush with the surface of the road.

from which

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 71¼° E., 68.8 lks. dist., with brass cap mkd. RM T1S R1E S3 AP3 PA 45.4 FT 1983 and an arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 65¼° E., 71.5 lks. dist., with brass cap mkd. RM T1S R1E S3 AP4 PB 47.2 FT 1983 and an arrow pointing to the cor.

N. 89° 26' E., on line 3-4, Parcel A, identical with line 3-4, Parcel B.

5.00 Point for AP 4, Parcel A, identical with AP 3, Parcel B.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T1S R1E	
S 3	
PA	PB
AP 4	AP 3
1983	

Survey of Parcel A, Section 3,
T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS	
	Set a steel fence post alongside the iron post. <hr/>
	N. 0° 46' E., on line 4-1, Parcel A, identical with line 2-3, Parcel B.
5.00	AP 1, Parcel A, identical with AP 2, Parcel B, and the point of beginning. <hr/>
Survey of Parcel B, Section 3, T. 1 S., R. 1 E., Wind River Meridian, Wyoming	
	From AP 1, Parcel B, identical with the true point for the standard W. 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	S. 89° 26' W., on line 1-2, Parcel B, identical in part with the line bet. secs. 3 and 34.
15.02	AP 2, Parcel B, identical with AP 1, Parcel A. <hr/>
	S. 0° 46' W., on line 2-3, Parcel B, identical with line 4-1, Parcel A.
5.00	AP 3, Parcel B, identical with AP 4, Parcel A. <hr/>
	S. 89° 26' W., on line 3-4, Parcel B, identical with line 3-4, Parcel A.
5.00	AP 4, Parcel B, identical with AP 3, Parcel A. <hr/>
	S. 0° 46' W., on line 4-5, Parcel B, identical in part with the line bet. secs. 3 and 4.
13.75	AP 5, Parcel B, identical with the N. 1/16 sec. cor. of secs. 3 and 4. <hr/>
	S. 89° 47' E., on line 5-6, Parcel B, identical in part with the E. and W. center line of the NW $\frac{1}{4}$ of sec. 3.
20.10	AP 6, Parcel B, identical with the NW. 1/16 sec. cor. of sec. 3. <hr/>
	N. 0° 24' E., on line 6-1, Parcel B, identical in part with the N. and S. center line of the NW $\frac{1}{4}$ of sec. 3.
19.05	True point for AP 1, Parcel B, and the point of beginning. <hr/>
GENERAL DESCRIPTION	
The land encompassed in this survey is located in the vicinity of Ethete, Wyoming. Numerous canals and ditches in the area carry water for irrigation purposes. The average elevation is 5,500 feet above sea level.	

143

T. 1 S., R. 1 E., Wind River Meridian, Wyoming

CHAINS

Access is provided by U. S. Highway No. 287 and numerous paved and gravelled county roads.

There are scattering stands of brush and timber along the canals and ditches, with undergrowth consisting primarily of native grasses.

Form 9600-11
(September 1983)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Richard P. Godesiabois	Surveying Aid
Bruce G. Cartwright	Surveying Aid
Laurie J. Neary	Surveying Aid
Walter G. Bell	Surveying Aid
Robert L. Clark	Surveying Aid
Gerald M. Lowe	Surveying Aid
Daniel J. Medina	Surveying Aid
Dennis R. Davidson	Surveying Aid
Karl L. Meyer	Surveying Aid
Kevin E. King	Surveying Aid
James P. Beard	Surveying Aid
Carol J. Jacobson	Surveying Technician
York E. Morlan	Surveying Technician

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Santiago T. Chavez, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day
 of August, 19 75, ~~(XXX) have~~ and Supplemental Special Instructions
 dated June 14, 1979, (I) have dependently resurveyed portions of the Wind
 River Meridian (west boundary), Wind River Base Line (north Boundary), south
 boundary, subdivisional lines and subdivision of certain sections, and
 surveyed the subdivision of certain sections and Parcels A and B of section
 3, Township 1 South, Range 1 East,

of the Wind River Meridian, in the State of Wyoming, which
 are represented in the foregoing field notes as having been executed by (me) ~~(XXX)~~ and under (my)
~~(XXX)~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

July 14, 1983
 (Date)

Santiago T. Chavez
 (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of portions of the Wind River
 Meridian (west boundary), Wind River Base Line (north boundary), south
 boundary, subdivisional lines and subdivision of certain sections, and the
 survey of the subdivision of certain sections and Parcels A and B of section 3,
 Township 1 South, Range 1 East, of the Wind River Meridian, Wyoming,
 executed by Santiago T. Chavez, Cadastral Surveyor,
 having been critically examined and found correct, are hereby approved.

JUL 17 1984
 (Date)

Richard L. Oakes
 (Signature of Authorized Officer)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 , is a true copy of the original field notes.

(Date)

(Signature of Authorized Officer)